



## RADIO FREQUENCY EXPOSURE

### LIMIT

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See §15.247(b)(4) and §1.1307(b)(1) of this chapter.

### Conducted Power Results

#### *Bluetooth*

Mode	Frequency(MHz)	Peak Conducted Output Power (dBm)
IEEE 802.11b	2412	14.87
	2437	14.17
	2462	14.82
IEEE 802.11g	2412	18.56
	2437	19.94
	2462	18.91
IEEE 802.11n HT20	2412	20.97
	2437	22.45
	2462	21.50
IEEE 802.11n HT40	2422	19.72
	2437	19.35
	2452	19.58

### Manufacturing tolerance

#### *WIFI*

IEEE 802.11b (Peak)			
Frequency (MHz)	2412	2437	2462
Target (dBm)	14.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11g (Peak)			
Frequency (MHz)	2412	2437	2462
Target (dBm)	18.0	19.0	18.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Peak)			
Frequency (MHz)	2412	2437	2462
Target (dBm)	20.0	22.0	21.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Peak)			
Frequency (MHz)	2422	2437	2452
Target (dBm)	19.0	19.0	19.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0



## Compliance Certification Services Inc.

Report No: C150804Z02-RP1\_MPE FCC ID: ALX700773-001 Date of Issue: August 12, 2015

### EUT Specification

<b>EUT</b>	Powered Loudspeaker
<b>Frequency band (Operating)</b>	<input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5825GHz <input type="checkbox"/> Bluetooth: 2.402GHz~ 2.480GHz <input type="checkbox"/> Others _____
<b>Device category</b>	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others _____
<b>Exposure classification</b>	<input type="checkbox"/> Occupational/Controlled exposure ( $S = 5mW/cm^2$ ) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure ( $S=1mW/cm^2$ )
<b>Antenna diversity</b>	<input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas <input checked="" type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
<b>Max. output power</b>	23dBm (199.53mW)
<b>Antenna gain (Max)</b>	1.16dBi (Numeric gain:1.31)
<b>Evaluation applied</b>	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

**Note:**

1. The maximum output power(including turn tolerance) is 23dBm (199.53mW) and maximum antenna gain is 1.16.dBi
2. For mobile or fixed location transmitters, no SAR consideration applied. The minimum separation generally be used is at least 20 cm, even if the calculations indicate that the MPE distance would be lesser.



## **TEST RESULT**

*No non-compliance noted.*

### **Calculation**

Given 
$$S = \frac{P \times G}{4\pi d^2} \quad \text{Equation 1}$$

Where  $d$  = distance in cm

$P$  = Power in mW

$G$  = Numeric antenna gain

$S$  = Power Density in  $\text{mW/cm}^2$

### **Maximum Permissible Exposure**

EUT Output Power=199.53mW

Numeric antenna gain=1.31

Substituting the MPE safe distance using  $d=20$  cm into **Equation 1** :

Fields

The power density  $S = 199.53 \times 1.31 / (4\pi \times 400) \text{ cm}^2 = 5.20 \times 10^{-2} \text{ mW/cm}^2$

(For mobile or fixed location transmitters, the maximum power density is  $1.0 \text{ mW/cm}^2$  even if the calculation indicates that the power density would be larger.)