FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247(i)and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Report No.: R2DG130930001-00A

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure									
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)					
0.3-1.34	614	1.63	*(100)	30					
1.34–30	824/f	2.19/f	*(180/f²)	30					
30–300	27.5	0.073	0.2	30					
300–1500	/	/	f/1500	30					
1500-100,000	/	/	1.0	30					

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

 $S = PG/4\pi R^2 = power density (in appropriate units, e.g. mW/cm^2);$

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Mode	Frequency (MHz)	Antenna Gain		Conducted Power		Evaluation Distance	Power Density	MPE Limit
		(dBi)	(numeric)	(dBm)	(mW)	(cm)	(mW/cm^2)	(mW/cm^2)
2.4G-802.11b	2412	2.17	1.65	17.87	61.24	20.00	0.02009	1.0
2.4G-802.11g	2437	2.17	1.65	13.78	23.88	20.00	0.00783	1.0
2.4G-802.11n20	2437	2.17	1.65	14.36	27.29	20.00	0.00895	1.0
2.4G-802.11n40	2422	2.17	1.65	13.08	20.32	20.00	0.00667	1.0
802.11a	5825	2.20	1.66	12.92	19.59	20.00	0.00647	1.0
5G-802.11n20	5825	2.20	1.66	13.55	22.65	20.00	0.00748	1.0
5G-802.11n40	5755	2.20	1.66	13.24	21.09	20.00	0.00697	1.0
5G-802.11ac20	5745	2.20	1.66	13.2	20.89	20.00	0.00690	1.0
5G-802.11ac40	5755	2.20	1.66	13.49	22.34	20.00	0.00738	1.0
5G-802.11ac80	5775	2.20	1.66	11.36	13.68	20.00	0.00452	1.0

Result: The device meet FCC MPE at 20 cm distance

FCC Part 15.247 Page 11 of 179