



RF Exposure Evaluation Report

APPLICANT : Emerson Digital Cold Chain, Inc
EQUIPMENT : GO Tracker 1.7
BRAND NAME : Emerson
MODEL NAME : GO Tracker 1.7
FCC ID : AMH101014
STANDARD : 47 CFR Part 2.1091
FCC KDB 447498 D01 v06

We, Sporton International (ShenZhen) Inc., would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and FCC KDB 447498 D01 v06, and pass the limit. Without written approval of Sporton International (ShenZhen) Inc., the test report shall not be reproduced except in full.



Reviewed by: Hank Huang / Supervisor



Approved by: Johnny Chen / Manager



Sporton International (ShenZhen) Inc.

**1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055
People's Republic of China**



Table of Contents

1. ADMINISTRATION DATA	4
1.1. Testing Laboratory	4
2. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	5
3. MAXIMUM RF AVERAGE OUTPUT TUNE UP POWER AMONG PRODUCTION UNITS	6
4. RF EXPOSURE LIMIT INTRODUCTION	7
5. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION	8
5.1. Standalone Power Density Calculation	8

**Revision History**

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA172307	Rev. 01	Initial issue of report.	Sep. 08, 2021



1. Administration Data

1.1. Testing Laboratory

Sporton International (Shenzhen) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Testing Laboratory			
Test Firm	Sporton International (Shenzhen) Inc.		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	SAR01-SZ	CN1256	421272

Applicant	
Company Name	Emerson Digital Cold Chain, Inc
Address	7121 Fairway Drive Suite 400 Palm Beach Gardens Florida 33418 United States

Manufacturer	
Company Name	Queclink Wireless Solutions Co., Ltd.
Address	No.30, Lane 500, Xinlong Road, Minhang District, Shanghai, China

2. Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT Type	GO Tracker 1.7
Brand Name	Emerson
Model Name	GO Tracker 1.7
FCC ID	AMH101014
Wireless Technology and Frequency Range	GSM850: 824 MHz ~ 849 MHz GSM1900: 1850 MHz ~ 1910 MHz LTE Category M1: LTE Band 2 : 1850 MHz ~ 1910 MHz LTE Band 4 : 1710 MHz ~ 1755 MHz LTE Band 5 : 824 MHz ~ 849 MHz LTE Band 12 : 699 MHz ~ 716 MHz LTE Band 13 : 777 MHz ~ 787 MHz LTE Band 25 : 1850 MHz ~ 1915 MHz LTE Band 26 : 814 MHz ~ 849 MHz LTE Band 66 : 1710 MHz ~ 1780 MHz LTE Band 85 : 698 MHz ~ 716 MHz NB-IOT Category NB2 : NB-IOT Band 2 : 1850 MHz ~ 1910 MHz NB-IOT Band 4 : 1710 MHz ~ 1755 MHz NB-IOT Band 5 : 824 MHz ~ 849 MHz NB-IOT Band 12 : 699 MHz ~ 716 MHz NB-IOT Band 13 : 777 MHz ~ 787 MHz NB-IOT Band 25 : 1850 MHz ~ 1915 MHz NB-IOT Band 66 : 1710 MHz ~ 1780 MHz NB-IOT Band 71 : 663 MHz ~ 698 MHz NB-IOT Band 85 : 698 MHz ~ 716 MHz
Mode	GPRS/EGPRS LTE Category M1: QPSK / 16QAM NB-IOT Category NB2 :BPSK / QPSK
HW Version	V1.03
SW Version	R00A02V10
EUT Stage	Production Unit

Remark:

- The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Comments and Explanations:

- The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.
- The maximum RF output tune up power, antenna gain and the safe distance used for evaluate RF exposure were declared by manufacturer.

**3. Maximum RF average output tune up power among production units****<GSM>**

Mode	Burst average power(dBm)	
	GSM 850	GSM 1900
GPRS (1 Tx slot)	33.50	30.50
GPRS (2 Tx slots)	33.00	29.00
GPRS (3 Tx slots)	32.00	27.00
GPRS (4 Tx slots)	30.00	26.50
EDGE (1 Tx slot)	27.00	26.00
EDGE (2 Tx slots)	26.00	24.50
EDGE (3 Tx slots)	24.50	22.50
EDGE (4 Tx slots)	23.50	21.50

<LTE>

Mode		Maximum Average power(dBm)
LTE Cat M1	Band 2	23.00
	Band 4	23.00
	Band 5	22.50
	Band 12	22.50
	Band 13	22.50
	Band 25	23.00
	Band 26	22.50
	Band 66	23.00
	Band 85	22.50
NB-IOT	Band 2	24.00
	Band 4	24.00
	Band 5	24.00
	Band 12	24.00
	Band 13	24.00
	Band 25	24.00
	Band 66	24.00
	Band 71	24.00
	Band 85	24.00



4. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna



5. Radio Frequency Radiation Exposure Evaluation

5.1. Standalone Power Density Calculation

Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power(dBm)	Maximum EIRP (dBm)	Maximum EIRP (W)	Average EIRP (mW)	Power Density at 20cm (mW/cm ²)	Limit (mW/cm ²)
GPRS 850 (1 Tx slot)	824.2	0.00	33.50	33.500	2.239	281.838	0.056	0.549
GPRS 850 (2 Tx slots)	824.2	0.00	33.00	33.000	1.995	501.187	0.100	0.549
GPRS 850 (3 Tx slots)	824.2	0.00	32.00	32.000	1.585	594.292	0.118	0.549
GPRS 850 (4 Tx slots)	824.2	0.00	30.00	30.000	1.000	501.187	0.100	0.549
EGPRS 850 (1 Tx slot)	824.2	0.00	27.00	27.000	0.501	63.096	0.013	0.549
EGPRS 850 (2 Tx slots)	824.2	0.00	26.00	26.000	0.398	100.000	0.020	0.549
EGPRS 850 (3 Tx slots)	824.2	0.00	24.50	24.500	0.282	105.682	0.021	0.549
EGPRS 850 (4 Tx slots)	824.2	0.00	23.50	23.500	0.224	112.202	0.022	0.549
GPRS 1900 (1 Tx slot)	1850.2	1.00	30.50	31.500	1.413	177.828	0.035	1.000
GPRS 1900 (2 Tx slots)	1850.2	1.00	29.00	30.000	1.000	251.189	0.050	1.000
GPRS 1900 (3 Tx slots)	1850.2	1.00	27.00	28.000	0.631	236.592	0.047	1.000
GPRS 1900 (4 Tx slots)	1850.2	1.00	26.50	27.500	0.562	281.838	0.056	1.000
EGPRS 1900 (1 Tx slot)	1850.2	1.00	26.00	27.000	0.501	63.096	0.013	1.000
EGPRS 1900 (2 Tx slots)	1850.2	1.00	24.50	25.500	0.355	89.125	0.018	1.000
EGPRS 1900 (3 Tx slots)	1850.2	1.00	22.50	23.500	0.224	83.946	0.017	1.000
EGPRS 1900 (4 Tx slots)	1850.2	1.00	21.50	22.500	0.178	89.125	0.018	1.000
CAT M1 Band 2	1850.7	1.00	23.00	24.000	0.251	251.189	0.050	1.000
CAT M1 Band 4	1710.7	0.50	23.00	23.500	0.224	223.872	0.045	1.000
CAT M1 Band 5	824.7	0.00	22.50	22.500	0.178	177.828	0.035	0.550
CAT M1 Band 12	699.7	-1.50	22.50	21.000	0.126	125.893	0.025	0.466
CAT M1 Band 13	779.5	-1.50	22.50	21.000	0.126	125.893	0.025	0.520
CAT M1 Band 25	1850.7	1.00	23.00	24.000	0.251	251.189	0.050	1.000
CAT M1 Band 26	814.7	0.00	22.50	22.500	0.178	177.828	0.035	0.543
CAT M1 Band 66	1710.7	0.50	23.00	23.500	0.224	223.872	0.045	1.000
CAT M1 Band 85	700.5	-1.50	22.50	21.000	0.126	125.893	0.025	0.467
NB-IOT Band 2	1850.1	1.00	24.00	25.000	0.316	316.228	0.063	1.000
NB-IOT Band 4	1710.2	0.50	24.00	24.500	0.282	281.838	0.056	1.000
NB-IOT Band 5	824.1	0.00	24.00	24.000	0.251	251.189	0.050	0.549
NB-IOT Band 12	699.1	-1.50	24.00	22.500	0.178	177.828	0.035	0.466
NB-IOT Band 13	782.0	-1.50	24.00	22.500	0.178	177.828	0.035	0.521
NB-IOT Band 25	1851.9	1.00	24.00	25.000	0.316	316.228	0.063	1.000
NB-IOT Band 66	1711.9	0.50	24.00	24.500	0.282	281.838	0.056	1.000
NB-IOT Band 71	663.2	-2.00	24.00	22.000	0.158	158.489	0.032	0.442
NB-IOT Band 85	698.2	-1.50	24.00	22.500	0.178	177.828	0.035	0.465

Note:

- For conservativeness, the lowest frequency of each band is used to determine the MPE limit of that band.

Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.

-----THE END-----