

TABLE OF CONTENTS LIST

APPLICANT: UNIDEN AMERICA CORPORATION
FCC ID: AMWUC728

TEST REPORT:

PAGE 1.....SECURITY CODING INFORMATION
PAGE 2-3.....TEST PROCEDURE AND TEST EQUIPMENT LIST
PAGE 4.....POWER LINE CONDUCTED INTERFERENCE
PAGE 5.....OCCUPIED BANDWIDTH AND PEAK POWER OUTPUT
PAGE 6-7.....ANTENNA CONDUCTED EMISSIONS
PAGE 8.....RADIATED SPURIOUS EMISSIONS HANDSET
PAGE 9.....RADIATED SPURIOUS EMISSIONS BASE
PAGE 10.....SPECTRAL POWER DENSITY AND PROCESSING GAIN

EXHIBITS:

EXHIBIT 1.....FCC ID LABEL SAMPLES
EXHIBIT 2A.....SKETCH OF LABEL LOCATION - HANDSET
EXHIBIT 2B.....SKETCH OF LABEL LOCATION - BASE
EXHIBIT 3.....BLOCK DIAGRAM - BASE
EXHIBIT 4.....BLOCK DIAGRAM - PORTABLE
EXHIBIT 5.....SCHEMATIC - MAIN - BASE
EXHIBIT 6.....SCHEMATIC - RF - BASE
EXHIBIT 7.....SCHEMATIC - MAIN - HANDSET
EXHIBIT 8.....SCHEMATIC - RF - HANDSET
EXHIBIT 9-10.....POWERLINE CONDUCTED EMISSIONS PLOT
EXHIBIT 11.....6dB B/W PLOT 29dB ATTN - CHANNEL 1 BASE
EXHIBIT 12.....6dB B/W PLOT 40dB ATTN - CHANNEL 1- HANDSET
EXHIBIT 13.....6dB B/W PLOT 40dB ATTN - CHANNEL 11 - HANDSET
EXHIBIT 14.....6dB B/W PLOT 29dB ATTN - CHANNEL 10 - BASE
EXHIBIT 15.....6dB B/W PLOT 40dB ATTN - CHANNEL 19 - HANDSET
EXHIBIT 16.....6dB BANDWIDTH PLOT CHANNEL 19 - BASE
EXHIBIT 17.....SPECTRAL DENSITY PLOT 29dB ATTN - CH 1 - BASE
EXHIBIT 18.....SPECTRAL DENSITY PLOT 40dB ATTN - CH 1 - H/SET
EXHIBIT 19A-B....UPPER & LOWER B/EDGE PLOT 29dB ATTN - BASE
EXHIBIT 20A-B....UPPER & LOWER B/EDGE PLOT 40dB ATTN - HANDSET
EXHIBIT 21A.....EXTERNAL PHOTO - FRONT VIEW - BASE
EXHIBIT 21B.....EXTERNAL PHOTO - BOTTOM VIEW - BASE
EXHIBIT 21C.....EXTERNAL PHOTO - FRONT VIEW - HANDSET
EXHIBIT 21D.....EXTERNAL PHOTO - REAR VIEW - HANDSET
EXHIBIT 21E.....INTERNAL COMPONENT SIDE PHOTO - BASE
EXHIBIT 21F.....INTERNAL SOLDER SIDE PHOTO - BASE
EXHIBIT 21G.....INTERNAL COMPONENT SIDE PHOTO - HANDSET
EXHIBIT 21H.....INTERNAL SOLDER SIDE PHOTO - HANDSET
EXHIBIT 22.....INSTRUCTION MANUAL
EXHIBIT 23.....CIRCUIT DESCRIPTION
EXHIBIT 24A.....RADIATED TEST SET UP PHOTO - HANDSET
EXHIBIT 24B.....RADIATED TEST SET UP PHOTO - BASE
EXHIBIT 24C.....POWERLINE CONDUCTED TEST SET UP PHOTO - BASE
EXHIBIT 25.....PROCESSING GAIN TEST DATA

APPLICANT: UNIDEN AMERICA CORPORATION
FCCID: AMWUC728
DATE: DECEMBER 4, 2000
REPORT #: T:\CUS\U\Uniden\526BU0\526BU0RPT.doc

APPLICANT: UNIDEN AMERICA CORPORATION
FCC ID: AMWUC728

15.214(d) - THIS DEVICE COMPLIES WITH THE SECURITY CODE REQUIREMENTS OF 15.214(d)(1)(2) AND (3) BY MEANS OF THE FOLLOWING:

THIS DEVICE HAS 65536 SECURITY CODES. THE CPU CONTROLS THE RF FREQUENCY CHANNEL. AND THE ASIC CONTROLS ADPCM CODEC AND AUDIO SIGNAL SWITCHING ALSO SET UP THE SPREADING CODE. BEFORE THE COMMUNICATION LINK IS ESTABLISHED, THE DEVICE SEARCHES VACANT RF CHANNELS AND THEN TRANSMITS RF SIGNAL AT THE VACANT CHANNEL. THE CPU GENERATES A RANDOM SECURITY CODE OUT OF 65536 CODES WHICH CAN PROTECT PRIVACY.

APPLICANT: UNIDEN AMERICA CORPORATION
FCCID: AMWUC728
DATE: DECEMBER 4, 2000
REPORT #: T:\CUS\U\Uniden\526BU0\526BU0RPT.doc
PAGE #: 1

APPLICANT: UNIDEN AMERICA CORPORATION
FCCID : AMWUC728

TEST EQUIPMENT LIST

1. X Spectrum Analyzer: HP 8566B-Opt 462, S/N 3138A07786, w/
preselector HP 85685A, S/N 3221A01400, Quasi-Peak Adapter
HP 85650A, S/N 3303A01690 & Preamplifier HP 8449B-OPT H02,
S/N 3008A00372 Cal. 10/17/99
2. X Biconnical Antenna: Eaton Model 94455-1, S/N 1057
3. Biconnical Antenna: Electro-Metrics Model BIA-25, S/N 1171
4. X Log-Periodic Antenna: Electro-Metrics Model EM-6950, S/N 632
5. Log-Periodic Antenna: Electro-Metrics Model LPA-30, S/N 409
6. X Double-Ridged Horn Antenna: Electro-Metrics Model RGA-180,
1-18 GHz, S/N 2319
7. 18-26.3GHz Systron Donner Standard Gain Horn #DBE-520-20
8. Horn 40-60GHz: ATM Part #19-443-6R
9. Line Impedance Stabilization Network: Electro-Metrics Model
ANS-25/2, S/N 2604 Cal. 2/9/00
10. Temperature Chamber: Tenney Engineering Model TTRC, S/N 11717-7
11. Frequency Counter: HP Model 5385A, S/N 3242A07460 Cal 10/6/99
12. Peak Power Meter: HP Model 8900C, S/N 2131A00545
13. X Open Area Test Site #1-3meters Cal. 12/22/99
14. Signal Generator: HP 8640B, S/N 2308A21464 Cal. 9/23/99
15. Signal Generator: HP 8614A, S/N 2015A07428
16. Passive Loop Antenna: EMC0 Model 6512, 9KHz to 30MHz, S/N
9706-1211 Cal. 6/10/00
17. X Dipole Antenna Kit: Electro-Metrics Model TDA-30/1-4, S/N 153
Cal. 11/24/99
18. AC Voltmeter: HP Model 400FL, S/N 2213A14499 Cal. 9/21/99
19. Digital Multimeter: Fluke Model 8012A, S/N 4810047 Cal 9/21/99
20. Digital Multimeter: Fluke Model 77, S/N 43850817 Cal 9/21/99
21. Oscilloscope: Tektronix Model 2230, S/N 300572 Cal 9/23/99

TEST PROCEDURE

GENERAL: This report shall NOT be reproduced except in full without the written approval of TIMCO ENGINEERING, INC. Shielded interface cables were used in all cases except for cables connecting to the telephone line and the power cords. A test program was run which simulated a normal data transmission on a network.

POWER LINE CONDUCTED INTERFERENCE: The procedure used was ANSI STANDARD C63.4-1992 using a 50uH LISN. Both lines were observed. The bandwidth of the spectrum analyzer was 10kHz with an appropriate sweep speed. The ambient temperature of the UUT was 74°F with a humidity of 44%.

BANDWIDTH 6.0dB: The measurements were made with the spectrum analyzer's resolution bandwidth(RBW)=100KHz and the video bandwidth(VBW)=300KHz and the span set as shown on plot.

FCC ID : AMWUC728
DATE: DECEMBER 4, 2000
REPORT #: T:\CUS\U\Uniden\526BU0\526BU0RPT.doc
PAGE # : 2

APPLICANT : UNIDEN AMERICA CORPORATION

FCC ID : AMWUC728

TEST PROCEDURES CONTINUED

POWER OUTPUT: The RF power output was measured at the antenna feed point by removing the permanent antenna and connecting the UUT to a peak power meter, HP Model No. 8900C.

ANTENNA CONDUCTED EMISSIONS: The RBW=100KHz, VBW > or = RBW and the spectrum was scanned from 30MHz to the 10th Harmonic of the fundamental.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.4-1992 using a HEWLETT PACKARD spectrum analyzer with a pre-selector. The bandwidth(RBW) of the spectrum analyzer was 100kHz up to 1GHz and 1.0MHz above 1GHz with an appropriate sweep speed. The VBW above 1.0GHz was = 1.0MHz. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The ambient temperature of the UUT was 74°F with a humidity of 44%.

15.247(d) POWER SPECTRAL DENSITY. The peak within the pass band was located with a RBW OF 3KHz and a span of 2.0 MHz, slightly greater than the 6dB bandwidth, then span was centered on the display and the span is reduced to 900KHz and the sweep time set to 500 seconds. Since the spectral line spacing could not be resolved, the spectral density was measured using the noise power density and adding the correction of 35dB. This response is then plotted.

15.247(e): PROCESSING GAIN, This gain is supplied by the manufacturer of the UUT.

2.1033(b)(4)

ANTENNA AND GROUND SYSTEM:

This unit uses a short, inductively loaded, antenna element for the base unit and the handset. The antenna is permanently attached to the unit and no provision is made for connection to an external antenna.

No ground connection is provided. The only ground in use is the ground plane on the printed circuit board.

APPLICANT: UNIDEN AMERICA CORPORATION

FCCID: AMWUC728

DATE: DECEMBER 4, 2000

REPORT #: T:\CUS\U\Uniden\526BU0\526BU0RPT.doc

PAGE #: 3

APPLICANT: UNIDEN AMERICA CORPORATION

FCC ID: AMWUC728

NAME OF TEST: POWER LINE CONDUCTED INTERFERENCE

RULES PART NUMBER: 15.207

MINIMUM REQUIREMENTS:	FREQUENCY MHz	LEVEL dBuV
	0.450-30	48 dBuV or 250 uV

TEST PROCEDURE: ANSI STANDARD C63.4-1992

THE HIGHEST EMISSION READ FOR LINE 1 WAS 21.4 uV @ 570KHz.

THE HIGHEST EMISSION READ FOR LINE 2 WAS 11.7 uV @ 570KHz.

THE GRAPHS IN EXHIBITS 9-10 REPRESENT THE EMISSIONS READ FOR
POWERLINE CONDUCTED FOR THIS DEVICE.

TEST RESULTS: Both lines were observed with the UUT transmitting.
The measurements indicate that the unit DOES appear to meet the FCC
requirements for this class of equipment.

PERFORMED BY: JOE SCOGLIO

DATE: DECEMBER 4, 2000

APPLICANT: UNIDEN AMERICA CORPORATION

FCCID: AMWUC728

DATE: DECEMBER 4, 2000

REPORT #: T:\CUS\U\Uniden\526BU0\526BU0RPT.doc

PAGE #: 4

APPLICANT: UNIDEN AMERICA CORPORATION

FCC ID: AMWUC728

NAME OF TEST: OCCUPIED BANDWIDTH

RULES PART NUMBER: 15.247

15.247(a)(2)

6dB bandwidth shall be at least 500 kHz. The 6dB points for both the base is 1.530 MHz and handset is 1.510 MHz. As shown in the accompanying plots. The bandwidth was measured at three places in the band and the narrowest is reported below.

Base 6dB Bandwidth = 1.530 MHz

Handset 6 dB Bandwidth = 1.510 MHz

15.247(B) PEAK POWER OUTPUT

The maximum peak output power shall not exceed 1 watt (30 dBm). If directional transmitting antennas with a gain of more than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Both the base and handset have a maximum power output of less than +30 dBm. Power was measured by disconnecting the antennas and measuring across a 50 ohm load as recommended by the manufacturer using a HP peak power meter Model 8900C. The antennas are non directional and do not exceed 6 dBi gain. The power output was measured at three places in the band highest is reported below.

POWER OUTPUT - LIMIT +30 dBm

BASE PEAK POWER OUTPUT = +12 dBm or 16 mWatts

HANDSET PEAK POWER OUTPUT = +12 dBm or 16 mWatts

APPLICANT: UNIDEN AMERICA CORPORATION

FCCID: AMWUC728

DATE: DECEMBER 4, 2000

REPORT #: T:\CUS\U\Uniden\526BU0\526BU0RPT.doc

PAGE #: 5

APPLICANT: UNIDEN AMERICA CORPORATION

FCC ID: AMWUC728

NAME OF TEST: ANTENNA CONDUCTED SPURIOUS EMISSIONS

RULES PART NUMBER: 15.247(c) Spurious Emissions must be 20dBc.

FREQUENCY MHz	ATTENUATION dBc
BASE	
904.7	0.0
1809.4	40.6
2714.1	50.8
3618.8	62.2
4523.5	60.4
5428.2	59.1
6332.9	80.0
7237.6	78.7
8142.3	84.6
9047.0	86.0
914.9	0.0
1829.8	48.4
2744.7	63.5
3659.6	64.0
4574.5	56.6
5489.4	61.8
6404.3	80.2
7319.2	73.7
8234.1	78.9
9149.0	NF
923.1	0.0
1846.2	54.5
2769.3	63.4
3692.4	68.3
4615.5	57.1
5538.6	66.5
6461.7	80.8
7384.8	74.9
8307.9	73.2
9231.0	NF

APPLICANT: UNIDEN AMERICA CORPORATION

FCCID: AMWUC728

DATE: DECEMBER 4, 2000

REPORT #: T:\CUS\U\Uniden\526BU0\526BU0RPT.doc

PAGE #: 6

APPLICANT : UNIDEN AMERICA CORPORATION
FCC ID : AMWUC728
NAME OF TEST: ANTENNA CONDUCTED SPURIOUS EMISSIONS
RULES PART NUMBER: 15.247(c) Spurious Emissions must be 20dBc.

FREQUENCY MHz	ATTENUATION dBc
HANDSET	
904.6	0.0
1809.2	51.8
2713.8	61.6
3618.4	70.3
4523.0	68.4
5427.6	63.4
6332.2	64.6
7236.8	68.7
8141.4	91.6
9046.0	89.8
912.8	0.0
1825.6	49.8
2738.4	65.2
3651.2	67.8
4564.0	71.8
5476.8	68.1
6389.6	60.8
7302.4	75.3
8215.2	82.2
9128.0	104.2
923.1	0.0
1846.2	53.3
2769.3	76.8
3692.4	74.8
4615.5	65.4
5538.6	72.6
6461.7	63.4
7384.8	69.6
8307.9	89.5
9231.0	97.5

The searches were made to the tenth harmonic.

APPLICANT: UNIDEN AMERICA CORPORATION
FCCID: AMWUC728
DATE: DECEMBER 4, 2000
REPORT #: T:\CUS\U\Uniden\526BU0\526BU0RPT.doc
PAGE #: 7

APPLICANT: UNIDEN AMERICA CORPORATION

FCC ID: AMWUC728

NAME OF TEST: RADIATED SPURIOUS EMISSIONS - HANDSET

RULES PART NUMBER: 15.247(c)

REQUIREMENTS: Emissions that fall in the restricted bands (15.205). These emissions must be less than or equal to 500 uV/m (54 dBuV/m). Spurious not in a restricted band must be 20dBc.

Manufacturer supplied a CW test mode for radiated and power output measurements and included a peak to duty cycle/DSSS mode correction factor of -6.02 dB which was applied to the following values. Even without the correction factor the unit complies with current rules.

TEST DATA:

EMISSION FREQUENCY MHz	METER READING @ 3m dBuV	COAX LOSS dB	ACF dB	C.F. dB	FIELD STRENGTH dBuV/m	FCC LIMIT dBuV/m	MARGIN dB	
HANDSET TUNED FREQUENCY 904.80								
904.60	73.80	4.40	27.70	-6.02	99.88	127.34	27.46	V
1809.20	16.70	1.00	27.20	-6.02	38.88	79.88	41.00	V
2713.80R	13.26	1.14	29.78	-6.02	38.16	54.00	15.84	H
3618.40R	15.92	1.27	32.05	-6.02	43.22	54.00	10.78	H
4523.00R	15.48	1.41	33.59	-6.02	44.46	54.00	9.54	H
5427.60R	11.25	1.54	34.61	-6.02	41.38	54.00	12.62	V
HANDSET TUNED FREQUENCY 914.40								
912.90	75.70	4.40	27.70	-6.02	101.78	127.34	25.56	V
1825.80	15.40	1.00	27.30	-6.02	37.68	81.78	44.10	V
2738.70R	12.16	1.14	29.85	-6.02	37.13	54.00	16.87	H
3651.60R	14.82	1.28	32.13	-6.02	42.21	54.00	11.79	H
4564.50R	17.68	1.42	33.64	-6.02	46.72	54.00	7.28	H
5477.40R	11.45	1.55	34.66	-6.02	41.64	54.00	12.36	V
HANDSET TUNED FREQUENCY 923.10								
921.10	74.20	4.40	27.70	-6.02	100.28	127.34	27.06	V
1842.20	15.00	1.01	27.37	-6.02	37.36	80.28	42.92	V
2763.30R	13.16	1.14	29.91	-6.02	38.19	54.00	15.81	H
3684.40R	13.22	1.28	32.21	-6.02	40.69	54.00	13.31	H
4605.50R	15.98	1.42	33.68	-6.02	45.06	54.00	8.94	H
5526.60	9.05	1.56	34.72	-6.02	39.31	80.28	40.97	V
6447.70	5.10	1.70	35.75	-6.02	36.53	80.28	43.75	V
7368.80R	13.96	1.84	36.79	-6.02	46.57	54.00	7.43	H

APPLICANT: UNIDEN AMERICA CORPORATION

FCCID: AMWUC728

DATE: NOVEMBER 7, 2000

REPORT #: T:\CUS\U\Uniden\526BU0\526BU0RPT.doc

PAGE #: 8

APPLICANT: UNIDEN AMERICA CORPORATION

FCC ID: AMWUC728

NAME OF TEST: RADIATED SPURIOUS EMISSIONS - BASE

TEST DATA CONTD.:

EMISSION FREQUENCY MHz	METER READING @ 3m dBuV	COAX LOSS dB	ACF dB	C.F. dB	FIELD STRENGTH dBuV/m	FCC LIMIT dBuV/m	MARGIN dB	
BASE TUNED FREQUENCY 904.80								
905.70	75.90	4.40	27.70	-6.02	101.98	127.34	25.36	V
1811.40	23.10	1.00	27.25	-6.02	45.33	81.98	36.65	V
2717.10R	13.76	1.14	29.79	-6.02	38.67	54.00	15.33	V
3622.80R	8.52	1.27	32.06	-6.02	35.83	54.00	18.17	H
4528.50R	11.95	1.41	33.59	-6.02	40.93	54.00	13.07	V
5434.20R	4.85	1.55	34.61	-6.02	34.99	54.00	19.01	V
BASE TUNED FREQUENCY 914.40								
913.90	75.10	4.40	27.70	-6.02	101.18	127.34	26.16	V
1827.80	22.50	1.00	27.31	-6.02	44.79	81.18	36.39	V
2741.70R	11.96	1.14	29.85	-6.02	36.93	54.00	17.07	V
3655.60R	8.42	1.28	32.14	-6.02	35.82	54.00	18.18	V
4569.50R	11.68	1.42	33.64	-6.02	40.72	54.00	13.28	V
BASE TUNED FREQUENCY 922.80								
920.10	73.90	4.40	27.70	-6.02	99.98	127.34	27.36	V
1840.20	21.90	1.01	27.36	-6.02	44.25	79.98	35.73	V
2760.30R	11.96	1.14	29.90	-6.02	36.98	54.00	17.02	V
3680.40R	9.72	1.28	32.20	-6.02	37.18	54.00	16.82	V
4600.50R	11.30	1.42	33.68	-6.02	40.38	54.00	13.62	V
5520.60	5.35	1.56	34.71	-6.02	35.60	79.98	44.38	H

SAMPLE CALCULATION: FSdBuV/m = MR(dBuV) + ACFdB + COAX+ C.F.

METHOD OF MEASUREMENT: The procedure used was ANSI STANDARD C63.4-1992. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported. The spectrum was scanned from 30 MHz to 10 GHz using a Hewlett Packard Model 8566B Spectrum Analyzer, Hewlett Packard Model 85685A Preselector, Hewlett Packard Model 85650A Quasi-Peak Adaptor, and an appropriate antenna. Low loss coax was used above 1 GHz. Measurements were made at Timco Engineering, Inc. 849 NW State Road 45 Newberry, Fl.

TEST RESULTS: The unit DOES meet the FCC requirements.

PERFORMED BY: Joseph Scoglio

DATE: NOVEMBER 7, 2000

REPORT #: T:\CUS\U\Uniden\526BU0\526BU0RPT.doc

PAGE #: 9

APPLICANT: UNIDEN AMERICA CORPORATION

FCC ID: AMWUC728

NAME OF TEST: POWER SPECTRAL DENSITY

RULES PART NUMBER: 15.247(d)

REQUIREMENTS: The power spectral density averaged over any 1 second interval shall not be greater than 8 dBm in any 3 kHz bandwidth within these bands.

TEST DATA:

The spectrum line spacing could not be resolved so the noise power density was measured;

Measurement Method:

Starting from the settings that were used for the 6 dB bandwidth the peak signal was located and the span was reduced and the sweep time increased in a manner to maintain calibration and to keep the peak emission in the display, then once the sweep time reached 500seconds at 2.00 MHz span the spectrum analyzer was put into the noise power mode and the plots made.

A value of -26.2 dBm was calculated for the handset.

A value of -24.2 dBm was calculated for the base.

SEE ATTACHED PLOTS

NAME OF TEST: PROCESSING GAIN

RULES PART NUMBER: 15.247(e)

REQUIREMENTS: The processing gain shall be at least 10 dB.

TEST DATA:

The processing gain of this unit is at least 12.1dB . This information was provided by the manufacturer.

FCCID: AMWUC728

DATE: DECEMBER 4, 2000

REPORT #: T:\CUS\U\Uniden\526BU0\526BU0RPT.doc

PAGE #: 10

