

FCC AND IC CERTIFICATION TEST REPORT

FOR

Applicant	:	Harman International Industries, Inc.
Address	:	8500 Balboa Boulevard, Northridge, CA 91329, UNITED STATES
Equipment under Test	:	Portable Bluetooth Speaker
Model No.	:	CHARGE4Q
Trade Mark	:	JBL
FCC ID	:	APIJBLCHARGE4Q
IC	:	6132A-JBLCHARGE4Q
Manufacturer	:	Harman International Industries, Inc.
Address	:	8500 Balboa Boulevard, Northridge, CA 91329, UNITED STATES

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan
City, Guangdong Province, China, 523808

Tel: +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

REPORT

TABLE OF CONTENTS

	Test report declares.....	4
1.	Summary of test results	6
2.	General test information	7
2.1.	Description of EUT	7
2.2.	Accessories of EUT.....	7
2.3.	Assistant equipment used for test.....	8
2.4.	Block diagram of EUT configuration for test	8
2.5.	Test environment conditions	8
2.6.	Deviations of test standard.....	9
2.7.	Test laboratory	9
2.8.	Measurement uncertainty.....	9
3.	Equipment used during test	10
4.	6dB Bandwidth and 99% Bandwidth.....	13
4.1.	Block diagram of test setup.....	13
4.2.	Limits	13
4.3.	Test Procedure	13
4.4.	Test Result	13
4.5.	Original test data	14
5.	Maximum Peak Output Power	16
5.1.	Block diagram of test setup.....	16
5.2.	Limits	16
5.3.	Test Procedure	16
5.4.	Test Result	16
5.5.	Original test data	17
6.	Power Spectral Density.....	19
6.1.	Block diagram of test setup.....	19
6.2.	Limits	19
6.3.	Test Procedure	19
6.4.	Test Result	19
6.5.	Original test data	20
7.	Band Edge Compliance (conducted method).....	22
7.1.	Block diagram of test setup.....	22
7.2.	Limits	22
7.3.	Test Procedure	22
7.4.	Test Result	22
7.5.	Original test data	23
8.	Radiated emission.....	24

8.1.	Block diagram of test setup.....	24
8.2.	Limit.....	25
8.3.	Test Procedure.....	26
8.4.	Test result.....	28
9.	RF Conducted Spurious Emissions	42
9.1.	Block diagram of test setup.....	42
9.2.	Limits	42
9.3.	Test Procedure.....	42
9.4.	Test Result	43
9.5.	Original test data	43
10.	Emissions in restricted frequency bands	48
10.1.	Block diagram of test setup.....	48
10.2.	Limit.....	48
10.3.	Test Procedure.....	48
10.4.	Test result.....	48
11.	Power Line Conducted Emission	53
11.1.	Block diagram of test setup.....	53
11.2.	Power Line Conducted Emission Limits	53
11.3.	Test Procedure.....	53
11.4.	Test Result	54
12.	Antenna Requirements	67
12.1.	Limit.....	67
12.2.	Result	67

TEST REPORT DECLARE

Applicant	:	Harman International Industries, Inc.
Address	:	8500 Balboa Boulevard, Northridge, CA 91329, UNITED STATES
Equipment under Test	:	Portable Bluetooth Speaker
Model No.	:	CHARGE4Q
Trade mark	:	JBL
Manufacturer	:	Harman International Industries, Inc.
Address	:	8500 Balboa Boulevard, Northridge, CA 91329, UNITED STATES

Test Standard Used:

FCC Rules and Regulations Part 15 Subpart C, RSS-247 Issue 2 February 2017.

Test procedure used:

ANSI C63.10:2013, RSS-Gen Issue 5, Apr. 2018

We Declare:

The equipment described above is tested by Dongguan Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Dongguan Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After test and evaluation, our opinion is that the equipment provided for test compliance with the requirement of the above FCC&IC standards.

Report No:	DDT-R18093005-5E5		
Date of Receipt:	Jan. 29, 2019, May 14, 2019 and Dec. 01, 2019	Date of Test:	Jan. 29, 2019 ~ Mar. 13, 2019, May. 14, 2019 ~ May 29, 2019 and Dec. 01, 2019 ~ Jan. 03, 2020

Prepared By:

Ella Gong
Ella Gong/Engineer

Approved By:


Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

Revision history

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Mar. 13, 2019	
Rev. 01	Removed Microphone-related circuits, and added new batteries, this change doesn't influence the RF performance, so only power line conducted and radiated emission (below 1GHz) were tested and updated in this report.	Jan. 02, 2020	Ella Gong

1. Summary of test results

The EUT have been tested according to the applicable standards as referenced below.		
Description of Test Item	Standard	Results
6dB Bandwidth and 99% Bandwidth	FCC Part 15: 15.247 ANSI C63.10:2013 RSS-247 Issue 2	PASS
Peak Output Power	FCC Part 15: 15.247 ANSI C63.10:2013 RSS-247 Issue 2	PASS
Power Spectral Density	FCC Part 15:15.247 ANSI C63.10:2013 RSS-247 Issue 2	PASS
Band Edge Compliance (conducted method)	FCC Part 15: 15.209 FCC Part 15: 15.247 ANSI C63.10: 2013 RSS-247 Issue 2 RSS-Gen Issue 5	PASS
Radiation Emission	FCC Part 15: 15.247 ANSI C63.10:2013 RSS-247 Issue 2 RSS-Gen Issue 5	PASS
RF Conducted Spurious Emissions	FCC Part 15: 15.209 FCC Part 15: 15.247 ANSI C63.10: 2013 RSS-247 Issue 2 RSS-Gen Issue 5	PASS
Emission in restricted frequency bands	FCC Part 15: 15.209 FCC Part 15: 15.247 ANSI C63.10: 2013 RSS-247 Issue 2 RSS-Gen Issue 5	PASS
Power Line Conducted Emission	FCC Part 15: 15.207 ANSI C63.10: 2013 RSS-Gen Issue 5	PASS
Antenna requirement	FCC Part 15: 15.203 RSS-Gen Issue 5	PASS
Note: This report removed Microphone-related circuits, and added new batteries based on the original report: DDT-R18093005-4E5, these changes don't influence the RF performance, so only radiated emission (below 1GHz) and Power Line Conducted Emissions were tested and recorded in this report, and the original test data was retained in this report.		

2. General test information

2.1. Description of EUT

EUT* Name	: Portable Bluetooth Speaker
Model Number	: CHARGE4Q
EUT function description	: Please reference user manual of this device
Power supply	: DC 5V from external AC Adapter : DC 3.6V 7500mAh Polymer Li-ion built-in battery
Radio Specification	: Bluetooth V4.2
Operation frequency	: 2402MHz-2480MHz
Modulation	: GFSK
Data rate	: 1Mbps
Antenna Type	: Dedicated FPCB antenna, maximum PK gain: 2.24 dBi
Sample Type	: Series production

Note: EUT is the ab. of equipment under test.

Channel information					
Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	14	2430MHz	28	2458MHz
1	2404MHz	15	2432MHz	29	2460MHz
2	2406MHz	16	2434MHz	30	2462MHz
3	2408MHz	17	2436MHz	31	2464MHz
4	2410MHz	18	2438MHz	32	2466MHz
5	2412MHz	19	2440MHz	33	2468MHz
6	2414MHz	20	2442MHz	34	2470MHz
7	2416MHz	21	2444MHz	35	2472MHz
8	2418MHz	22	2446MHz	36	2474MHz
9	2420MHz	23	2448MHz	37	2476MHz
10	2422MHz	24	2450MHz	38	2478MHz
11	2424MHz	25	2452MHz	39	2480MHz
12	2426MHz	26	2454MHz		
13	2428MHz	27	2456MHz		

2.2. Accessories of EUT

Description of Accessories	Manufacturer	Model number	Parameter	Remark
Built-in Battery	ICON ENERGY SYSTEM (SHENZHEN) CO., LTD.	ID998	DC 3.6V, 7500mAh, 27.0Wh	Factory 1 Alternative
Built-in Battery	ICON ENERGY SYSTEM (SHENZHEN) CO., LTD.	ID998-B	DC 3.6V, 7500mAh, 27.0Wh	
Built-in Battery	SUNWODA Electronic Co.,Ltd	SUN-INTE-118	3.6V, 7500mAh, 27.0Wh	Factory 2
USB cable	Harman	N/A	N/A	Length: 1.2m, unshielded


New Battery information:

Description of Accessories	Manufacturer	Model number	Description	Remark
Built-in Battery	ICON ENERGY SYSTEM (SHENZHEN) CO., LTD.	IY1068	DC 3.6V, 7500mAh, 27.0Wh	Factory 1 Alternative
Built-in Battery	ICON ENERGY SYSTEM (SHENZHEN) CO., LTD.	IAA011NA	3.6V, 7500mAh, 27.0Wh	
Built-in Battery	SUNWODA Electronic Co., Ltd	SUN-INTE-156	3.6V, 7500mAh, 27.0Wh	Factory 2 Alternative
Built-in Battery	GREAT POWER BATTERY CO., LTD	GSP-1S3P-CH4A	3.6V, 7500mAh, 27.0Wh	

2.3. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	EMC Compliance	Other
Notebook	DELL	Latitude D610	FCC DOC	00045-534-136-300
AC Adapter	Tencent	A215-050210U-CN1	N/A	Input: AC 100-240V -50/60Hz, 0.35A; Output: DC 5V, 2.1A

2.4. Block diagram of EUT configuration for test



Test software: BlueTest3.EXE

The test software was used to control EUT work in Continuous Tx mode, and select test channel, wireless mode as below table:

Tested mode, channel, information		
Mode	Channel	Frequency (MHz)
GFSK	CH0	2402
	CH19	2440
	CH39	2480

2.5. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	21-25°C
Humidity range:	40-75%
Pressure range:	86-106kPa

2.6. Deviations of test standard

No Deviation.

2.7. Test laboratory

Dongguan Dongdian Testing Service Co., Ltd

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City,
Guangdong Province, China, 523808

Tel: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com

CNAS Accreditation No. L6451; A2LA Accreditation No. 3870.01

FCC Designation Number: CN1182; FCC Test Firm Registration Number: 540522

Industry Canada site registration number: 10288A-1

2.8. Measurement uncertainty

Test Item	Uncertainty
Bandwidth	1.1%
Peak Output Power (Conducted) (Spectrum analyzer)	0.86dB (10MHz ≤ f < 3.6GHz); 1.38dB (3.6GHz ≤ f < 8GHz)
Peak Output Power (Conducted) (Power Sensor)	0.74dB
Power Spectral Density	0.74dB (10MHz ≤ f < 3.6GHz); 1.38dB (3.6GHz ≤ f < 8GHz)
Frequencies Stability	6.7 × 10 ⁻⁸ (Antenna couple method) 5.5 × 10 ⁻⁸ (Conducted method)
Conducted spurious emissions	0.86dB (1 MHz ≤ f < 3.6GHz); 1.40dB (3.6GHz ≤ f < 8GHz) 1.66dB (8GHz ≤ f < 22GHz)
Uncertainty for radio frequency (RBW<20kHz)	3×10 ⁻⁸
Temperature	0.4℃
Humidity	2%
Uncertainty for Radiation Emission test (30MHz-1GHz)	4.70dB (Antenna Polarize: V) 4.84dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1GHz-40GHz)	4.10dB (1-6GHz) 4.40dB (6GHz-18GHz) 3.54dB (18GHz-26GHz) 4.30dB (26GHz-40GHz)
Uncertainty for Power line conduction emission test	3.32dB (150kHz-30MHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

3. Equipment used during test


Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
RF Connected Test (Tonscend RF Measurement System)					
Spectrum analyzer	R&S	FSU26	200071	Oct. 12, 2018	1 Year
Wideband Radio Communication tester	R&S	CMW500	117491	Jun. 29, 2018	1 Year
Vector Signal Generator	Agilent	E8267D	US49060192	Oct. 12, 2018	1 Year
Vector Signal Generator	Agilent	N5182A	MY48180737	Jun. 29, 2018	1 Year
Power Sensor	Agilent	U2021XA	MY55150010	Oct. 21, 2018	1 Year
Power Sensor	Agilent	U2021XA	MY55150011	Oct. 23, 2018	1 Year
DC Power Source	MATRIS	MPS-3005L-3	D813058W	Aug. 18, 2018	1 Year
Attenuator	Mini-Circuits	BW-S10W2	101109	Aug. 18, 2018	1 Year
RF Cable	Micable	C10-01-01-1	100309	Oct. 21, 2018	1 Year
Temp&Humi Programmable	ZHIXIANG	ZXGDJS-150L	ZX170110-A	Oct. 21, 2018	1 Year
Test Software	JS Tonscend	JS1120-3	Ver.2.7	N/A	N/A
Radiation 1#chamber					
EMI Test Receiver	R&S	ESU8	100316	Oct. 12, 2018	1 Year
Spectrum analyzer	Agilent	E4447A	MY50180031	Jun. 29, 2018	1 Year
Trilog Broadband Antenna	Schwarzbeck	VULB9163	9163-462	Nov. 09, 2018	1 Year
Active Loop antenna	Schwarzbeck	FMZB-1519	1519-038	Oct. 20, 2018	1 Year
Double Ridged Horn Antenna	R&S	HF907	100276	Oct. 17, 2018	1 Year
Broad Band Horn Antenna	Schwarzbeck	BBHA 9170	790	Oct. 25, 2018	1 Year
Pre-amplifier	A.H.	PAM-0118	360	Oct. 12, 2018	1 Year
Pre-amplifier	TERA-MW	TRLA-0040 G35	101303	Oct. 12, 2018	1 Year
RF Cable	HUBSER	CP-X2+ CP-X1	W11.03+ W12.02	Oct. 21, 2018	1 Year
RF Cable	N/A	SMAJ-SMAJ -1M+ 11M	17070133+17070131	Nov. 08, 2018	1 Year
MI Cable	HUBSER	C10-01-01-1M	1091629	Oct. 21, 2018	1 Year
Test software	Audix	E3	V 6.11111b	N/A	N/A
Power Line Conducted Emissions Test					
EMI Test Receiver	R&S	ESU8	100316	Oct. 21, 2018	1 Year
LISN 1	R&S	ENV216	101109	Oct. 21, 2018	1 Year
LISN 2	R&S	ESH2-Z5	100309	Oct. 21, 2018	1 Year
Pulse Limiter	R&S	ESH3-Z2	101242	Oct. 21, 2018	1 Year
CE Cable 1	HUBSER	N/A	W10.01	Oct. 21, 2018	1 Year
Test software	Audix	E3	V 6.11111b	N/A	N/A

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
RF Connected Test (Tonscend RF Measurement System)					
Spectrum analyzer	R&S	FSU26	200071	Oct. 12, 2018	1 Year
Wideband Radio Communication tester	R&S	CMW500	117491	Jun. 25, 2019	1 Year
Vector Signal Generator	Agilent	E8267D	US49060192	Oct. 12, 2018	1 Year
Vector Signal Generator	Agilent	N5182A	MY48180737	Jun. 25, 2019	1 Year
Power Sensor	Agilent	U2021XA	MY55150010	Oct. 21, 2018	1 Year
Power Sensor	Agilent	U2021XA	MY55150011	Oct. 23, 2018	1 Year
DC Power Source	MATRIS	MPS-3005L-3	D813058W	Aug. 18, 2018	1 Year
Attenuator	Mini-Circuits	BW-S10W2	101109	Aug. 18, 2018	1 Year
RF Cable	Micable	C10-01-01-1	100309	Oct. 21, 2018	1 Year
Temp&Humi Programmable	ZHIXIANG	ZXGDJS-150L	ZX170110-A	Oct. 21, 2018	1 Year
Test Software	JS Tonscend	JS1120-3	Ver.2.7	N/A	N/A
Radiation 1#chamber					
EMI Test Receiver	R&S	ESU8	100316	Oct. 12, 2018	1 Year
Spectrum analyzer	Agilent	E4447A	MY50180031	Jun. 25, 2019	1 Year
Trilog Broadband Antenna	Schwarzbeck	VULB9163	9163-462	Nov. 09, 2018	1 Year
Active Loop antenna	Schwarzbeck	FMZB-1519	1519-038	Oct. 20, 2018	1 Year
Double Ridged Horn Antenna	R&S	HF907	100276	Oct. 17, 2018	1 Year
Broad Band Horn Antenna	Schwarzbeck	BBHA 9170	790	Oct. 25, 2018	1 Year
Pre-amplifier	A.H.	PAM-0118	360	Oct. 12, 2018	1 Year
Pre-amplifier	TERA-MW	TRLA-0040 G35	101303	Oct. 12, 2018	1 Year
RF Cable	HUBSER	CP-X2+ CP-X1	W11.03+ W12.02	Oct. 21, 2018	1 Year
RF Cable	N/A	SMAJ-SMAJ -1M+ 11M	17070133+17070131	Nov. 08, 2018	1 Year
MI Cable	HUBSER	C10-01-01-1 M	1091629	Oct. 21, 2018	1 Year
Test software	Audix	E3	V 6.11111b	N/A	N/A
Power Line Conducted Emissions Test					
EMI Test Receiver	R&S	ESU8	100316	Oct. 21, 2018	1 Year
LISN 1	R&S	ENV216	101109	Oct. 21, 2018	1 Year
LISN 2	R&S	ESH2-Z5	100309	Oct. 21, 2018	1 Year
Pulse Limiter	R&S	ESH3-Z2	101242	Oct. 21, 2018	1 Year
CE Cable 1	HUBSER	N/A	W10.01	Oct. 21, 2018	1 Year
Test software	Audix	E3	V 6.11111b	N/A	N/A

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
RF Connected Test (Tonscend RF Measurement System)					
Spectrum analyzer	R&S	FSU26	200071	Sep. 29, 2019	1 Year
Wideband Radio Communication tester	R&S	CMW500	117491	Jun. 25, 2019	1 Year
Vector Signal Generator	Agilent	E8267D	US49060192	Sep. 29, 2019	1 Year
Vector Signal Generator	Agilent	N5182A	MY48180737	Jun. 25, 2019	1 Year
Power Sensor	Agilent	U2021XA	MY55150010	Jun. 28, 2019	1 Year
Power Sensor	Agilent	U2021XA	MY55150011	Jun. 28, 2019	1 Year
DC Power Source	MATRIS	MPS-3005L-3	D813058W	Jun. 25, 2019	1 Year
RF Cable	Micable	C10-01-01-1	100309	Sep. 29, 2019	1 Year
Temp&Humi Programmable	ZHIXIANG	ZXGDJS-150L	ZX170110-A	Sep. 29, 2019	1 Year
Test Software	JS Tonscend	JS1120-3	Ver.2.7	N/A	N/A
Radiation 1#chamber					
EMI Test Receiver	R&S	ESU8	100316	Sep. 29, 2019	1 Year
Spectrum analyzer	Agilent	E4447A	MY50180031	Jun. 25, 2019	1 Year
Trilog Broadband Antenna	Schwarzbeck	VULB9163	9163-462	Nov. 15, 2019	1 Year
Active Loop antenna	Schwarzbeck	FMZB-1519	1519-038	Sep. 29, 2019	1 Year
Double Ridged Horn Antenna	R&S	HF907	100276	Nov. 15, 2019	1 Year
Broad Band Horn Antenna	Schwarzbeck	BBHA 9170	790	Sep. 29, 2019	1 Year
Pre-amplifier	A.H.	PAM-0118	360	Sep. 29, 2019	1 Year
Pre-amplifier	TERA-MW	TRLA-0040 G35	101303	Sep. 29, 2019	1 Year
RF Cable	HUBSER	CP-X2+ CP-X1	W11.03+ W12.02	Sep. 29, 2019	1 Year
RF Cable	N/A	SMAJ-SMAJ -1M+ 11M	17070133+17070131	Sep. 29, 2019	1 Year
MI Cable	HUBSER	C10-01-01-1M	1091629	Sep. 29, 2019	1 Year
Test software	Audix	E3	V 6.11111b	N/A	N/A
Power Line Conducted Emissions Test					
EMI Test Receiver	R&S	ESU8	100316	Sep. 29, 2019	1 Year
LISN 1	R&S	ENV216	101109	Sep. 29, 2019	1 Year
LISN 2	R&S	ESH2-Z5	100309	Sep. 29, 2019	1 Year
Pulse Limiter	R&S	ESH3-Z2	101242	Sep. 29, 2019	1 Year
CE Cable 1	HUBSER	N/A	W10.01	Sep. 29, 2019	1 Year
Test software	Audix	E3	V 6.11111b	N/A	N/A

4. 6dB Bandwidth and 99% Bandwidth

4.1. Block diagram of test setup



4.2. Limits

For direct sequence systems, the minimum 6dB bandwidth shall be at least 500 kHz

4.3. Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Set the spectrum analyzer as follows:


RBW:	100kHz
VBW:	300kHz
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold


(3) Allow the trace to stabilize, measure the 6dB and 99% bandwidth of signal.

4.4. Test Result

Mode	Channel	6dB bandwidth Result (MHz)	99% bandwidth Result (MHz)	6dB width Limit (MHz)	Conclusion
GFSK	CH0	0.720	1.092	>0.5	PASS
	CH19	0.728	1.088	>0.5	PASS
	CH39	0.716	1.076	>0.5	PASS

4.5. Original test data





5. Maximum Peak Output Power

5.1. Block diagram of test setup

Same with 4.1

5.2. Limits

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. If transmitting antennas of directional gain greater than 6dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6dBi.

5.3. Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Set the spectrum analyzer as follows:


RBW:	≥DTS bandwidth
VBW:	≥3 x RBW
Span	≥3 x RBW
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold


(3) Allow the trace to stabilize, Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges measure out the PK output power.

5.4. Test Result

Test Mode	Antenna	Channel	Peak Output Power (dBm)	Limit (dBm)	Verdict
BLE	ANT1	2402	5.52	30	PASS
BLE	ANT1	2440	6.17	30	PASS
BLE	ANT1	2480	6.40	30	PASS

5.5. Original test data





6. Power Spectral Density

6.1. Block diagram of test setup

Same with 4.1

6.2. Limits

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

6.3. Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Set the spectrum analyzer as follows:

Center frequency	DTS Channel center frequency
RBW:	$3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$
VBW:	$\geq 3\text{RBW}$
Span	1.5 times the DTS bandwidth
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold


(3) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.


(4) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.4. Test Result

EUT Set Mode	Antenna	Channel	Result (dBm/3kHz)
GFSK	ANT1	CH0	-11.18
	ANT1	CH19	-10.48
	ANT1	CH39	-10.22
Limit: <8dBm/3kHz			Conclusion: PASS

6.5. Original test data





7. Band Edge Compliance (conducted method)

7.1. Block diagram of test setup

Same with 4.1

7.2. Limits

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

7.3. Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Establish a reference level by using the following procedure:

Center frequency	DTS Channel center frequency
RBW:	100kHz
VBW:	300kHz
Span	1.5times the DTS bandwidth
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.

(4) Set the spectrum analyzer as follows:

RBW:	100kHz
VBW:	300kHz
Span	Encompass frequency range to be measured
Number of measurement points	$\geq \text{span/RBW}$
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold


(5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band

7.4. Test Result

EUT Set Mode	CH or Frequency	Measured Range	Result (dBm)
--------------	-----------------	----------------	--------------

EUT Set Mode	CH or Frequency	Measured Range	Result (dBm)
GFSK	CH0	2.310GHz-2.410GHz	PASS
	CH39	2.470GHz-2.570GHz	PASS


7.5. Original test data




8. Radiated emission

8.1. Block diagram of test setup


In 3m Anechoic Chamber Test Setup Diagram for 9kHz-30MHz



In 3m Anechoic Chamber Test Setup Diagram for 30MHz-1GHz



In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



Note: For harmonic emissions test an appropriate high pass filter was inserted in the input port of AMP.

8.2. Limit

8.2.1 FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

8.2.2 FCC 15.209 Limit.

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		$\mu\text{V/m}$	$\text{dB}(\mu\text{V})/\text{m}$
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

Note: (1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000MHz. Radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3\text{m}}(\text{dB}\mu\text{V}/\text{m}) = \text{Limit}_{30\text{m}}(\text{dB}\mu\text{V}/\text{m}) + 40\text{Log}(30\text{m}/3\text{m})$$

8.2.3 Limit for this EUT

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions or comply with 15.209 limits.

8.3. Test Procedure

- (1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1G and 150 cm above the ground plane inside a semi-anechoic chamber for above 1G.
- (2) Test antenna was located 3m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used	Test antenna distance
9kHz-30MHz	Active Loop antenna	3m
30MHz-1GHz	Trilog Broadband Antenna	3m
1GHz-18GHz	Double Ridged Horn Antenna(1GHz-18GHz)	3m
18GHz-40GHz	Horn Antenna(18GHz-40GHz)	1m

According ANSI C63.10:2013 clause 6.4.4.2 and 6.5.3, for measurements below 30 MHz, the loop antenna was positioned with its plane vertical from the EUT and rotated about its vertical axis for maximum response at each azimuth position around the EUT. And the loop antenna also

be positioned with its plane horizontal at the specified distance from the EUT. The center of the loop is 1 m above the ground. for measurement above 30MHz, the Trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9kHz to 25GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1m to 4m (Except loop antenna, it's fixed 1m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9kHz to 25GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 9kHz to 30MHz and 18GHz to 25GHz, so below final test was performed with frequency range from 30MHz to 18GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10:2013 on Radiated Emission test.

(5) The emissions from 9kHz to 1GHz were measured based on CISPR QP detector except for the frequency bands 9-90kHz, 110-490kHz, for emissions from 9kHz-90kHz,110kHz-490kHz and above 1GHz were measured based on average detector, for emissions above 1GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9kHz to 1GHz, QP or average values were measured with EMI receiver with below RBW

Frequency band	RBW
9kHz-150kHz	200Hz
150kHz-30MHz	9kHz
30MHz-1GHz	120kHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RBW is set at 1MHz, VBW is set at 10Hz for Average measure (according ANSI C63.10:2013 clause 4.1.4.2.2 procedure for average measure).

(8) X axis, Y axis, Z axis are tested, and worse setup X axis is reported.

8.4. Test result

PASS. (See below detailed test result)

All the emissions except fundamental emission from 9kHz to 25GHz were comply with 15.209 limit.

Note1: According exploratory test no any obvious emission was detected from 9kHz to 30MHz and 18GHz to 25GHz, so the final test was performed with frequency range from 30MHz to 18GHz and recorded in below.

Note2: For emissions below 1GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1GHz, the final test was only performed with EUT working in GFSK, Tx 2480MHz mode.

Note3: For emissions above 1GHz. If peak results comply with AV limit, AV Result is deemed to comply with AV limit.


Radiated Emission test (below 1GHz)

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#
Test Date : 2019-02-21
EUT : Portable Bluetooth Speaker
Power Supply : Battery
Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa
Memo : Original

D:\2018 RE1# Report Data\Q18093005-1E CHARGE4Q\FCC BELOW1G.EM6
Tested By : Talent
Model Number : CHARGE4Q
Test Mode : Tx mode
Antenna/Distance : 2018 VULB 9163 1#/3m/HORIZONTAL

Data: 3



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	34.04	6.67	12.11	3.70	22.48	40.00	-17.52	QP	HORIZONTAL
2	85.00	9.82	9.47	4.11	23.40	40.00	-16.60	QP	HORIZONTAL
3	149.49	9.18	8.41	4.51	22.10	43.50	-21.40	QP	HORIZONTAL
4	274.19	0.80	13.42	5.09	19.31	46.00	-26.69	QP	HORIZONTAL
5	601.43	3.11	18.52	6.10	27.73	46.00	-18.27	QP	HORIZONTAL
6	638.37	2.44	19.14	6.20	27.78	46.00	-18.22	QP	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2018 RE1# Report Data\Q18093005-1E CHARGE4Q\FCC
BELOW1G.EM6

Test Date : 2019-02-21

Tested By : Talent

EUT : Portable Bluetooth Speaker

Model Number : CHARGE4Q

Power Supply : Battery


Test Mode : Tx mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2018 VULB 9163 1#/3m/VERTICAL

Memo : Original

Data: 4



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	34.28	7.73	12.17	3.70	23.60	40.00	-16.40	QP	VERTICAL
2	57.39	3.65	12.18	3.93	19.76	40.00	-20.24	QP	VERTICAL
3	85.30	10.77	9.50	4.12	24.39	40.00	-15.61	QP	VERTICAL
4	149.49	7.94	8.41	4.51	20.86	43.50	-22.64	QP	VERTICAL
5	348.03	1.04	14.83	5.35	21.22	46.00	-24.78	QP	VERTICAL
6	601.43	3.17	18.52	6.10	27.79	46.00	-18.21	QP	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2018 RE1# Report Data\Q18093005-1E CHARGE4Q\FCC
BELOW1G.EM6

Test Date : 2019-02-21

Tested By : Talent

EUT : Portable Bluetooth Speaker

Model Number : CHARGE4Q


Power Supply : Battery

Test Mode : Tx mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2018 VULB 9163 1#/3m/HORIZONTAL

Memo : Original



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	34.52	7.52	12.22	3.70	23.44	40.00	-16.56	QP	HORIZONTAL
2	85.00	10.82	9.47	4.11	24.40	40.00	-15.60	QP	HORIZONTAL
3	149.49	10.73	8.41	4.51	23.65	43.50	-19.85	QP	HORIZONTAL
4	239.99	3.31	12.57	4.96	20.84	46.00	-25.16	QP	HORIZONTAL
5	601.43	4.15	18.52	6.10	28.77	46.00	-17.23	QP	HORIZONTAL
6	779.61	2.19	20.58	6.56	29.33	46.00	-16.67	QP	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2018 RE1# Report Data\Q18093005-1E CHARGE4Q\FCC
BELOW1G.EM6

Test Date : 2019-02-21

Tested By : Talent

EUT : Portable Bluetooth Speaker

Model Number : CHARGE4Q


Power Supply : Battery

Test Mode : Tx mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2018 VULB 9163 1#/3m/VERTICAL

Memo : Original



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	33.92	7.89	12.08	3.70	23.67	40.00	-16.33	QP	VERTICAL
2	85.30	10.98	9.50	4.12	24.60	40.00	-15.40	QP	VERTICAL
3	149.49	9.40	8.41	4.51	22.32	43.50	-21.18	QP	VERTICAL
4	390.72	1.13	15.47	5.48	22.08	46.00	-23.92	QP	VERTICAL
5	601.43	3.72	18.52	6.10	28.34	46.00	-17.66	QP	VERTICAL
6	752.74	2.35	20.43	6.51	29.29	46.00	-16.71	QP	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2019 RE1# Report Data\Q19043005-1E Charge 4\FCC
BELOW1G.EM6

Test Date : 2019-05-06

Tested By : Talent

EUT : Portable Bluetooth Speaker

Model Number : CHARGE4Q


Power Supply : Battery

Test Mode : Tx mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2018 VULB 9163 1#/3m/VERTICAL

Memo : New Battery: IY1068



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	50.59	2.14	14.40	3.87	20.41	40.00	-19.59	QP	VERTICAL
2	113.32	2.13	11.08	4.27	17.48	43.50	-26.02	QP	VERTICAL
3	260.14	3.50	13.09	5.04	21.63	46.00	-24.37	QP	VERTICAL
4	329.04	3.17	14.51	5.29	22.97	46.00	-23.03	QP	VERTICAL
5	642.86	2.73	19.22	6.22	28.17	46.00	-17.83	QP	VERTICAL
6	869.13	2.31	21.40	6.79	30.50	46.00	-15.50	QP	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2019 RE1# Report Data\Q19043005-1E Charge 4\FCC
BELOW1G.EM6

Test Date : 2019-05-06

Tested By : Talent

EUT : Portable Bluetooth Speaker

Model Number : CHARGE4Q


Power Supply : Battery

Test Mode : Tx mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2018 VULB 9163 1#/3m/HORIZONTAL

Memo : New Battery: IY1068



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	50.59	2.58	14.40	3.87	20.85	40.00	-19.15	QP	HORIZONTAL
2	104.54	2.03	11.75	4.23	18.01	43.50	-25.49	QP	HORIZONTAL
3	238.31	1.23	12.52	4.95	18.70	46.00	-27.30	QP	HORIZONTAL
4	344.39	2.80	14.77	5.34	22.91	46.00	-23.09	QP	HORIZONTAL
5	570.61	4.79	18.11	6.01	28.91	46.00	-17.09	QP	HORIZONTAL
6	706.70	4.41	20.14	6.40	30.95	46.00	-15.05	QP	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2019 RE1# Report Data\Q19103117-1E TCL 三星电池\fcc
below 1G.EM6

Test Date : 2019-12-22

Tested By : Jacky

EUT : Portable Bluetooth Speaker

Model Number : CHARGE4Q

Power Supply : Battery


Test Mode : Tx mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2019 VULB 9163 1#/3m/VERTICAL

Memo : New Battery: IAA011NA

Data: 9



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	37.42	4.52	13.12	3.88	21.52	40.00	-18.48	QP	VERTICAL
2	52.95	3.46	13.82	4.02	21.30	40.00	-18.70	QP	VERTICAL
3	226.89	12.56	12.24	5.17	29.97	46.00	-16.03	QP	VERTICAL
4	407.51	2.09	15.46	5.99	23.54	46.00	-22.46	QP	VERTICAL
5	636.13	2.76	19.47	6.87	29.10	46.00	-16.90	QP	VERTICAL
6	929.01	2.65	22.10	7.77	32.52	46.00	-13.48	QP	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2019 RE1# Report Data\Q19103117-1E TCL 三星电池\fcc
below 1G.EM6

Test Date : 2019-12-22

Tested By : Jacky

EUT : Portable Bluetooth Speaker

Model Number : CHARGE4Q

Power Supply : Battery


Test Mode : Tx mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2019 VULB 9163 1#/3m/HORIZONTAL

Memo : New Battery: IAA011NA

Data: 10



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	37.55	4.65	13.15	3.88	21.68	40.00	-18.32	QP	HORIZONTAL
2	57.39	6.64	13.29	4.07	24.00	40.00	-16.00	QP	HORIZONTAL
3	225.31	21.51	12.19	5.17	38.87	46.00	-7.13	QP	HORIZONTAL
4	355.43	9.58	14.81	5.78	30.17	46.00	-15.83	QP	HORIZONTAL
5	468.88	3.75	16.65	6.23	26.63	46.00	-19.37	QP	HORIZONTAL
6	813.11	3.31	20.85	7.41	31.57	46.00	-14.43	QP	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2019 RE1# Report Data\Q19043005-1E Charge 4\FCC
BELOW1G.EM6

Test Date : 2019-05-09

Tested By : Talent

EUT : Portable Bluetooth Speaker

Model Number : CHARGE4Q


Power Supply : Battery

Test Mode : TX mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2018 VULB 9163 1#/3m/VERTICAL

Memo : New Battery: SUN-INTE-156



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	44.59	6.08	13.98	3.82	23.88	40.00	-16.12	QP	VERTICAL
2	87.42	7.91	9.73	4.13	21.77	40.00	-18.23	QP	VERTICAL
3	106.39	7.32	11.76	4.24	23.32	43.50	-20.18	QP	VERTICAL
4	251.18	3.72	12.86	5.01	21.59	46.00	-24.41	QP	VERTICAL
5	423.54	2.82	15.98	5.59	24.39	46.00	-21.61	QP	VERTICAL
6	661.15	3.43	19.51	6.27	29.21	46.00	-16.79	QP	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2019 RE1# Report Data\Q19043005-1E Charge 4\FCC
BELOW1G.EM6

Test Date : 2019-05-09

Tested By : Talent

EUT : Portable Bluetooth Speaker

Model Number : CHARGE4Q


Power Supply : Battery

Test Mode : TX mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2018 VULB 9163 1#/3m/HORIZONTAL

Memo : New Battery: SUN-INTE-156



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	52.58	8.45	13.72	3.89	26.06	40.00	-13.94	QP	HORIZONTAL
2	101.64	4.43	11.72	4.21	20.36	43.50	-23.14	QP	HORIZONTAL
3	245.09	4.75	12.70	4.98	22.43	46.00	-23.57	QP	HORIZONTAL
4	425.03	2.24	16.01	5.59	23.84	46.00	-22.16	QP	HORIZONTAL
5	677.58	2.78	19.76	6.31	28.85	46.00	-17.15	QP	HORIZONTAL
6	919.29	5.83	21.92	7.01	34.76	46.00	-11.24	QP	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2019 RE1# Report Data\Q19110107-4E 国光 三星电池\FCC
BELOW 1G.EM6

Test Date : 2019-12-22

Tested By : Jacky

EUT : Portable Bluetooth Speaker

Model Number : CHARGE4Q


Power Supply : Battery

Test Mode : Tx mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2019 VULB 9163 1#/3m/HORIZONTAL

Memo : New Battery: GSP-1S3P-CH4A



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	38.62	4.98	13.39	3.89	22.26	40.00	-17.74	QP	HORIZONTAL
2	52.76	3.87	13.85	4.02	21.74	40.00	-18.26	QP	HORIZONTAL
3	99.18	2.27	11.82	4.40	18.49	43.50	-25.01	QP	HORIZONTAL
4	219.85	8.61	12.03	5.14	25.78	46.00	-20.22	QP	HORIZONTAL
5	251.18	13.38	12.92	5.30	31.60	46.00	-14.40	QP	HORIZONTAL
6	310.00	7.61	14.24	5.57	27.42	46.00	-18.58	QP	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2019 RE1# Report Data\Q19110107-4E 国光 三星电池\FCC
BELOW 1G.EM6

Test Date : 2019-12-22

Tested By : Jacky

EUT : Portable Bluetooth Speaker

Model Number : CHARGE4Q


Power Supply : Battery

Test Mode : Tx mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2019 VULB 9163 1#/3m/VERTICAL

Memo : New Battery: GSP-1S3P-CH4A



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	37.03	5.05	13.03	3.88	21.96	40.00	-18.04	QP	VERTICAL
2	50.59	2.26	14.12	4.00	20.38	40.00	-19.62	QP	VERTICAL
3	249.43	7.49	12.87	5.29	25.65	46.00	-20.35	QP	VERTICAL
4	350.48	8.01	14.75	5.76	28.52	46.00	-17.48	QP	VERTICAL
5	609.92	2.72	19.27	6.78	28.77	46.00	-17.23	QP	VERTICAL
6	813.11	3.00	20.85	7.41	31.26	46.00	-14.74	QP	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

Radiated Emission test (above 1GHz)

Freq. (MHz)	Read level (dBμV)	Antenn a Factor (dB/m)	PRM Facto r(dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit (dBμ V/m)	Margin (dB)	Detecto r type	Polarization
GFSK Tx mode 2402MHz									
4808.00	47.56	33.79	44.24	11.23	48.34	74.00	-25.66	Peak	HORIZONTAL
5828.00	48.65	34.57	44.03	11.42	50.61	74.00	-23.39	Peak	HORIZONTAL
6865.00	47.70	35.52	43.58	12.33	51.97	74.00	-22.03	Peak	HORIZONTAL
7936.00	46.06	36.25	43.13	13.90	53.08	74.00	-20.92	Peak	HORIZONTAL
9466.00	45.97	37.09	43.85	14.70	53.91	74.00	-20.09	Peak	HORIZONTAL
10520.00	44.06	37.69	43.95	15.63	53.43	74.00	-20.57	Peak	HORIZONTAL
4808.00	48.66	33.79	44.24	11.23	49.44	74.00	-24.56	Peak	VERTICAL
6202.00	47.23	34.95	43.90	12.29	50.57	74.00	-23.43	Peak	VERTICAL
7375.00	46.17	35.83	43.35	12.98	51.63	74.00	-22.37	Peak	VERTICAL
8310.00	46.51	36.61	43.27	13.37	53.22	74.00	-20.78	Peak	VERTICAL
9415.00	44.98	37.06	43.83	14.85	53.06	74.00	-20.94	Peak	VERTICAL
10129.00	44.46	37.48	44.06	15.36	53.24	74.00	-20.76	Peak	VERTICAL
GFSK Tx mode 2440MHz									
4808.00	48.66	33.79	44.24	11.23	49.44	74.00	-24.56	Peak	HORIZONTAL
6049.00	48.83	34.76	43.97	11.32	50.94	74.00	-23.06	Peak	HORIZONTAL
6865.00	47.31	35.52	43.58	12.33	51.58	74.00	-22.42	Peak	HORIZONTAL
8021.00	45.73	36.32	43.11	13.96	52.90	74.00	-21.10	Peak	HORIZONTAL
8956.00	46.01	36.80	43.61	14.19	53.39	74.00	-20.61	Peak	HORIZONTAL
9415.00	45.36	37.06	43.83	14.85	53.44	74.00	-20.56	Peak	HORIZONTAL
4655.00	48.82	33.70	44.26	9.92	48.18	74.00	-25.82	Peak	VERTICAL
5828.00	48.40	34.57	44.03	11.42	50.36	74.00	-23.64	Peak	VERTICAL
6899.00	47.45	35.54	43.56	12.32	51.75	74.00	-22.25	Peak	VERTICAL
7885.00	45.94	36.21	43.15	13.75	52.75	74.00	-21.25	Peak	VERTICAL
8990.00	45.25	36.80	43.62	14.33	52.76	74.00	-21.24	Peak	VERTICAL
10027.00	44.81	37.42	44.09	15.56	53.70	74.00	-20.30	Peak	VERTICAL
GFSK Tx mode 2480MHz									
4434.00	47.08	33.51	44.31	9.80	46.08	74.00	-27.92	Peak	HORIZONTAL
5097.00	46.79	33.98	44.18	10.28	46.87	74.00	-27.13	Peak	HORIZONTAL
6168.00	46.50	34.91	43.91	11.97	49.47	74.00	-24.53	Peak	HORIZONTAL
7375.00	46.95	35.83	43.35	12.98	52.41	74.00	-21.59	Peak	HORIZONTAL
8208.00	45.99	36.51	43.22	13.39	52.67	74.00	-21.33	Peak	HORIZONTAL
9313.00	45.58	36.99	43.78	14.65	53.44	74.00	-20.56	Peak	HORIZONTAL
4519.00	48.62	33.61	44.29	9.99	47.93	74.00	-26.07	Peak	VERTICAL
5726.00	47.99	34.49	44.05	11.26	49.69	74.00	-24.31	Peak	VERTICAL
6525.00	47.28	35.32	43.74	11.94	50.80	74.00	-23.20	Peak	VERTICAL
7885.00	44.27	36.21	43.15	13.75	51.08	74.00	-22.92	Peak	VERTICAL
8803.00	44.66	36.80	43.53	14.08	52.01	74.00	-21.99	Peak	VERTICAL
10061.00	44.34	37.44	44.08	15.49	53.19	74.00	-20.81	Peak	VERTICAL
Result: Pass									

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. For emissions above 1GHz. If peak results comply with AV limit, AV Result is deemed to comply with AV limit.

9. RF Conducted Spurious Emissions

9.1. Block diagram of test setup

Same as section 4.1

9.2. Limits

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

9.3. Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Establish a reference level by using the following procedure:

Center frequency	Test frequency
RBW:	100kHz
VBW:	300kHz
Span	Wide enough to capture the peak level of the in-band emission
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.

(4) Set the spectrum analyzer as follows:


RBW:	100kHz
VBW:	300kHz
Span	Encompass frequency range to be measured
Number of measurement points	$\geq \text{span}/\text{RBW}$
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold



(5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band


9.4. Test Result


Mode	Freq. (MHz)	Conclusion
GFSK	2402	PASS
	2440	PASS
	2480	PASS

9.5. Original test data










Date: 28.FEB.2019 11:32:25

BLE ANT1 2480 30~1000




Date: 28.FEB.2019 11:32:33

BLE ANT1 2480 1000~26500



10. Emissions in restricted frequency bands

10.1. Block diagram of test setup



10.2. Limit

All restriction band should comply with 15.209, other emission should be at least 20dB below the fundamental.

10.3. Test Procedure

Same with clause 8.3 except change investigated frequency range from 2310MHz to 2410MHz and 2470MHz to 2500MHz.

Remark: All restriction band have been tested, and only the worst case is shown in report.

10.4. Test result

PASS. (See below detailed test result)

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2018 RE1# Report Data\Q18093005-1E CHARGE4Q\FCC ABOVE1G.EM6

Test Date : 2019-03-11

Tested By : Talent

EUT : Portable Bluetooth Speaker

Model Number : CHARGE4Q

Power Supply : Battery


Test Mode : Tx mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2018 HF 907/3m/HORIZONTAL

Memo : BLE 2402

Data: 51



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2380.90	56.37	29.08	44.17	4.57	45.85	74.00	-28.15	Peak	HORIZONTAL
2	2390.00	54.11	29.10	44.18	4.56	43.59	74.00	-30.41	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2018 RE1# Report Data\Q18093005-1E CHARGE4Q\FCC ABOVE1G.EM6

Test Date : 2019-03-11

Tested By : Talent

EUT : Portable Bluetooth Speaker

Model Number : CHARGE4Q

Power Supply : Battery


Test Mode : Tx mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2018 HF 907/3m/VERTICAL

Memo : BLE 2402

Data: 50



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2375.10	59.52	29.07	44.17	4.57	48.99	74.00	-25.01	Peak	VERTICAL
2	2390.00	57.66	29.10	44.18	4.56	47.14	74.00	-26.86	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2018 RE1# Report Data\Q18093005-1E CHARGE4Q\FCC ABOVE1G.EM6

Test Date : 2019-03-11

Tested By : Talent

EUT : Portable Bluetooth Speaker

Model Number : CHARGE4Q

Power Supply : Battery


Test Mode : Tx mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2018 HF 907/3m/HORIZONTAL

Memo : BLE 2480

Data: 52



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	56.14	29.27	44.21	4.89	46.09	74.00	-27.91	Peak	HORIZONTAL
2	2487.67	59.28	29.28	44.22	4.91	49.25	74.00	-24.75	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2018 RE1# Report Data\Q18093005-1E CHARGE4Q\FCC ABOVE1G.EM6

Test Date : 2019-03-11

Tested By : Talent

EUT : Portable Bluetooth Speaker

Model Number : CHARGE4Q

Power Supply : Battery


Test Mode : Tx mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2018 HF 907/3m/VERTICAL

Memo : BLE 2480

Data: 53



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	61.68	29.27	44.21	4.89	51.63	74.00	-22.37	Peak	VERTICAL
2	2485.63	63.48	29.27	44.21	4.90	53.44	74.00	-20.56	Peak	VERTICAL


Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

11. Power Line Conducted Emission

11.1. Block diagram of test setup



11.2. Power Line Conducted Emission Limits

Frequency	Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

11.3. Test Procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

Configuration EUT to simulate typical usage as described in clause 2.4 and test equipment as described in clause 10.2 of this report.

All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

11.4. Test Result

PASS. (See below detailed test result)


Note1: All emissions not reported below are too low against the prescribed limits.

Note2: “----” means Peak detection; “----” means Average detection

Note3: Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/60Hz, recorded worse case (AC 120V/60Hz).

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room **D:\2018 CE report data\Q18093005-4E\CE.EM6**
Test Date : 2019-02-22 **Tested By** : Aaron
EUT : Portable Bluetooth Speaker **Model Number** : CHARGE4Q
Power Supply : AC 120V/60Hz **Test Mode** : Tx mode
Condition : Temp:24.5°C,Humi:55%,Press:100.1KPa **LISN** : 2018 ENV216/LINE
Memo : Original



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBμV)	Limit Line (dBμV)	Over Limit (dB)	Detector	Phase
1	0.32	16.09	9.63	0.02	9.86	35.60	59.80	-24.20	QP	LINE
2	0.32	8.59	9.63	0.02	9.86	28.10	49.80	-21.70	Average	LINE
3	0.57	22.40	9.64	0.03	9.86	41.93	56.00	-14.07	QP	LINE
4	0.57	11.46	9.64	0.03	9.86	30.99	46.00	-15.01	Average	LINE
5	0.64	20.09	9.64	0.03	9.86	39.62	56.00	-16.38	QP	LINE
6	0.64	8.48	9.64	0.03	9.86	28.01	46.00	-17.99	Average	LINE
7	0.76	18.83	9.64	0.04	9.86	38.37	56.00	-17.63	QP	LINE
8	0.76	5.74	9.64	0.04	9.86	25.28	46.00	-20.72	Average	LINE
9	1.02	16.05	9.64	0.10	9.87	35.66	56.00	-20.34	QP	LINE
10	1.02	2.95	9.64	0.10	9.87	22.56	46.00	-23.44	Average	LINE
11	1.92	14.82	9.65	0.06	9.87	34.40	56.00	-21.60	QP	LINE
12	1.92	0.83	9.65	0.06	9.87	20.41	46.00	-25.59	Average	LINE

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.


2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).

4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room **D:\2018 CE report data\Q18093005-4E\CE.EM6**
Test Date : 2019-02-22 **Tested By** : Aaron
EUT : Portable Bluetooth Speaker **Model Number** : CHARGE4Q
Power Supply : AC 120V/60Hz **Test Mode** : Tx mode
Condition : Temp:24.5°C,Humi:55%,Press:100.1KPa **LISN** : 2018 ENV216/NEUTRAL
Memo : Original



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBμV)	Limit Line (dBμV)	Over Limit (dB)	Detector	Phase
1	0.19	21.36	9.64	0.02	9.86	40.88	63.98	-23.10	QP	NEUTRAL
2	0.19	9.27	9.64	0.02	9.86	28.79	53.98	-25.19	Average	NEUTRAL
3	0.25	17.29	9.64	0.02	9.86	36.81	61.64	-24.83	QP	NEUTRAL
4	0.25	5.93	9.64	0.02	9.86	25.45	51.64	-26.19	Average	NEUTRAL
5	0.32	14.67	9.64	0.02	9.86	34.19	59.80	-25.61	QP	NEUTRAL
6	0.32	3.20	9.64	0.02	9.86	22.72	49.80	-27.08	Average	NEUTRAL
7	0.57	14.82	9.64	0.03	9.86	34.35	56.00	-21.65	QP	NEUTRAL
8	0.57	5.42	9.64	0.03	9.86	24.95	46.00	-21.05	Average	NEUTRAL
9	0.76	12.12	9.64	0.04	9.86	31.66	56.00	-24.34	QP	NEUTRAL
10	0.76	0.67	9.64	0.04	9.86	20.21	46.00	-25.79	Average	NEUTRAL
11	1.52	9.06	9.66	0.07	9.87	28.66	56.00	-27.34	QP	NEUTRAL
12	1.52	-1.60	9.66	0.07	9.87	18.00	46.00	-28.00	Average	NEUTRAL

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.


2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).

4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room **D:\2018 CE report data\Q18093005-1E\CE.EM6**
Test Date : 2019-01-30 **Tested By** : David
EUT : Portable Bluetooth Speaker **Model Number** : CHARGE4Q
Power Supply : AC 120V/60Hz **Test Mode** : Tx mode
Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa **LISN** : 2018 ENV216/NEUTRAL
Memo : Original



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBμV)	Limit Line (dBμV)	Over Limit (dB)	Detector	Phase
1	0.19	18.89	9.64	0.02	9.86	38.41	63.93	-25.52	QP	NEUTRAL
2	0.19	7.57	9.64	0.02	9.86	27.09	53.93	-26.84	Average	NEUTRAL
3	0.25	15.59	9.64	0.02	9.86	35.11	61.64	-26.53	QP	NEUTRAL
4	0.25	5.16	9.64	0.02	9.86	24.68	51.64	-26.96	Average	NEUTRAL
5	0.57	14.93	9.64	0.03	9.86	34.46	56.00	-21.54	QP	NEUTRAL
6	0.57	6.48	9.64	0.03	9.86	26.01	46.00	-19.99	Average	NEUTRAL
7	0.64	13.97	9.64	0.03	9.86	33.50	56.00	-22.50	QP	NEUTRAL
8	0.64	3.87	9.64	0.03	9.86	23.40	46.00	-22.60	Average	NEUTRAL
9	0.76	12.17	9.64	0.04	9.86	31.71	56.00	-24.29	QP	NEUTRAL
10	0.76	2.63	9.64	0.04	9.86	22.17	46.00	-23.83	Average	NEUTRAL
11	8.41	9.38	9.78	0.04	9.90	29.10	60.00	-30.90	QP	NEUTRAL
12	8.41	0.03	9.78	0.04	9.90	19.75	50.00	-30.25	Average	NEUTRAL

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.


2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).

4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room **D:\2018 CE report data\Q18093005-1E\CE.EM6**
Test Date : 2019-01-30 **Tested By** : David
EUT : Portable Bluetooth Speaker **Model Number** : CHARGE4Q
Power Supply : AC 120V/60Hz **Test Mode** : Tx mode
Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa **LISN** : 2018 ENV216/LINE
Memo : Original




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBμV)	Limit Line (dBμV)	Over Limit (dB)	Detector	Phase
1	0.31	16.82	9.63	0.02	9.86	36.33	59.84	-23.51	QP	LINE
2	0.31	9.14	9.63	0.02	9.86	28.65	49.84	-21.19	Average	LINE
3	0.58	23.05	9.64	0.03	9.86	42.58	56.00	-13.42	QP	LINE
4	0.58	10.43	9.64	0.03	9.86	29.96	46.00	-16.04	Average	LINE
5	0.64	21.85	9.64	0.03	9.86	41.38	56.00	-14.62	QP	LINE
6	0.64	8.22	9.64	0.03	9.86	27.75	46.00	-18.25	Average	LINE
7	0.75	19.69	9.64	0.04	9.86	39.23	56.00	-16.77	QP	LINE
8	0.75	2.30	9.64	0.04	9.86	21.84	46.00	-24.16	Average	LINE
9	1.12	18.01	9.64	0.09	9.87	37.61	56.00	-18.39	QP	LINE
10	1.12	3.37	9.64	0.09	9.87	22.97	46.00	-23.03	Average	LINE
11	1.96	16.86	9.65	0.06	9.87	36.44	56.00	-19.56	QP	LINE
12	1.96	1.40	9.65	0.06	9.87	20.98	46.00	-25.02	Average	LINE

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.
 2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
 4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

: DDT 1# Shield Room
 : 2019-05-09
 : Portable Bluetooth Speaker
 : AC 120V/60Hz
 : Temp:24.5°C,Humi:71.2%,Press:101.4kPa
 : New Battery: IY1068

D:\2019 CE report data\Q19043005-1E Charge 4Q\CE.EM6
 Tested By : JACKY
 Model Number : CHARGE4Q
 Test Mode : Tx mode
 : 2018 ENV216/LINE



Item	Freq.	Read Level	LISN Factor	Cable Loss	Pulse Limiter Factor	Result Level	Limit Line	Over Limit	Detector	Phase
(Mark)	(MHz)	(dBμV)	(dB)	(dB)	(dB)	(dBμV)	(dBμV)	(dB)		
1	0.20	27.88	9.63	0.02	9.86	47.39	63.71	-16.32	QP	LINE
2	0.20	21.92	9.63	0.02	9.86	41.43	53.71	-12.28	Average	LINE
3	0.32	25.14	9.63	0.02	9.86	44.65	59.62	-14.97	QP	LINE
4	0.32	19.32	9.63	0.02	9.86	38.83	49.62	-10.79	Average	LINE
5	0.46	29.47	9.64	0.02	9.86	48.99	56.76	-7.77	QP	LINE
6	0.46	24.07	9.64	0.02	9.86	43.59	46.76	-3.17	Average	LINE
7	0.98	27.00	9.64	0.10	9.87	46.61	56.00	-9.39	QP	LINE
8	0.98	21.10	9.64	0.10	9.87	40.71	46.00	-5.29	Average	LINE
9	1.43	26.85	9.65	0.08	9.87	46.45	56.00	-9.55	QP	LINE
10	1.43	20.48	9.65	0.08	9.87	40.08	46.00	-5.92	Average	LINE
11	1.73	24.29	9.65	0.06	9.87	43.87	56.00	-12.13	QP	LINE
12	1.73	17.98	9.65	0.06	9.87	37.56	46.00	-8.44	Average	LINE

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.


2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).

4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

: DDT 1# Shield Room
 D:\2019 CE report data\Q19043005-1E Charge 4Q\CE.EM6
Test Date : 2019-05-09 **Tested By** : JACKY
EUT : Portable Bluetooth Speaker **Model Number** : CHARGE4Q
Power Supply : AC 120V/60Hz **Test Mode** : Tx mode
Condition : Temp:24.5°C,Humi:71.2%,Press:101.4kPa **LISN** : 2018 ENV216/NEUTRAL
Memo : New Battery: IY1068



Item	Freq.	Read Level	LISN Factor	Cable Loss	Pulse Limiter Factor	Result Level	Limit Line	Over Limit	Detector	Phase
(Mark)	(MHz)	(dBμV)	(dB)	(dB)	(dB)	(dBμV)	(dBμV)	(dB)		
1	0.19	23.65	9.64	0.02	9.86	43.17	63.93	-20.76	QP	NEUTRAL
2	0.19	18.00	9.64	0.02	9.86	37.52	53.93	-16.41	Average	NEUTRAL
3	0.46	24.96	9.64	0.02	9.86	44.48	56.76	-12.28	QP	NEUTRAL
4	0.46	19.22	9.64	0.02	9.86	38.74	46.76	-8.02	Average	NEUTRAL
5	0.52	23.85	9.64	0.02	9.86	43.37	56.00	-12.63	QP	NEUTRAL
6	0.52	17.43	9.64	0.02	9.86	36.95	46.00	-9.05	Average	NEUTRAL
7	0.78	23.08	9.64	0.05	9.86	42.63	56.00	-13.37	QP	NEUTRAL
8	0.78	17.04	9.64	0.05	9.86	36.59	46.00	-9.41	Average	NEUTRAL
9	1.04	24.06	9.64	0.10	9.87	43.67	56.00	-12.33	QP	NEUTRAL
10	1.04	17.77	9.64	0.10	9.87	37.38	46.00	-8.62	Average	NEUTRAL
11	1.69	23.11	9.66	0.07	9.87	42.71	56.00	-13.29	QP	NEUTRAL
12	1.69	17.12	9.66	0.07	9.87	36.72	46.00	-9.28	Average	NEUTRAL

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.


2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).

4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room **D:\2019 CE report data\Q19103117-1E\20191211 CE.EM6**
Test Date : 2019-12-12 **Tested By** : Huang
EUT : Portable Bluetooth Speaker **Model Number** : CHARGE4Q
Power Supply : AC 120V/60Hz **Test Mode** : Tx mode
Condition : Temp:24.5°C,Humi:55%,Press:101.4KPa **LISN** : 2018 ENV216/NEUTRAL
Memo : New Battery: IAA011NA



Item	Freq.	Read Level	LISN Factor	Cable Loss	Pulse Limiter Factor	Result Level	Limit Line	Over Limit	Detector	Phase
(Mark)	(MHz)	(dBμV)	(dB)	(dB)	(dB)	(dBμV)	(dBμV)	(dB)		
1	0.41	17.84	9.64	0.02	9.86	37.36	57.59	-20.23	QP	NEUTRAL
2	0.41	6.75	9.64	0.02	9.86	26.27	47.59	-21.32	Average	NEUTRAL
3	0.48	19.48	9.64	0.02	9.86	39.00	56.27	-17.27	QP	NEUTRAL
4	0.48	6.84	9.64	0.02	9.86	26.36	46.27	-19.91	Average	NEUTRAL
5	0.55	20.20	9.64	0.02	9.86	39.72	56.00	-16.28	QP	NEUTRAL
6	0.55	7.74	9.64	0.02	9.86	27.26	46.00	-18.74	Average	NEUTRAL
7	1.51	16.10	9.66	0.07	9.87	35.70	56.00	-20.30	QP	NEUTRAL
8	1.51	2.50	9.66	0.07	9.87	22.10	46.00	-23.90	Average	NEUTRAL
9	3.22	12.90	9.68	0.04	9.87	32.49	56.00	-23.51	QP	NEUTRAL
10	3.22	3.42	9.68	0.04	9.87	23.01	46.00	-22.99	Average	NEUTRAL
11	9.50	16.60	9.80	0.10	9.90	36.40	60.00	-23.60	QP	NEUTRAL
12	9.50	10.80	9.80	0.10	9.90	30.60	50.00	-19.40	Average	NEUTRAL

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.


2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).

4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room **D:\2019 CE report data\Q19103117-1E\20191211 CE.EM6**
Test Date : 2019-12-12 **Tested By** : Huang
EUT : Portable Bluetooth Speaker **Model Number** : CHARGE4Q
Power Supply : AC 120V/60Hz **Test Mode** : Tx mode
Condition : Temp:24.5°C,Humi:55%,Press:101.4KPa **LISN** : 2018 ENV216/LINE
Memo : New Battery: IAA011NA



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBμV)	Limit Line (dBμV)	Over Limit (dB)	Detector	Phase
1	0.34	24.36	9.63	0.02	9.86	43.87	59.09	-15.22	QP	LINE
2	0.34	15.67	9.63	0.02	9.86	35.18	49.09	-13.91	Average	LINE
3	0.41	23.72	9.64	0.02	9.86	43.24	57.59	-14.35	QP	LINE
4	0.41	14.04	9.64	0.02	9.86	33.56	47.59	-14.03	Average	LINE
5	0.48	25.38	9.64	0.02	9.86	44.90	56.36	-11.46	QP	LINE
6	0.48	14.23	9.64	0.02	9.86	33.75	46.36	-12.61	Average	LINE
7	0.55	25.86	9.64	0.02	9.86	45.38	56.00	-10.62	QP	LINE
8	0.55	14.27	9.64	0.02	9.86	33.79	46.00	-12.21	Average	LINE
9	1.30	23.31	9.64	0.08	9.87	42.90	56.00	-13.10	QP	LINE
10	1.30	8.38	9.64	0.08	9.87	27.97	46.00	-18.03	Average	LINE
11	2.36	21.56	9.66	0.05	9.87	41.14	56.00	-14.86	QP	LINE
12	2.36	8.50	9.66	0.05	9.87	28.08	46.00	-17.92	Average	LINE

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.


2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).

4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room **D:\2019 CE report data\Q19043005-4E CHARGE 4Q\CE.EM6**
Test Date : 2019-05-09 **Tested By** : JACKY
EUT : Portable Bluetooth Speaker **Model Number** : CHARGE4Q
Power Supply : AC 120V/60Hz **Test Mode** : Tx mode
Condition : Temp:24.5°C,Humi:71.2%,Press:101.4kPa **LISN** : 2018 ENV216/NEUTRAL
Memo : New Battery: SUN-INTE-156



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBμV)	Limit Line (dBμV)	Over Limit (dB)	Detector	Phase
1	0.20	28.75	9.64	0.02	9.86	48.27	63.76	-15.49	QP	LINE
2	0.20	19.85	9.64	0.02	9.86	39.37	53.76	-14.39	Average	LINE
3	0.26	25.12	9.64	0.02	9.86	44.64	61.38	-16.74	QP	LINE
4	0.26	17.56	9.64	0.02	9.86	37.08	51.38	-14.30	Average	LINE
5	0.46	22.21	9.64	0.02	9.86	41.73	56.67	-14.94	QP	LINE
6	0.46	16.81	9.64	0.02	9.86	36.33	46.67	-10.34	Average	LINE
7	0.52	24.44	9.64	0.02	9.86	43.96	56.00	-12.04	QP	LINE
8	0.52	17.64	9.64	0.02	9.86	37.16	46.00	-8.84	Average	LINE
9	1.64	24.76	9.66	0.07	9.87	44.36	56.00	-11.64	QP	LINE
10	1.64	17.83	9.66	0.07	9.87	37.43	46.00	-8.57	Average	LINE
11	2.14	23.54	9.67	0.05	9.87	43.13	56.00	-12.87	QP	LINE
12	2.14	14.57	9.67	0.05	9.87	34.16	46.00	-11.84	Average	LINE

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.


2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).

4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room **D:\2019 CE report data\Q19043005-4E CHARGE 4Q\CE.EM6**
Test Date : 2019-05-09 **Tested By** : JACKY
EUT : Portable Bluetooth Speaker **Model Number** : CHARGE4Q
Power Supply : AC 120V/60Hz **Test Mode** : Tx mode
Condition : Temp:24.5°C,Humi:71.2%,Press:101.4kPa **LISN** : 2018 ENV216/LINE
Memo : New Battery: SUN-INTE-156



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBμV)	Limit Line (dBμV)	Over Limit (dB)	Detector	Phase
1	0.20	28.92	9.63	0.02	9.86	48.43	63.76	-15.33	QP	LINE
2	0.20	22.07	9.63	0.02	9.86	41.58	53.76	-12.18	Average	LINE
3	0.39	24.74	9.64	0.02	9.86	44.26	58.03	-13.77	QP	LINE
4	0.39	17.89	9.64	0.02	9.86	37.41	48.03	-10.62	Average	LINE
5	0.46	28.76	9.64	0.02	9.86	48.28	56.71	-8.43	QP	LINE
6	0.46	23.34	9.64	0.02	9.86	42.86	46.71	-3.85	Average	LINE
7	0.65	26.81	9.64	0.03	9.86	46.34	56.00	-9.66	QP	LINE
8	0.65	21.06	9.64	0.03	9.86	40.59	46.00	-5.41	Average	LINE
9	1.24	26.17	9.64	0.09	9.87	45.77	56.00	-10.23	QP	LINE
10	1.24	20.08	9.64	0.09	9.87	39.68	46.00	-6.32	Average	LINE
11	1.74	25.06	9.65	0.06	9.87	44.64	56.00	-11.36	QP	LINE
12	1.74	17.95	9.65	0.06	9.87	37.53	46.00	-8.47	Average	LINE

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.


2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).

4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room **D:\2019 CE report data\Q19103117-4E\20191211 CE.EM6**
Test Date : 2019-12-12 **Tested By** : Huang
EUT : Portable Bluetooth Speaker **Model Number** : CHARGE4Q
Power Supply : AC 120V/60Hz **Test Mode** : Tx mode
Condition : Temp:24.5°C,Humi:55%,Press:101.4KPa **LISN** : 2018 ENV216/LINE
Memo : New Battery: GSP-1S3P-CH4A



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBμV)	Limit Line (dBμV)	Over Limit (dB)	Detector	Phase
1	0.19	23.76	9.63	0.02	9.86	43.27	64.20	-20.93	QP	LINE
2	0.19	13.77	9.63	0.02	9.86	33.28	54.20	-20.92	Average	LINE
3	0.25	21.26	9.63	0.02	9.86	40.77	61.91	-21.14	QP	LINE
4	0.25	9.55	9.63	0.02	9.86	29.06	51.91	-22.85	Average	LINE
5	0.31	18.93	9.63	0.02	9.86	38.44	59.97	-21.53	QP	LINE
6	0.31	9.39	9.63	0.02	9.86	28.90	49.97	-21.07	Average	LINE
7	0.56	22.01	9.64	0.03	9.86	41.54	56.00	-14.46	QP	LINE
8	0.56	10.42	9.64	0.03	9.86	29.95	46.00	-16.05	Average	LINE
9	1.11	15.84	9.64	0.09	9.87	35.44	56.00	-20.56	QP	LINE
10	1.11	3.05	9.64	0.09	9.87	22.65	46.00	-23.35	Average	LINE
11	3.16	15.74	9.67	0.04	9.87	35.32	56.00	-20.68	QP	LINE
12	3.16	3.07	9.67	0.04	9.87	22.65	46.00	-23.35	Average	LINE

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.


2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).

4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room **D:\2019 CE report data\Q19103117-4E\20191211 CE.EM6**
Test Date : 2019-12-12 **Tested By** : Huang
EUT : Portable Bluetooth Speaker **Model Number** : CHARGE4Q
Power Supply : AC 120V/60Hz **Test Mode** : Tx mode
Condition : Temp:24.5°C,Humi:55%,Press:101.4KPa **LISN** : 2018 ENV216/NEUTRAL
Memo : New Battery: GSP-1S3P-CH4A



Item	Freq.	Read Level	LISN Factor	Cable Loss	Pulse Limiter Factor	Result Level	Limit Line	Over Limit	Detector	Phase
(Mark)	(MHz)	(dBμV)	(dB)	(dB)	(dB)	(dBμV)	(dBμV)	(dB)		
1	0.19	23.37	9.64	0.02	9.86	42.89	64.20	-21.31	QP	NEUTRAL
2	0.19	10.89	9.64	0.02	9.86	30.41	54.20	-23.79	Average	NEUTRAL
3	0.25	20.91	9.64	0.02	9.86	40.43	61.86	-21.43	QP	NEUTRAL
4	0.25	7.30	9.64	0.02	9.86	26.82	51.86	-25.04	Average	NEUTRAL
5	0.31	17.59	9.64	0.02	9.86	37.11	59.93	-22.82	QP	NEUTRAL
6	0.31	4.51	9.64	0.02	9.86	24.03	49.93	-25.90	Average	NEUTRAL
7	0.56	15.70	9.64	0.03	9.86	35.23	56.00	-20.77	QP	NEUTRAL
8	0.56	1.71	9.64	0.03	9.86	21.24	46.00	-24.76	Average	NEUTRAL
9	3.66	11.96	9.69	0.05	9.87	31.57	56.00	-24.43	QP	NEUTRAL
10	3.66	3.03	9.69	0.05	9.87	22.64	46.00	-23.36	Average	NEUTRAL
11	9.45	14.88	9.80	0.09	9.90	34.67	60.00	-25.33	QP	NEUTRAL
12	9.45	7.23	9.80	0.09	9.90	27.02	50.00	-22.98	Average	NEUTRAL

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).

4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

12. Antenna Requirements

12.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

12.2. Result

The antennas used for this product is integrated antenna and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is only 2.24 dBi.

END OF REPORT