

RF Exposure Compliance Requirement

1. Standard requirement

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

(a) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S)(mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100000			5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S)(mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/500	30
1500-100000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

2. MPE Calculation Method

$$S (\text{mW/cm}^2) = P \cdot G / 4\pi R^2$$

S= Power Density (mW/cm^2)

P=Peak RF conducted output Power (mW)

G=EUT Antenna numeric gain (numeric)

R= Separation distance between radiator and human body (cm);

From the peak EUT RF output power, the minimum mobile separation distance, d=20cm, as well as the gain of the used antenna, the RF power density can be obtained.

3. Calculated Result and Limit

802.11b mode:

Frequency (MHz)	Antenna Gain (Numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm^2)	Limit of Power Density (S) (mW/cm^2)	Test Result
2412	2.19	21.08	128.2	0.056	1	Complies
2437	2.19	21.44	139.3	0.060	1	Complies
2462	2.19	21.39	137.7	0.060	1	Complies

802.11g mode:

Frequency (MHz)	Antenna Gain (Numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm^2)	Limit of Power Density (S) (mW/cm^2)	Test Result
2412	2.19	23.41	219.3	0.095	1	Complies
2437	2.19	23.99	250.6	0.109	1	Complies
2462	2.19	24.34	271.6	0.118	1	Complies