



Compliance Testing, LLC

Previously Flom Test Lab

EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268

fax: (480) 926-3598

<http://www.ComplianceTesting.com>

info@ComplianceTesting.com

Test Report

Prepared for: CalAmp

Model: LMU30G60BL

Description:

The LMU-3050 is a full-featured tracking unit with, OBD-II interface, backup battery, and a 3-axis accelerometer.

These features enable the LMU-3050 to access vehicle diagnostic interface data, track vehicle speed and location, plus detect hard braking, cornering, acceleration, crash detection and capture pre and post-impact data.

Serial Number: 359316074408946

FCC ID: APV-3050GBL

IC: 5843C-3050GBL

To

FCC Part 15.247 DTS

And

IC RSS-247

Date of Issue: August 11, 2017

On the behalf of the applicant:

CalAmp
2177 Salk Avenue
Suite 200
Carlsbad, CA 92008

Attention of:

Imad Rizk, Compliance Manager
Ph: (626)353-5140
E-mail: irizk@calamp.com

Prepared By
Compliance Testing, LLC
1724 S. Nevada Way
Mesa, AZ 85204
(480) 926-3100 phone / (480) 926-3598 fax
www.compliancetesting.com
Project No: p1640020

Kenneth Lee
Project Test Engineer

This report may not be reproduced, except in full, without written permission from Compliance Testing.
All results contained herein relate only to the sample tested.



Test Report Revision History

Revision	Date	Revised By	Reason for Revision
1.0	May 14, 2016	Kenneth Lee	Original Document
2.0	August 9, 2017	Kenneth Lee	Updated referenced paragraph for Conducted Spurious testing in the Test Summary Table Removed Conducted Emissions from report



Table of Contents

<u>Description</u>	<u>Page</u>
Standard Test Conditions Engineering Practices	6
Peak Output Power	9
Radiated Spurious Emissions	10
Emissions at Band Edges	11
Occupied Bandwidth	15
Transmitter Power Spectral Density (PSD)	18
Receiver Spurious Emissions	20
Test Equipment Utilized	23



ILAC / A2LA

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to the joint ISO-ILAC-IAF Communiqué dated January 2009).

The tests results contained within this test report all fall within our scope of accreditation, unless noted below.

Please refer to <http://www.compliancetesting.com/labscope.html> for current scope of accreditation.

Testing Certificate Number: **2152.01**



FCC Site Reg. #349717

IC Site Reg. #2044A-2

Non-accredited tests contained in this report:

N/A

The applicant has been cautioned as to the following

15.21 - Information to User

The user's manual or instruction manual for an intentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

15.27(a) - Special Accessories

Equipment marked to a consumer must be capable of complying with the necessary regulations in the configuration in which the equipment is marketed. Where special accessories, such as shielded cables and/or special connectors are required to enable an unintentional or intentional radiator to comply with the emission limits in this part, the equipment must be marketed with, i.e. shipped and sold with, those special accessories. However, in lieu of shipping or packaging the special accessories with the unintentional or intentional radiator, the responsible party may employ other methods of ensuring that the special accessories are provided to the consumer without an additional charge.

Information detailing any alternative method used to supply the special accessories for a grant of equipment authorization or retained in the verification records, as appropriate. The party responsible for the equipment, as detailed in § 2.909 of this chapter, shall ensure that these special accessories are provided with the equipment. The instruction manual for such devices shall include appropriate instructions on the first page of text concerned with the installation of the device that these special accessories must be used with the device. It is the responsibility of the user to use the needed special accessories supplied with the equipment.



Standard Test Conditions Engineering Practices

Except as noted herein, the following conditions and procedures were observed during the testing:

In accordance with ANSI C63.10-2009 and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40°C (50° to 104°F) unless the particular equipment requirements specified testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10% to 90% relative humidity.

Measurement results, unless otherwise noted, are worst-case measurements.

Environmental Conditions		
Temperature (°C)	Humidity (%)	Pressure (mbar)
24.6	31.8	941.7

EUT Description

Model: LMU30G60BL

Description: The LMU-3050 is a full-featured tracking unit with, OBD-II interface, backup battery, and a 3-axis accelerometer. These features enable the LMU-3050 to access vehicle diagnostic interface data, track vehicle speed and location, plus detect hard braking, cornering, acceleration, crash detection and capture pre and post-impact data.

Firmware: Device Firmware 195-5.0j / BLE Firmware BLE-SPP-10e

Software: N/A

Serial Number: 359316074408946

Additional Information: None

EUT Operation during Tests

The EUT was operating normally during testing



Accessories: None

Cables:

Qty	Description	Length (M)	Shielding Y/N	Shielded Hood Y/N	Ferrite Y/N
1	USB to D9	0.3	Y	Y	N

Modifications: None

15.203: Antenna Requirement:

- ☒ The antenna is permanently attached to the EUT
- ☐ The antenna uses a unique coupling
- ☐ The EUT must be professionally installed
- ☐ The antenna requirement does not apply



Test Results Summary

Specification	Test Name	Pass, Fail, N/A	Comments
15.247(b)	Peak Output Power	Pass	
15.247(d)	Conducted Spurious Emissions	Pass	
15.247(d), 15.209(a), 15.205	Radiated Spurious Emissions	Pass	
15.247(d), 15.209(a), 15.205	Emissions At Band Edges	Pass	
15.247(a)(2)	Occupied Bandwidth	Pass	
15.247(e)	Transmitter Power Spectral Density	Pass	
15.207	A/C Powerline Conducted Emissions	N/A	EUT is a DC powered device
RSS-Gen §7	Receiver Spurious Emission Limits	Pass	



Peak Output Power


Engineer: Kenneth Lee

Test Date: 05/14/2016

Test Procedure

The EUT was tested in a semi- anechoic chamber at a distance of 3 meters from the receiving antenna. A spectrum analyzer was used to verify that the EUT met the requirements for Peak Output Power. The antenna correction and distance correction factors were summed with the measurement to ensure correct readings.

Test Setup



Transmitter Peak Output Power

Tuned Frequency (MHz)	Measured Value (dBm)	Specification Limit	Result
2402	-24.44	1 W (30 dBm)	Pass
2442	-29.03	1 W (30 dBm)	Pass
2480	-28.71	1 W (30 dBm)	Pass



Radiated Spurious Emissions

Engineer: Kenneth Lee

Test Date: 05/14/2016

Test Procedure Radiated Spurious Emissions: 30 – 1000 MHz

The EUT was tested in a semi-anechoic test chamber set 3m from the receiving antenna. A spectrum analyzer was used to verify that the EUT met the requirements for Radiated Emissions. The EUT was tested by rotating it 360° with the antennas in both the vertical and horizontal orientation and was raised from 1 to 4 meters to ensure the TX signal levels were maximized.

All emissions from 30 MHz to 1 GHz were examined.

Measured Level includes antenna and receiver cable correction factors.


Correction factors were input into the spectrum analyzer before recording “Measured Level”.

RBW = 100 KHz

VBW = 300 KHz

Detector – Quasi Peak


Test Setup



Test Procedure for Radiated Spurious Emissions above 1 GHz

The EUT was tested in a semi anechoic chamber set 3m from the receiving antenna. A spectrum analyzer was used to verify that the EUT met the requirements for Radiated Spurious Emissions. The antenna, band reject filter, amplifier and cable correction factors were input into the spectrum analyzer before recording the Measured Level to ensure accurate readings. The spectrum for each tuned frequency was examined to the 10th harmonic.

Test Setup



Detector Settings	RBW (MHz)	VBW (MHz)	Span
Peak	1	3	As Necessary
Average	1	3	As Necessary

See Annex A for test data



Emissions at Band Edges


Engineer: Kenneth Lee

Test Date: 05/14/2016

Test Procedure


The EUT was tested in a semi-anechoic chamber set 3m from the receiving antenna. A spectrum analyzer was used to verify that the EUT met the requirements for band edge and restricted band for both peak and average measurements. The cable and antenna correction factors were input into the analyzer as a reference level offset to ensure accurate readings. For the restricted band the amplifier and band reject filter correction factors were also input to the spectrum analyzer.

Band Edge Test Setup






Band Edge 2400 MHz
Tuned Freq = 2402 MHz




Band Edge 2483.5 MHz
Tuned Freq = 2480 MHz






Restricted Band 2300 – 2390 MHz – Peak
Tuned Freq = 2400 MHz




Restricted Band 2300 – 2390 MHz – Avg
Tuned Freq = 2400 MHz





Restricted Band 2483.5 – 2500 MHz – Peak
Tuned Freq = 2480 MHz





Occupied Bandwidth

Engineer: Kenneth Lee

Test Date: 05/14/2016

Test Procedure

The EUT was tested in a semi-anechoic chamber at a distance of 3 meters from the receiving antenna. The Span was set wide enough to capture the entire transmit spectrum and the resolution bandwidth was set to at least 1% of the span. The analyzer was set to max hold while the 6dB and 99% bandwidths were measured.

Test Setup



6 dB Occupied Bandwidth Summary


Frequency (MHz)	Measured Bandwidth (MHz)	Specification Limit (kHz)	Result
2402	685.292	≥ 500	Pass
2442	691.57	≥ 500	Pass
2480	689.898	≥ 500	Pass

99% Bandwidth Summary


Frequency (MHz)	Measured Bandwidth (MHz)	Result
2402	1.0934	Pass
2442	1.0825	Pass
2480	1.0844	Pass



6dB and 99% Bandwidths – Low Channel




6dB and 99% Bandwidths – Middle Channel





6dB and 99% Bandwidths – High Channel





Transmitter Power Spectral Density (PSD)


Engineer: Kenneth Lee

Test Date: 05/14/2016

Test Procedure

The EUT was tested in a semi-anechoic chamber at a distance of 3 meters from the receiving antenna. The test was performed per section 6.11.2.3 of C63.10 - 2009 "Procedure for determining PSD for DTS devices".


Test Setup



PSD Summary


Frequency (MHz)	Measured Data (dBm)	Specification Limit (dBm)	Result
2402	-24.43	8	Pass
2442	-29.58	8	Pass
2480	-29.59	8	Pass

PSD 2402 MHz






PSD 2442 MHz



PSD 2480 MHz





Receiver Spurious Emissions


Engineer: Kenneth Lee

Test Date: 05/14/2016

Test Procedure


The EUT was tested in a semi-anechoic chamber at a distance of 3 meters from the receiving antenna. The receiver spurious emissions were measured from 30 MHz to greater than 3 times the highest tunable frequency.

Test Setup




Receiver Spurious Emissions Summary

Receiver Spurious Emissions – 25-1000 MHz – Vertical






Receiver Spurious Emissions – 25-1000 MHz – Horizontal




Receiver Spurious Emissions – 1-18 GHz – Vertical





Receiver Spurious Emissions – 1-18 GHz – Horizontal





Test Equipment Utilized

Description	Manufacturer	Model #	CT Asset #	Last Cal Date	Cal Due Date
Horn Antenna, Amplified	ARA	DRG-118/A	i00271	5/8/14	5/8/16*
Horn Antenna, Amplified	ARA	MWH-1826/B	i00273	4/22/15	4/22/18
Spectrum Analyzer	Agilent	E4407B	i00331	9/18/15	9/18/16
Horn Antenna	EMCO	3115	i00103	1/20/15	1/20/17
Bi-Log Antenna	Schaffner	CBL 6111D	i00349	10/19/15	10/19/17
EMI Analyzer	Agilent	E7405A	i00379	2/11/16	2/11/17
3 Meter Semi-Anechoic Chamber	Panashield	3 Meter Semi-Anechoic Chamber	i00428	7/27/14	7/27/16
PSA Spectrum Analyzer	Agilent	E4445A	i00471	8/26/15	8/26/16

* 30 day calibration extension per lab manager

In addition to the above listed equipment standard RF connectors and cables were utilized in the testing of the described equipment. Prior to testing these components were tested to verify proper operation.

END OF TEST REPORT