************ INFORMATION FOR CERTIFICATION (1) **********

APPLICANT:

Name : <u>Sharp Corporation, Reliability Control Group</u>

Address <u>22-22 Nagaike-Cho, Abeno-Ku</u>

Osaka 545-8522, Japan

Grantee Code: : <u>APY</u>
Applicant Rep. : <u>K. Aoyagi</u>

CONTACT PERSON:

Name : <u>Sharp Electronics Corporation</u>

Address : <u>Sharp Plaza, Mahwah, New Jersey 07430</u> Applicant Rep. : <u>Steve Petruska, Product Safety Dept.</u>

Telephone No. : <u>201-529-9299</u>

MEASUREMENT SITE:

Name : <u>Japan Quality Assurance Organization</u>

Kita-Kansai Testing Center, EMC Division

Address : <u>7-1 Ishimaru 1-Chome</u>

Minoh-shi, Osaka 562, Japan

MANUFACTURER:

Name : <u>Sharp Appliances (Thailand) Ltd.</u>

Address : <u>64 Moo 5, Tambol Bangsamuk Amphur Bangpakong</u>

Chachoengsao Province, Thailand

FCC IDENTIFICATION : <u>APYDMR0113</u>

EQUIPMENT : <u>Microwave Oven Model KSA-8574A</u>

Brand : Montgomery Ward (Admiral Brand)

Importer : Montgomery Ward & Co.

******* INFORMATION FOR CERTIFICATION (2) ********

(1) Type(s) of emission: Not Applicable

(2) Frequency range: 2450 MHz

(3) Range of operating power and description of means provided for variation of operating power:

RF output power 1100 W (Average power output is controlled by ON/OFF switching cycles.)

(4) Max. power rating as described in the applicable rules:

1100 W (Measured by IEC705-1988 measurement method.)

(5) The voltage and current to magnetron:

For Magnetron Cat. No. 2M253H(L) : 3.8 kV peak, 350 mA (rms)

(6) Function of each electro tube, semiconductor or other active circuit device:

Fixed Magnetron, Type 2M253H(L) as power generator

- (7) Complete circuit diagram: Same as that of previously reported model.
- (8) Instruction book: Similar to the previously reported base model.
- (9) Tune up procedure over the power range or at specific operating power levels: Not adjustable
- (10) A description of all circuitry and devices provided for determining and stabilizing frequency:

Fixed by magnetron and oven design

(11) A description of any circuit or devices employed for suppression of spurious radiation, for limiting modulation, and for limiting the operating power:

Suppression obtained by shielding design

(12) Identification plate or label: <u>Same as that of previously reported base model.</u>
Location of identification plate or label: <u>Same as that of previously reported base model.</u>

********** INFORMATION FOR CERTIFICATION (3) *********

DESCRIPTION OF THE MICROWAVE OVEN

Unit Body Dimensions : <u>550 mm wide, 315 mm high, 442 mm deep</u>

(include feet)

Door Dimensions : <u>448 mm wide, 293 mm high</u>

(Viewing Area: 298 mm wide, 151 mm)

Oven Cavity Dimensions : <u>378 mm wide, 243 mm high, 425 mm deep</u>

(without tray)

Feed Type and Location : <u>Supplied by waveguide located side of oven</u>

Door Seal Type : <u>Choke and Capacitive Seals</u>

Magnetron Type : <u>2M253H(L), mfd by Toshiba</u>