

TOSHIBA

TOSHIBA HOKUTO ELECTRONICS CORPORATION

MAGNETRON ENGINEERING GROUP

1975, 23-CHOME MINAMI 5-JODORI, ASAHIKAWA, HOKKAIDO 078-8335, JAPAN

PHONE : (0185) 31-4728 FACSIMILE : (0185) 31-4739

Sharp Manufacturing Company of America

October 12, 2001
(Ref. No. : 01-097)

RE : Electromagnetic radiation from microwave oven R-1200 with Toshiba magnetron 2M253H(L)


Dear sir

We are enclosing herewith the above mentioned test results based on FCC measuring method in our measuring facility of FCC file number 430A.

We confirmed test results are satisfied with FCC limit.

Please feel free to contact us, if you have any question or request.

Sincerely yours,



Toshiki Azuma
Manager
Magnetron Engineering Group

AZ / is / tk

cc : Mr. Nakazawa TOSHIBA HOKUTO TOKYO

Electromagnetic radiation test of microwave oven

The following measurements were conducted in Toshiba Hokuto Electronics Corporation measurement facility of FCC file number 430A.

1. Description of oven

Manufacturer of oven : Sharp Manufacturing Company of America
Model name : R-1200
Line voltage : 120V/60Hz
Output RF power : 1100W/2450MHz
Magnetron type : Toshiba 2M253H(L)

2. Equipment class : Part 18 Consumer Device

3. Test procedure : FCC/OST MP-5

4. Date of measurement : October 10, 2001 ~ October 12, 2001

5. Measurement data

5-1. Output power (Load : 1500ml water / center)

Input power : 1505W
Output power : 830W (Calorimetric Method)
Permissible FIS @300m : $32.2 \mu\text{V/m}$ = $25 \sqrt{\text{Output power} / 500}$
FIS : Field Intensity Strength

5-2. Power leak (Load : 275ml water / center)

Po leak : 0.2 mW/cm²

5-3. FIS measurements

Band	Frequency (MHz)	FIS @300m ($\mu\text{V/m}$)	Permissible FIS @300m ($\mu\text{V/m}$)	Load
Side band	2387	8.0	32.2	1050ml/ center
Side band	2501	7.0		1050ml/ center
2nd harmonic	2493	11.1		1050ml/ side
3rd harmonic	7843	9.6		1050ml/ side
4th harmonic	10248	6.0		1050ml/ center

Note 2nd and 3rd harmonics : The maximum value with the load condition such as 450ml or 1050ml water in the center or side position.

5-4. Frequency sweeping

None of higher FIS value than those shown in the above table existed in the following frequency band.

Frequency (MHz)	Load condition
2000 - 2400	1050ml / center
2500 - 4100	
4100 - 7700	450ml or 1050ml / center or side
7700 - 10000	1050ml / center

5-5. Frequency measurements

The variation of frequency for load variation

Volume of water (ml)	Frequency (MHz)
1500	2463
1200	2461
900	2462
600	2459
300	2451

The variation of frequency for line voltage variation (Load : 1500ml water center)

Line voltage (V)	Frequency (MHz)
96	2457
108	2456
120	2459
132	2458
150	2459

6. Description of instrumentation and calculation

6-1. Measurement equipment (Refer Page-4)

Interference analyzer : EMC-60 MK-IV (Bandwidth : 5MHz, Detector function : Linear average)
Antenna : CA-S, CA-M and CA-X

6-2. Test condition

Distance of antenna to oven : 3.0m
Antenna height range : 0.5m - 1.8m
Turn table height : 0.8m (360 degree movable)

6-3. Calculation formula

$FIS_{@3m} (dB \mu v/m) = \text{Analyzer reading}(dB \mu v) + \text{Antenna factor}(dB/m) + \text{Cable loss}(dB)$
 $FIS_{@300m} (\mu v/m) = K \times 10^{\wedge} (FIS_{@3m} / 20)$

K : Conversion factor for 3m to 300m

Antenna factor and Cable loss for our equipment are as follows :

Band	Frequency (MHz)	Antenna	Antenna factor (dB/m)	Cable loss (dB)	K
Fundamental	2450	CA-S	21.8	1.174	0.0062
2nd harmonic	4900	CA-M	39.1	1.288	0.01
3rd harmonic	7350	CA-M	39.2	1.397	0.01
4th harmonic	9800	CA-X	42.5	1.679	0.01

Example : 2nd harmonics

Analyzer reading = 22(dB μv)
 $FIS_{@300m} = 0.01 \times 10^{\wedge} ((22 + 39.1 + 1.288) / 20) = 13.1 (\mu v/m)$

7. Measurement equipment : Attached please find "Measurement equipment"(Refer Page-4).

Table 1 Measurement equipment

No.	Equipment name	Model name & manufacturer	Specification	Last calibration date	Calibration frequency
1	Interference analyzer	EMC-60 MK-IV Ser. : 44116 Electro-metrics	0.5 to 18 GHz	March 2000	once two year
2	Antenna	(1) CA-S Ser : 22-1 Polarad	2.1 to 4.34 GHz		
		(2) CA-M Ser : 20-15 Polarad	4.19 to 7.74 GHz		
		(3) CA-X Ser : 20-10 Polarad	7.36 to 10 GHz		
3	Signal generator	8671B Ser : 2545A00106 Hewlett packard	2.0 to 18 GHz	March 2000	once two year
4	Frequency counter	85340A Ser : 134A01280 Hewlett packard		March 2001	Annually
5	Power meter	435A Ser : 1312J00144 Hewlett packard	0 to 1 mW	March 2001	Annually
6	Power sensor	8481A Ser : 1234A871 Hewlett packard		March 2000	once two year
7	Spectrum analyzer	8562A SER : 2923A03932 Hewlett packard	1 kHz to 22 GHz	March 2000	once two year