

US Tech Test Report:
 FCC ID:
 Test Report Number:
 Issue Date:
 Customer:
 Model:

FCC Part 18 Subpart C
 APYDMR0183
 24-0408
 February 17, 2025
 Sharp Corporation
 SWA3099MS

**Maximum Permissible Exposure to RF (MPE), CFR 1.1310 (e)
 And Total Sum of MPE Calculation**

The maximum exposure level to the public from the RF power of the EUT shall not exceed a power density, **S** as per the respective limits in Table 1 below, at a distance, **d**, of 20 cm (Mobile condition) from the EUT.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

Therefore, for:

MPE for 2404 MHz – 2480 MHz for BLE:

Limit: 1.0 mW/cm²

Tuen up Average Power (dBm) = 4.0 dBm (2.51 mW)

Gain of Transmit Antenna = +2.49 dBi (1.77 numeric)

d = Distance = 20 cm = 0.2 m

$$S = (PG / 4\pi d^2)$$

Where: P = Watts, G = numeric

$$= (0.00251 * 1.77) / (4 * \pi * 0.2 * 0.2) =$$

$$= 0.0088 \text{ mW/cm}^2$$

which is << less than S = 1.0 mW/cm²

See attached RF Exposure Report # CN24ZRJX 001 for details.

US Tech Test Report:
FCC ID:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 18 Subpart C
APYDMR0183
24-0408
February 17, 2025
Sharp Corporation
SWA3099MS

MPE for 2412 MHz – 2462 MHz for WiFi:

Limit: 1.0 mW/cm²

Tuen up Average Power (dBm) = 16.0 dBm (39.8 mW)

Gain of Transmit Antenna = +2.49 dBi (1.77 numeric)

d = Distance = 20 cm = 0.2 m

$$S = (PG / 4\pi d^2)$$

Where: P = Watts, G = numeric

$$= (0.0398 * 1.77) / (4 * \pi * 0.2 * 0.2) =$$
$$= 0.1401 \text{ mW/cm}^2$$

which is << less than S = 1.0 mW/cm²

See attached RF Exposure Report # CN24ZRJX 001 for details.

MPE for 2400 MHz – 2500 MHz for Microwave Oven:

Limit: 1.0 mW/cm²

Signal Strength (V/m) = 7.8 V/m

$$\text{Power Flux Density (PFD)} = V/m^2 / 377 = W/m^2$$
$$= 7.8^2 / 377 = 0.1631 \text{ W/m}^2$$
$$= (0.1631 \text{ W/m}^2) (1\text{m}^2/\text{W}) (0.1 \text{ mW/cm}^2)$$
$$= 0.01631 \text{ mW/cm}^2$$

which is << less than S = 1.0 mW/cm²

See attached US Tech report # 23-0051 for details.

US Tech Test Report:
FCC ID:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 18 Subpart C
APYDMR0183
24-0408
February 17, 2025
Sharp Corporation
SWA3099MS

Simultaneous Transmission Collocation considerations:

Please either confirm that the transmitters operate standalone per KDB 447498 D01 v06 section 7.1 or, if the transmitters can transmit simultaneously, include the necessary calculations for simultaneous transmission per KDB 447498 D01 v06 section 7.2.

The Transmitters **do** simultaneously broadcast at the same frequency band, 2400-2483.5 MHz. The device has three radios on board, however two of the radios are Wi-Fi or BLE combo radio and not both can transmit at the same time. The radios that operate at the same time is either one Wi-Fi/BLE radio and Microwave Oven or the other Wi-Fi/BLE and Microwave Oven.

The Wi-Fi and BLE radio share a common antenna. The microwave oven has it's own transmit antenna.

Calculations for simultaneous transmission per KDB 447498 D01 v06 section 7.2 is provided here to show that Simultaneous transmission MPE test exclusion applies since the sum of the MPE ratios for all simultaneously transmitting antennas incorporated in a host device is ≤ 1.0 .

Total Sum of MPE:

Sum of the total MPE for BLE + Wi-Fi + Microwave Oven =
 $0.009 \text{ mW/cm}^2 + 0.140 \text{ mW/cm}^2 + 0.016 \text{ mW/cm}^2 = \underline{\mathbf{0.165}}$ which is << less than 1.0

The EUT was tested with all radios ON and active. The emissions generated with a single radio ON and active versus all radios ON and active did not produce additional unwanted spurious emissions or intermodulation that would require additional testing. The radios can be collocated as designed.