

EMI TEST REPORT

Test Report No. : 30EE0168-HO-B

Applicant : **Sharp Corporation, Communication Systems Group.**
Type of Equipment : **Cellular Phone**
Model No. : **943SH**
FCC ID : **APYHRO00115**
Test regulation : **FCC Part 15 Subpart B 2009 Class B**
Test Result : **Complied**

1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the above regulation.
4. The test results in this report are traceable to the national or international standards.
5. This test report must not be used by the customer product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.


Date of test: December 29, 2009

Tested by:



Hironobu Ohnishi
EMC Services

Approved by:



Yufaka Yoshida
Group Leader of EMC Services



NVLAP LAB CODE: 200572-0

This laboratory is accredited by the NVLAP LAB CODE 200572-0, U.S.A. The tests reported herein have been performed in accordance with its terms of accreditation.
*As for the range of Accreditation in NVLAP, you may refer to the WEB address,
<http://uljapan.co.jp/emc/nvlap.html>

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

MF060b (06.08.09)

CONTENTS	PAGE
SECTION 1: Customer information	3
SECTION 2: Equipment under test (E.U.T.)	3
SECTION 3: Test specification, procedures & results	4
SECTION 4: Operation of E.U.T. during testing	6
SECTION 5: Conducted Emission	8
SECTION 6: Radiated Emission	9
APPENDIX 1: Photographs of test setup.....	10
Conducted Emission	10
Radiated Emission	11
Worst Case Position (Horizontal: X-axis/ Vertical:X-axis)	12
APPENDIX 2: Data of EMI test	13
Conducted Emission	13
Radiated Emission	15
APPENDIX 3: Test instruments	19

SECTION 1: Customer information

Company Name : Sharp Corporation, Communication Systems Group.
Address : 2-13-1 Iida Hachihonmatsu HigashiHiroshima-City, Hiroshima,
739-0192 Japan
Telephone Number : +81-82-420-1827
Facsimile Number : +81-82-420-1572
Contact Person : Hiroyuki Uwatoko

SECTION 2: Equipment under test (E.U.T.)

2.1 Identification of E.U.T.

Type of Equipment : Cellular Phone
Model No. : 943SH
Serial No. : 004401/11/229705/2
Rating : AC 120V / 60Hz, DC 4.0V
Receipt Date of Sample : December 25, 2009
Country of Mass-production : Japan
Condition of EUT : Production prototype
(Not for Sale: This sample is equivalent to mass-produced items.)
Modification of EUT : No Modification by the test lab

2.2 Product description

Model No: 943SH (referred to as the EUT in this report) is the Cellular Phone.

Feature of EUT : 943SH is Dual-band (FDD I/FDD XI) WCDMA & Tri-band (900/1800/1900)
GSM Dual mode Cellular Phone.
The EUT has the function that Bluetooth wireless technology interface and
wireless LAN technical interface for establishing contact and transmitting data
with certain device.
Clock frequency : CPU: 26MHz
RTC: 32.768kHz
Internal: 208MHz

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

SECTION 3: Test specification, procedures & results

3.1 Test specification

Test Specification : FCC Part 15 Subpart B 2009, final revised on December 2, 2009
Title : FCC 47CFR Part15 Radio Frequency Device
Subpart B Unintentional Radiators

3.2 Procedures and results

Item	Test Procedure	Limits	Deviation	Worst margin	Result
Conducted emission	FCC: ANSI C63.4: 2003 7. AC powerline conducted emission measurements	Class B	N/A	[QP] 13.0dB 3.74355MHz, L [AV] 9.4dB 1.98582MHz, L	Complied
Radiated emission	FCC: ANSI C63.4: 2003 8. Radiated emission measurements	Class B	N/A	8.7dB 72.388MHz Horizontal, QP	Complied

*Note: UL Japan, Inc's EMI Work Procedure QPM05.

3.3 Addition to standard

No addition, exclusion nor deviation has been made from the standard.

3.4 Uncertainty

EMI

The following uncertainties have been calculated to provide a confidence level of 95% using a coverage factor k=2.

Test room (semi-anechoic chamber)	Conducted emission (±dB)
	150kHz-30MHz
No.1	2.6dB
No.2	2.9dB
No.3	3.3dB
No.4	2.8dB

Test room (semi-anechoic chamber)	Radiated emission (10m*)(±dB)			Radiated emission					
				(3m*)(±dB)					(1m*)(±dB)
	9kHz -30MHz	30MHz -300MHz	300MHz -1GHz	9kHz -30MHz	30MHz -300MHz	300MHz -1GHz	1GHz -18GHz	18GHz -26.5GHz	26.5GHz -40GHz
No.1	2.7dB	4.8dB	5.0dB	2.9dB	4.8dB	5.0dB	3.9dB	4.5dB	4.4dB
No.2	-	-	-	3.5dB	4.8dB	5.1dB	4.0dB	4.3dB	4.2dB
No.3	-	-	-	3.8dB	4.6dB	4.7dB	4.0dB	4.5dB	4.4dB
No.4	-	-	-	3.5dB	4.4dB	4.9dB	4.0dB	4.6dB	4.5dB

*10m/3m/1m = Measurement distance

Conducted Emission test

The data listed in this test report has enough margin, more than the site margin.

Radiated emission test (3m)

The data listed in this test report has enough margin, more than the site margin.

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

3.5 Test Location

UL Japan, Inc. Head Office EMC Lab. *NVLAP Lab. code: 200572-0
4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN
Telephone : +81 596 24 8116 Facsimile : +81 596 24 8124

	FCC Registration Number	IC Registration Number	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Other rooms
No.1 semi-anechoic chamber	313583	2973C-1	19.2 x 11.2 x 7.7m	7.0 x 6.0m	No.1 Power source room
No.2 semi-anechoic chamber	655103	2973C-2	7.5 x 5.8 x 5.2m	4.0 x 4.0m	-
No.3 semi-anechoic chamber	148738	2973C-3	12.0 x 8.5 x 5.9m	6.8 x 5.75m	No.3 Preparation room
No.3 shielded room	-	-	4.0 x 6.0 x 2.7m	N/A	-
No.4 semi-anechoic chamber	134570	2973C-4	12.0 x 8.5 x 5.9m	6.8 x 5.75m	No.4 Preparation room
No.4 shielded room	-	-	4.0 x 6.0 x 2.7m	N/A	-
No.5 semi-anechoic chamber	-	-	6.0 x 6.0 x 3.9m	6.0 x 6.0m	-
No.6 shielded room	-	-	4.0 x 4.5 x 2.7m	4.75 x 5.4 m	-
No.6 measurement room	-	-	4.75 x 5.4 x 3.0m	4.75 x 4.15 m	-
No.7 shielded room	-	-	4.7 x 7.5 x 2.7m	4.7 x 7.5m	-
No.8 measurement room	-	-	3.1 x 5.0 x 2.7m	N/A	-
No.9 measurement room	-	-	8.0 x 4.5 x 2.8m	2.0 x 2.0m	-
No.10 measurement room	-	-	2.6 x 2.8 x 2.5m	2.4 x 2.4m	-
No.11 measurement room	-	-	3.1 x 3.4 x 3.0m	2.4 x 3.4m	-

* Size of vertical conducting plane (for Conducted Emission test) : 2.0 x 2.0m for No.1, No.2, No.3, and No.4 semi-anechoic chambers and No.3 and No.4 shielded rooms.

3.6 Test set up, Data of EMI, and Test instruments


Refer to APPENDIX 1 to 3.

SECTION 4: Operation of E.U.T. during testing

4.1 Operating modes

The mode is used : 1) USB Data Com mode
The USB data is communicated between EUT and Personal computer (Pair of EUT).
2) Standby mode
Standby state for USB communication

4.2 Configuration and peripherals



*Cabling and setup were taken into consideration and test data was taken under worse case conditions.

Description of EUT and Support equipment

No.	Item	Model number	Serial number	Manufacturer	Remark
A	Cellular Phone	943SH	004401/11/229705/2	SHARP	EUT
B	Lithium-Ion Battery	SHBCU1	SKA	SHARP	EUT
C	microSD Memory Card	SDSDQ-128	None	SanDisk	-
D	Personal Computer	PP11L	CN-0D4571-48643-55V-1651	Dell	-
E	Mouse	M-BE55	LZE21450232	Logitech	-
F	AC Adapter (PC)	PA-1650-05D2	CN-0F7970-71615-561-14A1	Dell	-
G	Printer	895Cxi	SG8BL1W16V	Hewlett Packard	-
H	AC Adapter (Printer)	C4557-60004	C8K28B	Hewlett Packard	-

List of cables used

No.	Name	Length (m)	Shield		Remark
			Cable	Connector	
1	USB Cable	0.8	Shielded	Shielded	-
2	Mouse Cable	0.72	Unshielded	Unshielded	-
3	AC Adapter Cable (PC)	1.76	Unshielded	Unshielded	-
4	AC Power Cable (PC)	0.85	Unshielded	Unshielded	-
5	Parallel Cable	1.65	Shielded	Shielded	-
6	AC Adapter Cable (Printer)	2.0	Unshielded	Unshielded	-
7	AC Power Cable (Printer)	1.75	Unshielded	Unshielded	-

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

SECTION 5: Conducted Emission

5.1 Operating environment

Test place : No.1 semi anechoic chamber.
Temperature : See data
Humidity : See data

5.2 Test configuration

EUT was placed on a urethane platform of nominal size, 1.0m by 1.5m, raised 0.8m above the conducting ground plane. The rear of tabletop was located 40cm to the vertical conducting plane. The rear of EUT and its peripherals was aligned and flushed with rear of tabletop. All other surfaces of tabletop were at least 80cm from any other grounded conducting surface. They were folded back and forth forming a bundle 30cm to 40cm long and were hanged at a 40cm height to the ground plane. Each EUT current-carrying power lead, except the ground (safety) lead, was individually connected through a LISN/AMN to the input power source. All unused 50 ohm connectors of the LISN/AMN were resistivity terminated in 50 ohm when not connected to the measuring equipment.

Photographs of the set up are shown in Appendix 1.

Frequency range : 0.15 MHz-30MHz
EUT position : Table top
EUT operation mode : See Clause 4.1

5.3 Test procedure

The AC Mains Terminal Continuous disturbance Voltage has been measured with the EUT within a semi anechoic chamber. The EUT was connected to a Line Impedance Stabilization Network (LISN)/ Artificial Mains network (AMN). An overview sweep with peak detection has been performed. The measurements have been performed with a quasi-peak detector and if required, with an average detector.

The conducted emission measurements were made with the following detector function of the test receiver.

Detector Type : Quasi-Peak and Average
IF Bandwidth : 9 kHz

5.4 Test result

Summary of the test results: Pass

Date: December 29, 2009

Test engineer: Hironobu Ohnishi

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

SECTION 6: Radiated Emission

6.1 Operating environment

Test place : No.1 semi anechoic chamber
Temperature : See data
Humidity : See data

6.2 Test configuration

EUT was placed on a urethane platform of nominal size, 1.0m by 1.5m, raised 0.8m above the conducting ground plane. The EUT was set on the edge of the tabletop. Test was made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna was varied in height above the conducting ground plane to obtain the maximum signal strength. Photographs of the set up are shown in Appendix 1.

6.3 Test conditions

Frequency range : 30MHz-300MHz (Biconical antenna) / 300MHz-1000MHz (Logperiodic antenna)
1000MHz - 2000MHz (Horn antenna)
Test distance : 3m
EUT position : Table top
EUT operation mode : See Clause 4.1

6.4 Test procedure

The height of the measuring antenna varied between 1 and 4m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity. The measurements were performed for both vertical and horizontal antenna polarization with the Test Receiver, or the Spectrum Analyzer. The radiated emission measurements were made with the following detector function of the test receiver and the Spectrum analyzer.

Frequency	Below 1GHz	Above 1GHz
Instrument used	Test Receiver	Spectrum Analyzer
IF Bandwidth	QP: BW 120kHz	PK: RBW:1MHz/VBW: 1MHz AV *1): RBW:1MHz/VBW:10Hz

*1) When using Spectrum analyzer, the test was made with adjusting span to zero by using peak hold.

- The carrier level and noise levels were confirmed at each position of X, Y and Z axes of EUT to see the position of maximum noise, and the test was made at the position that has the maximum noise.

6.5 Test result

Summary of the test results: Pass

Date: December 29, 2009

Test engineer: Hironobu Ohnishi

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

APPENDIX 1: Photographs of test setup

Conducted Emission

This page has been submitted for a separate exhibit.

Radiated Emission

This page has been submitted for a separate exhibit.

Worst Case Position (Horizontal: X-axis/ Vertical:X-axis)

This page has been submitted for a separate exhibit.

APPENDIX 2: Data of EMI test

Conducted Emission

DATA OF CONDUCTED EMISSION TEST


UL Japan, Inc. Head Office EMC Lab. No.1 Semi Anechoic Chamber
Date : 2009/12/29

Company : Sharp Corporation
Kind of EUT : Cellular Phone
Model No. : 943SH
Serial No. : 004401/11/229705/2

Report No. : 30EE0168-HO
Power : AC 120V / 60Hz
Temp./Humi. : 19deg. C. / 25%
Engineer : Hironobu Ohnishi

Mode / Remarks: USB Data Com Mode

LIMIT : FCC15.107(a) QP
FCC15.107(a) AV



Frequency [MHz]	Reading Level		Corr. Factor	Results		Limit		Margin		Phase	Comment
	QP [dBuV]	AV [dBuV]		QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	QP [dB]	AV [dB]		
0.16955	51.3	44.4	0.2	51.5	44.6	65.0	55.0	13.5	10.4	N	
0.22671	45.7	35.5	0.3	46.0	35.8	62.6	52.6	16.6	16.8	N	
0.28230	40.2	32.4	0.3	40.5	32.7	60.7	50.7	20.2	18.0	N	
0.33915	41.3	31.2	0.3	41.6	31.5	59.2	49.2	17.6	17.7	N	
2.03551	38.4	34.9	0.5	38.9	35.4	56.0	46.0	17.1	10.6	N	
3.79077	39.5	28.6	0.8	40.3	29.4	56.0	46.0	15.7	16.6	N	
10.58095	32.8	27.9	1.6	34.4	29.5	60.0	50.0	25.6	20.5	N	
0.17156	51.1	43.4	0.2	51.3	43.6	64.9	54.9	13.6	11.3	L	
0.22738	47.0	37.0	0.3	47.3	37.3	62.5	52.5	15.2	15.2	L	
0.28422	39.3	29.6	0.3	39.6	29.9	60.7	50.7	21.1	20.8	L	
0.28403	39.3	29.6	0.3	39.6	29.9	60.7	50.7	21.1	20.8	L	
1.98582	39.3	36.1	0.5	39.8	36.6	56.0	46.0	16.2	9.4	L	
3.74355	42.2	31.3	0.8	43.0	32.1	56.0	46.0	13.0	13.9	L	
10.71096	33.3	25.1	1.6	34.9	26.7	60.0	50.0	25.1	23.3	L	

CHART: WITH FACTOR, Peak hold data. CALCULATION: RESULT[dBuV]=READING[dBuV]+C.F[dB] (LISN LOSS+CABLE LOSS)
Except for the above table : adequate margin data below the limits.

*The test result is rounded off to one or two decimal places, so some differences might be observed.

Conducted Emission

DATA OF CONDUCTED EMISSION TEST


UL Japan, Inc. Head Office EMC Lab. No.1 Semi Anechoic Chamber
Date : 2009/12/29

Company : Sharp Corporation
Kind of EUT : Cellular Phone
Model No. : 943SH
Serial No. : 004401/11/229705/2

Report No. : 30EE0168-HO
Power : AC 120V / 60Hz
Temp./Humi. : 19deg. C. / 25%
Engineer : Hironobu Ohnishi

Mode / Remarks : Standby Mode

LIMIT : FCC15.107(a) QP
FCC15.107(a) AV



Frequency [MHz]	Reading Level		Corr. Factor	Results		Limit		Margin		Phase	Comment
	QP [dBuV]	AV [dBuV]		QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	QP [dB]	AV [dB]		
0.17009	49.0	40.2	0.2	49.2	40.4	65.0	55.0	15.8	14.6	N	
0.22746	43.7	34.1	0.3	44.0	34.4	62.5	52.5	18.5	18.1	N	
0.28299	37.9	29.9	0.3	38.2	30.2	60.7	50.7	22.5	20.5	N	
0.33935	38.5	30.0	0.3	38.8	30.3	59.2	49.2	20.4	18.9	N	
1.75200	36.9	30.0	0.5	37.4	30.5	56.0	46.0	18.6	15.5	N	
3.90086	37.1	25.1	0.8	37.9	25.9	56.0	46.0	18.1	20.1	N	
10.68294	31.9	34.1	1.6	33.5	35.7	60.0	50.0	26.5	14.3	N	
0.16924	48.7	40.7	0.2	48.9	40.9	65.0	55.0	16.1	14.1	L	
0.22644	44.9	35.3	0.3	45.2	35.6	62.6	52.6	17.4	17.0	L	
0.28259	38.2	29.9	0.3	38.5	30.2	60.7	50.7	22.2	20.5	L	
0.33835	39.8	31.0	0.3	40.1	31.3	59.2	49.2	19.1	17.9	L	
2.09037	38.1	32.0	0.5	38.6	32.5	56.0	46.0	17.4	13.5	L	
3.72958	39.6	27.4	0.7	40.3	28.1	56.0	46.0	15.7	17.9	L	
10.79441	30.7	22.4	1.6	32.3	24.0	60.0	50.0	27.7	26.0	L	

CHART: WITH FACTOR, Peak hold data. CALCULATION: RESULT [dBuV]=READING [dBuV]+C. F [dB] (LISN LOSS+CABLE LOSS)
Except for the above table : adequate margin data below the limits.

*The test result is rounded off to one or two decimal places, so some differences might be observed.

Radiated Emission

DATA OF RADIATED EMISSION TEST


UL Japan, Inc. Head Office EMC Lab. No.1 Semi Anechoic Chamber
Date : 2009/12/29

Company : Sharp Corporation
Kind of EUT : Cellular Phone
Model No. : 943SH
Serial No. : 004401/11/229705/2

Report No. : 30EE0168-HO
Power : AC 120V / 60Hz
Temp./Humi. : 19deg. C. / 25%
Engineer : Hironobu Ohnishi

Mode / Remarks : USB Data Com Mode

LIMIT : FCC15.109(a) 3m, below 1GHz:QP, above 1GHz:PK
Except for the data below : adequate margin data below the limits.



Frequency [MHz]	Reading [dBuV]	DET	Antenna		Level [dBuV/m]	Angle [Deg]	Height [cm]	Polar.	Limit [dBuV/m]	Margin [dB]	Comment
			Factor [dB/m]	Loss & Gain [dB]							
60.324	53.4	QP	7.8	-33.9	27.3	290	364	Hori.	40.0	12.7	
60.324	49.7	QP	7.8	-33.9	23.6	161	100	Vert.	40.0	16.4	
72.388	58.5	QP	6.5	-33.7	31.3	309	246	Hori.	40.0	8.7	
72.388	55.2	QP	6.5	-33.7	28.0	273	100	Vert.	40.0	12.0	
78.156	57.3	QP	6.4	-33.6	30.1	301	257	Hori.	40.0	9.9	
78.156	53.7	QP	6.4	-33.6	26.5	227	100	Vert.	40.0	13.5	
223.679	50.4	QP	17.0	-31.3	36.1	311	153	Hori.	46.0	9.9	
223.679	50.3	QP	17.0	-31.3	36.0	304	158	Vert.	46.0	10.0	
447.357	47.7	QP	17.1	-29.7	35.1	300	100	Hori.	46.0	10.9	
447.357	44.8	QP	17.1	-29.7	32.2	30	149	Vert.	46.0	13.8	
901.810	40.3	QP	22.3	-26.7	35.9	315	102	Hori.	46.0	10.1	
901.810	38.8	QP	22.3	-26.7	34.4	46	164	Vert.	46.0	11.6	

CHART: WITH FACTOR ANT TYPE: -30MHz: LOOP, 30-300MHz: BICONICAL, 300MHz-1000MHz: LOGPERIODIC, 1000MHz-: HORN
CALCULATION: RESULT = READING + ANT FACTOR + LOSS (CABLE+ATTEN.) - GAIN (AMP)

*The limit is rounded down to one decimal place.

*The test result is rounded off to one or two decimal places, so some differences might be observed.

Radiated Emission

DATA OF RADIATED EMISSION TEST


UL Japan, Inc. Head Office EMC Lab. No.1 Semi Anechoic Chamber
Date : 2009/12/29

Company : Sharp Corporation
Kind of EUT : Cellular Phone
Model No. : 943SH
Serial No. : 004401/11/229705/2

Report No. : 30EE0168-HO
Power : AC 120V / 60Hz
Temp./Humi. : 19deg. C. / 25%
Engineer : Hironobu Ohnishi

Mode / Remarks : Standby Mode

LIMIT : FCC15.109(a) 3m, below 1GHz:QP, above 1GHz:PK
Except for the data below : adequate margin data below the limits.



Frequency [MHz]	Reading [dBuV]	DET	Antenna		Level [dBuV/m]	Angle [Deg]	Height [cm]	Polar.	Limit [dBuV/m]	Margin [dB]	Comment
			Factor [dB/m]	Loss & Gain [dB]							
60.327	53.5	QP	7.8	-33.9	27.4	288	358	Hori.	40.0	12.6	
60.327	49.2	QP	7.8	-33.9	23.1	162	100	Vert.	40.0	16.9	
72.393	57.8	QP	6.5	-33.7	30.6	310	248	Hori.	40.0	9.4	
72.393	54.1	QP	6.5	-33.7	26.9	265	100	Vert.	40.0	13.1	
78.425	57.3	QP	6.4	-33.6	30.1	306	242	Hori.	40.0	9.9	
78.425	53.3	QP	6.4	-33.6	26.1	229	100	Vert.	40.0	13.9	
223.678	50.1	QP	17.0	-31.3	35.8	307	163	Hori.	46.0	10.2	
223.678	49.3	QP	17.0	-31.3	35.0	359	100	Vert.	46.0	11.0	
447.357	46.0	QP	17.1	-29.7	33.4	300	100	Hori.	46.0	12.6	
447.357	44.7	QP	17.1	-29.7	32.1	29	148	Vert.	46.0	13.9	
901.810	37.0	QP	22.3	-26.7	32.6	315	102	Hori.	46.0	13.4	
901.810	35.0	QP	22.3	-26.7	30.6	46	164	Vert.	46.0	15.4	

CHART: WITH FACTOR ANT TYPE: -30MHz: LOOP, 30-300MHz: BICONICAL, 300MHz-1000MHz: LOGPERIODIC, 1000MHz-: HORN
CALCULATION: RESULT = READING + ANT FACTOR + LOSS (CABLE+ATTEN.) - GAIN (AMP)

*The limit is rounded down to one decimal place.

*The test result is rounded off to one or two decimal places, so some differences might be observed.

Radiated Emission

DATA OF RADIATED EMISSION TEST


UL Japan, Inc. Head Office EMC Lab. No.1 Semi Anechoic Chamber
Date : 2009/12/29

Company : Sharp Corporation
Kind of EUT : Cellular Phone
Model No. : 943SH
Serial No. : 004401/11/229705/2

Report No. : 30EE0168-HO
Power : AC 120V / 60Hz
Temp./Humi. : 19deg. C. / 25%
Engineer : Hironobu Ohnishi

Mode / Remarks : USB Data Com Mode

LIMIT : FCC15.109(a) 3m, below 1GHz:QP, above 1GHz:PK
FCC15.109(a) 3m, below 1GHz:QP, above 1GHz:AV



Frequency [MHz]	Reading [dBuV]	DET	Antenna	Loss &	Level	Angle	Height	Polar.	Limit	Margin	Comment
			Factor	Gain					[dBuV/m]	[dB]	
1596.100	58.5	PK	26.3	-34.6	50.2	259	101	Hori.	73.9	23.7	
1596.100	61.4	PK	26.3	-34.6	53.1	36	131	Vert.	73.9	20.8	
1596.100	38.2	AV	26.3	-34.6	29.9	259	101	Hori.	53.9	24.0	
1596.100	37.0	AV	26.3	-34.6	28.7	36	131	Vert.	53.9	25.2	

CHART: WITH FACTOR ANT TYPE: -30MHz: LOOP, 30-300MHz: BICONICAL, 300MHz-1000MHz: LOGPERIODIC, 1000MHz-: HORN
CALCULATION: RESULT = READING + ANT FACTOR + LOSS (CABLE+ATTEN.) - GAIN (AMP)

*The limit is rounded down to one decimal place.
*The test result is rounded off to one or two decimal places, so some differences might be observed.

Radiated Emission

DATA OF RADIATED EMISSION TEST


UL Japan, Inc. Head Office EMC Lab. No.1 Semi Anechoic Chamber
Date : 2009/12/29

Company : Sharp Corporation
Kind of EUT : Cellular Phone
Model No. : 943SH
Serial No. : 004401/11/229705/2

Report No. : 30EE0168-HO
Power : AC 120V / 60Hz
Temp./Humi. : 19deg. C. / 25%
Engineer : Hironobu Ohnishi

Mode / Remarks : Standby Mode

LIMIT : FCC15.109(a) 3m, below 1GHz:QP, above 1GHz:PK
FCC15.109(a) 3m, below 1GHz:QP, above 1GHz:AV



Frequency [MHz]	Reading [dBuV]	DET	Antenna		Level [dBuV/m]	Angle [Deg]	Height [cm]	Polar.	Limit [dBuV/m]	Margin [dB]	Comment
			Factor [dB/m]	Loss & Gain [dB]							
1596.100	58.1	PK	26.3	-34.6	49.8	259	101	Hori.	73.9	24.1	
1596.100	62.1	PK	26.3	-34.6	53.8	36	131	Vert.	73.9	20.1	
1596.100	36.8	AV	26.3	-34.6	28.5	259	101	Hori.	53.9	25.4	
1596.100	36.0	AV	26.3	-34.6	27.7	36	131	Vert.	53.9	26.2	

CHART: WITH FACTOR ANT TYPE: -30MHz: LOOP, 30-300MHz: BICONICAL, 300MHz-1000MHz: LOGPERIODIC, 1000MHz-: HORN
CALCULATION: RESULT = READING + ANT FACTOR + LOSS (CABLE+ATTEN.) - GAIN (AMP)

*The limit is rounded down to one decimal place.

*The test result is rounded off to one or two decimal places, so some differences might be observed.

APPENDIX 3: Test instruments

EMI test equipment

Control No.	Instrument	Manufacturer	Model No	Serial No	Test Item	Calibration Date * Interval(month)
MAEC-01	Semi Anechoic Chamber(NSA)	TDK	Semi Anechoic Chamber 10m	DA-06881	RE, CE	2009/06/26 * 12
MOS-01	Digital Humidity Indicator	N.T	NT-1800	MOS01	RE, CE	2009/02/06 * 12
MJM-01	Measure	KDS	ES19-55	-	RE, CE	-
COTS-MEMI	EMI measurement program	TSJ	TEPTO-DV	-	RE, CE	-
MTR-01	Test Receiver	Rohde & Schwarz	ESI40	100084	RE, CE	2009/12/17 * 12
MBA-01	Biconical Antenna	Schwarzbeck	BBA9106	VHA91032007	RE	2009/10/03 * 12
MLA-09	Logperiodic Antenna	Schwarzbeck	USLP9143B	9143B006	RE	2009/10/03 * 12
MAT-06	Attenuator(6dB)	Weinschel Corp	2	BL1069	RE	2009/11/26 * 12
MCC-01	Coaxial Cable 0.1-3000MHz	Suhner/storm/Agilent/TSJ	-	-	RE	2009/10/09 * 12
MPA-20	Pre Amplifier	Elena	EPA-4020YA	030801	RE	2009/03/17 * 12
MHA-05	Horn Antenna 1-18GHz	Schwarzbeck	BBHA9120D	253	RE	2009/06/15 * 12
MCC-18	Microwave Cable 1G-26.5GHz	Suhner	SUCOFLEX 104	233010(1m) / 292410(5m)	RE	2009/09/16 * 12
MPA-01	Pre Amplifier	Agilent	8449B	3008A01671	RE	2009/02/12 * 12
MLS-02	LISN(AMN)	Schwarzbeck	NSLK8127	8127383	CE(EUT)	2009/06/22 * 12
MLS-03	LISN(AMN)	Schwarzbeck	NSLK8127	8127384	CE(AE)	2009/07/16 * 12
MTA-06	Terminator	MCL	BTRM-50	1 9951	CE	2009/02/17 * 12
MCC-03	Coaxial Cable	Fujikura/Suhner/TSJ	5D-2W(20m)/3D-2W(7.5m)/RG400u(1.5m)/RFM-E421(Switcher)	- /01068(Switcher)	CE	2008/12/16 * 12

The expiration date of the calibration is the end of the expired month.

All equipment is calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

As for some calibrations performed after the tested dates, those test equipment have been controlled by means of an unbroken chains of calibrations.

Test Item:

CE: Conducted emission

RE: Radiated emission

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124