

TEST REPORT

APPLICANT : Sharp Corporation, Communication Systems Group
ADDRESS : 2-13-1, Iida Hachihonmatsu, Higashi-Hiroshima City, Hiroshima,
739-0192, JAPAN

PRODUCTS : Cellular Phone

MODEL NO. : 945SH
SERIAL NO. : 004401/11/260163/4
004401/11/260200/4

FCC ID : APYHRO00124

TEST STANDARD : CFR 47 FCC Rules and Regulations Part 15

TESTING LOCATION : Japan Quality Assurance Organization
KITA-KANSAI Testing Center
1-7-7, Ishimaru, Minoh-shi, Osaka 562-0027, Japan

TEST RESULTS : **Passed**

DATE OF TEST : April 19, 2009 ~ May 11, 2010

This report must not be used by the client to claim product endorsement by NVLAP or NIST or any agency of the U.S. Government.



NVLAP LAB CODE 200191-0

A handwritten signature in black ink, appearing to read 'K. Shibata', is written over a horizontal line.

Kousei Shibata

Manager

Japan Quality Assurance Organization

KITA-KANSAI Testing Center

Testing Dept. EMC Division

1-7-7, Ishimaru, Minoh-shi, Osaka 562-0027, Japan

- The measurement values stated in Test Report was made with traceable to National Institute of Advanced Industrial Science and Technology (AIST) of Japan and National Institute of Information and Communications Technology (NICT) of Japan.
- The applicable standard, testing condition and testing method which were used for the tests are based on the request of the applicant.
- The test results presented in this report relate only to the offered test sample.
- The contents of this test report cannot be used for the purposes, such as advertisement for consumers.
- This test report shall not be reproduced except in full without the written approval of JQA.

TABLE OF CONTENTS**Page**

Documentation	3
1 Test Regulation.....	3
2 Test Location.....	3
3 Recognition of Test Laboratory.....	3
4 Description of the Equipment Under Test.....	4
5 Test Condition.....	5
6 Preliminary Test and Test Setup.....	7
7 Equipment Under Test Modification.....	13
8 Responsible Party.....	13
9 Deviation from Standard.....	13
10 Test Results.....	14
11 Summary.....	17
12 Operating Condition.....	18
13 Test Configuration.....	18
14 Equipment Under Test Arrangement (Drawings).....	19
Appendix A: Test Data.....	20
Appendix B: Test Arrangement (Photographs).....	68
Appendix C: Test Instruments.....	70

DEFINITIONS FOR ABBREVIATION AND SYMBOLS USED IN THIS TEST REPORT**EUT** : Equipment Under Test**EMC** : Electromagnetic Compatibility**AE** : Associated Equipment**EMI** : Electromagnetic Interference**N/A** : Not Applicable**EMS** : Electromagnetic Susceptibility**N/T** : Not Tested - indicates that the listed condition, standard or equipment is applicable for this report. - indicates that the listed condition, standard or equipment is not applicable for this report.

Documentation**1 Test Regulation**

Applied Standard : CFR 47 FCC Rules and Regulations Part 15
Subpart C – Intentional Radiators

Test Requirements : §15.247, §15.207 and §15.209

Test Procedure : ANSI C63.4–2003

The tests were performed with reference to the FCC Public Notice DA 00-705, released March 30, 2000.

The test set-up was made in accordance to the general provisions of ANSI C63.4-2003.

2 Test Location

KITA-KANSAI Testing Center

1-7-7, Ishimaru, Minoh-shi, Osaka 562-0027, Japan

KAMEOKA EMC Branch

9-1, Ozaki, Inukanno, Nishibetsuin-cho, Kameoka-shi, Kyoto 621-0126, Japan

3 Recognition of Test Laboratory

VLAC Code : VLAC-001-2 (Effective through : March 30, 2012)

NVLAP Lab Code : 200191-0 (Effective through : June 30, 2010)

BSMI Recognition No. : SL2-IS-E-6006, SL2-IN-E-6006, SL2-AI-E-6006
(Effective through : September 14, 2010)

VCCI Registration No. : R-008, C-006, C-007, C-1674, C-2143, C-3685, T-1418, T-1419, T-1819, T-1820,
T-1821, G-172, G-173
(Effective through : March 30, 2012)

IC Registration No. : 2079E-1, 2079E-2 (Effective through : January 6, 2011)

Accredited as conformity assessment body for Japan electrical appliances and material law by METI.
(Effective through : February 22, 2012)

4 Description of the Equipment Under Test

4.1 General Information

1. Manufacturer : Sharp Corporation, Communication Systems Group
2-13-1, Iida Hachihonmatsu, Higashi-Hiroshima City, Hiroshima,
739-0192, JAPAN
2. Products : Cellular Phone
3. Model No. : 945SH
4. Serial No. : 004401/11/260163/4
: 004401/11/260200/4
5. Product Type : Pre-production
6. Date of Manufacture : March, 2010
7. Transmitting Frequency : 2412.0 MHz(01CH) –2462.0MHz(11CH)
8. Receiving Frequency : 2412.0 MHz(01CH) –2462.0MHz(11CH)
9. Max. RF Output Power : 18.04dBm(Measure Value of IEEE801.11b)
: 20.61dBm(Measure Value of IEEE801.11g)
10. Power Rating : 4.0VDC (Lithium-ion Battery Pack SHBDA1 800mAh)
11. EUT Grounding : None
12. EUT Authorization : Certification
13. Receive Date of EUT : April 16, 2010

4.2 Channel Plan

The carrier spacing is 5 MHz.

The carrier frequency is designated by the absolute frequency channel number (ARFCN).

The carrier frequency is expressed in the equation shown as follows:

$$\text{Transmitting Frequency (in MHz)} = 2407.0 + 5*n$$

$$\text{Receiving Frequency (in MHz)} = 2407.0 + 5*n$$

where, n : channel number ($1 \leq n \leq 11$)

5 Test Condition

5.1 Channel Separation

The requirements are - Applicable [- Tested. - Not tested by applicant request.]
 - Not Applicable

Test site : KITA-KANSAI - Shielded room - 2nd Shielded room
KAMEOKA - Shielded room - Conducted emission facility

Test instruments : Refer to Appendix C.

5.2 Minimum Hopping Channel

The requirements are - Applicable [- Tested. - Not tested by applicant request.]
 - Not Applicable

Test site : KITA-KANSAI - Shielded room - 2nd Shielded room
KAMEOKA - Shielded room - Conducted emission facility

Test instruments : Refer to Appendix C.

5.3 Occupied Bandwidth

The requirements are - Applicable [- Tested. - Not tested by applicant request.]
 - Not Applicable

Test site : KITA-KANSAI - Shielded room - 2nd Shielded room
KAMEOKA - Shielded room - Conducted emission facility

Test instruments : Refer to Appendix C.

5.4 Dwell Time

The requirements are - Applicable [- Tested. - Not tested by applicant request.]
 - Not Applicable

Test site : KITA-KANSAI - Shielded room - 2nd Shielded room
KAMEOKA - Shielded room - Conducted emission facility

Test instruments : Refer to Appendix C.

5.5 Peak Output Power and Density (Conduction)

The requirements are - Applicable - Tested. - Not tested by applicant request.]
 - Not Applicable

Test site : KITA-KANSAI - Shielded room - 2nd Shielded room
KAMEOKA - Shielded room - Conducted emission facility

Test instruments : Refer to Appendix C.

5.6 Spurious Emission (Conduction)

The requirements are - Applicable - Tested. - Not tested by applicant request.]
 - Not Applicable

Test site : KITA-KANSAI - Shielded room - 2nd Shielded room
KAMEOKA - Shielded room - Conducted emission facility

Test instruments : Refer to Appendix C.

5.7 AC Powerline Conducted Emission

The requirements are - Applicable - Tested. - Not tested by applicant request.]
 - Not Applicable

Test site : KITA-KANSAI - Shielded room - Anechoic chamber
KAMEOKA - Shielded room - Conducted emission facility
 - 1st open site

Test instruments : Refer to Appendix C.

5.8 Field Strength of Spurious Radiation

The requirements are - Applicable - Tested. - Not tested by applicant request.]
 - Not Applicable

Test site : - KAMEOKA 1st open site - 3 m - 10 m
 - KAMEOKA 2nd open site - 3 m - 10 m

Test instruments : Refer to Appendix C.

6 Preliminary Test and Test Setup

6.1 Channel Separation


Not Applicable

6.2 Minimum Hopping Channel

Not Applicable

6.3 Occupied Bandwidth

The test system is shown as follows:



The setting of the spectrum analyzer are shown as follows:


Res. Bandwidth	10 kHz
Video Bandwidth	30 kHz
Span	3 MHz
Sweep Time	AUTO
Trace	Maxhold

6.4 Dwell Time


Not Applicable

6.5 Peak Output Power and Peak Power Density

The Conducted RF Power Output was measured with a power meter, one 10dB attenuator and a short, low loss cable.



The Peak Power Density was measured with a power meter, one 10dB attenuator and a short, low loss cable.



6.6 Spurious Emission(Conduction)

The test system is shown as follows:



The setting of the spectrum analyzer are shown as follows:

Frequency Range	30 MHz - 25 GHz	Band-Edge
Res. Bandwidth	100 kHz	200 kHz
Video Bandwidth	300 kHz	200 kHz
Sweep Time	AUTO	AUTO
Trace	Maxhold	Maxhold


6.7 AC Powerline Conducted Emission

The preliminary tests were performed using the scan mode of test receiver or spectrum analyzer to observe the emissions characteristics of the EUT.

The EUT configuration, cable configuration and mode of operation were determined for producing the maximum level of emissions.

This configurations was used for final tests.

– Side View –



NOTE

AMN : Artificial Mains Network

6.8 Field Strength of Spurious Emission

6.8.1 Field Strength of Spurious Emission 9 kHz – 30 MHz

The preliminary tests were performed at the measurement distance that specified for compliance to determine the emission characteristics of the EUT.

The EUT configuration(in X, Y and Z axis), cable configuration and mode of operation were determined for producing the maximum level of emissions.

This configurations was used for the final tests.

– Side View –




6.8.2 Field Strength of Spurious Emission 30 MHz – 1000 MHz

The preliminary tests were performed at the measurement distance that specified for compliance to determine the emission characteristics of the EUT.

The EUT configuration(in X, Y and Z axis), cable configuration and mode of operation were determined for producing the maximum level of emissions.

This configurations was used for the final tests.

– Side View –




6.8.3 Field Strength of Spurious Emission above 1 GHz

The preliminary tests were performed at the measurement distance that specified for compliance to determine the emission characteristics of the EUT.

The EUT configuration(in X, Y and Z axis), cable configuration and mode of operation were determined for producing the maximum level of emissions.

This configurations was used for the final tests.

– Side View –



NOTE

The antenna height is scanned depending on the EUT's size and mounting height.

7 Equipment Under Test Modification

- No modifications were conducted by JQA to achieve compliance to the limitations.
 - To achieve compliance to the limitations, the following changes were made by JQA during the compliance test.

The modifications will be implemented in all production models of this equipment.

Applicant : Not Applicable

Date : Not Applicable

Typed Name : Not Applicable

Position : Not Applicable

Signatory : Not Applicable

8 Responsible PartyResponsible Party of Test Item (Product)

Responsible Party :	
Contact Person :	_____
	Signatory

9 Deviation from Standard

- No deviations from the standard described in clause 1.
 - The following deviations were employed from the standard described in clause 1.
-

10 Test Results**10.1 RF Power Output (§2.1046)****10.1.1 Channel Separation**

The requirements are - Applicable [- Tested. - Not tested by applicant request.]
 - Not Applicable

- Passed - Failed - Not judged

Channel Separation is _____ MHz
 Channel Separation(Inquiry) is _____ MHz

Uncertainty of Measurement Results at Frequency _____ kHz(2 σ)

Remarks : _____

10.1.2 Minimum Hopping Channel

The requirements are - Applicable [- Tested. - Not tested by applicant request.]
 - Not Applicable

Number of Channel is _____
 Number of Channel (Inquiry) is _____

Uncertainty of Measurement Results at Frequency _____ kHz(2 σ)

Remarks : _____

10.1.3 Occupied Bandwidth

The requirements are - Applicable [- Tested. - Not tested by applicant request.]
 - Not Applicable

- Passed - Failed - Not judged

The 99% Bandwidth of IEEE802.11b is 14.765 MHz at 2462.0 MHz
 The 99% Bandwidth of IEEE802.11g is 16.477 MHz at 2462.0 MHz

The 6dB Bandwidth of IEEE802.11b is 10.042 MHz at 2462.0 MHz
 The 6dB Bandwidth of IEEE802.11g is 16.571 MHz at 2462.0 MHz

Uncertainty of Measurement Results at Frequency +/-50.0 kHz(2 σ)
 Uncertainty of Measurement Results at Amplitude +/-0.24 dB(2 σ)

Remarks : _____

10.1.4 Dwell Time

The requirements are - Applicable [- Tested. - Not tested by applicant request.]
 - Not Applicable

- Passed - Failed - Not judged

Dwell Time is _____ msec

Dwell Time (Inquiry) is _____ msec

Uncertainty of Measurement Results at Frequency _____ μ sec(2 σ)

Remarks : _____

10.1.5 Peak Output Power(Conduction)

The requirements are - Applicable [- Tested. - Not tested by applicant request.]
 - Not Applicable

Peak Output Power of IEEE802.11b is 18.04 dBm at 2462.0 MHz

Peak Output Power of IEEE802.11g is 20.61 dBm at 2412.0 MHz

Uncertainty of Measurement Results at Amplitude +/-0.19 dB(2 σ)

Remarks : _____

10.1.6 Peak Power Density(Conduction)

The requirements are - Applicable [- Tested. - Not tested by applicant request.]
 - Not Applicable

Peak Power Density of IEEE802.11b is -6.79 dBm at 2462.0 MHz

Peak Power Density of IEEE802.11g is -12.96 dBm at 2462.0 MHz

Uncertainty of Measurement Results at Amplitude +/-0.24 dB(2 σ)

Remarks : _____

10.2 Spurious Emissions(Conduction)

The requirements are - Applicable - Tested. - Not tested by applicant request.]
 - Not Applicable

- Passed - Failed - Not judged

Uncertainty of Measurement Results at Amplitude +/-0.24 dB(2 σ)

Remarks : _____

10.3 AC Powerline Conducted Emission

The requirements are - Applicable - Tested. - Not tested by applicant request.]
 - Not Applicable

- Passed - Failed - Not judged

Min. Limit Margin (Quasi-Peak) 21.4 dB at 2.57 MHz

Max. Limit Exceeding (Quasi-Peak) _____ dB at _____ MHz

Uncertainty of Measurement Results +/-2.9 dB(2 σ)

Remarks : _____

10.4 Field Strength of Spurious Emission

The requirements are - Applicable - Tested. - Not tested by applicant request.]
 - Not Applicable

- Passed - Failed - Not judged

Min. Limit Margin (Average) >4.0 dB at 22158.0 MHz

Max. Limit Exceeding (Average) _____ dB at _____ MHz

Uncertainty of Measurement Results
9 kHz – 30 MHz +/-1.6 dB(2 σ)
30 MHz – 300 MHz +/-4.3 dB(2 σ)
300 MHz – 1000 MHz +/-4.5 dB(2 σ)
above 1 GHz +/-3.7 dB(2 σ)

Remarks : _____

11 Summary**General Remarks :**

The EUT was tested according to the requirements of the following standard.

CFR 47 FCC Rules and Regulations Part 15

The test configuration is shown in clause 12 to 14.

The conclusion for the test items of which are required by the applied regulation is indicated under the test results.

Determining compliance with the limits in this report was based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

Test Results :

The "as received" sample;

- fulfill the test requirements of the regulation mentioned on clause 1.
- doesn't fulfill the test requirements of the regulation mentioned on clause 1.

Reviewed by:

Tested by:



Shigeru Kinoshita
Deputy Manager
Testing Dept. EMC Div.
JQA KITA-KANSAI Testing Center



Akio Hosoda
Advisor
Testing Dept. EMC Div.
JQA KITA-KANSAI Testing Center

12 Operating Condition

Transmitting/Receiving

Transmitting frequency : 2412.0 MHz(1CH) – 2462.0 MHz(11CH)

Receiver frequency : 2412.0 MHz(1CH) – 2462.0 MHz(11CH)

Other Clock Frequency

RTC : 32.768 kHz

Reference : 26.0 MHz

WLAN : 40.0 MHz

13 Test Configuration

The equipment under test (EUT) consists of :

	Item	Manufacturer	Model No.	Serial No.	FCC ID
A	Cellular Phone	Sharp	945SH	004401/11/26 0163/4*1) 004401/11/26 0200/4*2)	APYHRO00124
B	Lithium-ion Battery	SANYO	SHBDA1	--	N/A
C	AC Charger	KYUSHU MITSUMI	ZTDAA1	--	N/A
D	Stereo Handsfree	HOSIDEN	RPHoHA019A FSB	--	N/A

*1) Used for AC Powerline Conducted Emission and Field Strength of Spurious Emission

*2) Used for Antenna Conducted Emission

The auxiliary equipment used for testing :


None

Type of Cable:


No.	Description	Identification (Manu. etc.)	Connector Shielded	Cable Shielded	Ferrite Core	Length (m)
1	DC Power Cord	--	NO	--	NO	1.5
2	Headset Cable	--	NO	--	NO	1.7

14 Equipment Under Test Arrangement (Drawings)

1) AC Charger used



2) Headset used



Appendix A: Test Data**A.1 Channel Separation**

Not Applicable

A.2 Minimum Hopping Channel

Not Applicable

A.3 Occupied Bandwidth

Test Date : May 10, 2010

Temp.:22°C, Humi:48%

The resolution bandwidth was set to about 1% of emission bandwidth, -6dBc display line was placed on the screen (or 99% bandwidth), the occupied bandwidth is the delta frequency between the two points where the display line intersects the signal trace.

A) IEEE 802.11b

1)Data Rate : 1Mbps

Channel	Frequency (MHz)	99% Bandwidth (MHz)	-6dBc Bandwidth (MHz)
01	2412.0	14.689	9.137
06	2437.0	14.804	9.604
11	2462.0	14.763	9.572

2)Data Rate : 2Mbps

Channel	Frequency (MHz)	99% Bandwidth (MHz)	-6dBc Bandwidth (MHz)
01	2412.0	14.726	9.588
06	2437.0	14.696	9.934
11	2462.0	14.765	10.042

3)Data Rate : 5.5Mbps

Channel	Frequency (MHz)	99% Bandwidth (MHz)	-6dBc Bandwidth (MHz)
01	2412.0	14.130	9.181
06	2437.0	14.205	8.965
11	2462.0	14.132	9.337

4)Data Rate : 11Mbps

Channel	Frequency (MHz)	99% Bandwidth (MHz)	-6dBc Bandwidth (MHz)
01	2412.0	14.312	9.660
06	2437.0	14.285	9.692
11	2462.0	14.507	8.799

B) IEEE 802.11g


5) Data Rate : 6Mbps

Channel	Frequency (MHz)	99% Bandwidth (MHz)	-6dBc Bandwidth (MHz)
01	2412.0	16.470	16.566
06	2437.0	16.470	16.558
11	2462.0	16.477	16.571


6) Data Rate : 54Mbps

Channel	Frequency (MHz)	99% Bandwidth (MHz)	-6dBc Bandwidth (MHz)
01	2412.0	16.427	16.506
06	2437.0	16.442	16.511
11	2462.0	16.434	16.511


1)Data Rate : 1Mbps(IEEE 802.11b)
Low Channel



Middle Channel



High Channel




2)Data Rate : 2Mbps(IEEE 802.11b)


Low Channel




Middle Channel




High Channel




3)Data Rate : 5.5Mbps(IEEE 802.11b)
Low Channel



Middle Channel




High Channel




4)Data Rate : 11Mbps(IEEE 802.11b)


Low Channel




Middle Channel




High Channel




5)Data Rate : 6Mbps(IEEE 802.11g)
Low Channel



Middle Channel




High Channel




6)Data Rate : 54Mbps(IEEE 802.11g)


Low Channel



Middle Channel



High Channel



A.4 Dwell Time

Not Applicable

A.5 Peak Output Power(Conduction)

1)Data Rate : 1Mbps(IEEE 802.11b)

Data Rate : 1Mbps						Test Date: May 10, 2010 Temp.: 22 °C. Humi: 48 %	
Transmitting Frequency	Correction Factor	Meter Reading	Conducted Peak Output Power		Limits	Margin	
CH [MHz]	[dB]	[dBm]	[dBm]	[mW]	[dBm]	[dB]	
01 2412	10.18	7.11	17.29	53.58	30.00	+12.71	
05 2437	10.18	7.64	17.82	60.53	30.00	+12.18	
11 2462	10.18	7.86	18.04	63.68	30.00	+11.96	

Calculated result at 2462.000 MHz, as the worst point shown on underline:		
Correction Factor	=	10.18 dB
+) Meter Reading	=	7.86 dBm
Result	=	18.04 dBm = 63.68 mW
Minimum Margin: 30.00 - 18.04 = 11.96 (dB)		

NOTES	
1. The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.	
2. Setting of measuring instrument(s) :	
Detector Function	Video B.W.
Peak	5 MHz

2)Data Rate : 2Mbps(IEEE 802.11b)

Data Rate : 2Mbps						Test Date: May 10, 2010 Temp.: 22 °C. Humi: 48 %	
Transmitting Frequency	Correction Factor	Meter Reading	Conducted Peak Output Power		Limits	Margin	
CH [MHz]	[dB]	[dBm]	[dBm]	[mW]	[dBm]	[dB]	
01 2412	10.18	7.11	17.29	53.58	30.00	+12.71	
05 2437	10.18	7.56	17.74	59.43	30.00	+12.26	
11 2462	10.18	7.59	17.77	59.84	30.00	+12.23	

Calculated result at 2462.000 MHz, as the worst point shown on underline:		
Correction Factor	=	10.18 dB
+) Meter Reading	=	7.59 dBm
Result	=	17.77 dBm = 59.84 mW
Minimum Margin: 30.00 - 17.77 = 12.23 (dB)		

NOTES	
1. The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.	
2. Setting of measuring instrument(s) :	
Detector Function	Video B.W.
Peak	5 MHz

3)Data Rate : 5.5Mbps(IEEE 802.11b)

Test Date: May 10, 2010
Temp.: 22 °C, Humi: 48 %

Data Rate : 5.5Mbps

CH	Transmitting Frequency	Correction Factor	Meter Reading	Conducted Peak Output Power		Limits	Margin
	[MHz]			[dBm]	[dBm]		
01	2412	10.18	6.87	17.05	50.70	30.00	+12.95
05	2437	10.18	7.31	17.49	56.10	30.00	+12.51
11	2462	10.18	7.59	17.77	59.84	30.00	+12.23

Calculated result at 2462.000 MHz, as the worst point shown on underline:	
Correction Factor	= 10.18 dB
+) Meter Reading	= 7.59 dBm
Result	= 17.77 dBm = 59.84 mW
Minimum Margin: 30.00 - 17.77 = 12.23 (dB)	

NOTES	
1. The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.	
2. Setting of measuring instrument(s) :	
Detector Function	Video B.W.
Peak	5 MHz

4)Data Rate : 11Mbps(IEEE 802.11b)

Test Date: May 10, 2010
Temp.: 22 °C, Humi: 48 %

Data Rate : 11Mbps

CH	Transmitting Frequency	Correction Factor	Meter Reading	Conducted Peak Output Power		Limits	Margin
	[MHz]			[dBm]	[dBm]		
01	2412	10.18	7.14	17.32	53.95	30.00	+12.68
05	2437	10.18	7.56	17.74	59.43	30.00	+12.26
11	2462	10.18	7.78	17.96	62.52	30.00	+12.04

Calculated result at 2462.000 MHz, as the worst point shown on underline:	
Correction Factor	= 10.18 dB
+) Meter Reading	= 7.78 dBm
Result	= 17.96 dBm = 62.52 mW
Minimum Margin: 30.00 - 17.96 = 12.04 (dB)	

NOTES	
1. The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.	
2. Setting of measuring instrument(s) :	
Detector Function	Video B.W.
Peak	5 MHz

5)Data Rate : 6Mbps(IEEE 802.11g)

Test Date: May 10, 2010
Temp.: 22 °C, Humi: 48 %

Data Rate : 6Mbps

CH	Transmitting Frequency [MHz]	Correction Factor [dB]	Meter Reading [dBm]	Conducted Peak Output Power		Limits [dBm]	Margin [dB]
				[dBm]	[mW]		
01	2412	10.03	10.58	20.61	115.08	30.00	+ 9.39
05	2437	10.03	10.40	20.43	110.41	30.00	+ 9.57
11	2462	10.03	10.29	20.32	107.65	30.00	+ 9.68

Calculated result at 2412.000 MHz, as the worst point shown on underline:

Correction Factor	=	10.03 dB
+) Meter Reading	=	10.58 dBm
Result	=	20.61 dBm = 115.08 mW

Minimum Margin: 30.00 - 20.61 = 9.39 (dB)

NOTES

- The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.
- Setting of measuring instrument(s) :

Detector Function	Video B.W.
Peak	5 MHz

6)Data Rate : 54Mbps(IEEE 802.11g)

Test Date: May 10, 2010
Temp.: 22 °C, Humi: 48 %

Data Rate : 54Mbps

CH	Transmitting Frequency [MHz]	Correction Factor [dB]	Meter Reading [dBm]	Conducted Peak Output Power		Limits [dBm]	Margin [dB]
				[dBm]	[mW]		
01	2412	10.03	10.38	20.41	109.90	30.00	+ 9.59
05	2437	10.03	10.44	20.47	111.43	30.00	+ 9.53
11	2462	10.03	10.44	20.47	111.43	30.00	+ 9.53

Calculated result at 2437.000 MHz, as the worst point shown on underline:

Correction Factor	=	10.03 dB
+) Meter Reading	=	10.44 dBm
Result	=	20.47 dBm = 111.43 mW

Minimum Margin: 30.00 - 20.47 = 9.53 (dB)

NOTES

- The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.
- Setting of measuring instrument(s) :

Detector Function	Video B.W.
Peak	5 MHz

A.6 Peak Power Density(Conduction)

1)Data Rate : 1Mbps(IEEE 802.11b)


Data Rate : 1Mbps						Test Date: May 11, 2010 Temp.: 23 °C, Humi: 47 %	
Transmitting Frequency	Correction Factor	Meter Reading	Conducted Peak Output Power		Limits	Margin	
CH	[MHz]	[dB]	[dBm]	[dBm]	[mW]	[dBm]	[dB]
01	2412	10.03	-16.94	-6.91	0.20	8.00	+14.91
05	2437	10.03	-16.88	-6.85	0.21	8.00	+14.85
11	2462	10.03	-16.82	-6.79	0.21	8.00	+14.79

Calculated result at 2462.000 MHz, as the worst point shown on underline:
 Correction Factor = 10.03 dB
 +) Meter Reading = -16.82 dBm
 Result = -6.79 dBm = 0.21 mW
 Minimum Margin: 8.00 - -6.79 = 14.79 (dB)


NOTES
 1. The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.
 2. Setting of measuring instrument(s) :

Detector Function	RES B.W.	Video B.W.
Peak	3kHz	10kHz


Low Channel



Middle Channel



High Channel



2)Data Rate : 2Mbps(IEEE 802.11b)

Test Date: May 11, 2010
Temp.: 23 °C, Humi: 47 %

Data Rate : 1Mbps

CH	Transmitting Frequency [MHz]	Correction Factor [dB]	Meter Reading [dBm]	Conducted Peak Output Power		Limits [dBm]	Margin [dB]
				[dBm]	[mW]		
01	2412	10.03	-17.90	-7.87	0.16	8.00	+15.87
05	2437	10.03	-18.75	-8.72	0.13	8.00	+16.72
11	2462	10.03	-17.28	-7.25	0.19	8.00	+15.25

Calculated result at 2462.000 MHz, as the worst point shown on underline:

Correction Factor	=	10.03 dB
+) Meter Reading	=	-17.28 dBm
Result	=	-7.25 dBm = 0.19 mW


Minimum Margin: 8.00 - 7.25 = 15.25 (dB)

NOTES

- The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.
- Setting of measuring instrument(s) :

Detector Function	RES B.W.	Video B.W.
Peak	3kHz	10kHz

Low Channel



3)Data Rate : 5.5Mbps(IEEE 802.11b)

Data Rate : 1Mbps

Test Date: May 11, 2010
Temp: 23 °C, Humi: 47 %


CH	Transmitting Frequency [MHz]	Correction Factor [dB]	Meter Reading [dBm]	Conducted Peak Output Power		Limits [dBm]	Margin [dB]
				[dBm]	[mW]		
01	2412	10.03	-18.24	-8.21	0.15	8.00	+16.21
05	2437	10.03	-17.55	-7.52	0.18	8.00	+15.52
11	2462	10.03	-18.21	-8.18	0.15	8.00	+16.18

Calculated result at 2437.000 MHz, as the worst point shown on underline:
 Correction Factor = 10.03 dB
 +) Meter Reading = -17.55 dBm
 Result = -7.52 dBm = 0.18 mW
 Minimum Margin: 8.00 - -7.52 = 15.52 (dB)


NOTES
 1. The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.
 2. Setting of measuring instrument(s):

Detector Function	RES B.W.	Video B.W.
Peak	3kHz	10kHz


Low Channel



Middle Channel



High Channel



4)Data Rate : 11Mbps(IEEE 802.11b)

Data Rate : 11Mbps

Test Date: May 11, 2010
Temp.: 23 °C. Humi: 47 %

CH	Transmitting Frequency		Correction Factor [dB]	Meter Reading [dBm]	Conducted Peak Output Power		Limits [dBm]	Margin [dB]
	[MHz]				[dBm]	[mW]		
01	2412		10.03	-19.04	-9.01	0.13	8.00	+17.01
05	2437		10.03	-18.30	-8.27	0.15	8.00	+16.27
11	2462		10.03	-17.83	-7.80	0.17	8.00	+15.80

Calculated result at 2462.000 MHz, as the worst point shown on underline:

Correction Factor	=	10.03 dB
+) Meter Reading	=	-17.83 dBm
Result	=	-7.80 dBm = 0.17 mW


Minimum Margin: 8.00 - -7.80 = 15.80 (dB)

NOTES

- The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.
- Setting of measuring instrument(s) :

Detector Function	RES B.W.	Video B.W.
Peak	3kHz	10kHz

Low Channel



5)Data Rate : 6Mbps(IEEE 802.11g)

Data Rate : 6Mbps

Test Date: May 11, 2010
Temp.: 23 °C. Humi: 47 %


CH	Transmitting Frequency [MHz]	Correction Factor [dB]	Meter Reading [dBm]	Conducted Peak Output Power		Limits [dBm]	Margin [dB]
				[dBm]	[mW]		
01	2412	10.03	-23.92	-13.89	0.04	8.00	+21.89
05	2437	10.03	-24.17	-14.14	0.04	8.00	+22.14
11	2462	10.03	-22.99	-12.96	0.05	8.00	+20.96

Calculated result at 2462.000 MHz, as the worst point shown on underline:
 Correction Factor = 10.03 dB
 +) Meter Reading = -22.99 dBm
 Result = -12.96 dBm = 0.05 mW
 Minimum Margin: 8.00 - -12.96 = 20.96 (dB)


NOTES
 1. The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.
 2. Setting of measuring instrument(s):

Detector Function	RES B.W.	Video B.W.
Peak	3kHz	10kHz


Low Channel



Middle Channel



High Channel



6)Data Rate : 54Mbps(IEEE 802.11g)

Data Rate : 6Mbps

Test Date: May 11, 2010
Temp.: 23 °C, Humi: 47 %

CH	Transmitting Frequency [MHz]	Correction Factor [dB]	Meter Reading [dBm]	Conducted Peak Output Power [dBm]	[mW]	Limits [dBm]	Margin [dB]
01	2412	10.03	-23.89	-13.86	0.04	8.00	+21.86
05	2437	10.03	-23.69	-13.66	0.04	8.00	+21.66
11	2462	10.03	-23.84	-13.81	0.04	8.00	+21.81

Calculated result at 2437.000 MHz, as the worst point shown on underline:

Correction Factor	=	10.03 dB
+) Meter Reading	=	-23.69 dBm
Result	=	-13.66 dBm = 0.04 mW


Minimum Margin: 8.00 - -13.66 = 21.66 (dB)

NOTES

- The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.
- Setting of measuring instrument(s) :

Detector Function	RES B.W.	Video B.W.
Peak	3kHz	10kHz

Low Channel




A.7 Spurious Emission(Conduction)

Test Date : May 11, 2010


Temp.:23C, Humi:47%

1)Data Rate : 1Mbps(IEEE 802.11b)


Low Channel



Middle Channel




High Channel




2)Data Rate : 11Mbps(IEEE 802.11b)


Low Channel




Middle Channel




High Channel




3)Data Rate : 6Mbps(IEEE 802.11g)
Low Channel



Middle Channel




High Channel




4)Data Rate : 54Mbps(IEEE 802.11g)


Low Channel



Middle Channel




High Channel




Band-Edge Emission


1)Data Rate : 1Mbps(IEEE 802.11b)
Low Channel




High Channel



2)Data Rate : 6Mbps(IEEE 802.11g)
Low Channel



High Channel




A.8 AC Powerline Conducted Emission

Mode of EUT : All modes have been investigated and the worst case mode for channel (06ch: 2437MHz / IEEE 802.11b and IEEE 802.11b) has been listed.

Test Date: April 22, 2010
Temp.: 24 °C, Humi: 47 %

Frequency [MHz]	Corr. Factor [dB]	Meter Readings [dB(μV)]				Limits [dB(μV)]		Results [dB(μV)]		Margin [dB]	Remarks
		VA		VB		QP	AVE	QP	AVE		
0.28	9.9	22.6	--	26.0	--	60.8	50.8	35.9	--	+24.9	-
0.29	9.9	19.5	--	22.4	--	60.5	50.5	32.3	--	+28.2	-
0.57	9.9	< 10.0	--	< 10.0	--	56.0	46.0	< 19.9	--	> +36.1	-
1.43	10.0	13.2	--	13.2	--	56.0	46.0	23.2	--	+32.8	-
2.00	10.0	< 10.0	--	< 10.0	--	56.0	46.0	< 20.0	--	> +36.0	-
2.57	10.0	24.6	--	18.9	--	56.0	46.0	34.6	--	+21.4	-
3.71	10.1	22.7	--	16.9	--	56.0	46.0	32.8	--	+23.2	-



NOTES

1. The spectrum was checked from 0.15 MHz to 30 MHz.
2. The correction factor includes the AMN insertion loss and the cable loss.
3. The symbol of "<" means "or less".
4. The symbol of ">" means "more than".
5. The symbol of "--" means "not applicable".
6. Calculated result at 2.57 MHz, as the worst point shown on underline:
Correction Factor + Meter Reading = 10.0 + 24.6 = 34.6 dB(μV)
7. QP : Quasi-Peak Detector / AVE : Average Detector
8. Test receiver setting(s) : CISPR QP 9 kHz / Average 9 kHz


A.9 Field Strength of Spurious Radiation
A.9.1 Band-edge Compliance

Test Date : April 28, 2010

Temp.:21°C, Humi:31%

Mode of EUT : TX(1ch: 2412 MHz, data rate : 1Mbps(IEEE 802.11b))


Antenna Polarization : Horizontal



Note: The trace 1 is Peak detection. The trace 2 is Average detection.

Mode of EUT : TX(1ch: 2412 MHz, data rate : 1Mbps(IEEE 802.11b))


Antenna Polarization : Vertical



Note: The trace 1 is Peak detection. The trace 2 is Average detection.

Mode of EUT : TX(11ch: 2462 MHz, data rate : 1Mbps(IEEE 802.11b))


Antenna Polarization : Horizontal



Note: The trace 1 is Peak detection. The trace 2 is Average detection.


Mode of EUT : TX(11ch: 2462 MHz, data rate : 1Mbps(IEEE 802.11b))

Antenna Polarization : Vertical




Note: The trace 1 is Peak detection. The trace 2 is Average detection.

Mode of EUT : TX(1ch: 2412 MHz, data rate : 6Mbps(IEEE 802.11g))
 Antenna Polarization : Horizontal




Note: The trace 1 is Peak detection. The trace 2 is Average detection.

Mode of EUT : TX(1ch: 2412 MHz, data rate : 6Mbps(IEEE 802.11g))
 Antenna Polarization : Vertical



Note: The trace 1 is Peak detection. The trace 2 is Average detection.


Mode of EUT : TX(11ch: 2462 MHz, data rate : 6Mbps(IEEE 802.11g))
 Antenna Polarization : Horizontal



Note: The trace 1 is Peak detection. The trace 2 is Average detection.

Mode of EUT : TX(11ch: 2462 MHz, data rate : 6Mbps(IEEE 802.11g))

Antenna Polarization : Vertical



Note: The trace 1 is Peak detection. The trace 2 is Average detection.

A.9.2 Other Spurious Emission

A.9.2.1 Other Spurious Emission(9kHz – 30MHz)

Test Date : April 23, 2010

Temp.:16°C, Humi:56%

Mode of EUT : All modes have been investigated and the worst case mode for channel (06ch: 2437MHz / IEEE 802.11b and IEEE 802.11g) has been listed.

Results : No spurious emissions in the range 20dB below the limit.


A.9.2.2 Other Spurious Emission(30MHz – 1000MHz)

Mode of EUT : All modes have been investigated and the worst case mode for channel (06ch: 2437MHz / IEEE802.11b and IEEE802.11g) has been listed.

Test Date: April 23, 2010

Temp: 16 °C, Humi: 56 %

Frequency [MHz]	Antenna Factor [dB(1/m)]	Cable Loss [dB]	Meter Readings [dB(μV)]		Limits [dB(μV/m)]	Results [dB(μV/m)]		Margin [dB]	Remarks
			Hori.	Vert.		Hori.	Vert.		
66.4	8.2	1.4	< 0.0	< 0.0	40.0	< 9.6	< 9.6	> +30.4	-
260.0	17.5	3.1	7.4	< 0.0	46.0	28.0	< 20.6	+18.0	-
285.7	17.9	3.3	< 0.0	< 0.0	46.0	< 21.2	< 21.2	> +24.8	-
312.0	14.1	3.5	2.5	< 0.0	46.0	20.1	< 17.6	+25.9	-
342.8	14.6	3.7	15.4	3.5	46.0	33.7	21.8	+12.3	-



NOTES

1. Test Distance : 3 m
2. The spectrum was checked from 30 MHz to 1000 MHz.
3. The symbol of "<" means "or less".
4. The symbol of ">" means "more than".
5. Calculated result at 342.8 MHz, as the worst point shown on underline:
Antenna Factor + Cable Loss + Meter Reading = 14.6 + 3.7 + 15.4 = 33.7 dB(μV/m)
6. Test receiver setting(s) : CISPR QP 120 kHz (QP : Quasi-Peak)

A.9.2.3 Other Spurious Emission(Above 1000MHz)

Mode of EUT : TX(IEEEE802.11b / IEEEE 802.11g)

Test Date: April 19, 2010
Temp.: 24 °C, Humi: 43 %

Frequency [MHz]	Antenna Factor [dB(1/m)]	Corr. Factor [dB]	Meter Readings [dB(μV)]				Limits [dB(μV/m)]		Results [dB(μV/m)]		Margin [dB]	Remarks
			Horizontal		Vertical		PK	AVE	PK	AVE		
Test condition : Tx Low Ch												
4824.0	27.4	-20.8	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 46.6	< 36.6	> +17.4	A/B
12060.0	33.7	-25.5	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 48.2	< 38.2	> +15.8	A/B
19296.0	40.4	-21.5	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 58.9	< 48.9	> + 5.1	A/B
Test condition : TX Middle Ch												
4874.0	27.3	-20.7	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 46.6	< 36.6	> +17.4	A/B
7311.0	29.8	-19.0	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 50.8	< 40.8	> +13.2	A/B
12185.0	33.6	-25.4	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 48.2	< 38.2	> +15.8	A/B
19496.0	40.4	-21.5	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 58.9	< 48.9	> + 5.1	A/B
Test condition : TX High Ch												
4924.0	27.3	-20.8	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 46.5	< 36.5	> +17.5	A/B
7386.0	29.8	-18.8	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 51.0	< 41.0	> +13.0	A/B
12310.0	33.6	-25.4	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 48.2	< 38.2	> +15.8	A/B
19696.0	40.4	-21.4	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 59.0	< 49.0	> + 5.0	A/B
22158.0	40.6	-20.6	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 60.0	< 50.0	> + 4.0	A/B

Calculated result at 19696.0 MHz, as the worst point shown on underline:

Antenna Factor = 40.4 dB(1/m)
 Corr. Factor = -21.4 dB
 +) Meter Reading = <30.0 dB(μV)
 Result = <49.0 dB(μV/m)

Minimum Margin: 54.0 - <49.0 = >4.0 (dB)

NOTES

- Test Distance : 3 m
- The spectrum was checked from 1 GHz to 25 GHz (10th harmonic of the highest fundamental frequency).
- The correction factor is shown as follows:
 Corr. Factor [dB] = Cable Loss + 20dB Pad Att. - Pre-Amp. Gain [dB] (1.0 - 7.6GHz)
 Corr. Factor [dB] = Cable Loss + 10dB Pad Att. - Pre-Amp. Gain [dB] (7.6 - 18.0GHz)
 Corr. Factor [dB] = Cable Loss - Pre-Amp. Gain [dB] (over 18 GHz)
- The symbol of "<" means "or less".
- The symbol of ">" means "more than".
- PK : Peak Detector / AVE : Average Detector
- Setting of measuring instrument(s) :

	Detector Function	Resolution B.W.	Video B.W.	Sweep Time
A	Peak	1 MHz	1 MHz	AUTO
B	Peak	1 MHz	10 Hz	AUTO

Mode of EUT : RX(IEEEE802.11b / IEEEE 802.11g)

Test Date: April 19, 2010
Temp.: 24 °C, Humi: 43 %

Frequency [MHz]	Antenna Factor [dB(1/m)]	Corr. Factor [dB]	Meter Readings [dB(μV)]				Limits [dB(μV/m)]		Results [dB(μV/m)]		Margin [dB]	Remarks
			Horizontal		Vertical		PK	AVE	PK	AVE		
			PK	AVE	PK	AVE	PK	AVE	PK	AVE		
Test condition : RX Middle Ch												
2437.0	21.5	-21.8	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 39.7	< 29.7	> +24.3	A/B
4874.0	27.3	-21.0	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 46.3	< 36.3	> +17.7	A/B
7311.0	29.8	-19.3	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 50.5	< 40.5	> +13.5	A/B

Calculated result at 4874.0 MHz, as the worst point shown on underline:

Antenna Factor = 27.3 dB(1/m)

Corr. Factor = -21.0 dB

+) Meter Reading = <30.0 dB(μV)

Result = <36.3 dB(μV/m)

Minimum Margin: 54.0 - <36.3 = >13.5 (dB)

NOTES

1. Test Distance : 3 m
2. The spectrum was checked from 1 GHz to 25 GHz (10th harmonic of the highest fundamental frequency).
3. The correction factor is shown as follows:
Corr. Factor [dB] = Cable Loss + 20dB Pad Att. - Pre-Amp. Gain [dB] (1.0 - 7.6GHz)
4. The symbol of "<" means "or less".
5. The symbol of ">" means "more than".
6. PK : Peak Detector / AVE : Average Detector
7. Setting of measuring instrument(s) :

	Detector Function	Resolution B.W.	Video B.W.	Sweep Time
A	Peak	1 MHz	1 MHz	AUTO
B	Peak	1 MHz	10 Hz	AUTO

Appendix B: Test Arrangement (Photographs)

B.1 AC Powerline Conducted Emission

This page is CONFIDENTIAL.

B.2 Radiated Emission

This page is CONFIDENTIAL.

Appendix C: Test Instruments

C.1 Channel Separation

Not Applicable

C.2 Minimum Hopping Channel

Not Applicable

C.3 Occupied Bandwidth

Type	Model	Manufacturer	ID No.	Last Cal.	Interval
Spectrum Analyzer	E4446A	Agilent	A-39	2010/1	1 Year
Attenuator	54A-10	Weinschel	D-29	2009/9	1 Year
RF Cable	SUCOFLEX102	SUHNER	C-52	2009/6	1 Year

C.4 Dwell Time

Not Applicable

C.5.1 Peak Output Power (Conduction)

Type	Model	Manufacturer	ID No.	Last Cal.	Interval
Power Meter	N1911A	Agilent	B-63	2009/6	1 Year
Power Sensor	N1921A	Agilent	B-64	2009/6	1 Year
Attenuator	54A-10	Weinschel	D-29	2009/9	1 Year
RF Cable	SUCOFLEX102	SUHNER	C-52	2009/6	1 Year

C.5.2 Peak Output Power Density (Conduction)

Type	Model	Manufacturer	ID No.	Last Cal.	Interval
Spectrum Analyzer	E4446A	Agilent	A-39	2010/1	1 Year
Attenuator	54A-10	Weinschel	D-29	2009/9	1 Year
RF Cable	SUCOFLEX102	SUHNER	C-52	2009/6	1 Year

C.6 Spurious Emission (Conduction)

Type	Model	Manufacturer	ID No.	Last Cal.	Interval
Spectrum Analyzer	E4446A	Agilent	A-39	2010/1	1 Year
Attenuator	54A-10	Weinschel	D-29	2009/9	1 Year
RF Cable	SUCOFLEX102	SUHNER	C-52	2009/6	1 Year

C.7 AC Power Conducted Emission

Type	Model	Manufacturer	ID No.	Last Cal.	Interval
Test Receiver	ESCI	Rohde & Schwarz	A-42	2009/11	1 Year
AMN (main)	KNW-407R	Kyoritsu	D-39	2009/9	1 Year
Attenuator	MP721C	Anritsu	D-105	2009/9	1 Year
RF Cable	---	----	H-33	2009/4	1 Year

C.8 Radiated Emission

C.8.1 Radiated Emission 9 kHz – 30 MHz

Type	Model	Manufacturer	ID No.	Last Cal.	Interval
Test Receiver	ESCS 30	Rohde & Schwarz	A-1	2010/2	1 Year
Loop Antenna	HFH2-Z2	Rohde & Schwarz	C-3	2009/8	1 Year
RF Cable	RG213/U	Rohde & Schwarz	H-29	2009/8	1 Year

C.8.2 Radiated Emission 30MHz – 1000 MHz

Type	Model	Manufacturer	ID No.	Last Cal.	Interval
Test Receiver	ESVS 10	Rohde & Schwarz	A-5	2009/10	1 Year
Biconical Antenna	VHA9103/FBAB9177	Schwarzbeck	C-25	2009/5	1 Year
Log-periodic Antenna	UHALP9108-A1	Schwarzbeck	C-28	2009/5	1 Year
RF Cable	--	----	H-2	2009/5	1 Year
Site Attenuation	--	----	H-12	2009/11	1 Year

C.8.3 Radiated Emission Above 1000 MHz

Type	Model	Manufacturer	ID No.	Last Cal.	Interval
Spectrum Analyzer	E4446A	Agilent	A-39	2010/1	1 Year
RF Cable	SUCOFLEX104	SUHNER	C-40-11	2010/1	1 Year
RF Cable	SUCOFLEX104	SUHNER	C-40-14	2010/1	1 Year
RF Cable	SUCOFLEX102	SUHNER	C-54	2010/1	1 Year
RF Cable	SUCOFLEX102EA	SUHNER	C-69	2010/1	1 Year
Attenuator	2-10	Weinschel	D-79	2009/9	1 Year
Attenuator	54-10	Weinschel	D-82	2009/6	1 Year
Pre-Amplifier	WJ-6611-513	Watkins Johnson	A-23	2010/1	1 Year
Pre-Amplifier	WJ-6882-824	Watkins Johnson	A-21	2010/1	1 Year
Pre-Amplifier	DBL-0618N515	DBS Microwave	A-33	2010/1	1 Year
Pre-Amplifier	BZ1804LD1	B&T Technologies	A-29	2010/1	1 Year
Band Rejection Filter	BRM50701	MICRO-TRONICS	D-93	2010/2	1 Year
Horn Antenna	91888-2	EATON	C-41-1	2009/6	1 Year
Horn Antenna	91889-2	EATON	C-41-2	2009/6	1 Year
Horn Antenna	91889-2	EATON	C-40-2	2009/6	1 Year
Horn Antenna	3160-05	EMCO	C-55	2009/6	2 Years
Horn Antenna	3160-06	EMCO	C-57	2009/6	2 Years
Horn Antenna	3160-07	EMCO	C-58	2009/6	2 Years
Horn Antenna	3160-08	EMCO	C-59	2009/6	2 Years
Horn Antenna	3160-09	EMCO	C-48	2009/6	2 Years