



Product Service

**Choose certainty.
Add value.**

Report On

Limited FCC Testing of the
Sharp CDMA SHI14 Dual Band CDMA (800 MHz, BC0 and 1900 MHz,
BC6) Cellular Phone with Bluetooth, WLAN, FeliCa and GPS
In accordance with FCC CFR 47 Part 15C

COMMERCIAL-IN-CONFIDENCE

FCC ID: APYHRO00163

Document 75915808 Report 07 Issue 1

December 2011



Product Service

TÜV SÜD Product Service Ltd, Octagon House, Concorde Way, Segensworth North,
Fareham, Hampshire, United Kingdom, PO15 5RL
Tel: +44 (0) 1489 558100. Website: www.tuvps.co.uk

COMMERCIAL-IN-CONFIDENCE

REPORT ON

Limited FCC Testing of the
Sharp CDMA SH114 Dual Band CDMA (800 MHz, BC0 and 1900
MHz, BC6) Cellular Phone with Bluetooth, WLAN, FeliCa and GPS
In accordance with FCC CFR 47 Part 15C

Document 75915808 Report 07 Issue 1

December 2011

PREPARED FOR

Sharp Communication Compliance Ltd
Azure House
Bagshot Road
Bracknell
Berkshire
RG12 7QY

PREPARED BY

Natalie Bennett
Senior Administrator

APPROVED BY

Mark Jenkins
Authorised Signatory

DATED

08 December 2011

ENGINEERING STATEMENT

The measurements shown in this report were made in accordance with the procedures described on test pages. All reported testing was carried out on a sample equipment to demonstrate limited compliance with FCC CFR 47 Part 15C. The sample tested was found to comply with the requirements defined in the applied rules.

Test Engineer(s);

G Lawler





CONTENTS

Section	Page No
1	REPORT SUMMARY 3
1.1	Introduction 4
1.2	Brief Summary of Results 5
1.3	Application Form 6
1.4	Product Information 11
1.5	Test Conditions 11
1.6	Deviations from the Standard 11
1.7	Modification Record 11
2	TEST DETAILS 12
2.1	Spurious and Band Edge Emissions 13
3	TEST EQUIPMENT USED 29
3.1	Test Equipment Used 30
3.2	Measurement Uncertainty 31
4	ACCREDITATION, DISCLAIMERS AND COPYRIGHT 32
4.1	Accreditation, Disclaimers and Copyright 33



Product Service

SECTION 1

REPORT SUMMARY

Limited FCC Testing of the
Sharp CDMA SHI14 Dual Band CDMA (800 MHz, BC0 and 1900 MHz, BC6) Cellular Phone
with Bluetooth, WLAN, FeliCa and GPS
In accordance with FCC CFR 47 Part 15C



1.1 INTRODUCTION

The information contained in this report is intended to show verification of the Limited FCC Testing of the Sharp CDMA SHI14 Dual Band CDMA (800 MHz, BC0 and 1900 MHz, BC6) Cellular Phone with Bluetooth, WLAN, FeliCa and GPS to the requirements of FCC CFR 47 Part 15C.

Objective	To perform Limited FCC Testing to determine the Equipment Under Test's (EUT's) compliance with the Test Specification, for the series of tests carried out.
Manufacturer	Sharp Corporation
Model Number(s)	CDMA SHI14
Serial Number(s)	SSHFA002157
Number of Samples Tested	1
Test Specification/Issue/Date	FCC CFR 47 Part 15C (2010)
Incoming Release Date	Application Form 24 October 2011
Disposal Reference Number Date	Held Pending Disposal Not Applicable Not Applicable
Order Number Date	8857 07 November 2011
Start of Test	9 November 2011
Finish of Test	21 November 2011
Name of Engineer(s)	G Lawler
Related Document(s)	ANSI C63.10: 2009



Product Service

1.2 BRIEF SUMMARY OF RESULTS

A brief summary of the tests carried out in accordance with FCC CFR 47 Part 15C is shown below.

Section	Spec Clause	Test Description	Result	Comments/Base Standard
802.11(b)				
2.1	15.247 (d)	Spurious and Band Edge Emissions	Pass	
802.11(g)				
2.1	15.247 (d)	Spurious and Band Edge Emissions	Pass	
802.11(n)				
2.1	15.247 (d)	Spurious and Band Edge Emissions	Pass	



Product Service

1.3 APPLICATION FORM

EQUIPMENT DESCRIPTION	
Model Name/Number	CDMA SHI14
Part Number	
FCC ID (if applicable)	APYHRO00163
Industry Canada ID (if applicable)	
Technical Description (Please provide a brief description of the intended use of the equipment)	Dual-Band CDMA(800MHz_BC0, 1900MHz_BC6) Cellular Phone with Bluetooth, W-LAN, FeliCa and GPS receiver.

EXTREME TEMPERATURE RANGE over which the equipment is to be type tested	
<input type="checkbox"/> -20°C to +55°C	
<input checked="" type="checkbox"/> Other (2)	
<input type="checkbox"/> Not applicable (no extreme temperature testing required)	
Extreme temperature range for the host(s):	-20C to +60C

- (2) The equipment shall be tested over the following temperature ranges :
- a) 0°C to +35°C for equipment for indoor use only, or intended for used in areas where the temperature is controlled within this range.
 - b) Over the extremes of the temperature range(s) of the declared host equipment(s) in case of plug-in radio devices.

TYPE OF ANTENNA	
<input checked="" type="checkbox"/> Integral	
Temporary RF connector provided:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
<input type="checkbox"/> Antenna connector	
<input type="checkbox"/> Number of antenna assembly(ies) submitted	
Gain of the antenna intended for normal use:	
0 dBi for assembly identified as Bluetooth	
0 dBi for assembly identified as WLAN	
dBi for assembly identified as	
dBi for assembly identified as	
dBi for assembly identified as	

TRANSMITTER TECHNICAL CHARACTERISTICS		
TRANSMITTER OPERATING FREQUENCY RANGE(S)		
	FCC and/or Industry Canada	EU
Bluetooth	2402 to 2480 MHz	2402 to 2480 MHz
WLAN	2412 to 2462 MHz	2412 to 2472 MHz
FCC and/or Industry Canada (only)		
Highest Internally Generated Frequency 1401.6 MHz		



SPREAD SPECTRUM PARAMETERS			
<input checked="" type="checkbox"/> Bluetooth			
FHSS: Channel <input checked="" type="checkbox"/> 79 Other	EDR <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		
Medium Access Protocol (Customer Declaration)			
"We have implemented Bluetooth protocol which satisfies the medium access protocol requirement of EN 300 328".			
<input checked="" type="checkbox"/> WLAN			
IEEE 802.11(b) – DSSS <input checked="" type="checkbox"/>			
IEEE 802.11(g) – OFDM <input checked="" type="checkbox"/>			
IEEE 802.11(n) – OFDM <input checked="" type="checkbox"/>			
Supported Spatial Streams	2.4 GHz	5GHz	
Transmitter (Tx)	Yes	No	
Receiver (Rx)	Yes	No	
GI (Guard Interval) <input checked="" type="checkbox"/> 800 ns <input type="checkbox"/> 400 ns			
Band Width <input checked="" type="checkbox"/> 20 MHz <input type="checkbox"/> 40 MHz			
<input type="checkbox"/> Other Technology			
Direct Sequence <input type="checkbox"/>	Frequency Hopping <input type="checkbox"/>	Combined <input type="checkbox"/>	Other <input type="checkbox"/>
DSSS	Chip Sequence Length	bit	
	Spectrum Width	MHz	
FHSS	Total Number of Hops		
	Dwell Time	ms	
	Bandwidth Per Hop	MHz	
	Maximum Separation of Hops	MHz for ETSI EN 300 328	
Other			
Medium Access Protocol (Customer Declaration)			
"We have implemented IEEE 802.11 (b/g/n) protocol which satisfies the medium access protocol requirement of EN 300 328".			



TRANSMITTER POWER CHARACTERISTICS				
Bluetooth				
Maximum Rated Transmitter Output				
Effective radiated power (for equipment with antenna connector)	0.0025	W		
Effective radiated power (for equipment with integral antenna)	0.0025	W		
Minimum Rated Transmitter Output				
Effective radiated power (for equipment with antenna connector)	0.00025	W		
Effective radiated power (for equipment with integral antenna)	0.00025	W		
Is transmitter intended for :				
Continuous duty	<input checked="" type="checkbox"/>	Yes	<input type="checkbox"/>	No
Intermittent duty	<input type="checkbox"/>	Yes	<input checked="" type="checkbox"/>	No
If intermittent state DUTY CYCLE				
Transmitter ON	seconds	Transmitter OFF	minutes	
Is continuous operation possible for testing purposes?				
	<input checked="" type="checkbox"/>	Yes	<input type="checkbox"/>	No
Is transmitter output power variable:				
	<input type="checkbox"/>	Yes	<input checked="" type="checkbox"/>	No
State during the test:				
Transmitter duty cycle	Tx on	Seconds	Tx Off	Seconds
Duty cycle (Tx on / (Tx on +Tx off))				
	%			
<input type="checkbox"/>	Continuously variable	<input type="checkbox"/>	Stepped	
	dB per step			
WLAN				
Maximum Rated Transmitter Output				
Effective radiated power (for equipment with antenna connector)	0.065(b/0.025(g.n	W		
)			
Effective radiated power (for equipment with integral antenna)	0.065(b/0.025(g/n	W		
)			
Minimum Rated Transmitter Output				
Effective radiated power (for equipment with antenna connector)		W		
Effective radiated power (for equipment with integral antenna)		W		
Is transmitter intended for :				
Continuous duty	<input checked="" type="checkbox"/>	Yes	<input type="checkbox"/>	No
Intermittent duty	<input type="checkbox"/>	Yes	<input type="checkbox"/>	No
If intermittent state DUTY CYCLE				
Transmitter ON	seconds	Transmitter OFF	minutes	
Is continuous operation possible for testing purposes?				
	<input checked="" type="checkbox"/>	Yes	<input type="checkbox"/>	No
Is transmitter output power variable:				
	<input type="checkbox"/>	Yes	<input checked="" type="checkbox"/>	No
State during the test:				
Transmitter duty cycle	Tx on	Seconds	Tx Off	Seconds
Duty cycle (Tx on / (Tx on +Tx off))				
	%			
<input type="checkbox"/>	Continuously variable	<input type="checkbox"/>	Stepped	
	dB per step			



Product Service

TRANSMITTER POWER SOURCE (3)				
<input checked="" type="checkbox"/> Common power source for transmitter and receiver				
<input type="checkbox"/> AC mains				
AC supply frequency	(Hz)	VAC	Max Current	Hz
<input type="checkbox"/> Single phase		<input type="checkbox"/> Three phase		
And / Or				
<input type="checkbox"/> External DC supply				
Nominal voltage		Max Current A		
Extreme upper voltage		Extreme lower voltage		
Battery				
<input type="checkbox"/> Nickel Cadmium				
<input type="checkbox"/> Lead acid (Vehicle regulated)				
<input type="checkbox"/> Alkaline				
<input checked="" type="checkbox"/> Lithium				
<input type="checkbox"/> Other Details :				
4.0 Volts nominal.				
End point voltage as quoted by equipment manufacturer		3.7 V		

(3) If a transmitter and receiver use the same power source, this should be declared. In such cases only the box for the transmitter power source should be filled in.

AUTOMATIC EQUIPMENT SWITCH OFF	
If the equipment is designed to automatically switch off at a predetermined voltage level which is higher or lower in value than the battery minimum and minimum calculated values this shall be clearly stated.	
<input checked="" type="checkbox"/> Applies	3.4 V cut-off voltage
<input type="checkbox"/> Does not apply	



Product Service

RECEIVER POWER SOURCE (4)				
<input type="checkbox"/> AC mains		State voltage		
AC supply frequency	(Hz)	VAC	Max Current	Hz
<input type="checkbox"/> Single phase		<input type="checkbox"/> Three phase		
And / Or				
<input type="checkbox"/> External DC supply				
Nominal voltage		Max Current		A
Extreme upper voltage		Extreme lower voltage		
Battery				
<input type="checkbox"/> Nickel Cadmium				
<input type="checkbox"/> Lead acid (Vehicle regulated)				
<input type="checkbox"/> Alkaline				
<input type="checkbox"/> Lithium				
<input type="checkbox"/> Other Details :				
	Volts nominal.			
End point voltage as quoted by equipment manufacturer				V

(4) If a transmitter and receiver use the same power source, this should be declared. In such cases only the box for the transmitter power source should be filled in.

AUTOMATIC EQUIPMENT SWITCH OFF	
If the equipment is designed to automatically switch off at a predetermined voltage level which is higher or lower in value than the battery minimum and minimum calculated values this shall be clearly stated.	
<input type="checkbox"/> Applies	V cut-off voltage
<input type="checkbox"/> Does not apply	

I hereby declare that I am entitled to sign on behalf of the applicant and that the information supplied is correct and complete.

Signature: Yasuhiro Kawauchi Name: Yasuhiro Kawauchi
 Position held: Manager Date: 24th, October 2011



Product Service

1.4 PRODUCT INFORMATION

1.4.1 Technical Description

The Equipment Under Test (EUT) was a Sharp CDMA SHI14 Dual Band CDMA (800 MHz, BC0 and 1900 MHz, BC6) Cellular Phone with Bluetooth, WLAN, FeliCa and GPS. A full technical description can be found in the manufacturer's documentation.

1.5 TEST CONDITIONS

For all tests the EUT was set up in accordance with the relevant test standard and to represent typical operating conditions. Tests were applied with the EUT situated in a shielded enclosure.

The EUT was powered from a 4.0 V DC supply.

FCC Accreditation
90987 Octagon House, Fareham Test Laboratory

1.6 DEVIATIONS FROM THE STANDARD

No deviations from the applicable test standard or test plan were made during testing.

1.7 MODIFICATION RECORD

Modification 0 - No modifications were made to the test sample during testing.



Product Service

SECTION 2

TEST DETAILS

Limited FCC Testing of the
Sharp CDMA SHI14 Dual Band CDMA (800 MHz, BC0 and 1900 MHz, BC6) Cellular Phone
with Bluetooth, WLAN, FeliCa and GPS
In accordance with FCC CFR 47 Part 15C



Product Service

2.1 SPURIOUS AND BAND EDGE EMISSIONS

2.1.1 Specification Reference

FCC CFR 47 Part 15C, Clause 15.247 (d)

2.1.2 Equipment Under Test and Modification State

CDMA SH114 S/N: SSHFA002157 - Modification State 0

2.1.3 Date of Test

9 November 2011, 12 November 2011, 14 November 2011 & 21 November 2011

2.1.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.1.5 Test Procedure

For conducted emissions, the EUT was set to operate at maximum power on the worst case data rate. The test was performed on the bottom, middle and top channels. The test was performed from 9 kHz to 25 GHz. Firstly, the power of each fundamental frequency was measured in 100 kHz bandwidth and this was used to show a -20 dBc limit line on the trace. The measurement path loss in each relevant frequency band was measured and entered as a reference level offset.

For radiated emissions, the test method described above was also used. However, the measurement was performed from 30 MHz to 25 GHz and the path loss is incorporated as a transducer factor and entered into the spectrum analyser.

The band edge measurements were performed in accordance with ANSI C63.10, Clause 6.9.3. The results were analysed to ensure compliance with restricted bands. The EUT was set to the lowest and highest operating frequencies.

2.1.6 Environmental Conditions

Ambient Temperature	19.7 - 21.1°C
Relative Humidity	42.0 - 54.0%



Product Service

2.1.7 Test Results


802.11(b)

4.0 V DC Supply

Spurious Radiated Emissions

2412 MHz


30 MHz to 1 GHz



Frequency (MHz)	QP Level (dBµV/m)	QP Level (µV/m)	QP Limit (dBµV/m)	QP Limit (µV/m)	QP Margin (dBµV/m)	QP Margin (µV/m)	Angle (Deg)	Height (m)	Polarity
30.097	30.4	33.1	40.0	100	-9.6	66.9	180	1.00	Vertical
31.116	30.0	31.6	40.0	100	-10.0	68.4	0	1.00	Vertical
34.074	28.8	27.5	40.0	100	-11.2	72.5	180	1.00	Vertical
39.555	26.0	20.0	40.0	200	-14.0	80.0	0	1.00	Vertical
818.125	32.9	44.2	46.0	200	-13.1	155.8	180	1.00	Vertical
901.933	33.6	47.9	46.0	200	-12.4	152.1	0	1.00	Vertical




1 GHz to 3 GHz



Date: 8.NOV.2011 20:58:23


3 GHz to 8 GHz



Date: 12.NOV.2011 17:49:27




8 GHz to 18 GHz



Date: 12.NOV.2011 21:25:32

18 GHz to 25 GHz



Date: 21.NOV.2011 17:06:31

Limit

Peak (dBμV/m)	Average (dBμV/m)
74.0	54.0




Product Service

Band Edge Emissions

2412 MHz

Polarisation	Final Peak (dBµV/m)	Final Average (dBµV/m)
Horizontal	63.1	50.3




Date: 8.NOV.2011 20:56:51



2462 MHz

Polarisation	Final Peak (dBµV/m)	Final Average (dBµV/m)
Horizontal	55.2	44.5



Date: 8.NOV.2011 21:14:31

Limit

Peak (dBµV/m)	Average (dBµV/m)
74.0	54.0



Product Service


802.11(g)

4.0 V DC Supply

Spurious Radiated Emissions

2412 MHz

30 MHz to 1 GHz




Frequency (MHz)	QP Level (dBµV/m)	QP Level (µV/m)	QP Limit (dBµV/m)	QP Limit (µV/m)	QP Margin (dBµV/m)	QP Margin (µV/m)	Angle (Deg)	Height (m)	Polarity
31.180	30.4	33.1	40.0	100	-9.6	66.9	0	0.00	Horizontal
31.770	29.7	30.5	40.0	100	-10.3	69.5	0	0.00	Horizontal
33.250	30.0	31.6	40.0	100	-10.0	68.4	180	1.00	Vertical
734.463	32.3	41.2	46.0	200	-13.7	158.8	180	1.00	Vertical
884.279	33.1	45.2	46.0	200	-12.9	154.8	0	1.00	Horizontal
966.972	33.9	49.5	54.0	500	-20.1	450.5	0	1.00	Vertical




Product Service

1 GHz to 3 GHz



Date: 8.NOV.2011 21:26:23

3 GHz to 8 GHz




Date: 12.NOV.2011 18:31:04




Product Service

8 GHz to 18 GHz



Date: 14.NOV.2011 18:32:42

18 GHz to 25 GHz



Date: 21.NOV.2011 17:47:39

Limit

Peak (dBμV/m)	Average (dBμV/m)
74.0	54.0




Product Service

Band Edge Emissions

2412 MHz

Polarisation	Final Peak (dBµV/m)	Final Average (dBµV/m)
Horizontal	64.7	49.4




Date: 8.NOV.2011 21:32:23



2462 MHz

Polarisation	Final Peak (dBµV/m)	Final Average (dBµV/m)
Horizontal	67.7	51.8



Date: 8.NOV.2011 21:53:03

Limit

Peak (dBµV/m)	Average (dBµV/m)
74.0	54.0



Product Service


802.11(n)

4.0 V DC Supply

Spurious Radiated Emissions

2412 MHz


30 MHz to 1 GHz



Frequency (MHz)	QP Level (dBµV/m)	QP Level (µV/m)	QP Limit (dBµV/m)	QP Limit (µV/m)	QP Margin (dBµV/m)	QP Margin (µV/m)	Angle (Deg)	Height (m)	Polarity
30.922	30.1	32.0	40.0	100	-9.9	68.0	0	1.00	Vertical
31.455	29.8	30.9	40.0	100	-10.2	69.1	180	1.00	Vertical
35.141	28.3	26.0	40.0	100	-11.7	74.0	180	1.00	Horizontal
737.761	32.5	42.2	46.0	200	-13.5	157.8	0	1.00	Horizontal
785.921	32.4	41.7	46.0	200	-13.6	158.3	180	1.00	Vertical
886.462	33.3	46.2	46.0	200	-12.7	153.8	180	1.00	Horizontal




1 GHz to 3 GHz



Date: 8.NOV.2011 22:23:43

3 GHz to 8 GHz




Date: 12.NOV.2011 19:07:40




Product Service

8 GHz to 18 GHz



Date: 14.NOV.2011 19:21:09

18 GHz to 25 GHz



Date: 21.NOV.2011 18:14:44

Limit


Peak (dBμV/m)	Average (dBμV/m)
74.0	54.0



Band Edge Emissions

2412 MHz

Polarisation	Final Peak (dBµV/m)	Final Average (dBµV/m)
Horizontal	64.7	49.4




Date: 8.NOV.2011 22:19:37



2462 MHz

Polarisation	Final Peak (dBµV/m)	Final Average (dBµV/m)
Horizontal	67.7	51.8



Date: 8.NOV.2011 22:47:27

Limit

Peak (dBµV/m)	Average (dBµV/m)
74.0	54.0



Product Service

SECTION 3

TEST EQUIPMENT USED



3.1 TEST EQUIPMENT USED

List of absolute measuring and other principal items of test equipment.

Instrument	Manufacturer	Type No.	TE No.	Calibration Period (months)	Calibration Due
Section 2.1 - Spurious and Band Edge Emissions					
Antenna (Double Ridge Guide, 1GHz-18GHz)	EMCO	3115	235	12	12-Nov-2011
Antenna (Double Ridge Guide)	Q-Par Angus Ltd	QSH 180K	1511	24	2-Aug-2012
Pre-Amplifier	Phase One	PS04-0086	1533	12	20-Sep-2012
Pre-Amplifier	Phase One	PSO4-0087	1534	12	26-Sep-2012
Screened Room (5)	Rainford	Rainford	1545	36	3-Feb-2014
Mast Controller	Inn-Co GmbH	CO 1000	1606	-	TU
Antenna (Bilog)	Chase	CBL6143	2904	24	12-May-2013
Antenna (DRG Horn)	ETS-LINDGREN	3115	3125	12	27-Apr-2012
Amplifier (1 - 8GHz)	Phase One	PS06-0060	3175	12	5-Jul-2012
EMI Test Receiver	Rohde & Schwarz	ESU40	3506	12	29-Sep-2012
3 GHz High Pass Filter	K&L Microwave	11SH10-3000/X18000-O/O	3552	12	14-Apr-2012
'3.5mm' - '3.5mm' RF Cable (2m)	Rhophase	3PS-1803-2000-3PS	3703	-	TU
9m RF Cable (N Type)	Rhophase	NPS-2303-9000-NPS	3791	12	26-Aug-2012
Tilt Antenna Mast	maturo GmbH	TAM 4.0-P	3916	-	TU
Mast Controller	maturo GmbH	NCD	3917	-	TU

TU – Traceability Unscheduled



Product Service

3.2 MEASUREMENT UNCERTAINTY

For a 95% confidence level, the measurement uncertainties for defined systems are:-

Test Discipline	MU
Spurious and Band Edge Emissions	30MHz to 1GHz: ± 5.1 dB 1GHz to 40GHz: ± 6.3 dB



Product Service

SECTION 4

ACCREDITATION, DISCLAIMERS AND COPYRIGHT



Product Service

4.1 ACCREDITATION, DISCLAIMERS AND COPYRIGHT



This report relates only to the actual item/items tested.

Our UKAS Accreditation does not cover opinions and interpretations and any expressed are outside the scope of our UKAS Accreditation.

Results of tests not covered by our UKAS Accreditation Schedule are marked NUA
(Not UKAS Accredited).

This report must not be reproduced, except in its entirety, without the written permission of
TÜV SÜD Product Service Limited

© 2011 TÜV SÜD Product Service Limited