

## TEST REPORT

**APPLICANT** : Sharp Corporation, Communication Systems Group  
**ADDRESS** : 2-13-1, Iida Hachihonmatsu, Higashi-Hiroshima City, Hiroshima,  
739-0192, JAPAN

**PRODUCTS** : Cellular Phone

**MODEL NO.** : SH-01E  
**SERIAL NO.** : 004401113975177  
**FCC ID** : APYHRO00169

**TEST STANDARD** : CFR 47 FCC Rules and Regulations Part 24

**TESTING LOCATION** : Japan Quality Assurance Organization  
KITA-KANSAI Testing Center  
1-7-7, Ishimaru, Minoh-shi, Osaka 562-0027, Japan

**TEST RESULTS** : **Passed**

**DATE OF TEST** : July 20 ~ August 6, 2012



---

Kousei Shibata  
Manager  
Japan Quality Assurance Organization  
KITA-KANSAI Testing Center  
SAITO EMC Branch  
7-3-10, Saito-asagi, Ibaraki-shi, Osaka 567-0085, Japan

- 
- The measurement values stated in Test Report was made with traceable to National Institute of Advanced Industrial Science and Technology (AIST) of Japan and National Institute of Information and Communications Technology (NICT) of Japan.
  - The applicable standard, testing condition and testing method which were used for the tests are based on the request of the applicant.
  - The test results presented in this report relate only to the offered test sample.
  - The contents of this test report cannot be used for the purposes, such as advertisement for consumers.
  - This test report shall not be reproduced except in full without the written approval of JQA.
  - VLAC does not approve, certify or warrant the product by this test report.

**TABLE OF CONTENTS**

	<b>Page</b>
<b>Documentation</b> .....	<b>3</b>
1 <b>Test Regulation</b> .....	3
2 <b>Test Location</b> .....	3
3 <b>Recognition of Test Laboratory</b> .....	3
4 <b>Description of the Equipment Under Test</b> .....	4
5 <b>Test Condition</b> .....	5
6 <b>Preliminary Test and Test Setup</b> .....	7
7 <b>Equipment Under Test Modification</b> .....	16
8 <b>Responsible Party</b> .....	16
9 <b>Deviation from Standard</b> .....	16
10 <b>Test Results</b> .....	17
11 <b>Summary</b> .....	20
12 <b>Operating Condition</b> .....	21
13 <b>Test Configuration</b> .....	21
14 <b>Equipment Under Test Arrangement (Drawings)</b> .....	22
<b>Appendix A: Test Data</b> .....	<b>23</b>
<b>Appendix B: Test Arrangement (Photographs)</b> .....	<b>40</b>
<b>Appendix C: Test Instruments</b> .....	<b>42</b>

**DEFINITIONS FOR ABBREVIATION AND SYMBOLS USED IN THIS TEST REPORT****EUT** : Equipment Under Test**EMC** : Electromagnetic Compatibility**AE** : Associated Equipment**EMI** : Electromagnetic Interference**N/A** : Not Applicable**EMS** : Electromagnetic Susceptibility**N/T** : Not Tested - indicates that the listed condition, standard or equipment is applicable for this report. - indicates that the listed condition, standard or equipment is not applicable for this report.

**Documentation****1 Test Regulation**

- Applied Standard : CFR 47 FCC Rules and Regulations Part 24  
Subpart E - Broadband PCS
- Test Requirements : CFR 47 FCC Rules and Regulations Part 2  
§2.1046, §2.1047, §2.1049, §2.1051, §2.1053, §2.1055 and §2.1057
- Test Procedure : ANSI C63.4–2003, TIA/EIA–603-C-2004

**2 Test Location**

Japan Quality Assurance Organization (JQA)  
KITA-KANSAI Testing Center SAITO EMC Branch  
7-3-10, Saito-asagi, Ibaraki-shi, Osaka 567-0085, Japan  
MINOH Test Site (KITA-KANSAI Testing Center)  
7-7, Ishimaru, 1-chome, Minoh-shi, Osaka, 562-0027, Japan  
KAMEOKA EMC Branch  
9-1, Ozaki, Inukanno, Nishibetsuin-cho, Kameoka-shi, Kyoto, 621-0126, Japan

**3 Recognition of Test Laboratory**

JQA KITA-KANSAI Testing Center SAITO EMC Branch is accredited under ISO/IEC 17025 by following accreditation bodies and the test facility of Testing Division is registered by the following bodies.

- VLAC Code : VLAC-001-2 (Effective through : March 30, 2014)  
VCCI Registration No. : A-0002 (Expiry date : March 30, 2014)  
BSMI Recognition No. : SL2-IS-E-6006, SL2-IN-E-6006, SL2-AI-E-6006  
(Effective through : September 14, 2013)  
IC Registration No. : 2079E-3, 2079E-4 (Effective through : July 20, 2014)

Accredited as conformity assessment body for Japan electrical appliances and material law by METI.  
(Effective through : February 22, 2013)

## 4 Description of the Equipment Under Test

### 4.1 General Information

1. Manufacturer : Sharp Corporation  
2-13-1, Iida Hachihonmatsu, Higashi-Hiroshima City, Hiroshima,  
739-0192, JAPAN
2. Products : Cellular Phone
3. Model No. : SH-01E
4. Serial No. : 004401113975177
5. Product Type : Pre-production
6. Date of Manufacture : July, 2012
7. Transmitting Frequency : 1850.2 MHz(512CH) – 1909.8MHz(810CH)
8. Receiving Frequency : 1930.2 MHz(512CH) – 1989.8MHz(810CH)
9. Emission Designations : 245KGXW
10. Max. RF Output Power : 1.514W (EIRP)
11. Power Rating : 4.0VDC (Lithium-ion Battery Pack SH36 1660mAh)
12. EUT Grounding : None
13. Category : Broadband PCS
14. EUT Authorization : Certification
15. Receive Date of EUT : July 20, 2012

### 4.2 Channel Plan

The carrier spacing is 200 kHz.

The carrier frequency is designated by the absolute frequency channel number (ARFCN).

The carrier frequency is expressed in the equation shown as follows:

$$\text{Transmitting Frequency (in MHz)} = 1850.2 + 0.2 \times (n - 512)$$

$$\text{Receiving Frequency (in MHz)} = 1930.2 + 0.2 \times (n - 512)$$

where, n : channel number ( $512 \leq n \leq 810$ )

**5 Test Condition****5.1 RF Power Output (§2.1046)****5.1.1 Conducted RF Power Output**

The requirements are  - Applicable  - Tested.  - Not tested by applicant request.]  
 - Not Applicable

Test site : SAITO  - Shielded room (S1)  - Shielded room (S2)  
 - Shielded room (S3)  - Shielded room (S4)  
MINOH  - Shielded room  - 2nd shielded room  
KAMEOKA  - Shielded room  - Conducted emission facility

Test instruments : Refer to Appendix C.

**5.1.2 ERP / EIRP RF Power Output**

The requirements are  - Applicable  - Tested.  - Not tested by applicant request.]  
 - Not Applicable

Test site : SAITO  - Anechoic chamber (A1)  - Anechoic chamber (A2)  
KAMEOKA  - 1st open site

Test instruments : Refer to Appendix C.

**5.2 Modulation Characteristics (§2.1047)**

The requirements are  - Applicable  - Tested.  - Not tested by applicant request.]  
 - Not Applicable

Test site : SAITO  - Shielded room (S1)  - Shielded room (S2)  
 - Shielded room (S3)  - Shielded room (S4)  
MINOH  - Shielded room  - 2nd shielded room  
KAMEOKA  - Shielded room  - Conducted emission facility

Test instruments : Refer to Appendix C.

**5.3 Occupied Bandwidth (§2.1049)**

The requirements are  - Applicable  - Tested.  - Not tested by applicant request.]  
 - Not Applicable

Test site : SAITO  - Shielded room (S1)  - Shielded room (S2)  
 - Shielded room (S3)  - Shielded room (S4)  
MINOH  - Shielded room  - 2nd shielded room  
KAMEOKA  - Shielded room  - Conducted emission facility

Test instruments : Refer to Appendix C.

**5.4 Spurious Emissions at Antenna Terminals (§2.1051)**

The requirements are  - Applicable  - Tested.  - Not tested by applicant request.]  
 - Not Applicable

Test site : SAITO  - Shielded room (S1)  - Shielded room (S2)  
 - Shielded room (S3)  - Shielded room (S4)  
MINOH  - Shielded room  - 2nd shielded room  
KAMEOKA  - Shielded room  - Conducted emission facility

Test instruments : Refer to Appendix C.

**5.5 Band-Edge Emission (§2.1051)**

The requirements are  - Applicable  - Tested.  - Not tested by applicant request.]  
 - Not Applicable

Test site : SAITO  - Shielded room (S1)  - Shielded room (S2)  
 - Shielded room (S3)  - Shielded room (S4)  
MINOH  - Shielded room  - 2nd shielded room  
KAMEOKA  - Shielded room  - Conducted emission facility

Test instruments : Refer to Appendix C.

**5.6 Field Strength of Spurious Radiation (§2.1053)**

The requirements are  - Applicable  - Tested.  - Not tested by applicant request.]  
 - Not Applicable

Test site : SAITO  - Anechoic chamber (A1)  - Anechoic chamber (A2)  
KAMEOKA  - 1st open site

Test instruments : Refer to Appendix C.

**5.7 Frequency Stability (§2.1055)**

The requirements are  - Applicable  - Tested.  - Not tested by applicant request.]  
 - Not Applicable

Test site : SAITO  - Environment Testing Room  
MINOH  - Environment Testing Room


Test instruments : Refer to Appendix C.

**6 Preliminary Test and Test Setup**

**6.1 RF Power Output (§2.1046)**

**6.1.1 Conducted RF Power Output**

The Conducted RF Power Output was measured with a power meter, one 10dB attenuator and a short, low loss cable.



**6.1.2 ERP / EIRP RF Power Output**

Step 1:

In order to obtain the maximum emission, the EUT was placed at the height 1.5 m on the non-conducted support and was varying at three orthogonal axes, at the distance 3 m from the receiving antenna and rotated around 360 degrees.

The receiving antenna height was varied from 1 m to 4 m.

The EUT on the table was placed to be maximum emission against at the receiving antenna polarized (vertical and horizontal).

Then the meter reading of the spectrum analyzer at the maximum emission was A dB(μV).

Step 2:

The EUT was replaced to substitution antenna at the same polarized under the same condition as step 1.

The RF power was fed to the transmitting antenna through the RF amplifier from the signal generator.

In order to obtain the maximum emission level, the height of the receiving antenna was varied from 1 m to 4 m.

The level of maximum emission was A dB(μV), same as the recorded level in the step 1.

Then the RF power into the substitution horn antenna was P (dBm).


The ERP/EIRP output power was calculated in the following equation.

$$\text{ERP (dBm)} = P \text{ (dBm)} - \text{Balun loss of the half-wave dipole antenna (dB)} + \text{Cable loss (dB)}$$


$$\text{EIRP (dBm)} = P \text{ (dBm)} + G_h \text{ (dBi)}$$

where,  $G_h \text{ (dBi)}$  : Gain of the substitution horn antenna.

- Side View -



(a) EUT




(b) Substitution Horn Antenna

**6.2 Modulation Characteristics (§2.1047)**

Not Applicable

**6.3 Occupied Bandwidth (§2.1049)**

The test system is shown as follows:




The setting of the spectrum analyzer are shown as follows:

Res. Bandwidth	10 kHz
Video Bandwidth	30 kHz
Span	1 MHz
Sweep Time	AUTO
Trace	Maxhold


**6.4 Spurious Emissions at Antenna Terminals (§2.1051)**

The Antenna Conducted Emission was with a spectrum analyzer. The test system is shown as follows:

a) Frequency Range : 9kHz - 2GHz



b) Frequency Range : 2GHz - 20GHz




The setting of the spectrum analyzer are shown as follows:

Frequency Range	9 kHz - 150 kHz	150 kHz - 30 MHz	30 MHz - 20 GHz
Res. Bandwidth	200 Hz	10 kHz	1 MHz
Video Bandwidth	1 kHz	30 kHz	3 MHz
Sweep Time	AUTO	AUTO	AUTO
Trace	Maxhold	Maxhold	Maxhold

## 6.5 Band-Edge Emission (§2.1051)

The test system is shown as follows:



The setting of the spectrum analyzer are shown as follows:

TX Frequency	1850.20 MHz / 1909.80 MHz
Band-Edge Frequency	1850.00 MHz / 1910.00 MHz
Res. Bandwidth	3 kHz
Video Bandwidth	10 kHz
Span	2 MHz
Sweep Time	AUTO
Trace	Maxhold

## 6.6 Field Strength of Spurious Radiation (§2.1053)

Step 1) The spurious radiation for transmitter were measured at the distance 3 m away from the EUT which was placed on a non-conducted support 1.0 m in height and was varying at three orthogonal axes. The receiving antenna was oriented for vertical polarization and varied from 1 m to 4 m until the maximum emission level was detected on the measuring instrument. The EUT was rotated 360 degrees until the maximum emission was received. The measurement was also repeated with the receiving antenna in the horizontal polarization.

This test was carried out using the half-wave dipole antenna for up to 1GHz and using the horn antenna for above 1 GHz.

Step 2)

A) Up to 1 GHz

The ERP measurement was carried out with according to Step 2 in page 8. Then the RF power in the substitution antenna half-wave dipole antenna for up to 1 GHz and the substitution horn antenna for above 1 GHz.

The ERP is calculated in the following equation.

$$\text{ERP(dBm)} = P \text{ (dBm)} - (\text{Balun Loss of the half-wave dipole Ant. (dB)}) + \text{Cable Loss (dB)}$$

B) Above 1 GHz

The ERP is calculated from the maximum emission level by the following formula.

$$\frac{e^2}{120\pi} = \frac{eirp}{4\pi d^2} \quad \text{----(Eq.1)}$$

$$erp = eirp - Gd \quad \text{----(Eq.2)}$$

Where,  $e[V/m]$  : Field Strength at measuring distance( $d=3m$ )

$eirp[W]$  : Equivalent Isotropic Radiated Power

$erp[W]$  : Effective Radiated Power

$Gd(dBi)$  : Gain of the substitution half-wave dipole antenna(2.15dBi)

$$eirp = \frac{(de)^2}{30} = \frac{3}{10} e^2$$

$$\therefore 10\log(eirp) = 20\log(e) + 10\log(3/10) = 20\log(e) - 5.23$$

$$10\log(eirp) = EIRP[dBm] - 30$$


$$20\log(e) = E[dB(\mu V/m)] - 120$$

$$\therefore EIRP = E - 120 + 30 - 5.23 = E - 95.23$$


$$\therefore ERP[dBm] = EIRP - 2.15 = E - 97.38$$

The respective calculated ERP of the spurious and harmonics were compared with the ERP of fundamental frequency by specified attenuation limits,  $43+10\log_{10}(TP \text{ in watt})[dB]$ . Where, TP = Transmitter power at the ANT OUT under test configuration as the hands free unit used.

## Radiated Emission 30 MHz to 1000 MHz




## Radiated Emission above 1 GHz

**NOTE**

The antenna height is scanned depending on the EUT's size and mounting height.

Radiated Emission 30 to 1000 MHz – Substitution Method




## 6.7 Frequency Stability (§2.1055)

### Frequency Stability versus Temperature

The EUT was placed in an environmental chamber and was tested in the range from -30 to +50 degrees Celsius. The EUT was stabilized at each temperature. The power (4.0VDC) supplied was applied to the transmitter and allowed to stabilize for 10 minutes. The transmitting frequency was measured at startup and 2 minutes, 5 minutes and 10 minutes after startup. This procedure was repeated from -30 to +50 degrees Celsius at the interval of 10 degrees.

### Frequency Stability versus Power Supply Voltage

The EUT was placed in an environmental chamber and was tested at the temperature of +20 degrees Celsius. The EUT was stabilized at the temperature. The power (4.0VDC) and the power (3.7VDC, the ending voltage) was applied to the EUT allowed to stabilize for 10 minutes. The transmitting frequency was measured at startup and 2 minutes, 5 minutes and 10 minutes after startup.



**7 Equipment Under Test Modification**

- No modifications were conducted by JQA to achieve compliance to the limitations.  
 - To achieve compliance to the limitations, the following changes were made by JQA during the compliance test.

The modifications will be implemented in all production models of this equipment.

Applicant : Not Applicable

Date : Not Applicable

Typed Name : Not Applicable

Position : Not Applicable

Signatory : Not Applicable

**8 Responsible Party**Responsible Party of Test Item (Product)

Responsible Party :	
Contact Person :	_____
	Signatory

**9 Deviation from Standard**

- No deviations from the standard described in clause 1.  
 - The following deviations were employed from the standard described in clause 1.
-

**10 Test Results****10.1 RF Power Output (§2.1046)****10.1.1 Conducted RF Power Output**

The requirements are  - Applicable  - Tested.  - Not tested by applicant request.]  
 - Not Applicable

Transmitter Power is 926.8 mW at 1909.800 MHz

Uncertainty of Measurement Results +/-0.8 dB(2 $\sigma$ )

Remarks : \_\_\_\_\_

**10.1.2 ERP / EIRP RF Power Output**

The requirements are  - Applicable  - Tested.  - Not tested by applicant request.]  
 - Not Applicable

- Passed  - Failed  - Not judged

Min. Limit Margin 1.2 dB at 1909.800 MHz

Max. Limit Exceeding \_\_\_\_\_ dB at \_\_\_\_\_ MHz

Uncertainty of Measurement Results +/-2.2 dB(2 $\sigma$ )

Remarks : The maximum EIRP is 1.514 W at 1909.800 MHz. The measurement result is within the range of measurement uncertainty.

**10.2 Modulation Characteristics (§2.1047)**

The requirements are  - Applicable  - Tested.  - Not tested by applicant request.]  
 - Not Applicable

- Passed  - Failed  - Not judged

Remarks : \_\_\_\_\_

**10.3 Occupied Bandwidth (§2.1049)**

The requirements are  - Applicable [ - Tested.  - Not tested by applicant request.]  
 - Not Applicable

- Passed  - Failed  - Not judged

The 99% Bandwidth is 245.4 kHz at 1909.800 MHz

The 26dB Bandwidth is 315.8 kHz at 1850.200 MHz

Uncertainty of Measurement Results +/-0.9 %(2 $\sigma$ )

Remarks : \_\_\_\_\_

**10.4 Spurious Emissions at Antenna Terminals (§2.1051)**

The requirements are  - Applicable [ - Tested.  - Not tested by applicant request.]  
 - Not Applicable

- Passed  - Failed  - Not judged

Min. Limit Margin >32.3 dB at 19098.000 MHz

Max. Limit Exceeding \_\_\_\_\_ dB at \_\_\_\_\_ MHz

Uncertainty of Measurement Results  
9 kHz – 1GHz +/-1.0 dB(2 $\sigma$ )  
1GHz – 18GHz +/-1.2 dB(2 $\sigma$ )  
18GHz – 40GHz +/-1.6 dB(2 $\sigma$ )

Remarks : \_\_\_\_\_

**10.5 Band-Edge Emission (§2.1051)**

The requirements are  - Applicable  - Tested.  - Not tested by applicant request.]  
 - Not Applicable

- Passed  - Failed  - Not judged

The Band-Edge level is     -15.4     dBm at   1910.0   MHz

Uncertainty of Measurement Results     +/-1.2     dB(2 $\sigma$ )

Remarks : \_\_\_\_\_

**10.6 Field Strength of Spurious Radiation (§2.1053)**

The requirements are  - Applicable  - Tested.  - Not tested by applicant request.]  
 - Not Applicable

- Passed  - Failed  - Not judged

Min. Limit Margin     19.5     dB at   9549.0   MHz

Max. Limit Exceeding              dB at              MHz

Uncertainty of Measurement Results 30 MHz – 1000 MHz     +/-1.4     dB(2 $\sigma$ )  
above 1 GHz     +/-2.2     dB(2 $\sigma$ )

Remarks : \_\_\_\_\_

**10.7 Frequency Stability (§2.1055)**

The requirements are  - Applicable  - Tested.  - Not tested by applicant request.]  
 - Not Applicable

The Frequency Stability level is     +0.06     ppm at   1880.000   MHz

Uncertainty of Measurement Results     +/-0.02     ppm(2 $\sigma$ )

Remarks : \_\_\_\_\_

**11 Summary****General Remarks :**

The EUT was tested according to the requirements of the following standard.

CFR 47 FCC Rules and Regulations Part 24

The test configuration is shown in clause 12 to 14.

The conclusion for the test items of which are required by the applied regulation is indicated under the test results.

Determining compliance with the limits in this report was based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

**Test Results :**

The "as received" sample;

- fulfill the test requirements of the regulation mentioned on clause 1.
- doesn't fulfill the test requirements of the regulation mentioned on clause 1.

Reviewed by:

Tested by:



---

Shigeru Kinoshita  
Deputy Manager  
JQA KITA-KANSAI Testing Center  
SAITO EMC Branch



---

Shigeru Osawa  
Deputy Manager  
JQA KITA-KANSAI Testing Center  
SAITO EMC Branch

## 12 Operating Condition

The test were carried under one modulation type shown as follows:

Modulation Burst Signal : DATA TSC 5 in accordance with GSM 05.02.

The Radiated Emission test were carried under 3 test configurations shown in clause 14.

In all tests, the fully charged battery is used for the EUT.

Detailed Transmitter portion:

Transmitter frequency : 1850.2 MHz(512CH) – 1909.8 MHz(810CH)

Local frequency : 3861.28 MHz(512CH) – 3985.66 MHz(810CH)

Detailed Receiver portion:

Receiver frequency : 1930.2 MHz(512CH) – 1989.8 MHz(810CH)

Local frequency : 3700.4 MHz(512CH) – 3819.6 MHz(810CH)

Other Clock Frequency

32.768 kHz, 19.2 MHz, 27 MHz, 27.12 MHz

## 13 Test Configuration

The equipment under test (EUT) consists of :

	Item	Manufacturer	Model No.	Serial No.	FCC ID
A	Cellular Phone	Sharp	SH-01E	004401113 975177	APYHRO00169
B	Lithium-ion Battery	Sharp	SH36	--	N/A
C	AC Adapter	Sharp	SHCR01	--	N/A
D	USB conversion cable	Sharp	SH-01E(Optional)	--	N/A
E	Stereo Handsfree	Sharp	SHLDL1	--	N/A
F	One-seg antenna cable	Sharp	SH01	--	N/A

The auxiliary equipment used for testing :


None

Type of Cable:


No.	Description	Identification (Manu. etc.)	Connector Shielded	Cable Shielded	Ferrite Core	Length (m)
1	DC Power Cord	--	--	NO	NO	1.5
2	AC Power Cord	--	--	NO	NO	1.2
3	USB conversion cable	--	--	NO	NO	0.1
4	Handsfree Cable	--	NO	--	NO	1.5
5	One-seg antenna cable	--	--	NO	NO	0.1

**14 Equipment Under Test Arrangement (Drawings)**


a) Single Unit



b) AC Adapter used



c) Stereo Earphone used



**Appendix A: Test Data****A.1 RF Power Output (§2.1046)****A.1.1 Conducted RF Power Output****(GSM-PCS1900)**Test Date: July 20, 2012  
Temp.: 25 °C, Humi: 76 %

Transmitting Frequency CH	[MHz]	Correction Factor [dB]	Meter Reading (Peak) [dBm]	Results (Peak)	
				[dBm]	[mW]
512	1850.200	10.36	19.17	29.53	897.4
661	1880.000	10.37	18.76	29.13	818.5
810	1909.800	10.37	19.30	29.67	926.8

Calculated result at 1909.800 MHz, as the maximum level point shown on underline:

Correction Factor	=	10.37	dB
+ ) Meter Reading	=	19.30	dBm
Result	=	29.67	dBm = 926.8 mW

NOTE : The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.

**A.1.2 ERP /EIRP Power Output**

**(GSM-PCS1900)**

Test Date: July 20, 2012  
Temp.: 25 °C, Humi: 76 %

**1. Measurement Results**

CH	Transmitting Frequency [MHz]	Emission Measurement [dB(uV)]		Substitution Measurement [dB(uV)]		Supplied Power to Substitution Antenna [dBm]	Gain of Substitution Antenna [dB]
		Hori. (Mh)	Vert. (Mv)	Hori. (Msh)	Vert. (Msv)		
512	1850.200	94.5	94.3	72.6	72.8	- 5.0	14.1
661	1880.000	94.7	94.4	72.8	72.9	- 5.0	14.3
810	1909.800	95.4	94.6	73.1	73.1	- 5.0	14.5

**2. Calculation Results**

CH	Transmitting Frequency [MHz]	Peak EIRP [dBm]		Maximum Peak EIRP [W]	Limits [dBm]	Margin [dB]
		(EIRPh)	Vert. (EIRPv)			
512	1850.200	31.0	30.6	1.259	33.0	+ 2.0
661	1880.000	31.2	30.8	1.318	33.0	+ 1.8
810	1909.800	31.8	31.0	1.514	33.0	+ 1.2

Calculated result at 1909.800 MHz, as the worst point shown on underline:

Emission Measurement (Mh)	=	95.4 dB(uV)
Substitution Measurement (Msh)	=	-73.1 dB(uV)
Supplied Power to Substitution Antenna	=	-5.0 dBm
+ ) Gain of Substitution Antenna	=	14.5 dB
Result (EIRPh)	=	31.8 dBm = 1.514 W

Minimum Margin: 33.0 - 31.8 = 1.2 (dB)

NOTE : Setting of measuring instrument(s) :

Detector Function	Resolution B.W.	V.B.W.	Sweep Time
Peak	1 MHz	1 MHz	20 msec.

**A.2 Modulation Characteristics (§2.1047)**

Not Applicable

**A.3 Occupied Bandwidth (§2.1049)**


The resolution bandwidth was set to about 1% of emission bandwidth, -26dBc display line was placed on the screen (or 99% bandwidth), the occupied bandwidth is the delta frequency between the two points where the display line intersects the signal trace.

Test Date : August 3, 2012


Temp.:28°C, Humi:53%

Channel	Frequency (MHz)	99% Bandwidth (kHz)	-26dBc Bandwidth (kHz)
512	1850.200	244.3	315.8
661	1880.000	242.8	312.3
810	1909.800	245.4	312.5


Low Channel



### Middle Channel



### High Channel



**A.4 Spurious Emissions at Antenna Terminals (§2.1051)**

**(GSM-PCS1900)**

Test Date: August 3, 2012

Temp.: 28 °C, Humi: 53 %

Transmitting Frequency CH [MHz]	Measured Frequency [MHz]	Corr. Factor [dB]	Meter Readings [dBm]	Limits [dBm]	Results [dBm]	Margin [dB]	Remarks
512 1850.200	3700.400	11.6	< -63.0	-13.0	< -51.4	> +38.4	C
	5550.600	12.0	< -63.0	-13.0	< -51.0	> +38.0	C
	7400.800	12.5	< -63.0	-13.0	< -50.5	> +37.5	C
	9251.000	12.9	< -63.0	-13.0	< -50.1	> +37.1	C
	11101.200	13.4	< -63.0	-13.0	< -49.6	> +36.6	C
	12951.400	15.2	< -63.0	-13.0	< -47.8	> +34.8	C
	14801.600	15.9	< -63.0	-13.0	< -47.1	> +34.1	C
	16651.800	16.7	< -63.0	-13.0	< -46.3	> +33.3	C
18502.000	17.5	< -63.0	-13.0	< -45.5	> +32.5	C	
661 1880.000	3760.000	11.6	< -63.0	-13.0	< -51.4	> +38.4	C
	5640.000	11.9	< -63.0	-13.0	< -51.1	> +38.1	C
	7520.000	12.5	< -63.0	-13.0	< -50.5	> +37.5	C
	9400.000	13.0	< -63.0	-13.0	< -50.0	> +37.0	C
	11280.000	13.5	< -63.0	-13.0	< -49.5	> +36.5	C
	13160.000	15.2	< -63.0	-13.0	< -47.8	> +34.8	C
	15040.000	16.0	< -63.0	-13.0	< -47.0	> +34.0	C
	16920.000	16.9	< -63.0	-13.0	< -46.1	> +33.1	C
18800.000	17.6	< -63.0	-13.0	< -45.4	> +32.4	C	
810 1909.800	3819.600	11.6	< -63.0	-13.0	< -51.4	> +38.4	C
	5729.400	11.9	< -63.0	-13.0	< -51.1	> +38.1	C
	7639.200	12.5	-61.2	-13.0	-48.7	+35.7	C
	9549.000	13.1	< -63.0	-13.0	< -49.9	> +36.9	C
	11458.800	13.5	< -63.0	-13.0	< -49.5	> +36.5	C
	13368.600	15.3	< -63.0	-13.0	< -47.7	> +34.7	C
	15278.400	16.1	< -63.0	-13.0	< -46.9	> +33.9	C
	17188.200	17.0	< -63.0	-13.0	< -46.0	> +33.0	C
19098.000	17.7	< -63.0	-13.0	< -45.3	> +32.3	C	

Calculated result at 19098.0 MHz, as the worst point shown on underline:

Corr. Factor	=	17.7 dB
+ ) Meter Reading	=	<63.0 dBm
Result	=	<45.3 dBm


Minimum Margin: -13.0 - (<45.3) = >32.3 (dB)

NOTES


- The spectrum was checked from 9 kHz to 20 GHz.
- Applied limits : -13.0 [dBm] =  $10\log(TP[mW]) - (43 + 10\log(tp[W])) = 10\log(TP[mW]) - (43 + (10 \log(TP[mW]) - 30))$   
where,  $tp[W] = TP[mW] / 1000$  : Transmitter power at antenna terminal
- The correction factor is shown as follows:  
Corr. Factor [dB] = Cable Loss + 10dB Pad Att. [dB] (9 kHz - 2 GHz)  
Corr. Factor [dB] = Cable Loss + 10dB Pad Att. + High Pass Filter Loss (D-96) [dB] (over 2 GHz)
- The symbol of "<" means "or less".
- The symbol of ">" means "more than".
- Setting of measuring instrument(s) :

	Detector Function	RES B.W.	V.B.W.	Sweep Time
A	Peak	200 Hz	1 kHz	AUTO
B	Peak	10 kHz	30 kHz	AUTO
C	Peak	1 MHz	3 MHz	AUTO


### Low Channel, Out-Of-Band Emissions (9 kHz – 150 kHz)




### Low Channel, Out-Of-Band Emissions (150 kHz – 30 MHz)




Low Channel, Out-Of-Band Emissions (30 MHz – 2 GHz)




Low Channel, Out-Of-Band Emissions (2 GHz – 20 GHz)




### Middle Channel, Out-Of-Band Emissions (9 kHz – 150 kHz)




### Middle Channel, Out-Of-Band Emissions (150 kHz – 30 MHz)




Middle Channel, Out-Of-Band Emissions (30 MHz – 2 GHz)




Middle Channel, Out-Of-Band Emissions (2 GHz – 20 GHz)




### High Channel, Out-Of-Band Emissions (9 kHz – 150 kHz)




### High Channel, Out-Of-Band Emissions (150 kHz – 30 MHz)



High Channel, Out-Of-Band Emissions (30 MHz – 2 GHz)



High Channel, Out-Of-Band Emissions (2 GHz – 20 GHz)




**A.5 Band-Edge Emission(\$2.1051)**Test Date : August 3, 2012Temp.:28°C, Humi:53%


(GSM-PCS1900)

Channel	Frequency (MHz)	Band-Edge Frequency (MHz)	Band-Edge Level (dBm)
512	1850.200	1850.00	-17.1
810	1909.800	1910.00	-15.4

### Low Channel, Band-Edge Emission



### High Channel, Band-Edge Emission



**A.6 Field Strength of Spurious Radiation (§2.1053)**

**(GSM-PCS1900)**

Test Configuration : Single Unit

Test Date: August 1, 2012

Temp.: 26 °C, Humi: 67 %

CH	Transmitting Frequency [MHz]	Measured Frequency [MHz]	ERP [dBm]		Limits [dBm]	Margin [dB]	Remarks		
			Hori.	Vert.					
512	1850.200	3700.400	-55.1	-55.0	-13.0	+42.0	C		
		5550.600	-42.8	-43.3	-13.0	+29.8	C		
		7400.800	-42.2	-43.0	-13.0	+29.2	C		
		9251.000	-38.2	< -40.9	-13.0	+25.2	C		
		11101.200	< -40.2	< -40.2	-13.0	> +27.2	C		
		12951.400	< -36.0	< -36.0	-13.0	> +23.0	C		
		14801.600	< -36.0	< -36.0	-13.0	> +23.0	C		
		16651.800	< -46.5	< -46.5	-13.0	> +33.5	C		
		18502.000	< -39.7	< -39.7	-13.0	> +26.7	C		
661	1880.000	3760.000	-49.8	-51.7	-13.0	+36.8	C		
		5640.000	-41.1	-44.1	-13.0	+28.1	C		
		7520.000	-40.3	-40.1	-13.0	+27.1	C		
		9400.000	-35.5	-37.6	-13.0	+22.5	C		
		11280.000	< -40.4	< -40.4	-13.0	> +27.4	C		
		13160.000	< -35.9	< -35.9	-13.0	> +22.9	C		
		15040.000	< -36.1	< -36.1	-13.0	> +23.1	C		
		16920.000	< -46.7	< -46.7	-13.0	> +33.7	C		
		18800.000	< -39.8	< -39.8	-13.0	> +26.8	C		
810	1909.800	3819.600	-47.7	-49.9	-13.0	+34.7	C		
		5729.400	-41.1	-42.7	-13.0	+28.1	C		
		7639.200	-38.1	-37.2	-13.0	+24.2	C		
		9549.000	-32.5	-34.5	-13.0	+19.5	C		
				11458.800	< -40.6	< -40.6	-13.0	> +27.6	C
				13368.600	< -36.0	< -36.0	-13.0	> +23.0	C
				15278.400	< -36.2	< -36.2	-13.0	> +23.2	C
				17188.200	< -46.8	< -46.8	-13.0	> +33.8	C
				19098.000	< -39.7	< -39.7	-13.0	> +26.7	C

Calculated result at 9549.0 MHz, as the worst point shown on underline:  
Minimum Margin:  $-13.0 - (-32.5) = 19.5$  (dB)

**NOTES**

1. Test Distance : 3 m
2. The spectrum was checked from 30 MHz to 20 GHz.
3. All emissions not reported were more than 20 dB below the applied limits.
4. Applied limits :  $-13.0$  [dBm] =  $10\log(TP[mW]) - (43 + 10\log(tp[W])) = 10\log(TP[mW]) - (43 + (10 \log(TP[mW]) - 30))$   
where,  $tp[W] = TP[mW] / 1000$  : Transmitter power at antenna terminal
5. The symbol of "<" means "or less".
6. The symbol of ">" means "more than".
7. Setting of measuring instrument(s) :

	Detector Function	RES B.W.	V.B.W.	Sweep Time
A	Peak	10 kHz	30 kHz	20 msec.
B	Peak	100 kHz	300 kHz	20 msec.
C	Peak	1 MHz	3 MHz	20 msec.

**A.7 Frequency Stability (§2.1055)**

**(GSM-PCS1900)**

Test Date: August 3, 2012  
- August 6, 2012

**1. Frequency Stability Measurement versus Temperature**

Transmitting Frequency : 1880.000 MHz (661 ch)  
 DC Supply Voltage : 4.0 VDC

Ambient Temperature [°C]	Startup	Deviation [ppm]			Limits [ppm]	Margin [ppm]
		2 minutes	5 minutes	10 minutes		
-30	+ 0.05	+ 0.03	+ 0.03	+ 0.03	N/A	N/A
-20	+ 0.04	+ 0.03	+ 0.03	+ 0.03	N/A	N/A
-10	+ 0.05	+ 0.05	+ 0.04	+ 0.04	N/A	N/A
0	<u>+ 0.06</u>	+ 0.05	+ 0.05	+ 0.05	N/A	N/A
10	+ 0.04	+ 0.04	+ 0.03	+ 0.03	N/A	N/A
20	+ 0.03	+ 0.02	+ 0.02	+ 0.02	N/A	N/A
30	+ 0.03	+ 0.02	+ 0.02	+ 0.02	N/A	N/A
40	+ 0.03	+ 0.02	+ 0.02	+ 0.02	N/A	N/A
50	+ 0.03	+ 0.02	+ 0.02	+ 0.02	N/A	N/A

**2. Frequency Stability Measurement versus Power Supply Voltage**

Transmitting Frequency : 1880.000 MHz (661 ch)  
 Ambient Temperature: : 20 °C

DC Supply Voltage [V]	Startup	Deviation [ppm]			Limits [ppm]	Margin [ppm]
		2 minutes	5 minutes	10 minutes		
4.0	+ 0.03	+ 0.02	+ 0.02	+ 0.02	N/A	N/A
3.7 (Ending)	+ 0.02	+ 0.02	+ 0.02	+ 0.02	N/A	N/A

Test condition example as the maximum deviation point shown on underline:

Ambient Temperature : 0 °C / Startup

DC Supply Voltage : 4 VDC

NOTE : The measurement were made after all of components of the oscillator sufficiently stabilized at each temperature.

**Appendix C: Test Instruments**

**C.1 RF Power Output**

**C.1.1 Conducted RF Power Output**

Type	Model	Manufacturer	ID No.	Last Cal.	Interval
Power Meter	N1911A	Agilent	B-63	2012/7	1 Year
Power Sensor	N1921A	Agilent	B-64	2012/7	1 Year
Attenuator	54A-10	Weinschel	D-28	2011/9	1 Year
RF Cable	SUCOFLEX102	SUHNER	C-52	2012/7	1 Year

**C.1.2 ERP /EIRP Power Output**

Type	Model	Manufacturer	ID No.	Last Cal.	Interval
Test Receiver	ESU 26	Rohde & Schwarz	A-6	2012/4	1 Year
Signal Generator	E8257D	Agilent	B-39	2011/8	1 Year
Power Meter	N1911A	Agilent	B-63	2012/7	1 Year
Power Sensor	N1921A	Agilent	B-64	2012/7	1 Year
Attenuator(RX)	2-10	Weinschel	D-79	2011/11	1 Year
Attenuator(TX)	2-10	Weinschel	D-80	2011/11	1 Year
RF Cable(RX)	SUCOFLEX104	SUHNER	C-66	2012/1	1 Year
RF Cable(TX)	SUCOFLEX 102/E	SUHNER	C-70	2011/11	1 Year
Horn Antenna(TX)	91889-2	EATON	C-40-2	2011/6	2 Years
Horn Antenna(RX)	91889-2	EATON	C-41-2	2012/6	1 Year

**B.2 Modulation Characteristics**

Not Applicable

**C.3 Occupied Bandwidth**

Type	Model	Manufacturer	ID No.	Last Cal.	Interval
Spectrum Analyzer	E4446A	Agilent	A-39	2011/9	1 Year
Attenuator	54A-10	Weinschel	D-28	2011/9	1 Year
RF Cable	SUCOFLEX102	SUHNER	C-52	2012/7	1 Year

**C.4 Spurious Emissions at Antenna Terminals**

Type	Model	Manufacturer	ID No.	Last Cal.	Interval
Spectrum Analyzer	E4446A	Agilent	A-39	2011/9	1 Year
Attenuator	54A-10	Weinschel	D-28	2011/9	1 Year
RF Cable	SUCOFLEX102	SUHNER	C-52	2012/7	1 Year
HPF	HPM13899	MICRO-TRONICS	D-96	2012/2	1 Year

**C.5 Band-Edge Emission**

Type	Model	Manufacturer	ID No.	Last Cal.	Interval
Spectrum Analyzer	E4446A	Agilent	A-39	2011/9	1 Year
Attenuator	54A-10	Weinschel	D-28	2011/9	1 Year
RF Cable	SUCOFLEX102	SUHNER	C-52	2012/7	1 Year

**C.6 Field Strength of Spurious Radiation**

Type	Model	Manufacturer	ID No.	Last Cal.	Interval
Test Receiver	ESU 26	Rohde & Schwarz	A-6	2012/4	1 Year
Signal Generator	E8257D	Agilent	B-39	2011/8	1 Year
Power Meter	N1911A	Agilent	B-63	2012/7	1 Year
Power Sensor	N1921A	Agilent	B-64	2012/7	1 Year
Horn Antenna(TX)	91889-2	EATON	C-40-2	2011/6	2 Year
Horn Antenna	91888-2	EATON	C-41-1	2012/6	1 Year
Horn Antenna(RX)	91889-2	EATON	C-41-2	2012/6	1 Year
Horn Antenna	3160-04	EMCO	C-55	2011/6	2 Years
Horn Antenna	3160-05	EMCO	C-56	2011/6	2 Years
Horn Antenna	3160-06	EMCO	C-57	2011/6	2 Years
Horn Antenna	3160-07	EMCO	C-58	2011/6	2 Years
Horn Antenna	3160-08	EMCO	C-59	2011/6	2 Years
Horn Antenna)	3160-09	EMCO	C-48	2011/6	2 Years
RF Cable(TX)	SUCOFLEX E102E	SUHNER	C-70	2011/11	1 Year
RF Cable(RX)	SUCOFLEX102	SUHNER	C-52	2012/7	1 Year
RF Cable(RX)	SUCOFLEX104	SUHNER	C-66	2012/1	1 Year
RF Cable(RX)	SUCOFLEX104	SUHNER	C-67	2012/1	1 Year
RF Cable(RX)	SUCOFLEX102EA	SUHNER	C-69	2012/1	1 Year
Attenuator(TX)	2-10	Weinschel	D-40	2011/9	1 Year
Attenuator(RX)	2-10	Weinschel	D-79	2011/11	1 Year
Attenuator(RX)	54-10	Weinschel	D-29	2011/9	1 Year
Pre-Amplifier	WJ-6611-513	Watkins Johnson	A-23	2012/1	1 Year
Pre-Amplifier	WJ-6882-824	Watkins Johnson	A-21	2012/1	1 Year
Pre-Amplifier	DBL-0618N515	DBS Microwave	A-33	2012/1	1 Year
Pre-Amplifier	BZ1840LD1	B&Z	A-29	2012/1	1 Year
HPF	HPM13899	MICRO-TRONICS	D-96	2012/2	1 Year

**C.7 Frequency Stability**

Type	Model	Manufacturer	ID No.	Last Cal.	Interval
Radio Communication Analyzer	MT8820C	Anritsu	B-5	2012/2	1 Year
DC Voltage Meter	2011-39	YEW	B-33	2012/4	1 Year
Environmental Chamber	SH-641	ESPEC	F-32	2012/7	1 Year
DC Power Supply	NL035-10	TAKASAGO	F-4	N/A	N/A