

## TEST REPORT

**APPLICANT** : Sharp Corporation, Communication Systems Group  
**ADDRESS** : 2-13-1, Iida Hachihonmatsu, Higashi-Hiroshima City, Hiroshima,  
739-0192, JAPAN

**PRODUCTS** : Cellular Phone

**MODEL NO.** : SH-09D  
**SERIAL NO.** : 004401113965335  
**FCC ID** : APYHRO00170

**TEST STANDARD** : CFR 47 FCC Rules and Regulations Part 22

**TESTING LOCATION** : Japan Quality Assurance Organization  
KITA-KANSAI Testing Center  
1-7-7, Ishimaru, Minoh-shi, Osaka 562-0027, Japan

**TEST RESULTS** : **Passed**

**DATE OF TEST** : May 9 ~ 11, 2012



Kousei Shibata  
Manager  
Japan Quality Assurance Organization  
KITA-KANSAI Testing Center  
SAITO EMC Branch  
7-3-10, Saito-asagi, Ibaraki-shi, Osaka 567-0085, Japan

- The measurement values stated in Test Report was made with traceable to National Institute of Advanced Industrial Science and Technology (AIST) of Japan and National Institute of Information and Communications Technology (NICT) of Japan.
- The applicable standard, testing condition and testing method which were used for the tests are based on the request of the applicant.
- The test results presented in this report relate only to the offered test sample.
- The contents of this test report cannot be used for the purposes, such as advertisement for consumers.
- This test report shall not be reproduced except in full without the written approval of JQA.
- VLAC does not approve, certify or warrant the product by this test report.

**TABLE OF CONTENTS**

	<b>Page</b>
<b>Documentation</b> .....	<b>3</b>
1 <b>Test Regulation</b> .....	3
2 <b>Test Location</b> .....	3
3 <b>Recognition of Test Laboratory</b> .....	3
4 <b>Description of the Equipment Under Test</b> .....	4
5 <b>Test Condition</b> .....	5
6 <b>Preliminary Test and Test Setup</b> .....	7
7 <b>Equipment Under Test Modification</b> .....	16
8 <b>Responsible Party</b> .....	16
9 <b>Deviation from Standard</b> .....	16
10 <b>Test Results</b> .....	17
11 <b>Summary</b> .....	20
12 <b>Operating Condition</b> .....	21
13 <b>Test Configuration</b> .....	21
14 <b>Equipment Under Test Arrangement (Drawings)</b> .....	22
<b>Appendix A: Test Data</b> .....	<b>23</b>
<b>Appendix B: Test Arrangement (Photographs)</b> .....	<b>43</b>
<b>Appendix C: Test Instruments</b> .....	<b>45</b>

**DEFINITIONS FOR ABBREVIATION AND SYMBOLS USED IN THIS TEST REPORT****EUT** : Equipment Under Test**EMC** : Electromagnetic Compatibility**AE** : Associated Equipment**EMI** : Electromagnetic Interference**N/A** : Not Applicable**EMS** : Electromagnetic Susceptibility**N/T** : Not Tested - indicates that the listed condition, standard or equipment is applicable for this report. - indicates that the listed condition, standard or equipment is not applicable for this report.

**Documentation****1 Test Regulation**

Applied Standard : CFR 47 FCC Rules and Regulations Part 22  
Subpart H – Cellular Radiotelephone Service

Test Requirements : CFR 47 FCC Rules and Regulations Part 2  
§2.1046, §2.1047, §2.1049, §2.1051, §2.1053, §2.1055 and §2.1057

Test Procedure : ANSI C63.4–2003, TIA/EIA–603-C-2004

**2 Test Location**

Japan Quality Assurance Organization (JQA)

KITA-KANSAI Testing Center SAITO EMC Branch

7-3-10, Saito-asagi, Ibaraki-shi, Osaka 567-0085, Japan

MINOH Test Site (KITA-KANSAI Testing Center)

7-7, Ishimaru, 1-chome, Minoh-shi, Osaka, 562-0027, Japan

KAMEOKA EMC Branch

9-1, Ozaki, Inukanno, Nishibetsuin-cho, Kameoka-shi, Kyoto, 621-0126, Japan

**3 Recognition of Test Laboratory**

JQA KITA-KANSAI Testing Center SAITO EMC Branch is accredited under ISO/IEC 17025 by following accreditation bodies and the test facility of Testing Division is registered by the following bodies.

VLAC Code : VLAC-001-2 (Effective through : March 30, 2014)

VCCI Registration No. : A-0002 (Expiry date : March 30, 2014)

BSMI Recognition No. : SL2-IS-E-6006, SL2-IN-E-6006, SL2-AI-E-6006  
(Effective through : September 14, 2013)

IC Registration No. : 2079E-3, 2079E-4 (Effective through : July 20, 2014)

Accredited as conformity assessment body for Japan electrical appliances and material law by METI.  
(Effective through : February 22, 2013)

## 4 Description of the Equipment Under Test

### 4.1 General Information

1. Manufacturer : Sharp Corporation, Communication Systems Group  
2-13-1, Iida Hachihonmatsu, Higashi-Hiroshima City, Hiroshima,  
739-0192, JAPAN
2. Products : Cellular Phone
3. Model No. : SH-09D
4. Serial No. : 004401113965335
5. Product Type : Pre-production
6. Date of Manufacture : April, 2012
7. Transmitting Frequency : 824.2 MHz(128CH) – 848.8 MHz(251CH)
8. Receiving Frequency : 869.2 MHz(128CH) – 893.8 MHz(251CH)
9. Emission Designations : 246KGXW
10. Max. RF Output Power : 2.089W (ERP)
11. Power Rating : 4.0VDC (Lithium-ion Battery Pack SH37 1900mAh)
12. EUT Grounding : None
13. Category : GSM850
14. EUT Authorization : Certification
15. Receive Date of EUT : April 27, 2012

### 4.2 Channel Plan

The carrier spacing is 200 kHz.

The carrier frequency is designated by the absolute frequency channel number (ARFCN).

The carrier frequency is expressed in the equation shown as follows:

$$\text{Transmitting Frequency (in MHz)} = 824.2 + 0.2 \times (n - 128)$$

where, n : channel number ( $128 \leq n \leq 251$ )

$$\text{Receiving Frequency (in MHz)} = 869.2 + 0.2 \times (n - 128)$$

where, n : channel number ( $128 \leq n \leq 251$ )

**5 Test Condition****5.1 RF Power Output (§2.1046)****5.1.1 Conducted RF Power Output**

The requirements are  - Applicable  - Tested.  - Not tested by applicant request.]  
 - Not Applicable

Test site : SAITO  - Shielded room (S1)  - Shielded room (S2)  
 - Shielded room (S4)  
MINOH  - Shielded room  
KAMEOKA  - Shielded room  - Conducted emission facility

Test instruments : Refer to Appendix C.

**5.1.2 ERP / EIRP RF Power Output**

The requirements are  - Applicable  - Tested.  - Not tested by applicant request.]  
 - Not Applicable

Test site : SAITO  - Anechoic chamber (A1)  - Anechoic chamber (A2)  
KAMEOKA  - 1st open site

Test instruments : Refer to Appendix C.

**5.2 Modulation Characteristics (§2.1047)**

The requirements are  - Applicable  - Tested.  - Not tested by applicant request.]  
 - Not Applicable

Test site : SAITO  - Shielded room (S1)  - Shielded room (S2)  
 - Shielded room (S4)  
MINOH  - Shielded room  
KAMEOKA  - Shielded room  - Conducted emission facility

Test instruments : Refer to Appendix B.

**5.3 Occupied Bandwidth (§2.1049)**

The requirements are  - Applicable  - Tested.  - Not tested by applicant request.]  
 - Not Applicable

Test site : SAITO  - Shielded room (S1)  - Shielded room (S2)  
 - Shielded room (S4)  
MINOH  - Shielded room  
KAMEOKA  - Shielded room  - Conducted emission facility

Test instruments : Refer to Appendix C.

**5.4 Spurious Emissions at Antenna Terminals (§2.1051)**

The requirements are  - Applicable  - Tested.  - Not tested by applicant request.]  
 - Not Applicable

Test site : SAITO  - Shielded room (S1)  - Shielded room (S2)  
 - Shielded room (S4)  
MINOH  - Shielded room  
KAMEOKA  - Shielded room  - Conducted emission facility

Test instruments : Refer to Appendix C.

**5.5 Band-Edge Emission (§2.1051)**

The requirements are  - Applicable  - Tested.  - Not tested by applicant request.]  
 - Not Applicable

Test site : SAITO  - Shielded room (S1)  - Shielded room (S2)  
 - Shielded room (S4)  
MINOH  - Shielded room  
KAMEOKA  - Shielded room  - Conducted emission facility

Test instruments : Refer to Appendix C.

**5.6 Field Strength of Spurious Radiation (§2.1053)**

The requirements are  - Applicable  - Tested.  - Not tested by applicant request.]  
 - Not Applicable

Test site : SAITO  - Anechoic chamber (A1)  - Anechoic chamber (A2)  
KAMEOKA  - 1st open site

Test instruments : Refer to Appendix C.

**5.7 Frequency Stability (§2.1055)**

The requirements are  - Applicable  - Tested.  - Not tested by applicant request.]  
 - Not Applicable

Test site : SAITO  - Environment Testing Room  
MINOH  - Environment Testing Room


Test instruments : Refer to Appendix C.

**6 Preliminary Test and Test Setup**

**6.1 RF Power Output (§2.1046)**

**6.1.1 Conducted RF Power Output**

The Conducted RF Power Output was measured with a power meter, one 10dB attenuator and a short, low loss cable.



**6.1.2 ERP / EIRP RF Power Output**

Step 1:

In order to obtain the maximum emission, the EUT was placed at the height 1.5 m on the non-conducted support and was varying at three orthogonal axes, at the distance 3 m from the receiving antenna and rotated around 360 degrees.

The receiving antenna height was varied from 1 m to 4 m.

The EUT on the table was placed to be maximum emission against at the receiving antenna polarized (vertical and horizontal).

Then the meter reading of the spectrum analyzer at the maximum emission was A dB(μV).

Step 2:

The EUT was replaced to substitution antenna at the same polarized under the same condition as step 1.

The RF power was fed to the transmitting antenna through the RF amplifier from the signal generator.

In order to obtain the maximum emission level, the height of the receiving antenna was varied from 1 m to 4 m.

The level of maximum emission was A dB(μV), same as the recorded level in the step 1.

Then the RF power into the substitution horn antenna was P (dBm).


The ERP/EIRP output power was calculated in the following equation.

$$\text{ERP (dBm)} = P \text{ (dBm)} - \text{Balun loss of the tuned dipole antenna (dB)} + \text{Cable loss (dB)}$$


$$\text{EIRP (dBm)} = P \text{ (dBm)} + G_h \text{ (dBi)}$$

where,  $G_h \text{ (dBi)}$  : Gain of the substitution horn antenna.

– Side View –



(a)EUT




(b) Substitution Half-wave Dipole Antenna

**6.2 Modulation Characteristics (§2.1047)**

Not Applicable

**6.3 Occupied Bandwidth (§2.1049)**

The test system is shown as follows:




The setting of the spectrum analyzer are shown as follows:

Res. Bandwidth	10 kHz
Video Bandwidth	30 kHz
Span	1 MHz
Sweep Time	AUTO
Trace	Maxhold

**6.4 Spurious Emissions at Antenna Terminals (§2.1051)**

The Antenna Conducted Emission was measured with a spectrum analyzer. The test system is shown as follows:

a) Frequency Range : 9kHz - 1.2GHz



b) Frequency Range : 1.2GHz - 10GHz




The setting of the spectrum analyzer are shown as follows:

Frequency Range	9 kHz - 150 kHz	150 kHz - 30 MHz	30 MHz - 10 GHz
Res. Bandwidth	200 Hz	10 kHz	1 MHz
Video Bandwidth	1 kHz	30 kHz	3 MHz
Sweep Time	AUTO	AUTO	AUTO
Trace	Maxhold	Maxhold	Maxhold

## 6.5 Band-Edge Emission (§2.1051)

The test system is shown as follows:



The setting of the spectrum analyzer are shown as follows:

TX Frequency	824.20 MHz / 848.8 MHz
Band-Edge Frequency	824.00 MHz / 849.00 MHz
Res. Bandwidth	2.7 kHz
Video Bandwidth	10 kHz
Span	2 MHz
Sweep Time	AUTO
Trace	Maxhold

## 6.6 Field Strength of Spurious Radiation (§2.1053)

Step 1) The spurious radiation for transmitter were measured at the distance 3 m away from the EUT which was placed on a non-conducted support 0.8 m in height and was varying at three orthogonal axes. The receiving antenna was oriented for vertical polarization and varied from 1 m to 4 m until the maximum emission level was detected on the measuring instrument. The EUT was rotated 360 degrees until the maximum emission was received. The measurement was also repeated with the receiving antenna in the horizontal polarization.

This test was carried out using the half-wave dipole antenna for up to 1GHz and using the horn antenna for above 1 GHz.

Step 2)

A) Up to 1 GHz

The ERP measurement was carried out with according to Step 2 in page 8. Then the RF power in the substitution antenna half-wave dipole antenna for up to 1 GHz and the substitution horn antenna for above 1 GHz.

The ERP is calculated in the following equation.

$$\text{ERP(dBm)} = P \text{ (dBm)} - (\text{Balun Loss of the half-wave dipole Ant. (dB)}) + \text{Cable Loss (dB)}$$

B) Above 1 GHz

The ERP is calculated from the maximum emission level by the following formula.

$$\frac{e^2}{120\pi} = \frac{eirp}{4\pi d^2} \quad \text{---(Eq.1)}$$

$$erp = eirp - Gd \quad \text{---(Eq.2)}$$

Where,  $e[V/m]$  : Field Strength at measuring distance( $d=3m$ )

$eirp[W]$  : Equivalent Isotropic Radiated Power

$erp[W]$  : Effective Radiated Power

$Gd(dBi)$  : Gain of the substitution half-wave dipole antenna(2.15dBi)

$$eirp = \frac{(de)^2}{30} = \frac{3}{10} e^2$$

$$\therefore 10\log(eirp) = 20\log(e) + 10\log(3/10) = 20\log(e) - 5.23$$

$$10\log(eirp) = EIRP[dBm] - 30$$


$$20\log(e) = E[dB(\mu V/m)] - 120$$

$$\therefore EIRP = E - 120 + 30 - 5.23 = E - 95.23$$


$$\therefore ERP[dBm] = EIRP - 2.15 = E - 97.38$$

The respective calculated ERP of the spurious and harmonics were compared with the ERP of fundamental frequency by specified attenuation limits,  $43+10\log_{10}(TP \text{ in watt})[dB]$ . Where, TP = Transmitter power at the ANT OUT under test configuration as the hands free unit used.

## Radiated Emission 30 MHz to 1000 MHz




## Radiated Emission above 1 GHz

**NOTE**

The antenna height is scanned depending on the EUT's size and mounting height.

Radiated Emission 30 to 1000 MHz – Substitution Method




## 6.7 Frequency Stability (§2.1055)

### Frequency Stability versus Temperature

The EUT was placed in an environmental chamber and was tested in the range from -30 to +50 degrees Celsius. The EUT was stabilized at each temperature. The power (4.0VDC) supplied was applied to the transmitter and allowed to stabilize for 10 minutes. The transmitting frequency was measured at startup and 2 minutes, 5 minutes and 10 minutes after startup. This procedure was repeated from -30 to +50 degrees Celsius at the interval of 10 degrees.

### Frequency Stability versus Power Supply Voltage

The EUT was placed in an environmental chamber and was tested at the temperature of +20 degrees Celsius. The EUT was stabilized at the temperature. The power (4.0VDC) and the power (3.7VDC, the ending voltage) was applied to the EUT allowed to stabilize for 10 minutes. The transmitting frequency was measured at startup and 2 minutes, 5 minutes and 10 minutes after startup.



**7 Equipment Under Test Modification**

- No modifications were conducted by JQA to achieve compliance to the limitations.  
 - To achieve compliance to the limitations, the following changes were made by JQA during the compliance test.

The modifications will be implemented in all production models of this equipment.

Applicant : Not Applicable

Date : Not Applicable

Typed Name : Not Applicable

Position : Not Applicable

Signatory : Not Applicable

**8 Responsible Party**Responsible Party of Test Item (Product)

Responsible Party :	
Contact Person :	_____
	Signatory

**9 Deviation from Standard**

- No deviations from the standard described in clause 1.  
 - The following deviations were employed from the standard described in clause 1.
-

**10 Test Results****10.1 RF Power Output (§2.1046)****10.1.1 Conducted RF Power Output**

The requirements are  - Applicable  - Tested.  - Not tested by applicant request.]  
 - Not Applicable

Transmitter Power is 1945.4 mW at 824.200 MHz

Uncertainty of Measurement Results at Amplitude +/-0.7 dB(2 $\sigma$ )

Remarks : \_\_\_\_\_

**10.1.2 ERP / EIRP RF Power Output**

The requirements are  - Applicable  - Tested.  - Not tested by applicant request.]  
 - Not Applicable

- Passed  - Failed  - Not judged

Min. Limit Margin 5.3 dB at 848.800 MHz

Max. Limit Exceeding \_\_\_\_\_ dB at \_\_\_\_\_ MHz

Uncertainty of Measurement Results +/-1.4 dB(2 $\sigma$ )

Remarks : The maximum ERP is 2.089 W at 848.8 MHz.

**10.2 Modulation Characteristics (§2.1047)**

The requirements are  - Applicable  - Tested.  - Not tested by applicant request.]  
 - Not Applicable

- Passed  - Failed  - Not judged

Remarks : \_\_\_\_\_

**10.3 Occupied Bandwidth (§2.1049)**

The requirements are  - Applicable [ - Tested.  - Not tested by applicant request.]  
 - Not Applicable

- Passed  - Failed  - Not judged

The 99% Bandwidth is 246.0 kHz at 848.800 MHz  
 The 26dB Bandwidth is 317.1 kHz at 824.200 MHz

Uncertainty of Measurement Results +/-0.9 %(2 $\sigma$ )

Remarks : \_\_\_\_\_

**10.4 Spurious Emissions at Antenna Terminals (§2.1051)**

The requirements are  - Applicable [ - Tested.  - Not tested by applicant request.]  
 - Not Applicable

- Passed  - Failed  - Not judged

Min. Limit Margin 35.1 dB at 1648.400 MHz

Max. Limit Exceeding \_\_\_\_\_ dB at \_\_\_\_\_ MHz

Uncertainty of Measurement Results  
 9 kHz – 1GHz +/-1.0 dB(2 $\sigma$ )  
 1GHz – 18GHz +/-1.2 dB(2 $\sigma$ )  
 18GHz – 40GHz +/-1.6 dB(2 $\sigma$ )

Remarks : \_\_\_\_\_

**10.5 Band-Edge Emission (§2.1051)**

The requirements are  - Applicable  - Tested.  - Not tested by applicant request.]  
 - Not Applicable

- Passed  - Failed  - Not judged

The Band-Edge level is     -13.8     dBm at   824.000   MHz

Uncertainty of Measurement Results     +/-1.2     dB(2 $\sigma$ )

Remarks : \_\_\_\_\_

**10.6 Field Strength of Spurious Radiation (§2.1053)**

The requirements are  - Applicable  - Tested.  - Not tested by applicant request.]  
 - Not Applicable

- Passed  - Failed  - Not judged

Min. Limit Margin     34.0     dB at  1648.400  MHz

Max. Limit Exceeding              dB at              MHz

Uncertainty of Measurement Results 30 MHz – 1000 MHz     +/-1.4     dB(2 $\sigma$ )  
above 1 GHz     +/-2.2     dB(2 $\sigma$ )

Remarks : \_\_\_\_\_

**10.7 Frequency Stability (§2.1055)**

The requirements are  - Applicable  - Tested.  - Not tested by applicant request.]  
 - Not Applicable

The Frequency Stability level is     +0.05     ppm at   836.400   MHz

Uncertainty of Measurement Results     +/-0.02     ppm(2 $\sigma$ )

Remarks : \_\_\_\_\_

**11 Summary****General Remarks :**

The EUT was tested according to the requirements of the following standard.

CFR 47 FCC Rules and Regulations Part 22

The test configuration is shown in clause 12 to 14.

The conclusion for the test items of which are required by the applied regulation is indicated under the test results.

Determining compliance with the limits in this report was based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

**Test Results :**

The "as received" sample;

- fulfill the test requirements of the regulation mentioned on clause 1.
- doesn't fulfill the test requirements of the regulation mentioned on clause 1.

Reviewed by:

Tested by:



---

Shigeru Kinoshita  
Deputy Manager  
JQA KITA-KANSAI Testing Center  
SAITO EMC Branch



---

Shigeru Osawa  
Deputy Manager  
JQA KITA-KANSAI Testing Center  
SAITO EMC Branch

## 12 Operating Condition

The test were carried under one modulation type shown as follows:

Modulation Burst Signal : DATA TSC 5 in accordance with GSM 05.02.

The Radiated Emission test were carried under 4 test configurations shown in clause 14.

In all tests, the fully charged battery is used for the EUT.

Detailed Transmitter portion:

Transmitter frequency : 824.2 MHz(128CH) – 848.8 MHz(251CH)

Local frequency : 3296.8 MHz(128CH) – 3395.2 MHz(251CH)

Detailed Receiver portion:

Receiver frequency : 869.2 MHz(128CH) – 893.8 MHz(251CH)

Local frequency : 3476.8 MHz(128CH) – 3575.2 MHz(251CH)

Other Clock Frequency

32.768 kHz, 19.2 MHz, 27 MHz, 27.12 MHz

## 13 Test Configuration

The equipment under test (EUT) consists of :

	Item	Manufacturer	Model No.	Serial No.	FCC ID
A	Cellular Phone	Sharp	SH-09D	004401113 965335	APYHRO00170
B	Lithium-ion Battery	Sharp	SH37	--	N/A
C	AC Adapter	Panasonic Mobile	03	--	N/A
D	Stereo Handsfree	Sharp	555006	--	N/A

The auxiliary equipment used for testing :


	Item	Manufacturer	Model No.	Serial No.	FCC ID
E	Wireless Charger	Sharp	NC-WP04	--	N/A
F	AC Adapter (Wireless Charger)	Sharp	NC-WP04	--	N/A

Type of Cable:


No.	Description	Identification (Manu. etc.)	Connector Shielded	Cable Shielded	Ferrite Core	Length (m)
1	USB conversion cable (For AC Adapter)	--	--	NO	YES	1.2
2	Handsfree Cable	--	NO	--	NO	1.5
3	DC Power Cable (For Wireless Charger)	--	--	NO	YES	1.9

**14 Equipment Under Test Arrangement (Drawings)**


a) Single Unit




b) AC Adapter used



c) Wireless Charger used



d) Single Unit with Wireless Charger



■ : Ferrite Core

**Appendix A: Test Data**

**A.1 RF Power Output (§2.1046)**

**A.1.1 Conducted RF Power Output**

(GSM850)

Test Date: May 11, 2012  
Temp.: 21 °C, Humi: 40 %

Transmitting Frequency CH	[MHz]	Correction Factor [dB]	Meter Reading (Peak) [dBm]	Results (Peak)	
				[dBm]	[mW]
128	824.200	10.07	22.82	32.89	1945.4
189	836.400	10.07	22.78	32.85	1927.5
251	848.800	10.07	22.77	32.84	1923.1

Calculated result at 824.200 MHz, as the maximum level point shown on underline:

Correction Factor	=	10.07	dB
+ ) Meter Reading	=	22.82	dBm
Result	=	32.89	dBm = 1945.4 mW

NOTE : The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.

**A.1.2 ERP /EIRP Power Output**

(GSM850)

Test Date: May 11, 2012  
Temp.: 19 °C, Humi: 47 %

**1. Measurement Results**

CH	Transmitting Frequency [MHz]	Emission Measurement [dB(uV)]		Substitution Measurement [dB(uV)]		Supplied Power to Substitution Antenna [dBm]	Balun Loss of Substitution Antenna [dB]
		Hori. (Mh)	Vert. (Mv)	Hori. (Msh)	Vert. (Msv)		
128	824.200	105.7	104.9	66.6	66.2	- 5.0	1.4
189	836.400	105.3	103.1	66.2	65.8	- 5.0	1.4
251	848.800	105.4	103.0	65.8	65.1	- 5.0	1.4

**2. Calculation Results**

CH	Transmitting Frequency [MHz]	Peak ERP [dBm]		Maximum Peak ERP [W]	Limits [dBm]	Margin [dB]
		Hori. (ERPh)	Vert. (ERPv)			
128	824.200	32.7	32.3	1.862	38.5	+ 5.8
189	836.400	32.7	30.9	1.862	38.5	+ 5.8
251	848.800	33.2	31.5	2.089	38.5	+ 5.3

Calculated result at 848.800 MHz, as the worst point shown on underline:

Emission Measurement (Mh)	=	105.4 dB(uV)
Substitution Measurement (Msh)	=	-65.8 dB(uV)
Supplied Power to Substitution Antenna	=	-5.0 dBm
+ ) Balun Loss of Substitution Antenna	=	-1.4 dB
Result (ERPh)	=	33.2 dBm = 2.089 W

Minimum Margin: 38.5 - 33.2 = 5.3 (dB)

NOTE : Setting of measuring instrument(s) :

Detector Function	Resolution B.W.	V.B.W.	Sweep Time
Peak	1 MHz	1 MHz	AUTO

**A.2 Modulation Characteristics (§2.1047)**

Not Applicable


**A.3 Occupied Bandwidth (§2.1049)**

The resolution bandwidth was set to about 1% of emission bandwidth, -26dBc display line was placed on the screen (or 99% bandwidth), the occupied bandwidth is the delta frequency between the two points where the display line intersects the signal trace.


Test Date : May 11, 2012Temp.:21°C, Humi:40%

Channel	Frequency (MHz)	99% Bandwidth (kHz)	-26dBc Bandwidth (kHz)
128	824.20	244.3	317.1
189	836.40	242.4	311.8
251	848.80	246.0	314.1


### Low Channel



### Middle Channel



## High Channel



**A.4 Spurious Emissions at Antenna Terminals (§2.1051)**

**(GSM850)**

Test Date: May 11, 2012  
Temp.: 21 °C, Humi: 40 %

CH	Transmitting Frequency [MHz]	Measured Frequency [MHz]	Corr. Factor [dB]	Meter Readings [dBm]	Limits [dBm]	Results [dBm]	Margin [dB]	Remarks
128	824.200	1648.400	11.3	-59.4	-13.0	-48.1	+35.1	C
		2472.600	11.0	-62.8	-13.0	-51.8	+38.8	C
		3296.800	11.1	< -63.0	-13.0	< -51.9	> +38.9	C
		4121.000	11.2	< -63.0	-13.0	< -51.8	> +38.8	C
		4945.200	11.3	< -63.0	-13.0	< -51.7	> +38.7	C
		5769.400	11.4	< -63.0	-13.0	< -51.6	> +38.6	C
		6593.600	11.5	< -63.0	-13.0	< -51.5	> +38.5	C
		7417.800	11.9	< -63.0	-13.0	< -51.1	> +38.1	C
		8242.000	12.1	< -63.0	-13.0	< -50.9	> +37.9	C
189	836.400	1672.800	11.3	-62.5	-13.0	-51.2	+38.2	C
		2509.200	11.0	< -63.0	-13.0	< -52.0	> +39.0	C
		3345.600	11.1	< -63.0	-13.0	< -51.9	> +38.9	C
		4182.000	11.2	< -63.0	-13.0	< -51.8	> +38.8	C
		5018.400	11.3	< -63.0	-13.0	< -51.7	> +38.7	C
		5854.800	11.4	< -63.0	-13.0	< -51.6	> +38.6	C
		6691.200	11.6	< -63.0	-13.0	< -51.4	> +38.4	C
		7527.600	11.9	< -63.0	-13.0	< -51.1	> +38.1	C
		8364.000	12.1	< -63.0	-13.0	< -50.9	> +37.9	C
251	848.800	1697.600	11.3	< -63.0	-13.0	< -51.7	> +38.7	C
		2546.400	11.0	< -63.0	-13.0	< -52.0	> +39.0	C
		3395.200	11.1	< -63.0	-13.0	< -51.9	> +38.9	C
		4244.000	11.2	< -63.0	-13.0	< -51.8	> +38.8	C
		5092.800	11.3	< -63.0	-13.0	< -51.7	> +38.7	C
		5941.600	11.4	< -63.0	-13.0	< -51.6	> +38.6	C
		6790.400	11.7	< -63.0	-13.0	< -51.3	> +38.3	C
		7639.200	11.9	< -63.0	-13.0	< -51.1	> +38.1	C
		8488.000	12.2	< -63.0	-13.0	< -50.8	> +37.8	C

Calculated result at 1648.4 MHz, as the worst point shown on underline:

Corr. Factor	=	11.3 dB
+ ) Meter Reading	=	-59.4 dBm
<u>Result</u>	=	<u>-48.1 dBm</u>


Minimum Margin: -13.0 - (-48.1) = 35.1 (dB)

NOTES


1. The spectrum was checked from 9 kHz to 10 GHz.
2. Applied limits : -13.0 [dBm] =  $10\log(TP[mW]) - (43 + 10\log(tp[W])) = 10\log(TP[mW]) - (43 + (10 \log(TP[mW]) - 30))$   
 where,  $tp[W] = TP[mW] / 1000$  : Transmitter power at antenna terminal
3. The correction factor is shown as follows:  
 Corr. Factor [dB] = Cable Loss + 10dB Pad Att. [dB] (9 kHz - 2 GHz)  
 Corr. Factor [dB] = Cable Loss + 10dB Pad Att. + High Pass Filter Loss (D-96) [dB] (over 2 GHz)
4. The symbol of "<" means "or less".
5. The symbol of ">" means "more than".
6. Setting of measuring instrument(s) :

	Detector Function	RES B.W.	V.B.W.	Sweep Time
A	Peak	200 Hz	1 kHz	AUTO
B	Peak	10 kHz	30 kHz	AUTO
C	Peak	1 MHz	3 MHz	AUTO


Low Channel, Out-Of-Band Emissions (9 kHz – 150 kHz)




Low Channel, Out-Of-Band Emissions (150 kHz – 30 MHz)



Low Channel, Out-Of-Band Emissions (30 MHz – 1.2 GHz)




Low Channel, Out-Of-Band Emissions (1.2 GHz – 10 GHz)







Middle Channel, Out-Of-Band Emissions (30 MHz – 1.2 GHz)




Middle Channel, Out-Of-Band Emissions (1.2 GHz – 10 GHz)




High Channel, Out-Of-Band Emissions (9 kHz – 150 kHz)




High Channel, Out-Of-Band Emissions (150 kHz – 30 MHz)



High Channel, Out-Of-Band Emissions (30 MHz – 1.2 GHz)




High Channel, Out-Of-Band Emissions (1.2 GHz – 10 GHz)




**A.5 Band-Edge Emission(\$2.1051)**Test Date : May 11, 2012Temp.:21°C, Humi:40%

Channel	Frequency (MHz)	Band-Edge Frequency (MHz)	Band-Edge Level (dBm)
128	824.2	824.0	-13.8
251	848.8	849.0	-14.1

Low Channel, Band-Edge Emission



High Channel, Band-Edge Emission



**A.6 Field Strength of Spurious Radiation (§2.1053)**

**A.6.1 Single Unit**

(GSM850)

Test Configuration : Single Unit

Test Date: May 11, 2012  
Temp.: 19 °C, Humi: 47 %

CH	Transmitting Frequency [MHz]	Measured Frequency [MHz]	ERP [dBm]		Limits [dBm]	Margin [dB]	Remarks
			Hori.	Vert.			
128	824.200	1648.400	-47.0	-48.3	-13.0	+34.0	C
		2472.600	-51.9	-50.6	-13.0	+37.6	C
		3296.800	< -57.0	< -57.0	-13.0	> +44.0	C
		4121.000	< -51.1	< -51.1	-13.0	> +38.1	C
		4945.200	< -51.6	< -51.6	-13.0	> +38.6	C
		5769.400	< -50.8	< -50.8	-13.0	> +37.8	C
		6593.600	< -47.8	< -47.8	-13.0	> +34.8	C
		7417.800	< -57.1	< -57.1	-13.0	> +44.1	C
		8242.000	< -51.2	< -51.2	-13.0	> +38.2	C
189	836.400	1672.800	-48.6	-49.3	-13.0	+35.6	C
		2509.200	-53.7	-54.2	-13.0	+40.7	C
		3345.600	< -56.6	< -56.6	-13.0	> +43.6	C
		4182.000	< -51.1	< -51.1	-13.0	> +38.1	C
		5018.400	< -51.6	< -51.6	-13.0	> +38.6	C
		5854.800	< -50.7	< -50.7	-13.0	> +37.7	C
		6691.200	< -47.8	< -47.8	-13.0	> +34.8	C
		7527.600	< -57.0	< -57.0	-13.0	> +44.0	C
		8364.000	< -51.2	< -51.2	-13.0	> +38.2	C
251	848.800	1697.600	-51.8	-52.6	-13.0	+38.8	C
		2546.400	-53.4	-54.7	-13.0	+40.4	C
		3395.200	< -56.7	< -56.7	-13.0	> +43.7	C
		4244.000	< -51.1	< -51.1	-13.0	> +38.1	C
		5092.800	< -51.5	< -51.5	-13.0	> +38.5	C
		5941.600	< -50.1	< -50.1	-13.0	> +37.1	C
		6790.400	< -47.8	< -47.8	-13.0	> +34.8	C
		7639.200	< -55.1	< -55.1	-13.0	> +42.1	C
		8488.000	< -51.3	< -51.3	-13.0	> +38.3	C

Calculated result at 1648.4 MHz, as the worst point shown on underline:  
Minimum Margin:  $-13.0 - (-47.0) = 34.0$  (dB)

**NOTES**

1. Test Distance : 3 m
2. The spectrum was checked from 30 MHz to 10 GHz.
3. All emissions not reported were more than 20 dB below the applied limits.
4. Applied limits :  $-13.0$  [dBm] =  $10\log(TP[mW]) - (43 + 10\log(tp[W])) = 10\log(TP[mW]) - (43 + (10 \log(TP[mW]) - 30))$   
where,  $tp[W] = TP[mW] / 1000$  : Transmitter power at antenna terminal
5. The symbol of "<" means "or less".
6. The symbol of ">" means "more than".
7. Setting of measuring instrument(s) :

	Detector Function	RES B.W.	V.B.W.	Sweep Time
A	Peak	10 kHz	30 kHz	20 msec.
B	Peak	100 kHz	300 kHz	20 msec.
C	Peak	1 MHz	3 MHz	20 msec.

**A.6.2 Single Unit with Wireless Charger**

(GSM850)

Test Configuration : Single Unit(WPC)

Test Date: May 11, 2012  
Temp.: 19 °C, Humi: 47 %

CH	Transmitting Frequency [MHz]	Measured Frequency [MHz]	ERP [dBm]		Limits [dBm]	Margin [dB]	Remarks
			Hori.	Vert.			
128	824.200	1648.400	-48.8	< -53.4	-13.0	+35.8	C
		2472.600	-49.9	-47.1	-13.0	+34.1	C
		3296.800	< -57.0	< -57.0	-13.0	> +44.0	C
		4121.000	< -51.1	< -51.1	-13.0	> +38.1	C
		4945.200	< -51.6	< -51.6	-13.0	> +38.6	C
		5769.400	< -50.8	< -50.8	-13.0	> +37.8	C
		6593.600	< -47.8	< -47.8	-13.0	> +34.8	C
		7417.800	< -57.1	< -57.1	-13.0	> +44.1	C
189	836.400	8242.000	< -51.2	< -51.2	-13.0	> +38.2	C
		1672.800	-51.4	< -53.6	-13.0	+38.4	C
		2509.200	-51.9	-51.2	-13.0	+38.2	C
		3345.600	< -56.6	< -56.6	-13.0	> +43.6	C
		4182.000	< -51.1	< -51.1	-13.0	> +38.1	C
		5018.400	< -51.6	< -51.6	-13.0	> +38.6	C
		5854.800	< -50.7	< -50.7	-13.0	> +37.7	C
		6691.200	< -47.8	< -47.8	-13.0	> +34.8	C
251	848.800	7527.600	< -57.0	< -57.0	-13.0	> +44.0	C
		8364.000	< -51.2	< -51.2	-13.0	> +38.2	C
		1697.600	-51.7	-50.9	-13.0	+37.9	C
		2546.400	-49.5	-51.9	-13.0	+36.5	C
		3395.200	< -56.7	< -56.7	-13.0	> +43.7	C
		4244.000	< -51.1	< -51.1	-13.0	> +38.1	C
		5092.800	< -51.5	< -51.5	-13.0	> +38.5	C
		5941.600	< -50.1	< -50.1	-13.0	> +37.1	C
6790.400	< -47.8	< -47.8	-13.0	> +34.8	C		
7639.200	< -55.1	< -55.1	-13.0	> +42.1	C		
8488.000	< -51.3	< -51.3	-13.0	> +38.3	C		

Calculated result at 2472.6 MHz, as the worst point shown on underline:  
Minimum Margin:  $-13.0 - (-47.1) = 34.1$  (dB)

**NOTES**

1. Test Distance : 3 m
2. The spectrum was checked from 30 MHz to 10 GHz.
3. All emissions not reported were more than 20 dB below the applied limits.
4. Applied limits :  $-13.0$  [dBm] =  $10\log(TP[mW]) - (43 + 10\log(tp[W])) = 10\log(TP[mW]) - (43 + (10 \log(TP[mW]) - 30))$   
where,  $tp[W] = TP[mW] / 1000$  : Transmitter power at antenna terminal
5. The symbol of "<" means "or less".
6. The symbol of ">" means "more than".
7. Setting of measuring instrument(s) :

	Detector Function	RES B.W.	V.B.W.	Sweep Time
A	Peak	10 kHz	30 kHz	20 msec.
B	Peak	100 kHz	300 kHz	20 msec.
C	Peak	1 MHz	3 MHz	20 msec.

**A.7 Frequency Stability (§2.1055)**

(GSM850)

Test Date: May 9, 2012  
- May 10, 2012

**1. Frequency Stability Measurement versus Temperature**

Transmitting Frequency : 836.400 MHz (189 ch)  
 DC Supply Voltage : 4.0 VDC

Ambient Temperature [°C]	Startup	Deviation [ppm]			Limits [ppm]	Margin [ppm]
		2 minutes	5 minutes	10 minutes		
-30	<u>+ 0.05</u>	<u>+ 0.05</u>	+ 0.03	+ 0.03	2.50	2.45
-20	<u>+ 0.05</u>	<u>+ 0.05</u>	+ 0.02	+ 0.02	2.50	2.45
-10	<u>+ 0.05</u>	<u>+ 0.05</u>	+ 0.03	+ 0.03	2.50	2.45
0	+ 0.03	+ 0.03	+ 0.03	+ 0.03	2.50	2.47
10	+ 0.02	+ 0.02	+ 0.02	+ 0.03	2.50	2.47
20	+ 0.02	+ 0.02	+ 0.02	+ 0.02	2.50	2.48
30	- 0.02	- 0.02	+ 0.02	+ 0.02	2.50	2.48
40	- 0.02	- 0.02	+ 0.02	+ 0.02	2.50	2.48
50	+ 0.02	+ 0.02	+ 0.02	+ 0.02	2.50	2.48

**2. Frequency Stability Measurement versus Power Supply Voltage**

Transmitting Frequency : 836.400 MHz (189 ch)  
 Ambient Temperature: : 20 °C

DC Supply Voltage [V]	Startup	Deviation [ppm]			Limits [ppm]	Margin [ppm]
		2 minutes	5 minutes	10 minutes		
4.0	+ 0.02	+ 0.02	+ 0.02	+ 0.02	2.50	2.48
3.7 (Ending)	+ 0.02	+ 0.02	+ 0.02	+ 0.02	2.50	2.48

Test condition example as the maximum deviation point shown on underline:

Ambient Temperature : -30 °C / Startup

DC Supply Voltage : 4 VDC

Minimum Margin: 2.50 - 0.05 = 2.45 (ppm)

NOTE : The measurement were made after all of components of the oscillator sufficiently stabilized at each temperature.

**Appendix C: Test Instruments**

**C.1 RF Power Output**

**C.1.1 Conducted RF Power Output**

Type	Model	Manufacturer	ID No.	Last Cal.	Interval
Power Meter	N1911A	Agilent	B-63	2011/7	1 Year
Power Sensor	N1921A	Agilent	B-64	2011/7	1 Year
Attenuator	54A-10	Weinschel	D-28	2011/9	1 Year
RF Cable	SUCOFLEX102	SUHNER	C-52	2011/6	1 Year

**C.1.2 ERP /EIRP Power Output**

Type	Model	Manufacturer	ID No.	Last Cal.	Interval
Test Receiver	ESU26	Rohde & Schwarz	A-6	2012/4	1 Year
Signal Generator	E8257D	Agilent	B-39	2011/8	1 Year
Power Meter	N1911A	Agilent	B-63	2011/7	1 Year
Power Sensor	N1921A	Agilent	B-64	2011/7	1 Year
Attenuator(TX)	2-10	Weinschel	D-79	2011/11	1 Year
Log-periodic Antenna	UHALP9108-A1	Schwarzbeck	C-31	2011/5	1 Year
Dipole Antenna(TX)	KBA-611	Kyoritsu	C-20	2011/8	2 Years

**C.2 Modulation Characteristics**

Not Applicable

**C.3 Occupied Bandwidth**

Type	Model	Manufacturer	ID No.	Last Cal.	Interval
Spectrum Analyzer	E4446A	Agilent	A-39	2011/9	1 Year
Attenuator	54A-10	Weinschel	D-28	2011/9	1 Year
RF Cable	SUCOFLEX102	SUHNER	C-52	2011/6	1 Year

**C.4 Spurious Emissions at Antenna Terminals**

Type	Model	Manufacturer	ID No.	Last Cal.	Interval
Spectrum Analyzer	E4446A	Agilent	A-39	2011/9	1 Year
Attenuator	54A-10	Weinschel	D-28	2011/9	1 Year
RF Cable	SUCOFLEX102	SUHNER	C-52	2011/6	1 Year
HPF	HPM5010S	MICRO-TRONICS	D-94	2012/2	1 Year

**C.5 Band-Edge Emission**

Type	Model	Manufacturer	ID No.	Last Cal.	Interval
Spectrum Analyzer	E4446A	Agilent	A-39	2011/9	1 Year
Attenuator	54A-10	Weinschel	D-28	2011/9	1 Year
RF Cable	SUCOFLEX102	SUHNER	C-52	2011/6	1 Year

**C.6 Field Strength of Spurious Radiation**

Type	Model	Manufacturer	ID No.	Last Cal.	Interval
Test Receiver	ESU26	Rohde & Schwarz	A-6	2012/4	1 Year
Signal Generator	E8257A	Agilent	B-39	2011/8	1 Year
Power Meter	N1911A	Agilent	B-63	2011/7	1 Year
Power Sensor	N1921A	Agilent	B-64	2011/7	1 Year
Horn Antenna	91888-2	EATON	C-41-1	2011/6	1 Year
Horn Antenna	91889-2	EATON	C-41-2	2011/6	1 Year
Horn Antenna	3160-05	EATON	C-56	2011/6	2 Years
Horn Antenna	3160-06	EATON	C-57	2011/6	2 Years
Horn Antenna	3160-07	EATON	C-58	2011/6	2 Years
RF Cable	SUCOFLEX104	SUHNER	C-66	2012/1	1 Year
RF Cable	SUCOFLEX104	SUHNER	C-67	2012/1	1 Year
Attenuator	2-10	Weinschel	D-79	2011/10	1 Year
Attenuator	54-10	Weinschel	D-29	2011/9	1 Year
Pre-Amplifier	WJ-6611-513	Watkins Johnson	A-23	2012/1	1 Year
Pre-Amplifier	WJ-6882-824	Watkins Johnson	A-21	2012/1	1 Year
Pre-Amplifier	DBL-0618N515	DBS Microwave	A-33	2012/1	1 Year
HPF	HPM5010S	MICRO-TRONICS	D-94	2012/2	1 Year

**C.7 Frequency Stability**

Type	Model	Manufacturer	ID No.	Last Cal.	Interval
Radio Communication Analyzer	MT8815B	Anritsu	B-69	2011/9	1 Year
DC Voltage Meter	2011-39	YEW	B-33	2012/4	1 Year
Environmental Chamber	SH-641	ESPEC	F-32	2011/6	1 Year
DC Power Supply	NL035-10	TAKASAGO	F-4	N/A	N/A