

TEST REPORT

Applicant : Sharp Corporation, Communication Systems Group
Address : 2-13-1, Iida Hachihonmatsu, Higashi-Hiroshima City, Hiroshima,
739-0192, JAPAN

Products : Cellular Phone
Model No. : SH-05E
SERIAL NO. : 004401114675115
004401114675131

FCC ID : APYHRO00186

Test Standard : CFR 47 FCC Rules and Regulations Part 15

Test Results : **Passed**

Date of Test : November 27 ~ December 5, 2012



A handwritten signature in black ink, appearing to read 'K. Shibata', is written over a horizontal line.

Kousei Shibata
Manager
Japan Quality Assurance Organization
KITA-KANSAI Testing Center
SAITO EMC Branch
7-3-10, Saito-asagi, Ibaraki-shi, Osaka 567-0085, Japan

- The measurement values stated in Test Report was made with traceable to National Institute of Advanced Industrial Science and Technology (AIST) of Japan and National Institute of Information and Communications Technology (NICT) of Japan.
- The applicable standard, testing condition and testing method which were used for the tests are based on the request of the applicant.
- The test results presented in this report relate only to the offered test sample.
- The contents of this test report cannot be used for the purposes, such as advertisement for consumers.
- This test report shall not be reproduced except in full without the written approval of JQA.
- VLAC does not approve, certify or warrant the product by this test report.

TABLE OF CONTENTS

	Page
1 Description of the Equipment Under Test.....	3
2 Summary of Test Results.....	4
3 Test Procedure.....	5
4 Test Location.....	5
5 Recognition of Test Laboratory.....	5
6 Details of the Equipment Under Test.....	6
7 Details of the Test Item.....	8

DEFINITIONS FOR ABBREVIATION AND SYMBOLS USED IN THIS TEST REPORT**EUT** : Equipment Under Test**AE** : Associated Equipment**N/A** : Not Applicable**N/T** : Not Tested**EMC** : Electromagnetic Compatibility**EMI** : Electromagnetic Interference**EMS** : Electromagnetic Susceptibility - indicates that the listed condition, standard or equipment is applicable for this report. - indicates that the listed condition, standard or equipment is not applicable for this report.

1 Description of the Equipment Under Test

1. Manufacturer : Sharp Corporation, Communication Systems Group
2-13-1, Iida Hachihonmatsu, Higashi-Hiroshima City, Hiroshima,
739-0192, JAPAN
2. Products : Cellular Phone
3. Model No. : SH-05E
4. Serial No. : 004401114675115
: 004401114675131
5. Product Type : Pre-production
6. Date of Manufacture : November, 2012
7. Power Rating : 4.0VDC (Internal Lithium-ion Battery SH36 1660mAh)
8. EUT Grounding : None
9. Transmitting Frequency : 2412.0 MHz(01CH) –2462.0MHz(11CH)
10. Receiving Frequency : 2412.0 MHz(01CH) –2462.0MHz(11CH)
11. Max. RF Output Power : 17.69dBm(Measure Value of IEEE802.11b)
: 20.04dBm(Measure Value of IEEE802.11g)
: 20.11dBm(Measure Value of IEEE802.11n)
12. Category : DTS
13. EUT Authorization : Certification
14. Received Date of EUT : November 27, 2012

15. Channel Plan

The carrier spacing is 5 MHz.

The carrier frequency is designated by the absolute frequency channel number (ARFCN).

The carrier frequency is expressed in the equation shown as follows:

Transmitting Frequency (in MHz) = $2407.0 + 5 \cdot n$

Receiving Frequency (in MHz) = $2407.0 + 5 \cdot n$

where, n : channel number ($1 \leq n \leq 11$)

2 Summary of Test Results

Applied Standard : CFR 47 FCC Rules and Regulations Part 15
Subpart C – Intentional Radiators

The EUT described in clause 1 was tested according to the applied standard shown above.
Details of the test configuration is shown in clause 6.

The conclusion for the test items of which are required by the applied standard is indicated under the test result.

- The test result was **passed** for the test requirements of the applied standard.
- The test result was **failed** for the test requirements of the applied standard.
- The test result was **not judged** the test requirements of the applied standard.

In the approval of test results,

- Determining compliance with the limits in this report was based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
- No deviations were employed from the applied standard.
- No modifications were conducted by JQA to achieve compliance to the limitations.

Reviewed by:

Tested by:



Shigeru Kinoshita
Deputy Manager
JQA KITA-KANSAI Testing Center
SAITO EMC Branch



Shigeru Osawa
Deputy Manager
JQA KITA-KANSAI Testing Center
SAITO EMC Branch

3 Test Procedure

Test Requirements : §15.247, §15.207 and §15.209

Test Procedure : ANSI C63.4-2003

The tests were performed with reference to FCC KDB 558074 D01 DTS Meas Guidance v02, released October 4, 2012. The test set-up was made in accordance to the general provisions of ANSI C63.4-2003.

4 Test Location

Japan Quality Assurance Organization (JQA)
KITA-KANSAI Testing Center
7-7, Ishimaru, 1-chome, Minoh-shi, Osaka, 562-0027, Japan
SAITO EMC Branch
7-3-10, Saito-asagi, Ibaraki-shi, Osaka 567-0085, Japan

5 Recognition of Test Laboratory

JQA KITA-KANSAI Testing Center SAITO EMC Branch is accredited under ISO/IEC 17025 by following accreditation bodies and the test facility is registered by the following bodies.

VLAC Accreditation No. : VLAC-001-2 (Expiry date : March 30, 2014)
VCCI Registration No. : A-0002 (Expiry date : March 30, 2014)
BSMI Registration No. : SL2-IN-E-6006, SL2-A1-E-6006 (Expiry date : September 14, 2013)
IC Registration No. : 2079E-3, 2079E-4 (Expiry date : July 20, 2014)

Accredited as conformity assessment body for Japan electrical appliances and material law by METI.
(Expiry date : February 22, 2013)

6 Details of the Equipment Under Test

6.1 Operating Condition

Transmitting/Receiving

Transmitting frequency : 2412.0 MHz(1CH) – 2462.0 MHz(11CH)
 Receiver frequency : 2412.0 MHz(1CH) – 2462.0 MHz(11CH)

Modulation Type

1. 802.11b : DSSS
2. 802.11g : OFDM
3. 802.11n : OFDM

Other Clock Frequency

32.768 kHz, 19.2 MHz, 27 MHz, 27.12 MHz

The EUT was rotated through three orthogonal axis (X, Y and Z axis) in radiated measurement.
 The EUT with temporary antenna port was used in conducted measurement.

6.2 Test Configuration

The equipment under test (EUT) consists of :

	Item	Manufacturer	Model No.	Serial No.	FCC ID
A	Cellular Phone	Sharp	SH-05E	0044011146 75115*1) 0044011146 75131*2)	APYHRO00186
B	Lithium-ion Battery	Sharp	SH36	--	N/A
C	AC Adapter	Panasonic Mobile	03	--	N/A
D	Stereo Handsfree	Sharp	SHLDL1	--	N/A

*1) Used for AC Powerline Conducted Emission and Field Strength of Spurious Emission

*2) Used for Antenna Conducted Emission

The auxiliary equipment used for testing :


None

Type of Cable:


No.	Description	Identification (Manu. etc.)	Connector Shielded	Cable Shielded	Ferrite Core	Length (m)
1	USB conversion cable (For AC Adapter)	--	--	NO	YES	1.2
2	Handsfree Cable	--	--	NO	NO	1.5

6.3 Test Arrangement (Drawings)


a) Single Unit



b) AC Adapter used



c) Stereo Handsfree used



■ : Ferrite Core

7 Details of the Test Item

7.1 Channel Separation

For the requirements, - Applicable [- Tested. - Not tested by applicant request.]
 - Not Applicable

For the limits, - **Passed** - **Failed** - **Not judged**

7.2 Minimum Hopping Channel

For the requirements, - Applicable [- Tested. - Not tested by applicant request.]
 - Not Applicable

For the limits, - **Passed** - **Failed** - **Not judged**

7.3 Occupied Bandwidth

For the requirements, - Applicable [- Tested. - Not tested by applicant request.]
 - Not Applicable

For the limits, - **Passed** - **Failed** - **Not judged**

7.3.1 Worst Point and Measurement Uncertainty

The 99% Bandwidth of IEEE802.11b is	<u>13.026</u> MHz	at	<u>2462.0</u> MHz
The 99% Bandwidth of IEEE802.11g is	<u>16.538</u> MHz	at	<u>2412.0</u> MHz
The 99% Bandwidth of IEEE802.11n is	<u>17.685</u> MHz	at	<u>2437.0</u> MHz

The 6dB Bandwidth of IEEE802.11b is	<u>8.493</u> MHz	at	<u>2412.0</u> MHz
The 6dB Bandwidth of IEEE802.11g is	<u>16.543</u> MHz	at	<u>2437.0</u> MHz
The 6dB Bandwidth of IEEE802.11n is	<u>17.750</u> MHz	at	<u>2437.0</u> MHz

Uncertainty of Measurement Results +/-0.9 %(2σ)

Remarks : _____

7.3.2 Test Site

KITA-KANSAI Testing Center

Test site : SAITO


<input type="checkbox"/> - Anechoic chamber (A1)	<input type="checkbox"/> - Measurement room (M1)
<input type="checkbox"/> - Measurement room (M2)	<input type="checkbox"/> - Measurement room (M3)
<input type="checkbox"/> - Shielded room (S1)	<input type="checkbox"/> - Shielded room (S2)
<input type="checkbox"/> - Shielded room (S3)	<input checked="" type="checkbox"/> - Shielded room (S4)

7.3.3 Test Instruments

Type	Model	Manufacturer	ID No.	Last Cal.	Interval
Spectrum Analyzer	E4446A	Agilent	A-39	2012/9	1 Year
RF Cable	SUCOFLEX102	SUHNER	C-52	2012/7	1 Year
Attenuator	54A-10	Weinschel	D-28	2012/9	1 Year

7.3.4 Test Method and Test Setup (Diagrammatic illustration)

The test system is shown as follows:



The setting of the spectrum analyzer are shown as follows:

Res. Bandwidth	100 kHz
Video Bandwidth	300 kHz
Span	30 MHz
Sweep Time	AUTO
Trace	Maxhold

7.3.5 Test Data

Test Date : December 4, 2012

Temp.:23°C, Humi:24%

The resolution bandwidth was set to 1 - 5 % of emission bandwidth (Max. 100 kHz), -6dBc display line was placed on the screen (or 99% bandwidth), the occupied bandwidth is the delta frequency between the two points where the display line intersects the signal trace.

A) IEEE 802.11b

1)Data Rate : 1Mbps

Channel	Frequency (MHz)	99% Bandwidth (MHz)	-6dBc Bandwidth (MHz)
01	2412.0	12.878	8.074
06	2437.0	12.966	8.088
11	2462.0	13.026	8.106

2)Data Rate : 2Mbps

Channel	Frequency (MHz)	99% Bandwidth (MHz)	-6dBc Bandwidth (MHz)
01	2412.0	12.925	7.992
06	2437.0	12.981	8.205
11	2462.0	12.991	8.042

3)Data Rate : 5.5Mbps

Channel	Frequency (MHz)	99% Bandwidth (MHz)	-6dBc Bandwidth (MHz)
01	2412.0	12.769	8.493
06	2437.0	12.807	7.778
11	2462.0	12.764	8.410

4)Data Rate : 11Mbps

Channel	Frequency (MHz)	99% Bandwidth (MHz)	-6dBc Bandwidth (MHz)
01	2412.0	12.779	8.346
06	2437.0	12.755	8.195
11	2462.0	12.916	8.443

B) IEEE 802.11g

1) Data Rate : 6Mbps

Channel	Frequency (MHz)	99% Bandwidth (MHz)	-6dBc Bandwidth (MHz)
01	2412.0	16.538	16.414
06	2437.0	16.518	16.445
11	2462.0	16.510	16.413

2) Data Rate : 54Mbps

Channel	Frequency (MHz)	99% Bandwidth (MHz)	-6dBc Bandwidth (MHz)
01	2412.0	16.447	16.505
06	2437.0	16.463	16.543
11	2462.0	16.454	16.491

C) IEEE 802.11n


1) Data Rate : 6.5Mbps

Channel	Frequency (MHz)	99% Bandwidth (MHz)	-6dBc Bandwidth (MHz)
01	2412.0	17.684	17.630
06	2437.0	17.685	17.630
11	2462.0	17.678	17.612

2) Data Rate : 65Mbps


Channel	Frequency (MHz)	99% Bandwidth (MHz)	-6dBc Bandwidth (MHz)
01	2412.0	17.647	17.718
06	2437.0	17.651	17.750
11	2462.0	17.644	17.700

1)Data Rate : 1Mbps(IEEE 802.11b)
Low Channel




Transmit Freq Error 65.506 kHz
Occupied Bandwidth 8.074 MHz

Middle Channel




Transmit Freq Error -3.967 kHz
Occupied Bandwidth 8.088 MHz

High Channel




2)Data Rate : 2Mbps(IEEE 802.11b)


Low Channel




Middle Channel




High Channel




3)Data Rate : 5.5Mbps(IEEE 802.11b)
Low Channel



Middle Channel




High Channel




4)Data Rate : 11Mbps(IEEE 802.11b)


Low Channel




Middle Channel




High Channel




5)Data Rate : 6Mbps(IEEE 802.11g)
Low Channel



Middle Channel




High Channel




6)Data Rate : 54Mbps(IEEE 802.11g)


Low Channel




Middle Channel




High Channel




7)Data Rate : 6.5Mbps(IEEE 802.11n)
 Low Channel



Middle Channel




High Channel




8)Data Rate : 65Mbps(IEEE 802.11n)


Low Channel



Middle Channel



High Channel



7.4 Dwell Time

For the requirements, - Applicable - Tested. - Not tested by applicant request.]
 - Not Applicable

For the limits, - Passed - Failed - Not judged

7.5 Peak Output Power(Conduction)

For the requirements, - Applicable - Tested. - Not tested by applicant request.]
 - Not Applicable

For the limits, - Passed - Failed - Not judged

7.5.1 Worst Point and Measurement Uncertainty

Peak Output Power of IEEE802.11b is	<u>17.69</u>	dBm	at	<u>2412.0</u>	MHz
Peak Output Power of IEEE802.11g is	<u>20.04</u>	dBm	at	<u>2412.0</u>	MHz
Peak Output Power of IEEE802.11n is	<u>20.11</u>	dBm	at	<u>2412.0</u>	MHz

Uncertainty of Measurement Results at Amplitude +/-1.2 dB(2 σ)

Remarks : _____

7.5.2 Test Site

KITA-KANSAI Testing Center

Test site : SAITO


<input type="checkbox"/> - Anechoic chamber (A1)	<input type="checkbox"/> - Measurement room (M1)
<input type="checkbox"/> - Measurement room (M2)	<input type="checkbox"/> - Measurement room (M3)
<input type="checkbox"/> - Shielded room (S1)	<input type="checkbox"/> - Shielded room (S2)
<input type="checkbox"/> - Shielded room (S3)	<input checked="" type="checkbox"/> - Shielded room (S4)

7.5.3 Test Instruments

Type	Model	Manufacturer	ID No.	Last Cal.	Interval
Spectrum Analyzer	E4446A	Agilent	A-39	2012/9	1 Year
Attenuator	54A-10	Weinschel	D-28	2012/9	1 Year
RF Cable	SUCOFLEX102	SUHNER	C-52	2012/7	1 Year

7.5.4 Test Method and Test Setup (Diagrammatic illustration)

The Conducted RF Power Output was measured with a power meter, one 10dB attenuator and a short, low loss cable.



7.5.5 Test Data

1) Data Rate : 1Mbps(IEEE 802.11b)

Test Date: November 27, 2012
Temp.: 22 °C, Humi.: 35 %

Data Rate : 1Mbps


Transmitting Frequency	Correction Factor	Meter Reading	Conducted Peak Output Power		Limits	Margin	
CH	[MHz]	[dB]	[dBm]	[dBm]	[mW]	[dB]	
01	2412	10.31	3.94	14.25	26.61	30.00	+15.75
06	2437	10.31	3.86	14.17	26.12	30.00	+15.83
11	2462	10.32	3.55	13.87	24.38	30.00	+16.13

Calculated result at 2412.000 MHz, as the worst point shown on underline:
 Correction Factor = 10.31 dB
 +) Meter Reading = 3.94 dBm
 Result = 14.25 dBm = 26.61 mW
 Minimum Margin: 30.00 - 14.25 = 15.75 (dB)

NOTES
 1. The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.
 2. Setting of measuring instrument(s):

Detector Function	RES B.W.	Video B.W.
Peak	1MHz	3MHz

The band power function was used.



2)Data Rate : 2Mbps(IEEE 802.11b)

Test Date: November 27, 2012

Temp.: 22 °C, Humi: 35 %

Data Rate : 2Mbps

CH	Transmitting Frequency [MHz]	Correction Factor [dB]	Meter Reading [dBm]	Conducted Peak Output Power		Limits [dBm]	Margin [dB]
				[dBm]	[mW]		
01	2412	10.31	4.22	14.53	28.38	30.00	+15.47
06	2437	10.31	4.16	14.47	27.99	30.00	+15.53
11	2462	10.32	3.86	14.18	26.18	30.00	+15.82

Calculated result at 2412.000 MHz, as the worst point shown on underline:

Correction Factor	=	10.31 dB
+) Meter Reading	=	4.22 dBm
Result	=	14.53 dBm = 28.38 mW


Minimum Margin: 30.00 - 14.53 = 15.47 (dB)

NOTES

- The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.
- Setting of measuring instrument(s) :

Detector Function	RES B.W.	Video B.W.
Peak	1MHz	3MHz

The band power function was used.



3)Data Rate : 5.5Mbps(IEEE 802.11b)

Test Date: November 27, 2012
 Temp: 22 °C, Humi: 35 %

Data Rate : 5.5Mbps


CH	Transmitting Frequency [MHz]	Correction Factor [dB]	Meter Reading [dBm]	Conducted Peak Output Power		Limits [dBm]	Margin [dB]
				[dBm]	[mW]		
01	2412	10.31	5.53	15.84	38.37	30.00	+14.16
06	2437	10.31	5.73	16.04	40.18	30.00	+13.96
11	2462	10.32	5.47	15.79	37.93	30.00	+14.21

Calculated result at 2437.000 MHz, as the worst point shown on underline:
 Correction Factor = 10.31 dB
 +) Meter Reading = 5.73 dBm
 Result = 16.04 dBm = 40.18 mW
 Minimum Margin: 30.00 - 16.04 = 13.96 (dB)

NOTES
 1. The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.
 2. Setting of measuring instrument(s):

Detector Function	RES B.W.	Video B.W.
Peak	1MHz	3MHz

The band power function was used.



4)Data Rate : 11Mbps(IEEE 802.11b)

Test Date: November 27, 2012
 Temp: 22 °C, Humi: 35 %

Data Rate : 11Mbps


CH	Transmitting Frequency [MHz]	Correction Factor [dB]	Meter Reading [dBm]	Conducted Peak Output Power [dBm]	Conducted Peak Output Power [mW]	Limits [dBm]	Margin [dB]
01	2412	10.31	7.38	17.69	58.75	30.00	+12.31
06	2437	10.31	6.99	17.30	53.70	30.00	+12.70
11	2462	10.32	6.94	17.26	53.21	30.00	+12.74

Calculated result at 2412.000 MHz, as the worst point shown on underline:
 Correction Factor = 10.31 dB
 +) Meter Reading = 7.38 dBm
 Result = 17.69 dBm = 58.75 mW
 Minimum Margin: 30.00 - 17.69 = 12.31 (dB)

NOTES
 1. The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.
 2. Setting of measuring instrument(s) :

Detector Function	RES B.W.	Video B.W.
Peak	1MHz	3MHz

The band power function was used.



5)Data Rate : 6Mbps(IEEE 802.11g)

Test Date: November 27, 2012
Temp: 22 °C. Humi: 35 %

Data Rate : 6Mbps


CH	Transmitting Frequency [MHz]	Correction Factor [dB]	Meter Reading [dBm]	Conducted Peak Output Power [dBm]	Conducted Peak Output Power [mW]	Limits [dBm]	Margin [dB]
01	2412	10.31	8.85	19.16	82.41	30.00	+10.84
06	2437	10.31	8.75	19.06	80.54	30.00	+10.94
11	2462	10.32	8.38	18.70	74.13	30.00	+11.30

Calculated result at 2412.000 MHz, as the worst point shown on underline:
 Correction Factor = 10.31 dB
 +) Meter Reading = 8.85 dBm
 Result = 19.16 dBm = 82.41 mW
 Minimum Margin: 30.00 - 19.16 = 10.84 (dB)

NOTES
 1. The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.
 2. Setting of measuring instrument(s) :

Detector Function	RES B.W.	Video B.W.
Peak	1MHz	3MHz

The band power function was used.



6) Data Rate : 54Mbps(IEEE 802.11g)

Test Date: November 27, 2012
 Temp.: 22 °C, Humi: 35 %

Data Rate : 54Mbps


Transmitting Frequency	Correction Factor	Meter Reading	Conducted Peak Output Power		Limits	Margin	
CH	[MHz]	[dB]	[dBm]	[dBm]	[mW]	[dB]	
01	2412	10.31	9.73	20.04	100.93	30.00	+ 9.96
06	2437	10.31	9.72	20.03	100.69	30.00	+ 9.97
11	2462	10.32	9.28	19.60	91.20	30.00	+10.40

Calculated result at 2412.000 MHz, as the worst point shown on underline:
 Correction Factor = 10.31 dB
 +) Meter Reading = 9.73 dBm
 Result = 20.04 dBm = 100.93 mW
 Minimum Margin: 30.00 - 20.04 = 9.96 (dB)

NOTES
 1. The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.
 2. Setting of measuring instrument(s):

Detector Function	RES B.W.	Video B.W.
Peak	1MHz	3MHz

The band power function was used.



7)Data Rate : 6.5Mbps(IEEE 802.11n)

Test Date: November 27, 2012
Temp.: 22 °C, Humi.: 35 %

Data Rate : 6.5Mbps


CH	Transmitting Frequency [MHz]	Correction Factor [dB]	Meter Reading [dBm]	Conducted Peak Output Power [dBm]	Conducted Peak Output Power [mW]	Limits [dBm]	Margin [dB]
01	2412	10.31	9.05	19.36	86.30	30.00	+10.64
06	2437	10.31	8.78	19.09	81.10	30.00	+10.91
11	2462	10.32	8.35	18.67	73.62	30.00	+11.33

Calculated result at 2412.000 MHz, as the worst point shown on underline:
 Correction Factor = 10.31 dB
 +) Meter Reading = 9.05 dBm
 Result = 19.36 dBm = 86.30 mW
 Minimum Margin: 30.00 - 19.36 = 10.64 (dB)

NOTES
 1. The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.
 2. Setting of measuring instrument(s):

Detector Function	RES B.W.	Video B.W.
Peak	1MHz	3MHz

The band power function was used.



8)Data Rate : 65Mbps(IEEE 802.11n)

Test Date: November 27, 2012
 Temp: 22 °C, Humi: 35 %

Data Rate : 65Mbps


Transmitting Frequency	Correction Factor	Meter Reading	Conducted Peak Output Power		Limits	Margin	
CH	[MHz]	[dB]	[dBm]	[dBm]	[mW]	[dB]	
01	2412	10.31	9.80	20.11	102.57	30.00	+ 9.89
06	2437	10.31	9.48	19.79	95.28	30.00	+10.21
11	2462	10.32	9.31	19.63	91.83	30.00	+10.37

Calculated result at 2412.000 MHz, as the worst point shown on underline:
 Correction Factor = 10.31 dB
 +) Meter Reading = 9.80 dBm
 Result = 20.11 dBm = 102.57 mW
 Minimum Margin: 30.00 - 20.11 = 9.89 (dB)

NOTES
 1. The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.
 2. Setting of measuring instrument(s):

Detector Function	RES B.W.	Video B.W.
Peak	1MHz	3MHz

The band power function was used.



7.6 Peak Power Density(Conduction)

For the requirements, - Applicable - Tested. - Not tested by applicant request.]
 - Not Applicable

For the limits, - Passed - Failed - Not judged

7.6.1 Worst Point and Measurement Uncertainty

Peak Power Density of IEEE802.11b is	<u>-10.11</u>	dBm	at	<u>2412.0</u>	MHz
Peak Power Density of IEEE802.11g is	<u>-14.80</u>	dBm	at	<u>2437.0</u>	MHz
Peak Power Density of IEEE802.11n is	<u>-15.36</u>	dBm	at	<u>2462.0</u>	MHz

Uncertainty of Measurement Results at Amplitude +/-1.2 dB(2σ)

Remarks : _____

7.6.2 Test Site

KITA-KANSAI Testing Center

Test site : SAITO


<input type="checkbox"/> - Anechoic chamber (A1)	<input type="checkbox"/> - Measurement room (M1)
<input type="checkbox"/> - Measurement room (M2)	<input type="checkbox"/> - Measurement room (M3)
<input type="checkbox"/> - Shielded room (S1)	<input type="checkbox"/> - Shielded room (S2)
<input type="checkbox"/> - Shielded room (S3)	<input checked="" type="checkbox"/> - Shielded room (S4)

7.6.3 Test Instruments

Type	Model	Manufacturer	ID No.	Last Cal.	Interval
Spectrum Analyzer	E4446A	Agilent	A-39	2012/9	1 Year
Attenuator	54A-10	Weinschel	D-28	2012/9	1 Year
RF Cable	SUCOFLEX102	SUHNER	C-52	2012/7	1 Year

7.6.4 Test Method and Test Setup (Diagrammatic illustration)

The Conducted RF Power Output was measured with a power meter, one 10dB attenuator and a short, low loss cable.



7.6.5 Test Data

1) Data Rate : 1Mbps(IEEE 802.11b)

Test Date: December 4, 2012

Temp.: 23 °C. Humi: 24 %

Data Rate : 1Mbps

Transmitting Frequency	Correction Factor	BWCF	Meter Reading	Conducted Peak Power Density		Limits	Margin
CH	[MHz]	[dB]	[dBm]	[dBm]	[mW]	[dBm]	[dB]
01	2412	10.31	-10.42	-10.11	0.10	8.00	+18.11
06	2437	10.31	-10.70	-10.39	0.09	8.00	+18.39
11	2462	10.32	-11.67	-11.35	0.07	8.00	+19.35

Calculated result at 2412.000 MHz, as the worst point shown on underline:


Correction Factor	=	10.31 dB
BWCF	=	-10.00 dB
+) Meter Reading	=	-10.42 dBm
Result	=	-10.11 dBm = 0.10 mW

Minimum Margin: 8.00 - -10.11 = 18.11 (dB)

NOTES

1. The peak power density complied with the limit without BWCF.
2. The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.
3. BWCF(bandwidth correction factor) = $10 \log(3 \text{ kHz}/30 \text{ kHz}) = -10.0 \text{ dB}$
4. Setting of measuring instrument(s) :

Detector Function	RES B.W.	Video B.W.
Peak	30kHz	100kHz



2)Data Rate : 2Mbps(IEEE 802.11b)

Test Date: December 4, 2012

Temp.: 23 °C. Humi: 24 %

Data Rate : 2Mbps

Transmitting Frequency	Correction Factor	BWCF	Meter Reading	Conducted Peak Power Density		Limits	Margin
CH	[MHz]	[dB]	[dBm]	[dBm]	[mW]	[dBm]	[dB]
01	2412	10.31	-10.00	-11.71	-11.40	0.07	+19.40
06	2437	10.31	-10.00	-11.42	-11.11	0.08	+19.11
11	2462	10.32	-10.00	-11.15	-10.83	0.08	+18.83

Calculated result at 2462.000 MHz, as the worst point shown on underline:



Correction Factor	=	10.32 dB
BWCF	=	-10.00 dB
+) Meter Reading	=	-11.15 dBm
Result	=	-10.83 dBm = 0.08 mW

Minimum Margin: 8.00 - -10.83 = 18.83 (dB)

NOTES

1. The peak power density complied with the limit without BWCF.
2. The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.
3. BWCF(bandwidth correction factor) = $10 \log (3 \text{ kHz}/30 \text{ kHz}) = -10.0 \text{ dB}$
4. Setting of measuring instrument(s) :

Detector Function	RES B.W.	Video B.W.
Peak	30kHz	100kHz



3)Data Rate : 5.5Mbps(IEEE 802.11b)

Test Date: December 4, 2012

Temp.: 23 °C. Humi: 24 %

Data Rate : 5.5Mbps

Transmitting Frequency	Correction Factor	BWCF	Meter Reading	Conducted Peak Power Density		Limits	Margin
CH	[MHz]	[dB]	[dBm]	[dBm]	[mW]	[dBm]	[dB]
01	2412	10.31	-10.89	-10.58	0.09	8.00	+18.58
06	2437	10.31	-12.11	-11.80	0.07	8.00	+19.80
11	2462	10.32	-12.92	-12.60	0.05	8.00	+20.60

Calculated result at 2412.000 MHz, as the worst point shown on underline:


Correction Factor	=	10.31 dB
BWCF	=	-10.00 dB
+) Meter Reading	=	-10.89 dBm
Result	=	-10.58 dBm = 0.09 mW

Minimum Margin: 8.00 - -10.58 = 18.58 (dB)

NOTES

1. The peak power density complied with the limit without BWCF.
2. The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.
3. BWCF(bandwidth correction factor) = $10 \log (3 \text{ kHz}/30 \text{ kHz}) = -10.0 \text{ dB}$
4. Setting of measuring instrument(s) :

Detector Function	RES B.W.	Video B.W.
Peak	30kHz	100kHz



4)Data Rate : 11Mbps(IEEE 802.11b)

Test Date: December 4, 2012
Temp.: 23 °C. Humi: 24 %


Data Rate : 11Mbps

Transmitting Frequency	Correction Factor	BWCF	Meter Reading	Conducted Peak Power Density		Limits	Margin
CH	[MHz]	[dB]	[dBm]	[dBm]	[mW]	[dBm]	[dB]
01	2412	10.31	-10.00	-12.08	0.07	8.00	+19.77
06	2437	10.31	-10.00	-12.16	0.07	8.00	+19.85
11	2462	10.32	-10.00	-11.87	0.07	8.00	+19.55

Calculated result at 2462.000 MHz, as the worst point shown on underline:
 Correction Factor = 10.32 dB
 BWCF = -10.00 dB
 +) Meter Reading = -11.87 dBm
 Result = -11.55 dBm = 0.07 mW
 Minimum Margin: 8.00 - -11.55 = 19.55 (dB)

NOTES
 1. The peak power density complied with the limit without BWCF.
 2. The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.
 3. BWCF(bandwidth correction factor) = 10 log (3 kHz/30 kHz) = -10.0 dB
 4. Setting of measuring instrument(s) :

Detector Function	RES B.W.	Video B.W.
Peak	30kHz	100kHz



5) Data Rate : 6Mbps(IEEE 802.11g)

Test Date: December 4, 2012
Temp.: 23 °C, Humi: 24 %


Data Rate : 6Mbps

CH	Transmitting Frequency [MHz]	Correction Factor [dB]	BWCF [dB]	Meter Reading [dBm]	Conducted Peak Power Density [dBm]	Conducted Peak Power Density [mW]	Limits [dBm]	Margin [dB]
01	2412	10.31	-10.00	-15.65	-15.34	0.03	8.00	+23.34
06	2437	10.31	-10.00	-15.84	-15.53	0.03	8.00	+23.53
11	2462	10.32	-10.00	-16.43	-16.11	0.02	8.00	+24.11

Calculated result at 2412.000 MHz, as the worst point shown on underline:
 Correction Factor = 10.31 dB
 BWCF = -10.00 dB
 +) Meter Reading = -15.65 dBm
 Result = -15.34 dBm = 0.03 mW
 Minimum Margin: 8.00 - -15.34 = 23.34 (dB)

NOTES
 1. The peak power density complied with the limit without BWCF.
 2. The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.
 3. BWCF(bandwidth correction factor) = 10 log (3 kHz/30 kHz) = -10.0 dB
 4. Setting of measuring instrument(s):

Detector Function	RES B.W.	Video B.W.
Peak	30kHz	100kHz



6) Data Rate : 54Mbps(IEEE 802.11g)

Test Date: December 4, 2012
 Temp.: 23 °C, Humi: 24 %


Data Rate : 54Mbps

CH	Transmitting Frequency [MHz]	Correction Factor [dB]	BWCF [dB]	Meter Reading [dBm]	Conducted Peak Power Density [dBm] [mW]	Limits [dBm]	Margin [dB]
01	2412	10.31	-10.00	-15.14	-14.83 0.03	8.00	+22.83
06	2437	10.31	-10.00	-15.11	-14.80 0.03	8.00	+22.80
11	2462	10.32	-10.00	-16.15	-15.83 0.03	8.00	+23.83

Calculated result at 2437.000 MHz, as the worst point shown on underline:
 Correction Factor = 10.31 dB
 BWCF = -10.00 dB
 +) Meter Reading = -15.11 dBm
 Result = -14.80 dBm = 0.03 mW
 Minimum Margin: 8.00 - -14.80 = 22.80 (dB)

NOTES
 1. The peak power density complied with the limit without BWCF.
 2. The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.
 3. BWCF(bandwidth correction factor) = 10 log (3 kHz/30 kHz) = -10.0 dB
 4. Setting of measuring instrument(s) :

Detector Function	RES B.W.	Video B.W.
Peak	30kHz	100kHz



7) Data Rate : 6.5Mbps(IEEE 802.11n)

Test Date: December 4, 2012
Temp.: 23 °C, Humi: 24 %

Data Rate : 6.5Mbps

CH	Transmitting Frequency [MHz]	Correction Factor [dB]	BWCF [dB]	Meter Reading [dBm]	Conducted Peak Power Density [dBm] [mW]	Limits [dBm]	Margin [dB]
01	2412	10.31	-10.00	-16.22	-15.91 0.03	8.00	+23.91
06	2437	10.31	-10.00	-16.20	-15.89 0.03	8.00	+23.89
11	2462	10.32	-10.00	-16.63	-16.31 0.02	8.00	+24.31

Calculated result at 2437.000 MHz, as the worst point shown on underline:


Correction Factor	=	10.31 dB
BWCF	=	-10.00 dB
+) Meter Reading	=	-16.20 dBm
Result	=	-15.89 dBm = 0.03 mW

Minimum Margin: 8.00 - -15.89 = 23.89 (dB)

NOTES

1. The peak power density complied with the limit without BWCF.
2. The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.
3. BWCF(bandwidth correction factor) = $10 \log(3 \text{ kHz}/30 \text{ kHz}) = -10.0 \text{ dB}$
4. Setting of measuring instrument(s) :

Detector Function	RES B.W.	Video B.W.
Peak	30kHz	100kHz



8) Data Rate : 65Mbps(IEEE 802.11n)

Test Date: December 4, 2012
 Temp.: 23 °C, Humi: 24 %


Data Rate : 65Mbps

CH	Transmitting Frequency [MHz]	Correction Factor [dB]	BWCF [dB]	Meter Reading [dBm]	Conducted Peak Power Density [dBm] [mW]	Limits [dBm]	Margin [dB]
01	2412	10.31	-10.00	-15.73	-15.42 0.03	8.00	+23.42
06	2437	10.31	-10.00	-15.84	-15.53 0.03	8.00	+23.53
11	2462	10.32	-10.00	-15.68	-15.36 0.03	8.00	+23.36

Calculated result at 2462.000 MHz, as the worst point shown on underline:
 Correction Factor = 10.32 dB
 BWCF = -10.00 dB
 +) Meter Reading = -15.68 dBm
 Result = -15.36 dBm = 0.03 mW
 Minimum Margin: 8.00 - -15.36 = 23.36 (dB)

NOTES
 1. The peak power density complied with the limit without BWCF.
 2. The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.
 3. BWCF(bandwidth correction factor) = 10 log (3 kHz/30 kHz) = -10.0 dB
 4. Setting of measuring instrument(s) :

Detector Function	RES B.W.	Video B.W.
Peak	30kHz	100kHz



7.7 Spurious Emissions(Conduction)

For the requirements, - Applicable - Tested. - Not tested by applicant request.]
 - Not Applicable

For the limits, - Passed - Failed - Not judged

7.7.1 Worst Point and Measurement Uncertainty

Uncertainty of Measurement Results	9 kHz – 1GHz	<u>+/-1.0</u>	dB(2 σ)
	1GHz – 18GHz	<u>+/-1.2</u>	dB(2 σ)
	18GHz – 40GHz	<u>+/-1.6</u>	dB(2 σ)

Remarks : _____

7.7.2 Test Site

KITA-KANSAI Testing Center

Test site : SAITO


<input type="checkbox"/> - Anechoic chamber (A1)	<input type="checkbox"/> - Measurement room (M1)
<input type="checkbox"/> - Measurement room (M2)	<input type="checkbox"/> - Measurement room (M3)
<input type="checkbox"/> - Shielded room (S1)	<input type="checkbox"/> - Shielded room (S2)
<input type="checkbox"/> - Shielded room (S3)	<input checked="" type="checkbox"/> - Shielded room (S4)

7.7.3 Test Instruments

Type	Model	Manufacturer	ID No.	Last Cal.	Interval
Spectrum Analyzer	E4446A	Agilent	A-39	2012/9	1 Year
Attenuator	54A-10	Weinschel	D-28	2012/9	1 Year
RF Cable	SUCOFLEX102	SUHNER	C-52	2012/7	1 Year

7.7.4 Test Method and Test Setup (Diagrammatic illustration)

The test system is shown as follows:



The setting of the spectrum analyzer are shown as follows:


Frequency Range	30 MHz - 25 GHz	Band-Edge
Res. Bandwidth	100 kHz	100 kHz
Video Bandwidth	300 kHz	300 kHz
Sweep Time	AUTO	AUTO
Trace	Maxhold	Maxhold

7.7.5 Test Data


Test Date : December 4, 2012

Temp.:23°C, Humi:24%


1)Data Rate : 1Mbps(IEEE 802.11b)
Low Channel



Middle Channel




High Channel




2)Data Rate : 11Mbps(IEEE 802.11b)


Low Channel




Middle Channel




High Channel




3)Data Rate : 6Mbps(IEEE 802.11g)
Low Channel



Middle Channel




High Channel




4)Data Rate : 54Mbps(IEEE 802.11g)


Low Channel




Middle Channel




High Channel




5)Data Rate : 6.5Mbps(IEEE 802.11n)
Low Channel



Middle Channel




High Channel




6)Data Rate : 65Mbps(IEEE 802.11n)


Low Channel



Middle Channel




High Channel




Band-Edge Emission


1)Data Rate : 1Mbps(IEEE 802.11b)
Low Channel




High Channel




2)Data Rate : 11Mbps(IEEE 802.11b)
Low Channel




High Channel




3)Data Rate : 6Mbps(IEEE 802.11g)
Low Channel




High Channel




4)Data Rate : 54Mbps(IEEE 802.11g)
Low Channel




High Channel




5)Data Rate : 6.5Mbps(IEEE 802.11n)
Low Channel




High Channel



6) Data Rate : 65Mbps(IEEE 802.11n)
Low Channel



High Channel



7.8 AC Powerline Conducted Emission

For the requirements, - Applicable - Tested. - Not tested by applicant request.]
 - Not Applicable

For the limits, - Passed - Failed - Not judged

7.8.1 Worst Point and Measurement Uncertainty

Min. Limit Margin (Quasi-Peak) 16.2 dB at 2.77 MHz

Uncertainty of Measurement Results +/-2.7 dB(2σ)

Remarks : _____

7.8.2 Test Site

KITA-KANSAI Testing Center

Test site : SAITO - Anechoic chamber (A1) - Measurement room (M1)
 - Measurement room (M2) - Measurement room (M3)
 - Shielded room (S1) - Shielded room (S2)
 - Shielded room (S3) - Shielded room (S4)

7.8.3 Test Instruments

Type	Model	Manufacturer	ID No.	Last Cal.	Interval
Test Receiver	ESU 26	Rohde & Schwarz	A-6	2012/4	1 Year
AMN (main)	KNW-407R	Kyoritsu	D-39	2012/9	1 Year
RF Cable	RG223/U	SUHNER	H-9	2012/7	1 Year


7.8.4 Test Method and Test Setup (Diagrammatic illustration)

The preliminary tests were performed using the scan mode of test receiver or spectrum analyzer to observe the emissions characteristics of the EUT.

The EUT configuration, cable configuration and mode of operation were determined for producing the maximum level of emissions.

This configurations was used for final tests.

– Side View –



NOTE

AMN : Artificial Mains Network


7.8.5 Test Data

Mode of EUT : All modes have been investigated and the worst case mode for channel (06ch: 2437MHz / IEEE 802.11b, IEEE 802.11g and IEEE 802.11n) has been listed.

Test Date: December 5, 2012

Temp.: 23 °C, Humi.: 35 %

Frequency [MHz]	Corr. Factor [dB]	Meter Readings [dB(μV)]				Limits [dB(μV)]		Results [dB(μV)]		Margin [dB]	Remarks
		VA QP	VA AVE	VB QP	VB AVE	QP	AVE	QP	AVE		
0.17	10.4	26.4	--	25.3	--	65.0	55.0	36.8	--	+28.2	-
0.25	10.3	25.0	--	26.1	--	61.8	51.8	36.4	--	+25.4	-
0.88	10.3	24.5	--	20.5	--	56.0	46.0	34.8	--	+21.2	-
1.27	10.3	29.0	--	25.3	--	56.0	46.0	39.3	--	+16.7	-
1.65	10.4	25.7	--	25.3	--	56.0	46.0	36.1	--	+19.9	-
2.77	10.4	22.9	--	29.4	--	56.0	46.0	39.8	--	+16.2	-
3.43	10.4	25.5	--	11.5	--	56.0	46.0	35.9	--	+20.1	-
1.31	10.3	14.8	--	< 10.0	--	56.0	46.0	25.1	--	+30.9	-



NOTES

1. The spectrum was checked from 0.15 MHz to 30 MHz.
2. The correction factor includes the AMN insertion loss and the cable loss.
3. The symbol of "<" means "or less".
4. The symbol of ">" means "more than".
5. The symbol of "--" means "not applicable".
6. Calculated result at 2.77 MHz, as the worst point shown on underline:
Correction Factor + Meter Reading = 10.4 + 29.4 = 39.8 dB(μV)
7. QP : Quasi-Peak Detector / AVE : Average Detector
8. Test receiver setting(s) : CISPR QP 9 kHz / Average 9 kHz

7.9 Radiated Emission

The requirements are - Applicable - Tested. - Not tested by applicant request.]
 - Not Applicable

- Passed - Failed - Not judged

7.9.1 Worst Point and Measurement Uncertainty

Min. Limit Margin (Average) >5.4 dB at 22158.0 MHz

Uncertainty of Measurement Results	9 kHz – 30 MHz	<u>+/-1.9</u>	dB(2 σ)
	30 MHz – 300 MHz	<u>+/-4.3</u>	dB(2 σ)
	300 MHz – 1000 MHz	<u>+/-5.4</u>	dB(2 σ)
	1 GHz – 6 GHz	<u>+/-4.6</u>	dB(2 σ)
	6 GHz – 18 GHz	<u>+/-5.2</u>	dB(2 σ)
	18 GHz – 40 GHz	<u>+/-5.4</u>	dB(2 σ)

Remarks : _____

7.9.2 Test Site

KITA-KANSAI Testing Center SAITO EMC Branch

- Anechoic chamber A1

- Anechoic chamber A2

7.9.3 Test Instruments

Type	Model	Manufacturer	ID No.	Last Cal.	Interval
Test Receiver	ESU26	Rohde & Schwarz	A-6	2012/4	1 Year
Loop Antenna	HFH2-Z2	Rohde & Schwarz	C-2	2012/8	1 Year
RF Cable	RG213/U	SUHNER	H-28	2012/8	1 Year
Biconical Antenna	VHA9103/BBA9106	Schwarzbeck	C-30	2012/5	1 Year
Log-periodic Antenna	UHALP9108-A1	Schwarzbeck	C-31	2012/5	1 Year
RF Cable	S 10162 B-11 etc.	SUHNER	H-4	2012/3	1 Year
Site Attenuation	--	----	H-15	2012/2	1 Year
Pre-Amplifier	WJ-6882-824	Watkins Johnson	A-21	2012/1	1 Year
Pre-Amplifier	WJ-6611-513	Watkins Johnson	A-23	2012/1	1 Year
Pre-Amplifier	BZ1840LD1	B&Z	A-29	2012/1	1 Year
Pre-Amplifier	DBL-0618N515	DBS Microwave	A-33	2012/1	1 Year
Horn Antenna	91888-2	EATON	C-41-1	2012/6	1 Year
Horn Antenna	91889-2	EATON	C-41-2	2012/6	1 Year
Horn Antenna	3160-04	EMCO	C-55	2011/6	2 Years
Horn Antenna	3160-05	EMCO	C-56	2011/6	2 Years
Horn Antenna	3160-06	EMCO	C-57	2011/6	2 Years
Horn Antenna	3160-07	EMCO	C-58	2011/6	2 Years
Horn Antenna	3160-08	EMCO	C-59	2011/6	2 Years
Horn Antenna	3160-09	EMCO	C-48	2011/6	2 Years
Attenuator	54A-10	Weinschel	D-29	2012/9	1 Year
Attenuator	2-10	Weinschel	D-79	2012/11	1 Year
Band Rejection Filter	BRM50701	MICRO-TRONICS	D-93	2012/2	1 Year
RF Cable	SUCOFLEX102	SUHNER	C-52	2012/7	1 Year
RF Cable	SUCOFLEX104	SUHNER	C-66	2012/1	1 Year
RF Cable	SUCOFLEX104	SUHNER	C-67	2012/1	1 Year
RF Cable	SUCOFLEX102EA	SUHNER	C-69	2012/1	1 Year
SVSWR	--	----	H-19	2012/2	1 Year

7.9.4 Test Method and Test Setup (Diagrammatic illustration)


7.9.4.1 Radiated Emission 9 kHz – 30 MHz

The preliminary tests were performed at the measurement distance that specified for compliance to determine the emission characteristics of the EUT.

The EUT configuration(in X, Y and Z axis), cable configuration and mode of operation were determined for producing the maximum level of emissions.

This configurations was used for the final tests.

– Side View –




7.9.4.2 Radiated Emission 30 MHz – 1000 MHz

The preliminary tests were performed at the measurement distance that specified for compliance to determine the emission characteristics of the EUT.

The EUT configuration(in X, Y and Z axis), cable configuration and mode of operation were determined for producing the maximum level of emissions.

This configurations was used for the final tests.

– Side View –




7.9.4.3 Radiated Emission above 1 GHz

The preliminary tests were performed at the measurement distance that specified for compliance to determine the emission characteristics of the EUT.

The EUT configuration(in X, Y and Z axis), cable configuration and mode of operation were determined for producing the maximum level of emissions.

This configurations was used for the final tests.

– Side View –



NOTE

The antenna height is scanned depending on the EUT's size and mounting height.

7.9.5 Test Data


7.9.5.1 Band-edge Compliance

Test Date : December 1, 2012

Temp.:22°C, Humi:38%

Mode of EUT : TX(1ch: 2412 MHz, data rate : 1Mbps(IEEE 802.11b))


Antenna Polarization : Horizontal



Note: The trace 1 is Peak detection. The trace 2 is RMS detection.

Mode of EUT : TX(1ch: 2412 MHz, data rate : 1Mbps(IEEE 802.11b))


Antenna Polarization : Vertical



Note: The trace 1 is Peak detection. The trace 2 is RMS detection.

Mode of EUT : TX(11ch: 2462 MHz, data rate : 1Mbps(IEEE 802.11b))


Antenna Polarization : Horizontal



Note: The trace 1 is Peak detection. The trace 2 is RMS detection.


Mode of EUT : TX(11ch: 2462 MHz, data rate : 1Mbps(IEEE 802.11b))

Antenna Polarization : Vertical



Note: The trace 1 is Peak detection. The trace 2 is RMS detection.


Mode of EUT : TX(1ch: 2412 MHz, data rate : 11Mbps(IEEE 802.11b))
 Antenna Polarization : Horizontal



Note: The trace 1 is Peak detection. The trace 2 is RMS detection.

Mode of EUT : TX(1ch: 2412 MHz, data rate : 11Mbps(IEEE 802.11b))


Antenna Polarization : Vertical



Note: The trace 1 is Peak detection. The trace 2 is RMS detection.

Mode of EUT : TX(11ch: 2462 MHz, data rate : 11Mbps(IEEE 802.11b))


Antenna Polarization : Horizontal



Note: The trace 1 is Peak detection. The trace 2 is RMS detection.

Mode of EUT : TX(11ch: 2462 MHz, data rate : 11Mbps(IEEE 802.11b))


Antenna Polarization : Vertical



Note: The trace 1 is Peak detection. The trace 2 is RMS detection.

Mode of EUT : TX(1ch: 2412 MHz, data rate : 6Mbps(IEEE 802.11g))


Antenna Polarization : Horizontal



Note: The trace 1 is Peak detection. The trace 2 is RMS detection.

Mode of EUT : TX(1ch: 2412 MHz, data rate : 6Mbps(IEEE 802.11g))


Antenna Polarization : Vertical



Note: The trace 1 is Peak detection. The trace 2 is RMS detection.

Mode of EUT : TX(11ch: 2462 MHz, data rate : 6Mbps(IEEE 802.11g))


Antenna Polarization : Horizontal



Note: The trace 1 is Peak detection. The trace 2 is RMS detection.


Mode of EUT : TX(11ch: 2462 MHz, data rate : 6Mbps(IEEE 802.11g))

Antenna Polarization : Vertical




Note: The trace 1 is Peak detection. The trace 2 is RMS detection.

Mode of EUT : TX(1ch: 2412 MHz, data rate : 54Mbps(IEEE 802.11g))
 Antenna Polarization : Horizontal



Note: The trace 1 is Peak detection. The trace 2 is RMS detection.


Mode of EUT : TX(1ch: 2412 MHz, data rate : 54Mbps(IEEE 802.11g))
 Antenna Polarization : Vertical



Note: The trace 1 is Peak detection. The trace 2 is RMS detection.

Mode of EUT : TX(11ch: 2462 MHz, data rate : 54Mbps(IEEE 802.11g))


Antenna Polarization : Horizontal



Note: The trace 1 is Peak detection. The trace 2 is RMS detection.

Mode of EUT : TX(11ch: 2462 MHz, data rate : 54Mbps(IEEE 802.11g))


Antenna Polarization : Vertical



Note: The trace 1 is Peak detection. The trace 2 is RMS detection.

Mode of EUT : TX(1ch: 2412 MHz, data rate : 6.5Mbps(IEEE 802.11n))


Antenna Polarization : Horizontal



Note: The trace 1 is Peak detection. The trace 2 is RMS detection.

Mode of EUT : TX(1ch: 2412 MHz, data rate : 6.5Mbps(IEEE 802.11n))


Antenna Polarization : Vertical



Note: The trace 1 is Peak detection. The trace 2 is RMS detection.

Mode of EUT : TX(11ch: 2462 MHz, data rate : 6.5Mbps(IEEE 802.11n))


Antenna Polarization : Horizontal



Note: The trace 1 is Peak detection. The trace 2 is RMS detection.


Mode of EUT : TX(11ch: 2462 MHz, data rate : 6.5Mbps(IEEE 802.11n))

Antenna Polarization : Vertical




Note: The trace 1 is Peak detection. The trace 2 is RMS detection.

Mode of EUT : TX(1ch: 2412 MHz, data rate : 65Mbps(IEEE 802.11n))
 Antenna Polarization : Horizontal



Note: The trace 1 is Peak detection. The trace 2 is RMS detection.


Mode of EUT : TX(1ch: 2412 MHz, data rate : 65Mbps(IEEE 802.11n))
 Antenna Polarization : Vertical



Note: The trace 1 is Peak detection. The trace 2 is RMS detection.


Mode of EUT : TX(11ch: 2462 MHz, data rate : 65Mbps(IEEE 802.11n))

Antenna Polarization : Horizontal



Note: The trace 1 is Peak detection. The trace 2 is RMS detection.

Mode of EUT : TX(11ch: 2462 MHz, data rate : 65Mbps(IEEE 802.11n))
 Antenna Polarization : Vertical



Note: The trace 1 is Peak detection. The trace 2 is RMS detection.

7.9.5.2 Other Spurious Emission (9kHz – 30MHz)

Test Date : November 29, 2012

Temp.:20°C, Humi:51%

Mode of EUT : All modes have been investigated and the worst case mode for channel (06ch: 2437MHz / IEEE802.11b, IEEE802.11g and IEEE802.11n) has been listed.

Results : No spurious emissions in the range 20dB below the limit.


7.9.5.3 Other Spurious Emission (30MHz – 1000MHz)

Mode of EUT : All modes have been investigated and the worst case mode for channel (06ch: 2437MHz / IEEE802.11b, IEEE802.11g and IEEE802.11n) has been listed.

Test Date: November 29, 2012

Temp.: 20 °C, Humi: 51 %

Frequency [MHz]	Antenna Factor [dB(1/m)]	Cable Loss [dB]	Meter Readings [dB(μV)]		Limits [dB(μV/m)]	Results [dB(μV/m)]		Margin [dB]	Remarks
			Hori.	Vert.		Hori.	Vert.		
216.2	16.8	2.4	3.4	< 0.0	46.0	22.6	< 19.2	+23.4	-
345.9	14.5	3.1	14.6	10.2	46.0	32.2	27.8	+13.8	-
691.8	20.1	4.4	2.8	3.2	46.0	27.3	27.7	+18.3	-



NOTES

1. Test Distance : 3 m
2. The spectrum was checked from 30 MHz to 1000 MHz.
3. The cable factor is consist of several combination conductor cables.
4. The symbol of "<" means "or less".
5. The symbol of ">" means "more than".
6. Calculated result at 345.9 MHz, as the worst point shown on underline:
 Antenna Factor + Cable Loss + Meter Reading = 14.5 + 3.1 + 14.6 = 32.2 dB(μV/m)
7. Test receiver setting(s) : CISPR QP 120 kHz (QP : Quasi-Peak)

7.9.5.4 Other Spurious Emission (Above 1000MHz)

7.9.5.4.1 Mode of TX

7.9.5.4.1.1 IEEE802.11b

Test Date: December 1, 2012

Temp.: 22 °C, Humi: 38 %

Frequency [MHz]	Antenna Factor [dB(1/m)]	Corr. Factor [dB]	Meter Readings [dB(μV)]				Limits [dB(μV/m)]		Results [dB(μV/m)]		Margin [dB]	Remarks
			Horizontal		Vertical		PK	AVE	PK	AVE		
			PK	AVE	PK	AVE	PK	AVE	PK	AVE		
Test condition : Tx Low Ch												
4824.0	27.3	-21.2	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 46.1	< 36.1	> +17.9	A/B
12060.0	33.6	-27.2	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 46.4	< 36.4	> +17.6	A/B
19296.0	40.3	-22.7	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 57.6	< 47.6	> + 6.4	A/B
Test condition : TX Middle Ch												
4874.0	27.3	-21.2	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 46.1	< 36.1	> +17.9	A/B
7311.0	29.9	-19.6	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 50.3	< 40.3	> +13.7	A/B
12185.0	33.5	-26.9	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 46.6	< 36.6	> +17.4	A/B
19496.0	40.2	-22.7	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 57.5	< 47.5	> + 6.5	A/B
Test condition : TX High Ch												
4924.0	27.3	-21.3	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 46.0	< 36.0	> +18.0	A/B
7386.0	29.9	-19.5	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 50.4	< 40.4	> +13.6	A/B
12310.0	33.5	-26.8	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 46.7	< 36.7	> +17.3	A/B
19696.0	40.3	-22.7	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 57.6	< 47.6	> + 6.4	A/B
22158.0	40.3	-21.7	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 58.6	< 48.6	> + 5.4	A/B

Calculated result at 22158.0 MHz, as the worst point shown on underline:

Antenna Factor = 40.3 dB(1/m)

Corr. Factor = -21.7 dB

+) Meter Reading = <30.0 dB(μV)

Result = <48.6 dB(μV/m)

Minimum Margin: 54.0 - <48.6 = >5.4 (dB)

NOTES

1. Test Distance : 3 m
2. The spectrum was checked from 1 GHz to 25 GHz (10th harmonic of the highest fundamental frequency).
3. The correction factor is shown as follows:
 - Corr. Factor [dB] = Cable Loss + 20dB Pad Att. - Pre-Amp. Gain [dB] (1.0 - 7.6GHz)
 - Corr. Factor [dB] = Cable Loss + 10dB Pad Att. - Pre-Amp. Gain [dB] (7.6 - 18.0GHz)
 - Corr. Factor [dB] = Cable Loss - Pre-Amp. Gain [dB] (over 18 GHz)
4. The symbol of "<" means "or less".
5. The symbol of ">" means "more than".
6. PK : Peak Detector / AVE : Average Detector
7. Setting of measuring instrument(s) :

	Detector Function	Resolution B.W.	Video B.W.	Sweep Time
A	Peak	1 MHz	3 MHz	AUTO
B	RMS	1 MHz	3 MHz	AUTO

7.9.5.4.1.2 IEEE802.11g

Test Date: December 1, 2012

Temp.: 22 °C, Humi: 38 %

Frequency [MHz]	Antenna Factor [dB(1/m)]	Corr. Factor [dB]	Meter Readings [dB(μV)]				Limits [dB(μV/m)]		Results [dB(μV/m)]		Margin [dB]	Remarks
			Horizontal		Vertical		PK	AVE	PK	AVE		
			PK	AVE	PK	AVE						
Test condition : Tx Low Ch												
4824.0	27.3	-21.2	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 46.1	< 36.1	> +17.9	A/B
12060.0	33.6	-27.2	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 46.4	< 36.4	> +17.6	A/B
19296.0	40.3	-22.7	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 57.6	< 47.6	> + 6.4	A/B
Test condition : TX Middle Ch												
4874.0	27.3	-21.2	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 46.1	< 36.1	> +17.9	A/B
7311.0	29.9	-19.6	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 50.3	< 40.3	> +13.7	A/B
12185.0	33.5	-26.9	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 46.6	< 36.6	> +17.4	A/B
19496.0	40.2	-22.7	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 57.5	< 47.5	> + 6.5	A/B
Test condition : TX High Ch												
4924.0	27.3	-21.3	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 46.0	< 36.0	> +18.0	A/B
7386.0	29.9	-19.5	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 50.4	< 40.4	> +13.6	A/B
12310.0	33.5	-26.8	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 46.7	< 36.7	> +17.3	A/B
19696.0	40.3	-22.7	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 57.6	< 47.6	> + 6.4	A/B
22158.0	40.3	-21.7	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 58.6	< 48.6	> + 5.4	A/B

Calculated result at 22158.0 MHz, as the worst point shown on underline:

Antenna Factor	=	40.3 dB(1/m)
Corr. Factor	=	-21.7 dB
+) Meter Reading	=	<30.0 dB(μV)
Result	=	<48.6 dB(μV/m)

Minimum Margin: 54.0 - <48.6 = >5.4 (dB)

NOTES

- Test Distance : 3 m
- The spectrum was checked from 1 GHz to 25 GHz (10th harmonic of the highest fundamental frequency).
- The correction factor is shown as follows:
 - Corr. Factor [dB] = Cable Loss + 20dB Pad Att. - Pre-Amp. Gain [dB] (1.0 - 7.6GHz)
 - Corr. Factor [dB] = Cable Loss + 10dB Pad Att. - Pre-Amp. Gain [dB] (7.6 - 18.0GHz)
 - Corr. Factor [dB] = Cable Loss - Pre-Amp. Gain [dB] (over 18 GHz)
- The symbol of "<" means "or less".
- The symbol of ">" means "more than".
- PK : Peak Detector / AVE : Average Detector
- Setting of measuring instrument(s) :

	Detector Function	Resolution B.W.	Video B.W.	Sweep Time
A	Peak	1 MHz	3 MHz	AUTO
B	RMS	1 MHz	3 MHz	AUTO

7.9.5.4.1.3 IEEE802.11n

Test Date: December 1, 2012

Temp.: 22 °C, Humi: 38 %

Frequency [MHz]	Antenna Factor [dB(1/m)]	Corr. Factor [dB]	Meter Readings [dB(μV)]				Limits [dB(μV/m)]		Results [dB(μV/m)]		Margin [dB]	Remarks
			Horizontal		Vertical		PK	AVE	PK	AVE		
			PK	AVE	PK	AVE						
Test condition : Tx Low Ch												
4824.0	27.3	-21.2	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 46.1	< 36.1	> +17.9	A/B
12060.0	33.6	-27.2	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 46.4	< 36.4	> +17.6	A/B
19296.0	40.3	-22.7	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 57.6	< 47.6	> + 6.4	A/B
Test condition : TX Middle Ch												
4874.0	27.3	-21.2	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 46.1	< 36.1	> +17.9	A/B
7311.0	29.9	-19.6	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 50.3	< 40.3	> +13.7	A/B
12185.0	33.5	-26.9	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 46.6	< 36.6	> +17.4	A/B
19496.0	40.2	-22.7	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 57.5	< 47.5	> + 6.5	A/B
Test condition : TX High Ch												
4924.0	27.3	-21.3	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 46.0	< 36.0	> +18.0	A/B
7386.0	29.9	-19.5	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 50.4	< 40.4	> +13.6	A/B
12310.0	33.5	-26.8	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 46.7	< 36.7	> +17.3	A/B
19696.0	40.3	-22.7	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 57.6	< 47.6	> + 6.4	A/B
22158.0	40.3	-21.7	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 58.6	< 48.6	> + 5.4	A/B

Calculated result at 22158.0 MHz, as the worst point shown on underline:

Antenna Factor	=	40.3 dB(1/m)
Corr. Factor	=	-21.7 dB
+) Meter Reading	=	<30.0 dB(μV)
Result	=	<48.6 dB(μV/m)

Minimum Margin: 54.0 - <48.6 = >5.4 (dB)

NOTES

- Test Distance : 3 m
- The spectrum was checked from 1 GHz to 25 GHz (10th harmonic of the highest fundamental frequency).
- The correction factor is shown as follows:
 - Corr. Factor [dB] = Cable Loss + 20dB Pad Att. - Pre-Amp. Gain [dB] (1.0 - 7.6GHz)
 - Corr. Factor [dB] = Cable Loss + 10dB Pad Att. - Pre-Amp. Gain [dB] (7.6 - 18.0GHz)
 - Corr. Factor [dB] = Cable Loss - Pre-Amp. Gain [dB] (over 18 GHz)
- The symbol of "<" means "or less".
- The symbol of ">" means "more than".
- PK : Peak Detector / AVE : Average Detector
- Setting of measuring instrument(s) :

	Detector Function	Resolution B.W.	Video B.W.	Sweep Time
A	Peak	1 MHz	3 MHz	AUTO
B	RMS	1 MHz	3 MHz	AUTO

7.9.5.4.2 Mode of RX

Test Date: December 1, 2012

Temp.: 22 °C, Humi: 38 %

Frequency [MHz]	Antenna Factor [dB(1/m)]	Corr. Factor [dB]	Meter Readings [dB(μV)]				Limits [dB(μV/m)]		Results [dB(μV/m)]		Margin [dB]	Remarks
			Horizontal		Vertical		PK	AVE	PK	AVE		
			PK	AVE	PK	AVE	PK	AVE	PK	AVE		
Test condition : RX Middle Ch												
2437.0	21.3	-21.9	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 39.4	< 29.4	> +24.6	A/B
4874.0	27.3	-21.5	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 45.8	< 35.8	> +18.2	A/B
7311.0	29.9	-19.9	< 40.0	< 30.0	< 40.0	< 30.0	74.0	54.0	< 50.0	< 40.0	> +14.0	A/B

Calculated result at 4874.0 MHz, as the worst point shown on underline:

Antenna Factor = 27.3 dB(1/m)

Corr. Factor = -21.5 dB

+) Meter Reading = <30.0 dB(μV)

Result = <35.8 dB(μV/m)

Minimum Margin: 54.0 - <35.8 = >14.0 (dB)

NOTES

1. Test Distance : 3 m
2. The spectrum was checked from 1 GHz to 25 GHz (10th harmonic of the highest fundamental frequency).
3. The correction factor is shown as follows:
Corr. Factor [dB] = Cable Loss + 20dB Pad Att. - Pre-Amp. Gain [dB] (1.0 - 7.6GHz)
4. The symbol of "<" means "or less".
5. The symbol of ">" means "more than".
6. PK : Peak Detector / AVE : Average Detector
7. Setting of measuring instrument(s) :

	Detector Function	Resolution B.W.	Video B.W.	Sweep Time
A	Peak	1 MHz	3 MHz	AUTO
B	RMS	1 MHz	3 MHz	AUTO