

## TEST REPORT

**Applicant** : Sharp Corporation, Communication Systems Division  
**Address** : 2-13-1, Iida Hachihonmatsu, Higashi-Hiroshima City, Hiroshima,  
739-0192, JAPAN

**Products** : Cellular Phone  
**Model No.** : 304SH  
**SERIAL NO.** : 004401/11/507683/4  
004401/11/507702/2

**FCC ID** : APYHRO00205

**Test Standard** : CFR 47 FCC Rules and Regulations Part 15

**Test Results** : **Passed**

**Date of Test** : March 4 ~ April 9, 2014



A handwritten signature in black ink, appearing to read 'K. Shibata'.

Kousei Shibata  
Manager  
Japan Quality Assurance Organization  
KITA-KANSAI Testing Center  
SAITO EMC Branch  
7-3-10, Saito-asagi, Ibaraki-shi, Osaka 567-0085, Japan

- The measurement values stated in Test Report was made with traceable to National Institute of Advanced Industrial Science and Technology (AIST) of Japan and National Institute of Information and Communications Technology (NICT) of Japan.
- The applicable standard, testing condition and testing method which were used for the tests are based on the request of the applicant.
- The test results presented in this report relate only to the offered test sample.
- The contents of this test report cannot be used for the purposes, such as advertisement for consumers.
- This test report shall not be reproduced except in full without the written approval of JQA.
- VLAC does not approve, certify or warrant the product by this test report.

**TABLE OF CONTENTS**

|                                                 | <b>Page</b> |
|-------------------------------------------------|-------------|
| 1 Description of the Equipment Under Test ..... | 3           |
| 2 Summary of Test Results .....                 | 4           |
| 3 Test Procedure.....                           | 5           |
| 4 Test Location .....                           | 5           |
| 5 Recognition of Test Laboratory .....          | 5           |
| 6 Details of the Equipment Under Test .....     | 6           |
| 7 Details of the Test Item .....                | 9           |

**DEFINITIONS FOR ABBREVIATION AND SYMBOLS USED IN THIS TEST REPORT****EUT** : Equipment Under Test**AE** : Associated Equipment**N/A** : Not Applicable**N/T** : Not Tested**EMC** : Electromagnetic Compatibility**EMI** : Electromagnetic Interference**EMS** : Electromagnetic Susceptibility☒ - indicates that the listed condition, standard or equipment is applicable for this report.☐ - indicates that the listed condition, standard or equipment is not applicable for this report.

**1 Description of the Equipment Under Test**

1. Manufacturer : Sharp Corporation, Communication Systems Division  
2-13-1, Iida Hachihonmatsu, Higashi-Hiroshima City, Hiroshima,  
739-0192, JAPAN
2. Products : Cellular Phone
3. Model No. : 304SH
4. Serial No. : 004401/11/507683/4  
: 004401/11/507702/2
5. Product Type : Pre-production
6. Date of Manufacture : January, 2014
7. Power Rating : 4.0VDC (Lithium-ion Battery UBATIA243AFN1 2600mAh)
8. EUT Grounding : None
9. Transmitting Frequency : WLAN: 2412.0 MHz(01CH) –2462.0MHz(11CH)  
: Bluetooth LE: 2402.0 MHz(00CH) – 2480.0MHz(39CH)
10. Receiving Frequency : WLAN: 2412.0 MHz(01CH) –2462.0MHz(11CH)  
: Bluetooth LE: 2402.0 MHz(00CH) – 2480.0MHz(39CH)
11. Max. RF Output Power : 16.98dBm(Measure Value of IEEE802.11b)  
: 22.60dBm(Measure Value of IEEE802.11g)  
: 22.41dBm(Measure Value of IEEE802.11n)  
: 4.77dBm(Measure Value of Bluetooth LE)
12. Category : DTS
13. EUT Authorization : Certification
14. Received Date of EUT : March 4, 2014

**15. Channel Plan****WLAN:**

The carrier spacing is 5 MHz.

The carrier frequency is designated by the absolute frequency channel number (ARFCN).

The carrier frequency is expressed in the equation shown as follows:

Transmitting Frequency (in MHz) =  $2407.0 + 5 \cdot n$

Receiving Frequency (in MHz) =  $2407.0 + 5 \cdot n$

where, n : channel number ( $1 \leq n \leq 11$ )

**Bluetooth Low Energy Mode:**

The carrier spacing is 2 MHz.

The carrier frequency is designated by the absolute frequency channel number (ARFCN).

The carrier frequency is expressed in the equation shown as follows:

Transmitting Frequency (in MHz) =  $2402.0 + 2 \cdot n$

Receiving Frequency (in MHz) =  $2402.0 + 2 \cdot n$

where, n : channel number ( $0 \leq n \leq 39$ )

## 2 Summary of Test Results

Applied Standard : CFR 47 FCC Rules and Regulations Part 15  
Subpart C – Intentional Radiators

The EUT described in clause 1 was tested according to the applied standard shown above.  
Details of the test configuration is shown in clause 6.

The conclusion for the test items of which are required by the applied standard is indicated under the test result.

- ☒ - The test result was **passed** for the test requirements of the applied standard.
- ☐ - The test result was **failed** for the test requirements of the applied standard.
- ☐ - The test result was **not judged** the test requirements of the applied standard.

In the approval of test results,

- Determining compliance with the limits in this report was based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
- No deviations were employed from the applied standard.
- No modifications were conducted by JQA to achieve compliance to the limitations.

Reviewed by:

Tested by:



Shigeru Kinoshita  
Deputy Manager  
JQA KITA-KANSAI Testing Center  
SAITO EMC Branch



Shigeru Osawa  
Deputy Manager  
JQA KITA-KANSAI Testing Center  
SAITO EMC Branch

### 3 Test Procedure

Test Requirements : §15.247, §15.207 and §15.209

Test Procedure : ANSI C63.10–2009

The tests were performed with reference to FCC KDB 558074 D01 DTS Meas Guidance v03r01, released April 9, 2013.

### 4 Test Location

Japan Quality Assurance Organization (JQA)

KITA-KANSAI Testing Center

7-7, Ishimaru, 1-chome, Minoh-shi, Osaka, 562-0027, Japan

SAITO EMC Branch

7-3-10, Saito-asagi, Ibaraki-shi, Osaka 567-0085, Japan

### 5 Recognition of Test Laboratory

JQA KITA-KANSAI Testing Center SAITO EMC Branch is accredited under ISO/IEC 17025 by following accreditation bodies and the test facility is registered by the following bodies.

VLAC Accreditation No. : VLAC-001-2 (Expiry date : March 30, 2014)

VCCI Registration No. : A-0002 (Expiry date : March 30, 2014)

BSMI Registration No. : SL2-IS-E-6006, SL2-IN-E-6006, SL2-R1/R2-E-6006, SL2-A1-E-6006  
(Expiry date : September 14, 2016)

IC Registration No. : 2079E-3, 2079E-4 (Expiry date : July 20, 2014)

Accredited as conformity assessment body for Japan electrical appliances and material law by METI.  
(Expiry date : February 22, 2016)

## 6 Details of the Equipment Under Test

### 6.1 Operating Condition

Transmitting/Receiving

WLAN:

Transmitting frequency : 2412.0 MHz(1CH) – 2462.0 MHz(11CH)

Receiver frequency : 2412.0 MHz(1CH) – 2462.0 MHz(11CH)

Bluetooth Low Energy Mode(Bluetooth 4.0 + EDR + LE):

Transmitting frequency : 2402.0 MHz(0CH) – 2480.0 MHz(39CH)

Receiver frequency : 2402.0 MHz(0CH) – 2480.0 MHz(39CH)

Modulation Type

1. 802.11b : DSSS

2. 802.11g : OFDM

3. 802.11n : OFDM

4. LE Packet (Modulation Type : GFSK)

Other Clock Frequency

32.768 kHz, 19.2 MHz, 24 MHz, 27 MHz, 27.12 MHz, 48 MHz

The tests were performed in the following worst condition.

| Mode        | Condition      |
|-------------|----------------|
| IEEE802.11b | 11 Mbps        |
| IEEE802.11g | 6 Mbps         |
| IEEE802.11n | MCS3 (26 Mbps) |

Note: The worst condition was determined based on the test result of Maximum Peak Output Power(Mid channel).

The EUT was rotated through three orthogonal axis (X, Y and Z axis) in radiated measurement.

The EUT with temporary antenna port was used in conducted measurement.

## 6.2 Test Configuration

The equipment under test (EUT) consists of :

|   | Item           | Manufacturer       | Model No. | Serial No.                                             | FCC ID      |
|---|----------------|--------------------|-----------|--------------------------------------------------------|-------------|
| A | Cellular Phone | Sharp              | 304SH     | 004401/11/5<br>07683/4*1)<br>004401/11/5<br>07702/2*2) | APYHRO00205 |
| B | AC Adapter     | Sharp              | SHCEJ1    | --                                                     | N/A         |
| C | Earphone       | Softbank<br>Mobile | ZTCAA1    | --                                                     | N/A         |

\*1) Used for AC Powerline Conducted Emission and Field Strength of Spurious Emission

\*2) Used for Antenna Conducted Emission

The auxiliary equipment used for testing :


None

Type of Cable:


| No. | Description    | Identification<br>(Manu. etc.) | Connector<br>Shielded | Cable<br>Shielded | Ferrite<br>Core | Length<br>(m) |
|-----|----------------|--------------------------------|-----------------------|-------------------|-----------------|---------------|
| 1   | DC Power Cord  | --                             | --                    | NO                | NO              | 1.5           |
| 2   | Earphone Cable | --                             | --                    | NO                | NO              | 0.5           |

**6.3 Test Arrangement (Drawings)**


a) Single Unit



b) AC Adapter used



c) Earphone used



**7 Details of the Test Item****7.0 Summary of the Test Results**

| Test Item                       | FCC Specification         | Reference of the Test Report | Results | Remarks |
|---------------------------------|---------------------------|------------------------------|---------|---------|
| Channel Separation              | Section 15.247(a)(1)      | -                            | -       | -       |
| Minimum Hopping Channel         | Section 15.247(a)(1)(iii) | -                            | -       | -       |
| Occupied Bandwidth              | Section 15.247(a)(2)      | Section 7.3                  | Passed  | -       |
| Dwell Time                      | Section 15.247(a)(1)(iii) | -                            | -       | -       |
| Peak Output Power (Conduction)  | Section 15.247(b)(3)      | Section 7.5                  | Passed  | -       |
| Peak Power Density (Conduction) | Section 15.247(e)         | Section 7.6                  | Passed  | -       |
| Spurious Emissions (Conduction) | Section 15.247(d)         | Section 7.7                  | Passed  | -       |
| AC Powerline Conducted Emission | Section 15.207            | Section 7.8                  | Passed  | -       |
| Radiated Emission               | Section 15.247(d)         | Section 7.9                  | Passed  | -       |

### 7.1 Channel Separation

For the requirements, ☐ - Applicable ☐ - Tested. ☐ - Not tested by applicant request.]  
☒ - Not Applicable

For the limits, ☐ - Passed ☐ - Failed ☐ - Not judged

### 7.2 Minimum Hopping Channel

For the requirements, ☐ - Applicable ☐ - Tested. ☐ - Not tested by applicant request.]  
☒ - Not Applicable

For the limits, ☐ - Passed ☐ - Failed ☐ - Not judged

### 7.3 Occupied Bandwidth

For the requirements, ☒ - Applicable ☒ - Tested. ☐ - Not tested by applicant request.]  
☐ - Not Applicable

For the limits, ☒ - Passed ☐ - Failed ☐ - Not judged

#### 7.3.1 Worst Point and Measurement Uncertainty

|                                      |               |     |    |               |     |
|--------------------------------------|---------------|-----|----|---------------|-----|
| The 99% Bandwidth of IEEE802.11b is  | <u>12.938</u> | MHz | at | <u>2462.0</u> | MHz |
| The 99% Bandwidth of IEEE802.11g is  | <u>16.528</u> | MHz | at | <u>2437.0</u> | MHz |
| The 99% Bandwidth of IEEE802.11n is  | <u>17.660</u> | MHz | at | <u>2462.0</u> | MHz |
| The 99% Bandwidth of Bluetooth LE is | <u>1089.3</u> | kHz | at | <u>2402.0</u> | MHz |

|                                      |               |     |    |               |     |
|--------------------------------------|---------------|-----|----|---------------|-----|
| The 6dB Bandwidth of IEEE802.11b is  | <u>8.434</u>  | MHz | at | <u>2412.0</u> | MHz |
| The 6dB Bandwidth of IEEE802.11g is  | <u>16.420</u> | MHz | at | <u>2437.0</u> | MHz |
| The 6dB Bandwidth of IEEE802.11n is  | <u>17.730</u> | MHz | at | <u>2462.0</u> | MHz |
| The 6dB Bandwidth of Bluetooth LE is | <u>678.9</u>  | kHz | at | <u>2440.0</u> | MHz |

Uncertainty of Measurement Results +/-0.9 %(2σ)

Remarks : \_\_\_\_\_

## 7.3.2 Test Site and Instruments

### 7.3.2.1 Test Site

KITA-KANSAI Testing Center

Test site : SAITO


|                                                  |                                                          |
|--------------------------------------------------|----------------------------------------------------------|
| <input type="checkbox"/> - Anechoic chamber (A1) | <input type="checkbox"/> - Measurement room (M1)         |
| <input type="checkbox"/> - Measurement room (M2) | <input type="checkbox"/> - Measurement room (M3)         |
| <input type="checkbox"/> - Shielded room (S1)    | <input type="checkbox"/> - Shielded room (S2)            |
| <input type="checkbox"/> - Shielded room (S3)    | <input checked="" type="checkbox"/> - Shielded room (S4) |

### 7.3.2.2 Test Instruments

| Type              | Model       | Manufacturer | ID No. | Last Cal. | Interval |
|-------------------|-------------|--------------|--------|-----------|----------|
| Spectrum Analyzer | E4446A      | Agilent      | A-39   | 2013/9    | 1 Year   |
| Attenuator        | 54A-10      | Weinschel    | D-28   | 2013/9    | 1 Year   |
| RF Cable          | SUCOFLEX102 | SUHNER       | C-52   | 2013/7    | 1 Year   |

## 7.3.3 Test Method and Test Setup (Diagrammatic illustration)

The test system is shown as follows:



The setting of the spectrum analyzer are shown as follows:

|                 | WLAN    | Bluetooth |
|-----------------|---------|-----------|
| Res. Bandwidth  | 100 kHz | 100 kHz   |
| Video Bandwidth | 300 kHz | 300 kHz   |
| Span            | 30 MHz  | 3 MHz     |
| Sweep Time      | AUTO    | AUTO      |
| Trace           | Maxhold | Maxhold   |

### 7.3.4 Test Data

Mode of EUT : WLAN

Test Date : March 11, 2014

Temp.:22°C, Humi:23%

The resolution bandwidth was set to 100 kHz, -6dBc display line was placed on the screen (or 99% bandwidth), the occupied bandwidth is the delta frequency between the two points where the display line intersects the signal trace.

#### A) IEEE 802.11b

| Channel | Frequency (MHz) | 99% Bandwidth (MHz) | -6dBc Bandwidth (MHz) | Minimum -6dBc Bandwidth Limit (kHz) |
|---------|-----------------|---------------------|-----------------------|-------------------------------------|
| 01      | 2412.0          | 12.829              | 8.434                 | 500                                 |
| 06      | 2437.0          | 12.844              | 8.179                 | 500                                 |
| 11      | 2462.0          | 12.938              | 8.296                 | 500                                 |

#### B) IEEE 802.11g

| Channel | Frequency (MHz) | 99% Bandwidth (MHz) | -6dBc Bandwidth (MHz) | Minimum -6dBc Bandwidth Limit (kHz) |
|---------|-----------------|---------------------|-----------------------|-------------------------------------|
| 01      | 2412.0          | 16.527              | 16.402                | 500                                 |
| 06      | 2437.0          | 16.528              | 16.420                | 500                                 |
| 11      | 2462.0          | 16.526              | 16.399                | 500                                 |

#### C) IEEE 802.11n


| Channel | Frequency (MHz) | 99% Bandwidth (MHz) | -6dBc Bandwidth (MHz) | Minimum -6dBc Bandwidth Limit (kHz) |
|---------|-----------------|---------------------|-----------------------|-------------------------------------|
| 01      | 2412.0          | 17.654              | 17.729                | 500                                 |
| 06      | 2437.0          | 17.660              | 17.728                | 500                                 |
| 11      | 2462.0          | 17.660              | 17.730                | 500                                 |

## A) IEEE 802.11b

### Low Channel

Agilent

R L



Occupied Bandwidth  
12.8286 MHz


Occ BW % Pwr 99.00 %  
x dB -6.00 dB

Transmit Freq Error 17.523 kHz  
Occupied Bandwidth 8.434 MHz

### Middle Channel

Agilent



R L



Occupied Bandwidth  
12.8439 MHz

Occ BW % Pwr 99.00 %  
x dB -6.00 dB


Transmit Freq Error 3.539 kHz  
Occupied Bandwidth 8.179 MHz



## Middle Channel

Agilent

R T



Occupied Bandwidth  
16.5278 MHz


Occ BW % Pwr 99.00 %  
x dB -6.00 dB

Transmit Freq Error -114.934 Hz  
Occupied Bandwidth 16.420 MHz

## High Channel

Agilent

R L



Occupied Bandwidth  
16.5260 MHz

Occ BW % Pwr 99.00 %  
x dB -6.00 dB


Transmit Freq Error 12.131 kHz  
Occupied Bandwidth 16.399 MHz

## C) IEEE 802.11n

### Low Channel

Agilent

R T



Occupied Bandwidth  
17.6542 MHz


Occ BW % Pwr 99.00 %  
x dB -6.00 dB

Transmit Freq Error 16.734 kHz  
Occupied Bandwidth 17.729 MHz

### Middle Channel

Agilent


R L



Occupied Bandwidth  
17.6598 MHz

Occ BW % Pwr 99.00 %  
x dB -6.00 dB

Transmit Freq Error 7.377 kHz  
Occupied Bandwidth 17.728 MHz



Mode of EUT : Bluetooth Low Energy

Test Date : April 9, 2014

Temp.:24°C, Humi:33%

The resolution bandwidth was set to 100 kHz, -6dBc display line was placed on the screen (or 99% bandwidth), the occupied bandwidth is the delta frequency between the two points where the display line intersects the signal trace.

1)Packet Setting : LE (Modulation type : GFSK)


| Channel | Frequency (MHz) | 99% Bandwidth (kHz) | -6dBc Bandwidth (kHz) | Minimum -6dBc Bandwidth Limit (kHz) |
|---------|-----------------|---------------------|-----------------------|-------------------------------------|
| 00      | 2402.0          | 1089.3              | 676.4                 | 500                                 |
| 19      | 2440.0          | 1087.9              | 678.9                 | 500                                 |
| 39      | 2480.0          | 1087.7              | 676.2                 | 500                                 |

1)Packet Setting : LE (Modulation type : GFSK)

Low Channel

Agilent

L



Occupied Bandwidth

1.0893 MHz


Occ BW % Pwr 99.00 %  
x dB -6.00 dB

Transmit Freq Error 23.634 kHz  
Occupied Bandwidth 676.424 kHz

## Middle Channel

Agilent

L




Transmit Freq Error 23.836 kHz  
Occupied Bandwidth 678.902 kHz

## High Channel

Agilent

L



Transmit Freq Error 23.048 kHz  
Occupied Bandwidth 676.167 kHz

#### 7.4 Dwell Time

For the requirements, ☐ - Applicable ☐ - Tested. ☐ - Not tested by applicant request.]  
☒ - Not Applicable

For the limits, ☐ - Passed ☐ - Failed ☐ - Not judged

#### 7.5 Peak Output Power(Conduction)

For the requirements, ☒ - Applicable ☒ - Tested. ☐ - Not tested by applicant request.]  
☐ - Not Applicable

For the limits, ☒ - Passed ☐ - Failed ☐ - Not judged

##### 7.5.1 Worst Point and Measurement Uncertainty

|                                      |              |     |    |               |     |
|--------------------------------------|--------------|-----|----|---------------|-----|
| Peak Output Power of IEEE802.11b is  | <u>16.98</u> | dBm | at | <u>2412.0</u> | MHz |
| Peak Output Power of IEEE802.11g is  | <u>22.60</u> | dBm | at | <u>2437.0</u> | MHz |
| Peak Output Power of IEEE802.11n is  | <u>22.41</u> | dBm | at | <u>2462.0</u> | MHz |
| Peak Output Power of Bluetooth LE is | <u>4.77</u>  | dBm | at | <u>2440.0</u> | MHz |

Uncertainty of Measurement Results at Amplitude +/-1.2 dB(2 $\sigma$ )

Remarks : \_\_\_\_\_

##### 7.5.2 Test Site and Instruments

###### 7.5.2.1 Test Site

KITA-KANSAI Testing Center

Test site : SAITO


|                                                  |                                                          |
|--------------------------------------------------|----------------------------------------------------------|
| <input type="checkbox"/> - Anechoic chamber (A1) | <input type="checkbox"/> - Measurement room (M1)         |
| <input type="checkbox"/> - Measurement room (M2) | <input type="checkbox"/> - Measurement room (M3)         |
| <input type="checkbox"/> - Shielded room (S1)    | <input type="checkbox"/> - Shielded room (S2)            |
| <input type="checkbox"/> - Shielded room (S3)    | <input checked="" type="checkbox"/> - Shielded room (S4) |

### 7.5.2.2 Test Instruments

| Type         | Model       | Manufacturer | ID No. | Last Cal. | Interval |
|--------------|-------------|--------------|--------|-----------|----------|
| Power Meter  | N1911A      | Agilent      | B-63   | 2013/7    | 1 Year   |
| Power Sensor | N1921A      | Agilent      | B-64   | 2013/7    | 1 Year   |
| Attenuator   | 54A-10      | Weinschel    | D-28   | 2013/9    | 1 Year   |
| RF Cable     | SUCOFLEX102 | SUHNER       | C-52   | 2013/7    | 1 Year   |

### 7.5.3 Test Method and Test Setup (Diagrammatic illustration)

The Conducted RF Power Output was measured with a power meter, one 10dB attenuator and a short, low loss cable.



## 7.5.4 Test Data

### 1) IEEE 802.11b

Data Rate : 11Mbps

Test Date: March 4, 2014

Temp.: 22 °C, Humi: 26 %

| Transmitting Frequency |       | Correction Factor | Meter Reading | Conducted Peak Output Power |       | Limits | Margin |
|------------------------|-------|-------------------|---------------|-----------------------------|-------|--------|--------|
| CH                     | [MHz] | [dB]              | [dBm]         | [dBm]                       | [mW]  | [dBm]  | [dB]   |
| 01                     | 2412  | 10.10             | 6.88          | 16.98                       | 49.89 | 30.00  | +13.02 |
| 06                     | 2437  | 10.11             | 6.55          | 16.66                       | 46.34 | 30.00  | +13.34 |
| 11                     | 2462  | 10.11             | 6.55          | 16.66                       | 46.34 | 30.00  | +13.34 |

Calculated result at 2412.000 MHz, as the worst point shown on underline:

|                   |   |                      |
|-------------------|---|----------------------|
| Correction Factor | = | 10.10 dB             |
| + ) Meter Reading | = | 6.88 dBm             |
| Result            | = | 16.98 dBm = 49.89 mW |

Minimum Margin: 30.00 - 16.98 = 13.02 (dB)

#### NOTES

- The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.
- Setting of measuring instrument(s) :

|                   |            |
|-------------------|------------|
| Detector Function | Video B.W. |
| Peak              | OFF        |

CH [MHz]  
06 2437

| Rate    | Meter Reading [dBm] | Remark |
|---------|---------------------|--------|
| 1Mbps   | 6.17                |        |
| 2Mbps   | 6.28                |        |
| 5.5Mbps | 6.30                |        |
| 11Mbps  | 6.55                | *      |

\* : Worst Rate

All comparison were performed on the same measurement condition.

## 2) IEEE 802.11g

Data Rate : 6Mbps

Test Date: March 4, 2014

Temp.: 22 °C, Humi: 26 %

| Transmitting Frequency |       | Correction Factor | Meter Reading | Conducted Peak Output Power |        | Limits | Margin |
|------------------------|-------|-------------------|---------------|-----------------------------|--------|--------|--------|
| CH                     | [MHz] | [dB]              | [dBm]         | [dBm]                       | [mW]   | [dBm]  | [dB]   |
| 01                     | 2412  | 10.10             | 11.88         | 21.98                       | 157.76 | 30.00  | + 8.02 |
| 06                     | 2437  | 10.11             | 12.49         | 22.60                       | 181.97 | 30.00  | + 7.40 |
| 11                     | 2462  | 10.11             | 12.06         | 22.17                       | 164.82 | 30.00  | + 7.83 |

Calculated result at 2437.000 MHz, as the worst point shown on underline:

|                   |   |                       |
|-------------------|---|-----------------------|
| Correction Factor | = | 10.11 dB              |
| + ) Meter Reading | = | 12.49 dBm             |
| Result            | = | 22.60 dBm = 181.97 mW |

Minimum Margin: 30.00 - 22.60 = 7.40 (dB)

## NOTES

- The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.
- Setting of measuring instrument(s) :

|                   |            |
|-------------------|------------|
| Detector Function | Video B.W. |
| Peak              | OFF        |

CH  
06 [MHz]  
2437

| Rate   | Meter Reading<br>[dBm] | Remark |
|--------|------------------------|--------|
| 6Mbps  | 12.49                  | *      |
| 9Mbps  | 11.86                  |        |
| 12Mbps | 11.92                  |        |
| 18Mbps | 12.03                  |        |
| 24Mbps | 12.15                  |        |
| 36Mbps | 12.07                  |        |
| 48Mbps | 12.09                  |        |
| 54Mbps | 12.17                  |        |

\* : Worst Rate

All comparison were performed on the same measurement condition.

## 3) IEEE 802.11n

Data Rate : MCS3(26Mbps)

Test Date: March 4, 2014

Temp.: 22 °C, Humi: 26 %

| Transmitting Frequency |       | Correction Factor | Meter Reading | Conducted Peak Output Power |        | Limits | Margin |
|------------------------|-------|-------------------|---------------|-----------------------------|--------|--------|--------|
| CH                     | [MHz] | [dB]              | [dBm]         | [dBm]                       | [mW]   | [dBm]  | [dB]   |
| 01                     | 2412  | 10.10             | 11.93         | 22.03                       | 159.59 | 30.00  | + 7.97 |
| 06                     | 2437  | 10.11             | 12.27         | 22.38                       | 172.98 | 30.00  | + 7.62 |
| 11                     | 2462  | 10.11             | 12.30         | 22.41                       | 174.18 | 30.00  | + 7.59 |

Calculated result at 2462.000 MHz, as the worst point shown on underline:

|                   |   |                       |
|-------------------|---|-----------------------|
| Correction Factor | = | 10.11 dB              |
| + ) Meter Reading | = | 12.30 dBm             |
| Result            | = | 22.41 dBm = 174.18 mW |

Minimum Margin: 30.00 - 22.41 = 7.59 (dB)

## NOTES

- The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.
- Setting of measuring instrument(s) :

|                   |            |
|-------------------|------------|
| Detector Function | Video B.W. |
| Peak              | OFF        |

| CH              | [MHz]         |        |
|-----------------|---------------|--------|
| 06              | 2437          |        |
| Rate            | Meter Reading | Remark |
|                 | [dBm]         |        |
| MCS0 (6.5Mbps)  | 12.21         |        |
| MCS1 (13Mbps)   | 12.00         |        |
| MCS2 (19.5Mbps) | 11.98         |        |
| MCS3 (26Mbps)   | 12.27         | *      |
| MCS4 (39Mbps)   | 12.13         |        |
| MCS5 (52Mbps)   | 12.11         |        |
| MCS6 (58.5Mbps) | 11.94         |        |
| MCS7 (65Mbps)   | 12.12         |        |

\* : Worst Rate

All comparison were performed on the same measurement condition.

## 4) Bluetooth LE(Modulation type : GFSK)

Test Date: March 11, 2014

Temp.: 21 °C, Humi: 23 %

| Transmitting Frequency |       | Correction Factor | Meter Reading | Conducted Peak Output Power |      | Limits | Margin |
|------------------------|-------|-------------------|---------------|-----------------------------|------|--------|--------|
| CH                     | [MHz] | [dB]              | [dBm]         | [dBm]                       | [mW] | [dBm]  | [dB]   |
| 00                     | 2402  | 10.10             | -6.28         | 3.82                        | 2.41 | 30.00  | +26.18 |
| 19                     | 2440  | 10.11             | -5.34         | 4.77                        | 3.00 | 30.00  | +25.23 |
| 39                     | 2480  | 10.11             | -5.67         | 4.44                        | 2.78 | 30.00  | +25.56 |

Calculated result at 2440.000 MHz, as the worst point shown on underline:

|                   |   |                    |
|-------------------|---|--------------------|
| Correction Factor | = | 10.11 dB           |
| + ) Meter Reading | = | -5.34 dBm          |
| Result            | = | 4.77 dBm = 3.00 mW |

Minimum Margin: 30.00 - 4.77 = 25.23 (dB)

## NOTES

1. The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.

2. Setting of measuring instrument(s) :

|                   |            |
|-------------------|------------|
| Detector Function | Video B.W. |
| Peak              | Off        |

## 7.6 Peak Power Density(Conduction)

For the requirements, ☒ - Applicable ☒ - Tested. ☐ - Not tested by applicant request.]  
☐ - Not Applicable

For the limits, ☒ - Passed ☐ - Failed ☐ - Not judged

### 7.6.1 Worst Point and Measurement Uncertainty

|                                       |               |     |    |               |     |
|---------------------------------------|---------------|-----|----|---------------|-----|
| Peak Power Density of IEEE802.11b is  | <u>-8.36</u>  | dBm | at | <u>2462.0</u> | MHz |
| Peak Power Density of IEEE802.11g is  | <u>-12.79</u> | dBm | at | <u>2412.0</u> | MHz |
| Peak Power Density of IEEE802.11n is  | <u>-12.65</u> | dBm | at | <u>2462.0</u> | MHz |
| Peak Power Density of Bluetooth LE is | <u>-8.57</u>  | dBm | at | <u>2440.0</u> | MHz |

Uncertainty of Measurement Results at Amplitude +/-1.2 dB(2 $\sigma$ )

Remarks : \_\_\_\_\_

### 7.6.2 Test Site and Instruments

#### 7.6.2.1 Test Site

KITA-KANSAI Testing Center

Test site : SAITO


|                                                  |                                                          |
|--------------------------------------------------|----------------------------------------------------------|
| <input type="checkbox"/> - Anechoic chamber (A1) | <input type="checkbox"/> - Measurement room (M1)         |
| <input type="checkbox"/> - Measurement room (M2) | <input type="checkbox"/> - Measurement room (M3)         |
| <input type="checkbox"/> - Shielded room (S1)    | <input type="checkbox"/> - Shielded room (S2)            |
| <input type="checkbox"/> - Shielded room (S3)    | <input checked="" type="checkbox"/> - Shielded room (S4) |

**7.6.2.2 Test Instruments**

| Type              | Model       | Manufacturer | ID No. | Last Cal. | Interval |
|-------------------|-------------|--------------|--------|-----------|----------|
| Spectrum Analyzer | E4446A      | Agilent      | A-39   | 2013/9    | 1 Year   |
| Attenuator        | 54A-10      | Weinschel    | D-28   | 2013/9    | 1 Year   |
| RF Cable          | SUCOFLEX102 | SUHNER       | C-52   | 2013/7    | 1 Year   |

**7.6.3 Test Method and Test Setup (Diagrammatic illustration)**

The Conducted RF Power Output was measured with a power meter, one 10dB attenuator and a short, low loss cable.



## 7.6.4 Test Data

### 1) IEEE 802.11b

Test Date: March 11, 2014

Temp: 22 °C, Humi: 23 %

Data Rate : 11Mbps

| Transmitting Frequency |       | Correction Factor | BWCF   | Meter Reading | Conducted Peak Power Density |      | Limits | Margin |
|------------------------|-------|-------------------|--------|---------------|------------------------------|------|--------|--------|
| CH                     | [MHz] | [dB]              | [dB]   | [dBm]         | [dBm]                        | [mW] | [dBm]  | [dB]   |
| 01                     | 2412  | 10.10             | -10.00 | -8.86         | -8.76                        | 0.13 | 8.00   | +16.76 |
| 06                     | 2437  | 10.11             | -10.00 | -9.24         | -9.13                        | 0.12 | 8.00   | +17.13 |
| 11                     | 2462  | 10.11             | -10.00 | -8.47         | -8.36                        | 0.15 | 8.00   | +16.36 |

Calculated result at 2462.000 MHz, as the worst point shown on underline:


|                   |   |                     |
|-------------------|---|---------------------|
| Correction Factor | = | 10.11 dB            |
| BWCF              | = | -10.00 dB           |
| + ) Meter Reading | = | -8.47 dBm           |
| Result            | = | -8.36 dBm = 0.15 mW |

Minimum Margin: 8.00 - -8.36 = 16.36 (dB)

#### NOTES

1. The peak power density complied with the limit without BWCF.
2. The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.
3. BWCF(bandwidth correction factor) =  $10 \log (3 \text{ kHz}/30 \text{ kHz}) = -10.0 \text{ dB}$
4. Setting of measuring instrument(s) :

| Detector Function | RES B.W. | Video B.W. |
|-------------------|----------|------------|
| Peak              | 30kHz    | 100kHz     |



## 2) IEEE 802.11g

Data Rate : 6Mbps

Test Date: March 11, 2014

Temp.: 22 °C, Humi: 23 %

| Transmitting Frequency |       | Correction Factor | BWCF   | Meter Reading | Conducted Peak Power Density |      | Limits | Margin |
|------------------------|-------|-------------------|--------|---------------|------------------------------|------|--------|--------|
| CH                     | [MHz] | [dB]              | [dB]   | [dBm]         | [dBm]                        | [mW] | [dBm]  | [dB]   |
| 01                     | 2412  | 10.10             | -10.00 | -12.89        | -12.79                       | 0.05 | 8.00   | +20.79 |
| 06                     | 2437  | 10.11             | -10.00 | -13.26        | -13.15                       | 0.05 | 8.00   | +21.15 |
| 11                     | 2462  | 10.11             | -10.00 | -13.05        | -12.94                       | 0.05 | 8.00   | +20.94 |

Calculated result at 2412.000 MHz, as the worst point shown on underline:


|                   |   |                      |
|-------------------|---|----------------------|
| Correction Factor | = | 10.10 dB             |
| BWCF              | = | -10.00 dB            |
| + ) Meter Reading | = | -12.89 dBm           |
| Result            | = | -12.79 dBm = 0.05 mW |

Minimum Margin: 8.00 - -12.79 = 20.79 (dB)

## NOTES

- The peak power density complied with the limit without BWCF.
- The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.
- BWCF(bandwidth correction factor) =  $10 \log(3 \text{ kHz}/30 \text{ kHz}) = -10.0 \text{ dB}$
- Setting of measuring instrument(s) :

| Detector Function | RES.B.W. | Video B.W. |
|-------------------|----------|------------|
| Peak              | 30kHz    | 100kHz     |



### 3) IEEE 802.11n

Data Rate : MCS3(26Mbps)

Test Date: March 11, 2014

Temp.: 22 °C, Humi: 23 %

| CH | Transmitting Frequency |  | Correction Factor [dB] | BWCF [dB] | Meter Reading [dBm] | Conducted Peak Power Density |      | Limits [dBm] | Margin [dB] |
|----|------------------------|--|------------------------|-----------|---------------------|------------------------------|------|--------------|-------------|
|    | [MHz]                  |  |                        |           |                     | [dBm]                        | [mW] |              |             |
| 01 | 2412                   |  | 10.10                  | -10.00    | -13.12              | -13.02                       | 0.05 | 8.00         | +21.02      |
| 06 | 2437                   |  | 10.11                  | -10.00    | -13.90              | -13.79                       | 0.04 | 8.00         | +21.79      |
| 11 | 2462                   |  | 10.11                  | -10.00    | -12.76              | -12.65                       | 0.05 | 8.00         | +20.65      |

Calculated result at 2462.000 MHz, as the worst point shown on underline:


|                   |   |                      |
|-------------------|---|----------------------|
| Correction Factor | = | 10.11 dB             |
| BWCF              | = | -10.00 dB            |
| + ) Meter Reading | = | -12.76 dBm           |
| Result            | = | -12.65 dBm = 0.05 mW |

Minimum Margin: 8.00 - 12.65 = 20.65 (dB)

#### NOTES

1. The peak power density complied with the limit without BWCF.
2. The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.
3. BWCF(bandwidth correction factor) =  $10 \log(3 \text{ kHz}/30 \text{ kHz}) = -10.0 \text{ dB}$
4. Setting of measuring instrument(s) :

| Detector Function | RES B.W. | Video B.W. |
|-------------------|----------|------------|
| Peak              | 30kHz    | 100kHz     |



## 4) Bluetooth LE(Modulation type : GFSK)

Test Date: March 11, 2014

Temp.: 21 °C, Humi: 23 %

| Transmitting Frequency |       | Correction Factor | BWCF   | Meter Reading | Conducted Peak Power Density |      | Limits | Margin |
|------------------------|-------|-------------------|--------|---------------|------------------------------|------|--------|--------|
| CH                     | [MHz] | [dB]              | [dB]   | [dBm]         | [dBm]                        | [mW] | [dBm]  | [dB]   |
| 00                     | 2402  | 10.10             | -10.00 | -9.62         | -9.52                        | 0.11 | 8.00   | +17.52 |
| 19                     | 2440  | 10.11             | -10.00 | -8.68         | -8.57                        | 0.14 | 8.00   | +16.57 |
| 39                     | 2480  | 10.11             | -10.00 | -9.02         | -8.91                        | 0.13 | 8.00   | +16.91 |

Calculated result at 2440.000 MHz, as the worst point shown on underline:


|                   |   |                     |
|-------------------|---|---------------------|
| Correction Factor | = | 10.11 dB            |
| BWCF              | = | -10.00 dB           |
| + ) Meter Reading | = | -8.68 dBm           |
| Result            | = | -8.57 dBm = 0.14 mW |

Minimum Margin: 8.00 - -8.57 = 16.57 (dB)

## NOTES

1. The peak power density complied with the limit without BWCF.
2. The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.
3. BWCF(bandwidth correction factor) =  $10 \log(3 \text{ kHz}/30 \text{ kHz}) = -10.0 \text{ dB}$
4. Setting of measuring instrument(s) :

| Detector Function | RES.B.W. | Video B.W. |
|-------------------|----------|------------|
| Peak              | 30kHz    | 100kHz     |



## 7.7 Spurious Emissions(Conduction)

For the requirements, ☒ - Applicable ☒ - Tested. ☐ - Not tested by applicant request.]  
☐ - Not Applicable

For the limits, ☒ - Passed ☐ - Failed ☐ - Not judged

### 7.7.1 Worst Point and Measurement Uncertainty

|                                    |               |               |        |
|------------------------------------|---------------|---------------|--------|
| Uncertainty of Measurement Results | 9 kHz – 1GHz  | <u>+/-1.0</u> | dB(2σ) |
|                                    | 1GHz – 18GHz  | <u>+/-1.2</u> | dB(2σ) |
|                                    | 18GHz – 40GHz | <u>+/-1.6</u> | dB(2σ) |

Remarks : \_\_\_\_\_

### 7.7.2 Test Site and Instruments

#### 7.7.2.1 Test Site

KITA-KANSAI Testing Center


|                   |                                                  |                                                          |
|-------------------|--------------------------------------------------|----------------------------------------------------------|
| Test site : SAITO | <input type="checkbox"/> - Anechoic chamber (A1) | <input type="checkbox"/> - Measurement room (M1)         |
|                   | <input type="checkbox"/> - Measurement room (M2) | <input type="checkbox"/> - Measurement room (M3)         |
|                   | <input type="checkbox"/> - Shielded room (S1)    | <input type="checkbox"/> - Shielded room (S2)            |
|                   | <input type="checkbox"/> - Shielded room (S3)    | <input checked="" type="checkbox"/> - Shielded room (S4) |

### 7.7.2.2 Test Instruments

| Type              | Model       | Manufacturer | ID No. | Last Cal. | Interval |
|-------------------|-------------|--------------|--------|-----------|----------|
| Spectrum Analyzer | E4446A      | Agilent      | A-39   | 2013/9    | 1 Year   |
| Attenuator        | 54A-10      | Weinschel    | D-28   | 2013/9    | 1 Year   |
| RF Cable          | SUCOFLEX102 | SUHNER       | C-52   | 2013/7    | 1 Year   |

### 7.7.3 Test Method and Test Setup (Diagrammatic illustration)

The test system is shown as follows:



The setting of the spectrum analyzer are shown as follows:

|                 |                 |           |
|-----------------|-----------------|-----------|
| Frequency Range | 30 MHz - 25 GHz | Band-Edge |
| Res. Bandwidth  | 100 kHz         | 100 kHz   |
| Video Bandwidth | 300 kHz         | 300 kHz   |
| Sweep Time      | AUTO            | AUTO      |
| Trace           | Maxhold         | Maxhold   |


## 7.7.4 Test Data

Test Date : March 11, 2014


Temp.:21°C, Humi:23%

### 1) IEEE 802.11b


#### Low Channel



## Middle Channel




## High Channel




## 2) IEEE 802.11g


### Low Channel



## Middle channel




## High Channel




## 3) IEEE 802.11n

### Low Channel



## Middle Channel




## High Channel




## 4) Bluetooth Low Energy


### Low Channel



## Middle Channel




## High Channel




## Band-Edge Emission

### 1) IEEE 802.11b

#### Low Channel




#### High Channel




## 2) IEEE 802.11g

### Low Channel




### High Channel




## 3) IEEE 802.11n

### Low Channel




### High Channel




## 4) Bluetooth Low Energy

### Low Channel



### High Channel



**7.8 AC Powerline Conducted Emission**

For the requirements, ☒ - Applicable ☒ - Tested. ☐ - Not tested by applicant request.]  
☐ - Not Applicable

For the limits, ☒ - Passed ☐ - Failed ☐ - Not judged

**7.8.1 Worst Point and Measurement Uncertainty**

Min. Limit Margin (Quasi-Peak) 13.8 dB at 0.52 MHz

Uncertainty of Measurement Results +/-2.7 dB(2 $\sigma$ )

Remarks : WLAN mode

**7.8.2 Test Site and Instruments****7.8.2.1 Test Site**

KITA-KANSAI Testing Center

Test site : SAITO ☐ - Anechoic chamber (A1) ☐ - Measurement room (M1)  
☒ - Measurement room (M2) ☐ - Measurement room (M3)  
☐ - Shielded room (S1) ☐ - Shielded room (S2)  
☐ - Shielded room (S3) ☐ - Shielded room (S4)

**7.8.2.2 Test Instruments**

| Type          | Model    | Manufacturer    | ID No. | Last Cal. | Interval |
|---------------|----------|-----------------|--------|-----------|----------|
| Test Receiver | ESU 26   | Rohde & Schwarz | A-6    | 2013/4    | 1 Year   |
| AMN (main)    | KNW-407R | Kyoritsu        | D-39   | 2013/9    | 1 Year   |
| RF Cable      | RG223/U  | SUHNER          | H-7    | 2013/11   | 1 Year   |


### 7.8.3 Test Method and Test Setup (Diagrammatic illustration)

The preliminary tests were performed using the scan mode of test receiver or spectrum analyzer to observe the emissions characteristics of the EUT.

The EUT configuration, cable configuration and mode of operation were determined for producing the maximum level of emissions.

This configurations was used for final tests.

– Side View –



#### NOTE

AMN : Artificial Mains Network


#### 7.8.4 Test Data

- 1) Mode of EUT : (WLAN) All modes have been investigated and the worst case mode for channel (06ch: 2437MHz / IEEE 802.11b, IEEE 802.11g and IEEE 802.11n) has been listed.

Test Date: March 14, 2014

Temp.: 20 °C, Humi.: 39 %

| Frequency<br>[MHz] | Corr.<br>Factor<br>[dB] | Meter Readings [dB(μV)] |    |      |    | Limits<br>[dB(μV)] |      | Results<br>[dB(μV)] |     | Margin<br>[dB] | Remarks |
|--------------------|-------------------------|-------------------------|----|------|----|--------------------|------|---------------------|-----|----------------|---------|
|                    |                         | VA                      |    | VB   |    | QP                 | AVE  | QP                  | AVE |                |         |
| 0.21               | 10.2                    | 38.8                    | -- | 36.7 | -- | 63.2               | 53.2 | 49.0                | --  | +14.2          | -       |
| 0.31               | 10.2                    | 29.8                    | -- | 28.5 | -- | 60.0               | 50.0 | 40.0                | --  | +20.0          | -       |
| 0.41               | 10.2                    | 27.1                    | -- | 26.9 | -- | 57.6               | 47.6 | 37.3                | --  | +20.3          | -       |
| 0.52               | 10.1                    | 32.1                    | -- | 28.7 | -- | 56.0               | 46.0 | 42.2                | --  | +13.8          | -       |
| 0.63               | 10.2                    | 31.3                    | -- | 25.8 | -- | 56.0               | 46.0 | 41.5                | --  | +14.5          | -       |
| 2.57               | 10.3                    | 31.7                    | -- | 17.8 | -- | 56.0               | 46.0 | 42.0                | --  | +14.0          | -       |
| 4.34               | 10.4                    | 26.8                    | -- | 13.7 | -- | 56.0               | 46.0 | 37.2                | --  | +18.8          | -       |
| 30.00              | 11.5                    | 28.8                    | -- | 22.7 | -- | 60.0               | 50.0 | 40.3                | --  | +19.7          | -       |




#### NOTES

- The spectrum was checked from 0.15 MHz to 30 MHz.
- The correction factor includes the AMN insertion loss and the cable loss.
- The symbol of "<" means "or less".
- The symbol of ">" means "more than".
- The symbol of "--" means "not applicable".
- Calculated result at 0.52 MHz, as the worst point shown on underline:  
Correction Factor + Meter Reading = 10.1 + 32.1 = 42.2 dB(μV)
- QP : Quasi-Peak Detector / AVE : Average Detector
- Test receiver setting(s) : CISPR QP 9 kHz / Average 9 kHz

## 2) Mode of EUT : Bluetooth Low Energy

Test Date: March 14, 2014  
Temp.: 20 °C, Humi.: 39 %

| Frequency<br>[MHz] | Corr.<br>Factor<br>[dB] | Meter Readings [dB(μV)] |     |      |     | Limits<br>[dB(μV)] |      | Results<br>[dB(μV)] |     | Margin<br>[dB] | Remarks |
|--------------------|-------------------------|-------------------------|-----|------|-----|--------------------|------|---------------------|-----|----------------|---------|
|                    |                         | VA                      |     | VB   |     | QP                 | AVE  | QP                  | AVE |                |         |
|                    |                         | QP                      | AVE | QP   | AVE |                    |      |                     |     |                |         |
| 0.21               | 10.2                    | 38.7                    | --  | 36.6 | --  | 63.2               | 53.2 | 48.9                | --  | +14.3          | -       |
| 0.31               | 10.2                    | 29.8                    | --  | 28.5 | --  | 60.0               | 50.0 | 40.0                | --  | +20.0          | -       |
| 0.41               | 10.2                    | 27.3                    | --  | 27.0 | --  | 57.6               | 47.6 | 37.5                | --  | +20.1          | -       |
| 0.51               | 10.1                    | 31.9                    | --  | 28.7 | --  | 56.0               | 46.0 | 42.0                | --  | +14.0          | -       |
| 0.62               | 10.2                    | 31.3                    | --  | 25.8 | --  | 56.0               | 46.0 | 41.5                | --  | +14.5          | -       |
| 2.57               | 10.3                    | 31.8                    | --  | 17.6 | --  | 56.0               | 46.0 | 42.1                | --  | +13.9          | -       |
| 3.43               | 10.3                    | 27.7                    | --  | 14.3 | --  | 56.0               | 46.0 | 38.0                | --  | +18.0          | -       |
| 30.00              | 11.5                    | 27.8                    | --  | 22.0 | --  | 60.0               | 50.0 | 39.3                | --  | +20.7          | -       |



## NOTES

1. The spectrum was checked from 0.15 MHz to 30 MHz.
2. The correction factor includes the AMN insertion loss and the cable loss.
3. The symbol of "<" means "or less".
4. The symbol of ">" means "more than".
5. The symbol of "--" means "not applicable".
6. Calculated result at 2.57 MHz, as the worst point shown on underline:  
Correction Factor + Meter Reading = 10.3 + 31.8 = 42.1 dB(μV)
7. QP : Quasi-Peak Detector / AVE : Average Detector
8. Test receiver setting(s) : CISPR QP 9 kHz / Average 9 kHz

## 7.9 Radiated Emission

The requirements are ☒ - Applicable ☒ - Tested. ☐ - Not tested by applicant request.]  
☐ - Not Applicable

☒ - Passed ☐ - Failed ☐ - Not judged

### 7.9.1 Worst Point and Measurement Uncertainty

|                                    |                    |               |                   |
|------------------------------------|--------------------|---------------|-------------------|
| Min. Limit Margin (Peak)           | <u>3.1</u> dB      | at            | <u>2389.8</u> MHz |
| Uncertainty of Measurement Results | 9 kHz – 30 MHz     | <u>+/-1.9</u> | dB(2 $\sigma$ )   |
|                                    | 30 MHz – 300 MHz   | <u>+/-4.3</u> | dB(2 $\sigma$ )   |
|                                    | 300 MHz – 1000 MHz | <u>+/-5.4</u> | dB(2 $\sigma$ )   |
|                                    | 1 GHz – 6 GHz      | <u>+/-4.6</u> | dB(2 $\sigma$ )   |
|                                    | 6 GHz – 18 GHz     | <u>+/-5.2</u> | dB(2 $\sigma$ )   |
|                                    | 18 GHz – 40 GHz    | <u>+/-5.4</u> | dB(2 $\sigma$ )   |

Remarks : IEEE802.11n mode. The measurement result is within the range of measurement uncertainty.

### 7.9.2 Test Site and Instruments

#### 7.9.2.1 Test Site

KITA-KANSAI Testing Center SAITO EMC Branch

☐ - Anechoic chamber A1

☒ - Anechoic chamber A2

### 7.9.2.2 Test Instruments

| Type                  | Model             | Manufacturer    | ID No. | Last Cal. | Interval |
|-----------------------|-------------------|-----------------|--------|-----------|----------|
| Test Receiver         | ESU 26            | Rohde & Schwarz | A-6    | 2013/4    | 1 Year   |
| Loop Antenna          | HFH2-Z2           | Rohde & Schwarz | C-2    | 2013/8    | 1 Year   |
| RF Cable              | RG213/U           | SUHNER          | H-28   | 2013/8    | 1 Year   |
| Biconical Antenna     | VHA9103/BBA9106   | Schwarzbeck     | C-30   | 2013/5    | 1 Year   |
| Log-periodic Antenna  | UHALP9108-A1      | Schwarzbeck     | C-31   | 2013/5    | 1 Year   |
| RF Cable              | S 10162 B-11 etc. | SUHNER          | H-4    | 2013/4    | 1 Year   |
| Site Attenuation      | --                | ----            | H-15   | 2014/1    | 1 Year   |
| Pre-Amplifier         | WJ-6882-824       | Watkins Johnson | A-21   | 2014/1    | 1 Year   |
| Pre-Amplifier         | WJ-6611-513       | Watkins Johnson | A-23   | 2014/1    | 1 Year   |
| Pre-Amplifier         | BZ1840LD1         | B&Z             | A-29   | 2014/1    | 1 Year   |
| Pre-Amplifier         | DBL-0618N515      | DBS Microwave   | A-33   | 2014/1    | 1 Year   |
| Horn Antenna          | 91888-2           | EATON           | C-41-1 | 2013/6    | 1 Year   |
| Horn Antenna          | 91889-2           | EATON           | C-41-2 | 2013/6    | 1 Year   |
| Horn Antenna          | 3160-04           | EMCO            | C-55   | 2013/7    | 1 Year   |
| Horn Antenna          | 3160-05           | EMCO            | C-56   | 2013/7    | 1 Year   |
| Horn Antenna          | 3160-06           | EMCO            | C-57   | 2013/7    | 1 Year   |
| Horn Antenna          | 3160-07           | EMCO            | C-58   | 2013/7    | 1 Year   |
| Horn Antenna          | 3160-08           | EMCO            | C-59   | 2013/7    | 1 Year   |
| Horn Antenna          | 3160-09           | EMCO            | C-48   | 2013/7    | 1 Year   |
| Attenuator            | 54A-10            | Weinschel       | D-29   | 2013/9    | 1 Year   |
| Attenuator            | 2-10              | Weinschel       | D-79   | 2013/11   | 1 Year   |
| Band Rejection Filter | BRM50701          | MICRO-TRONICS   | D-93   | 2014/2    | 1 Year   |
| RF Cable              | SUCOFLEX102E      | HUBER+SUHNER    | C-75   | 2014/2    | 1 Year   |
| RF Cable              | SUCOFLEX104       | SUHNER          | C-66   | 2014/1    | 1 Year   |
| RF Cable              | SUCOFLEX104       | SUHNER          | C-67   | 2014/1    | 1 Year   |
| RF Cable              | SUCOFLEX102EA     | SUHNER          | C-69   | 2014/2    | 1 Year   |
| SVSWR                 | --                | ----            | H-19   | 2013/9    | 1 Year   |
| Pre-Amplifier         | 310N              | SONOMA          | A-17   | 2013/4    | 1 Year   |

### 7.9.3 Test Method and Test Setup (Diagrammatic illustration)


#### 7.9.3.1 Radiated Emission 9 kHz – 30 MHz

The preliminary tests were performed at the measurement distance that specified for compliance to determine the emission characteristics of the EUT.

The EUT configuration(in X, Y and Z axis), cable configuration and mode of operation were determined for producing the maximum level of emissions.

This configurations was used for the final tests.

– Side View –




### 7.9.3.2 Radiated Emission 30 MHz – 1000 MHz

The preliminary tests were performed at the measurement distance that specified for compliance to determine the emission characteristics of the EUT.

The EUT configuration(in X, Y and Z axis), cable configuration and mode of operation were determined for producing the maximum level of emissions.

This configurations was used for the final tests.

– Side View –



### 7.9.3.3 Radiated Emission above 1 GHz

The preliminary tests were performed at the measurement distance that specified for compliance to determine the emission characteristics of the EUT.

The EUT configuration(in X, Y and Z axis), cable configuration and mode of operation were determined for producing the maximum level of emissions.


This configurations was used for the final tests.

The setting of the measuring instruments are shown as follows:

| Type              | Peak     | Average         |
|-------------------|----------|-----------------|
| Detector Function | Peak     | RMS             |
| Res. Bandwidth    | 1 MHz    | 1 MHz           |
| Video Bandwidth   | 3 MHz    | $\geq 1/T * 1)$ |
| Sweep Time        | AUTO     | AUTO            |
| Trace             | Max Hold | Max Hold        |

Note: 1. T: Minimum transmission duration

– Side View –



#### NOTE

The antenna height is scanned depending on the EUT's size and mounting height.

## 7.9.4 Test Data


### 7.9.4.1 Band-edge Compliance

Test Date : March 5, 2014

Temp.:22°C, Humi:33%

Mode of EUT : TX( 1ch: 2412 MHz, (IEEE 802.11b))


Antenna Polarization : Horizontal



Note: The trace 1 is Peak detection. The trace 2 is RMS detection.

Mode of EUT : TX( 1ch: 2412 MHz, (IEEE 802.11b))


Antenna Polarization : Vertical



Note: The trace 1 is Peak detection. The trace 2 is RMS detection.

Mode of EUT : TX( 11ch: 2462 MHz, (IEEE 802.11b))


Antenna Polarization : Horizontal



Note: The trace 1 is Peak detection. The trace 2 is RMS detection.

Mode of EUT : TX( 11ch: 2462 MHz, (IEEE 802.11b))


Antenna Polarization : Vertical



Note: The trace 1 is Peak detection. The trace 2 is RMS detection.

Mode of EUT : TX( 1ch: 2412 MHz, (IEEE 802.11g))


Antenna Polarization : Horizontal



Note: The trace 1 is Peak detection. The trace 2 is RMS detection.

Mode of EUT : TX( 1ch: 2412 MHz, (IEEE 802.11g))


Antenna Polarization : Vertical



Note: The trace 1 is Peak detection. The trace 2 is RMS detection.

Mode of EUT : TX( 11ch: 2462 MHz, (IEEE 802.11g))


Antenna Polarization : Horizontal



Note: The trace 1 is Peak detection. The trace 2 is RMS detection.

Mode of EUT : TX( 11ch: 2462 MHz, (IEEE 802.11g))


Antenna Polarization : Vertical



Note: The trace 1 is Peak detection. The trace 2 is RMS detection.

Mode of EUT : TX( 1ch: 2412 MHz, (IEEE 802.11n))


Antenna Polarization : Horizontal



Note: The trace 1 is Peak detection. The trace 2 is RMS detection.

Mode of EUT : TX( 1ch: 2412 MHz, (IEEE 802.11n))


Antenna Polarization : Vertical



Note: The trace 1 is Peak detection. The trace 2 is RMS detection.

Mode of EUT : TX( 11ch: 2462 MHz, (IEEE 802.11n))


Antenna Polarization : Horizontal



Note: The trace 1 is Peak detection. The trace 2 is RMS detection.

Mode of EUT : TX( 11ch: 2462 MHz, (IEEE 802.11n))


Antenna Polarization : Vertical



Note: The trace 1 is Peak detection. The trace 2 is RMS detection.

Mode of EUT : Bluetooth Low Energy, Hopping off (0ch: 2402 MHz)


Antenna Polarization : Horizontal



Note: The trace 1 is Peak detection. The trace 2 is RMS detection.

Mode of EUT : Bluetooth Low Energy, Hopping off (0ch: 2402 MHz)


Antenna Polarization : Vertical



Note: The trace 1 is Peak detection. The trace 2 is RMS detection.

Mode of EUT : Bluetooth Low Energy, Hopping off (78ch: 2480 MHz)


Antenna Polarization : Horizontal



Note: The trace 1 is Peak detection. The trace 2 is RMS detection.

Mode of EUT : Bluetooth Low Energy, Hopping off (78ch: 2480 MHz)

Antenna Polarization : Vertical



Note: The trace 1 is Peak detection. The trace 2 is RMS detection.

#### 7.9.4.2 Other Spurious Emission (9kHz – 30MHz)

Test Date : March 13, 2014

Temp.:20°C, Humi:47%

Mode of EUT : WLAN/Bluetooth LE

Results : No spurious emissions in the range 20dB below the limit.


#### 7.9.4.3 Other Spurious Emission (30MHz – 1000MHz)

Mode of EUT : (WLAN) All modes have been investigated and the worst case mode for channel (06ch: 2437MHz / IEEE802.11b, IEEE802.11g and IEEE802.11n) has been listed.

Test Date: March 13, 2014

Temp.: 20 °C, Humi: 47 %

| Frequency<br>[MHz] | Antenna<br>Factor<br>[dB(1/m)] | Cable<br>Loss<br>[dB] | Meter Readings<br>[dB(μV)] |        | Limits<br>[dB(μV/m)] | Results<br>[dB(μV/m)] |        | Margin<br>[dB] | Remarks |
|--------------------|--------------------------------|-----------------------|----------------------------|--------|----------------------|-----------------------|--------|----------------|---------|
|                    |                                |                       | Hori.                      | Vert.  |                      | Hori.                 | Vert.  |                |         |
| 31.0               | 18.4                           | -27.7                 | < 25.0                     | 26.0   | 40.0                 | < 15.7                | 16.7   | +23.3          | -       |
| 40.7               | 14.7                           | -27.5                 | < 25.0                     | 27.7   | 40.0                 | < 12.2                | 14.9   | +25.1          | -       |
| 192.0              | 16.3                           | -26.1                 | 27.0                       | 25.2   | 43.5                 | 17.2                  | 15.4   | +26.3          | -       |
| 207.6              | 16.7                           | -25.9                 | 35.1                       | 29.2   | 43.5                 | 25.9                  | 20.0   | +17.6          | -       |
| 311.4              | 14.1                           | -25.3                 | 34.2                       | 27.9   | 46.0                 | 23.0                  | 16.7   | +23.0          | -       |
| 415.2              | 16.5                           | -24.8                 | 27.1                       | < 25.0 | 46.0                 | 18.8                  | < 16.7 | +27.2          | -       |



#### NOTES


1. Test Distance : 3 m
2. The spectrum was checked from 30 MHz to 1000 MHz.
3. The symbol of "<" means "or less".
4. The symbol of ">" means "more than".
5. Calculated result at 207.6 MHz, as the worst point shown on underline:  
Antenna Factor + Cable Loss + Meter Reading = 16.7 + -25.9 + 35.1 = 25.9 dB(μV/m)
6. Test receiver setting(s) : CISPR QP 120 kHz (QP : Quasi-Peak)

Mode of EUT : Bluetooth Low Energy

Test Date: March 14, 2014

Temp.: 20 °C, Humi: 39 %

| Frequency<br>[MHz] | Antenna<br>Factor<br>[dB(1/m)] | Cable<br>Loss<br>[dB] | Meter Readings<br>[dB(μV)] |        | Limits<br>[dB(μV/m)] | Results<br>[dB(μV/m)] |        | Margin<br>[dB] | Remarks |
|--------------------|--------------------------------|-----------------------|----------------------------|--------|----------------------|-----------------------|--------|----------------|---------|
|                    |                                |                       | Hori.                      | Vert.  |                      | Hori.                 | Vert.  |                |         |
| 30.0               | 18.8                           | -27.7                 | < 25.0                     | 26.0   | 40.0                 | < 16.1                | 17.1   | +22.9          | -       |
| 40.2               | 14.9                           | -27.5                 | < 25.0                     | 26.7   | 40.0                 | < 12.4                | 14.1   | +25.9          | -       |
| 172.9              | 15.7                           | -26.2                 | 29.7                       | < 25.0 | 43.5                 | 19.2                  | < 14.5 | +24.3          | -       |
| 207.6              | 16.7                           | -25.9                 | 35.1                       | 36.1   | 43.5                 | 25.9                  | 26.9   | +16.6          | -       |
| 311.4              | 14.1                           | -25.3                 | 31.9                       | 25.2   | 46.0                 | 20.7                  | 14.0   | +25.3          | -       |
| 415.2              | 16.5                           | -24.8                 | 28.1                       | < 25.0 | 46.0                 | 19.8                  | < 16.7 | +26.2          | -       |



## NOTES

1. Test Distance : 3 m
2. The spectrum was checked from 30 MHz to 1000 MHz.
3. The symbol of "<" means "or less".
4. The symbol of ">" means "more than".
5. Calculated result at 207.6 MHz, as the worst point shown on underline:  
Antenna Factor + Cable Loss + Meter Reading = 16.7 + -25.9 + 36.1 = 26.9 dB(μV/m)
6. Test receiver setting(s) : CISPR QP 120 kHz (QP : Quasi-Peak)

#### 7.9.4.4 Other Spurious Emission (Above 1000MHz)

##### 7.9.4.4.1 Mode of TX

##### 7.9.4.4.1.1 IEEE802.11b

Test Date: March 10, 2014

Temp.: 19 °C, Humi: 33 %

| Frequency                     | Antenna<br>Factor | Corr.<br>Factor | Meter Readings [dB(μV)] |        |          |        | Limits     |      | Results    |        | Margin  | Remarks |
|-------------------------------|-------------------|-----------------|-------------------------|--------|----------|--------|------------|------|------------|--------|---------|---------|
|                               |                   |                 | Horizontal              |        | Vertical |        | [dB(μV/m)] |      | [dB(μV/m)] |        |         |         |
| [MHz]                         | [dB(1/m)]         | [dB]            | PK                      | AVE    | PK       | AVE    | PK         | AVE  | PK         | AVE    | [dB]    |         |
| Test condition : Tx Low Ch    |                   |                 |                         |        |          |        |            |      |            |        |         |         |
| 4824.0                        | 27.2              | -20.9           | 41.8                    | 33.8   | 41.5     | 33.5   | 74.0       | 54.0 | 48.1       | 40.1   | +13.9   |         |
| 12060.0                       | 33.7              | -27.1           | < 40.0                  | < 30.0 | < 40.0   | < 30.0 | 74.0       | 54.0 | < 46.6     | < 36.6 | > +17.4 |         |
| 19296.0                       | 40.5              | -22.2           | < 38.0                  | < 28.0 | < 38.0   | < 28.0 | 74.0       | 54.0 | < 56.3     | < 46.3 | > + 7.7 |         |
| Test condition : TX Middle Ch |                   |                 |                         |        |          |        |            |      |            |        |         |         |
| 4874.0                        | 27.2              | -21.1           | 42.7                    | 35.6   | 42.8     | 36.3   | 74.0       | 54.0 | 48.9       | 42.4   | +11.6   |         |
| 7311.0                        | 30.0              | -19.6           | < 40.0                  | < 30.0 | < 40.0   | < 30.0 | 74.0       | 54.0 | < 50.4     | < 40.4 | > +13.6 |         |
| 12185.0                       | 33.5              | -26.9           | < 40.0                  | < 30.0 | < 40.0   | < 30.0 | 74.0       | 54.0 | < 46.6     | < 36.6 | > +17.4 |         |
| 19496.0                       | 40.5              | -22.2           | < 38.0                  | < 28.0 | < 38.0   | < 28.0 | 74.0       | 54.0 | < 56.3     | < 46.3 | > + 7.7 |         |
| Test condition : TX High Ch   |                   |                 |                         |        |          |        |            |      |            |        |         |         |
| 4924.0                        | 27.2              | -21.2           | 41.6                    | 33.9   | 42.3     | 34.4   | 74.0       | 54.0 | 48.3       | 40.4   | +13.6   |         |
| 7386.0                        | 29.9              | -19.5           | < 40.0                  | < 30.0 | < 40.0   | < 30.0 | 74.0       | 54.0 | < 50.4     | < 40.4 | > +13.6 |         |
| 12310.0                       | 33.5              | -26.7           | < 40.0                  | < 30.0 | < 40.0   | < 30.0 | 74.0       | 54.0 | < 46.8     | < 36.8 | > +17.2 |         |
| 19696.0                       | 40.5              | -22.2           | < 38.0                  | < 28.0 | < 38.0   | < 28.0 | 74.0       | 54.0 | < 56.3     | < 46.3 | > + 7.7 |         |
| 22158.0                       | 40.6              | -21.3           | < 38.0                  | < 28.0 | < 38.0   | < 28.0 | 74.0       | 54.0 | < 57.3     | < 47.3 | > + 6.7 |         |

Calculated result at 22158.0 MHz, as the worst point shown on underline:

|                   |   |                |
|-------------------|---|----------------|
| Antenna Factor    | = | 40.6 dB(1/m)   |
| Corr. Factor      | = | -21.3 dB       |
| + ) Meter Reading | = | <28.0 dB(μV)   |
| Result            | = | <47.3 dB(μV/m) |

Minimum Margin: 54.0 - <47.3 = >6.7 (dB)

#### NOTES

- Test Distance : 3 m
- The spectrum was checked from 1 GHz to 25 GHz (10th harmonic of the highest fundamental frequency).
- The correction factor is shown as follows:
 

|                   |                                                                   |
|-------------------|-------------------------------------------------------------------|
| Corr. Factor [dB] | = Cable Loss + 20dB Pad Att. - Pre-Amp. Gain [dB] (1.0 - 7.6GHz)  |
| Corr. Factor [dB] | = Cable Loss + 10dB Pad Att. - Pre-Amp. Gain [dB] (7.6 - 18.0GHz) |
| Corr. Factor [dB] | = Cable Loss - Pre-Amp. Gain [dB] (over 18 GHz)                   |
- The symbol of "<" means "or less".
- The symbol of ">" means "more than".
- PK : Peak Detector / AVE : RMS Detector

### 7.9.4.4.1.2 IEEE802.11g

Test Date: March 10, 2014

Temp.: 19 °C, Humi: 33 %

| Frequency                     | Antenna<br>Factor | Corr.<br>Factor | Meter Readings [dB(μV)] |        |          |        | Limits     |      | Results    |        | Margin  | Remarks |
|-------------------------------|-------------------|-----------------|-------------------------|--------|----------|--------|------------|------|------------|--------|---------|---------|
|                               |                   |                 | Horizontal              |        | Vertical |        | [dB(μV/m)] |      | [dB(μV/m)] |        |         |         |
| [MHz]                         | [dB(1/m)]         | [dB]            | PK                      | AVE    | PK       | AVE    | PK         | AVE  | PK         | AVE    | [dB]    |         |
| Test condition : Tx Low Ch    |                   |                 |                         |        |          |        |            |      |            |        |         |         |
| 4824.0                        | 27.2              | -20.9           | < 40.0                  | < 30.0 | < 40.0   | < 30.0 | 74.0       | 54.0 | < 46.3     | < 36.3 | > +17.7 |         |
| 12060.0                       | 33.7              | -27.1           | < 40.0                  | < 30.0 | < 40.0   | < 30.0 | 74.0       | 54.0 | < 46.6     | < 36.6 | > +17.4 |         |
| 19296.0                       | 40.5              | -22.2           | < 38.0                  | < 28.0 | < 38.0   | < 28.0 | 74.0       | 54.0 | < 56.3     | < 46.3 | > + 7.7 |         |
| Test condition : TX Middle Ch |                   |                 |                         |        |          |        |            |      |            |        |         |         |
| 4874.0                        | 27.2              | -21.1           | < 40.0                  | < 30.0 | < 40.0   | < 30.0 | 74.0       | 54.0 | < 46.1     | < 36.1 | > +17.9 |         |
| 7311.0                        | 30.0              | -19.6           | < 40.0                  | < 30.0 | < 40.0   | < 30.0 | 74.0       | 54.0 | < 50.4     | < 40.4 | > +13.6 |         |
| 12185.0                       | 33.5              | -26.9           | < 40.0                  | < 30.0 | < 40.0   | < 30.0 | 74.0       | 54.0 | < 46.6     | < 36.6 | > +17.4 |         |
| 19496.0                       | 40.5              | -22.2           | < 38.0                  | < 28.0 | < 38.0   | < 28.0 | 74.0       | 54.0 | < 56.3     | < 46.3 | > + 7.7 |         |
| Test condition : TX High Ch   |                   |                 |                         |        |          |        |            |      |            |        |         |         |
| 4924.0                        | 27.2              | -21.2           | < 40.0                  | < 30.0 | < 40.0   | < 30.0 | 74.0       | 54.0 | < 46.0     | < 36.0 | > +18.0 |         |
| 7386.0                        | 29.9              | -19.5           | < 40.0                  | < 30.0 | < 40.0   | < 30.0 | 74.0       | 54.0 | < 50.4     | < 40.4 | > +13.6 |         |
| 12310.0                       | 33.5              | -26.7           | < 40.0                  | < 30.0 | < 40.0   | < 30.0 | 74.0       | 54.0 | < 46.8     | < 36.8 | > +17.2 |         |
| 19696.0                       | 40.5              | -22.2           | < 38.0                  | < 28.0 | < 38.0   | < 28.0 | 74.0       | 54.0 | < 56.3     | < 46.3 | > + 7.7 |         |
| 22158.0                       | 40.6              | -21.3           | < 38.0                  | < 28.0 | < 38.0   | < 28.0 | 74.0       | 54.0 | < 57.3     | < 47.3 | > + 6.7 |         |

Calculated result at 22158.0 MHz, as the worst point shown on underline:

|                   |   |                |
|-------------------|---|----------------|
| Antenna Factor    | = | 40.6 dB(1/m)   |
| Corr. Factor      | = | -21.3 dB       |
| + ) Meter Reading | = | <28.0 dB(μV)   |
| Result            | = | <47.3 dB(μV/m) |

Minimum Margin: 54.0 - <47.3 = >6.7 (dB)

#### NOTES

- Test Distance : 3 m
- The spectrum was checked from 1 GHz to 25 GHz (10th harmonic of the highest fundamental frequency).
- The correction factor is shown as follows:
  - Corr. Factor [dB] = Cable Loss + 20dB Pad Att. - Pre-Amp. Gain [dB] (1.0 - 7.6GHz)
  - Corr. Factor [dB] = Cable Loss + 10dB Pad Att. - Pre-Amp. Gain [dB] (7.6 - 18.0GHz)
  - Corr. Factor [dB] = Cable Loss - Pre-Amp. Gain [dB] (over 18 GHz)
- The symbol of "<" means "or less".
- The symbol of ">" means "more than".
- PK : Peak Detector / AVE : RMS Detector

### 7.9.4.4.1.3 IEEE802.11n

Test Date: March 10, 2014

Temp.: 19 °C, Humi: 33 %

| Frequency                     | Antenna | Corr.     | Meter Readings [dB(μV)] |        |          |        | Limits     |      | Results    |        | Margin  | Remarks |
|-------------------------------|---------|-----------|-------------------------|--------|----------|--------|------------|------|------------|--------|---------|---------|
|                               | Factor  | Factor    | Horizontal              |        | Vertical |        | [dB(μV/m)] |      | [dB(μV/m)] |        | [dB]    |         |
|                               | [MHz]   | [dB(1/m)] | [dB]                    | PK     | AVE      | PK     | AVE        | PK   | AVE        | PK     | AVE     |         |
| Test condition : Tx Low Ch    |         |           |                         |        |          |        |            |      |            |        |         |         |
| 4824.0                        | 27.2    | -20.9     | < 40.0                  | < 30.0 | < 40.0   | < 30.0 | 74.0       | 54.0 | < 46.3     | < 36.3 | > +17.7 |         |
| 12060.0                       | 33.7    | -27.1     | < 40.0                  | < 30.0 | < 40.0   | < 30.0 | 74.0       | 54.0 | < 46.6     | < 36.6 | > +17.4 |         |
| 19296.0                       | 40.5    | -22.2     | < 38.0                  | < 28.0 | < 38.0   | < 28.0 | 74.0       | 54.0 | < 56.3     | < 46.3 | > + 7.7 |         |
| Test condition : TX Middle Ch |         |           |                         |        |          |        |            |      |            |        |         |         |
| 4874.0                        | 27.2    | -21.1     | < 40.0                  | < 30.0 | < 40.0   | < 30.0 | 74.0       | 54.0 | < 46.1     | < 36.1 | > +17.9 |         |
| 7311.0                        | 30.0    | -19.6     | < 40.0                  | < 30.0 | < 40.0   | < 30.0 | 74.0       | 54.0 | < 50.4     | < 40.4 | > +13.6 |         |
| 12185.0                       | 33.5    | -26.9     | < 40.0                  | < 30.0 | < 40.0   | < 30.0 | 74.0       | 54.0 | < 46.6     | < 36.6 | > +17.4 |         |
| 19496.0                       | 40.5    | -22.2     | < 38.0                  | < 28.0 | < 38.0   | < 28.0 | 74.0       | 54.0 | < 56.3     | < 46.3 | > + 7.7 |         |
| Test condition : TX High Ch   |         |           |                         |        |          |        |            |      |            |        |         |         |
| 4924.0                        | 27.2    | -21.2     | < 40.0                  | < 30.0 | < 40.0   | < 30.0 | 74.0       | 54.0 | < 46.0     | < 36.0 | > +18.0 |         |
| 7386.0                        | 29.9    | -19.5     | < 40.0                  | < 30.0 | < 40.0   | < 30.0 | 74.0       | 54.0 | < 50.4     | < 40.4 | > +13.6 |         |
| 12310.0                       | 33.5    | -26.7     | < 40.0                  | < 30.0 | < 40.0   | < 30.0 | 74.0       | 54.0 | < 46.8     | < 36.8 | > +17.2 |         |
| 19696.0                       | 40.5    | -22.2     | < 38.0                  | < 28.0 | < 38.0   | < 28.0 | 74.0       | 54.0 | < 56.3     | < 46.3 | > + 7.7 |         |
| 22158.0                       | 40.6    | -21.3     | < 38.0                  | < 28.0 | < 38.0   | < 28.0 | 74.0       | 54.0 | < 57.3     | < 47.3 | > + 6.7 |         |

Calculated result at 22158.0 MHz, as the worst point shown on underline:

|                   |   |                |
|-------------------|---|----------------|
| Antenna Factor    | = | 40.6 dB(1/m)   |
| Corr. Factor      | = | -21.3 dB       |
| + ) Meter Reading | = | <28.0 dB(μV)   |
| Result            | = | <47.3 dB(μV/m) |

Minimum Margin: 54.0 - <47.3 = >6.7 (dB)

#### NOTES

- Test Distance : 3 m
- The spectrum was checked from 1 GHz to 25 GHz (10th harmonic of the highest fundamental frequency).
- The correction factor is shown as follows:
  - Corr. Factor [dB] = Cable Loss + 20dB Pad Att. - Pre-Amp. Gain [dB] (1.0 - 7.6GHz)
  - Corr. Factor [dB] = Cable Loss + 10dB Pad Att. - Pre-Amp. Gain [dB] (7.6 - 18.0GHz)
  - Corr. Factor [dB] = Cable Loss - Pre-Amp. Gain [dB] (over 18 GHz)
- The symbol of "<" means "or less".
- The symbol of ">" means "more than".
- PK : Peak Detector / AVE : RMS Detector

#### 7.9.4.4.1.4 Bluetooth Low Energy

Test Date: March 10, 2014

Temp.: 19 °C, Humi: 33 %

| Frequency                     | Antenna<br>Factor | Corr.<br>Factor | Meter Readings [dB(μV)] |        |          |        | Limits     |      | Results    |        | Margin  | Remarks |
|-------------------------------|-------------------|-----------------|-------------------------|--------|----------|--------|------------|------|------------|--------|---------|---------|
|                               |                   |                 | Horizontal              |        | Vertical |        | [dB(μV/m)] |      | [dB(μV/m)] |        |         |         |
|                               | [MHz]             | [dB(1/m)]       | [dB]                    | PK     | AVE      | PK     | AVE        | PK   | AVE        | PK     | AVE     |         |
| Test condition : Tx Low Ch    |                   |                 |                         |        |          |        |            |      |            |        |         |         |
| 4804.0                        | 27.2              | -20.9           | < 40.0                  | < 30.0 | < 40.0   | < 30.0 | 74.0       | 54.0 | < 46.3     | < 36.3 | > +17.7 |         |
| 12010.0                       | 33.7              | -27.1           | < 40.0                  | < 30.0 | < 40.0   | < 30.0 | 74.0       | 54.0 | < 46.6     | < 36.6 | > +17.4 |         |
| 19216.0                       | 40.5              | -22.2           | < 38.0                  | < 28.0 | < 38.0   | < 28.0 | 74.0       | 54.0 | < 56.3     | < 46.3 | > + 7.7 |         |
| Test condition : TX Middle Ch |                   |                 |                         |        |          |        |            |      |            |        |         |         |
| 4880.0                        | 27.2              | -21.1           | < 40.0                  | < 30.0 | < 40.0   | < 30.0 | 74.0       | 54.0 | < 46.1     | < 36.1 | > +17.9 |         |
| 7320.0                        | 30.0              | -19.6           | < 40.0                  | < 30.0 | < 40.0   | < 30.0 | 74.0       | 54.0 | < 50.4     | < 40.4 | > +13.6 |         |
| 12200.0                       | 33.5              | -26.9           | < 40.0                  | < 30.0 | < 40.0   | < 30.0 | 74.0       | 54.0 | < 46.6     | < 36.6 | > +17.4 |         |
| 19520.0                       | 40.5              | -22.2           | < 38.0                  | < 28.0 | < 38.0   | < 28.0 | 74.0       | 54.0 | < 56.3     | < 46.3 | > + 7.7 |         |
| Test condition : TX High Ch   |                   |                 |                         |        |          |        |            |      |            |        |         |         |
| 4960.0                        | 27.2              | -21.2           | < 40.0                  | < 30.0 | < 40.0   | < 30.0 | 74.0       | 54.0 | < 46.0     | < 36.0 | > +18.0 |         |
| 7440.0                        | 29.9              | -19.5           | < 40.0                  | < 30.0 | < 40.0   | < 30.0 | 74.0       | 54.0 | < 50.4     | < 40.4 | > +13.6 |         |
| 12400.0                       | 33.6              | -26.6           | < 40.0                  | < 30.0 | < 40.0   | < 30.0 | 74.0       | 54.0 | < 47.0     | < 37.0 | > +17.0 |         |
| 19840.0                       | 40.4              | -22.2           | < 38.0                  | < 28.0 | < 38.0   | < 28.0 | 74.0       | 54.0 | < 56.2     | < 46.2 | > + 7.8 |         |
| 22320.0                       | 40.6              | -21.2           | < 38.0                  | < 28.0 | < 38.0   | < 28.0 | 74.0       | 54.0 | < 57.4     | < 47.4 | > + 6.6 |         |

Calculated result at 22320.0 MHz, as the worst point shown on underline:

|                   |   |                |
|-------------------|---|----------------|
| Antenna Factor    | = | 40.6 dB(1/m)   |
| Corr. Factor      | = | -21.2 dB       |
| + ) Meter Reading | = | <28.0 dB(μV)   |
| Result            | = | <47.4 dB(μV/m) |

Minimum Margin: 54.0 - <47.4 = >6.6 (dB)

#### NOTES

- Test Distance : 3 m
- The spectrum was checked from 1 GHz to 25 GHz (10th harmonic of the highest fundamental frequency).
- The correction factor is shown as follows:
  - Corr. Factor [dB] = Cable Loss + 20dB Pad Att. - Pre-Amp. Gain [dB] (1.0 - 7.6GHz)
  - Corr. Factor [dB] = Cable Loss + 10dB Pad Att. - Pre-Amp. Gain [dB] (7.6 - 18.0GHz)
  - Corr. Factor [dB] = Cable Loss - Pre-Amp. Gain [dB] (over 18 GHz)
- The symbol of "<" means "or less".
- The symbol of ">" means "more than".
- PK : Peak Detector / AVE : Average Detector

### 7.9.4.4.2 Mode of RX (WLAN)

Test Date: March 10, 2014

Temp.: 19 °C, Humi: 33 %

| Frequency<br>[MHz]            | Antenna<br>Factor<br>[dB(1/m)] | Corr.<br>Factor<br>[dB] | Meter Readings [dB(μV)] |        |          |        | Limits<br>[dB(μV/m)] |      | Results<br>[dB(μV/m)] |        | Margin<br>[dB] | Remarks |
|-------------------------------|--------------------------------|-------------------------|-------------------------|--------|----------|--------|----------------------|------|-----------------------|--------|----------------|---------|
|                               |                                |                         | Horizontal              |        | Vertical |        | PK                   | AVE  | PK                    | AVE    |                |         |
|                               |                                |                         | PK                      | AVE    | PK       | AVE    |                      |      |                       |        |                |         |
| Test condition : RX Middle Ch |                                |                         |                         |        |          |        |                      |      |                       |        |                |         |
| 2437.0                        | 21.6                           | -21.7                   | < 40.0                  | < 30.0 | < 40.0   | < 30.0 | 74.0                 | 54.0 | < 39.9                | < 29.9 | > +24.1        |         |
| 4874.0                        | 27.2                           | -21.4                   | < 40.0                  | < 30.0 | < 40.0   | < 30.0 | 74.0                 | 54.0 | < 45.8                | < 35.8 | > +18.2        |         |
| 7311.0                        | 30.0                           | -19.9                   | < 40.0                  | < 30.0 | < 40.0   | < 30.0 | 74.0                 | 54.0 | < 50.1                | < 40.1 | > +13.9        |         |

Calculated result at 4874.0 MHz, as the worst point shown on underline:

|                   |   |                |
|-------------------|---|----------------|
| Antenna Factor    | = | 27.2 dB(1/m)   |
| Corr. Factor      | = | -21.4 dB       |
| + ) Meter Reading | = | <30.0 dB(μV)   |
| Result            | = | <35.8 dB(μV/m) |

Minimum Margin: 54.0 - <35.8 = >13.9 (dB)

#### NOTES

1. Test Distance : 3 m
2. The spectrum was checked from 1 GHz to 25 GHz (10th harmonic of the highest fundamental frequency).
3. The correction factor is shown as follows:  
Corr. Factor [dB] = Cable Loss + 20dB Pad Att. - Pre-Amp. Gain [dB] (1.0 - 7.6GHz)
4. The symbol of "<" means "or less".
5. The symbol of ">" means "more than".
6. PK : Peak Detector / AVE : RMS Detector

### 7.9.4.4.3 Mode of RX (Bluetooth Low Energy)

Test Date: March 10, 2014

Temp.: 19 °C, Humi: 33 %

| Frequency<br>[MHz]            | Antenna<br>Factor<br>[dB(1/m)] | Corr.<br>Factor<br>[dB] | Meter Readings [dB(μV)] |        |          |        | Limits<br>[dB(μV/m)] |      | Results<br>[dB(μV/m)] |        | Margin<br>[dB] | Remarks |
|-------------------------------|--------------------------------|-------------------------|-------------------------|--------|----------|--------|----------------------|------|-----------------------|--------|----------------|---------|
|                               |                                |                         | Horizontal              |        | Vertical |        | PK                   | AVE  | PK                    | AVE    |                |         |
|                               |                                |                         | PK                      | AVE    | PK       | AVE    |                      |      |                       |        |                |         |
| Test condition : RX Middle Ch |                                |                         |                         |        |          |        |                      |      |                       |        |                |         |
| 2440.0                        | 21.6                           | -21.7                   | < 40.0                  | < 30.0 | < 40.0   | < 30.0 | 74.0                 | 54.0 | < 39.9                | < 29.9 | > +24.1        |         |
| 4880.0                        | 27.2                           | -21.4                   | < 40.0                  | < 30.0 | < 40.0   | < 30.0 | 74.0                 | 54.0 | < 45.8                | < 35.8 | > +18.2        |         |
| 7320.0                        | 30.0                           | -19.9                   | < 40.0                  | < 30.0 | < 40.0   | < 30.0 | 74.0                 | 54.0 | < 50.1                | < 40.1 | > +13.9        |         |

Calculated result at 7320.0 MHz, as the worst point shown on underline:

|                   |   |                |
|-------------------|---|----------------|
| Antenna Factor    | = | 30.0 dB(1/m)   |
| Corr. Factor      | = | -19.9 dB       |
| + ) Meter Reading | = | <30.0 dB(μV)   |
| Result            | = | <40.1 dB(μV/m) |

Minimum Margin: 54.0 - <40.1 = >13.9 (dB)

#### NOTES

1. Test Distance : 3 m
2. The spectrum was checked from 1 GHz to 7.5 GHz .
3. The correction factor is shown as follows:  
Corr. Factor [dB] = Cable Loss + 20dB Pad Att. - Pre-Amp. Gain [dB] (1.0 - 7.6GHz)
4. The symbol of "<" means "or less".
5. The symbol of ">" means "more than".
6. PK : Peak Detector / AVE : RMS Detector