



EMI TEST REPORT

Test Report No. : 11232756H-B

Applicant : Sharp Corporation, Consumer Electronics Company,
Communication Systems Division

Type of Equipment : Smart Phone

Model No. : 506SH

FCC ID : APYHRO00233

Test standard : FCC Part 15 Subpart B 2015 Class B

Test Result : Complied

1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the above regulation.
4. The test results in this report are traceable to the national or international standards.
5. This test report must not be used by the customer product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.
6. This test report covers EMC technical requirements. It does not cover administrative issues such as Manual or non-EMC test related Requirements. (if applicable)

Date of test:

April 8, 2016

**Representative
test engineer:**

Shinya Watanabe
Engineer

Consumer Technology Division

Approved by :

Tsubasa Takayama
Engineer

Consumer Technology Division



NVLAP LAB CODE: 200572-0

This laboratory is accredited by the NVLAP LAB CODE 200572-0, U.S.A. The tests reported herein have been performed in accordance with its terms of accreditation.
*As for the range of Accreditation in NVLAP, you may refer to the WEB address,
http://japan.ul.com/resources/emc_accredited/

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

13-EM-F0429

REVISION HISTORY

Original Test Report No.: 11232756H-B

[illegible]

CONTENTS	PAGE
SECTION 1: Customer information	4
SECTION 2: Equipment under test (E.U.T.)	4
SECTION 3: Test specification, procedures & results	5
SECTION 4: Operation of E.U.T. during testing	8
SECTION 5: Conducted Emission	9
SECTION 6: Radiated Emission	10
APPENDIX 1: Test data	11
Conducted Emission	11
Radiated Emission	13
APPENDIX 2: Test instruments	17
APPENDIX 3: Photographs of test setup.....	18
Conducted Emission	18
Radiated Emission	19
Worst Case Position (Horizontal: X-axis/ Vertical:X-axis)	21

SECTION 1: Customer information

Company Name : Sharp Corporation, Consumer Electronics Company, Communication Systems Division
Address : 2-13-1 Iida Hachihonmatsu HigashiHiroshima-City, Hiroshima, 739-0192 Japan
Telephone Number : +81-82-420-1552
Facsimile Number : +81-82-420-1555
Contact Person : Hiroyuki Uwatoko

SECTION 2: Equipment under test (E.U.T.)

2.1 Identification of E.U.T.

Type of Equipment : Smart Phone
Model No. : 506SH
Serial No. : Refer to Section 4, Clause 4.2
Receipt Date of Sample : April 1, 2016
Country of Mass-production : Japan
Condition of EUT : Production prototype
(Not for Sale: This sample is equivalent to mass-produced items.)
Modification of EUT : No Modification by the test lab

2.2 Product description

Feature of EUT : 506SH is AXGP, Penta-band LTE(Band 1 / 2 / 3 / 4 / 8), Quad-band WCDMA(FDD I / II / IV / VIII) & Quad-band GSM(850 / 900 / 1800 / 1900) Multi-mode Smart Phone.
The EUT has the function that NFC, Bluetooth and Wireless-LAN technology interface for establishing contact and transmitting data with certain device.

Clock frequencies in the system : CPU: 2.1504 GHz (max)
Source oscillation: 19.2MHz, 27.12MHz(NFC), 27MHz(DTV), 48MHz(BT/WLAN)

SECTION 3: Test specification, procedures & results

3.1 Test specification

Test specification : FCC Part 15 Subpart B: 2015, final revised on November 23, 2015
*Some parts are effective on and after December 17, 2015 or December 23, 2015.
The revision does not affect the test specification applied to the EUT.

Title : FCC 47CFR Part15 Radio Frequency Device
Subpart B Unintentional Radiators

3.2 Procedures and results

Item	Test Procedure	Limits	Deviation	Worst margin	Result
Conducted emission	ANSI C63.4: 2014 7. AC powerline conducted emission measurements	Class B	N/A	[QP] 3.2 dB 0.16915 MHz, N [AV] 5.5 dB 0.16915 MHz, N	Complied
Radiated emission	ANSI C63.4: 2014 8. Radiated emission measurements	Class B	N/A	11.4 dB 72.027 MHz, Horizontal, QP	Complied

*Note: UL Japan, Inc's EMI Work Procedure 13-EM-W0420.

3.3 Addition to standard

No addition, exclusion nor deviation has been made from the standard.

3.4 Uncertainty

EMI

The following uncertainties have been calculated to provide a confidence level of 95 % using a coverage factor $k = 2$.

Frequency range	Conducted emission using AMN(LISN) (+dB)
0.009 – 0.15MHz	3.5 dB
0.15 – 30MHz	2.9 dB

Polarity	Radiated emission (Below 1GHz)			
	(3 m*)(+dB)		(10 m*)(+dB)	
	30 – 300 MHz	300 – 1000MHz	30 – 300 MHz	300 – 1000MHz
Horizontal	4.8 dB	5.2 dB	4.8 dB	5.0 dB
Vertical	4.5 dB	5.9 dB	4.8 dB	5.1 dB

Radiated emission				
(3 m*)(+dB)		(1 m*)(+dB)	(0.5 m*)(+dB)	(10 m*)(+dB)
1 – 6GHz	6 – 18GHz	10 – 26.5 GHz	26.5 – 40GHz	1 – 18 GHz
5.1 dB	5.3 dB	5.1 dB	5.1 dB	5.3 dB

Conducted Emission test

The data listed in this test report has enough margin, more than the site margin.

Radiated emission test(3 m)

The data listed in this test report has enough margin, more than the site margin.

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

3.5 Test Location

UL Japan, Inc. Ise EMC Lab. *NVLAP Lab. code: 200572-0
4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN
Telephone : +81 596 24 8999 Facsimile : +81 596 24 8124

	IC Registration Number	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Other rooms
No.1 semi-anechoic chamber	2973C-1	19.2 x 11.2 x 7.7m	7.0 x 6.0m	No.1 Power source room
No.2 semi-anechoic chamber	2973C-2	7.5 x 5.8 x 5.2m	4.0 x 4.0m	-
No.3 semi-anechoic chamber	2973C-3	12.0 x 8.5 x 5.9m	6.8 x 5.75m	No.3 Preparation room
No.3 shielded room	-	4.0 x 6.0 x 2.7m	N/A	-
No.4 semi-anechoic chamber	2973C-4	12.0 x 8.5 x 5.9m	6.8 x 5.75m	No.4 Preparation room
No.4 shielded room	-	4.0 x 6.0 x 2.7m	N/A	-
No.5 semi-anechoic chamber	-	6.0 x 6.0 x 3.9m	6.0 x 6.0m	-
No.6 shielded room	-	4.0 x 4.5 x 2.7m	4.0 x 4.5 m	-
No.6 measurement room	-	4.75 x 5.4 x 3.0m	4.75 x 4.15 m	-
No.7 shielded room	-	4.7 x 7.5 x 2.7m	4.7 x 7.5m	-
No.8 measurement room	-	3.1 x 5.0 x 2.7m	N/A	-
No.9 measurement room	-	8.8 x 4.6 x 2.8m	2.4 x 2.4m	-
No.11 measurement room	-	6.2 x 4.7 x 3.0m	4.8 x 4.6m	-

* Size of vertical conducting plane (for Conducted Emission test) : 2.0 x 2.0m for No.1, No.2, No.3, and No.4 semi-anechoic chambers and No.3 and No.4 shielded rooms.

3.6 Test data, Test instruments, and Test set up


Refer to APPENDIX.

SECTION 4: Operation of E.U.T. during testing

4.1 Operating modes

The mode(s) : 1) USB Data Com Mode
The USB data is communicated between EUT and Personal computer (Pair of EUT).
2) Standby Mode
Standby state for USB communication.

4.2 Configuration and peripherals



■ : Ferrite core which has been standard on support equipment.

*Cabling and setup were taken into consideration and test data was taken under worse case conditions.

Description of EUT and Support equipment

No.	Item	Model number	Serial number	Manufacturer	Remarks
A	Smart Phone	506SH	004401/11/570786/7	Sharp Corporation	EUT
B	microSD Memory Card	SD-C02G	None	TOSHIBA	-
C	Personal Computer	PP11L	CN-0D4571-48643-58P-1053	Dell	-
D	Mouse	M-UAG120	LZ733B70EVV	TOSHIBA	-
E	AC Adapter(PC)	PA-1650-05D3	CN-0YD637-71615-64Q-2243	Dell	-
F	Printer	895Cxi	SG8BA1W18J	Hewlett Packard	-
G	AC Adapter(Printer)	C4557-60004	C8L01B	Hewlett Packard	-

List of cables used

No.	Name	Length (m)	Shield		Remarks
			Cable	Connector	
1	USB Data Cable	0.95	Shielded	Shielded	-
2	Mouse Cable	0.72	Unshielded	Unshielded	-
3	AC Adaptor Cable (PC)	1.76	Unshielded	Unshielded	-
4	AC Power Cable (PC)	0.85	Unshielded	Unshielded	-
5	Parallel Cable	1.85	Shielded	Shielded	-
6	AC Adapter Cable (printer)	2.00	Unshielded	Unshielded	-
7	AC Power Cable (printer)	1.75	Unshielded	Unshielded	-

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

SECTION 5: Conducted Emission

5.1 Operating environment

Test place	: No. 1 semi anechoic chamber
Temperature	: See data
Humidity	: See data

5.2 Test configuration

EUT was placed on a urethane platform of nominal size, 1.0 m by 1.5 m, raised 0.8 m above the conducting ground plane.

The rear of tabletop was located 40 cm to the vertical conducting plane. The rear of EUT and its peripherals was aligned and flushed with rear of tabletop. All other surfaces of tabletop were at least 80 cm from any other grounded conducting surface. EUT was located 80 cm from the LISN/AMN and excess AC cable was bundled in center. I/O cables that were connected to the other peripherals were bundled in center. They were folded back and forth forming a bundle 30 cm to 40 cm long and were hanged at a 40 cm height to the ground plane. Each EUT current-carrying power lead, except the ground (safety) lead, was individually connected through a LISN/AMN to the input power source. All unused 50 ohm connectors of the LISN/AMN were resistivity terminated in 50 ohm when not connected to the measuring equipment.

Photographs of the set up are shown in Appendix 3.

Frequency range	: 0.15 MHz - 30 MHz
EUT position	: Table top
EUT operation mode	: See Clause 4.1

5.3 Test procedure

The AC Mains Terminal Continuous disturbance Voltage has been measured with the EUT within a semi anechoic chamber. The EUT was connected to a Line Impedance Stabilization Network (LISN)/ Artificial Mains network (AMN). An overview sweep with peak detection has been performed. The measurements have been performed with a quasi-peak detector and if required, with an average detector.

The conducted emission measurements were made with the following detector function of the test receiver.

Detector Type	: Quasi-Peak and CISPR AV
IF Bandwidth	: 9 kHz

5.4 Test result

Summary of the test results: Pass

Date: April 8, 2016

Test engineer: Shinya Watanabe

SECTION 6: Radiated Emission

6.1 Operating environment

Test place : No. 1 semi anechoic chamber
Temperature : See data
Humidity : See data

6.2 Test configuration

EUT was placed on a urethane platform of nominal size, 1.0 m by 1.5 m, raised 0.8 m above the conducting ground plane.

The EUT was set on the center of the tabletop.

Test was made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna was varied in height above the conducting ground plane to obtain the maximum signal strength.

Photographs of the set up are shown in Appendix 3.

6.3 Test conditions

Frequency range : 30 MHz - 300 MHz (Biconical antenna) / 300 MHz - 1000 MHz (Logperiodic antenna)
1000 MHz - 13000 MHz (Horn antenna)
Test distance : 3 m
EUT position : Table top
EUT operation mode : See Clause 4.1

6.4 Test procedure

The height of the measuring antenna varied between 1 m and 4 m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity.

The measurements were performed for both vertical and horizontal antenna polarization with the Test Receiver.

The radiated emission measurements were made with the following detector function of the Test Receiver.

Frequency	Below 1GHz	Above 1GHz *1)
Instrument used	Test Receiver	Test Receiver
IF Bandwidth	QP: BW 120kHz	PK: BW 1MHz, CISPR AV: BW 1MHz

*1) The measurement data was adjusted to a 3 m distance using the following Distance Factor.

Distance Factor: $20 \times \log (3.4\text{m} / 3\text{m}) = 1.09 \text{ dB}$

- The carrier level and noise levels were confirmed at each position of X, Y and Z axes of EUT to see the position of maximum noise, and the test was made at the position that has the maximum noise.

6.5 Test result

Summary of the test results: Pass

Date: April 8, 2016

Test engineer: Shinya Watanabe

Conducted Emission

DATA OF CONDUCTED EMISSION TEST


UL Japan, Inc. Ise EMC Lab. No.1 Semi Anechoic Chamber
Date : 2016/04/08

Report No. : 11232756H

Temp./Humi. : 21deg. C / 50% RH
Engineer : Shinya Watanabe

Mode / Remarks : Standby Mode

LIMIT : FCC15.107(a) QP ClassB
FCC15.107(a) AV ClassB



Frequency [MHz]	Reading Level		Corr. Factor [dB]	Results		Limit		Margin		Phase	Comment
	QP [dBuV]	AV [dBuV]		QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	QP [dB]	AV [dB]		
0.16786	46.3	33.8	13.2	59.5	47.0	65.1	55.1	5.6	8.1	N	
0.22383	39.7	26.8	13.3	53.0	40.1	62.7	52.7	9.7	12.6	N	
0.33558	30.1	19.2	13.3	43.4	32.5	59.3	49.3	15.9	16.8	N	
0.39158	27.9	16.1	13.3	41.2	29.4	58.0	48.0	16.8	18.6	N	
2.01605	22.6	20.0	13.6	36.2	33.6	56.0	46.0	19.8	12.4	N	
4.19721	29.0	17.1	14.0	43.0	31.1	56.0	46.0	13.0	14.9	N	
11.95901	19.3	12.7	14.7	34.0	27.4	60.0	50.0	26.0	22.6	N	
0.16766	45.9	33.2	13.2	59.1	46.4	65.1	55.1	6.0	8.7	L	
0.22323	39.9	26.4	13.3	53.2	39.7	62.7	52.7	9.5	13.0	L	
0.33512	31.9	19.1	13.3	45.2	32.4	59.3	49.3	14.1	16.9	L	
0.39129	28.3	17.6	13.3	41.6	30.9	58.0	48.0	16.4	17.1	L	
2.01605	18.5	14.4	13.6	32.1	28.0	56.0	46.0	23.9	18.0	L	
4.19721	31.8	20.4	14.0	45.8	34.4	56.0	46.0	10.2	11.6	L	
11.99919	22.0	15.4	14.7	36.7	30.1	60.0	50.0	23.3	19.9	L	

CHART : WITH FACTOR, Peak hold data. CALCULATION : RESULT = READING + C.F (LISN + ATTEN. + CABLE)
Except for the above table : adequate margin data below the limits.

*The limit is rounded down to one decimal place.

*The test result is rounded off to one or two decimal places, so some differences might be observed.

Radiated Emission
(Below 1GHz)

DATA OF RADIATED EMISSION TEST


UL Japan, Inc. Ise EMC Lab. No.1 Semi Anechoic Chamber
Date : 2016/04/08

Report No. : 11232756H

Temp./Humi. : 21deg. C. / 50%RH
Engineer : Shinya Watanabe

Mode / Remarks : USB Data Com Mode

LIMIT : FCC15.109(a) 3m, below 1GHz:QP, above 1GHz:PK
Except for the data below : adequate margin data below the limits.



Frequency	Reading	DET	Antenna Factor	Loss& Gain	Level	Angle	Height	Polar.	Limit	Margin	Comment
[MHz]	[dBuV]		[dB/m]	[dB]	[dBuV/m]	[Deg]	[cm]		[dBuV/m]	[dB]	
55.211	45.6	QP	8.9	-31.2	23.3	0	350	Hori.	40.0	16.7	
55.311	50.7	QP	8.9	-31.2	28.4	277	100	Vert.	40.0	11.6	
72.026	53.4	QP	6.2	-31.2	28.4	91	248	Hori.	40.0	11.6	
72.026	48.9	QP	6.2	-31.2	23.9	56	100	Vert.	40.0	16.1	
133.630	34.2	QP	13.9	-30.3	17.8	89	271	Hori.	43.5	25.7	
133.630	39.7	QP	13.9	-30.3	23.3	148	100	Vert.	43.5	20.2	
239.994	47.1	QP	12.3	-29.0	30.4	84	100	Hori.	46.0	15.6	
239.999	40.3	QP	12.3	-29.0	23.6	41	168	Vert.	46.0	22.4	
249.700	47.9	QP	12.5	-28.8	31.6	278	119	Hori.	46.0	14.4	
249.700	42.4	QP	12.5	-28.8	26.1	20	255	Vert.	46.0	19.9	
639.132	31.8	QP	19.3	-25.5	25.6	122	400	Hori.	46.0	20.4	
639.132	40.1	QP	19.3	-25.5	33.9	0	100	Vert.	46.0	12.1	
749.992	37.6	QP	20.3	-24.9	33.0	62	221	Hori.	46.0	13.0	
749.992	35.2	QP	20.3	-24.9	30.6	0	100	Vert.	46.0	15.4	

CHART:WITH FACTOR ANT TYPE:-30MHz:LOOP, 30-300MHz:BICONICAL, 300MHz-1000MHz:LOGPERIODIC, 1000MHz-:HORN
CALCULATION:RESULT = READING + ANT FACTOR + LOSS(CABLE + ATTEN. - GAIN(AMP))

*The limit is rounded down to one decimal place.

*The test result is rounded off to one or two decimal places, so some differences might be observed.

Radiated Emission (Below 1GHz)

DATA OF RADIATED EMISSION TEST


UL Japan, Inc. Ise EMC Lab. No.1 Semi Anechoic Chamber
Date : 2016/04/08

Report No. : 11232756H

Temp./Humi. : 21deg. C. / 50%RH
Engineer : Shinya Watanabe

Mode / Remarks : Standby Mode

LIMIT : FCC15.109(a) 3m, below 1GHz:QP, above 1GHz:PK
Except for the data below : adequate margin data below the limits.



Frequency	Reading	DET	Antenna Factor	Loss& Gain	Level	Angle	Height	Polar.	Limit	Margin	Comment
[MHz]	[dBuV]		[dB/m]	[dB]	[dBuV/m]	[Deg]	[cm]		[dBuV/m]	[dB]	
55.892	45.2	QP	8.7	-31.2	22.7	126	329	Hori.	40.0	17.3	
55.892	49.1	QP	8.7	-31.2	26.6	273	100	Vert.	40.0	13.4	
72.027	53.6	QP	6.2	-31.2	28.6	97	244	Hori.	40.0	11.4	
72.027	49.4	QP	6.2	-31.2	24.4	47	174	Vert.	40.0	15.6	
132.990	36.5	QP	13.8	-30.3	20.0	245	265	Hori.	43.5	23.5	
132.990	34.0	QP	13.8	-30.3	17.5	77	100	Vert.	43.5	26.0	
175.750	32.2	QP	15.8	-29.8	18.2	100	400	Hori.	43.5	25.3	
175.750	34.5	QP	15.8	-29.8	20.5	0	100	Vert.	43.5	23.0	
240.080	48.1	QP	12.3	-29.0	31.4	107	121	Hori.	46.0	14.6	
240.307	40.6	QP	12.3	-29.0	23.9	46	157	Vert.	46.0	22.1	
250.000	45.8	QP	12.5	-28.8	29.5	276	124	Hori.	46.0	16.5	
250.000	42.9	QP	12.5	-28.8	26.6	21	215	Vert.	46.0	19.4	
639.091	37.7	QP	19.3	-25.5	31.5	140	141	Hori.	46.0	14.5	
639.091	38.2	QP	19.3	-25.5	32.0	0	100	Vert.	46.0	14.0	

CHART:WITH FACTOR ANT TYPE:-30MHz:LOOP, 30-300MHz:BICONICAL, 300MHz-1000MHz:LOGPERIODIC, 1000MHz-:HORN
CALCULATION:RESULT = READING + ANT FACTOR + LOSS(CABLE + ATTEN. - GAIN(AMP))

*The limit is rounded down to one decimal place.

*The test result is rounded off to one or two decimal places, so some differences might be observed.

Radiated Emission (Above 1GHz)

DATA OF RADIATED EMISSION TEST


UL Japan, Inc. Ise EMC Lab. No.1 Semi Anechoic Chamber
Date : 2016/04/08

Report No. : 11232756H

Temp./Humi. : 21deg. C. / 50%RH
Engineer : Shinya Watanabe

Mode / Remarks : USB Data Com Mode

LIMIT : FCC15.109(a) 3m, below 1GHz:QP, above 1GHz:PK
FCC15.109(a) 3m, below 1GHz:QP, above 1GHz:AV



Frequency	Reading	DET	Antenna Factor	Loss& Gain	Level	Angle	Height	Polar.	Limit	Margin	Comment
[MHz]	[dBuV]		[dB/m]	[dB]	[dBuV/m]	[Deg]	[cm]		[dBuV/m]	[dB]	
1596.100	50.7	PK	25.6	-33.0	43.3	169	100	Hori.	73.9	30.6	
1596.100	54.4	PK	25.6	-33.0	47.0	190	100	Vert.	73.9	26.9	
1596.100	34.5	AV	25.6	-33.0	27.1	169	100	Hori.	53.9	26.8	
1596.100	36.3	AV	25.6	-33.0	28.9	190	100	Vert.	53.9	25.0	

CHART:WITH FACTOR ANT TYPE:-30MHz:LOOP, 30-300MHz:BICONICAL, 300MHz-1000MHz:LOGPERIODIC, 1000MHz-:HORN
CALCULATION:RESULT = READING + ANT FACTOR + LOSS(CABLE + ATTEN. - GAIN(AMP))

*The limit is rounded down to one decimal place.

*The test result is rounded off to one or two decimal places, so some differences might be observed.

Radiated Emission (Above 1GHz)

DATA OF RADIATED EMISSION TEST


UL Japan, Inc. Ise EMC Lab. No.1 Semi Anechoic Chamber
Date : 2016/04/08

Report No. : 11232756H

Temp./Humi. : 21deg. C. / 50%RH
Engineer : Shinya Watanabe

Mode / Remarks : Standby Mode

LIMIT : FCC15.109(a) 3m, below 1GHz:QP, above 1GHz:PK
FCC15.109(a) 3m, below 1GHz:QP, above 1GHz:AV



Frequency	Reading	DET	Antenna Factor	Loss& Gain	Level	Angle	Height	Polar.	Limit	Margin	Comment
[MHz]	[dBuV]		[dB/m]	[dB]	[dBuV/m]	[Deg]	[cm]		[dBuV/m]	[dB]	
1596.100	51.2	PK	25.6	-33.0	43.8	163	100	Hori.	73.9	30.1	
1596.100	53.6	PK	25.6	-33.0	46.2	188	100	Vert.	73.9	27.7	
1596.100	34.3	AV	25.6	-33.0	26.9	163	100	Hori.	53.9	27.0	
1596.100	35.7	AV	25.6	-33.0	28.3	188	100	Vert.	53.9	25.6	

CHART:WITH FACTOR ANT TYPE:-30MHz:LOOP, 30-300MHz:BICONICAL, 300MHz-1000MHz:LOGPERIODIC, 1000MHz-:HORN
CALCULATION:RESULT = READING + ANT FACTOR + LOSS (CABLE + ATTEN. - GAIN(AMP) + D-factor)

*The limit is rounded down to one decimal place.

*The test result is rounded off to one or two decimal places, so some differences might be observed.

APPENDIX 2: Test instruments

EMI Test Instruments

Control No.	Instrument	Manufacturer	Model No	Serial No	Test Item	Calibration Date * Interval(month)
MAEC-01	Semi Anechoic Chamber(NSA)	TDK	Semi Anechoic Chamber 10m	DA-06881	RE/CE	2015/09/19 * 12
MOS-27	Thermo-Hygrometer	CUSTOM	CTH-201	A08Q26	RE/CE	2016/01/21 * 12
MJM-25	Measure	KOMELON	KMC-36	-	RE/CE	-
COTS-MEMI	EMI measurement program	TSJ	TEPTO-DV	-	RE/CE	-
MTR-09	EMI Test Receiver	Rohde & Schwarz	ESU26	100412	RE/CE	2015/06/08 * 12
KBA-05	Biconical Antenna	Schwarzbeck	BBA9106	2513	RE	2015/11/02 * 12
MLA-20	Logperiodic Antenna(200-1000MHz)	Schwarzbeck	VUSLP9111B	911B-189	RE	2016/01/30 * 12
MAT-08	Attenuator(6dB)	Weinschel Corp	2	BK7971	RE	2015/11/10 * 12
MCC-02	Coaxial Cable	Suhner/storm/Agilent/T SJ	-	-	RE	2015/09/29 * 12
MPA-19	Pre Amplifier	MITEQ	MLA-10K01-B01-35	1237616	RE	2016/02/25 * 12
MMM-03	Digital Tester	Fluke	FLUKE 26-3	78030621	RE/CE	2015/08/19 * 12
MHA-05	Horn Antenna 1-18GHz	Schwarzbeck	BBHA9120D	253	RE	2015/05/18 * 12
MCC-165	Microwave Cable	Junkosha	MWX221	1203S213(1m) / 1311S166(5m)	RE	2015/11/10 * 12
MPA-01	Pre Amplifier	Agilent	8449B	3008A01671	RE	2016/02/26 * 12
MLS-24	LISN(AMN)	Schwarzbeck	NSLK8127	8127-730	CE(EUT)	2015/07/10 * 12
MAT-64	Attenuator(13dB)	JFW Industries, Inc.	50FP-013H2 N	-	CE	2016/01/14 * 12
MLS-26	LISN(AMN)	Schwarzbeck	NSLK8127	8127-732	CE(AE)	2015/07/17 * 12
MTA-52	Terminator	TME	CT-01BP	-	CS	2015/12/01 * 12
MCC-03	Coaxial Cable	Fujikura/Suhner/TSJ	5D-2W(20m)/3D-2W(7.5m)/RG400u(1.5m)/RFM-E421(Switcher)	- /01068(Switcher)	CE	2015/09/29 * 12
MJG-52	Extension Tap EU	UL Japan			CE	-

The expiration date of the calibration is the end of the expired month.

All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or international standards.

As for some calibrations performed after the tested dates, those test equipment have been controlled by means of an unbroken chains of calibrations.

Test Item:

CE: Conducted Emissions

RE: Radiated Emissions

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124