



FCC RF Test Report

APPLICANT : SHARP CORPORATION, IoT Communication BU
EQUIPMENT : Smart Phone
FCC ID : APYHRO00245
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DSS) Spread Spectrum Transmitter

The product was received on Oct. 15, 2016 and testing was completed on Nov. 11, 2016. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.

SPORTON INTERNATIONAL INC.

TEL : 886-3-327-3456

FAX : 886-3-328-4978

FCC ID : APYHRO00245

Page Number : 1 of 68

Report Issued Date : Dec. 08, 2016

Report Version : Rev. 01

Report Template No.: BU5-FR15CBT Version 1.1



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1 GENERAL DESCRIPTION..... 5

 1.1 Applicant 5

 1.2 Manufacturer..... 5

 1.3 Product Feature of Equipment Under Test..... 5

 1.4 Product Specification of Equipment Under Test..... 6

 1.5 Modification of EUT 6

 1.6 Testing Location 7

 1.7 Applicable Standards..... 7

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST..... 8

 2.1 Descriptions of Test Mode 8

 2.2 Test Mode..... 9

 2.3 Connection Diagram of Test System..... 10

 2.4 Support Unit used in test configuration and system 11

 2.5 EUT Operation Test Setup 11

 2.6 Measurement Results Explanation Example..... 12

3 TEST RESULT 13

 3.1 Number of Channel Measurement 13

 3.2 Hopping Channel Separation Measurement 15

 3.3 Dwell Time Measurement..... 22

 3.4 20dB and 99% Bandwidth Measurement 24

 3.5 Peak Output Power Measurement 37

 3.6 Conducted Band Edges Measurement..... 39

 3.7 Conducted Spurious Emission Measurement 46

 3.8 Radiated Band Edges and Spurious Emission Measurement 56

 3.9 AC Conducted Emission Measurement..... 62

 3.10 Antenna Requirements..... 66

4 LIST OF MEASURING EQUIPMENT..... 67

5 UNCERTAINTY OF EVALUATION..... 68

APPENDIX A. RADIATED SPURIOUS EMISSION

APPENDIX B. RADIATED SPURIOUS EMISSION PLOTS

APPENDIX C. SETUP PHOTOGRAPHS



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(1)	Number of Channels	≥ 15 Chs	Pass	-
3.2	15.247(a)(1)	Hopping Channel Separation	$\geq 2/3$ of 20dB BW	Pass	-
3.3	15.247(a)(1)	Dwell Time of Each Channel	≤ 0.4 sec in 31.6sec period	Pass	-
3.4	15.247(a)(1)	20dB Bandwidth	NA	Pass	-
3.4	-	99% Bandwidth	-	Pass	-
3.5	15.247(b)(1)	Peak Output Power	≤ 125 mW	Pass	-
3.6	15.247(d)	Conducted Band Edges	≤ 20 dBc	Pass	-
3.7	15.247(d)	Conducted Spurious Emission	≤ 20 dBc	Pass	-
3.8	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 11.91 dB at 938.890 MHz
3.9	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 14.40 dB at 0.550 MHz
0	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

SHARP CORPORATION, IoT Communication BU

2-13-1, Hachihonmatsu-lida, Higashi-hiroshima-shi, Hiroshima pref. 739-0192, Japan

1.2 Manufacturer

SHARP CORPORATION, IoT Communication BU

2-13-1, Hachihonmatsu-lida, Higashi-hiroshima-shi, Hiroshima pref. 739-0192, Japan

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Smart Phone
FCC ID	APYHRO00245
Sample 1	eMMC Brand Name : Samsung
Sample 2	eMMC Brand Name : hynix
EUT supports Radios application	GSM/GPRS/WCDMA/HSPA/LTE/NFC WLAN 11b/g/n HT20 WLAN 11a/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE
HW Version	PP1
SW Version	CA240
EUT Stage	Identical Prototype

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. All tests were performed with sample 1.



1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	79
Carrier Frequency of Each Channel	2402+n*1 MHz; n=0~78
Maximum Output Power to Antenna	Bluetooth BR(1Mbps) : 5.32 dBm (0.0034 W) Bluetooth EDR (2Mbps) : 5.24 dBm (0.0033 W) Bluetooth EDR (3Mbps) : 5.69 dBm (0.0037 W)
99% Occupied Bandwidth	Bluetooth BR(1Mbps) : 0.904MHz Bluetooth EDR (2Mbps) : 1.168MHz Bluetooth EDR (3Mbps) : 1.160MHz
Antenna Type / Gain	ILA Antenna type with gain 0.00 dBi
Type of Modulation	Bluetooth BR (1Mbps) : GFSK Bluetooth EDR (2Mbps) : $\pi/4$ -DQPSK Bluetooth EDR (3Mbps) : 8-DPSK

1.5 Modification of EUT

No modifications are made to the EUT during all test items.



1.6 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1022 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	TH05-HY	CO05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.	
Test Site Location	No. 101, Complex Building C, Guanlong Village, Xili Town, Nanshan District, Shenzhen, Guangdong, P.R.C. TEL: +86-755-8637-9589	
Test Site No.	Sporton Site No. :	
	03CH03-SZ	

Note: The test site complies with ANSI C63.4 2014 requirement.

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Descriptions of Test Mode

Preliminary tests were performed in different data rates and recorded the RF output power in the following table:

Channel	Frequency	Bluetooth RF Output Power		
		Data Rate / Modulation		
		GFSK	$\pi/4$ -DQPSK	8-DPSK
		1Mbps	2Mbps	3Mbps
Ch00	2402MHz	4.36 dBm	4.19 dBm	4.50 dBm
Ch39	2441MHz	5.32 dBm	5.24 dBm	5.69 dBm
Ch78	2480MHz	3.50 dBm	3.25 dBm	3.64 dBm

Remark:

1. All the test data for each data rate were verified, but only the worst case was reported.
 2. The data rate was set in 3Mbps for all the test items due to the highest RF output power.
- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). Pre-scanned tests, X, Y, Z in three orthogonal panels, and different data rates were conducted to determine the final configuration (Z plane as worst plane) from all possible combinations, and the worst mode of radiated spurious emissions is Bluetooth 3Mbps mode, and recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.




2.2 Test Mode

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth BR 1Mbps GFSK	Bluetooth EDR 2Mbps $\pi/4$ -DQPSK	Bluetooth EDR 3Mbps 8-DPSK
Conducted Test Cases	Mode 1: CH00_2402 MHz	Mode 4: CH00_2402 MHz	Mode 7: CH00_2402 MHz
	Mode 2: CH39_2441 MHz	Mode 5: CH39_2441 MHz	Mode 8: CH39_2441 MHz
	Mode 3: CH78_2480 MHz	Mode 6: CH78_2480 MHz	Mode 9: CH78_2480 MHz
Radiated Test Cases	Bluetooth EDR 3Mbps 8-DPSK		
	Mode 1: CH00_2402 MHz		
	Mode 2: CH39_2441 MHz		
	Mode 3: CH78_2480 MHz		
AC Conducted Emission	Mode 1 :GSM850 Idle + Bluetooth Link + WLAN (2.4GHz) Link + Earphone + NFC On + USB Cable (Charging from Adapter)		
<p>Remark: For radiated test cases, the worst mode data rate 3Mbps was reported only, because this data rate has the highest RF output power at preliminary tests, and the conducted spurious emissions and conducted band edge measurement for each data rate are no worse than 3Mbps, and no other significantly frequencies found in conducted spurious emission.</p>			

2.3 Connection Diagram of Test System

<Bluetooth Tx Mode>



<AC Conducted Emission Mode>





2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
3.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
4.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
5.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A
6.	iPod Earphone	Apple	MC690ZP/A	Verification	Unshielded, 1.6 m	N/A
7.	USB Cable	SHARP(P1X accessory)	CUBB01M-FA00 2-DH	N/A	Shielded, 0.9m	N/A
8.	Earphone	SONY	SHLDL1	N/A	Unshielded, 1.5m	N/A
9.	Adapter	SHARP	DSA-10PFL-05 FUS 050200	N/A	N/A	N/A

2.5 EUT Operation Test Setup

For Bluetooth function, the RF utility, "Tera Term" was installed in EUT which was programmed in order to make the EUT get into the engineering modes for continuous transmitting and receiving signals.



2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$

3 Test Result

3.1 Number of Channel Measurement

3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation; RBW = 300kHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

3.1.4 Test Setup




3.1.5 Test Result of Number of Hopping Frequency

Test Mode :	3Mbps	Temperature :	24~26°C
Test Engineer :	AC Chang and Aking Chang	Relative Humidity :	48~51%


Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
79	20	> 15	Pass



Number of Hopping Channel Plot on Channel 00 - 78



Date: 6.NOV.2016 08:45:40



Date: 6.NOV.2016 08:50:29

3.2 Hopping Channel Separation Measurement

3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.2.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels;
RBW = 300kHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.2.4 Test Setup






3.2.5 Test Result of Hopping Channel Separation

Test Mode :	1Mbps	Temperature :	24~26°C
Test Engineer :	AC Chang and Aking Chang	Relative Humidity :	48~51%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	0.858	0.6187	Pass
39	2441	1.008	0.6187	Pass
78	2480	1.008	0.6107	Pass


Channel Separation Plot on Channel 00 - 01



Date: 6.NOV.2016 09:04:49




Channel Separation Plot on Channel 39 - 40



Date: 6.NOV.2016 09:09:59

Channel Separation Plot on Channel 77 - 78




Date: 6.NOV.2016 09:18:17



Test Mode :	2Mbps	Temperature :	24~26°C
Test Engineer :	AC Chang and Aking Chang	Relative Humidity :	48~51%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.008	0.8360	Pass
39	2441	1.002	0.8320	Pass
78	2480	1.020	0.8320	Pass


Channel Separation Plot on Channel 00 - 01



Date: 6.NOV.2016 09:29:37




Channel Separation Plot on Channel 39 - 40



Date: 6.NOV.2016 09:34:41

Channel Separation Plot on Channel 77 - 78




Date: 6.NOV.2016 09:37:13



Test Mode :	3Mbps	Temperature :	24~26°C
Test Engineer :	AC Chang and Aking Chang	Relative Humidity :	48~51%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.008	0.8160	Pass
39	2441	1.008	0.8160	Pass
78	2480	1.002	0.8160	Pass


Channel Separation Plot on Channel 00 - 01



Date: 6.NOV.2016 09:47:22




Channel Separation Plot on Channel 39 - 40



Date: 6.NOV.2016 09:50:56

Channel Separation Plot on Channel 77 - 78



Date: 6.NOV.2016 09:58:52

3.3 Dwell Time Measurement

3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.4.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW \geq RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.3.4 Test Setup





3.3.5 Test Result of Dwell Time


Test Mode :	DH5	Temperature :	24~26°C
Test Engineer :	AC Chang and Aking Chang	Relative Humidity :	48~51%

Mode	Hopping Channel Number	Hops Over Occupancy Time(hops)	Package Transfer Time (msec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Normal	79	106.67	2.90	0.31	0.4	Pass
AFH	20	53.33	2.90	0.15	0.4	Pass

Remark:

- In normal mode, hopping rate is 1600 hops/s with 6 slots in 79 hopping channels.
With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s),
Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops.
- In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels.
With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s),
Hops Over Occupancy Time comes to (800 / 6 / 20) x (0.4 x 20) = 53.33 hops.
- Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time

Package Transfer Time Plot



Date: 2.NOV.2016 17:07:59

3.4 20dB and 99% Bandwidth Measurement

3.4.1 Limit of 20dB and 99% Bandwidth

Reporting only


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 6.9.2 and 6.9.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.
Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;
RBW \geq 1% of the 20 dB bandwidth; VBW \geq RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
5. Use the following spectrum analyzer settings for 99 % Bandwidth measurement.
Span = approximately 1.5 to 5 times the 99% bandwidth, centered on a hopping channel;
RBW \geq 1% of the 99% bandwidth; VBW \geq RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
6. Measure and record the results in the test report.

3.4.4 Test Setup






3.4.5 Test Result of 20dB Bandwidth

Test Mode :	1Mbps	Temperature :	24~26°C
Test Engineer :	AC Chang and Aking Chang	Relative Humidity :	48~51%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	0.928
39	2441	0.928
78	2480	0.916


20 dB Bandwidth Plot on Channel 00



Date: 6.NOV.2016 09:02:46




20 dB Bandwidth Plot on Channel 39



Date: 6.NOV.2016 09:08:20

20 dB Bandwidth Plot on Channel 78




Date: 6.NOV.2016 09:16:24



Test Mode :	2Mbps	Temperature :	24~26°C
Test Engineer :	AC Chang and Aking Chang	Relative Humidity :	48~51%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.254
39	2441	1.248
78	2480	1.248


20 dB Bandwidth Plot on Channel 00



Date: 6.NOV.2016 09:26:44




20 dB Bandwidth Plot on Channel 39



Date: 6.NOV.2016 09:33:01

20 dB Bandwidth Plot on Channel 78




Date: 6.NOV.2016 09:40:49



Test Mode :	3Mbps	Temperature :	24~26°C
Test Engineer :	AC Chang and Aking Chang	Relative Humidity :	48~51%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.224
39	2441	1.224
78	2480	1.224


20 dB Bandwidth Plot on Channel 00



Date: 6.NOV.2016 09:45:42




20 dB Bandwidth Plot on Channel 39



Date: 6.NOV.2016 09:49:58

20 dB Bandwidth Plot on Channel 78



Date: 6.NOV.2016 10:02:05




3.4.6 Test Result of 99% Occupied Bandwidth

Test Mode :	1Mbps	Temperature :	24~26°C
Test Engineer :	AC Chang and Aking Chang	Relative Humidity :	48~51%

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
00	2402	0.904
39	2441	0.896
78	2480	0.896


99% Occupied Bandwidth Plot on Channel 00



Date: 6.NOV.2016 08:59:41




99% Occupied Bandwidth Plot on Channel 39



Date: 6.NOV.2016 09:06:51

99% Occupied Bandwidth Plot on Channel 78




Date: 6.NOV.2016 09:14:19



Test Mode :	2Mbps	Temperature :	24~26°C
Test Engineer :	AC Chang and Aking Chang	Relative Humidity :	48~51%

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
00	2402	1.168
39	2441	1.168
78	2480	1.168


99% Occupied Bandwidth Plot on Channel 00



Date: 6.NOV.2016 09:24:12




99% Occupied Bandwidth Plot on Channel 39



Date: 6.NOV.2016 09:31:30

99% Occupied Bandwidth Plot on Channel 78




Date: 6.NOV.2016 09:39:19



Test Mode :	3Mbps	Temperature :	24~26°C
Test Engineer :	AC Chang and Aking Chang	Relative Humidity :	48~51%

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
00	2402	1.160
39	2441	1.156
78	2480	1.160


99% Occupied Bandwidth Plot on Channel 00



Date: 6.NOV.2016 09:43:05




99% Occupied Bandwidth Plot on Channel 39



Date: 6.NOV.2016 09:48:59

99% Occupied Bandwidth Plot on Channel 78



Date: 6.NOV.2016 10:00:28

Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.5 Peak Output Power Measurement

3.5.1 Limit of Peak Output Power

Section 15.247 (b) The maximum peak conducted output power of the intentional radiator shall not exceed the following: (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts. The power limit for 1Mbps, 2Mbps, 3Mbps and AFH modes are 0.125 watts.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.5.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

3.5.4 Test Setup





3.5.5 Test Result of Peak Output Power

Test Mode :	1Mbps	Temperature :	24~26°C
Test Engineer :	AC Chang and Aking Chang	Relative Humidity :	48~51%

Channel	Frequency (MHz)	RF Power (dBm)		
		GFSK	Max. Limits (dBm)	Pass/Fail
		1 Mbps		
00	2402	4.36	20.97	Pass
39	2441	5.32	20.97	Pass
78	2480	3.50	20.97	Pass

Note: For AFH mode using 20 hopping channels, the maximum output power limit is 20.97dBm.

Test Mode :	2Mbps	Temperature :	24~26°C
Test Engineer :	AC Chang and Aking Chang	Relative Humidity :	48~51%

Channel	Frequency (MHz)	RF Power (dBm)		
		$\pi/4$ -DQPSK	Max. Limits (dBm)	Pass/Fail
		2 Mbps		
00	2402	4.19	20.97	Pass
39	2441	5.24	20.97	Pass
78	2480	3.25	20.97	Pass

Test Mode :	3Mbps	Temperature :	24~26°C
Test Engineer :	AC Chang and Aking Chang	Relative Humidity :	48~51%

Channel	Frequency (MHz)	RF Power (dBm)		
		8-DPSK	Max. Limits (dBm)	Pass/Fail
		3 Mbps		
00	2402	4.50	20.97	Pass
39	2441	5.69	20.97	Pass
78	2480	3.64	20.97	Pass

3.6 Conducted Band Edges Measurement

3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.6.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100kHz, VBW = 300kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2. and 3.
5. Measure and record the results in the test report.

3.6.4 Test Setup






3.6.5 Test Result of Conducted Band Edges


Test Mode :	1Mbps	Temperature :	24~26°C
Test Channel :	00 and 78	Relative Humidity :	48~51%
		Test Engineer :	AC Chang and Aking Chang

Low Band Edge Plot on Channel 00



Date: 6.NOV.2016 09:00:01

High Band Edge Plot on Channel 78




Date: 6.NOV.2016 09:14:43




Test Mode :	2Mbps	Temperature :	24~26°C
Test Channel :	00 and 78	Relative Humidity :	48~51%
		Test Engineer :	AC Chang and Aking Chang

Low Band Edge Plot on Channel 00



Date: 6.NOV.2016 09:25:25

High Band Edge Plot on Channel 78




Date: 6.NOV.2016 09:39:43




Test Mode :	3Mbps	Temperature :	24~26°C
Test Channel :	00 and 78	Relative Humidity :	48~51%
		Test Engineer :	AC Chang and Aking Chang

Low Band Edge Plot on Channel 00



Date: 6.NOV.2016 09:44:23

High Band Edge Plot on Channel 78




Date: 6.NOV.2016 10:00:50



3.6.6 Test Result of Conducted Hopping Mode Band Edges


Test Mode :	1Mbps	Temperature :	24~26°C
Test Engineer :	AC Chang and Aking Chang	Relative Humidity :	48~51%

1Mbps Hopping Mode Low Band Edge Plot



Date: 6.NOV.2016 09:22:07

1Mbps Hopping Mode High Band Edge Plot




Date: 6.NOV.2016 08:32:52




Test Mode :	2Mbps	Temperature :	24~26°C
Test Engineer :	AC Chang and Aking Chang	Relative Humidity :	48~51%

2Mbps Hopping Mode Low Band Edge Plot



Date: 6.NOV.2016 08:39:39

2Mbps Hopping Mode High Band Edge Plot




Date: 6.NOV.2016 08:37:54




Test Mode :	3Mbps	Temperature :	24~26°C
Test Engineer :	AC Chang and Aking Chang	Relative Humidity :	48~51%

3Mbps Hopping Mode Low Band Edge Plot



Date: 6.NOV.2016 08:54:05

3Mbps Hopping Mode High Band Edge Plot



Date: 6.NOV.2016 08:56:31

3.7 Conducted Spurious Emission Measurement

3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.8.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.7.4 Test Setup






3.7.5 Test Result of Conducted Spurious Emission


Test Mode :	1Mbps	Temperature :	24~26°C
Test Channel :	00	Relative Humidity :	48~51%
		Test Engineer :	AC Chang and Aking Chang

1Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 6.NOV.2016 08:58:32

1Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz




Date: 6.NOV.2016 08:58:53




Test Mode :	1Mbps	Temperature :	24~26°C
Test Channel :	39	Relative Humidity :	48~51%
		Test Engineer :	AC Chang and Aking Chang

1Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 6.NOV.2016 09:05:35

1Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz




Date: 6.NOV.2016 09:05:57




Test Mode :	1Mbps	Temperature :	24~26°C
Test Channel :	78	Relative Humidity :	48~51%
		Test Engineer :	AC Chang and Aking Chang

1Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 6.NOV.2016 09:13:01

1Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz




Date: 6.NOV.2016 09:13:23




Test Mode :	2Mbps	Temperature :	24~26°C
Test Channel :	00	Relative Humidity :	48~51%
		Test Engineer :	AC Chang and Aking Chang

2Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 6.NOV.2016 09:24:41

2Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz




Date: 6.NOV.2016 09:25:03




Test Mode :	2Mbps	Temperature :	24~26°C
Test Channel :	39	Relative Humidity :	48~51%
		Test Engineer :	AC Chang and Aking Chang

2Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 6.NOV.2016 09:30:30

2Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz




Date: 6.NOV.2016 09:30:52




Test Mode :	2Mbps	Temperature :	24~26°C
Test Channel :	78	Relative Humidity :	48~51%
		Test Engineer :	AC Chang and Aking Chang

2Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 6.NOV.2016 09:37:55

2Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz




Date: 6.NOV.2016 09:38:17




Test Mode :	3Mbps	Temperature :	24~26°C
Test Channel :	00	Relative Humidity :	48~51%
		Test Engineer :	AC Chang and Aking Chang

3Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 6.NOV.2016 09:43:32

3Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz




Date: 6.NOV.2016 09:43:53




Test Mode :	3Mbps	Temperature :	24~26°C
Test Channel :	39	Relative Humidity :	48~51%
		Test Engineer :	AC Chang and Aking Chang

3Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 6.NOV.2016 09:48:02

3Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz




Date: 6.NOV.2016 09:48:24




Test Mode :	3Mbps	Temperature :	24~26°C
Test Channel :	78	Relative Humidity :	48~51%
		Test Engineer :	AC Chang and Aking Chang

3Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 6.NOV.2016 09:59:33

3Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz



Date: 6.NOV.2016 09:59:55



3.8 Radiated Band Edges and Spurious Emission Measurement

3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




3.8.3 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1 \text{ GHz}$, RBW=1MHz for $f > 1\text{GHz}$; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
 - (3) For average measurement: use duty cycle correction factor method per 15.35(c).
Duty cycle = On time/100 milliseconds
On time = $N_1 * L_1 + N_2 * L_2 + \dots + N_{n-1} * L_{n-1} + N_n * L_n$
Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulses, etc.
Average Emission Level = Peak Emission Level + $20 * \log(\text{Duty cycle})$
6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level


Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.79dB) derived from $20 \log(\text{dwell time}/100\text{ms})$. This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

3.8.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz




3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.




3.8.6 Duty cycle correction factor for average measurement

3DH5 on time (One Pulse) Plot on Channel 39



3DH5 on time (Count Pulses) Plot on Channel 39



Note:

1. Worst case Duty cycle = on time/100 milliseconds = $2 * 2.88 / 100 = 5.76 \%$
2. Worst case Duty cycle correction factor = $20 * \log(\text{Duty cycle}) = -24.79 \text{ dB}$
3. 3DH5 has the highest duty cycle worst case and is reported.



Duty Cycle Correction Factor Consideration for AFH mode:

Bluetooth normal hopping rate is 1600Hz and reduced to 800Hz in AFH mode; due to the reduced number of hopping frequencies, with the same packet configuration the dwell time in each channel frequency within 100msec period is longer in AFH mode than normal mode.

In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time DH5 packet is observed; the period to have DH5 packet completing one hopping sequence is

$$2.88 \text{ ms} \times 20 \text{ channels} = 57.6 \text{ ms}$$

There cannot be 2 complete hopping sequences within 100ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period. $[100\text{ms} / 57.6\text{ms}] = 2 \text{ hops}$

Thus, the maximum possible ON time:

$$2.88 \text{ ms} \times 2 = 5.76 \text{ ms}$$

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

$$20 \times \log(5.76 \text{ ms}/100\text{ms}) = -24.79 \text{ dB}$$

3.8.7 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix A and B.

3.8.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix A and B.



3.9 AC Conducted Emission Measurement

3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBµV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.9.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.9.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


3.9.4 Test Setup





3.9.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	23~25°C
Test Engineer :	Arthur Hsieh	Relative Humidity :	50~52%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 Idle + Bluetooth Link + WLAN (2.4GHz) Link + Earphone + NFC On + USB Cable (Charging from Adapter)		



Final Result : Quasi-Peak


Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	41.3	Off	L1	19.6	24.7	66.0
0.182000	31.0	Off	L1	19.6	33.4	64.4
0.550000	37.7	Off	L1	19.6	18.3	56.0
0.590000	38.0	Off	L1	19.6	18.0	56.0
0.678000	31.9	Off	L1	19.6	24.1	56.0
13.558000	37.8	Off	L1	20.3	22.2	60.0
26.278000	32.7	Off	L1	21.0	27.3	60.0

Final Result : Average

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	22.2	Off	L1	19.6	33.8	56.0
0.182000	20.1	Off	L1	19.6	34.3	54.4
0.550000	31.6	Off	L1	19.6	14.4	46.0
0.590000	31.5	Off	L1	19.6	14.5	46.0
0.678000	26.1	Off	L1	19.6	19.9	46.0
13.558000	31.5	Off	L1	20.3	18.5	50.0
26.278000	23.6	Off	L1	21.0	26.4	50.0



Test Mode :	Mode 1	Temperature :	23~25°C
Test Engineer :	Arthur Hsieh	Relative Humidity :	50~52%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + Bluetooth Link + WLAN (2.4GHz) Link + Earphone + NFC On + USB Cable (Charging from Adapter)		



Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	46.7	Off	N	19.6	19.3	66.0
0.182000	36.5	Off	N	19.6	27.9	64.4
0.582000	32.8	Off	N	19.6	23.2	56.0
7.734000	27.0	Off	N	20.0	33.0	60.0
13.558000	31.5	Off	N	20.4	28.5	60.0
20.718000	33.5	Off	N	20.8	26.5	60.0
25.302000	42.0	Off	N	21.1	18.0	60.0

Final Result : Average

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	24.0	Off	N	19.6	32.0	56.0
0.182000	21.0	Off	N	19.6	33.4	54.4
0.582000	22.6	Off	N	19.6	23.4	46.0
7.734000	19.5	Off	N	20.0	30.5	50.0
13.558000	23.7	Off	N	20.4	26.3	50.0
20.718000	23.0	Off	N	20.8	27.0	50.0
25.302000	27.6	Off	N	21.1	22.4	50.0



3.10 Antenna Requirements

3.10.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.10.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.10.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Agilent	E4416A	GB41292344	300MHz~40GHz	Jan. 08, 2016	Nov. 02, 2016 ~ Nov. 06, 2016	Jan. 07, 2017	Conducted (TH05-HY)
Power Sensor	Agilent	E9327A	US40441548	300MHz~40GHz	Jan. 07, 2016	Nov. 02, 2016 ~ Nov. 06, 2016	Jan. 06, 2017	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100057	9kHz-40GHz	Nov. 23, 2015	Nov. 02, 2016 ~ Nov. 06, 2016	Nov. 22, 2016	Conducted (TH05-HY)
Programmable Power Supply	GW Instek	PSS-2005	GEO821763	N/A	Nov. 13, 2015	Nov. 02, 2016 ~ Nov. 06, 2016	Nov. 12, 2016	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Nov. 08, 2016	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESCI 7	100724	9kHz~7GHz	Aug. 30, 2016	Nov. 08, 2016	Aug. 29, 2017	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Dec. 02, 2015	Nov. 08, 2016	Dec. 01, 2016	Conduction (CO05-HY)
EMI Test Receiver&SA	KEYSIGHT	N9038A	MY54450083	20Hz~8.4GHz	May 07, 2016	Nov. 05, 2016 ~ Nov. 11, 2016	May 06, 2017	Radiation (03CH03-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150246	10Hz~44GHz;	May 07, 2016	Nov. 05, 2016 ~ Nov. 11, 2016	May 06, 2017	Radiation (03CH03-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	May 07, 2016	Nov. 05, 2016 ~ Nov. 11, 2016	May 06, 2017	Radiation (03CH03-SZ)
Bilog Antenna	TeseQ	CBL6112D	35408	30MHz-2GHz	May 21, 2016	Nov. 05, 2016 ~ Nov. 11, 2016	May 20, 2017	Radiation (03CH03-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-1355	1GHz~18GHz	May 07, 2016	Nov. 05, 2016 ~ Nov. 11, 2016	May 06, 2017	Radiation (03CH03-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz	Jul. 16, 2016	Nov. 05, 2016 ~ Nov. 11, 2016	Jul. 15, 2017	Radiation (03CH03-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18GHz-40GHz	Aug. 10, 2016	Nov. 05, 2016 ~ Nov. 11, 2016	Aug. 09, 2017	Radiation (03CH03-SZ)
Amplifier	Burgeon	BPA-530	102210	0.01Hz~3000MHz	Oct. 11, 2016	Nov. 05, 2016 ~ Nov. 11, 2016	Oct. 10, 2017	Radiation (03CH03-SZ)
HF Amplifier	MITEQ	AMF-7D-00101800-30-10P-R	1943528	1GHz~18GHz	Oct. 11, 2016	Nov. 05, 2016 ~ Nov. 11, 2016	Oct. 10, 2017	Radiation (03CH03-SZ)
Amplifier	Agilent Technologies	83017A	MY39501302	500MHz~26.5GHz	Jan. 12, 2016	Nov. 05, 2016 ~ Nov. 11, 2016	Jan. 11, 2017	Radiation (03CH03-SZ)
AC Power Source	Chroma	61601	616010001985	N/A	N/A	Nov. 05, 2016 ~ Nov. 11, 2016	N/A	Radiation (03CH03-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	N/A	Nov. 05, 2016 ~ Nov. 11, 2016	N/A	Radiation (03CH03-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	N/A	Nov. 05, 2016 ~ Nov. 11, 2016	N/A	Radiation (03CH03-SZ)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.7
---	-----

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.1
---	-----

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0
---	-----

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0
---	-----



Appendix A. Radiated Spurious Emission

Test Engineer :	Jeff Yao	Temperature :	23~25°C
		Relative Humidity :	48~52%

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
BT CH00 2402MHz		2340.55	39.9	-34.1	74	42.94	27.19	4.82	35.05	222	148	P	H	
		2340.55	15.11	-38.89	54	-	-	-	-	-	-	A	H	
	*	2402	96.61	-	-	99.46	27.29	4.86	35	222	148	P	H	
	*	2402	71.82	-	-	-	-	-	-	-	-	A	H	
													H	
														H
			2389.04	40.73	-33.27	74	43.6	27.29	4.86	35.02	185	133	P	V
			2389.04	15.94	-38.06	54	-	-	-	-	-	-	A	V
	*		2402	97.82	-	-	100.67	27.29	4.86	35	185	133	P	V
	*		2402	73.03	-	-	-	-	-	-	-	-	A	V
														V
														V
BT CH 39 2441MHz		2352.37	40.28	-33.72	74	43.29	27.22	4.82	35.05	221	146	P	H	
		2352.37	15.49	-38.51	54	-	-	-	-	-	-	A	H	
	*	2441	98.07	-	-	100.74	27.4	4.88	34.95	221	146	P	H	
	*	2441	73.28	-	-	-	-	-	-	-	-	A	H	
			2488.98	39.83	-34.17	74	42.33	27.5	4.92	34.92	221	146	P	H
			2488.98	15.04	-38.96	54	-	-	-	-	-	-	A	H
			2356.36	41.56	-32.44	74	44.57	27.22	4.82	35.05	181	126	P	V
			2356.36	16.77	-37.23	54	-	-	-	-	-	-	A	V
	*		2441	99.07	-	-	101.74	27.4	4.88	34.95	181	126	P	V
	*		2441	74.28	-	-	-	-	-	-	-	-	A	V
			2493.73	41.29	-32.71	74	43.77	27.5	4.92	34.9	181	126	P	V
			2493.73	16.5	-37.5	54	-	-	-	-	-	-	A	V



BT	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
BT CH 78 2480MHz	*	2480	94.51	-	-	97.06	27.47	4.9	34.92	250	136	P	H	
	*	2480	69.72	-	-	-	-	-	-	-	-	A	H	
		2483.69	42.13	-31.87	74	44.68	27.47	4.9	34.92	250	136	P	H	
		2483.69	17.34	-36.66	54	-	-	-	-	-	-	A	H	
													H	
													H	
	*	2480	94.71	-	-	97.26	27.47	4.9	34.92	208	134	P	V	
	*	2480	69.92	-	-	-	-	-	-	-	-	-	A	V
		2483.5	42.5	-31.5	74	45.05	27.47	4.9	34.92	208	134	P	V	
		2483.5	17.71	-36.29	54	-	-	-	-	-	-	A	V	
													V	
													V	
	Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BT (Harmonic @ 3m)

BT	Note	Frequency (MHz)	Level (dB μ V/m)	Over Limit (dB)	Limit Line (dB μ V/m)	Read Level (dB μ V)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
BT CH 00 2402MHz		4804	42.23	-31.77	74	61.05	32.52	6.96	58.3	151	219	P	H	
		4804	17.44	-36.56	54	-	-	-	-	-	-	A	H	
													H	
													H	
		4804	42.49	-31.51	74	61.31	32.52	6.96	58.3	151	219	P	V	
		4804	17.7	-36.3	54	-	-	-	-	-	-	-	A	V
														V
														V
BT CH 39 2441MHz		4882	41.12	-32.88	74	60.13	32.66	6.99	58.66	150	258	P	H	
		4882	16.33	-37.67	54	-	-	-	-	-	-	A	H	
		7323	48.16	-25.84	74	60.16	37.67	8.93	58.6	152	309	P	H	
		7323	23.37	-30.63	54	-	-	-	-	-	-	A	H	
		4882	41.39	-32.61	74	60.4	32.66	6.99	58.66	150	258	P	V	
		4882	16.6	-37.4	54	-	-	-	-	-	-	A	V	
		7323	48.42	-25.58	74	60.42	37.67	8.93	58.6	152	309	P	V	
		7323	23.63	-30.37	54	-	-	-	-	-	-	A	V	
BT CH 78 2480MHz		4960	41.9	-32.1	74	60.3	32.83	7.07	58.3	118	289	P	H	
		4960	17.11	-36.89	54	-	-	-	-	-	-	A	H	
		7440	48.09	-25.91	74	59.7	37.69	9.15	58.45	158	273	P	H	
		7440	23.3	-30.7	54	-	-	-	-	-	-	A	H	
		4960	41.01	-32.99	74	59.41	32.83	7.07	58.3	118	289	P	V	
		4960	16.22	-37.78	54	-	-	-	-	-	-	A	V	
		7440	47.53	-26.47	74	59.14	37.69	9.15	58.45	158	273	P	V	
		7440	22.74	-31.26	54	-	-	-	-	-	-	A	V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.													



Emission below 1GHz

2.4GHz BT (LF)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)	
2.4GHz BT LF		30	25.96	-14.04	40	31.62	26.7	1	33.36	-	-	P	H	
		83.35	20.18	-19.82	40	36.15	16.28	1.14	33.39	-	-	P	H	
		291.9	20.01	-25.99	46	32.19	18.93	1.94	33.05	-	-	P	H	
		410.24	27.13	-18.87	46	31.88	25.77	2.22	32.74	-	-	P	H	
		626.55	28.87	-17.13	46	33.09	25.21	2.64	32.07	-	-	P	H	
		831.22	32.08	-13.92	46	32.73	27.84	2.99	31.48	140	80	P	H	
														H
														H
														H
														H
														H
														H
														H
			30	26.16	-13.84	40	31.82	26.7	1	33.36	-	-	P	V
			111.48	19.31	-24.19	43.5	32.7	18.57	1.38	33.34	-	-	P	V
			219.15	17.81	-28.19	46	32.63	16.52	1.8	33.14	-	-	P	V
			401.51	26.89	-19.11	46	31.58	25.96	2.12	32.77	-	-	P	V
			590.66	28.63	-17.37	46	33.14	25.08	2.57	32.16	-	-	P	V
			938.89	34.09	-11.91	46	32.84	29.21	3.15	31.11	180	120	P	V
														V
													V	
													V	
													V	
													V	
													V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.													



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

- Level(dBμV/m) =
Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
- Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

- Level(dBμV/m)
= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)
= 55.45 (dBμV/m)
- Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 55.45(dBμV/m) – 74(dBμV/m)
= -18.55(dB)

For Average Limit @ 2390MHz:

- Level(dBμV/m)
= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)
= 43.54 (dBμV/m)
- Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 43.54(dBμV/m) – 54(dBμV/m)
= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix B. Radiated Spurious Emission Plots

Test Engineer :	Jeff Yao	Temperature :	23~25°C
		Relative Humidity :	48~52%

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH00 2402MHz	
1	Horizontal	Fundamental
Peak	<p>Site : 03CH03-SZ Condition : FCC CLASS-B 3m HF_ANT_160507 HORIZONTAL Detector : Peak Project : (FR) 601512 Mode : Mode 1 Sample : #20 Plane : 2 (Single) 指内 : 3HD5</p>	<p>Site : 03CH03-SZ Condition : FCC CLASS-B 3m HF_ANT_160507 HORIZONTAL Detector : Peak Project : (FR) 601512 Mode : Mode 1 Sample : #20 Plane : 2 (Single) 指内 : 3HD5</p>



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH00 2402MHz	
1	Vertical	Fundamental
Peak	<p>No. 3 Building, the third floor of south, Shahe River west, Fengqiyuan warehouse, NanshanDistrict, Shenzhen, Guangdong, china</p> <p>Date: 2016-11-07</p> <p>Site : 03CH03-SZ Condition : FCC CLASS-B 3m HF_ANT_160507 VERTICAL Detector : Peak Project : (FR) 601512 Mode : Mode 1 Sample : 400 Plane : Z (Single) 指向 : 3HDS</p>	<p>No. 3 Building, the third floor of south, Shahe River west, Fengqiyuan warehouse, NanshanDistrict, Shenzhen, Guangdong, china</p> <p>Date: 2016-11-07</p> <p>Site : 03CH03-SZ Condition : FCC CLASS-B 3m HF_ANT_160507 VERTICAL Detector : Peak Project : (FR) 601512 Mode : Mode 1 Sample : 400 Plane : Z (Single) 指向 : 3HDS</p>



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH39 2441MHz	
1	Horizontal	Fundamental
Peak	<p>No. 3 Building, the third floor of south, Shahe River west, Fengze Yuan warehouse, Nanshan District, Shenzhen, Guangdong, China</p> <p>Date: 2016-11-07</p> <p>Site : 03CH03-SZ Condition : FCC CLASS-B 3m HF_ANT_160507 HORIZONTAL Detector : Peak Project : (FR) 601512 Mode : Mode 2 Sample : #20 Plane : Z (Single) 指向 : 3HDS</p>	<p>No. 3 Building, the third floor of south, Shahe River west, Fengze Yuan warehouse, Nanshan District, Shenzhen, Guangdong, China</p> <p>Date: 2016-11-07</p> <p>Site : 03CH03-SZ Condition : FCC CLASS-B 3m HF_ANT_160507 HORIZONTAL Detector : Peak Project : (FR) 601512 Mode : Mode 2 Sample : #20 Plane : Z (Single) 指向 : 3HDS</p>





BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH39 2441MHz	
1	Vertical	Fundamental
Peak	<p>No. 3 Building, the third floor of south, Shahe River west, Fengqiyuan warehouse, NanshanDistrict, Shenzhen, Guangdong, china</p> <p>Date: 2016-11-07</p> <p>Site : 03CH03-SZ Condition : FCC CLASS-B 3m HF_ANT_160507 VERTICAL Detector : Peak Project : (FR) 601512 Mode : Mode 2 Sample : #20 Plane : Z (Single) 指向 : 3HDS</p>	<p>No. 3 Building, the third floor of south, Shahe River west, Fengqiyuan warehouse, NanshanDistrict, Shenzhen, Guangdong, china</p> <p>Date: 2016-11-07</p> <p>Site : 03CH03-SZ Condition : FCC CLASS-B 3m HF_ANT_160507 VERTICAL Detector : Peak Project : (FR) 601512 Mode : Mode 2 Sample : #20 Plane : Z (Single) 指向 : 3HDS</p>



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH78 2480MHZ	
1	Horizontal	Fundamental
Peak	<p style="text-align: right; font-size: small;">No. 3 Building, the third floor of south, Shahe River west, Fengze Yuan warehouse, Nanshan District, Shenzhen, Guangdong, China</p> <p style="font-size: x-small;">Data: 2 Date: 2016-11-07</p> <p style="font-size: x-small;">Site : 03CH03-SZ Condition : FCC CLASS-B 3m HF_ANT_160507 HORIZONTAL Detector : Peak Project : (FR) 601512 Mode : Mode 3 Sample : #20 Plane : Z (Single) 指向 : 3HDS</p>	<p style="text-align: right; font-size: small;">No. 3 Building, the third floor of south, Shahe River west, Fengze Yuan warehouse, Nanshan District, Shenzhen, Guangdong, China</p> <p style="font-size: x-small;">Data: 1 Date: 2016-11-07</p> <p style="font-size: x-small;">Site : 03CH03-SZ Condition : FCC CLASS-B 3m HF_ANT_160507 HORIZONTAL Detector : Peak Project : (FR) 601512 Mode : Mode 3 Sample : #20 Plane : Z (Single) 指向 : 3HDS</p>



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH78 2480MHZ	
1	Vertical	Fundamental
Peak	 <p>No. 3 Building, the third floor of south, Shihe River west, Fengze Yuan warehouse, Nanshan District, Shenzhen, Guangdong, China</p> <p>Date: 2016-11-07</p> <p>Site : 03CH03-SZ Condition : FCC CLASS-B 3m HF_ANT_160507 VERTICAL Detector : Peak Project : (FR) 601512 Mode : Mode 3 Sample : #20 Plane : Z (Single) 指向 : 3HDS</p>	 <p>No. 3 Building, the third floor of south, Shihe River west, Fengze Yuan warehouse, Nanshan District, Shenzhen, Guangdong, China</p> <p>Date: 2016-11-11</p> <p>Site : 03CH03-SZ Condition : FCC CLASS-B 3m HF_ANT_160507 VERTICAL Detector : Peak Project : (FR) 601512 Mode : Mode 3 Sample : #20 Plane : Z (Single) 指向 : 3HDS</p>



2.4GHz 2400~2483.5MHz

BT (Harmonic @ 3m)

BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BT CH00 2402MHz	
1	Horizontal	Vertical
Peak Avg.	<p>No. 3 Building, the third floor of south, Shahe River west, Fengqiyuan warehouse, NanshanDistrict, Shenzhen, Guangdong, china</p> <p>Date: 19 Date: 2016-11-05</p> <p>Site : 03CH03-SZ Condition : FCC CLASS-B 3m HF_ANT_160507 HORIZONTAL Detector : Peak Project : (FR) 601512 Mode : Mode 1 Sample : #20 Plane : Z (Single) 指向 : 3H2c</p>	<p>No. 3 Building, the third floor of south, Shahe River west, Fengqiyuan warehouse, NanshanDistrict, Shenzhen, Guangdong, china</p> <p>Date: 20 Date: 2016-11-05</p> <p>Site : 03CH03-SZ Condition : FCC CLASS-B 3m HF_ANT_160507 VERTICAL Detector : Peak Project : (FR) 601512 Mode : Mode 1 Sample : #20 Plane : Z (Single) 指向 : 3H2c</p>



BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BT CH39 2441MHz	
1	Horizontal	Vertical
<p>Peak Avg.</p>	<p style="font-size: small;"> No. 3 Building, the third floor of south, Shehe River west, Fengze Yuan warehouse, NanShanDistrict, Shenzhen, Guangdong, china </p> <p style="font-size: x-small;"> Date: 19 Level (dBuV/m) Date: 2016-11-05 Site : 03CH03-SZ Condition : FCC CLASS-B 3m HF_ANT_160507 HORIZONTAL Detector : Peak Project : (FR) 601512 Mode : Mode 2 Sample : #20 Plane : 2, (Single) 指内 : 3HDS </p>	<p style="font-size: small;"> No. 3 Building, the third floor of south, Shehe River west, Fengze Yuan warehouse, NanShanDistrict, Shenzhen, Guangdong, china </p> <p style="font-size: x-small;"> Date: 20 Level (dBuV/m) Date: 2016-11-05 Site : 03CH03-SZ Condition : FCC CLASS-B 3m HF_ANT_160507 VERTICAL Detector : Peak Project : (FR) 601512 Mode : Mode 2 Sample : #20 Plane : 2, (Single) 指内 : 3HDS </p>





BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BT CH78 2480MHZ	
1	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH03-SZ Condition : FCC CLASS-B 3m HF_ANT_160507 HORIZONTAL Detector : Peak Project : (FR) 601512 Mode : Mode 3 Sample : #20 Plane : Z (Single) 指向 : 3HDS</p>	<p>Site : 03CH03-SZ Condition : FCC CLASS-B 3m HF_ANT_160507 VERTICAL Detector : Peak Project : (FR) 601512 Mode : Mode 3 Sample : #20 Plane : Z (Single) 指向 : 3HDS</p>



Emission below 1GHz

2.4GHz BT (LF)

BT	2.4GHz 2400~2483.5MHz	
ANT	BT LF	
1	Horizontal	Vertical
QP / Peak	 <p>No. 3 Building, the third floor of south, Shahe River west, Fengqiyuan warehouse, NanshanDistrict, Shenzhen, Guangdong, china</p> <p>Date: 2016-11-07</p> <p>Site : 03CH03-SZ Condition : FCC CLASS-B 3m LF35408CBL6112D_6 HORIZONTAL Detector : Peak Project : (FR) 601512 Mode : Mode 2 Sample : #20 Plane : Z (Single) 指向 : 3HDS</p>	 <p>No. 3 Building, the third floor of south, Shahe River west, Fengqiyuan warehouse, NanshanDistrict, Shenzhen, Guangdong, china</p> <p>Date: 2016-11-07</p> <p>Site : 03CH03-SZ Condition : FCC CLASS-B 3m LF35408CBL6112D_6 VERTICAL Detector : Peak Project : (FR) 601512 Mode : Mode 2 Sample : #20 Plane : Z (Single) 指向 : 3HDS</p>