



FCC RF Test Report

APPLICANT : SHARP CORPORATION, IoT Communication BU
EQUIPMENT : Smart Phone
BRAND NAME : NTT docomo
MODEL NAME : SH-03J
FCC ID : APYHRO00248
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The product was received on Apr. 01, 2017 and testing was completed on Apr. 29, 2017. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.

SPORTON INTERNATIONAL INC.

TEL : 886-3-327-3456

FAX : 886-3-328-4978

FCC ID : APYHRO00248

Page Number : 1 of 51

Report Issued Date : Jun. 02, 2017

Report Version : Rev. 01

Report Template No.: BU5-FR15CWLAC MA Version 2.0



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1 GENERAL DESCRIPTION 5

 1.1 Applicant 5

 1.2 Manufacturer 5

 1.3 Product Feature of Equipment Under Test..... 5

 1.4 Modification of EUT 5

 1.5 Testing Location 6

 1.6 Applicable Standards 7

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST 8

 2.1 Carrier Frequency and Channel 8

 2.2 Test Mode 9

 2.3 Connection Diagram of Test System 10

 2.4 Support Unit used in test configuration and system 10

 2.5 EUT Operation Test Setup 11

 2.6 Measurement Results Explanation Example 11

3 TEST RESULT 12

 3.1 6dB and 99% Bandwidth Measurement 12

 3.2 Peak Output Power Measurement 14

 3.3 Power Spectral Density Measurement 15

 3.4 Conducted Band Edges and Spurious Emission Measurement 18

 3.5 Radiated Band Edges and Spurious Emission Measurement 43

 3.6 AC Conducted Emission Measurement 47

 3.7 Antenna Requirements 49

4 LIST OF MEASURING EQUIPMENT 50

5 UNCERTAINTY OF EVALUATION 51

APPENDIX A. CONDUCTED TEST RESULTS

APPENDIX B. AC CONDUCTED EMISSION TEST RESULT

APPENDIX C. RADIATED SPURIOUS EMISSION

APPENDIX D. RADIATED SPURIOUS EMISSION PLOTS

APPENDIX E. DUTY CYCLE PLOTS

APPENDIX F. SETUP PHOTOGRAPHS



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.1	-	99% Bandwidth	-	Pass	-
3.2	15.247(b)	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 8.76 dB at 2389.520 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 17.40 dB at 0.502 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

SHARP CORPORATION, IoT Communication BU

2-13-1, Hachihonmatsu-lida, Higashi-hiroshima-shi, Hiroshima pref. 739-0192, Japan

1.2 Manufacturer

SHARP CORPORATION, IoT Communication BU

2-13-1, Hachihonmatsu-lida, Higashi-hiroshima-shi, Hiroshima pref. 739-0192, Japan

1.3 Product Feature of Equipment Under Test

GSM/WCDMA/LTE, Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n/ac, Wi-Fi 5GHz 802.11a/n/ac, NFC, and GPS

Product Specification subjective to this standard	
Sample 1	EUT with Memory 1
Sample 2	EUT with Memory 2
Antenna Type	WWAN: ILA Antenna WLAN: ILA Antenna Bluetooth: ILA Antenna GPS/Glonass/Beidou/Galileo: ILA Antenna NFC: Loop Antenna

1.4 Modification of EUT

No modifications are made to the EUT during all test items.



1.5 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW0007 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	TH05-HY	CO05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd Rd. Guishan Dist, Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
Test Site No.	Sporton Site No.	
	03CH10-HY	

Note: The test site complies with ANSI C63.4 2014 requirement.



1.6 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ FCC KDB 644545 D03 Guidance for IEEE 802 11ac New Rules v01
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437		



2.2 Test Mode

Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates as below table.

Single Antenna


Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT20	MCS0
802.11ac VHT40	MCS0

MIMO Antenna

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT20	MCS0
802.11ac VHT40	MCS0

Test Cases	
AC Conducted Emission	Mode 1 :GSM1900 Idle + Bluetooth Link + WLAN (2.4GHz) Link + Earphone + USB Cable (Charging from Adapter) + Camera (Rear) for Sample 1
Remark: For Radiated Test Cases, The tests were performance with Sample 1.	

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
3.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
4.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
5.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A



2.5 EUT Operation Test Setup

The RF test items, programmed RF utility, "Tera Term" installed in the notebook make the EUT provide functions like channel selection and power level for continuous transmitting and receiving signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) = 1MHz and set the Video bandwidth (VBW) = 3MHz.
6. Measure and record the results in the test report.


3.1.4 Test Setup





3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A.



Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Peak Output Power Measurement

3.2.1 Limit of Peak Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna with directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v04 section 9.1.2 PKPM1 Peak power meter method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.
5. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average output Power (Reporting Only)

Please refer to Appendix A.



3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.


If measurements performed using method (2) plus $10 \log(N)$ exceeds the emission limit, the test should choose method (1) before declaring that the device fails the emission limit.

Method (1): Measure and sum the spectra across the outputs.

The total final Power Spectral Density is from a device with 2 transmitter outputs. The spectrum measurements of the individual outputs are all performed with the same span and number of points, the spectrum value in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 to obtain the value for the first frequency bin of the summed spectrum.



Method (2): Measure and add $10 \log(N)$ dB, where N is the number of outputs. (N=2)

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup






3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Number of TX = 2, Ant. 1 (Measured)

Number of TX	2	Ant. :	1
Test Mode :	802.11b	Temperature :	21~25°C
Test Band :	2.4GHz Low	Relative Humidity :	51~54%
Test Channel :	01	Test Engineer :	Allen Lin




Number of TX :	2	Ant. :	1
----------------	---	--------	---



Test Mode :	802.11b	Temperature :	21~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	51~54%
Test Channel :	06	Test Engineer :	Allen Lin


WLAN 802.11b Channel 06

100kHz PSD reference Level




Date: 22.APR.2017 13:53:11

Spurious Emission 30MHz~3GHz



Date: 22.APR.2017 13:53:22

Spurious Emission 2GHz~25GHz



Date: 22.APR.2017 13:53:31



Number of TX :	2	Ant. :	1
Test Mode :	802.11b	Temperature :	21~25°C
Test Band :	2.4GHz High	Relative Humidity :	51~54%
Test Channel :	11	Test Engineer :	Allen Lin


WLAN 802.11b Channel 11

100kHz PSD reference Level




Date: 22.APR.2017 13:57:17

High Channel Plot




Date: 22.APR.2017 13:57:29

Spurious Emission 30MHz~3GHz



Date: 22.APR.2017 13:57:41

Spurious Emission 2GHz~25GHz




Date: 22.APR.2017 13:57:49




Number of TX :	2	Ant. :	1
Test Mode :	802.11g	Temperature :	21~25°C
Test Band :	2.4GHz Low	Relative Humidity :	51~54%
Test Channel :	01	Test Engineer :	Allen Lin

WLAN 802.11g Channel 01


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Number of TX :	2	Ant. :	1
Test Mode :	802.11g	Temperature :	21~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	51~54%
Test Channel :	06	Test Engineer :	Allen Lin

WLAN 802.11g Channel 06


100kHz PSD reference Level



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Number of TX :	2	Ant. :	1
Test Mode :	802.11g	Temperature :	21~25°C
Test Band :	2.4GHz High	Relative Humidity :	51~54%
Test Channel :	11	Test Engineer :	Allen Lin

WLAN 802.11g Channel 11


100kHz PSD reference Level




High Channel Plot



Spurious Emission 30MHz~3GHz




Spurious Emission 2GHz~25GHz





Number of TX :	2	Ant. :	1
Test Mode :	802.11n HT20	Temperature :	21~25°C
Test Band :	2.4GHz Low	Relative Humidity :	51~54%
Test Channel :	01	Test Engineer :	Allen Lin







Number of TX :	2	Ant. :	1
Test Mode :	802.11n HT20	Temperature :	21~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	51~54%
Test Channel :	06	Test Engineer :	Allen Lin

WLAN 802.11n HT20 Channel 06


100kHz PSD reference Level



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Number of TX :	2	Ant. :	1
Test Mode :	802.11n HT20	Temperature :	21~25°C
Test Band :	2.4GHz High	Relative Humidity :	51~54%
Test Channel :	11	Test Engineer :	Allen Lin

WLAN 802.11n HT20 Channel 11


100kHz PSD reference Level




High Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Number of TX :	2	Ant. :	1
Test Mode :	802.11n HT40	Temperature :	21~25°C
Test Band :	2.4GHz Low	Relative Humidity :	51~54%
Test Channel :	03	Test Engineer :	Allen Lin

WLAN 802.11n HT40 Channel 03


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Number of TX :	2	Ant. :	1
Test Mode :	802.11n HT40	Temperature :	21~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	51~54%
Test Channel :	06	Test Engineer :	Allen Lin

WLAN 802.11n HT40 Channel 06


100kHz PSD reference Level



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Number of TX :	2	Ant. :	1
Test Mode :	802.11n HT40	Temperature :	21~25°C
Test Band :	2.4GHz High	Relative Humidity :	51~54%
Test Channel :	09	Test Engineer :	Allen Lin

WLAN 802.11n HT40 Channel 09


100kHz PSD reference Level




High Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz






Number of TX = 2, Ant. 2 (Measured)


Number of TX :	2	Ant. :	2
Test Mode :	802.11b	Temperature :	21~25°C
Test Band :	2.4GHz Low	Relative Humidity :	51~54%
Test Channel :	01	Test Engineer :	Allen Lin

WLAN 802.11b Channel 01


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz






Number of TX :	2	Ant. :	2
Test Mode :	802.11b	Temperature :	21~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	51~54%
Test Channel :	06	Test Engineer :	Allen Lin

WLAN 802.11b Channel 06


100kHz PSD reference Level



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Number of TX :	2	Ant. :	2
Test Mode :	802.11b	Temperature :	21~25°C
Test Band :	2.4GHz High	Relative Humidity :	51~54%
Test Channel :	11	Test Engineer :	Allen Lin

WLAN 802.11b Channel 11


100kHz PSD reference Level




High Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Number of TX :	2	Ant. :	2
Test Mode :	802.11g	Temperature :	21~25°C
Test Band :	2.4GHz Low	Relative Humidity :	51~54%
Test Channel :	01	Test Engineer :	Allen Lin

WLAN 802.11g Channel 01


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Number of TX :	2	Ant. :	2
Test Mode :	802.11g	Temperature :	21~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	51~54%
Test Channel :	06	Test Engineer :	Allen Lin

WLAN 802.11g Channel 06


100kHz PSD reference Level



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Number of TX :	2	Ant. :	2
Test Mode :	802.11g	Temperature :	21~25°C
Test Band :	2.4GHz High	Relative Humidity :	51~54%
Test Channel :	11	Test Engineer :	Allen Lin

WLAN 802.11g Channel 11


100kHz PSD reference Level




High Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Number of TX :	2	Ant. :	2
Test Mode :	802.11n HT20	Temperature :	21~25°C
Test Band :	2.4GHz Low	Relative Humidity :	51~54%
Test Channel :	01	Test Engineer :	Allen Lin

WLAN 802.11n HT20 Channel 01


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Number of TX :	2	Ant. :	2
Test Mode :	802.11n HT20	Temperature :	21~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	51~54%
Test Channel :	06	Test Engineer :	Allen Lin

WLAN 802.11n HT20 Channel 06


100kHz PSD reference Level



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Number of TX :	2	Ant. :	2
Test Mode :	802.11n HT20	Temperature :	21~25°C
Test Band :	2.4GHz High	Relative Humidity :	51~54%
Test Channel :	11	Test Engineer :	Allen Lin

WLAN 802.11n HT20 Channel 11


100kHz PSD reference Level




High Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Number of TX :	2	Ant. :	2
Test Mode :	802.11n HT40	Temperature :	21~25°C
Test Band :	2.4GHz Low	Relative Humidity :	51~54%
Test Channel :	03	Test Engineer :	Allen Lin

WLAN 802.11n HT40 Channel 03


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Number of TX :	2	Ant. :	2
Test Mode :	802.11n HT40	Temperature :	21~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	51~54%
Test Channel :	06	Test Engineer :	Allen Lin

WLAN 802.11n HT40 Channel 06


100kHz PSD reference Level



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Number of TX :	2	Ant. :	2
Test Mode :	802.11n HT40	Temperature :	21~25°C
Test Band :	2.4GHz High	Relative Humidity :	51~54%
Test Channel :	09	Test Engineer :	Allen Lin

WLAN 802.11n HT40 Channel 09


100kHz PSD reference Level




High Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz





3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




3.5.3 Test Procedures


1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

3.5.7 Duty Cycle

Please refer to Appendix E.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.



3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting Antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the Antenna exceeds 6 dBi. The use of a permanently attached Antenna or of an Antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

For CDD transmissions, directional gain is calculated as

Directional gain = $G_{ANT} + \text{Array Gain}$, where Array Gain is as follows.

For power spectral density (PSD) measurements on all devices,

Array Gain = $10 \log(N_{ANT}/N_{SS}=1)$ dB.

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$.

Directional gain may be calculated by using the formulas applicable to equal gain antennas with G_{ANT} set equal to the gain of the antenna having the highest gain;

The EUT supports CDD mode.

For power, the directional gain G_{ANT} is set equal to the antenna having the highest gain, i.e., F)2)f)i).

For PSD, the directional gain calculation is following F)2)f)ii) of KDB 662911 D01 v02r01.

The power and PSD limit should be modified if the directional gain of EUT is over 6 dBi,

The directional gain "DG" is calculated as following table.

	Ant. 1 (dBi)	Ant. 2 (dBi)	DG for Power (dBi)	DG for PSD (dBi)	Power Limit Reduction (dB)	PSD Limit Reduction (dB)
2.4 GHz	-1.80	-9.40	-1.80	-1.78	0.00	0.00

Power Limit Reduction = $DG(\text{Power}) - 6\text{dBi}$, (min = 0)

PSD Limit Reduction = $DG(\text{PSD}) - 6\text{dBi}$, (min = 0)



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Anritsu	ML2495A	0932001	300MHz~40GHz	Sep. 29, 2016	Apr. 14, 2017 ~ Apr. 24, 2017	Sep. 28, 2017	Conducted (TH05-HY)
Power Sensor	Anritsu	MA2411B	0846202	300MHz~40GHz	Sep. 29, 2016	Apr. 14, 2017 ~ Apr. 24, 2017	Sep. 28, 2017	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz-40GHz	Jul. 17, 2016	Apr. 14, 2017 ~ Apr. 24, 2017	Jul. 16, 2017	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Apr. 29, 2017	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESCI 7	100724	9kHz~7GHz	Aug. 30, 2016	Apr. 29, 2017	Aug. 29, 2017	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 29, 2016	Apr. 29, 2017	Nov. 28, 2017	Conduction (CO05-HY)
Amplifier	SONOMA	310N	187311	9kHz~1GHz	Oct. 26, 2016	Apr. 21, 2017 ~ Apr. 24, 2017	Oct. 25, 2017	Radiation (03CH10-HY)
Bilog Antenna	TESEQ	CBL 6111D&00800 N1D01N-06	35413&02	30MHz~1GHz	Jan. 07, 2017	Apr. 21, 2017 ~ Apr. 28, 2017	Jan. 06, 2018	Radiation (03CH10-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-132 5	1GHz ~ 18GHz	Sep. 30, 2016	Apr. 21, 2017 ~ Apr. 28, 2017	Sep. 29, 2017	Radiation (03CH10-HY)
Preamplifier	Keysight	83017A	MY532700 78	1GHz~26.5GHz	Oct. 26, 2016	Apr. 21, 2017 ~ Apr. 28, 2017	Oct. 25, 2017	Radiation (03CH10-HY)
Spectrum Analyzer	Keysight	N9010A	MY542004 85	10Hz ~ 44GHz	Oct. 17, 2016	Apr. 21, 2017 ~ Apr. 28, 2017	Oct. 16, 2017	Radiation (03CH10-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1~4m	N/A	Apr. 21, 2017 ~ Apr. 28, 2017	N/A	Radiation (03CH10-HY)
Turn Table	EMEC	TT 2200	N/A	0~360 Degree	N/A	Apr. 21, 2017 ~ Apr. 28, 2017	N/A	Radiation (03CH10-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Oct. 20, 2016	Apr. 21, 2017 ~ Apr. 28, 2017	Oct. 19, 2018	Radiation (03CH10-HY)
EMI Test Receiver	Keysight	N9038A (MXE)	MY554201 70	N/A	Mar. 03, 2017	Apr. 21, 2017 ~ Apr. 28, 2017	Mar. 02, 2018	Radiation (03CH10-HY)
Preamplifier	Jet-Power	JPA00101800 -30-10P	160118000 2	1GHz~18GHz	Jul. 27, 2016	Apr. 21, 2017 ~ Apr. 28, 2017	Jul. 26, 2017	Radiation (03CH10-HY)
Preamplifier	MITEQ	JS44-180040 00-33-8P	1840917	18GHz ~ 40GHz	Jun. 14, 2016	Apr. 21, 2017 ~ Apr. 28, 2017	Jun. 13, 2017	Radiation (03CH10-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170 584	18GHz- 40GHz	Nov. 08, 2016	Apr. 21, 2017 ~ Apr. 28, 2017	Nov. 07, 2017	Radiation (03CH10-HY)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.70
---	------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.60
---	------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.90
---	------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.20
---	------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Allen Lin	Temperature:	21~25	°C
Test Date:	2017/4/14~2017/4/24	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)		6dB BW (MHz)		6dB BW Limit (MHz)	Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2		
11b	1Mbps	2	1	2412	12.85	13.00	7.52	7.98	0.50	Pass
11b	1Mbps	2	6	2437	12.85	12.85	8.00	7.52	0.50	Pass
11b	1Mbps	2	11	2462	12.65	12.75	7.54	7.06	0.50	Pass
11g	6Mbps	2	1	2412	18.05	17.90	16.32	16.36	0.50	Pass
11g	6Mbps	2	6	2437	18.05	17.85	15.90	16.32	0.50	Pass
11g	6Mbps	2	11	2462	17.90	17.65	16.30	16.36	0.50	Pass
HT20	MCS0	2	1	2412	19.20	19.05	17.54	17.54	0.50	Pass
HT20	MCS0	2	6	2437	19.00	19.10	16.36	17.34	0.50	Pass
HT20	MCS0	2	11	2462	19.00	19.00	17.18	17.54	0.50	Pass
HT40	MCS0	2	3	2422	36.70	35.92	35.08	35.92	0.50	Pass
HT40	MCS0	2	6	2437	36.90	35.68	35.72	35.68	0.50	Pass
HT40	MCS0	2	9	2452	37.10	36.36	36.24	36.36	0.50	Pass

TEST RESULTS DATA
Peak Output Power

2.4GHz Band																
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
					Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	
11b	1Mbps	1	1	2412	13.56	13.98		30.00	30.00	0.00	0.00	13.56	13.98	36.00	36.00	Pass
11b	1Mbps	1	6	2437	13.82	14.35		30.00	30.00	0.00	0.00	13.82	14.35	36.00	36.00	Pass
11b	1Mbps	1	11	2462	13.89	14.10		30.00	30.00	0.00	0.00	13.89	14.10	36.00	36.00	Pass
11g	6Mbps	1	1	2412	20.02	20.10		30.00	30.00	0.00	0.00	20.02	20.10	36.00	36.00	Pass
11g	6Mbps	1	6	2437	20.11	20.47		30.00	30.00	0.00	0.00	20.11	20.47	36.00	36.00	Pass
11g	6Mbps	1	11	2462	20.12	20.04		30.00	30.00	0.00	0.00	20.12	20.04	36.00	36.00	Pass
HT20	MCS0	1	1	2412	20.06	20.22		30.00	30.00	0.00	0.00	20.06	20.22	36.00	36.00	Pass
HT20	MCS0	1	6	2437	20.02	20.36		30.00	30.00	0.00	0.00	20.02	20.36	36.00	36.00	Pass
HT20	MCS0	1	11	2462	20.19	20.16		30.00	30.00	0.00	0.00	20.19	20.16	36.00	36.00	Pass
HT40	MCS0	1	3	2422	20.67	20.63		30.00	30.00	0.00	0.00	20.67	20.63	36.00	36.00	Pass
HT40	MCS0	1	6	2437	20.35	20.90		30.00	30.00	0.00	0.00	20.35	20.90	36.00	36.00	Pass
HT40	MCS0	1	9	2452	20.61	21.13		30.00	30.00	0.00	0.00	20.61	21.13	36.00	36.00	Pass
VHT20	MCS0	1	1	2412	19.90	20.06		30.00	30.00	0.00	0.00	19.90	20.06	36.00	36.00	Pass
VHT20	MCS0	1	6	2437	19.92	20.10		30.00	30.00	0.00	0.00	19.92	20.10	36.00	36.00	Pass
VHT20	MCS0	1	11	2462	20.11	20.00		30.00	30.00	0.00	0.00	20.11	20.00	36.00	36.00	Pass
VHT40	MCS0	1	3	2422	20.11	20.04		30.00	30.00	0.00	0.00	20.11	20.04	36.00	36.00	Pass
VHT40	MCS0	1	6	2437	20.20	20.10		30.00	30.00	0.00	0.00	20.20	20.10	36.00	36.00	Pass
VHT40	MCS0	1	9	2452	20.22	20.12		30.00	30.00	0.00	0.00	20.22	20.12	36.00	36.00	Pass
11b	1Mbps	2	1	2412	13.66	14.00	16.84	30.00		0.00		16.84		36.00		Pass
11b	1Mbps	2	6	2437	13.85	14.40	17.14	30.00		0.00		17.14		36.00		Pass
11b	1Mbps	2	11	2462	13.95	14.22	17.10	30.00		0.00		17.10		36.00		Pass
11g	6Mbps	2	1	2412	20.04	20.22	23.14	30.00		0.00		23.14		36.00		Pass
11g	6Mbps	2	6	2437	20.15	20.50	23.34	30.00		0.00		23.34		36.00		Pass
11g	6Mbps	2	11	2462	20.21	20.12	23.18	30.00		0.00		23.18		36.00		Pass
HT20	MCS0	2	1	2412	20.09	19.93	23.02	30.00		0.00		23.02		36.00		Pass
HT20	MCS0	2	6	2437	20.03	20.40	23.23	30.00		0.00		23.23		36.00		Pass
HT20	MCS0	2	11	2462	20.03	20.01	23.03	30.00		0.00		23.03		36.00		Pass
HT40	MCS0	2	3	2422	20.35	20.71	23.54	30.00		0.00		23.54		36.00		Pass
HT40	MCS0	2	6	2437	20.40	20.95	23.69	30.00		0.00		23.69		36.00		Pass
HT40	MCS0	2	9	2452	20.59	20.59	23.60	30.00		0.00		23.60		36.00		Pass
VHT20	MCS0	2	1	2412	19.81	19.63	22.73	30.00		0.00		22.73		36.00		Pass
VHT20	MCS0	2	6	2437	19.95	19.15	22.58	30.00		0.00		22.58		36.00		Pass
VHT20	MCS0	2	11	2462	20.02	19.64	22.84	30.00		0.00		22.84		36.00		Pass
VHT40	MCS0	2	3	2422	19.95	20.03	23.00	30.00		0.00		23.00		36.00		Pass
VHT40	MCS0	2	6	2437	20.22	20.15	23.20	30.00		0.00		23.20		36.00		Pass
VHT40	MCS0	2	9	2452	20.31	20.12	23.23	30.00		0.00		23.23		36.00		Pass

Note: Measured power (dBm) has offset with cable loss.

TEST RESULTS DATA
Average Output Power

2.4GHz Band									
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)		
					Ant 1	Ant 2	Ant 1	Ant 2	SUM
11b	1Mbps	1	1	2412	0.04	0.06	11.01	11.26	
11b	1Mbps	1	6	2437	0.04	0.06	11.09	11.59	
11b	1Mbps	1	11	2462	0.04	0.06	11.17	11.37	
11g	6Mbps	1	1	2412	0.29	0.25	10.02	10.12	
11g	6Mbps	1	6	2437	0.29	0.25	10.11	10.57	
11g	6Mbps	1	11	2462	0.29	0.25	10.18	10.08	
HT20	MCS0	1	1	2412	0.25	0.28	10.02	10.17	
HT20	MCS0	1	6	2437	0.25	0.28	10.10	10.61	
HT20	MCS0	1	11	2462	0.25	0.28	10.14	10.00	
HT40	MCS0	1	3	2422	0.49	0.57	10.09	10.40	
HT40	MCS0	1	6	2437	0.49	0.57	10.14	10.32	
HT40	MCS0	1	9	2452	0.49	0.57	10.19	10.36	
VHT20	MCS0	1	1	2412	0.27	0.31	10.01	10.10	
VHT20	MCS0	1	6	2437	0.27	0.31	10.02	10.22	
VHT20	MCS0	1	11	2462	0.27	0.31	10.18	10.08	
VHT40	MCS0	1	3	2422	0.56	0.57	10.06	10.25	
VHT40	MCS0	1	6	2437	0.56	0.57	10.11	10.27	
VHT40	MCS0	1	9	2452	0.56	0.57	10.23	10.30	
11b	1Mbps	2	1	2412	0.06	0.04	10.96	11.27	14.13
11b	1Mbps	2	6	2437	0.06	0.04	11.04	11.60	14.34
11b	1Mbps	2	11	2462	0.06	0.04	11.26	11.39	14.34
11g	6Mbps	2	1	2412	0.25	0.25	9.95	10.05	13.01
11g	6Mbps	2	6	2437	0.25	0.25	10.12	10.67	13.41
11g	6Mbps	2	11	2462	0.25	0.25	10.15	9.95	13.06
HT20	MCS0	2	1	2412	0.25	0.25	9.98	10.02	13.01
HT20	MCS0	2	6	2437	0.25	0.25	10.11	10.63	13.39
HT20	MCS0	2	11	2462	0.25	0.25	10.12	9.89	13.02
HT40	MCS0	2	3	2422	0.57	0.57	10.11	10.31	13.22
HT40	MCS0	2	6	2437	0.57	0.57	10.17	10.34	13.26
HT40	MCS0	2	9	2452	0.57	0.57	10.24	10.25	13.25
VHT20	MCS0	2	1	2412	0.31	0.31	9.96	10.12	13.05
VHT20	MCS0	2	6	2437	0.31	0.31	10.06	10.24	13.16
VHT20	MCS0	2	11	2462	0.31	0.31	10.17	9.95	13.07
VHT40	MCS0	2	3	2422	0.53	0.61	9.95	10.26	13.12
VHT40	MCS0	2	6	2437	0.53	0.61	10.13	10.33	13.24
VHT40	MCS0	2	9	2452	0.53	0.61	10.21	10.29	13.26

Note: Measured power (dBm) has offset with cable loss.

TEST RESULTS DATA
Peak Power Spectral Density

2.4GHz Band												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm/3kHz)			DG (dBi)		Peak PSD Limit (dBm/3kHz)		Pass/Fail
					Ant 1	Ant 2	Worse + 3.01	Ant 1	Ant 2	Ant 1	Ant 2	
11b	1Mbps	2	1	2412	-10.82	-12.12	-7.81	3.01		8.00		Pass
11b	1Mbps	2	6	2437	-10.55	-10.71	-7.54	3.01		8.00		Pass
11b	1Mbps	2	11	2462	-12.57	-11.36	-8.35	3.01		8.00		Pass
11g	6Mbps	2	1	2412	-15.03	-15.22	-12.02	3.01		8.00		Pass
11g	6Mbps	2	6	2437	-14.75	-13.46	-10.45	3.01		8.00		Pass
11g	6Mbps	2	11	2462	-15.28	-15.66	-12.27	3.01		8.00		Pass
HT20	MCS0	2	1	2412	-15.10	-16.51	-12.09	3.01		8.00		Pass
HT20	MCS0	2	6	2437	-14.60	-16.12	-11.59	3.01		8.00		Pass
HT20	MCS0	2	11	2462	-13.68	-15.73	-10.67	3.01		8.00		Pass
HT40	MCS0	2	3	2422	-18.15	-17.63	-14.62	3.01		8.00		Pass
HT40	MCS0	2	6	2437	-17.53	-17.79	-14.52	3.01		8.00		Pass
HT40	MCS0	2	9	2452	-18.96	-18.06	-15.05	3.01		8.00		Pass

Measured power density (dBm) has offset with cable loss.




Appendix B. AC Conducted Emission Test Results

Test Engineer :	Eric Jeng	Temperature :	21~23°C
		Relative Humidity :	52~55%

EUT Information

Report NO : 740120
 Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Line

ENV216 Auto Test FCC Power Bar - L



Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.158000	40.6	Off	L1	19.6	25.0	65.6
0.214000	34.7	Off	L1	19.6	28.3	63.0
0.454000	32.0	Off	L1	19.6	24.8	56.8
0.502000	33.8	Off	L1	19.6	22.2	56.0
0.614000	31.2	Off	L1	19.6	24.8	56.0
1.222000	35.0	Off	L1	19.6	21.0	56.0
4.822000	30.1	Off	L1	19.8	25.9	56.0


Final Result 2

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.158000	26.7	Off	L1	19.6	28.9	55.6
0.214000	22.8	Off	L1	19.6	30.2	53.0
0.454000	24.0	Off	L1	19.6	22.8	46.8
0.502000	23.9	Off	L1	19.6	22.1	46.0
0.614000	26.6	Off	L1	19.6	19.4	46.0
1.222000	28.0	Off	L1	19.6	18.0	46.0
4.822000	19.8	Off	L1	19.8	26.2	46.0

EUT Information

Report NO : 740120
 Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Neutral

ENV216 Auto Test FCC Power Bar - N



Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	45.0	Off	N	19.5	21.0	66.0
0.182000	37.5	Off	N	19.5	26.9	64.4
0.430000	33.7	Off	N	19.5	23.6	57.3
0.502000	38.6	Off	N	19.5	17.4	56.0
0.710000	24.9	Off	N	19.5	31.1	56.0
4.590000	22.0	Off	N	19.7	34.0	56.0
5.886000	25.9	Off	N	19.8	34.1	60.0

Final Result 2

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	28.6	Off	N	19.5	27.4	56.0
0.182000	24.0	Off	N	19.5	30.4	54.4
0.430000	21.0	Off	N	19.5	26.3	47.3
0.502000	27.7	Off	N	19.5	18.3	46.0
0.710000	17.4	Off	N	19.5	28.6	46.0
4.590000	15.5	Off	N	19.7	30.5	46.0
5.886000	16.3	Off	N	19.8	33.7	50.0



Appendix C. Radiated Spurious Emission

Test Engineer :	Stan Hsieh and Kyle Chuang	Temperature :	22~24°C
		Relative Humidity :	43~44%

2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.	
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)	
802.11b CH 01 2412MHz		2347.38	50.49	-23.51	74	42.6	26.74	4.4	33.23	299	138	P	H	
		2390	39.6	-14.4	54	31.47	26.93	4.43	33.21	299	138	A	H	
	*	2412	96.86	-	-	88.63	26.99	4.47	33.21	299	138	P	H	
	*	2412	93.72	-	-	85.49	26.99	4.47	33.21	299	138	A	H	
													H	
														H
			2386.86	50.55	-23.45	74	42.43	26.93	4.43	33.22	193	250	P	V
			2389.065	39.77	-14.23	54	31.65	26.93	4.43	33.22	193	250	A	V
	*		2412	99.83	-	-	91.6	26.99	4.47	33.21	193	250	P	V
	*		2412	96.76	-	-	88.53	26.99	4.47	33.21	193	250	A	V
														V
														V
802.11b CH 06 2437MHz		2355.36	50.73	-23.27	74	42.78	26.8	4.4	33.23	328	134	P	H	
		2384.06	39.58	-14.42	54	31.52	26.87	4.43	33.22	328	134	A	H	
	*	2437	96.9	-	-	88.52	27.11	4.48	33.19	328	134	P	H	
	*	2437	93.67	-	-	85.29	27.11	4.48	33.19	328	134	A	H	
			2493.56	51.28	-22.72	74	42.63	27.3	4.53	33.16	328	134	P	H
			2496.5	40.06	-13.94	54	31.41	27.3	4.53	33.16	328	134	A	H
			2360.68	50.23	-23.77	74	42.26	26.8	4.42	33.23	224	247	P	V
			2389.94	39.7	-14.3	54	31.57	26.93	4.43	33.21	224	247	A	V
	*		2437	99.78	-	-	91.4	27.11	4.48	33.19	224	247	P	V
	*		2437	96.55	-	-	88.17	27.11	4.48	33.19	224	247	A	V
			2496.15	51.38	-22.62	74	42.73	27.3	4.53	33.16	224	247	P	V
			2484.95	40.1	-13.9	54	31.52	27.24	4.53	33.17	224	247	A	V



802.11b CH 11 2462MHz	*	2462	94.82	-	-	86.34	27.18	4.5	33.18	196	185	P	H
	*	2462	91.71	-	-	83.23	27.18	4.5	33.18	196	185	A	H
		2495.32	50.75	-23.25	74	42.1	27.3	4.53	33.16	196	185	P	H
		2484	40.02	-13.98	54	31.44	27.24	4.53	33.17	196	185	A	H
													H
													H
	*	2462	98.51	-	-	90.03	27.18	4.5	33.18	288	226	P	V
	*	2462	95.55	-	-	87.07	27.18	4.5	33.18	288	226	A	V
		2495.12	51.2	-22.8	74	42.55	27.3	4.53	33.16	288	226	P	V
		2484.44	40.06	-13.94	54	31.48	27.24	4.53	33.17	288	226	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11b (Harmonic @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11b CH 01 2412MHz		4824	44.66	-29.34	74	67.62	32.09	6.36	61.9	100	0	P	H	
													H	
													H	
													H	
			4824	44.41	-29.59	74	67.37	32.09	6.36	61.9	100	0	P	V
														V
														V
802.11b CH 06 2437MHz		4874	45.15	-28.85	74	67.95	32.21	6.41	61.9	100	0	P	H	
		7311	49.31	-24.69	74	66.15	36.86	7.96	62.06	100	0	P	H	
													H	
													H	
			4874	44.96	-29.04	74	67.76	32.21	6.41	61.9	100	0	P	V
			7311	49.89	-24.11	74	66.73	36.86	7.96	62.06	100	0	P	V
														V
802.11b CH 11 2462MHz		4924	46.12	-27.88	74	68.79	32.33	6.43	61.9	100	0	P	H	
		7386	49.05	-24.95	74	65.61	37.15	8.02	62.08	100	0	P	H	
													H	
													H	
			4924	44.96	-29.04	74	67.63	32.33	6.43	61.9	100	0	P	V
			7386	49.91	-24.09	74	66.47	37.15	8.02	62.08	100	0	P	V
														V
Remark	1. No other spurious found.													
	2. All results are PASS against Peak and Average limit line.													



2.4GHz 2400~2483.5MHz

WIFI 802.11g (Band Edge @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11g CH 01 2412MHz		2385.075	50.3	-23.7	74	42.24	26.87	4.43	33.22	303	121	P	H	
		2388.33	40.73	-13.27	54	32.61	26.93	4.43	33.22	303	121	A	H	
	*	2412	96.78	-	-	88.55	26.99	4.47	33.21	303	121	P	H	
	*	2412	89.26	-	-	81.03	26.99	4.47	33.21	303	121	A	H	
													H	
													H	
			2387.595	53.55	-20.45	74	45.43	26.93	4.43	33.22	195	246	P	V
			2389.905	41.3	-12.7	54	33.17	26.93	4.43	33.21	195	246	A	V
	*		2412	101.03	-	-	92.8	26.99	4.47	33.21	195	246	P	V
	*		2412	93.44	-	-	85.21	26.99	4.47	33.21	195	246	A	V
													V	
													V	
802.11g CH 06 2437MHz		2370.48	50.25	-23.75	74	42.2	26.87	4.42	33.22	326	119	P	H	
		2382.38	40.55	-13.45	54	32.49	26.87	4.43	33.22	326	119	A	H	
	*	2437	98.21	-	-	89.83	27.11	4.48	33.19	326	119	P	H	
	*	2437	90.44	-	-	82.06	27.11	4.48	33.19	326	119	A	H	
			2499.65	51.62	-22.38	74	42.97	27.3	4.53	33.16	326	119	P	H
			2494.47	40.94	-13.06	54	32.29	27.3	4.53	33.16	326	119	A	H
			2372.86	51.28	-22.72	74	43.23	26.87	4.42	33.22	253	239	P	V
			2388.96	40.74	-13.26	54	32.62	26.93	4.43	33.22	253	239	A	V
	*		2437	101.81	-	-	93.43	27.11	4.48	33.19	253	239	P	V
	*		2437	94.23	-	-	85.85	27.11	4.48	33.19	253	239	A	V
			2485.72	50.73	-23.27	74	42.15	27.24	4.53	33.17	253	239	P	V
			2483.5	41.01	-12.99	54	32.43	27.24	4.53	33.17	253	239	A	V



802.11g CH 11 2462MHz	*	2462	95.97	-	-	87.49	27.18	4.5	33.18	285	183	P	H
	*	2462	88.81	-	-	80.33	27.18	4.5	33.18	285	183	A	H
		2484.2	51.82	-22.18	74	43.24	27.24	4.53	33.17	285	183	P	H
		2483.88	41.47	-12.53	54	32.89	27.24	4.53	33.17	285	183	A	H
													H
													H
	*	2462	100.61	-	-	92.13	27.18	4.5	33.18	282	232	P	V
	*	2462	93.23	-	-	84.75	27.18	4.5	33.18	282	232	A	V
		2483.56	56.65	-17.35	74	48.07	27.24	4.53	33.17	282	232	P	V
		2483.6	42.97	-11.03	54	34.39	27.24	4.53	33.17	282	232	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11g (Harmonic @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11g CH 01 2412MHz		4824	45.18	-28.82	74	68.14	32.09	6.36	61.9	100	0	P	H	
													H	
													H	
													H	
			4824	46.44	-27.56	74	69.4	32.09	6.36	61.9	100	0	P	V
														V
														V
802.11g CH 06 2437MHz		4874	43.81	-30.19	74	66.61	32.21	6.41	61.9	100	0	P	H	
		7311	49.49	-24.51	74	66.33	36.86	7.96	62.06	100	0	P	H	
													H	
													H	
			4874	44.15	-29.85	74	66.95	32.21	6.41	61.9	100	0	P	V
			7311	49.18	-24.82	74	66.02	36.86	7.96	62.06	100	0	P	V
														V
802.11g CH 11 2462MHz		4924	44.4	-29.6	74	67.07	32.33	6.43	61.9	100	0	P	H	
		7386	49.52	-24.48	74	66.08	37.15	8.02	62.08	100	0	P	H	
													H	
													H	
			4924	45.21	-28.79	74	67.88	32.33	6.43	61.9	100	0	P	V
			7386	49.4	-24.6	74	65.96	37.15	8.02	62.08	100	0	P	V
														V
Remark	1. No other spurious found.													
	2. All results are PASS against Peak and Average limit line.													



2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11n HT20 CH 01 2412MHz		2360.295	50.23	-23.77	74	42.26	26.8	4.42	33.23	302	40	P	H	
		2389.485	40.56	-13.44	54	32.44	26.93	4.43	33.22	302	40	A	H	
	*	2412	96.36	-	-	88.13	26.99	4.47	33.21	302	40	P	H	
	*	2412	89.22	-	-	80.99	26.99	4.47	33.21	302	40	A	H	
													H	
														H
			2389.275	51.76	-22.24	74	43.64	26.93	4.43	33.22	148	303	P	V
			2390	42.23	-11.77	54	34.1	26.93	4.43	33.21	148	303	A	V
		*	2412	100.68	-	-	92.45	26.99	4.47	33.21	148	303	P	V
		*	2412	93.23	-	-	85	26.99	4.47	33.21	148	303	A	V
													V	
													V	
802.11n HT20 CH 06 2437MHz		2379.3	50.47	-23.53	74	42.41	26.87	4.43	33.22	155	333	P	H	
		2387.7	40.5	-13.5	54	32.38	26.93	4.43	33.22	155	333	A	H	
	*	2437	95.35	-	-	86.97	27.11	4.48	33.19	155	333	P	H	
	*	2437	88.11	-	-	79.73	27.11	4.48	33.19	155	333	A	H	
			2497.69	50.86	-23.14	74	42.21	27.3	4.53	33.16	155	333	P	H
			2487.4	41.1	-12.9	54	32.52	27.24	4.53	33.17	155	333	A	H
			2318.96	50.02	-23.98	74	42.24	26.68	4.36	33.24	135	301	P	V
			2389.1	40.51	-13.49	54	32.39	26.93	4.43	33.22	135	301	A	V
		*	2437	100.42	-	-	92.04	27.11	4.48	33.19	135	301	P	V
		*	2437	92.66	-	-	84.28	27.11	4.48	33.19	135	301	A	V
		2484.67	50.62	-23.38	74	42.04	27.24	4.53	33.17	135	301	P	V	
		2483.83	41.05	-12.95	54	32.47	27.24	4.53	33.17	135	301	A	V	



802.11n HT20 CH 11 2462MHz	*	2462	95.63	-	-	87.15	27.18	4.5	33.18	235	359	P	H
	*	2462	88.28	-	-	79.8	27.18	4.5	33.18	235	359	A	H
		2483.56	51.09	-22.91	74	42.51	27.24	4.53	33.17	235	359	P	H
		2483.64	41.14	-12.86	54	32.56	27.24	4.53	33.17	235	359	A	H
													H
													H
	*	2462	99.67	-	-	91.19	27.18	4.5	33.18	100	302	P	V
	*	2462	92.25	-	-	83.77	27.18	4.5	33.18	100	302	A	V
		2484	55.35	-18.65	74	46.77	27.24	4.53	33.17	100	302	P	V
		2484.24	42.35	-11.65	54	33.77	27.24	4.53	33.17	100	302	A	V
													V
												V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11n HT20 CH 01 2412MHz		4824	45.25	-28.75	74	68.21	32.09	6.36	61.9	100	0	P	H	
													H	
													H	
													H	
			4824	43.96	-30.04	74	66.92	32.09	6.36	61.9	100	0	P	V
														V
														V
802.11n HT20 CH 06 2437MHz		4874	43.69	-30.31	74	66.49	32.21	6.41	61.9	100	0	P	H	
		7311	49.29	-24.71	74	66.13	36.86	7.96	62.06	100	0	P	H	
													H	
													H	
			4874	44.02	-29.98	74	66.82	32.21	6.41	61.9	100	0	P	V
			7311	50.35	-23.65	74	67.19	36.86	7.96	62.06	100	0	P	V
														V
802.11n HT20 CH 11 2462MHz		4924	44.89	-29.11	74	67.56	32.33	6.43	61.9	100	0	P	H	
		7386	50.06	-23.94	74	66.62	37.15	8.02	62.08	100	0	P	H	
													H	
													H	
			4924	44.73	-29.27	74	67.4	32.33	6.43	61.9	100	0	P	V
			7386	49.9	-24.1	74	66.46	37.15	8.02	62.08	100	0	P	V
														V
Remark	1. No other spurious found.													
	2. All results are PASS against Peak and Average limit line.													



2.4GHz 2400~2483.5MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 03 2422MHz		2385.74	52.88	-21.12	74	44.76	26.93	4.43	33.22	211	342	P	H
		2389.38	42.8	-11.2	54	34.68	26.93	4.43	33.22	211	342	A	H
	*	2422	93.33	-	-	85.02	27.05	4.47	33.19	211	342	P	H
	*	2422	85.75	-	-	77.44	27.05	4.47	33.19	211	342	A	H
		2491.95	50.88	-23.12	74	42.23	27.3	4.53	33.16	211	342	P	H
		2498.25	41.57	-12.43	54	32.92	27.3	4.53	33.16	211	342	A	H
		2389.38	56.84	-17.16	74	48.72	26.93	4.43	33.22	132	300	P	V
		2389.52	45.24	-8.76	54	37.12	26.93	4.43	33.22	132	300	A	V
	*	2422	97.94	-	-	89.63	27.05	4.47	33.19	132	300	P	V
	*	2422	90.36	-	-	82.05	27.05	4.47	33.19	132	300	A	V
		2488.45	50.93	-23.07	74	42.29	27.3	4.53	33.17	132	300	P	V
		2489.29	41.78	-12.22	54	33.14	27.3	4.53	33.17	132	300	A	V
802.11n HT40 CH 06 2437MHz		2372.44	50.04	-23.96	74	41.99	26.87	4.42	33.22	151	337	P	H
		2388.12	41.15	-12.85	54	33.03	26.93	4.43	33.22	151	337	A	H
	*	2437	93.58	-	-	85.2	27.11	4.48	33.19	151	337	P	H
	*	2437	86.03	-	-	77.65	27.11	4.48	33.19	151	337	A	H
		2499.93	51.51	-22.49	74	42.86	27.3	4.53	33.16	151	337	P	H
		2487.75	41.85	-12.15	54	33.21	27.3	4.53	33.17	151	337	A	H
		2389.94	50.99	-23.01	74	42.86	26.93	4.43	33.21	227	239	P	V
		2389.52	41.9	-12.1	54	33.78	26.93	4.43	33.22	227	239	A	V
	*	2437	98.46	-	-	90.08	27.11	4.48	33.19	227	239	P	V
	*	2437	90.98	-	-	82.6	27.11	4.48	33.19	227	239	A	V
		2483.9	50.76	-23.24	74	42.18	27.24	4.53	33.17	227	239	P	V
		2494.05	42.03	-11.97	54	33.38	27.3	4.53	33.16	227	239	A	V



802.11n HT40 CH 09 2452MHz		2386.44	50.75	-23.25	74	42.63	26.93	4.43	33.22	131	332	P	H
		2385.88	41.33	-12.67	54	33.21	26.93	4.43	33.22	131	332	A	H
	*	2452	93.79	-	-	85.38	27.11	4.5	33.18	131	332	P	H
	*	2452	86.72	-	-	78.31	27.11	4.5	33.18	131	332	A	H
		2484.53	50.37	-23.63	74	41.79	27.24	4.53	33.17	131	332	P	H
		2484.32	41.98	-12.02	54	33.4	27.24	4.53	33.17	131	332	A	H
		2389.1	51.04	-22.96	74	42.92	26.93	4.43	33.22	262	238	P	V
		2389.8	41.57	-12.43	54	33.44	26.93	4.43	33.21	262	238	A	V
	*	2452	97.48	-	-	89.07	27.11	4.5	33.18	262	238	P	V
	*	2452	90.34	-	-	81.93	27.11	4.5	33.18	262	238	A	V
		2483.76	53.98	-20.02	74	45.4	27.24	4.53	33.17	262	238	P	V
		2483.5	44.57	-9.43	54	35.99	27.24	4.53	33.17	262	238	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 03 2422MHz		4844	43.74	-30.26	74	66.64	32.13	6.38	61.9	100	0	P	H
		7266	49.62	-24.38	74	66.58	36.74	7.93	62.06	100	0	P	H
													H
													H
		4844	43.74	-30.26	74	66.64	32.13	6.38	61.9	100	0	P	V
		7266	49.82	-24.18	74	66.78	36.74	7.93	62.06	100	0	P	V
802.11n HT40 CH 06 2437MHz		4874	43.33	-30.67	74	66.13	32.21	6.41	61.9	100	0	P	H
		7311	49.43	-24.57	74	66.27	36.86	7.96	62.06	100	0	P	H
													H
													H
		4874	44.43	-29.57	74	67.23	32.21	6.41	61.9	100	0	P	V
		7311	49.35	-24.65	74	66.19	36.86	7.96	62.06	100	0	P	V
802.11n HT40 CH 09 2452MHz		4904	44.13	-29.87	74	66.85	32.29	6.42	61.9	100	0	P	H
		7356	49.24	-24.76	74	65.9	37.03	8.01	62.07	100	0	P	H
													H
													H
		4904	44.79	-29.21	74	67.51	32.29	6.42	61.9	100	0	P	V
		7356	49.84	-24.16	74	66.5	37.03	8.01	62.07	100	0	P	V
Remark	1. No other spurious found.												
	2. All results are PASS against Peak and Average limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

- Level(dBμV/m) =
Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
- Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

- Level(dBμV/m)
= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)
= 55.45 (dBμV/m)
- Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 55.45(dBμV/m) – 74(dBμV/m)
= -18.55(dB)

For Average Limit @ 2390MHz:

- Level(dBμV/m)
= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)
= 43.54 (dBμV/m)
- Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 43.54(dBμV/m) – 54(dBμV/m)
= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix D. Radiated Spurious Emission Plots

Test Engineer :	Stan Hsieh and Kyle Chuang	Temperature :	22~24°C
		Relative Humidity :	43~44%

Note symbol

-L	Low channel location
-R	High channel location







2.4GHz 2400~2483.5MHz





WIFI 802.11b (Band Edge @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH01 2412MHz	
1+2	Horizontal	Fundamental
Peak	<p>Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 740120 Mode : 7</p>	<p>Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 740120 Mode : 7</p>
Avg.	<p>Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 740120 Mode : 7</p>	<p>Site : 03CH10-HY Condition : AVG_54 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 740120 Mode : 7</p>





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH01 2412MHz	
1+2	Vertical	Fundamental
Peak	 <p>Site : 03CHD-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : 740120 Mode : 7</p>	 <p>Site : 03CHD-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : 740120 Mode : 7</p>
Avg.	 <p>Site : 03CHD-HY Condition : AVG_BE_54 3m HORN 91200-HF VERTICAL Detector : Peak Project : 740120 Mode : 7</p>	 <p>Site : 03CHD-HY Condition : AVG_54 3m HORN 91200-HF VERTICAL Detector : Peak Project : 740120 Mode : 7</p>







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - L	
1+2	Horizontal	Fundamental
Peak	 <p>Site : 03CHD-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 740120 Mode : B</p>	 <p>Site : 03CHD-HY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 740120 Mode : B</p>
Avg.	 <p>Site : 03CHD-HY Condition : AVG_BE_54 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 740120 Mode : B</p>	 <p>Site : 03CHD-HY Condition : AVG_54 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 740120 Mode : B</p>





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - R	
1+2	Horizontal	Fundamental
<p>Peak</p>	 <p> Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 740120 Mode : B </p>	<p>Left blank</p>
<p>Avg.</p>	 <p> Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 740120 Mode : B </p>	<p>Left blank</p>







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - L	
1+2	Vertical	Fundamental
Peak	 <p>Site : 03CHD-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : 740120 Mode : 8</p>	 <p>Site : 03CHD-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : 740120 Mode : 8</p>
Avg.	 <p>Site : 03CHD-HY Condition : AVG_BE_54 3m HORN 91200-HF VERTICAL Detector : Peak Project : 740120 Mode : 8</p>	 <p>Site : 03CHD-HY Condition : AVG_54 3m HORN 91200-HF VERTICAL Detector : Peak Project : 740120 Mode : 8</p>







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - R	
1+2	Vertical	Fundamental
Peak	 <p>Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 740120 Mode : B</p>	Left blank
Avg.	 <p>Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 740120 Mode : B</p>	Left blank



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH11 2462MHz	
1+2	Horizontal	Fundamental
Peak	 <p>Site : 03CHD-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 740120 Mode : 9</p>	 <p>Site : 03CHD-HY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 740120 Mode : 9</p>
Avg.	 <p>Site : 03CHD-HY Condition : AVG_BE_54 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 740120 Mode : 9</p>	 <p>Site : 03CHD-HY Condition : AVG_54 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 740120 Mode : 9</p>



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH11 2462MHz	
1+2	Vertical	Fundamental
Peak	 <p>Site : 03CHD-HY Condition : PEAK_BE_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 740120 Mode : 9</p>	 <p>Site : 03CHD-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 740120 Mode : 9</p>
Avg.	 <p>Site : 03CHD-HY Condition : AVG_BE_54 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 740120 Mode : 9</p>	 <p>Site : 03CHD-HY Condition : AVG_54 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 740120 Mode : 9</p>







2.4GHz 2400~2483.5MHz





WIFI 802.11g (Band Edge @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH01 2412MHz	
1+2	Horizontal	Fundamental
Peak	<p>Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 740120 Mode : IO</p>	<p>Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 740120 Mode : IO</p>
Avg.	<p>Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 740120 Mode : IO</p>	<p>Site : 03CH10-HY Condition : AVG_54 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 740120 Mode : IO</p>





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH01 2412MHz	
1+2	Vertical	Fundamental
Peak	 <p>Site : 03CHD-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : 740120 Mode : 10</p>	 <p>Site : 03CHD-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : 740120 Mode : 10</p>
Avg.	 <p>Site : 03CHD-HY Condition : AVG_BE_54 3m HORN 91200-HF VERTICAL Detector : Peak Project : 740120 Mode : 10</p>	 <p>Site : 03CHD-HY Condition : AVG_54 3m HORN 91200-HF VERTICAL Detector : Peak Project : 740120 Mode : 10</p>







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - L	
1+2	Horizontal	Fundamental
Peak	 <p>Site : 03CHD-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 740120 Mode : 11</p>	 <p>Site : 03CHD-HY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 740120 Mode : 11</p>
Avg.	 <p>Site : 03CHD-HY Condition : AVG_BE_54 3m HORN 91200-HF HORIZONTAL : RBW:1000.000KHz VBW:1000KHz SWT:Auto Detector : Peak Project : 740120 Mode : 11</p>	 <p>Site : 03CHD-HY Condition : AVG_54 3m HORN 91200-HF HORIZONTAL : RBW:1000.000KHz VBW:1000KHz SWT:Auto Detector : Peak Project : 740120 Mode : 11</p>





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - R	
1+2	Horizontal	Fundamental
<p>Peak</p>	 <p>Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 740120 Mode : II</p>	<p>Left blank</p>
<p>Avg.</p>	 <p>Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 740120 Mode : II</p>	<p>Left blank</p>







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - L	
1+2	Vertical	Fundamental
Peak	 <p>Site : 03CHD-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : 740120 Mode : 11</p>	 <p>Site : 03CHD-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : 740120 Mode : 11</p>
Avg.	 <p>Site : 03CHD-HY Condition : AVG_BE_54 3m HORN 91200-HF VERTICAL Detector : Peak Project : 740120 Mode : 11</p>	 <p>Site : 03CHD-HY Condition : AVG_54 3m HORN 91200-HF VERTICAL Detector : Peak Project : 740120 Mode : 11</p>







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - R	
1+2	Vertical	Fundamental
Peak	 <p>Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 740120 Mode : II</p>	Left Blank
Avg.	 <p>Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:1000KHz SWT:Auto Detector : Peak Project : 740120 Mode : II</p>	Left Blank



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH11 2462MHz	
1+2	Horizontal	Fundamental
Peak	 <p>Site : 03CHD-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 740120 Mode : 12</p>	 <p>Site : 03CHD-HY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 740120 Mode : 12</p>
Avg.	 <p>Site : 03CHD-HY Condition : AVG_BE_54 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 740120 Mode : 12</p>	 <p>Site : 03CHD-HY Condition : AVG_54 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 740120 Mode : 12</p>



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH11 2462MHz	
1+2	Vertical	Fundamental
Peak	 <p>Site : 03CHD-HY Condition : PEAK_BE_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 740120 Mode : 12</p>	 <p>Site : 03CHD-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 740120 Mode : 12</p>
Avg.	 <p>Site : 03CHD-HY Condition : AVG_BE_54 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 740120 Mode : 12</p>	 <p>Site : 03CHD-HY Condition : AVG_54 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 740120 Mode : 12</p>







2.4GHz 2400~2483.5MHz





WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH01 2412MHz	
1+2	Horizontal	Fundamental
Peak	<p>Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 740120 Mode : 13</p>	<p>Site : 03CH10-HY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 740120 Mode : 13</p>
Avg.	<p>Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 740120 Mode : 13</p>	<p>Site : 03CH10-HY Condition : AVG_54 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 740120 Mode : 13</p>





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH01 2412MHz	
1+2	Vertical	Fundamental
Peak	 <p>Site : 03CHD-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : 740120 Mode : 13</p>	 <p>Site : 03CHD-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : 740120 Mode : 13</p>
Avg.	 <p>Site : 03CHD-HY Condition : AVG_BE_54 3m HORN 91200-HF VERTICAL Detector : Peak Project : 740120 Mode : 13</p>	 <p>Site : 03CHD-HY Condition : AVG_54 3m HORN 91200-HF VERTICAL Detector : Peak Project : 740120 Mode : 13</p>







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - L	
1+2	Horizontal	Fundamental
Peak	 <p>Site : 03CHD-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 740120 Mode : 14</p>	 <p>Site : 03CHD-HY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 740120 Mode : 14</p>
Avg.	 <p>Site : 03CHD-HY Condition : AVG_BE_54 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 740120 Mode : 14</p>	 <p>Site : 03CHD-HY Condition : AVG_54 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 740120 Mode : 14</p>





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - R	
1+2	Horizontal	Fundamental
Peak	 <p> Site : 03CHD-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 740120 Mode : 14 </p>	Left blank
Avg.	 <p> Site : 03CHD-HY Condition : AVG_BE_54 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 740120 Mode : 14 </p>	Left blank







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - L	
1+2	Vertical	Fundamental
Peak	 <p>Site : 03CHD-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : 740120 Mode : 14</p>	 <p>Site : 03CHD-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : 740120 Mode : 14</p>
Avg.	 <p>Site : 03CHD-HY Condition : AVG_BE_54 3m HORN 91200-HF VERTICAL Detector : Peak Project : 740120 Mode : 14</p>	 <p>Site : 03CHD-HY Condition : AVG_54 3m HORN 91200-HF VERTICAL Detector : Peak Project : 740120 Mode : 14</p>







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - R	
1+2	Vertical	Fundamental
Peak	 <p> Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 740120 Mode : 14 </p>	Left Blank
Avg.	 <p> Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 91200-HF VERTICAL : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 740120 Mode : 14 </p>	Left Blank



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH11 2462MHz	
1+2	Horizontal	Fundamental
Peak	 <p>Site : 03CHD-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 740120 Mode : 15</p>	 <p>Site : 03CHD-HY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 740120 Mode : 15</p>
Avg.	 <p>Site : 03CHD-HY Condition : AVG_BE_54 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 740120 Mode : 15</p>	 <p>Site : 03CHD-HY Condition : AVG_54 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 740120 Mode : 15</p>







WIFI	2.4GHz 2400~2483.5MHz Fundamental @ 3m	
ANT	802.11n HT20 CH11 2462MHz	
1+2	Vertical	Fundamental
Peak	 <p>Site : 03CHD-HY Condition : PEAK_BE_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 740120 Mode : 15</p>	 <p>Site : 03CHD-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 740120 Mode : 15</p>
Avg.	 <p>Site : 03CHD-HY Condition : AVG_BE_54 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 740120 Mode : 15</p>	 <p>Site : 03CHD-HY Condition : AVG_54 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 740120 Mode : 15</p>





2.4GHz 2400~2483.5MHz





WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH03 2422MHz - L	
1+2	Horizontal	Fundamental
Peak	 <p>Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 740120 Mode : 16</p>	 <p>Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 740120 Mode : 16</p>
Avg.	 <p>Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 740120 Mode : 16</p>	 <p>Site : 03CH10-HY Condition : AVG_54 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 740120 Mode : 16</p>





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH03 2422MHz - R	
1+2	Horizontal	Fundamental
<p>Peak</p>	 <p>Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 740120 Mode : 16</p>	<p>Left Blank</p>
<p>Avg.</p>	 <p>Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 740120 Mode : 16</p>	<p>Left Blank</p>







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH03 2422MHz - L	
1+2	Vertical	Fundamental
Peak	 <p>Site : 03CHD-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : 740120 Mode : 16</p>	 <p>Site : 03CHD-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : 740120 Mode : 16</p>
Avg.	 <p>Site : 03CHD-HY Condition : AVG_BE_54 3m HORN 91200-HF VERTICAL Detector : Peak Project : 740120 Mode : 16</p>	 <p>Site : 03CHD-HY Condition : AVG_54 3m HORN 91200-HF VERTICAL Detector : Peak Project : 740120 Mode : 16</p>





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH03 2422MHz - R	
1+2	Vertical	Fundamental
Peak	 <p>Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 740120 Mode : 16</p>	Left blank
Avg.	 <p>Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 740120 Mode : 16</p>	Left blank







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH06 2437MHz - L	
1+2	Horizontal	Fundamental
Peak	 <p>Site : 03CHD-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 740120 Mode : 17</p>	 <p>Site : 03CHD-HY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 740120 Mode : 17</p>
Avg.	 <p>Site : 03CHD-HY Condition : AVG_BE_54 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 740120 Mode : 17</p>	 <p>Site : 03CHD-HY Condition : AVG_54 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 740120 Mode : 17</p>





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH06 2437MHz - R	
1+2	Horizontal	Fundamental
Peak	 <p>Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 740120 Mode : 17</p>	Left blank
Avg.	 <p>Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 91200-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 740120 Mode : 17</p>	Left blank







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH06 2437MHz - L	
1+2	Vertical	Fundamental
Peak	 <p>Site : 03CHD-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : 740120 Mode : 17</p>	 <p>Site : 03CHD-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : 740120 Mode : 17</p>
Avg.	 <p>Site : 03CHD-HY Condition : AVG_BE_54 3m HORN 91200-HF VERTICAL Detector : Peak Project : 740120 Mode : 17</p>	 <p>Site : 03CHD-HY Condition : AVG_54 3m HORN 91200-HF VERTICAL Detector : Peak Project : 740120 Mode : 17</p>





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH06 2437MHz - R	
1+2	Horizontal	Fundamental
<p>Peak</p>	 <p>Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 740120 Mode : 17</p>	<p>Left blank</p>
<p>Avg.</p>	 <p>Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 91200-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 740120 Mode : 17</p>	<p>Left blank</p>







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH09 2452MHz - L	
1+2	Horizontal	Fundamental
Peak	 <p>Site : 03CHD-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 740120 Mode : 1B</p>	 <p>Site : 03CHD-HY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 740120 Mode : 1B</p>
Avg.	 <p>Site : 03CHD-HY Condition : AVG_BE_54 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 740120 Mode : 1B</p>	 <p>Site : 03CHD-HY Condition : AVG_54 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 740120 Mode : 1B</p>




WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH09 2452MHz - R	
1+2	Horizontal	Fundamental
<p>Peak</p>	 <p>Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 740120 Mode : 1B</p>	<p>Left blank</p>
<p>Avg.</p>	 <p>Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 91200-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 740120 Mode : 1B</p>	<p>Left blank</p>



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH09 2452MHz - L	
1+2	Vertical	Fundamental
Peak	 <p>Site : 03CHD-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : 740120 Mode : 1B</p>	 <p>Site : 03CHD-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : 740120 Mode : 1B</p>
Avg.	 <p>Site : 03CHD-HY Condition : AVG_BE_54 3m HORN 91200-HF VERTICAL Detector : Peak Project : 740120 Mode : 1B</p>	 <p>Site : 03CHD-HY Condition : AVG_54 3m HORN 91200-HF VERTICAL Detector : Peak Project : 740120 Mode : 1B</p>



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH09 2452MHz - R	
1+2	Vertical	Fundamental
Peak	 <p> Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 740120 Mode : 1B </p>	Left blank
Avg.	 <p> Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 740120 Mode : 1B </p>	Left blank



2.4GHz 2400~2483.5MHz

WIFI 802.11b (Harmonic @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11b CH01 2412MHz	
1+2	Horizontal	Vertical
<p>Peak Avg.</p>	<p>Site : 03CH10-14Y Condition : PEAK_74 3m HORN_9170_40G_0584 HORIZONTAL Detector : Peak Project : 740120 Mode : 7</p>	<p>Site : 03CH10-14Y Condition : PEAK_74 3m HORN_9170_40G_0584 VERTICAL Detector : Peak Project : 740120 Mode : 7</p>



WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11b CH06 2437MHz	
1+2	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH10-11Y Condition : PEAK_74 3m HORN_9170_40G_0584 HORIZONTAL Detector : Peak Project : 740120 Mode : 8</p>	<p>Site : 03CH10-11Y Condition : PEAK_74 3m HORN_9170_40G_0584 VERTICAL Detector : Peak Project : 740120 Mode : 8</p>



WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11b CH11 2462MHz	
1+2	Horizontal	Vertical
<p>Peak</p> <p>Avg.</p>	<p>Site : 03CH10-11Y Condition : PEAK_74 3m HORN_9170_40G_0584 HORIZONTAL Detector : Peak Project : 740120 Mode : -9</p>	<p>Site : 03CH10-11Y Condition : PEAK_74 3m HORN_9170_40G_0584 VERTICAL Detector : Peak Project : 740120 Mode : -9</p>



2.4GHz 2400~2483.5MHz

WIFI 802.11g (Harmonic @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11g CH01 2412MHz	
1+2	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH10-11Y Condition : PEAK_74 3m HORN_9170_40G_0584 HORIZONTAL Detector : Peak Project : 740120 Mode : 10</p>	<p>Site : 03CH10-11Y Condition : PEAK_74 3m HORN_9170_40G_0584 VERTICAL Detector : Peak Project : 740120 Mode : 10</p>



WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11g CH06 2437MHz	
1+2	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH10-11Y Condition : PEAK_74 3m HORN_9170_40G_0584 HORIZONTAL Detector : Peak Project : 740120 Mode : 11</p>	<p>Site : 03CH10-11Y Condition : PEAK_74 3m HORN_9170_40G_0584 VERTICAL Detector : Peak Project : 740120 Mode : 11</p>



WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11g CH11 2462MHz	
1+2	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH10-11Y Condition : PEAK_74 3m HORN_9170_40G_0584 HORIZONTAL Detector : Peak Project : 740120 Mode : 12</p>	<p>Site : 03CH10-11Y Condition : PEAK_74 3m HORN_9170_40G_0584 VERTICAL Detector : Peak Project : 740120 Mode : 12</p>



2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT20 CH01 2412MHz	
1+2	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH10-14Y Condition : PEAK_74 3m HORN_9170_40G_0584 HORIZONTAL Detector : Peak Project : 740120 Mode : 13</p>	<p>Site : 03CH10-14Y Condition : PEAK_74 3m HORN_9170_40G_0584 VERTICAL Detector : Peak Project : 740120 Mode : 13</p>



WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT20 CH06 2437MHz	
1+2	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH10-11Y Condition : PEAK_74 3m HORN_9170_40G_0584 HORIZONTAL Detector : Peak Project : 740120 Mode : 14</p>	<p>Site : 03CH10-11Y Condition : PEAK_74 3m HORN_9170_40G_0584 VERTICAL Detector : Peak Project : 740120 Mode : 14</p>



WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT20 CH11 2462MHz	
1+2	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH10-11Y Condition : PEAK_74 3m HORN_9170_40G_0584 HORIZONTAL Detector : Peak Project : 740120 Mode : 15</p>	<p>Site : 03CH10-11Y Condition : PEAK_74 3m HORN_9170_40G_0584 VERTICAL Detector : Peak Project : 740120 Mode : 15</p>



2.4GHz 2400~2483.5MHz

WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT40 CH03 2422MHz	
1+2	Horizontal	Vertical
Peak Avg.		



WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT40 CH06 2437MHz	
1+2	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH10-11Y Condition : PEAK_74 3m HORN_9170_40G_0584 HORIZONTAL Detector : Peak Project : 740120 Mode : 17</p>	<p>Site : 03CH10-11Y Condition : PEAK_74 3m HORN_9170_40G_0584 VERTICAL Detector : Peak Project : 740120 Mode : 17</p>



WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT40 CH09 2452MHz	
1+2	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH10-11Y Condition : PEAK_74 3m HORN_9170_40G_0584 HORIZONTAL Detector : Peak Project : 740120 Mode : 18</p>	<p>Site : 03CH10-11Y Condition : PEAK_74 3m HORN_9170_40G_0584 VERTICAL Detector : Peak Project : 740120 Mode : 18</p>



Emission below 1GHz
2.4GHz WIFI 802.11n HT40 (LF)

WIFI	2.4GHz 2400~2483.5MHz	
ANT	802.11n HT40 LF	
1+2	Horizontal	Vertical
QP / Peak	<p>Site : 03C110-11Y Condition : QP-3m-BE-LOG-6111D-LF HORIZONTAL Detector : Peak Project : 740120 Mode : Z1</p>	<p>Site : 03C110-11Y Condition : QP-3m-BE-LOG-6111D-LF VERTICAL Detector : Peak Project : 740120 Mode : Z1</p>




Appendix E. Duty Cycle Plots

Antenna	Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting
1	802.11b	99.024	-	-	10Hz
1	802.11g	93.578	2040	0.49	1kHz
1	2.4GHz 802.11n HT20	94.4	1888	0.53	1kHz
1	2.4GHz 802.11n HT40	89.423	930	1.08	3kHz
1	2.4GHz 802.11n VHT20	94.059	1900	0.53	1kHz
1	2.4GHz 802.11n VHT40	87.85	940	1.06	3kHz
2	802.11b	98.701	-	-	10Hz
2	802.11g	94.393	2020	0.50	1kHz
2	2.4GHz 802.11n HT20	93.651	1888	0.53	1kHz
2	2.4GHz 802.11n HT40	87.736	930	1.08	3kHz
2	2.4GHz 802.11n VHT20	93.137	1900	0.53	1kHz
2	2.4GHz 802.11n VHT40	87.736	930	1.08	3kHz
1+2	802.11b for Ant. 1	98.544	-	-	10Hz
1+2	802.11b for Ant. 2	99.024	-	-	10Hz
1+2	802.11g for Ant. 1	94.393	2020	0.50	1kHz
1+2	802.11g for Ant. 2	94.44	2040	0.49	1kHz
1+2	2.4GHz 802.11n HT20 for Ant. 1	94.4	1888	0.53	1kHz
1+2	2.4GHz 802.11n HT20 for Ant. 2	94.4	1888	0.53	1kHz
1+2	2.4GHz 802.11n HT40 for Ant. 1	87.736	930	1.08	3kHz
1+2	2.4GHz 802.11n HT40 for Ant. 2	87.736	930	1.08	3kHz
1+2	2.4GHz 802.11n VHT20 for Ant. 1	93.069	1880	0.53	1kHz
1+2	2.4GHz 802.11n VHT20 for Ant. 2	93.137	1900	0.53	1kHz
1+2	2.4GHz 802.11n VHT40 for Ant. 1	88.571	930	1.08	3kHz
1+2	2.4GHz 802.11n VHT40 for Ant. 2	86.916	930	1.08	3kHz




SISO <Ant. 1>

802.11b



Date: 14.APR.2017 15:53:58


802.11g



Date: 14.APR.2017 15:58:16




802.11n HT20



Date: 14.APR.2017 16:01:12


802.11n HT40



Date: 15.APR.2017 00:31:11




802.11ac VHT20



Date: 15.APR.2017 00:34:33

802.11ac VHT40




Date: 15.APR.2017 00:37:59




SISO <Ant. 2>

802.11b



Date: 14.APR.2017 15:56:23


802.11g



Date: 14.APR.2017 15:59:19




802.11n HT20



Date: 14.APR.2017 16:02:11


802.11n HT40



Date: 15.APR.2017 00:31:51




802.11ac VHT20



Date: 15.APR.2017 00:35:04

802.11ac VHT40




Date: 15.APR.2017 00:38:38




MIMO <Ant. 1+2(1)>

802.11b



Date: 14.APR.2017 23:30:04


802.11g



Date: 15.APR.2017 00:28:22




802.11n HT20



Date: 14.APR.2017 16:03:13


802.11n HT40



Date: 15.APR.2017 00:32:40




802.11ac VHT20



Date: 15.APR.2017 00:36:01

802.11ac VHT40




Date: 15.APR.2017 00:39:24




MIMO <Ant. 1+2(2)>

802.11b



Date: 14.APR.2017 23:30:37


802.11g



Date: 20.APR.2017 09:48:09




802.11n HT20



Date: 14.APR.2017 16:03:58


802.11n HT40



Date: 15.APR.2017 00:33:25




802.11ac VHT20



Date: 15.APR.2017 00:36:28

802.11ac VHT40



Date: 15.APR.2017 00:39:59