

**Environmental evaluation and exposure limit according to FCC CFR 47part 1,
§1.1307, §1.1310**

The calculation was done to confirm required safe distance for fixed device.

Limit for power density for general population/uncontrolled exposure is 1 mW/cm² for 1500 -100000 MHz frequency range:

The power density P (mW/cm²) = $P_T / 4\pi r^2$, where
 P_T is the maximum equivalent isotropically radiated power (EIRP).

1) The peak output power of 21.6 dBm with 17.5 dBi total antenna gain (please refer to corresponds to the equivalent isotropically radiated power (EIRP) of

$$21.6 \text{ dBm} + 17.5 \text{ dBi} = 39.1 \text{ dBm, which is equal to } 8128 \text{ mW.}$$

The minimum safe distance "r", where RF exposure does not exceed FCC permissible limit, is

$$r = \sqrt{P_T / (P \times 4\pi)} = \sqrt{8128 / 12.56} = 25.4 \text{ cm.}$$

2) In the transmit mode of 2 carrier 1sector (please refer to Table 6.6.2 of the test report) - 2 carriers occupy twice the BW- the total power will be 3 dB higher = 42.1 dBm = 16218 mW

$$r = \sqrt{P_T / (P \times 4\pi)} = \sqrt{16218 / 12.56} = 36 \text{ cm.}$$

General public cannot be exposed to dangerous RF level, a fixed device is located at least 2 m safe distance from the persons.