

RF EXPOSURE REPORT

Product: Out Door Unit

Model Name: CPE12000U PRO

FCC ID: ARA-CPE12000PRO5X

Applicant: Telrad Networks Ltd.

Address: Israel Lod Industrial Center PO Box 6118

Manufacturer: Asiatelco

Address: No 289 Bisheng Road, Building 8, 1F, Zhangjiang Hi-Tech Park, Pudong, Shanghai, PRC

Prepared by: BV 7Layers Communications Technology (Shenzhen) Co. Ltd

Lab Location: No. B102, Dazu Chuangxin Mansion, North of Beihuan Avenue, North Area, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, China

TEL: +86 755 8869 6566

FAX: +86 755 8869 6577

E-MAIL: customerservice.dg@cn.bureauveritas.com

Report No.: SA190116W005

Received Date: Jan. 17, 2019

Test Date: Jul. 17, 2019 ~ Aug. 05, 2019

Issued Date: Aug. 05, 2019

This report should not be used by the client to claim product certification, approval, or endorsement by A2LA or any government agencies.

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

TABLE OF CONTENTS

RF EXPOSURE REPORT.....	1
RELEASE CONTROL RECORD	3
1 CERTIFICATION	4
2 GENERAL INFORMATION	5
2.1 GENERAL DESCRIPTION OF EUT	5
3 RF EXPOSURE	7
3.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)	7
3.2 MPE CALCULATION FORMULA	7
3.3 CLASSIFICATION	7
3.4 CALCULATION RESULT OF MAXIMUM CONDUCTED POWER.....	8



Test Report No.: SA190116W005

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA190116W005	Original release	Aug. 05, 2019



Test Report No.: SA190116W005

1 CERTIFICATION

PRODUCT: Out Door Unit
BRAND NAME: Telrad
MODEL NAME: CPE12000U PRO
APPLICANT: Telrad Networks Ltd.
STANDARDS: **FCC Part 2 (Section 2.1091)**
FCC OET Bulletin 65, Supplement C (01-01)
KDB 447498 D01 General RF Exposure Guidance v06
IEEE C95.1

The above equipment has been tested by **BV 7Layers Communications Technology (Shenzhen) Co. Ltd** and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Alex, **DATE:** Aug. 05, 2019
(Alex Chen / Engineer)

APPROVED BY : Luke Lu, **DATE:** Aug. 05, 2019
(Luke Lu / Manager)

2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

EUT	Out Door Unit
MODEL NO.	CPE12000U PRO
POWER SUPPLY	54Vdc (POE)
MODULATION TYPE	64QAM, 16QAM, QPSK
MODULATION TECHNOLOGY	OFDM
OPERATING FREQUENCY	5150 ~ 5250MHz, 5725 ~ 5850MHz
DEVICE CAPABILITIES	LTE-TDD BAND 46 (10/20MHz BW) Support SISO and MIMO mode: 2TX 4RX
AVERAGE POWER	31.62mW for 5150 ~ 5250MHz(10MHz) 31.62mW for 5725 ~ 5850MHz(10MHz) 31.62mW for 5150 ~ 5250MHz(20MHz) 31.62mW for 5725 ~ 5850MHz(20MHz)
ANTENNA TYPE	Directional Antenna with 21dBi gain
HW VERSION	P2
SW VERSION	KT2A_OT29_TRD_1.0.0.21
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	RJ45 cable: non-shielded, detachable, 1.0 m

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

2. The EUT was powered by the following POE:

POE	
BRAND:	N/A
MODEL:	PSE801G
INPUT:	AC 100-240V, 700mA
OUTPUT:	DC 48-56V, 500mA

3. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

3 RF EXPOSURE

3.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

3.2 MPE CALCULATION FORMULA

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

3.3 CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

3.4 CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

THE WORST CASE IS SISO MODE

Frequency (MHz)	Operating Mode	Antenna Gain (dBi)	Tune-up Power (dBm)	Tune-up Power (mW)	Power Density (mW/cm ²)	limit (mW/cm ²)	PASS / FAIL
5150-5250	QPSK	21	15	31.62	0.79	1.00	PASS
5725-5850	QPSK	21	15	31.62	0.79	1.00	PASS

--END--