

RF Exposure Lab

802 N. Twin Oaks Valley Road, Suite 105 • San Marcos, CA 92069 • U.S.A.
TEL (760) 471-2100 • FAX (760) 471-2121
<http://www.rfexposurelab.com>

CERTIFICATE OF COMPLIANCE SAR EVALUATION

EF Johnson
123 N. State St.
Waseca, MN 56093


Dates of Test: July 16-17, September 24, 2012
Test Report Number: SAR.20120703
Revision A

FCC ID:	ATH2425720
IC Certificate:	933B-2425720
Model(s):	R0235170083
Test Sample:	Engineering Unit Same as Production
Serial Number:	517001208720021
Equipment Type:	Push-To-Talk Handheld Radio for Occupational Use
Classification:	Portable Transmitter Next to Body and In Front of Face
TX Frequency Range:	380 – 470 MHz
Frequency Tolerance:	± 2.5 ppm
Maximum RF Output:	425 MHz – 36.57 dB Conducted
Signal Modulation:	FM
Accessories:	Standard Body Worn Microphone; Body Worn Microphone with Antenna
Antenna Type:	Standard Whip Antenna P/N 501-0017-107
Battery:	Standard Lithium Ion Battery
Application Type:	Certification
FCC Rule Parts:	Part 2, 90
KDB Test Methodology:	KDB 447498 v04, KDB 643646 D01 v01r01
Industry Canada:	RSS-102, Safety Code 6
Maximum SAR Value:	4.670 W/kg
Separation Distance:	25 mm for Face; 0 mm for Body

This wireless mobile and/or portable device has been shown to be compliant for localized specific absorption rate (SAR) for uncontrolled environment/general exposure limits specified in ANSI/IEEE Std. C95.1-1992 and had been tested in accordance with the measurement procedures specified in IEEE 1528-2003, and OET Bulletin 65 Supp. C (See test report).

I attest to the accuracy of the data. All measurements were performed by myself or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

RF Exposure Lab, LLC certifies that no party to this application is subject to a denial of Federal benefits that includes FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 853(a).



Jay M. Moulton
Vice President



Certificate # 2387.01

Table of Contents

1. Introduction	3
SAR Definition [5].....	3
2. SAR Measurement Setup	4
Robotic System.....	4
System Hardware	4
System Description	4
E-Field Probe	5
3. Robot Specifications	7
4. Probe and Dipole Calibration	8
5. Phantom & Simulating Tissue Specifications	9
SAM Phantom.....	9
Head & Body Simulating Mixture Characterization	9
Device Holder	9
6. ANSI/IEEE C95.1 – 1992 RF Exposure Limits [2].....	10
Uncontrolled Environment.....	10
Controlled Environment	10
7. Measurement Uncertainty	11
8. System Validation	12
Tissue Verification.....	12
Test System Verification	12
9. SAR Test Data Summary	13
Procedures Used To Establish Test Signal.....	13
Device Test Condition.....	13
SAR Data Summary – Head SAR in Front of Face Measurements.....	17
SAR Data Summary – Body SAR Measurements	18
10. Test Equipment List	19
11. Conclusion	20
12. References.....	21
Appendix A – System Validation Plots and Data	22
Appendix B – SAR Test Data Plots.....	33
Appendix C – SAR Test Setup Photos	64
Appendix D – Probe Calibration Data Sheets.....	71
Appendix E – Dipole Calibration Data Sheets	92
Appendix F – Phantom Calibration Data Sheets	113

1. Introduction

This measurement report shows compliance of the EF Johnson Model R0235170083 FCC ID: ATH2425720 with FCC Part 2, 1093, ET Docket 93-62 Rules for mobile and portable devices and IC Certificate: 933B-2425720 with RSS102 & Safety Code 6. The FCC have adopted the guidelines for evaluating the environmental effects of radio frequency radiation in ET Docket 93-62 on August 6, 1996 to protect the public and workers from the potential hazards of RF emissions due to FCC regulated portable devices. [1], [6]

The test results recorded herein are based on a single type test of EF Johnson Model R0235170083 and therefore apply only to the tested sample.

The test procedures, as described in ANSI C95.1 – 1999 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [2], ANSI C95.3 – 2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields [3], FCC OET Bulletin 65 Supp. C – 2001 [4], IEEE Std.1528 – 2003 Recommended Practice [5], and Industry Canada Safety Code 6 Limits of Human Exposure to Radiofrequency Electromagnetic Fields in the Frequency Range from 3kHz to 300 GHz were employed.

SAR Definition [5]

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ).

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dV} \right)$$

SAR is expressed in units of watts per kilogram (W/kg). SAR can be related to the electric field at a point by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

where:

σ = conductivity of the tissue (S/m)

ρ = mass density of the tissue (kg/m³)

E = rms electric field strength (V/m)

2. SAR Measurement Setup

Robotic System

The measurements are conducted utilizing the ALSAS-10-U automated dosimetric assessment system. The ALSAS-10-U is designed and manufactured by Aprel Laboratories in Nepean, Ontario, Canada. The system utilizes a Robcomm 3 robot manufactured by ThermoCRS located in Michigan USA.

System Hardware

The system consists of a six axis articulated arm, controller for precise probe positioning (0.05 mm repeatability), a power supply, a teach pendent for teaching area scans, near field probe, an IBM Pentium 4™ 2.66 GHz PC with Windows XP Pro™, and custom software developed to enable communications between the robot controller software and the host operating system.

An amplifier is located on the articulated arm, which is isolated from the custom designed end effector and robot arm. The end effector provides the mechanical touch detection functionality and probe connection interface. The amplifier is functionally validated within the manufacturer's site and calibrated at NCL Calibration Laboratories. A Data Acquisition Card (DAC) is used to collect the signal as detected by the isotropic e-field probe. The DAC manufacturer calibrates the DAC to NIST standards. A formal validation is executed using all mechanical and electronic components to prove conformity of the measurement platform as a whole.

System Description

The ALSAS-10-U has been designed to measure devices within the compliance environment to meet all recognized standards. The system also conforms to standards, which are currently being developed by the scientific and manufacturing community.

The course scan resolution is defined by the operator and reflects the requirements of the standard to which the device is being tested. Precise measurements are made within the predefined course scan area and the values are logged.

The user predefines the sample rate for which the measurements are made so as to ensure that the full duty-cycle of a pulse modulation device is covered during the sample. The following algorithm is an example of the function used by the system for linearization of the output for the probe.

$$V_i = U_i + U_i^2 \bullet \frac{cf}{dcpi}$$



The Aprel E-Field probe is evaluated to establish the diode compression point.

A complex algorithm is then used to calculate the values within the measured points down to a resolution of 1mm. The data from this process is then used to provide the co-ordinates from which the cube scan is created for the determination of the 1 g and 10 g averages.

Cube scan averaging consists of a number of complex algorithms, which are used to calculate the one, and ten gram averages. The basis for the cube scan process is centered on the location where the maximum measured SAR value was found. When a secondary peak value is found which is within 60% of the initial peak value, the system will report this back to the operator who can then assess the need for further analysis of both the peak values prior to the one and ten-gram cube scan averaging process. The algorithm consists of 3D cubic Spline, and Lagrange extrapolation to the surface, which form the matrix for calculating the measurement output for the one and ten gram average values. The resolution for the physical scan integral is user defined with a final calculated resolution down to 1mm.

In-depth analysis for the differential of the physical scanning resolution for the cube scan analysis has been carried out, to identify the optimum setting for the probe positioning steps, and this has been determined at 8mm increments on the X, & Y planes. The reduction of the physical step increment increased the time taken for analysis but did not provide a better uncertainty or return on measured values.

The final output from the system provides data for the area scan measurements, physical and splined (1mm resolution) cube scan with physical and calculated values (1mm resolution).

The overall uncertainty for the methodology and algorithms the ALSAS-10-U used during the SAR calculation was evaluated using the data from IEEE 1528 f3 algorithm:

$$f_3(x, y, z) = A \frac{a^2}{\frac{a^2}{4} + x'^2 + y'^2} \left(e^{-\frac{2z}{a}} + \frac{a^2}{2(a + 2z)^2} \right)$$

The probe used during the measurement process has been assessed to provide values for diode compression. These values are calculated during the probe calibration exercise and are used in the mathematical calculations for the assessment of SAR.

E-Field Probe

The E-field probe used by RF Exposure Lab, LLC, has been fully calibrated and assessed for isotropic, and boundary effect. The probe utilizes a triangular sensor arrangement as detailed in the diagram below right.



The SAR is assessed with the probe which moves at a default height of 4mm from the center of the diode, which is mounted to the sensor, to the phantom surface (Z height). The diagram above right shows how the center of the sensor is defined with the location of the diode placed at the center of the dipole. The 4mm default in the Z axis is the optimum height for assessing SAR where the boundary effect is at its least, with the probe located closest to the phantom surface (boundary).

The manufacturer specified precision of the robot is ± 0.05 mm and the precision of the APREL bottom detection device is ± 0.1 mm. These precisions are calibrated and tested in the manufacturing process of the bottom detection device. A constant distance is maintained because the surface of the phantom is dynamically detected for each point. The surface detection algorithm corrects the position of the robot so that the probe rests on the surface of the phantom. The probe is then moved to the measurement location 2.44 mm above the phantom surface resulting in the probe center location to be at 4.0 mm above the phantom surface. Therefore, the probe sensor will be at 4.0 mm above the phantom surface ± 0.1 mm for each SAR location for frequencies below 3 GHz. The probe is moved to the measurement location 1.44 mm above the phantom surface resulting in the probe center location to be at 2.0 mm above the phantom surface. Therefore, the probe sensor will be at 2.0 mm above the phantom surface ± 0.1 mm for each SAR location for frequencies above 3 GHz.

The probe boundary effect compensation cannot be disabled in the ALSAS-10U testing system. The probe tip will always be at least half a probe tip diameter from the phantom surface. For frequencies up to 3 GHz, the probe diameter is 5 mm. With the sensor offset set at 1.54 mm (default setting), the sensor to phantom gap will be 4.0 mm which is greater than half the probe tip diameter. For frequencies greater than 3 GHz, the probe diameter is 3 mm. With the sensor offset set at 0.56 mm (default setting), the sensor to phantom gap will be 3.0 mm which is greater than half the probe tip diameter.

The separation of the first 2 measurement points in the zoom scan is specified in the test setup software. For frequencies below 3 GHz, the user must specify a zoom scan resolution of less than 6 mm in the z-axis to have the first two measurements within 1 cm of the surface. The z-axis is set to 4 mm as shown on each of the data sheets in Appendix B. For frequencies above 3 GHz, the user must specify a zoom scan resolution of less than 3 mm in the z-axis to have the first two measurements within 5 mm of the surface. The z-axis is set to 2 mm as shown on each of the data sheets in Appendix B.

The zoom scan volume for devices ≤ 3 GHz with a cube scan of 5x5x8 yields a volume of $32 \times 32 \times 28$ mm³. For devices > 3 GHz and < 4.5 GHz, the cube scan of 9x9x9 yields a volume of $32 \times 32 \times 24$ mm³. For devices ≥ 4.5 GHz, the cube scan of 7x7x12 yields a volume of $24 \times 24 \times 22$ mm³.

3. Robot Specifications

Specifications

Positioner:	ThermoCRS, Robot Model: Robocomm 3
Repeatability:	0.05 mm
No. of axis:	6

Data Acquisition Card (DAC) System

Cell Controller

Processor:	Pentium 4™
Clock Speed:	2.66 GHz
Operating System:	Windows XP Pro™

Data Converter

Features:	Signal Amplifier, End Effector, DAC
Software:	ALSAS 10-U Software

E-Field Probe

Model:	Various See Probe Calibration Sheet
Serial Number:	Various See Probe Calibration Sheet
Construction:	Triangular Core Touch Detection System
Frequency:	10MHz to 6GHz

Phantom

Phantom:	Uniphantom, Right Phantom, Left Phantom
----------	---



4. Probe and Dipole Calibration

See Appendix D and E.

5. Phantom & Simulating Tissue Specifications

SAM Phantom



The Aprel system utilizes three separate phantoms. Each phantom for SAR assessment testing is a low loss dielectric shell, with shape and dimensions derived from the anthropomorphic data of the 90th percentile adult male head dimensions as tabulated by the US Army. The SAM phantom shell is bisected along the mid sagittal plane into right and left halves. The perimeter sidewalls of each phantom half is extended to allow filling with liquid to a depth of 15 cm that is sufficient to minimize reflections from the upper surface [5]. The Uni-Phantom is used to conduct body measurements and head to face measurements. The depth of the phantom allows for 15 cm of tissue material to be filled within the phantom. See photos in Appendix C.

Head & Body Simulating Mixture Characterization

The head and body mixtures consist of the material based on the table listed below. The mixture is calibrated to obtain proper dielectric constant (permittivity) and conductivity of the desired tissue. Body tissue parameters that have not been specified in P1528 are derived from the issue dielectric parameters computed from the 4-Cole-Cole equations.

Table 5.1 Typical Composition of Ingredients for Tissue

Ingredients	Simulating Tissue	
	450 MHz Head	450 MHz Body
Mixing Percentage		
Water	38.56	51.16
Sugar	56.32	46.78
Salt	3.95	1.49
HEC	0.98	0.52
Bactericide	0.19	0.05
DGBE	0.00	0.00
Dielectric Constant	Target	43.50
Conductivity (S/m)	Target	0.87
		56.70
		0.94

Device Holder



In combination with the SAM phantom, the mounting device enables the rotation of the mounted transmitter in spherical coordinates whereby the rotation point is the ear opening. The devices can easily, accurately, and repeatably be positioned according to the FCC specifications. The device holder can be locked at different phantom locations (left head, right head, and uni-phantom).

6. ANSI/IEEE C95.1 – 1992 RF Exposure Limits [2]

Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table 6.1 Human Exposure Limits

	UNCONTROLLED ENVIRONMENT General Population (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT Professional Population (W/kg) or (mW/g)
SPATIAL PEAK SAR ¹ Head	1.60	8.00
SPATIAL AVERAGE SAR ² Whole Body	0.08	0.40
SPATIAL PEAK SAR ³ Hands, Feet, Ankles, Wrists	4.00	20.00

¹ The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

² The Spatial Average value of the SAR averaged over the whole body.

³ The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

7. Measurement Uncertainty

Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	$c_i^1 (1-g)$	$c_i^1 (10-g)$	Standard Uncertainty (1-g) %	Standard Uncertainty (10-g) %	v_i
Measurement System								
Probe Calibration	3.5	normal	1	1	1	3.5	3.5	∞
Axial Isotropy	3.7	rectangular	$\sqrt{3}$	0.7	0.7	1.5	1.5	∞
Hemispherical Isotropy	10.9	rectangular	$\sqrt{3}$	0.7	0.7	4.4	4.4	∞
Boundary Effect	1.0	rectangular	$\sqrt{3}$	1	1	0.6	0.6	∞
Linearity	4.7	rectangular	$\sqrt{3}$	1	1	2.7	2.7	∞
Detection Limit	1.0	rectangular	$\sqrt{3}$	1	1	0.6	0.6	∞
Readout Electronics	1.0	normal	1	1	1	1.0	1.0	∞
Response Time	0.8	rectangular	$\sqrt{3}$	1	1	0.5	0.5	∞
Integration Time	1.7	rectangular	$\sqrt{3}$	1	1	1.0	1.0	∞
RF Ambient Condition	3.0	rectangular	$\sqrt{3}$	1	1	1.7	1.7	∞
Probe Positioner Mech. Restriction	0.4	rectangular	$\sqrt{3}$	1	1	0.2	0.2	∞
Probe Positioning with respect to Phantom Shell	2.9	rectangular	$\sqrt{3}$	1	1	1.7	1.7	∞
Extrapolation and Integration	3.7	rectangular	$\sqrt{3}$	1	1	2.1	2.1	∞
Test Sample Positioning	4.0	normal	1	1	1	4.0	4.0	7
Device Holder Uncertainty	2.0	normal	1	1	1	2.0	2.0	2
Drift of Output Power	4.2	rectangular	$\sqrt{3}$	1	1	2.4	2.4	∞
Phantom and Setup								
Phantom Uncertainty (shape & thickness tolerance)	3.4	rectangular	$\sqrt{3}$	1	1	2.0	2.0	∞
Liquid Conductivity (target)	5.0	rectangular	$\sqrt{3}$	0.7	0.5	2.0	1.4	∞
Liquid Conductivity (meas.)	0.5	normal	1	0.7	0.5	0.4	0.3	5
Liquid Permittivity (target)	5.0	rectangular	$\sqrt{3}$	0.6	0.5	1.7	1.4	∞
Liquid Permittivity (meas.)	1.0	normal	1	0.6	0.5	0.6	0.5	5
Combined Uncertainty		RSS				9.6	9.4	>500
Combined Uncertainty (coverage factor=2)		Normal (k=2)				19.1	18.8	>500

8. System Validation

Tissue Verification

Table 8.1 Measured Tissue Parameters

		450 MHz Head		450 MHz Body		450 MHz Body	
Date(s)		Jul. 17, 2012		Jul. 16, 2012		Sep. 24, 2012	
Liquid Temperature (°C)	20.0	Target	Measured	Target	Measured	Target	Measured
Dielectric Constant: ϵ	43.50	43.20	56.70	56.70	56.59	56.46	
Conductivity: σ	0.87	0.89	0.94	0.94	0.96	0.95	

See Appendix A for data printout.

Test System Verification

Prior to assessment, the system is verified to the $\pm 10\%$ of the specifications at the test frequency by using the system kit. Power is normalized to 1 watt. (Graphic Plots Attached)

Table 8.2 System Dipole Validation Target & Measured

Plot	Date	Test Frequency	Targeted SAR _{1g} (W/kg)	Measure SAR _{1g} (W/kg)	Tissue Used for Verification	Deviation (%)
1	16-Jul-2012	450 MHz	5.05	5.19	Body	+ 2.77
2	17-Jul-2012	450 MHz	4.99	4.98	Head	- 0.20
3	24-Sep-2012	450 MHz	5.05	5.07	Body	+ 0.40

See Appendix A for data plots.




Figure 8.1 Dipole Validation Test Setup

Note: KDB 450824 was applied for probe calibration frequencies greater than or equal to 50 MHz of the DUT frequencies.

9. SAR Test Data Summary

See Measurement Result Data Pages

See Appendix B for SAR Test Data Plots.

See Appendix C for SAR Test Setup Photos.

Procedures Used To Establish Test Signal

The device was either placed into simulated transmit mode using the manufacturer's test codes or the actual transmission is activated through a base station simulator or similar equipment. See data pages for actual procedure used in measurement.

Device Test Condition

In order to verify that the device was tested at full power, conducted output power measurements were performed before and after each SAR measurement to confirm the output power unless otherwise noted. If a conducted power deviation of more than 5% occurred, the test was repeated. The power drift of each test is measured at the start of the test and again at the end of the test. The drift percentage is calculated by the formula $((\text{end/start})-1)*100$ and rounded to three decimal places. The drift percentage is calculated into the resultant SAR value on the data sheet for each test.

The EUT was tested in the face position with the front of the device 25 mm away from the flat phantom. The EUT was then tested in the body position with the belt clip in contact with the flat phantom. The microphone which did not contain an antenna was connected to the device for the body testing. The microphone containing an antenna on the device was tested in the face (25 mm gap) and body position (0 mm gap). For each of the tests conducted, the device was set to continuously transmit at a maximum output power on the channel specified in the test data. The SAR was scaled to 50% duty cycle per KDB 643646 D01 v01r01. All test reductions were reduced based on the reductions in KDB 643646 D01 v01r01.

Body Measurements	
	Lilon High Capacity Battery
Audio Accessory	Antenna A
Speaker/Microphone A	Tested
Speaker/Microphone B	Not Tested
Speaker/Microphone C	Not Tested
Speaker/Microphone D	Tested
Speaker/Microphone E	Not Tested
Speaker/Microphone F	Not Tested

Face Measurements	
	Lilon High Capacity Battery
Audio Accessory	Antenna A
Speaker/Microphone A	Not Tested
Speaker/Microphone B	Not Tested
Speaker/Microphone C	Not Tested
Speaker/Microphone D	Tested
Speaker/Microphone E	Not Tested
Speaker/Microphone F	Not Tested

ATH2425770 Accessories

Accessory	Description	Part Number
Battery	Lilon High Capacity Battery	587-5700-374
Belt Clip	Belt Clip 2.25"	585-5100-128
Antenna	1/2 Wave Antenna 450 MHz	501-0017-107
Audio Accessory A	Standard Speaker/mic 18" cable	589-3600-052-18
Audio Accessory B	Standard Speaker/mic 25" cable	589-3600-052-25
Audio Accessory C	Standard Speaker/mic 30" cable	589-3600-052-30
Audio Accessory D	Public Safety Speaker/mic (with antenna connector) 18" cable	589-3600-056-18
Audio Accessory E	Public Safety Speaker/mic (with antenna connector) 25" cable	589-3600-056-25
Audio Accessory F	Public Safety Speaker/mic (with antenna connector) 30" cable	589-3600-056-30

Only one battery was supplied for this testing. Speaker/Microphone A-C do not have any radiating source on the accessory. Therefore, one representative accessory was tested for body measurement per the table. For speaker/microphone D-E, the accessory contains an antenna. The only difference between the three accessories is the length of the cable. The length would not have an effect on the overall SAR value. Therefore, the 18" accessory version was tested in both the body and face position.

Band	Mode	Channel	Frequency (MHz)	Conducted Power (dBm)
				Main
450 MHz	FM	Low	380 MHz	36.32
		Low	406.1 MHz	36.52
		Mid	425 MHz	36.57
		Mid	450 MHz	36.49
		High	460 MHz	36.50
		High	470 MHz	36.53

Conducted Average Power Measurements

For US bands, per KDB 447498 D01 v04 page 7 section 6) c), the number of channels required to be tested is as follows:

$$F_{\text{high}} = 470 \text{ MHz}$$

$$F_c = 438 \text{ MHz}$$

$$F_{\text{low}} = 406.1 \text{ MHz}$$

$$N_c = \text{Round} \{ [100(f_{\text{high}} - f_{\text{low}})/f_c]^{0.5} \times (f_c/100)^{0.2} \} = \text{Round} \{ [100(470-406.1)/438]^{0.5} \times (438/100)^{0.2} \} = 5$$

Therefore, for the frequency band from 406.1 MHz to 470 MHz, 5 channels are required for testing.

For full band capability, per KDB 447498 D01 v04 page 7 section 6) c), the number of channels required to be tested is as follows:

$$F_{\text{high}} = 470 \text{ MHz}$$

$$F_c = 425 \text{ MHz}$$

$$F_{\text{low}} = 380 \text{ MHz}$$

$$N_c = \text{Round} \{ [100(f_{\text{high}} - f_{\text{low}})/f_c]^{0.5} \times (f_c/100)^{0.2} \} = \text{Round} \{ [100(470-380)/425]^{0.5} \times (425/100)^{0.2} \} = 6$$

Therefore, for the frequency band from 380 MHz to 470 MHz, 6 channels are required for testing.

Head SAR – In Front of Face (Handset)			
Antenna (MHz)	Channel Freq. (MHz)	Default Battery ¹	
		Measured Power (W)	Measure SAR (W/kg)
380 – 470	380	36.32	²
	406.1	36.52	²
	425	36.57	1.735
	450	36.49	²
	460	36.50	²
	470	36.53	²

¹See Accessory table on page 14 of this report.

²Measurement was reduced per KDB 643646 D01 v01r01 page 2 section 1) A) I) a).

Head SAR – In Front of Face (Audio Accessory D)			
Antenna (MHz)	Channel Freq. (MHz)	Default Battery ¹	
		Measured Power (W)	Measure SAR (W/kg)
380 – 470	380	36.32	²
	406.1	36.52	²
	425	36.57	1.170
	450	36.49	²
	460	36.50	²
	470	36.53	²

¹See Accessory table on page 14 of this report.

²Measurement was reduced per KDB 643646 D01 v01r01 page 2 section 1) A) I) a).

Body SAR					
Antenna (MHz)	Channel Freq. (MHz)	Default Battery ¹			
		Body Worn Device (Belt Clip) ¹			
		Audio Acc. A ^{1,2}	Audio Acc. D ^{1,3}		
380 – 470	Measured Power (W)	Calculated SAR (W/kg)	Calculated SAR (W/kg)		
	380	2.985	2.307		
	406.1	4.819	4.201		
	425	4.411	4.670		
	450	3.944	3.630		
	460	4.233	3.774		
	470	3.530	3.034		

¹See Accessory table on page 14 of this report.

²Audio Accessories B & C are the same as A with the exception of the length of the cable. See page 14 for details.

³Audio Accessories E & F are the same as D with the exception of the length of the cable. See page 14 for details.

SAR Data Summary – Head SAR in Front of Face Measurements

MEASUREMENT RESULTS

Gap	Plot	Configuration	Frequency		Modulation	Antenna	End Power (dBm)	SAR (W/kg)	SAR (W/kg) 50% Duty Cycle
			MHz	Ch.					
25 mm	1	Handset	425	2	FM	Standard	36.57	3.469	1.735
	2	Microphone with Antenna	425	2	FM	Standard	36.57	2.339	1.170

Body
8.0 W/kg (mW/g)
averaged over 1 gram

1. Battery is fully charged for all tests.

Power Measured Conducted ERP EIRP

2. SAR Measurement

Phantom Configuration Left Head Uniphantom Right Head

SAR Configuration Head Body

3. Test Signal Call Mode

Test Code Base Station Simulator

4. Test Configuration

With Belt Clip Without Belt Clip N/A

5. Tissue Depth is at least 15.0 cm



Jay M. Moulton
Vice President

Note: SAR Tested on the Highest output power channel. When the measured channel is less than 3.5 W/kg, the remaining channels are not required to be tested per KDB 643646 D01 v01r01 page 2 section 1) A) I) a). The SAR is calculated for the 50% duty cycle for PTT devices. The testing was conducted with the device 25 mm from the flat phantom. All testing was conducted per KDB 447498 v04, 643646 D01 v01r01 and OET Bulletin 65. See the photo in Appendix C a pictorial of the setup and labeling of the test locations.

SAR Data Summary – Body SAR Measurements

MEASUREMENT RESULTS

Gap	Plot	Configuration	Frequency		Modulation	Antenna	End Power (dBm)	SAR (W/kg)	SAR (W/kg) 50% Duty Cycle
			MHz	Ch.					
25 mm	3	Handset	380	1	FM	Standard	36.32	5.970	2.985
	4		406.1	2	FM	Standard	36.52	9.638	4.819
	5		425	3	FM	Standard	36.57	8.821	4.411
	6		450	4	FM	Standard	36.49	7.887	3.944
	7		460	5	FM	Standard	36.50	8.465	4.233
	8		470	6	FM	Standard	36.53	7.060	3.530
	9	Microphone with Antenna	380	1	FM	Standard	36.32	4.613	2.307
	10		406.1	2	FM	Standard	36.52	8.401	4.201
	11		425	3	FM	Standard	36.57	9.340	4.670
	12		450	4	FM	Standard	36.49	7.260	3.630
	13		460	5	FM	Standard	36.50	7.548	3.774
	14		470	6	FM	Standard	36.53	6.068	3.034

Body
8.0 W/kg (mW/g)
averaged over 1 gram

1. Battery is fully charged for all tests.

Power Measured

Conducted

ERP

EIRP

2. SAR Measurement

Phantom Configuration

Left Head

Uniphantom

Right Head

SAR Configuration

Head

Body

3. Test Signal Call Mode

Test Code

Base Station Simulator

4. Test Configuration

With Belt Clip

Without Belt Clip

N/A

5. Tissue Depth is at least 15.0 cm



Jay M. Moulton
Vice President

Note: SAR Tested on the Highest output power channel. When the measured channel is less than 3.5 W/kg, the remaining channels are not required to be tested per KDB 643646 D01 v01r01 page 2 section 1) A) I) a). The SAR is calculated for the 50% duty cycle for PTT devices. The testing was conducted with the device 0 mm from the flat phantom. All testing was conducted per KDB 447498 v04, 643646 D01 v01r01 and OET Bulletin 65. See the photo in Appendix C a pictorial of the setup and labeling of the test locations.

10. Test Equipment List

Table 10.1 Equipment Specifications

Type	Calibration Due Date	Calibration Done Date	Serial Number
ThermoCRS Robot	N/A	N/A	RAF0338198
ThermoCRS Controller	N/A	N/A	RCF0338224
ThermoCRS Teach Pendant (Joystick)	N/A	N/A	STP0334405
IBM Computer, 2.66 MHz P4	N/A	N/A	8189D8U KCPR08N
Aprel E-Field Probe ALS-E020	09/07/2012	09/07/2011	RFE-217
RF Exposure Lab Large Phantom	N/A	N/A	001
Aprel Validation Dipole ALS-D-450-S-2 Head	01/12/2012	01/12/2010	RFE-362
Aprel Validation Dipole ALS-D-450-S-2 Body	01/19/2012	01/19/2011	RFE-362
Agilent N1911A Power Meter	03/30/2012	03/30/2011	GB45100254
Agilent N1922A Power Sensor	03/30/2012	03/30/2011	MY45240464
Advantest R3261A Spectrum Analyzer	03/30/2012	03/30/2011	31720068
Agilent (HP) 8350B Signal Generator	03/31/2012	03/31/2011	2749A10226
Agilent (HP) 83525A RF Plug-In	03/31/2012	03/31/2011	2647A01172
Agilent (HP) 8753C Vector Network Analyzer	03/30/2012	03/30/2011	3135A01724
Agilent (HP) 85047A S-Parameter Test Set	03/31/2012	03/31/2011	2904A00595
Aprel Dielectric Probe Assembly	N/A	N/A	0011
Head Equivalent Matter (450 MHz)	N/A	N/A	N/A
Body Equivalent Matter (450 MHz)	N/A	N/A	N/A

11. Conclusion

The SAR measurement indicates that the EUT complies with the RF radiation exposure limits of the FCC. These measurements are taken to simulate the RF effects exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The tested device complies with the requirements in respect to all parameters subject to the test. The test results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body is a very complex phenomena that depends on the mass, shape, and size of the body; the orientation of the body with respect to the field vectors; and, the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because innumerable factors may interact to determine the specific biological outcome of an exposure to electromagnetic fields, any protection guide shall consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables.

12. References

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radio Frequency Radiation, August 1996
- [2] ANSI/IEEE C95.1 – 1992, American National Standard Safety Levels with respect to Human Exposure to Radio Frequency Electromagnetic Fields, 300kHz to 100GHz, New York: IEEE, 1992.
- [3] ANSI/IEEE C95.3 – 1992, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields – RF and Microwave, New York: IEEE, 1992.
- [4] Federal Communications Commission, OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01), Evaluating Compliance with FCC Guidelines for Human Exposure to Radio Frequency Electromagnetic Fields, June 2001.
- [5] IEEE Standard 1528 – 2003, IEEE Recommended Practice for Determining the Peak-Spatial Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communication Devices: Measurement Techniques, October 2003.
- [6] Industry Canada, RSS – 102e, Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands), March 2010.
- [7] Health Canada, Safety Code 6, Limits of Human Exposure to Radiofrequency Electromagnetic Fields in the Frequency Range from 3kHz to 300 GHz, 2009.

Appendix A – System Validation Plots and Data

 Test Result for UIM Dielectric Parameter
 Tue 17/Jul/2012 08:09:02
 Freq Frequency(GHz)
 FCC_eH FCC OET 65 Supplement C (June 2001) Limits for Head Epsilon
 FCC_sH FCC OET 65 Supplement C (June 2001) Limits for Head Sigma
 Test_e Epsilon of UIM
 Test_s Sigma of UIM

Freq	FCC_eH	FCC_sH	Test_e	Test_s
0.3700	44.46	0.87	44.03	0.87
0.3800	44.34	0.87	43.90	0.87
0.3900	44.22	0.87	43.89	0.87
0.4000	44.10	0.87	43.76	0.88
0.4100	43.98	0.87	43.65	0.88
0.4200	43.86	0.87	43.53	0.88
0.4250	43.80	0.87	43.47	0.88*
0.4300	43.74	0.87	43.40	0.88
0.4400	43.62	0.87	43.29	0.89
0.4500	43.50	0.87	43.20	0.89
0.4600	43.45	0.87	43.13	0.89
0.4700	43.40	0.87	43.07	0.89
0.4800	43.34	0.87	43.00	0.89

* value interpolated

 Test Result for UIM Dielectric Parameter
 Mon 16/Jul/2012 07:23:25
 Freq Frequency(GHz)
 FCC_eH FCC Bulletin 65 Supplement C (June 2001) Limits for Head Epsilon
 FCC_sH FCC Bulletin 65 Supplement C (June 2001) Limits for Head Sigma
 FCC_eB FCC Limits for Body Epsilon
 FCC_sB FCC Limits for Body Sigma
 Test_e Epsilon of UIM
 Test_s Sigma of UIM

Freq	FCC_eB	FCC_sB	Test_e	Test_s
0.3700	57.50	0.93	57.33	0.92
0.3800	57.40	0.93	57.22	0.92
0.3900	57.30	0.93	57.12	0.92
0.4000	57.20	0.93	57.01	0.93
0.4100	57.10	0.93	56.92	0.93
0.4200	57.00	0.94	56.84	0.93
0.4250	56.95	0.94	56.80	0.94*
0.4300	56.90	0.94	56.75	0.94
0.4400	56.80	0.94	56.67	0.95
0.4500	56.70	0.94	56.59	0.96
0.4600	56.66	0.94	56.50	0.96
0.4700	56.62	0.94	56.42	0.97
0.4800	56.58	0.94	56.36	0.97

* value interpolated

Test Result for UIM Dielectric Parameter

Mon 24/Sep/2012 07:53:25

Freq Frequency (GHz)

FCC_eH FCC Bulletin 65 Supplement C (June 2001) Limits for Head Epsilon

FCC_sH FCC Bulletin 65 Supplement C (June 2001) Limits for Head Sigma

FCC_eB FCC Limits for Body Epsilon

FCC_sB FCC Limits for Body Sigma

Test_e Epsilon of UIM

Test_s Sigma of UIM

Freq	FCC_eB	FCC_sB	Test_e	Test_s
0.3700	57.50	0.93	57.30	0.91
0.3800	57.40	0.93	57.19	0.92
0.3900	57.30	0.93	57.10	0.92
0.4000	57.20	0.93	57.01	0.92
0.4061	57.16	0.93	56.97	0.93*
0.4100	57.10	0.93	56.90	0.93
0.4200	57.00	0.94	56.79	0.93
0.4250	56.95	0.94	56.73	0.94*
0.4300	56.90	0.94	56.67	0.94
0.4400	56.80	0.94	56.55	0.95
0.4500	56.70	0.94	56.46	0.95
0.4600	56.66	0.94	56.41	0.96
0.4700	56.62	0.94	56.37	0.96
0.4800	56.58	0.94	56.32	0.97

* value interpolated

SAR Test Report - Plot 1

By Operator : Jay
Measurement Date : 16-Jul-2012
Starting Time : 16-Jul-2012 07:34:53 AM
End Time : 16-Jul-2012 07:52:17 AM
Scanning Time : 1044 secs

Product Data

Device Name : Validation
Serial No. : 450
Type : Dipole
Model : ALS-D-450-S-2
Frequency : 450.00 MHz
Max. Transmit Pwr : 0.1 W
Drift Time : 0 min(s)
Length : 270 mm
Width : 3.6 mm
Depth : 166.7 mm
Antenna Type : Internal
Orientation : Touch
Power Drift-Start : 0.498 W/kg
Power Drift-Finish: 0.483 W/kg
Power Drift (%) : -3.010

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : System Default
Location : Center
Description : Uni-Phantom

Tissue Data

Type : BODY
Serial No. : 450
Frequency : 450.00 MHz
Last Calib. Date : 16-Jul-2012
Temperature : 20.00 °C
Ambient Temp. : 23.00 °C
Humidity : 49.00 RH%
Epsilon : 56.59 F/m
Sigma : 0.96 S/m
Density : 1000.00 kg/cu. m

Probe Data


Name : RFEL 217
Model : E020
Type : E-Field Triangle
Serial No. : 217
Last Calib. Date : 07-Sep-2011
Frequency : 450.00 MHz
Duty Cycle Factor: 1
Conversion Factor: 6
Probe Sensitivity: 1.20 1.20 1.20 μ V/ (V/m)²
Compression Point: 95.00 mV
Offset : 1.56 mm

Measurement Data

Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 20.00 °C
Ambient Temp. : 23.00 °C
Set-up Date : 16-Jul-2012
Set-up Time : 11:01:10 AM
Area Scan : 6x9x1 : Measurement x=10mm, y=10mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm


Other Data

DUT Position : Touch
Separation : 15 mm
Channel : Mid



1 gram SAR value : 0.519 W/kg
10 gram SAR value : 0.352 W/kg
Area Scan Peak SAR : 0.537 W/kg
Zoom Scan Peak SAR : 0.796 W/kg

SAR-Z Axis
at Hotspot x:5.25 y:-0.17



SAR Test Report - Plot 2

By Operator : Jay
Measurement Date : 17-Jul-2012
Starting Time : 17-Jul-2012 08:12:09 AM
End Time : 17-Jul-2012 08:29:03 AM
Scanning Time : 1014 secs

Product Data

Device Name : Validation
Serial No. : 450
Type : Dipole
Model : ALS-D-450-S-2
Frequency : 450.00 MHz
Max. Transmit Pwr : 0.1 W
Drift Time : 0 min(s)
Length : 270 mm
Width : 3.6 mm
Depth : 166.7 mm
Antenna Type : Internal
Orientation : Touch
Power Drift-Start : 0.535 W/kg
Power Drift-Finish: 0.527 W/kg
Power Drift (%) : -1.498

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : System Default
Location : Center
Description : Uni-Phantom

Tissue Data

Type : HEAD
Serial No. : 450
Frequency : 450.00 MHz
Last Calib. Date : 17-Jul-2012
Temperature : 20.00 °C
Ambient Temp. : 23.00 °C
Humidity : 49.00 RH%
Epsilon : 43.20 F/m
Sigma : 0.89 S/m
Density : 1000.00 kg/cu. m

Probe Data


Name : Probe 217 - RFEL
Model : E020
Type : E-Field Triangle
Serial No. : 217
Last Calib. Date : 07-Sep-2011
Frequency : 450.00 MHz
Duty Cycle Factor: 1
Conversion Factor: 5.8
Probe Sensitivity: 1.20 1.20 1.20 μ V/ (V/m)²
Compression Point: 95.00 mV
Offset : 1.56 mm

Measurement Data


Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 20.00 °C
Ambient Temp. : 23.00 °C
Set-up Date : 17-Jul-2012
Set-up Time : 11:01:10 AM
Area Scan : 5x9x1 : Measurement x=15mm, y=15mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Touch
Separation : 15 mm
Channel : Mid



1 gram SAR value : 0.498 W/kg
10 gram SAR value : 0.346 W/kg
Area Scan Peak SAR : 0.522 W/kg
Zoom Scan Peak SAR : 0.693 W/kg



SAR Test Report - Plot 3

By Operator : Jay
Measurement Date : 24-Sep-2012
Starting Time : 24-Sep-2012 08:00:41 AM
End Time : 24-Sep-2012 08:15:49 AM
Scanning Time : 908 secs

Product Data

Device Name : Validation
Serial No. : 450
Type : Dipole
Model : ALS-D-450-S-2
Frequency : 450.00 MHz
Max. Transmit Pwr : 0.1 W
Drift Time : 0 min(s)
Length : 270 mm
Width : 3.6 mm
Depth : 166.7 mm
Antenna Type : Internal
Orientation : Touch
Power Drift-Start : 0.499 W/kg
Power Drift-Finish: 0.482 W/kg
Power Drift (%) : -3.406

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : System Default
Location : Center
Description : Uni-Phantom

Tissue Data

Type : BODY
Serial No. : 450
Frequency : 450.00 MHz
Last Calib. Date : 24-Sep-2012
Temperature : 20.00 °C
Ambient Temp. : 23.00 °C
Humidity : 49.00 RH%
Epsilon : 56.46 F/m
Sigma : 0.95 S/m
Density : 1000.00 kg/cu. m

Probe Data


Name : Probe 215 - RFEL
Model : E020
Type : E-Field Triangle
Serial No. : 215
Last Calib. Date : 23-Aug-2012
Frequency : 450.00 MHz
Duty Cycle Factor: 1
Conversion Factor: 6
Probe Sensitivity: 1.20 1.20 1.20 μ V/ (V/m)²
Compression Point: 95.00 mV
Offset : 1.56 mm

Measurement Data

Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 20.00 °C
Ambient Temp. : 25.00 °C
Set-up Date : 24-Sep-2012
Set-up Time : 9:21:48 AM
Area Scan : 5x7x1 : Measurement x=10mm, y=10mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm


Other Data

DUT Position : Touch
Separation : 15 mm
Channel : Mid



1 gram SAR value : 0.507 W/kg
10 gram SAR value : 0.390 W/kg
Area Scan Peak SAR : 0.694 W/kg
Zoom Scan Peak SAR : 0.791 W/kg

SAR-Z Axis
at Hotspot x:5.25 y:-0.17



Appendix B – SAR Test Data Plots

SAR Test Report - Plot 1

By Operator : Jay
Measurement Date : 17-Jul-2012
Starting Time : 17-Jul-2012 08:39:08 AM
End Time : 17-Jul-2012 09:01:55 AM
Scanning Time : 1367 secs

Product Data

Device Name : EF Johnson
Serial No. : 517001208720021
Mode : FM
Model : R0235170083
Frequency : 425.00 MHz
Max. Transmit Pwr : 4.539 W
Drift Time : 0 min(s)
Length : 166 mm
Width : 66 mm
Depth : 40 mm
Antenna Type : Stub
Orientation : Face of Handset
Power Drift-Start : 3.274 W/kg
Power Drift-Finish: 3.135 W/kg
Power Drift (%) : -4.239

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : System Default
Location : Center
Description : Uni-Phantom

Tissue Data

Type : HEAD
Serial No. : 425
Frequency : 425.00 MHz
Last Calib. Date : 17-Jul-2012
Temperature : 20.00 °C
Ambient Temp. : 23.00 °C
Humidity : 49.00 RH%
Epsilon : 43.47 F/m
Sigma : 0.88 S/m
Density : 1000.00 kg/cu. m

Probe Data


Name : RFEL 217
Model : E020
Type : E-Field Triangle
Serial No. : 217
Last Calib. Date : 07-Sep-2011
Frequency : 450.00 MHz
Duty Cycle Factor: 1
Conversion Factor: 5.8
Probe Sensitivity: 1.20 1.20 1.20 μ V/ (V/m)²
Compression Point: 95.00 mV
Offset : 1.56 mm

Measurement Data

Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 20.00 °C
Ambient Temp. : 23.00 °C
Set-up Date : 17-Jul-2012
Set-up Time : 7:08:47 AM
Area Scan : 7x11x1 : Measurement x=15mm, y=15mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm


Other Data

DUT Position : Face of Handset
Separation : 25 mm
Channel : Mid



1 gram SAR value : 3.469 W/kg
10 gram SAR value : 2.606 W/kg
Area Scan Peak SAR : 3.549 W/kg
Zoom Scan Peak SAR : 4.474 W/kg

SAR-Z Axis
at Hotspot x:15.12 y:-6.94



SAR Test Report - Plot 2

By Operator : Jay
Measurement Date : 17-Jul-2012
Starting Time : 17-Jul-2012 09:17:04 AM
End Time : 17-Jul-2012 09:39:54 AM
Scanning Time : 1370 secs

Product Data

Device Name : EF Johnson
Serial No. : 517001208720021
Mode : FM
Model : R0235170083
Frequency : 425.00 MHz
Max. Transmit Pwr : 4.539 W
Drift Time : 0 min(s)
Length : 75 mm
Width : 64 mm
Depth : 26 mm
Antenna Type : Stub
Orientation : Face of Microphone
Power Drift-Start : 1.954 W/kg
Power Drift-Finish: 2.029 W/kg
Power Drift (%) : 3.836

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : System Default
Location : Center
Description : Uni-Phantom

Tissue Data

Type : HEAD
Serial No. : 425
Frequency : 425.00 MHz
Last Calib. Date : 17-Jul-2012
Temperature : 20.00 °C
Ambient Temp. : 23.00 °C
Humidity : 49.00 RH%
Epsilon : 43.47 F/m
Sigma : 0.88 S/m
Density : 1000.00 kg/cu. m

Probe Data


Name : RFEL 217
Model : E020
Type : E-Field Triangle
Serial No. : 217
Last Calib. Date : 07-Sep-2011
Frequency : 450.00 MHz
Duty Cycle Factor: 1
Conversion Factor: 5.8
Probe Sensitivity: 1.20 1.20 1.20 μ V/ (V/m)²
Compression Point: 95.00 mV
Offset : 1.56 mm

Measurement Data

Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 20.00 °C
Ambient Temp. : 23.00 °C
Set-up Date : 17-Jul-2012
Set-up Time : 7:08:47 AM
Area Scan : 7x11x1 : Measurement x=15mm, y=15mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Face of Microphone
Separation : 25 mm
Channel : Mid



1 gram SAR value : 2.339 W/kg
10 gram SAR value : 1.730 W/kg
Area Scan Peak SAR : 2.403 W/kg
Zoom Scan Peak SAR : 3.032 W/kg

SAR Test Report - Plot 3

By Operator : Jay
Measurement Date : 16-Jul-2012
Starting Time : 16-Jul-2012 08:49:50 AM
End Time : 16-Jul-2012 09:12:42 AM
Scanning Time : 1372 secs

Product Data

Device Name : EF Johnson
Serial No. : 517001208720021
Mode : FM
Model : R0235170083
Frequency : 380.00 MHz
Max. Transmit Pwr : 4.285 W
Drift Time : 0 min(s)
Length : 166 mm
Width : 66 mm
Depth : 40 mm
Antenna Type : Stub
Orientation : Back of Handset
Power Drift-Start : 5.780 W/kg
Power Drift-Finish: 5.520 W/kg
Power Drift (%) : -4.490

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : System Default
Location : Center
Description : Uni-Phantom

Tissue Data

Type : BODY
Serial No. : 380
Frequency : 380.00 MHz
Last Calib. Date : 16-Jul-2012
Temperature : 20.00 °C
Ambient Temp. : 23.00 °C
Humidity : 49.00 RH%
Epsilon : 57.22 F/m
Sigma : 0.92 S/m
Density : 1000.00 kg/cu. m

Probe Data


Name : RFEL 217
Model : E020
Type : E-Field Triangle
Serial No. : 217
Last Calib. Date : 07-Sep-2011
Frequency : 450.00 MHz
Duty Cycle Factor: 1
Conversion Factor: 6
Probe Sensitivity: 1.20 1.20 1.20 μ V/ (V/m)²
Compression Point: 95.00 mV
Offset : 1.56 mm

Measurement Data

Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 20.00 °C
Ambient Temp. : 23.00 °C
Set-up Date : 16-Jul-2012
Set-up Time : 6:52:47 AM
Area Scan : 7x11x1 : Measurement x=15mm, y=15mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Back of Handset
Separation : 0 mm
Channel : Low



1 gram SAR value : 5.970 W/kg
10 gram SAR value : 4.281 W/kg
Area Scan Peak SAR : 6.129 W/kg
Zoom Scan Peak SAR : 8.147 W/kg

SAR Test Report - Plot 4

By Operator : Jay
Measurement Date : 24-Sep-2012
Starting Time : 24-Sep-2012 09:15:05 AM
End Time : 24-Sep-2012 09:39:13 AM
Scanning Time : 1448 secs

Product Data

Device Name : EF Johnson
Serial No. : 517001208720021
Mode : FM
Model : R0235170083
Frequency : 406.10 MHz
Max. Transmit Pwr : 4.487 W
Drift Time : 0 min(s)
Length : 166 mm
Width : 66 mm
Depth : 40 mm
Antenna Type : Stub
Orientation : Back of Handset
Power Drift-Start : 9.565 W/kg
Power Drift-Finish: 9.409 W/kg
Power Drift (%) : -1.622

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : System Default
Location : Center
Description : Uni-Phantom

Tissue Data

Type : BODY
Serial No. : 406
Frequency : 406.10 MHz
Last Calib. Date : 24-Sep-2012
Temperature : 20.00 °C
Ambient Temp. : 23.00 °C
Humidity : 49.00 RH%
Epsilon : 56.97 F/m
Sigma : 0.93 S/m
Density : 1000.00 kg/cu. m

Probe Data


Name : Probe 215 - RFEL
Model : E020
Type : E-Field Triangle
Serial No. : 215
Last Calib. Date : 23-Aug-2012
Frequency : 450.00 MHz
Duty Cycle Factor: 1
Conversion Factor: 6
Probe Sensitivity: 1.20 1.20 1.20 μ V/ (V/m)²
Compression Point: 95.00 mV
Offset : 1.56 mm

Measurement Data


Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 20.00 °C
Ambient Temp. : 23.00 °C
Set-up Date : 24-Sep-2012
Set-up Time : 6:52:47 AM
Area Scan : 7x11x1 : Measurement x=15mm, y=15mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Back of Handset
Separation : 0 mm
Channel : Low



1 gram SAR value : 9.638 W/kg
10 gram SAR value : 6.633 W/kg
Area Scan Peak SAR : 9.476 W/kg
Zoom Scan Peak SAR : 14.012 W/kg

SAR-Z Axis
at Hotspot x:8.22 y:-7.94

SAR Test Report - Plot 5

By Operator : Jay
Measurement Date : 16-Jul-2012
Starting Time : 16-Jul-2012 08:19:45 AM
End Time : 16-Jul-2012 08:42:13 AM
Scanning Time : 1348 secs

Product Data

Device Name : EF Johnson
Serial No. : 517001208720021
Mode : FM
Model : R0235170083
Frequency : 425.00 MHz
Max. Transmit Pwr : 4.539 W
Drift Time : 0 min(s)
Length : 166 mm
Width : 66 mm
Depth : 40 mm
Antenna Type : Stub
Orientation : Back of Handset
Power Drift-Start : 8.805 W/kg
Power Drift-Finish: 8.607 W/kg
Power Drift (%) : -2.248

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : System Default
Location : Center
Description : Uni-Phantom

Tissue Data

Type : BODY
Serial No. : 425
Frequency : 425.00 MHz
Last Calib. Date : 16-Jul-2012
Temperature : 20.00 °C
Ambient Temp. : 23.00 °C
Humidity : 49.00 RH%
Epsilon : 56.80 F/m
Sigma : 0.94 S/m
Density : 1000.00 kg/cu. m

Probe Data


Name : RFEL 217
Model : E020
Type : E-Field Triangle
Serial No. : 217
Last Calib. Date : 07-Sep-2011
Frequency : 450.00 MHz
Duty Cycle Factor: 1
Conversion Factor: 6
Probe Sensitivity: 1.20 1.20 1.20 μ V/ (V/m)²
Compression Point: 95.00 mV
Offset : 1.56 mm

Measurement Data

Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 20.00 °C
Ambient Temp. : 23.00 °C
Set-up Date : 16-Jul-2012
Set-up Time : 2:33:19 PM
Area Scan : 7x11x1 : Measurement x=15mm, y=15mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Back of Handset
Separation : 0 mm
Channel : Mid



1 gram SAR value : 8.821 W/kg
10 gram SAR value : 6.186 W/kg
Area Scan Peak SAR : 8.910 W/kg
Zoom Scan Peak SAR : 12.611 W/kg

SAR Test Report - Plot 6

By Operator : Jay
Measurement Date : 16-Jul-2012
Starting Time : 16-Jul-2012 10:15:50 AM
End Time : 16-Jul-2012 10:38:20 AM
Scanning Time : 1350 secs

Product Data

Device Name : EF Johnson
Serial No. : 517001208720021
Mode : FM
Model : R0235170083
Frequency : 450.00 MHz
Max. Transmit Pwr : 4.457 W
Drift Time : 0 min(s)
Length : 166 mm
Width : 66 mm
Depth : 40 mm
Antenna Type : Stub
Orientation : Back of Handset
Power Drift-Start : 7.454 W/kg
Power Drift-Finish: 7.401 W/kg
Power Drift (%) : -0.713

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : System Default
Location : Center
Description : Uni-Phantom

Tissue Data

Type : BODY
Serial No. : 450
Frequency : 450.00 MHz
Last Calib. Date : 16-Jul-2012
Temperature : 20.00 °C
Ambient Temp. : 23.00 °C
Humidity : 49.00 RH%
Epsilon : 56.59 F/m
Sigma : 0.96 S/m
Density : 1000.00 kg/cu. m

Probe Data


Name : RFEL 217
Model : E020
Type : E-Field Triangle
Serial No. : 217
Last Calib. Date : 07-Sep-2011
Frequency : 450.00 MHz
Duty Cycle Factor: 1
Conversion Factor: 6
Probe Sensitivity: 1.20 1.20 1.20 μ V/ (V/m)²
Compression Point: 95.00 mV
Offset : 1.56 mm

Measurement Data

Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 20.00 °C
Ambient Temp. : 23.00 °C
Set-up Date : 16-Jul-2012
Set-up Time : 2:33:19 PM
Area Scan : 7x11x1 : Measurement x=15mm, y=15mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Back of Handset
Separation : 0 mm
Channel : Mid



1 gram SAR value : 7.887 W/kg
10 gram SAR value : 5.448 W/kg
Area Scan Peak SAR : 8.295 W/kg
Zoom Scan Peak SAR : 11.410 W/kg

SAR Test Report - Plot 7

By Operator : Jay
Measurement Date : 24-Sep-2012
Starting Time : 24-Sep-2012 09:47:25 AM
End Time : 24-Sep-2012 10:10:26 AM
Scanning Time : 1381 secs

Product Data

Device Name : EF Johnson
Serial No. : 517001208720021
Mode : FM
Model : R0235170083
Frequency : 460.00 MHz
Max. Transmit Pwr : 4.467 W
Drift Time : 0 min(s)
Length : 166 mm
Width : 66 mm
Depth : 40 mm
Antenna Type : Stub
Orientation : Back of Handset
Power Drift-Start : 7.185 W/kg
Power Drift-Finish: 7.071 W/kg
Power Drift (%) : -1.589

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : System Default
Location : Center
Description : Uni-Phantom

Tissue Data

Type : BODY
Serial No. : 460
Frequency : 460.00 MHz
Last Calib. Date : 24-Sep-2012
Temperature : 20.00 °C
Ambient Temp. : 23.00 °C
Humidity : 49.00 RH%
Epsilon : 56.41 F/m
Sigma : 0.96 S/m
Density : 1000.00 kg/cu. m

Probe Data


Name : Probe 215 - RFEL
Model : E020
Type : E-Field Triangle
Serial No. : 215
Last Calib. Date : 23-Aug-2012
Frequency : 450.00 MHz
Duty Cycle Factor: 1
Conversion Factor: 6
Probe Sensitivity: 1.20 1.20 1.20 μ V/ (V/m)²
Compression Point: 95.00 mV
Offset : 1.56 mm

Measurement Data

Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 20.00 °C
Ambient Temp. : 23.00 °C
Set-up Date : 24-Sep-2012
Set-up Time : 6:52:47 AM
Area Scan : 7x11x1 : Measurement x=15mm, y=15mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Back of Handset
Separation : 0 mm
Channel : High



1 gram SAR value : 8.465 W/kg
10 gram SAR value : 5.575 W/kg
Area Scan Peak SAR : 9.064 W/kg
Zoom Scan Peak SAR : 13.212 W/kg

SAR Test Report - Plot 8

By Operator : Jay
Measurement Date : 16-Jul-2012
Starting Time : 16-Jul-2012 11:43:49 AM
End Time : 16-Jul-2012 12:07:48 PM
Scanning Time : 1439 secs

Product Data

Device Name : EF Johnson
Serial No. : 517001208720021
Mode : FM
Model : R0235170083
Frequency : 470.00 MHz
Max. Transmit Pwr : 4.498 W
Drift Time : 0 min(s)
Length : 166 mm
Width : 66 mm
Depth : 40 mm
Antenna Type : Stub
Orientation : Back of Handset
Power Drift-Start : 6.596 W/kg
Power Drift-Finish: 6.328 W/kg
Power Drift (%) : -4.060

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : System Default
Location : Center
Description : Uni-Phantom

Tissue Data

Type : BODY
Serial No. : 470
Frequency : 470.00 MHz
Last Calib. Date : 16-Jul-2012
Temperature : 20.00 °C
Ambient Temp. : 23.00 °C
Humidity : 49.00 RH%
Epsilon : 56.42 F/m
Sigma : 0.97 S/m
Density : 1000.00 kg/cu. m

Probe Data


Name : RFEL 217
Model : E020
Type : E-Field Triangle
Serial No. : 217
Last Calib. Date : 07-Sep-2011
Frequency : 450.00 MHz
Duty Cycle Factor: 1
Conversion Factor: 6
Probe Sensitivity: 1.20 1.20 1.20 μ V/ (V/m)²
Compression Point: 95.00 mV
Offset : 1.56 mm

Measurement Data

Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 20.00 °C
Ambient Temp. : 23.00 °C
Set-up Date : 16-Jul-2012
Set-up Time : 6:52:47 AM
Area Scan : 7x11x1 : Measurement x=15mm, y=15mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Back of Handset
Separation : 0 mm
Channel : High



1 gram SAR value : 7.060 W/kg
10 gram SAR value : 4.859 W/kg
Area Scan Peak SAR : 7.578 W/kg
Zoom Scan Peak SAR : 10.590 W/kg

SAR Test Report - Plot 9

By Operator : Jay
Measurement Date : 16-Jul-2012
Starting Time : 16-Jul-2012 02:33:28 PM
End Time : 16-Jul-2012 02:56:04 PM
Scanning Time : 1356 secs

Product Data

Device Name : EF Johnson
Serial No. : 517001208720021
Mode : FM
Model : R0235170083
Frequency : 380.00 MHz
Max. Transmit Pwr : 4.285 W
Drift Time : 0 min(s)
Length : 75 mm
Width : 64 mm
Depth : 26 mm
Antenna Type : Stub
Orientation : Back of Microphone
Power Drift-Start : 3.393 W/kg
Power Drift-Finish: 3.353 W/kg
Power Drift (%) : -1.185

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : System Default
Location : Center
Description : Uni-Phantom

Tissue Data

Type : BODY
Serial No. : 380
Frequency : 380.00 MHz
Last Calib. Date : 16-Jul-2012
Temperature : 20.00 °C
Ambient Temp. : 23.00 °C
Humidity : 49.00 RH%
Epsilon : 57.22 F/m
Sigma : 0.92 S/m
Density : 1000.00 kg/cu. m

Probe Data


Name : RFEL 217
Model : E020
Type : E-Field Triangle
Serial No. : 217
Last Calib. Date : 07-Sep-2011
Frequency : 450.00 MHz
Duty Cycle Factor: 1
Conversion Factor: 6
Probe Sensitivity: 1.20 1.20 1.20 μ V/ (V/m)²
Compression Point: 95.00 mV
Offset : 1.56 mm

Measurement Data

Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 20.00 °C
Ambient Temp. : 23.00 °C
Set-up Date : 16-Jul-2012
Set-up Time : 2:33:19 PM
Area Scan : 7x11x1 : Measurement x=15mm, y=15mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Back of Microphone
Separation : 0 mm
Channel : Low



1 gram SAR value : 4.613 W/kg
10 gram SAR value : 3.245 W/kg
Area Scan Peak SAR : 4.788 W/kg
Zoom Scan Peak SAR : 6.305 W/kg

SAR Test Report - Plot 10

By Operator : Jay
Measurement Date : 24-Sep-2012
Starting Time : 24-Sep-2012 11:00:11 AM
End Time : 24-Sep-2012 11:23:00 AM
Scanning Time : 1369 secs

Product Data

Device Name : EF Johnson
Serial No. : 517001208720021
Mode : FM
Model : R0235170083
Frequency : 406.10 MHz
Max. Transmit Pwr : 4.487 W
Drift Time : 0 min(s)
Length : 75 mm
Width : 64 mm
Depth : 26 mm
Antenna Type : Stub
Orientation : Back of Microphone
Power Drift-Start : 6.346 W/kg
Power Drift-Finish: 6.268 W/kg
Power Drift (%) : -1.223

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : System Default
Location : Center
Description : Uni-Phantom

Tissue Data

Type : BODY
Serial No. : 406
Frequency : 406.10 MHz
Last Calib. Date : 24-Sep-2012
Temperature : 20.00 °C
Ambient Temp. : 23.00 °C
Humidity : 49.00 RH%
Epsilon : 56.97 F/m
Sigma : 0.93 S/m
Density : 1000.00 kg/cu. m

Probe Data


Name : Probe 215 - RFEL
Model : E020
Type : E-Field Triangle
Serial No. : 215
Last Calib. Date : 23-Aug-2012
Frequency : 450.00 MHz
Duty Cycle Factor: 1
Conversion Factor: 6
Probe Sensitivity: 1.20 1.20 1.20 μ V/ (V/m)²
Compression Point: 95.00 mV
Offset : 1.56 mm

Measurement Data

Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 20.00 °C
Ambient Temp. : 23.00 °C
Set-up Date : 24-Sep-2012
Set-up Time : 6:52:47 AM
Area Scan : 7x11x1 : Measurement x=15mm, y=15mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Back of Microphone
Separation : 0 mm
Channel : Low



1 gram SAR value : 8.401 W/kg
10 gram SAR value : 5.717 W/kg
Area Scan Peak SAR : 9.009 W/kg
Zoom Scan Peak SAR : 11.510 W/kg

SAR Test Report - Plot 11

By Operator : Jay
Measurement Date : 16-Jul-2012
Starting Time : 16-Jul-2012 01:13:51 PM
End Time : 16-Jul-2012 01:36:35 PM
Scanning Time : 1364 secs

Product Data

Device Name : EF Johnson
Serial No. : 517001208720021
Mode : FM
Model : R0235170083
Frequency : 425.00 MHz
Max. Transmit Pwr : 4.539 W
Drift Time : 0 min(s)
Length : 75 mm
Width : 64 mm
Depth : 26 mm
Antenna Type : Stub
Orientation : Back of Microphone
Power Drift-Start : 7.335 W/kg
Power Drift-Finish: 7.354 W/kg
Power Drift (%) : 0.263

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : System Default
Location : Center
Description : Uni-Phantom

Tissue Data

Type : BODY
Serial No. : 425
Frequency : 425.00 MHz
Last Calib. Date : 16-Jul-2012
Temperature : 20.00 °C
Ambient Temp. : 23.00 °C
Humidity : 49.00 RH%
Epsilon : 56.80 F/m
Sigma : 0.94 S/m
Density : 1000.00 kg/cu. m

Probe Data


Name : RFEL 217
Model : E020
Type : E-Field Triangle
Serial No. : 217
Last Calib. Date : 07-Sep-2011
Frequency : 450.00 MHz
Duty Cycle Factor: 1
Conversion Factor: 6
Probe Sensitivity: 1.20 1.20 1.20 μ V/ (V/m)²
Compression Point: 95.00 mV
Offset : 1.56 mm

Measurement Data

Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 20.00 °C
Ambient Temp. : 23.00 °C
Set-up Date : 16-Jul-2012
Set-up Time : 12:23:27 PM
Area Scan : 7x11x1 : Measurement x=15mm, y=15mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Back of Microphone
Separation : 0 mm
Channel : Mid



1 gram SAR value : 9.340 W/kg
10 gram SAR value : 6.568 W/kg
Area Scan Peak SAR : 9.682 W/kg
Zoom Scan Peak SAR : 12.811 W/kg

SAR Test Report - Plot 12

By Operator : Jay
Measurement Date : 16-Jul-2012
Starting Time : 16-Jul-2012 03:58:04 PM
End Time : 16-Jul-2012 04:20:48 PM
Scanning Time : 1364 secs

Product Data

Device Name : EF Johnson
Serial No. : 517001208720021
Mode : FM
Model : R0235170083
Frequency : 450.00 MHz
Max. Transmit Pwr : 4.457 W
Drift Time : 0 min(s)
Length : 75 mm
Width : 64 mm
Depth : 26 mm
Antenna Type : Stub
Orientation : Back of Microphone
Power Drift-Start : 6.318 W/kg
Power Drift-Finish: 6.175 W/kg
Power Drift (%) : -2.263

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : System Default
Location : Center
Description : Uni-Phantom

Tissue Data

Type : BODY
Serial No. : 450
Frequency : 450.00 MHz
Last Calib. Date : 16-Jul-2012
Temperature : 20.00 °C
Ambient Temp. : 23.00 °C
Humidity : 49.00 RH%
Epsilon : 56.59 F/m
Sigma : 0.96 S/m
Density : 1000.00 kg/cu. m

Probe Data


Name : RFEL 217
Model : E020
Type : E-Field Triangle
Serial No. : 217
Last Calib. Date : 07-Sep-2011
Frequency : 450.00 MHz
Duty Cycle Factor: 1
Conversion Factor: 6
Probe Sensitivity: 1.20 1.20 1.20 μ V/ (V/m)²
Compression Point: 95.00 mV
Offset : 1.56 mm

Measurement Data

Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 20.00 °C
Ambient Temp. : 23.00 °C
Set-up Date : 16-Jul-2012
Set-up Time : 12:23:27 PM
Area Scan : 7x11x1 : Measurement x=15mm, y=15mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Back of Microphone
Separation : 0 mm
Channel : Mid



1 gram SAR value : 7.260 W/kg
10 gram SAR value : 5.141 W/kg
Area Scan Peak SAR : 7.594 W/kg
Zoom Scan Peak SAR : 9.919 W/kg

SAR Test Report - Plot 13

By Operator : Jay
Measurement Date : 24-Sep-2012
Starting Time : 24-Sep-2012 11:26:29 AM
End Time : 24-Sep-2012 11:49:20 AM
Scanning Time : 1371 secs

Product Data

Device Name : EF Johnson
Serial No. : 517001208720021
Mode : FM
Model : R0235170083
Frequency : 460.00 MHz
Max. Transmit Pwr : 4.467 W
Drift Time : 0 min(s)
Length : 75 mm
Width : 64 mm
Depth : 26 mm
Antenna Type : Stub
Orientation : Back of Microphone
Power Drift-Start : 5.871 W/kg
Power Drift-Finish: 5.752 W/kg
Power Drift (%) : -2.029

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : System Default
Location : Center
Description : Uni-Phantom

Tissue Data

Type : BODY
Serial No. : 460
Frequency : 460.00 MHz
Last Calib. Date : 24-Sep-2012
Temperature : 20.00 °C
Ambient Temp. : 23.00 °C
Humidity : 49.00 RH%
Epsilon : 56.41 F/m
Sigma : 0.96 S/m
Density : 1000.00 kg/cu. m

Probe Data


Name : Probe 215 - RFEL
Model : E020
Type : E-Field Triangle
Serial No. : 215
Last Calib. Date : 23-Aug-2012
Frequency : 450.00 MHz
Duty Cycle Factor: 1
Conversion Factor: 6
Probe Sensitivity: 1.20 1.20 1.20 μ V/ (V/m)²
Compression Point: 95.00 mV
Offset : 1.56 mm

Measurement Data

Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 20.00 °C
Ambient Temp. : 23.00 °C
Set-up Date : 24-Sep-2012
Set-up Time : 6:52:47 AM
Area Scan : 7x11x1 : Measurement x=15mm, y=15mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Back of Microphone
Separation : 0 mm
Channel : High



1 gram SAR value : 7.548 W/kg
10 gram SAR value : 4.345 W/kg
Area Scan Peak SAR : 8.098 W/kg
Zoom Scan Peak SAR : 9.040 W/kg

SAR Test Report - Plot 14

By Operator : Jay
Measurement Date : 16-Jul-2012
Starting Time : 16-Jul-2012 05:27:40 PM
End Time : 16-Jul-2012 05:50:02 PM
Scanning Time : 1342 secs

Product Data

Device Name : EF Johnson
Serial No. : 517001208720021
Mode : FM
Model : R0235170083
Frequency : 470.00 MHz
Max. Transmit Pwr : 4.498 W
Drift Time : 0 min(s)
Length : 75 mm
Width : 64 mm
Depth : 26 mm
Antenna Type : Stub
Orientation : Back of Microphone
Power Drift-Start : 4.464 W/kg
Power Drift-Finish: 4.406 W/kg
Power Drift (%) : -1.302

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size (mm) : 280 x 280 x 200
Serial No. : System Default
Location : Center
Description : Uni-Phantom

Tissue Data

Type : BODY
Serial No. : 470
Frequency : 470.00 MHz
Last Calib. Date : 16-Jul-2012
Temperature : 20.00 °C
Ambient Temp. : 23.00 °C
Humidity : 49.00 RH%
Epsilon : 56.42 F/m
Sigma : 0.97 S/m
Density : 1000.00 kg/cu. m

Probe Data


Name : RFEL 217
Model : E020
Type : E-Field Triangle
Serial No. : 217
Last Calib. Date : 07-Sep-2011
Frequency : 450.00 MHz
Duty Cycle Factor: 1
Conversion Factor: 6
Probe Sensitivity: 1.20 1.20 1.20 μ V/ (V/m)²
Compression Point: 95.00 mV
Offset : 1.56 mm

Measurement Data

Crest Factor : 1
Scan Type : Complete
Tissue Temp. : 20.00 °C
Ambient Temp. : 23.00 °C
Set-up Date : 16-Jul-2012
Set-up Time : 12:23:27 PM
Area Scan : 7x11x1 : Measurement x=15mm, y=15mm, z=4mm
Zoom Scan : 5x5x8 : Measurement x=8mm, y=8mm, z=4mm

Other Data

DUT Position : Back of Microphone
Separation : 0 mm
Channel : High




1 gram SAR value : 6.068 W/kg
10 gram SAR value : 4.244 W/kg
Area Scan Peak SAR : 6.316 W/kg
Zoom Scan Peak SAR : 8.337 W/kg

Appendix C – SAR Test Setup Photos




System Body Configuration



Body Tissue Depth

**Test Position Handset Face 25 mm Gap****Test Position Handset Body 0 mm Gap**

**Test Position Audio Accessory D Face 25 mm Gap****Test Position Audio Accessory D Body 0 mm Gap**



Front of Handset




Back of Handset


**Front of Battery****Back of Battery**



Audio Accessory A



Audio Accessory D



Handset with Audio Accessory D

Appendix D – Probe Calibration Data Sheets

NCL CALIBRATION LABORATORIES

Calibration File No.: PC1333-1350

Client.: RFEL

C E R T I F I C A T E O F C A L I B R A T I O N

It is certified that the equipment identified below has been calibrated in the
NCL CALIBRATION LABORATORIES by qualified personnel following recognized
procedures and using transfer standards traceable to NRC/NIST.

Equipment: Miniature Isotropic RF Probe

Record of Calibration

Head and Body

Manufacturer: APREL Laboratories

Model No.: E-020

Serial No.: 217

Calibration Procedure: D01-032-E020-V2, D22-012-Tissue, D28-002-Dipole
Project No: RFEL-PC-5620

Calibrated: 7th September 2011
Released on: 7th September 2011

Approved By: Stuart Nicol

This Calibration Certificate is Incomplete Unless Accompanied with the Calibration Results Summary

Released By: _____

NCL CALIBRATION LABORATORIES

303 Terry Fox Drive, Suite 102
Kanata, Ontario
CANADA K2K 3J1

Division of APREL
TEL: (613) 435-8300
FAX: (613) 435-8306

NCL Calibration Laboratories

Division of APREL Inc.

Introduction

This Calibration Report reproduces the results of the calibration performed in line with the references listed below. Calibration is performed using accepted methodologies as per the references listed below. Probes are calibrated for air, and tissue and the values reported are the results from the physical quantification of the probe through metrological practices.

Calibration Method

Probes are calibrated using the following methods.

<1000MHz

TEM Cell for sensitivity in air

Standard phantom using temperature transfer method for sensitivity in tissue

>1000MHz

Waveguide* method to determine sensitivity in air and tissue

*Waveguide is numerically (simulation) assessed to determine the field distribution and power

The boundary effect for the probe is assessed using a standard flat phantom where the probe output is compared against a numerically simulated series of data points

References

- IEEE Standard 1528 (2003) including Amendment 1
IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
- EN 62209-1 (2006)
Human Exposure to RF Fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures-Part 1: Procedure to measure the Specific Absorption Rate (SAR) for hand-held mobile wireless devices
- IEC 62209-2 Ed. 1.0 (2010-03)
Human exposure to RF fields from hand-held and body-mounted wireless devices - Human models, instrumentation, and procedures - Part 2: specific absorption rate (SAR) for wireless communication devices (30 MHz - 6 GHz)
- TP-D01-032-E020-V2 E-Field probe calibration procedure
- D22-012-Tissue dielectric tissue calibration procedure
- D28-002-Dipole procedure for validation of SAR system using a dipole
- IEEE 1309 Draft Standard for Calibration of Electromagnetic Field Sensors and Probes, Excluding Antennas, from 9kHz to 40GHz

NCL Calibration Laboratories

Division of APREL Inc.

Conditions

Probe 217 was a re-calibration.

Ambient Temperature of the Laboratory: 22 °C +/- 1.5°C
Temperature of the Tissue: 21 °C +/- 1.5°C
Relative Humidity: < 60%

Primary Measurement Standards

Instrument	Serial Number	Cal date
Power meter Anritsu MA2408A	90025437	Nov.4, 2010
Power Sensor Anritsu MA2481D	103555	Nov 4, 2010
Attenuator HP 8495A (70dB)	1944A10711	Sept. 14, 2010
Network Analyzer Anritsu MT8801C	MB11855	Feb. 8, 2011


Secondary Measurement Standards

Signal Generator Agilent E4438C -506 MY55182336 June 7, 2011


Attestation

The below named signatories have conducted the calibration and review of the data which is presented in this calibration report.

We the undersigned attest that to the best of our knowledge the calibration of this probe has been accurately conducted and that all information contained within this report has been reviewed for accuracy.



Stuart Nicol



Jesse Hones

NCL Calibration Laboratories

Division of APREL Inc.

Probe Summary

Probe Type: E-Field Probe E020
Serial Number: 217
Frequency: 750MHz
Sensor Offset: 1.56
Sensor Length: 2.5
Tip Enclosure: Composite*
Tip Diameter: < 2.9 mm
Tip Length: 55 mm
Total Length: 289 mm

*Resistive to recommended tissue recipes per IEEE-1528

Sensitivity in Air

Channel X: $1.2 \mu\text{V}/(\text{V}/\text{m})^2$
Channel Y: $1.2 \mu\text{V}/(\text{V}/\text{m})^2$
Channel Z: $1.2 \mu\text{V}/(\text{V}/\text{m})^2$
Diode Compression Point: 95 mV

NCL Calibration Laboratories

Division of APREL Inc.

Calibration for Tissue (Head H, Body B)

Frequency	Tissue Type	Measured Epsilon	Measured Sigma	Calibration Uncertainty	Tolerance Uncertainty for 5%*	Conversion Factor
450 H	Head	45.31	0.91	4.1	3.6	5.8
450 B	Body	56.77	0.99	4.1	3.6	6.0
650 B	Body	57.42	0.91	3.96	3.5	6.2
750 H	Head	42.16	0.87	3.94	3.5	6.2
750 B	Body	55.54	0.94	3.94	3.4	6.3
835 H	Head	42.5	0.93	3.5	3.4	6.4
835 B	Body	56.37	0.954	3.5	3.4	6.4
900 H	Head	41.89	1.0	3.5	3.4	6.1
900 B	Body	53.68	1.05	3.5	3.4	6.1
1450 H	Head	X	X	X	X	X
1450 B	Body	X	X	X	X	X
1500 H	Head	X	X	X	X	X
1500 B	Body	X	X	X	X	X
1640 H	Head	39.0	1.25	3.5	2.7	5.2
1640 B	Body	52.03	1.39	3.5	2.7	5.0
1735 H	Head	X	X	X	X	X
1735 B	Body	51.68	1.5	3.5	2.7	5.2
1800 H	Head	38.38	1.39	3.5	2.7	4.9
1800 B	Body	51.54	1.56	3.5	2.7	5.1
1900 H	Head	38.4	1.43	3.5	2.7	4.9
1900 B	Body	52.08	1.59	3.5	2.7	4.8
2000 H	Head	X	X	X	X	X
2000 B	Body	X	X	X	X	X
2100 H	Head	X	X	X	X	X
2100 B	Body	X	X	X	X	X
2300 H	Head	X	X	X	X	X
2300 B	Body	X	X	X	X	X
2450 H	Head	38.2	1.82	3.5	3.5	3.91
2450 B	Body	51.74	1.96	3.5	3.5	3.94
2600 H	Head	X	X	X	X	X
2600 B	Body	51.18	2.16	3.5	3.5	4.0
3000 H	Head	X	X	X	X	X
3000 B	Body	X	X	X	X	X
3600 H	Head	X	X	X	X	X
3600 B	Body	X	X	X	X	X
5200 H	Head	X	X	X	X	X
5200 B	Body	X	X	X	X	X
5600 H	Head	X	X	X	X	X
5600 B	Body	X	X	X	X	X
5800 H	Head	X	X	X	X	X
5800 B	Body	X	X	X	X	X

NCL Calibration Laboratories

Division of APREL Inc.

Boundary Effect:

Uncertainty resulting from the boundary effect is less than 2.1% for the distance between the tip of the probe and the tissue boundary, when less than 0.58mm.

Spatial Resolution:

The spatial resolution uncertainty is less than 1.5% for 4.9mm diameter probe.
The spatial resolution uncertainty is less than 1.0% for 2.5mm diameter probe.

DAQ-PAQ Contribution

To minimize the uncertainty calculation all tissue sensitivity values were calculated using a load impedance of $5\text{ M}\Omega$.

Boundary Effect:

For a distance of 0.58mm the worst case evaluated uncertainty (increase in the probe sensitivity) is less than 2.1%.


NOTES:

*The maximum deviation from the centre frequency when comparing the lower to upper range is listed.



The probe was received in good condition.

Probe was calibrated on new DAC-PAQ.

Receiving Pattern Air




Isotropy Error



Isotropicity Tissue:


0.12 dB

Dynamic Range



Video Bandwidth

Probe Frequency Characteristics



Video Bandwidth at 500 Hz

1 dB

Video Bandwidth at 1.02 KHz:

3 dB

Test Equipment

The test equipment used during Probe Calibration, manufacturer, model number and, current calibration status are listed and located on the main APREL server R:\NCL\Calibration Equipment\Instrument List May 2011.

NCL CALIBRATION LABORATORIES

Calibration File No.: PC-1442

Client.: RF Exposure Lab

C E R T I F I C A T E O F C A L I B R A T I O N

It is certified that the equipment identified below has been calibrated in the
NCL CALIBRATION LABORATORIES by qualified personnel following recognized
procedures and using transfer standards traceable to NRC/NIST.

Equipment: Miniature Isotropic RF Probe

Record of Calibration

Head and Body

Manufacturer: APREL Laboratories

Model No.: E-020

Serial No.: 215

Calibration Procedure: D01-032-E020-V2, D22-012-Tissue, D28-002-Dipole
Project No: RFEL-E20-cal-5676

Calibrated: 23rd August 2012
Released on: 23rd August 2012

This Calibration Certificate is Incomplete Unless Accompanied with the Calibration Results Summary

Released By:



Art Brennan, Quality Manager

NCL CALIBRATION LABORATORIES

303 Terry Fox Drive, Suite 102
Kanata, Ontario
CANADA K2K 3J1

Division of APREL
TEL: (613) 435-8300
FAX: (613) 435-8306

NCL Calibration Laboratories

Division of APREL Inc.

Introduction

This Calibration Report reproduces the results of the calibration performed in line with the references listed below. Calibration is performed using accepted methodologies as per the references listed below. Probes are calibrated for air, and tissue and the values reported are the results from the physical quantification of the probe through metrological practices.

Calibration Method

Probes are calibrated using the following methods.

<1000MHz

TEM Cell for sensitivity in air

Standard phantom using temperature transfer method for sensitivity in tissue

>1000MHz

Waveguide* method to determine sensitivity in air and tissue

*Waveguide is numerically (simulation) assessed to determine the field distribution and power

The boundary effect for the probe is assessed using a standard flat phantom where the probe output is compared against a numerically simulated series of data points

References

- IEEE Standard 1528 (2003) including Amendment 1
IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
- EN 62209-1 (2006)
Human Exposure to RF Fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures-Part 1: Procedure to measure the Specific Absorption Rate (SAR) for hand-held mobile wireless devices
- IEC 62209-2 Ed. 1.0 (2010-03)
Human exposure to RF fields from hand-held and body-mounted wireless devices - Human models, instrumentation, and procedures - Part 2: specific absorption rate (SAR) for wireless communication devices (30 MHz - 6 GHz)
- TP-D01-032-E020-V2 E-Field probe calibration procedure
- D22-012-Tissue dielectric tissue calibration procedure
- D28-002-Dipole procedure for validation of SAR system using a dipole
- IEEE 1309 Draft Standard for Calibration of Electromagnetic Field Sensors and Probes, Excluding Antennas, from 9kHz to 40GHz

NCL Calibration Laboratories

Division of APREL Inc.

Conditions

Probe 215 was a re-calibration.

Ambient Temperature of the Laboratory: 22 °C +/- 1.5°C
Temperature of the Tissue: 21 °C +/- 1.5°C
Relative Humidity: < 60%

Primary Measurement Standards

Instrument	Serial Number	Cal date
Power meter Anritsu MA2408A	90025437	Nov.4, 2012
Power Sensor Anritsu MA2481D	103555	Nov 4, 2012
Attenuator HP 8495A (70dB)	1944A10711	Sept. 14, 2012
Network Analyzer Anritsu MT8801C	MB11855	Feb. 8, 2013

Secondary Measurement Standards

Signal Generator Agilent E4438C -506 MY55182336 June 7, 2013


Attestation

The below named signatories have conducted the calibration and review of the data which is presented in this calibration report.

We the undersigned attest that to the best of our knowledge the calibration of this subject has been accurately conducted and that all information contained within the results pages have been reviewed for accuracy.



Art Brennan, Quality Manager



Dan Brooks, Test Engineer

NCL Calibration Laboratories

Division of APREL Inc.

Probe Summary

Probe Type: E-Field Probe E020
Serial Number: 215
Frequency: See page 5
Sensor Offset: 1.56
Sensor Length: 2.5
Tip Enclosure: Composite*
Tip Diameter: < 2.9 mm
Tip Length: 55 mm
Total Length: 289 mm

*Resistive to recommended tissue recipes per IEEE-1528

Sensitivity in Air

Channel X: $1.2 \mu\text{V}/(\text{V}/\text{m})^2$
Channel Y: $1.2 \mu\text{V}/(\text{V}/\text{m})^2$
Channel Z: $1.2 \mu\text{V}/(\text{V}/\text{m})^2$
Diode Compression Point: 95 mV

NCL Calibration Laboratories

Division of APREL Inc.

Calibration for Tissue (Head H, Body B)

Frequency	Tissue Type	Measured Epsilon	Measured Sigma	Calibration Uncertainty	Tolerance Uncertainty for 5%*	Conversion Factor
450 H	Head	43.98	0.9	4.1	3.6	6
450 B	Body	56.77	0.99	4.1	3.6	6.0
650 B	Body	57.42	0.91	3.96	3.5	6.2
750 H	Head	X	X	X	X	X
750 B	Body	55.54	0.94	3.94	3.4	6.3
835 H	Head	42.5	0.93	3.5	3.4	6.4
835 B	Body	56.37	0.954	3.5	3.4	6.4
900 H	Head	41.89	1.0	3.5	3.4	6.1
900 B	Body	53.68	1.05	3.5	3.4	6.1
1450 H	Head	X	X	X	X	X
1450 B	Body	X	X	X	X	X
1500 H	Head	X	X	X	X	X
1500 B	Body	X	X	X	X	X
1640 H	Head	39.0	1.25	3.5	2.7	5.2
1640 B	Body	52.03	1.39	3.5	2.7	5.0
1735 H	Head	X	X	X	X	X
1735 B	Body	52.88	1.5	3.5	2.7	5.5
1800 H	Head	X	X	X	X	X
1800 B	Body	X	X	X	X	X
1900 H	Head	38.88	1.43	3.5	2.7	5.5
1900 B	Body	51.57	1.57	3.5	2.7	5.3
2000 H	Head	X	X	X	X	X
2000 B	Body	X	X	X	X	X
2100 H	Head	X	X	X	X	X
2100 B	Body	X	X	X	X	X
2300 H	Head	X	X	X	X	X
2300 B	Body	X	X	X	X	X
2450 H	Head	38.2	1.82	3.5	3.5	3.91
2450 B	Body	51.74	1.96	3.5	3.5	3.94
2600 H	Head	X	X	X	X	X
2600 B	Body	X	X	X	X	X
3000 H	Head	X	X	X	X	X
3000 B	Body	X	X	X	X	X
3600 H	Head	X	X	X	X	X
3600 B	Body	X	X	X	X	X
5200 H	Head	X	X	X	X	X
5200 B	Body	X	X	X	X	X
5600 H	Head	X	X	X	X	X
5600 B	Body	X	X	X	X	X
5800 H	Head	X	X	X	X	X
5800 B	Body	X	X	X	X	X

NCL Calibration Laboratories

Division of APREL Inc.

Boundary Effect:

Uncertainty resulting from the boundary effect is less than 2.1% for the distance between the tip of the probe and the tissue boundary, when less than 0.58mm.

Spatial Resolution:

The spatial resolution uncertainty is less than 1.5% for 4.9mm diameter probe.
The spatial resolution uncertainty is less than 1.0% for 2.5mm diameter probe.

DAQ-PAQ Contribution

To minimize the uncertainty calculation all tissue sensitivity values were calculated using a load impedance of $5\text{ M}\Omega$.

Boundary Effect:


For a distance of 0.58mm the worst case evaluated uncertainty (increase in the probe sensitivity) is less than 2.1%.

NOTES:



*The maximum deviation from the centre frequency when comparing the lower to upper range is listed.

The probe was received in good condition.

Receiving Pattern Air




Isotropy Error



Isotropicity Tissue:


0.12 dB

Dynamic Range



Video Bandwidth

Probe Frequency Characteristics



Video Bandwidth at 500 Hz

1 dB

Video Bandwidth at 1.02 KHz:

3 dB

Test Equipment

The test equipment used during Probe Calibration, manufacturer, model number and, current calibration status are listed and located on the main APREL server R:\NCL\Calibration Equipment\Instrument List May 2012.

Appendix E – Dipole Calibration Data Sheets

NCL CALIBRATION LABORATORIES

Calibration File No: DC-1107
Project Number: RFEB-5493

C E R T I F I C A T E O F C A L I B R A T I O N

It is certified that the equipment identified below has been calibrated in the
NCL CALIBRATION LABORATORIES by qualified personnel following recognized
procedures and using transfer standards traceable to NRC/NIST.

Validation Dipole

Manufacturer: APREL Laboratories

Part number: ALS-D-450-S-2

Frequency: 450 MHz Head


Serial No: RFE-362

Customer: RFEL

Calibrated: 12th January 2010
Released on: 12th January 2010

This Calibration Certificate is Incomplete Unless Accompanied with the Calibration Results Summary

Released By: _____



NCL CALIBRATION LABORATORIES

51 SPECTRUM WAY
NEPEAN, ONTARIO
CANADA K2R 1E6

Division of APREL Lab.
TEL: (613) 820-4988
FAX: (613) 820-4162

NCL Calibration Laboratories

Division of APREL Laboratories.

Conditions

Dipole RFE-362 was a re-calibration.

Ambient Temperature of the Laboratory: 22 °C +/- 0.5°C
Temperature of the Tissue: 21 °C +/- 0.5°C

We the undersigned attest that to the best of our knowledge the calibration of this device has been accurately conducted and that all information contained within this report has been reviewed for accuracy.

We the undersigned attest that to the best of our knowledge the calibration of this device has been accurately conducted and that all information contained within this report has been reviewed for accuracy.



Stuart Nicol



C. Teodorian

Calibration Results Summary

The following results relate the Calibrated Dipole and should be used as a quick reference for the user.

Mechanical Dimensions


Length: 270.0 mm
Height: 166.7 mm

Electrical Specification

SWR: 1.13 U
Return Loss: -27.5 dB
Impedance: 50.4 Ω

System Validation Results

Frequency	1 Gram	10 Gram	Peak
450 MHz	4.99	3.28	7.33



Introduction

This Calibration Report has been produced in line with the SSI Dipole Calibration Procedure SSI-TP-018-ALSAS. The results contained within this report are for Validation Dipole RFE-362. The calibration routine consisted of a three-step process. Step 1 was a mechanical verification of the dipole to ensure that it meets the mechanical specifications. Step 2 was an Electrical Calibration for the Validation Dipole, where the SWR, Impedance, and the Return loss were assessed. Step 3 involved a System Validation using the ALSAS-10U, along with APREL E-020 130 MHz to 26 GHz E-Field Probe Serial Number 212.

References

SSI-TP-018-ALSAS Dipole Calibration Procedure

SSI-TP-016 Tissue Calibration Procedure

IEEE 1528 "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques"

Conditions

Dipole RFE-362 was a re-calibration.

Ambient Temperature of the Laboratory: 22 °C +/- 0.5°C

Temperature of the Tissue: 20 °C +/- 0.5°C

Dipole Calibration uncertainty

The calibration uncertainty for the dipole is made up of various parameters presented below.

Mechanical	1%
Positioning Error	1.22%
Electrical	1.7%
Tissue	2.2%
Dipole Validation	2.2%
TOTAL	8.32% (16.64% K=2)

NCL Calibration Laboratories

Division of APREL Laboratories.

Dipole Calibration Results

Mechanical Verification

APREL Length	APREL Height	Measured Length	Measured Height
280.0 mm	166.7 mm	280.0 mm	166.0 mm


Tissue Validation

Head Tissue 450MHz	Measured
Dielectric constant, ϵ_r	43.6
Conductivity, σ [S/m]	0.89


Electrical Calibration

Test	Result
S11 R/L	-27.5 dB
SWR	1.13 U
Impedance	50.4 Ω


The Following Graphs are the results as displayed on the Vector Network Analyzer.

S11 Parameter Return Loss

SWR




Smith Chart Dipole Impedance



System Validation Results Using the Electrically Calibrated Dipole

Head Tissue Frequency	1 Gram	10 Gram	Peak Above Feed Point
450 MHz	4.9	3.3	7.3



NCL Calibration Laboratories

Division of APREL Laboratories.

Test Equipment

The test equipment used during Probe Calibration, manufacturer, model number and, current calibration status are listed and located on the main APREL server R:\NCL\Calibration Equipment\Instrument List May 2009.

Extended Calibration

Usage of SAR dipoles calibrated less than 2 years ago but more than 1 year ago were confirmed in maintaining return loss (< -20 dB, within 20% of prior calibration) and impedance (within 5 ohm from prior calibration) requirements per extended calibrations in KDB Publication 450824:

ALS-D-450-S-2 SN: RFE-362				
Date of Measurement	Return Loss (dB)	Δ%	Impedance (Ω)	Δ%
1/12/2010	-27.514		50.349	
1/12/2011	-26.327	-4.3	50.167	-0.4
1/12/2012	-26.456	-3.8	50.097	-0.5

NCL CALIBRATION LABORATORIES

Calibration File No: DC-1183
Project Number: RFEB-5554

C E R T I F I C A T E O F C A L I B R A T I O N

It is certified that the equipment identified below has been calibrated in the
NCL CALIBRATION LABORATORIES by qualified personnel following recognized
procedures and using transfer standards traceable to NRC/NIST.

Validation Dipole

Manufacturer: APREL Laboratories

Part number: ALS-D-450-S-2

Frequency: 450 MHz

Serial No: RFE-362

Customer: RFEL


Body Calibration

Calibrated: 19th January 2011

Released on: 19th January 2011

This Calibration Certificate is Incomplete Unless Accompanied with the Calibration Results Summary

Released By: _____



NCL CALIBRATION LABORATORIES

51 SPECTRUM WAY
NEPEAN, ONTARIO
CANADA K2R 1E6

Division of APREL Lab.
TEL: (613) 820-4988
FAX: (613) 820-4162

NCL Calibration Laboratories

Division of APREL Laboratories.

Conditions

Dipole RFE-362 was a re-calibration.

Ambient Temperature of the Laboratory: 22 °C +/- 0.5°C
Temperature of the Tissue: 21 °C +/- 0.5°C

We the undersigned attest that to the best of our knowledge the calibration of this device has been accurately conducted and that all information contained within this report has been reviewed for accuracy.

We the undersigned attest that to the best of our knowledge the calibration of this device has been accurately conducted and that all information contained within this report has been reviewed for accuracy.



Stuart Nicol



C. Teodorian

Calibration Results Summary

The following results relate the Calibrated Dipole and should be used as a quick reference for the user.

Mechanical Dimensions


Length: 270.0 mm
Height: 166.7 mm

Electrical Specification

SWR: 1.024 U
Return Loss: -38.354 dB
Impedance: 49.416 Ω

System Validation Results Body

Frequency	1 Gram	10 Gram	Peak
450 MHz	5.05	3.41	7.5



Introduction

This Calibration Report has been produced in line with the SSI Dipole Calibration Procedure SSI-TP-018-ALSAS. The results contained within this report are for Validation Dipole RFE-362. The calibration routine consisted of a three-step process. Step 1 was a mechanical verification of the dipole to ensure that it meets the mechanical specifications. Step 2 was an Electrical Calibration for the Validation Dipole, where the SWR, Impedance, and the Return loss were assessed. Step 3 involved a System Validation using the ALSAS-10U, along with APREL E-020 130 MHz to 26 GHz E-Field Probe Serial Number 212.

References

SSI-TP-018-ALSAS Dipole Calibration Procedure

SSI-TP-016 Tissue Calibration Procedure

IEEE 1528 "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques"

Conditions

Dipole RFE-362 was a re-calibration.

Ambient Temperature of the Laboratory: 22 °C +/- 0.5°C

Temperature of the Tissue: 20 °C +/- 0.5°C

NCL Calibration Laboratories

Division of APREL Laboratories.

Dipole Calibration Results

Mechanical Verification

APREL Length	APREL Height	Measured Length	Measured Height
280.0 mm	166.7 mm	280.0 mm	166.0 mm

Tissue Validation

Body Tissue 450MHz	Measured
Dielectric constant, ϵ_r	56.7
Conductivity, σ [S/m]	0.94

Dipole Calibration uncertainty


The calibration uncertainty for the dipole is made up of various parameters presented below.

Mechanical	1%
Positioning Error	1.22%
Electrical	1.7%
Tissue	2.2%
Dipole Validation	2.2%
TOTAL	8.32% (16.64% K=2)


Electrical Calibration

Test	Result
S11 R/L	-38.354 dB
SWR	1.024 U
Impedance	49.416 Ω


The Following Graphs are the results as displayed on the Vector Network Analyzer.

S11 Parameter Return Loss

SWR




Smith Chart Dipole Impedance



System Validation Results Using the Electrically Calibrated Dipole

Body Tissue Frequency	1 Gram	10 Gram	Peak Above Feed Point
450 MHz	5.05	3.41	7.5



Test Equipment

The test equipment used during Probe Calibration, manufacturer, model number and, current calibration status are listed and located on the main APREL server R:\NCL\Calibration Equipment\Instrument List May 2010.

Extended Calibration

Usage of SAR dipoles calibrated less than 2 years ago but more than 1 year ago were confirmed in maintaining return loss (< -20 dB, within 20% of prior calibration) and impedance (within 5 ohm from prior calibration) requirements per extended calibrations in KDB Publication 450824:

ALS-D-450-S-2 SN: RFE-362				
Date of Measurement	Return Loss (dB)	Δ%	Impedance (Ω)	Δ%
1/19/2011	-38.354		49.416	
1/12/2012	-38.241	-0.3	49.328	-0.2

Appendix F – Phantom Calibration Data Sheets

RF EXPOSURE LAB, LLC

Calibration File No.: CAL.20080601


C E R T I F I C A T E O F C A L I B R A T I O N

It is certified that the equipment identified below has been calibrated in the
RF Exposure Lab, LLC facility by qualified personnel following recognized
Procedures and using transfer standards traceable to National Standards.

Thickness of the Phantom is 6 mm \pm 10%
Size : 600 mm x 450 mm x 200 mm
Ellipse of 2mm Thickness: 350 mm x 200 mm
Material : High Density Polyethylene

Resolution: 0.01 mm
Stability: OK

Calibrated to: 0.0 mm
Accuracy: < 0.1 mm



Calibrated by: _____ Date: June 10, 2008

 **RF Exposure Lab**

802 N. Twin Oaks Valley Rd., Suite 105

San Marcos, CA 92069

Phone: (760) 471-2100

Fax: (760) 471-2121