



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V03
Report Template Revision Date: Mar.1st, 2017

RF Exposure Evaluation Report

Report No. : CQASZ20180400019E-02

Applicant: iLUV Creative Technology

Address of Applicant: 2 Harbor Park Drive, Port Washington, NY11050, New York, United States

Manufacturer: Dongguan Jinwenhua Digital Technology Co., Ltd

Address of Manufacturer: No.1 Huada Road, Longbeiling Industry Zone, Tiangxia Town, Dongguan City, Guangdong Province, China 523700

Equipment Under Test (EUT):

Product: AUD MINI PLUS

Model No.: AUDMINIPSXX (XX=COLOR CODE : BK=BLACK; WH=WHITE; PN=PINK...ETC)

Test Model No.: AUDMINIPSBK

Brand Name: iLUV

FCC ID: ATL- AUDMINIPLUS


Standards: 47 CFR Part 1.1307
47 CFR Part 2.1093
KDB447498D01 General RF Exposure Guidance v06

Date of Test: 2018-04-15 to 2018-04-20

Date of Issue: 2018-04-20

Test Result : PASS*


Tested By:


(Aaron Ma)

Reviewed By:


(Owen Zhou)

Approved By:


(Jack Ai)



* In the configuration tested, the EUT complied with the standards specified above.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

2 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20180400019E-02	Rev.01	Initial report	2018-04-20

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION	2
3 CONTENTS	3
4 GENERAL INFORMATION.....	4
4.1 CLIENT INFORMATION.....	4
4.2 GENERAL DESCRIPTION OF EUT	4
5 SAR EVALUATION	5
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT	5
5.1.1 <i>Standard Requirement</i>	5
5.1.2 <i>Limits</i>	5
5.1.3 <i>EUT RF Exposure</i>	5

4 General Information

4.1 Client Information

Applicant:	iLUV Creative Technology
Address of Applicant:	2 Harbor Park Drive, Port Washington, NY11050, New York, United States
Manufacturer:	Dongguan Jinwenhua Digital Technology Co., Ltd
Address of Manufacturer:	No.1 Huada Road, Longbeiling Industry Zone, Tiangxia Town, Dongguan City, Guangdong Province, China 523700

4.2 General Description of EUT

Product Name:	AUD MINI PLUS
Model No.:	AUDMINIPSXX (XX=COLOR CODE : BK=BLACK; WH=WHITE; PN=PINK...ETC)
Trade Mark:	iLUV
Hardware Version:	V1.3
Software Version:	V1.1
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	4.2
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, $\pi/4$ DQPSK
Number of Channel:	79
Hopping Channel Type:	Adaptive Frequency Hopping systems
Sample Type:	portable production
Test Software of EUT:	FCCAssist V2.4 (manufacturer declare)
Antenna Type:	PCB antenna
Antenna Gain:	-0.58dBi
Power Supply:	lithium battery:DC3.7V Charge by DC5.0V

5 SAR Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

5.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{[\sqrt{f(\text{GHz})}]} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where} \right.$$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

5.1.3 EUT RF Exposure

For BT:

Measurement Data

GFSK mode	
Test channel	Peak Output Power (dBm)
Lowest	-4.21
Middle	-3.46
Highest	-3.64
$\pi/4$ DQPSK mode	
Test channel	Peak Output Power (dBm)
Lowest	-3.22
Middle	-2.58
Highest	-2.69

The Max Conducted Peak Output Power is -2.58dBm in middle channel(2.441GHz);

The best case gain of the antenna is -0.58dBi.

EIRP= -2.58dBm -0.58dBi = -3.16dBm

-3.16dBm logarithmic terms convert to numeric result is nearly 0.48mW

According to the formula. calculate the EIRP test result:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$$

General RF Exposure = $0.48\text{mW} / 5 \text{ mm}) \times \sqrt{2.441\text{GHz}} = 0.15$ ①

SAR requirement:

S= 3.0

② ;

① < ②.

So the SAR report is not required.

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20180400019E-01