

## RF EXPOSURE EVALUATION

### 1. PRODUCT INFORMATION

Product Description	Turntable
Model Name	CR6236A
Series Model	CR6236A-NA, CR6236X-XX (X-XX can be replaced by letter from "A" to "Z" or number from "0" to "9" or blank.) DA-666, DA-XXX (XXX can be by letter from "A" to "Z" or number from "0" to "9" or blank.)
FCC ID	AUSCR6236A

### 2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

Where  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation.

### 3. CALCULATION

$$P_t = 1.561 \text{ dBm} = 1.43 \text{ mW}$$

The value of the Maximum output power  $P_t$  is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation  $\text{SAR} = (1.43 \text{ mW} / 5 \text{ mm}) \cdot [\sqrt{2.402 \text{ GHz}}] = 0.44 < 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

### 4. CONCLUSION

The SAR evaluation is not required.