

FCC EMC Test Report

For

Electromagnetic Interference
Of

Product : TimeLink Multi-touch Screen

Trade Name :  **TimeLink**™
Vision at Fingers

Model Number : TE15, TE17, TE19, TE20, TN21, TN24,
TN26, TN27, iMask-M, iMask-A

Prepared for

TimeLink Technology Co.Ltd.
Room 310, Block C, Yingdali Digital Tech Park, Futian Bonded
Area, Futian District, Shenzhen, Guangdong, China

Prepared by

NTEK Testing Technology Co., Ltd.
1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street
Bao'an District, Shenzhen P.R. China
Tel.: +86-0755-61156588 Fax.: +86-0755-61156599
Website: www.ntek.org.cn

TEST RESULT CERTIFICATION

Applicant's name : TimeLink Technology Co.Ltd.

Address : Room 310, Block C, Yingdali Digital Tech Park, Futian Bonded Area, Futian District, Shenzhen, Guangdong, China

Manufacture's Name : TimeLink Technology Co.Ltd.

Address : Room 310, Block C, Yingdali Digital Tech Park, Futian Bonded Area, Futian District, Shenzhen, Guangdong, China

Product description

Product name : TimeLink Multi-touch Screen

Model and/or type reference : TE15, TE17, TE19, TE20, TN21, TN24, TN26, TN27, iMask-M, iMask-A

Rating(s) : DC 5V, 250mA

Standards : FCC Part15B:2011
ANSI C63.4: 2009

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with the 2004/108/EC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personal only, and shall be noted in the revision of the document.

Date of Test :

Date (s) of performance of tests : 01 Feb. 2012 ~07 Feb. 2012

Date of Issue : 07 Feb. 2012

Test Result : **Pass**

Testing Engineer : Apple Huang

(Apple Huang)

Technical Manager : Jim He

(Jim He)

Authorized Signatory : Bovey Yang

(Bovey Yang)

Table of Contents	Page
1 . TEST SUMMARY	4
1.1 TEST FACILITY	5
1.2 MEASUREMENT UNCERTAINTY	5
2 . GENERAL INFORMATION	6
2.1 GENERAL DESCRIPTION OF EUT	6
2.2 DESCRIPTION OF TEST MODES	7
2.3 DESCRIPTION OF TEST SETUP	8
2.4 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL	9
2.5 MEASUREMENT INSTRUMENTS LIST	10
3 . EMC EMISSION TEST	11
3.1 CONDUCTED EMISSION MEASUREMENT	11
3.1.1 POWER LINE CONDUCTED EMISSION	11
3.1.2 TEST PROCEDURE	12
3.1.3 TEST SETUP	12
3.1.4 EUT OPERATING CONDITIONS	12
3.1.5 TEST RESULTS	13
3.2 RADIATED EMISSION MEASUREMENT	15
3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	15
3.2.2 TEST PROCEDURE	15
3.2.3 TEST SETUP	16
3.2.4 EUT OPERATING CONDITIONS	16
3.2.5 TEST RESULTS	17
3.2.6 TEST RESULTS(Above 1GHz)	20
4 . EUT TEST PHOTO	21
ATTACHMENT PHOTOGRAPHS OF EUT	23

1. TEST SUMMARY

Test procedures according to the technical standards:

EMC Emission				
Standard	Test Item	Limit	Judgment	Remark
FCC Part15B:2011 ANSI C63.4: 2009	Conducted Emission	Class B	PASS	
	Radiated Emission	Class B	PASS	

NOTE:

- (1)" N/A" denotes test is not applicable in this Test Report
- (2) For client's request and manual description, the test will not be executed.

1.1 TEST FACILITY

NTEK Testing Technology Co., Ltd.

Add. : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen P.R. China.

FCC FRN Registration Number:238937; IC Registration Number:9270A-1

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 % .

A. Conducted Measurement :

Test Site	Method	Measurement Frequency Range	U , (dB)	NOTE
NTEKC01	ANSI	150 KHz ~ 30MHz	3.2	

B. Radiated Measurement :

Test Site	Method	Measurement Frequency Range	U , (dB)	NOTE
NTEKA01	ANSI	30MHz ~ 1000MHz	4.7	
		1GHz ~6GHz	5.0	

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	TimeLink Multi-touch Screen				
Brand Name	 TimeLink™ Vision of Fingers				
Model Name.	TE15, TE17, TE19, TE20, TN21, TN24, TN26, TN27, iMask-M, iMask-A				
Serial No	N/A				
Model Difference	All the model are identical except the model name.				
Product Description	<p>The EUT is a TimeLink Multi-touch Screen..</p> <table border="1"><tr><td>Operating frequency:</td><td>OSC 16MHz</td></tr><tr><td>Connecting I/O port:</td><td>USB port</td></tr></table> <p>Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.</p>	Operating frequency:	OSC 16MHz	Connecting I/O port:	USB port
Operating frequency:	OSC 16MHz				
Connecting I/O port:	USB port				
Power Source	DC Voltage				
Power Rating	DC 5V, 250mA				

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.


Pretest Mode	Description
Mode 1	Running

For Conducted Test	
Final Test Mode	Description
Mode 1	Running

For Radiated Test	
Final Test Mode	Description
Mode 1	Running

2.3 DESCRIPTION OF TEST SETUP

Mode 1:



2.4 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	TimeLink Multi-touch Screen	 TimeLink [™] Vision of Fingers	iMask-M	N/A	EUT
E-2	Notebook Computer	IBM	2366	N/A	
E-3	Mouse	HP	MS-SBF96	417441-002REV.OC	

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	100cm	
C-2	NO	Yes	180cm	

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) "YES" is means "shielded" "with core"; "NO" is means "unshielded" "without core".

2.5 MEASUREMENT INSTRUMENTS LIST

2.5.1 CONDUCTED TEST SITE

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	LISN	R&S	ENV216	101313	Jul. 06, 2012
2	LISN	EMCO	3816/2	00042990	Jul. 06, 2012
3	50Ω Switch	ANRITSU CORP	MP59B	6200983704	Jul. 06, 2012
4	Test Cable	N/A	C01	N/A	Jul. 06, 2012
5	Test Cable	N/A	C02	N/A	Jul. 06, 2012
6	Test Cable	N/A	C03	N/A	Jul. 06, 2012
7	EMI Test Receiver	R&S	ESCI	101160	Jul. 06, 2012
8	Passive Voltage Probe	ESH2-Z3	R&S	100196	Jul. 06, 2012
9	Triple-Loop Antenna	EVERFINE	LIA-2	11020003	Jul. 06, 2012
10	Absorbing Clamp	R&S	MDS-21	100423	Jul. 08, 2012

2.5.2 RADIATED TEST SITE

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Bilog Antenna	TESEQ	CBL6111D	31216	Jul. 06, 2012
2	Test Cable	N/A	R-01	N/A	Jul. 06, 2012
3	Test Cable	N/A	R-02	N/A	Jul. 06, 2012
4	EMI Test Receiver	R&S	ESCI-7	101318	Jul. 06, 2012
5	Antenna Mast	EM	SC100_1	N/A	N/A
6	Turn Table	EM	SC100	060531	N/A
7	50Ω Switch	Anritsu Corp	MP59B	6200983705	Jul. 06, 2012
8	Spectrum Analyzer	Aglient	E4407B	MY45108040	Jul. 06. 2012
9	Horn Antenna	EM	EM-AH-10180	2011071402	Jul. 06. 2012
10	Amplifier	EM	EM-30180	060538	Jul. 06. 2012

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *
0.50 -5.0	73.00	60.00	56.00	46.00
5.0 -30.0	73.00	60.00	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 TEST SETUP



3.1.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.


3.1.5 TEST RESULTS

EUT :	TimeLink Multi-touch Screen	Model Name. :	iMask-M
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Test Date :	2012-02-05
Test Mode :	Running	Phase :	L
Test Voltage :	DC 5V from PC		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dB μ V)	(dB)	(dB μ V)	(dB μ V)	(dB)	
0.158	47.72	10.56	58.28	65.56	-7.28	QP
0.158	37.19	10.56	47.75	55.56	-7.81	AVG
0.202	37.32	10.43	47.75	63.52	-15.77	QP
0.2099	25.95	10.43	36.38	53.21	-16.83	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	TimeLink Multi-touch Screen	Model Name. :	iMask-M
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Test Date :	2012-02-05
Test Mode :	Running	Phase :	N
Test Voltage :	DC 5V from PC		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dB μ V)	(dB)	(dB μ V)	(dB μ V)	(dB)	
0.1539	33.77	11.17	44.94	55.78	-10.84	AVG
0.158	47.02	10.69	57.71	65.56	-7.85	QP
0.21	29.73	10.44	40.17	53.2	-13.03	AVG
0.262	34.72	10.43	45.15	61.36	-16.21	QP

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.

100.0 dB μ V

3.2 RADIATED EMISSION MEASUREMENT

3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Class A (at 10m)	Class B (at 3m)
	dBuV/m	dBuV/m
30 ~ 88	39.0	40.0
88 ~ 216	43.5	43.5
216 ~ 960	46.5	46.0
Above 960	49.5	54.0

Notes:


- (1) The limit for radiated test was performed according to as following:
FCC PART 15B /ICES-003.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

3.2.2 TEST PROCEDURE


- a. The measuring distance of at 10 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured, above 1G Average detector mode will be instead.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP(AV) Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.2.3 TEST SETUP

(A) Radiated Emission Test Set-Up Frequency Below 1 GHz



(B) Radiated Emission Test Set-Up Frequency Above 1GHz



3.2.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.5 TEST RESULTS(Blow 30MHZ)

EUT :	TimeLink Multi-touch Screen	Model Name :	iMASK-M
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2012-02-05
Test Mode :	TX	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $20 \log (\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuV) + distance extrapolation factor.


3.2.6 TEST RESULTS(30MHZ-1GHZ)

EUT :	TimeLink Multi-touch Screen	Model Name :	iMASK-M
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2012-02-05
Test Mode :	Running	Polarization :	Horizontal
Test Power :	DC 5V from PC		

Freq. (MHz)	Reading (dBuV)	Factor (dBuV)	Measurement (dBuV)	Limit (dBuV)	Over (dB)	Detector
52.9453	29.16	6.84	36	40	-4	QP
66.7325	30.61	5.49	36.1	40	-3.9	QP
121.9753	23.08	11.82	34.9	43.5	-8.6	QP
204.2375	27.73	8.87	36.6	43.5	-6.9	QP
261.9753	27.55	14.15	41.7	46	-4.3	QP
401.8385	21.51	17.28	38.79	46	-7.21	QP

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Antenna Factor + Cable Loss.
3. N/A means All Data have pass Limit




EUT :	TimeLink Multi-touch Screen	Model Name :	iMASK-M
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2012-02-05
Test Mode :	Running	Polarization :	Vertical
Test Power :	DC 5V from PC		

Freq. (MHz)	Reading (dBuV)	Factor (dBuV)	Measurement (dBuV)	Limit (dBuV)	Over (dB)	Detector
42.3021	23.04	12.06	35.1	40	-4.9	QP
47.6584	26.81	9.29	36.1	40	-3.9	QP
66.266	31.13	5.45	36.58	40	-3.42	QP
122.834	23.55	11.85	35.4	43.5	-8.1	QP
273.2341	21.7	13.41	35.11	46	-10.89	QP
499.4245	19.49	19.42	38.91	46	-7.09	QP

Remark:


1. All readings are Quasi-Peak and Average values.
2. Factor = Antenna Factor + Cable Loss.
3. N/A means All Data have pass Limit





3.2.7 TEST RESULTS(Above 1GHz)

EUT :	TimeLink Multi-touch Screen	Model Name :	iMASK-M
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	N/A
Test Mode :	N/A	Polarization :	N/A
Test Power :	N/A		

Note: The operating frequency is 16MHz(osc), radiated emission above 1GHz don't need test.

4. EUT TEST PHOTO**Radiated Measurement Photos**

Conducted Measurement Photos

ATTACHMENT PHOTOGRAPHS OF EUT**Photo 1****Photo 2**

Photo 3




Photo 4




Photo 5




Photo 6




Photo 7




Photo 8




Photo 9




Photo 10

