



APPENDIX I

RADIO FREQUENCY EXPOSURE

LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

EUT Specification

EUT	Wireless module
Frequency band (Operating)	☒ WLAN: 2.412GHz ~ 2.462GHz ☐ WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz ☐ WLAN: 5.745GHz ~ 5.825GHz ☐ Others
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation) ☐ Others
Exposure classification	☒ Occupational/Controlled exposure ($S = 5\text{mW}/\text{cm}^2$) ☐ General Population/Uncontrolled exposure ($S=1\text{mW}/\text{cm}^2$)
Antenna diversity	☒ Single antenna ☐ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Max. output power	IEEE 802.11b mode: 15.41 dBm (34.75 mW) IEEE 802.11g mode: 19.44 dBm (87.90 mW) IEEE 802.11n HT 20 MHz Channel mode: 18.56 dBm (71.78 mW) IEEE 802.11n HT 40 MHz Channel mode: 16.59 dBm (45.60 mW)
Antenna gain (Max)	2.45 dBi (Numeric gain: 1.76)
Evaluation applied	☒ MPE Evaluation* ☐ SAR Evaluation ☐ N/A

Remark:

The maximum output power is 19.44dBm (87.90 mW) at 2442MHz (with 1.76 numeric antenna gain.)

MPE EVALUATION

No non-compliance noted.

**Calculation**

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{3770}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

Maximum Permissible Exposure

Substituting the MPE safe distance using $d = 20$ cm into Equation 1:

Yields

$$S = 0.000199 \times P \times G$$

Where P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²



IEEE 802.11b mode:

EUT output power = 34.75 mW

Numeric Antenna gain = 1.76

→ Power density = $0.01217 \text{ mW} / \text{cm}^2$

IEEE 802.11g mode:

EUT output power = 87.90 mW

Numeric Antenna gain = 1.76

→ Power density = $0.03079 \text{ mW} / \text{cm}^2$

IEEE 802.11n HT 20 MHz mode:

EUT output power = 71.78 mW

Numeric Antenna gain = 1.76

→ Power density = $0.02514 \text{ mW} / \text{cm}^2$

IEEE 802.11n HT 40 MHz mode:

EUT output power = 45.60 mW

Numeric Antenna gain = 1.76

→ Power density = $0.01597 \text{ mW} / \text{cm}^2$

(For mobile or fixed location transmitters, the maximum power density is $1.0 \text{ mW}/\text{cm}^2$ even if the calculation indicates that the power density would be larger.)