

OPERATIONAL DESCRIPTION**A. Transmitter Technical Characteristics -- Pursuant 2.983 (d)**

| | |
|---|-------------------------------------|
| a. RF Power Output: | 1W to 4.5 Watt Variable Power |
| b. Transmit Frequency Range: | 403 –470 MHz |
| c. Receive Frequency Range: | 403 – 470 MHz |
| d. Frequency Stability: | 2.5 PPM |
| e. Emissions | 16K0F3E & 11K0F3E (See Exhibit 8-5) |
| f. Spurious Emissions | 25uW |
| g. DC Voltage and Current into the final RF amplifier stage/stages | 7.5 VDC 1.5 A |

B. Transmitter Application

This transmitter is primarily intended for use in a portable environment. It is characterized by the following features, options, and accessories.

- a. Power Supply Available:
 - i. NiCd AFAT Battery
 - ii. NiCd Battery
 - iii. NiMH AA Battery
 - iv. NiMH AA FM Battery

- b. Antenna Available:
 - i. Helical Antenna
 - ii. Whip antenna

- c. Squelch Type Available:
 - i. Carrier Squelch
 - ii. Tone “Private Line”
 - iii. Digital “Private Line”
 - iv. DTMF
 - v. Quick Call II

- d. Microphone - Control:
 - i. Handset/Palm Microphone

- e. Maximum Transmit Channel Capability:
 - i. 16 Channel

- f. Housing:
 - i. The transmitter will be housed in the housing shown in the accompanying photographs

- g. Other Options:
 - i. Time out Timer

- h. The minimum voltage for the micro-Processor to operate is 3.3V.