



DECLARATION OF COMPLIANCE SAR ASSESSMENT Part 1 of 2

Motorola Solutions Inc.
EME Test Laboratory
 8000 West Sunrise Blvd
 Fort Lauderdale, FL. 33322.

Date of Report: 5/17/12
Report Revision: A
Report ID: SR10288 APX4000 U2 1 of 2
 Rev A 120517

Responsible Engineer: Michael Sailsman (Senior Staff Eng.)
Report Author: Michael Sailsman (Senior Staff Eng.)
Date/s Tested: 2/17/12-3/8/12; 3/16/12
Manufacturer/Location: Penang
Sector/Group/Div.: AESS Astro Engineering Subscriber Solutions
Date submitted for test: 2/02/12
DUT Description: 450 - 520MHz 3-5.6W 6.25K/12.5K/25K, Single Display Model full keypad. Capable of digital TDMA and analog FM transmission.

Test TX mode(s): CW (PTT)
Max. Power output: 5.6W
Nominal Power: 5.0W
Tx Frequency Bands: 450 - 520 MHz
Signaling type: FM; TDMA
Model(s) Tested: H51SDH9PW7AN (MUE3771)
Model(s) Certified: H51SDH9PW7AN (MUE3771)
Serial Number(s): 426TNB0563, 426TNB0531
Classification: Occupational/Controlled
FCC ID: AZ489FT4909; Rule Part 90 450-512MHz. Results outside this band are not applicable to demonstrate FCC compliance.

* Refer to section 15 of part 1 for highest SAR summary results.

The test results clearly demonstrate compliance with FCC Occupational/Controlled RF Exposure limits of 8 W/kg averaged over 1 gram per the requirements of 47 CFR 2.1093(d). The 10 grams result is not applicable to FCC filing. The test results clearly demonstrate compliance with ICNIRP (1998) Guidelines for limiting exposure in time-varying electric, magnetic, and electromagnetic fields (up to 300 GHz), Health Physics 74, 494-522 RF Exposure limits of 10 W/kg averaged over 10grams of contiguous tissue.

Based on the information and the testing results provided herein, the undersigned certifies that when used as stated in the operating instructions supplied, said product complies with the national and international reference standards and guidelines listed in section 3.0 of this report. This report shall not be reproduced without written approval from an officially designated representative of the Motorola Solutions Inc EME Laboratory.
I attest to the accuracy of the data and assume full responsibility for the completeness of these measurements. This reporting format is consistent with the suggested guidelines of the TIA TSB-150 December 2004. The results and statements contained in this report pertain only to the device(s) evaluated.

Deanna Zakharia
EMS EME Lab Senior Resource Manager,
Laboratory Director
Approval Date: 5/18/2012

Certification Date: 3/20/2012

Certification No.: L1120305P

Part 1 of 2

1.0	Introduction.....	4
2.0	Abbreviations / Definitions.....	4
3.0	Referenced Standards and Guidelines.....	4
4.0	SAR Limits	5
5.0	SAR Result Scaling Methodology.....	5
6.0	Description of Device Under Test (DUT).....	6
7.0	Optional Accessories and Test Criteria.....	7
7.1	Antennas	7
7.2	Batteries	7
7.3	Body worn Accessories.....	7
7.4	Audio Accessories	8
8.0	Description of Test System.....	10
8.1	Descriptions of Robotics/Probes/Readout Electronics	10
8.2	Description of Phantom(s).....	11
8.2.1	Dual Flat Phantom	11
8.2.2	SAM Phantom.....	11
8.2.3	Elliptical Phantom.....	11
8.3	Description of Simulated Tissue.....	11
9.0	Test System and Equipments	12
10.0	SAR System Check.....	13
10.1	System Check Test Results	16
11.0	Environmental Test Conditions	17
12.0	DUT Test Methodology.....	17
12.1	Measurements	17
12.2	DUT Configuration(s).....	17
12.3	DUT Positioning Procedures	17
12.3.1	Body	18
12.3.2	Head	18
12.3.3	Face.....	18
12.4	DUT Test Channels.....	18
12.5	DUT Test Plan	18
13.0	DUT Test Data.....	19
13.1	Assessments at the Body (450-512 MHz band).....	19
13.2	Assessments at the Body with Body worn PMLN4651A	19
13.3	Assessments at the Body with Body worn PMLN7008A	21
13.4	Assessments at the Body with Body worn PMLN6085A	22
13.5	Assessments at the Body with Body worn PMLN6085A/NTN5243A.....	22
13.6	Assessment at body with other offered audio accessories	23
13.7	Assessments of wireless BT configurations.....	29
13.8	Assessment outside FCC Part 90 at the body (512-520 MHz)	29
13.9	Assessments at the Face (450-512 MHz band).....	30
13.10	Assessment outside FCC Part 90 at the Face (512-520 MHz).....	31
13.11	Assessment of BT band	31
13.12	Shorten Scan Assessment	31
14.0	Simultaneous Transmission Exclusion	32
15.0	Conclusion	32

APPENDICES

A Measurement Uncertainty33
 B Probe Calibration Certificates36
 C Dipole Calibration Certificates50

Part 2 of 2

D System Check Scans2
 E FCC Part 90 (450-512 MHz band)
 DUT Scans (Shortened Scan and Highest SAR configurations)15
 F DUT scans - FCC Part 90 (450-512 MHz band)19
 G DUT scans – Outside FCC Part 90 (512-520 MHz band)42
 H DUT Supplementary Data (Power Slump)45
 I DUT Test Position Photos46
 J DUT, Body worn and audio accessories Photos47

Report Revision History

Date	Revision	Comments
3/19/12	O	Initial release
5/17/12	A	Revise sections 9.0, 10.0, 10.2, appendix D

1.0 Introduction

This report details the utilization, test setup, test equipment, and test results of the Specific Absorption Rate (SAR) measurements performed at the Motorola Solutions Inc. EME Test Laboratory for model number H51SDH9PW7AN (MUE3771)

2.0 Abbreviations / Definitions

CNR: Calibration Not Required

EME: Electromagnetic Energy

C4FM CQPSK: Continuous 4 level Frequency modulation Compatible Quadrature Phase-Shift Keying

CW: Continuous Wave

F2: 2 slot TDMA

DSP: Digital signal processing

DUT: Device Under Test

DC: Duty Cycle

FM: Frequency Modulation/Factory Mutual

NA: Not Applicable

PTT: Push to Talk

RSM: Remote Speaker Microphone

SAR: Specific Absorption Rate

TDMA: Time Division Multiple Access

Audio accessories: These accessories allow communication while the DUT is worn on the body.

Body worn accessories: These accessories allow the DUT to be worn on the body of the user.

Maximum Power: Defined as the upper limit of the production line final test station.

3.0 Referenced Standards and Guidelines

This product is designed to comply with the following applicable national and international standards and guidelines.

- IEC62209-1*(2005) Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)
- United States Federal Communications Commission, Code of Federal Regulations; Rule Part 47CFR § 2.1093(d) sub-part J:2011
- Federal Communications Commission, “Evaluating Compliance with FCC Guidelines for Human Exposure to Radio frequency Electromagnetic Fields”, OET Bulletin 65, Supplement C (Edition 01-01), FCC, Washington, D.C.: June 2001.
- IEEE 1528*(2003), Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
- American National Standards Institute (ANSI) / Institute of Electrical and Electronics Engineers (IEEE) C95. 1-1992

- Institute of Electrical and Electronics Engineers (IEEE) C95.1-2005
- International Commission on Non-Ionizing Radiation Protection (ICNIRP) 1998
- Ministry of Health (Canada) Safety Code 6 (2009), Limits of Human Exposure to Radio frequency Electromagnetic Fields in the Frequency Range from 3 kHz to 300 GHz
- Australian Communications Authority Radio communications (Electromagnetic Radiation - Human Exposure) Standard (2003)
- ANATEL, Brazil Regulatory Authority, Resolution No. 303 of July 2, 2002 "Regulation of the limitation of exposure to electrical, magnetic, and electromagnetic fields in the radio frequency range between 9 kHz and 300 GHz." and "Attachment to resolution # 303 from July 2, 2002"
- IEC62209-2 Edition 1.0 2010-03, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Human models, instrumentation, and procedures – Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz).

* The IEC62209-1 and IEEE 1528 are applicable for hand-held devices used in close proximity to the ear only.

4.0 SAR Limits

TABLE 1

EXPOSURE LIMITS	SAR (W/kg)	
	(General Population / Uncontrolled Exposure Environment)	(Occupational / Controlled Exposure Environment)
Spatial Average - ANSI - (averaged over the whole body)	0.08	0.4
Spatial Peak - ANSI - (averaged over any 1-g of tissue)	1.6	8.0
Spatial Peak – ICNIRP/ANSI - (hands/wrists/feet/ankles averaged over 10-g)	4.0	20.0
Spatial Peak - ICNIRP - (Head and Trunk 10-g)	2.0	10.0

5.0 SAR Result Scaling Methodology:

The calculated 1-gram and 10-gram averaged SAR results indicated as “Max Calc. 1g-SAR” and “Max Calc.10g-SAR” in the data tables is determined by scaling the measured SAR to account for power leveling variations and power slump. A table and graph of output power versus time is provided in APPENDIX H. For this device the “Max Calc. 1g-SAR” and “Max Calc.10g-SAR” are scaled using the following formula:

$$Max_Calc = SAR_meas \cdot 10^{\frac{-Drift}{10}} \cdot \frac{P_max}{P_int} \cdot DC$$

P_{max} = Maximum Power (W)
 P_{int} = Initial Power (W)
 Drift = DASY drift results (dB)
 SAR_{meas} = Measured 1-g or 10-g Avg. SAR (W/kg)
 DC = Transmission mode duty cycle in % where applicable
 50% duty cycle is applied for PTT operation

Note: for conservative results, the following are applied:

If $P_{int} > P_{max}$, then $P_{max}/P_{int} = 1$.

Drift = 1 for positive drift

Additional SAR scaling was applied using the methodologies outlined in FCC KDB450824 using tissue sensitivity values. SAR was scaled for conditions where the tissue permittivity was measured above the nominal target and for tissue conductivity that was measured below the nominal target.

6.0 Description of Device Under Test (DUT):

This device operates using TDMA and analog frequency modulation (FM) signaling incorporating traditional simplex two-way radio transmission protocol.

Time Division Multiple Access (TDMA) is used to allocate portions of the RF signal by dividing time into two slots. Time allocation enables each unit to transmit its voice information without interference from other transmitting units. Transmission from a unit or base station is accommodated during two time-slot lengths of 30 milliseconds with frame length of 60 milliseconds. C4FM CQPSK modulation is used at 12.5 kHz channel spacing. The TDMA technique requires sophisticated algorithms and a digital signal processor (DSP) to perform voice compressions/decompressions and RF modulation/demodulation. The maximum duty cycle for TDMA is 50% for F2 (2 slot TDMA) protocol and is controlled by software. The FM signal is continuous. However, because of hand shaking or Push-To-Talk (PTT) between users and/or base stations a conservative 50% duty cycle is applied.

The model represented under this filing utilizes removable antennas, (UHF band) capable of transmitting in the 450-520 MHz band. The UHF band nominal output power is 5.0W with maximum output power of 5.6 W as defined by the upper limit of the production line final test station. The intended operating positions are “at the face” with the DUT at least 1 inch from the mouth, and “at the body” by means of the offered body worn accessories. Body worn audio and PTT operation is accomplished by means of optional remote accessories that are connected to the radio.

7.0 Optional Accessories and Test Criteria:

This device is offered with optional accessories. All accessories were individually evaluated during the test plan creation to determine if testing was required per the guidelines outlined in “SAR Test Reduction Considerations for Occupational PTT Radios” FCC KDB 643646 D01 dated 4/4/11 to assess compliance of this device. The following sections identify the test criteria and details for each accessory category.

7.1 Antennas:

There are two UHF band antennas offered for this product. The table below lists their descriptions.

TABLE 2

Antenna Models	Description	Selected for test	*Tested
PMAE4065A	Whip UHF/GPS antenna (380- 520MHz/1575 MHz) ¼ wave, -10dBd	Yes	Yes
FAF5260A	UHF2/GPS stubby antenna (450- 520MHz/1575MHz) ¼ waves -2.0dBd	Yes	Yes

*Refer to Exhibit 7B for antenna separation distances.

7.2 Batteries:

There are three batteries offered for this product. The table below lists the batteries, and battery description.

TABLE 3

Battery Models	Description	Selected for test	*Tested	Comments
NNTN8128A	IMPRES Li Ion slim battery (Non FM 1900 mAh)	Yes	Yes	
NNTN8129A	IMPRES Hi-Cap Li-Ion FM 2300mAh	Yes	Yes	
PMNN4424A	IMPRES Li Ion High capacity Non FM 2300mAh	Yes	Yes	

*Refer to Exhibit 7B for antenna separation distances.

7.3 Body worn Accessories:

All body worn accessories were considered. The table below lists the body worn accessories, and body worn accessory descriptions.

TABLE 4

Body worn Models	Description	Selected for test	*Tested	Comments
PMLN6085A	Leather carry case w/ 2.5” swivel belt loop	Yes	Yes	
PMLN7008A	2.5” Belt clip	Yes	Yes	
PMLN4651A	2.0” Belt clip	Yes	Yes	
NTN5243A	Carry strap	Yes	Yes	Tested with PMLN6085A

*Refer to Exhibit 7B for antenna separation distances.

7.4 Audio Accessories:

All audio accessories were considered. The table below lists the offered audio accessories and their descriptions. Exhibit 7B illustrates photos of the tested audio accessories.

TABLE 5

Audio Acc. Models	Description	Selected for test	*Tested	Comments
HMN4104B	IMPRES Display Submersible RSM w/jack & Ch. Selector	Yes	Yes	
RMN5116A	Temple Transducer Headset	Yes	Yes	Tested with HMN4104B
HMN4101B	RSM w/o Display and w/o Channel Knob	No	No	Similar to HMN4104B – same cable length and connector pins
HMN4103B	Display RSM w/o Channel Knob	No	No	Similar to HMN4104B – same cable length and connector pins
RLN6424A	Rx-Only Secondary Audio Accessory for DRSM	No	No	Similar to RMN5116A – connects to RSM
PMLN5275C	Core H/D headset	Yes	Yes	
PMLN5111A	Plus 3-wire – Black - One programmable button	Yes	Yes	
PMLN5112A	Plus 3 wire - Beige-one programmable button	No	No	Similar to PMLN5111A
PMMN4062A	Large Plus Noise cancelling RSM IP55 3.5MM jack	Yes	Yes	
PMMN4069A	APX Basic Smart RSM, IP55	No	No	Similar to PMMN4062A
PMMN4025A	Smart RSM	No	No	Similar to PMMN4062A - same cable length and connector pins
PMMN4065A	Standard Large IP57 RSM	Yes	Yes	
PMMN4024A	Core RSM	Yes	Yes	
PMLN5101A	IMPRES Temple Transducer	Yes	Yes	
RMN5058A	Core L/W Headset	Yes	Yes	
RLN5879A	Core 1 wire – Beige	No	No	Receive only
RLN5878A	Core 1 wire – Black	No	No	Receive only
RLN5882A	Plus 2-wire with translucent tube – Black - One programmable button	Yes	Yes	
RLN5881A	Plus 2-wire Beige – one programmable button	No	No	Similar to RLN5882A
RLN5880A	Plus 2-wire Black – one programmable button	No	No	Similar to RLN5882A
RLN5883A	Plus 2-wire with translucent tube – Beige – one programmable button	No	No	Similar to RLN5882A

TABLE 5 (Continued)

Audio Acc. Models	Description	Selected for test	*Tested	Comments
AARLN4885B	3.5mm RX only earbud for REM spk mic short coiled cable	No	No	Receive only
WADN4190B	3.5mm ear receive w/coil cable - short	No	No	Similar to AARLN4885B - same cable length and connector pins
RLN4941A	3.5 mm Receive only Earpiece w/translucent tube – short coiled cable	No	No	Receive only
PMLN4620A	Rx-only earpiece	No	No	Receive only
RLN5886A	Low Noise Kit - tube	No	No	Receive only
RLN5887A	High Noise Kit	No	No	Receive only
PMMN4040A	IMPRES IP57 Submersible Remote Speaker Microphone	Yes	Yes	
PMMN4046A	IMPRES SPEAKER MIC W/VOL, IP57	Yes	Yes	
PMMN4050A	IMPRES REMOTE SPEAKER MIC, NC	Yes	Yes	
PMLN5102A	CORE ULTRA-LITE HEADSET	Yes	Yes	
PMLN5096A	CORE EARSET - D-SHELL	Yes	Yes	
PMLN5097A	IMPRES 3 WIRE SURVEILLANCE-BLACK	Yes	Yes	
PMLN5106A	IMPRES 3 WIRE SURVEILLANCE-BEIGE	No	No	Similar to PMLN5097A – different color
PMLN5653A	IMPRES Ear Mic System	Yes	Yes	

8.0 Description of Test System:



8.1 Descriptions of Robotics/Probes/Readout Electronics:

The laboratory utilizes a Dosimetric Assessment System (DASY5™) SAR measurement system Version 52.6.2.424 manufactured by Schmid & Partner Engineering AG (SPEAG™), of Zurich Switzerland. The test system consists of a Stäubli RX90L robot, DAE and E-field probe. The DASY5™ system is operated per the instructions in the DASY5™ Users Manual. The complete manual is available directly from SPEAG™. All measurement equipment used to assess EME SAR compliance was calibrated according to ISO/IEC 17025 A2LA guidelines. Section 9.0 presents additional test equipment information. Appendices B and C present the applicable calibration certificates. The E-field probe first scans a coarse grid over a large area inside the phantom in order to locate the interpolated maximum SAR distribution. After the coarse scan measurement, the probe is automatically moved to a position at the interpolated maximum. The subsequent scan can directly use this position as reference for the cube evaluations.

8.2 Description of Phantom(s)

8.2.1 Dual Flat Phantom

Not Applicable

8.2.2 SAM Phantom

Not Applicable

8.2.3 Elliptical Phantom

TABLE 6

Phantom ID (s)	Material Parameters	Phantom Dimensions LxWxD (mm)	Material Thickness (mm)	Support Structure Material	Loss Tangent (wood)
OVAL1090 OVAL1108	300MHz -6GHz; Er = 4+/- 1, Loss Tangent = ≤0.05	600x400x190	2mm +/- 0.2mm	Wood	< 0.05

8.3 Description of Simulated Tissue:

The simulated tissue used is compliant to that specified in FCC Supplement C (Edition 01-01) to OET Bulletin 65 (Edition 97-01) and IEEE Std 1528 - 2003 "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques". The simulated tissue used is also compliant to that specified in IEC62209-1 (2005) and adopted by CENELEC as EN62209-1 (2006).

The sugar based simulate tissue is produced by placing the correct measured amount of De-ionized water into a large container. Each of the dried ingredients are weighed and added to the water carefully to avoid clumping. If the solution has a high sugar concentration the water is pre-heated to aid in dissolving the ingredients. For Diacetin and similar type simulates, sugar and HEC ingredients are not needed. The solution is mixed thoroughly, covered, and allowed to sit overnight prior to use.

The simulated tissue mixture was mixed based on the Simulated Tissue Composition indicated in the table below for 450MHz. During the daily testing of this product, the applicable mixture was used to measure the Di-electric parameters for each of the tested frequencies to verify that the Di-electric parameters were within the tolerance of the tissue specifications.

Simulated Tissue Composition (by mass)

TABLE 7

% of listed ingredients	450 MHz	
	Head	Body
Sugar	56.0	46.5
Diacetin	NA	NA
De ionized -Water	39.1	50.53
Salt	3.8	1.87
HEC	1.00	1.00
Bact.	0.10	0.10

Reference section 10.1 for target parameters

9.0 Test System and Equipments:

The table below lists the test system and equipments used during the SAR assessment.

TABLE 8

Equipment Type	Model Number	Serial Number	Calibration Date	Calibration Due Date
Power Meter (Agilent)	E4419B	MY50000505	9/6/2011	9/6/2012
E-Series Avg. Power Sensor (Agilent)	E9301B	MY41495730	4/22/2011	4/22/2012
E-Series Avg. Power Sensor (Agilent)	E9301B	MY41495733	4/28/2011	4/28/2012
Bi-Directional Coupler (NARDA)	3020A	40295	6/3/2010	6/3/2012
Bi-Directional Coupler (NARDA)	3022	70181	11/14/2011	11/14/2013
Power Meter (Agilent)	E4418B	US39251150	4/6/2011	4/6/1012
Avg. Power Sensor (Agilent)	8481B	3318A10982	4/2/2011	4/2/2012
Signal Generator (Agilent)	E4421B	US40051446	8/12/2010	8/12/2012
AMP (Amplifier Research)	1W1000	16625	CNR	CNR
Dickson Temperature Recorder	TM125	1195889	3/9/2011	3/9/2012
Dickson Temperature Recorder	TM320	7081356	9/7/2011	9/7/2012
Omega Digital Thermometer with J Type TC Probe	HH202A	18812	5/3/2011	5/3/2012
Agilent PNA-L Network Analyzer	N5230A	MY45001092	6/9/2011	6/9/2012
Dielectric Probe Kit (HP)	85070C	US99360076	CNR	CNR
Speag Dipole	D450V3	1077	11/15/2011	11/15/2013
SPEAG probe	ES3DV3	3163	4/13/11	4/13/12
DAE	DAE4	729	6/20/11	6/20/12

TABLE 8 (Continued)

Equipment Type	Model Number	Serial Number	Calibration Date	Calibration Due Date
DASY 5	Stäubli RX90L robot	Version 52.6.2.424	NA	NA

10.0 SAR System Check:

The system performance check was conducted daily and within 24 hours prior to testing. DASY output files of the probe/dipole calibration certificates and system check test results are included in appendices B, C, D respectively.

Equivalent Tissue Test Results:

Simulated tissue prepared for SAR measurements is measured daily and within 24 hours prior to actual SAR testing to verify that the tissue is within +/- 5% of target parameters at the center of the transmit band. This measurement is done using the applicable equipment indicated in section 9.0. The table below summarizes the measured tissue parameters used for the SAR assessment.

TABLE 9

Frequency (MHz)	Tissue Type	Conductivity Target (S/m)	Dielectric Constant Target	Conductivity Meas. (S/m)	Dielectric Constant Meas.	Tested Date
450	IEEE/ IEC Head	0.87 (0.83-0.91)	43.5 (41.3-45.7)	0.84	42.9	2/25/12
450	FCC Body	0.94 (0.89-0.99)	56.7 (53.9-59.5)	0.93	57.4	2/17/12
				0.90	55.2	2/18/12
				0.91	57.0	2/19/12
				0.92	58.1	2/20/12
				0.91	57.6	2/21/12
				0.92	56.9	2/22/12
				0.93	56.7	2/23/12
				0.93	56.7	2/24/12
				0.93	56.5	2/25/12
				0.91	56.2	3/5/12
				0.91	56.4	3/8/12
				0.92	57.4	3/16/12
466	FCC Body	0.94 (0.89-0.99)	56.6 (53.8-59.5)	0.94	57.1	2/17/12
				0.91	54.8	2/18/12
				0.93	56.9	2/19/12
				0.94	57.9	2/20/12
				0.92	57.4	2/21/12
				0.93	56.7	2/22/12
				0.94	56.5	2/23/12
				0.94	56.4	2/24/12
				0.94	56.2	2/25/12
				0.93	57.0	3/16/12
481	FCC Body	0.94 (0.90-0.99)	56.6 (53.8-59.4)	0.93	54.6	2/18/12
				0.94	56.8	2/19/12
				0.95	57.6	2/20/12
				0.94	57.2	2/21/12
				0.94	56.4	2/22/12
				0.95	56.3	2/23/12
				0.95	56.2	2/24/12

TABLE 9 (Continued)

497	FCC Body	0.94 (0.90-0.99)	56.5 (53.7-59.3)	0.94	54.7	2/18/12
				0.97	57.4	2/20/12
				0.95	56.9	2/21/12
				0.97	56.9	2/22/12
				0.97	56.1	2/23/12
				0.97	56.0	2/24/12
503	FCC Body	0.94 (0.90-0.99)	56.5 (53.7-59.3)	0.95	54.7	2/18/12
				0.97	57.3	2/20/12
				0.96	56.8	2/21/12
				0.96	56.1	2/22/12
				0.97	56.0	2/23/12
				0.97	55.9	2/24/12
512	IEEE/ IEC Head	0.87 (0.83-0.92)	43.2 (41.0-45.3)	0.89	41.6	2/25/12
512	FCC Body	0.94 (0.90-0.99)	56.5 (53.7-59.3)	0.97	56.6	2/17/12
				0.96	54.9	2/18/12
				0.97	56.6	2/19/12
				0.98	57.2	2/20/12
				0.96	56.7	2/21/12
				0.97	56.0	2/22/12
				0.98	55.9	2/23/12
0.98	55.7	2/24/12				
512.5/513	IEEE/ IEC Head	0.87 (0.83-0.92)	43.2 (41.0-45.3)	0.89	41.6	2/25/12
				0.89	42.7	3/5/12
512.5/513	FCC Body	0.94 (0.90-0.99)	56.5 (53.7-59.3)	0.97	56.2	3/16/12
516	IEEE/ IEC Head	0.88 (0.83-0.92)	43.2 (41.0-45.3)	0.89	41.6	2/25/12
				0.90	42.7	3/5/12
516	FCC Body	0.95 (0.90-0.99)	56.4 (53.6-59.3)	0.98	56.1	3/16/12
520	IEEE/ IEC Head	0.88 (0.83-0.92)	43.1 (41.0-45.3)	0.90	41.5	2/25/12
				0.90	42.6	3/5/12
520	FCC Body	0.95 (0.90-0.99)	56.4 (53.6-59.2)	0.98	56.1	3/16/12

10.1 System Check Test Results:

System performance checks were conducted each day during the SAR assessment. The results are normalized to 1W. APPENDIX D includes DASY plots for each day during the SAR assessment. The table below summarizes the daily system check results used for the SAR assessment.

TABLE 10

Probe Serial #	Tissue Type	Dipole Kit / Serial #	Reference SAR @ 1W (W/kg)	System Check Test Results when normalized to 1W (W/kg)	Tested Date
3163	FCC Body	SPEAG D450V3 /1077	4.49 (+/- 10%)	4.52	2/17/12
				4.44	2/18/12
				4.48	2/19/12
				4.52	2/20/12
				4.56	2/21/12
				4.52	2/22/12
				4.56	2/23/12
				4.60	2/24/12
				4.56	2/25/12
				4.52	3/5/12
				4.52	3/8/12
				4.52	3/16/12

11.0 Environmental Test Conditions:

The EME Laboratory's ambient environment is well controlled resulting in very stable simulated tissue temperature and therefore stable dielectric properties. Simulated tissue temperature is measured prior to each scan to insure it is within $\pm 2^{\circ}\text{C}$ of the temperature at which the dielectric properties were determined. The liquid depth within the phantom used for measurements was at least 15cm. Additional precautions are routinely taken to ensure the stability of the simulated tissue such as covering the phantoms when scans are not actively in process in order to minimize evaporation. The lab environment is continuously monitored. The table below presents the range and average environmental conditions during the SAR tests reported herein:

TABLE 11

	Target	Measured
Ambient Temperature	18 - 25 °C	Range: 21.4-23.9°C Avg. 22.0°C
Relative Humidity	30 - 70 %	Range: 27.4-66.0% Avg. 51.3%
Tissue Temperature	NA	Range: 20.9-22.5°C Avg. 21.6C

Relative humidity target range is a recommended target

The EME Lab RF environment uses a Spectrum Analyzer to monitor for extraneous large signal RF contaminants that could possibly affect the test results. If such unwanted signals are discovered the SAR scans are repeated.

12.0 DUT Test Methodology

12.1 Measurements

SAR measurements were performed using the DASY system described in section 8.0 using zoom scans. Elliptical flat phantoms filled with applicable simulated tissue were used for body and face testing.

12.2 DUT Configuration(s)

The DUT is a portable device operational at the body and face as described in section 6.0 while using the applicable accessories listed in section 7.0. All accessories listed in section 7.0 of this report were considered when implementing the guidelines specified in KDB 643646 D01.

12.3 DUT Positioning Procedures

The positioning of the device for each body location is described below and illustrated in APPENDIX I.

12.3.1 Body:

The DUT was positioned in normal use configuration against the phantom with the offered body worn accessory as well as with the offered audio accessories as applicable.

12.3.2 Head:

Not applicable.

12.3.3 Face:

The DUT was positioned with its' front side separated 2.5cm from the phantom.

12.4 DUT Test Channels:

The number of test channels was determined by using the following IEEE 1528 equation. The use of this equation produces the same or more test channels compared to the FCC KDB 447498 number of test channels formula.

$$N_c = 2 * \text{roundup}[10 * (f_{\text{high}} - f_{\text{low}}) / f_c] + 1$$

Where

N_c = Number of channels

F_{high} = Upper channel

F_{low} = Lower channel

F_c = Center channel

12.5 DUT Test Plan:

The guidelines and requirements outlined in “SAR Test Reduction Considerations for Occupational PTT Radios” FCC KDB 643646 D01 dated 4/4/11 for head (face) and body were used to assess compliance of this device. All modes of operation identified in section 6.0 were considered during the development of the test plan. All tests were performed in 100% CW mode and then 50% duty cycle was applied to the final results. In some cases the initial power listed herein may exceed the reported maximum power due to software step size tuning limitations. However, the initial powers measured are not greater than the allowed 5% of the reported maximum power.

13.0 DUT Test Data

13.1 Assessment at the Body (450-512 MHz band):

The battery NNTN8128A was selected as default battery for assessments at the Body since it is the thinnest battery (refers to Exhibit 7B for the dimension of the battery). The conducted power measurement for all test channels within part 90 frequency range using the default battery NNTN8128A is indicated in the table below. The channel with highest conducted power will be identified as default channel per KDB 643646 D01 SAR Test for PTT Radios v01r01. SAR plots of the highest results per table (bolded) are presented in appendices E-G.

TABLE 12

Test Freq (MHz)	Power (W)
450.0	5.66
465.5	5.62
481.0	5.64
496.5	5.62
502.5	5.64
512.0	5.65

13.2 Assessments at the Body with Body worn PMLN4651A:

Assessment of offered antennas with the default battery and body worn accessory PMLN4651A and additional offered batteries per KDB 643646 D01 SAR Test for PTT Radios v01r01 – Body SAR Test Considerations for Body worn Accessories. Refer to the table above for highest output power channel.

TABLE 13

Antenna	Battery	Carry Accessory	Cable Accessory	Test Freq (MHz)	Init Pwr (W)	SAR Drift (dB)	Meas. 1g-SAR (mW/g)	Meas. 10g-SAR (mW/g)	Max Calc. 1g-SAR (mW/g)	Max Calc. 10g-SAR (mW/g)	Run#
PMAE4065A	NNTN8128A	PMLN4651A	HMN4104B	450.0	5.82	-0.52	8.00	5.76	4.51	3.25	ErC-Ab-120217-11
				465.5	5.76	-0.64	6.38	4.58	3.70	2.65	ErC-Ab-120217-12
				512.0	5.80	-0.36	4.02	2.90	2.18	1.58	ErC-Ab-120217-13
FAF5260A	NNTN8128A	PMLN4651A	HMN4104B	450.0	5.83	-0.46	8.36	6.01	4.65	3.34	ErC-Ab-120217-14
				465.5	5.79	-0.47	11.29	7.98	6.29	4.45	ErC-Ab-120218-02
				481.0	5.77	-0.69	9.81	7.00	5.75	4.10	ErC-Ab-120218-03
				496.5	5.79	-0.75	6.95	4.93	4.13	2.93	ErC-Ab-120218-04
				502.5	5.81	-0.62	6.47	4.58	3.73	2.64	ErC-Ab-120218-05
				512.0	5.83	-0.43	5.87	4.19	3.24	2.31	ErC-Ab-120218-06
Assessment of additional offered batteries											
PMAE4065A	NNTN8129A	PMLN4651A	HMN4104B	450.0	5.82	-0.77	5.53	3.97	3.30	2.37	ErC-Ab-120218-07
FAF5260A	NNTN8129A	PMLN4651A	HMN4104B	465.5	5.82	-0.76	8.62	6.16	5.13	3.67	ErC-Ab-120218-08
				450.0	5.86	-0.55	8.43	6.03	4.78	3.42	ErC-Ab-120218-09
				481.0	5.82	-0.57	6.23	4.46	3.55	2.54	ErC-Ab-120218-10
PMAE4065A	PMNN4424A	PMLN4651A	HMN4104B	450.0	5.86	-0.80	5.68	4.09	3.41	2.46	ErC-Ab-120218-11
FAF5260A	PMNN4424A	PMLN4651A	HMN4104B	465.5	5.82	-0.82	6.78	4.87	4.09	2.94	ErC-Ab-120218-12
				450.0	5.87	-0.24	8.20	5.87	4.33	3.10	CM-Ab-120218-13
				481.0	5.82	-0.91	6.81	4.88	4.20	3.01	CM-Ab-120218-14

13.3 Assessments at the Body with Body worn PMLN7008A:

Assessment of offered antenna with the default battery and body worn accessory PMLN7008A and additional offered batteries per KDB 643646 D01 SAR Test for PTT Radios v01r01 – Body SAR Test Considerations for Body worn Accessories. Refer to table 12 for highest output power channel.

TABLE 14

Antenna	Battery	Carry Accessory	Cable Accessory	Test Freq (MHz)	Init Pwr (W)	SAR Drift (dB)	Meas. 1g-SAR (mW/g)	Meas. 10g-SAR (mW/g)	Max Calc. 1g-SAR (mW/g)	Max Calc. 10g-SAR (mW/g)	Run#
PMAE4065A	NNTN8128A	PMLN7008A	HMN4104B	450.0	5.88	-0.630	7.18	5.09	4.15	2.94	CM-Ab-120218-15
				465.5	5.85	-0.610	6.60	4.68	3.80	2.69	CM-Ab-120218-16
				512.0	5.85	-0.160	3.35	2.36	1.74	1.22	CM-Ab-120218-17
FAF5260A	NNTN8128A	PMLN7008A	HMN4104B	450.0	5.88	-0.150	8.95	6.35	4.63	3.29	CM-Ab-120218-18
				465.5	5.87	-0.480	11.08	7.84	6.19	4.38	CM-Ab-120218-19
				481.0	5.86	-0.730	10.17	7.17	6.02	4.24	CM-Ab-120218-20
				496.5	5.83	-0.690	7.84	5.56	4.60	3.26	CM-Ab-120218-21
				502.5	5.85	-0.680	6.90	4.92	4.03	2.88	CM-Ab-120218-22
				512.0	5.83	-0.50	5.71	4.05	3.20	2.27	ErC-Ab-120219-02
Assessment of additional offered batteries											
PMAE4065A	NNTN8129A	PMLN7008A	HMN4104B	450.0	5.88	-0.80	5.15	3.68	3.10	2.21	ErC-Ab-120219-03
FAF5260A	NNTN8129A	PMLN7008A	HMN4104B	465.5	5.83	-0.74	8.35	5.99	4.95	3.55	ErC-Ab-120219-04
				450.0	5.88	-0.47	8.24	5.90	4.59	3.29	ErC-Ab-120219-05
				481.0	5.84	-0.89	7.09	5.12	4.35	3.14	ErC-Ab-120219-06
PMAE4065A	PMNN4424A	PMLN7008A	HMN4104B	450.0	5.87	-0.84	5.68	4.09	3.45	2.48	ErC-Ab-120219-07
FAF5260A	PMNN4424A	PMLN7008A	HMN4104B	465.5	5.85	-0.81	6.81	4.87	4.10	2.93	ErC-Ab-120219-08
				450.0	5.85	-0.40	8.37	6.01	4.59	3.29	ErC-Ab-120219-09
				481.0	5.84	-0.65	6.74	4.82	3.91	2.80	ErC-Ab-120219-10

13.4 Assessments at the Body with Body worn PMLN6085A:

Assessment of offered antenna with the default battery and body worn accessory PMLN6085A and additional offered batteries per KDB 643646 D01 SAR Test for PTT Radios v01r01 – Body SAR Test Considerations for Body worn Accessories. Refer to table 12 for highest output power channel.

TABLE 15

Antenna	Battery	Carry Accessory	Cable Accessory	Test Freq (MHz)	Init Pwr (W)	SAR Drift (dB)	Meas. 1g-SAR (mW/g)	Meas. 10g-SAR (mW/g)	Max Calc. 1g-SAR (mW/g)	Max Calc. 10g-SAR (mW/g)	Run#
PMAE4065A	NNTN8128A	PMLN6085A	HMN4104B	450.0	5.88	-0.47	1.69	1.29	0.94	0.72	CM-Ab-120308-05
FAF5260A	NNTN8128A	PMLN6085A	HMN4104B	450.0	5.88	-0.14	2.90	2.22	1.50	1.15	CM-Ab-120308-06
Assessment of additional offered batteries											
FAF5260A	NNTN8129A	PMLN6085A	HMN4104B	450.0	5.87	-0.67	1.90	1.45	1.11	0.85	CM-Ab-120308-07
FAF5260A	PMNN4424A	PMLN6085A	HMN4104B	450.0	5.87	-0.77	2.00	1.53	1.19	0.91	CM-Ab-120308-08

13.5 Assessments at the Body with Body worn PMLN6085A/NTN5243A:

Assessment of offered antenna with the default battery and body worn accessory PMLN6085A/NTN5243A and additional offered batteries per KDB 643646 D01 SAR Test for PTT Radios v01r01 – Body SAR Test Considerations for Body worn Accessories. Refer to table 12 for highest output power channel.

TABLE 16

Antenna	Battery	Carry Accessory	Cable Accessory	Test Freq (MHz)	Init Pwr (W)	SAR Drift (dB)	Meas. 1g-SAR (mW/g)	Meas. 10g-SAR (mW/g)	Max Calc. 1g-SAR (mW/g)	Max Calc. 10g-SAR (mW/g)	Run#
PMAE4065A	NNTN8128A	PMLN6085A /NTN5243A	HMN4104B	450.0	5.88	-0.55	4.33	3.21	2.46	1.82	CM-Ab-120308-09
FAF5260A	NNTN8128A	PMLN6085A /NTN5243A	HMN4104B	450.0	5.88	-0.26	5.68	4.26	3.02	2.26	CM-Ab-120308-10
Assessment of additional offered batteries											
FAF5260A	NNTN8129A	PMLN6085A /NTN5243A	HMN4104B	450.0	5.88	-0.75	4.17	3.10	2.48	1.84	CM-Ab-120308-11
FAF5260A	PMNN4424A	PMLN6085A /NTN5243A	HMN4104B	450.0	5.87	-0.73	3.92	2.93	2.32	1.73	CM-Ab-120308-12

13.6 Assessments at the Body with other offered audio accessories:

Tests of other offered audio accessories per KDB 643646 D01 SAR Test for PTT Radios v01r01 – Body SAR Test Considerations for audio accessories without Integral antenna.

TABLE 17

Antenna	Battery	Carry Accessory	Cable Accessory	Test Freq (MHz)	Init Pwr (W)	SAR Drift (dB)	Meas. 1g-SAR (mW/g)	Meas. 10g-SAR (mW/g)	Max Calc. 1g-SAR (mW/g)	Max Calc. 10g-SAR (mW/g)	Run#
FAF5260A	NNTN8128A	PMLN4651A	HMN4104B/ RMN5116A	450.0	5.88	-0.33	9.09	6.44	4.90	3.47	CM-Ab-120219-19
				465.5	5.87	-0.62	9.09	6.45	5.24	3.72	CM-Ab-120219-20
				481.0	5.84	-0.73	9.80	6.96	5.80	4.12	ErC-Ab-120220-02
				496.5	5.83	-0.95	7.81	5.52	4.86	3.43	ErC-Ab-120220-03
				502.5	5.83	-0.78	7.04	5.00	4.21	2.99	ErC-Ab-120220-04
				512.0	5.84	-0.60	6.06	4.34	3.48	2.49	ErC-Ab-120220-05

TABLE 18

Antenna	Battery	Carry Accessory	Cable Accessory	Test Freq (MHz)	Init Pwr (W)	SAR Drift (dB)	Meas. 1g-SAR (mW/g)	Meas. 10g-SAR (mW/g)	Max Calc. 1g-SAR (mW/g)	Max Calc. 10g-SAR (mW/g)	Run#
FAF5260A	NNTN8128A	PMLN4651A	RLN5882A	450.0	5.84	-0.21	10.11	7.19	5.31	3.77	ErC-Ab-120220-06
				465.5	5.86	-0.45	9.89	7.06	5.48	3.92	ErC-Ab-120220-07
				481.0	5.86	-0.61	9.39	6.65	5.40	3.83	ErC-Ab-120220-08
				496.5	5.85	-0.99	7.14	5.05	4.48	3.17	ErC-Ab-120220-09
				502.5	5.86	-0.76	6.73	4.77	4.01	2.84	ErC-Ab-120220-10
				512.0	5.88	-0.58	5.77	4.09	3.30	2.34	ErC-Ab-120220-11

TABLE 19

Antenna	Battery	Carry Accessory	Cable Accessory	Test Freq (MHz)	Init Pwr (W)	SAR Drift (dB)	Meas. 1g-SAR (mW/g)	Meas. 10g-SAR (mW/g)	Max Calc. 1g-SAR (mW/g)	Max Calc. 10g-SAR (mW/g)	Run#
FAF5260A	NNTN8128A	PMLN4651A	PMLN5111A	450.0	5.88	-0.03	10.34	7.33	5.21	3.69	ErC-Ab-120220-12
				465.5	5.88	-0.49	11.54	8.21	6.46	4.60	ErC-Ab-120220-13
				481.0	5.88	-0.60	10.30	7.29	5.91	4.19	ErC-Ab-120220-14
				496.5	5.87	-0.67	8.71	6.18	5.08	3.61	CM-Ab-120220-15
				502.5	5.88	-0.61	7.19	5.12	4.14	2.95	CM-Ab-120220-16
				512.0	5.88	-0.40	5.92	4.22	3.25	2.31	CM-Ab-120220-17

TABLE 20

Antenna	Battery	Carry Accessory	Cable Accessory	Test Freq (MHz)	Init Pwr (W)	SAR Drift (dB)	Meas. 1g-SAR (mW/g)	Meas. 10g-SAR (mW/g)	Max Calc. 1g-SAR (mW/g)	Max Calc. 10g-SAR (mW/g)	Run#
FAF5260A	NNTN8128A	PMLN4651A	PMMN4062A	450.0	5.87	-0.14	9.88	7.03	5.10	3.63	CM-Ab-120220-18
				465.5	5.84	-0.54	11.04	7.88	6.25	4.46	CM-Ab-120220-19
				481.0	5.84	-0.62	9.58	6.82	5.53	3.93	CM-Ab-120220-20
				496.5	5.86	-0.73	7.66	5.43	4.53	3.21	CM-Ab-120220-21
				502.5	5.88	-0.66	7.01	4.97	4.08	2.89	CM-Ab-120220-22
				512.0	5.88	-0.46	6.31	4.49	3.51	2.50	CM-Ab-120220-23

TABLE 21

Antenna	Battery	Carry Accessory	Cable Accessory	Test Freq (MHz)	Init Pwr (W)	SAR Drift (dB)	Meas. 1g-SAR (mW/g)	Meas. 10g-SAR (mW/g)	Max Calc. 1g-SAR (mW/g)	Max Calc. 10g-SAR (mW/g)	Run#
FAF5260A	NNTN8128A	PMLN4651A	PMMN4065A	450.0	5.87	-0.064	9.40	6.71	4.77	3.40	CM-Ab-120220-24
				465.5	5.85	-0.610	11.04	7.82	6.35	4.50	CM-Ab-120220-25
				481.0	5.86	-0.64	9.68	6.91	5.61	4.00	ErC-Ab-120221-02
				496.5	5.85	-0.80	7.56	5.38	4.54	3.23	ErC-Ab-120221-03
				502.5	5.88	-0.79	6.76	4.81	4.05	2.88	ErC-Ab-120221-04
				512.0	5.88	-0.56	6.03	4.33	3.43	2.46	ErC-Ab-120221-05

TABLE 22

Antenna	Battery	Carry Accessory	Cable Accessory	Test Freq (MHz)	Init Pwr (W)	SAR Drift (dB)	Meas. 1g-SAR (mW/g)	Meas. 10g-SAR (mW/g)	Max Calc. 1g-SAR (mW/g)	Max Calc. 10g-SAR (mW/g)	Run#
FAF5260A	NNTN8128A	PMLN4651A	PMMN4024A	450.0	5.88	0.06	8.72	6.18	4.36	3.09	ErC-Ab-120221-06
				465.5	5.88	-0.50	11.10	7.91	6.23	4.44	ErC-Ab-120221-07
				481.0	5.88	-0.61	9.49	6.80	5.46	3.91	ErC-Ab-120221-08
				496.5	5.86	-0.74	7.48	5.33	4.43	3.16	ErC-Ab-120221-09
				502.5	5.87	-0.79	6.80	4.86	4.08	2.91	ErC-Ab-120221-10
				512.0	5.88	-0.45	5.97	4.28	3.31	2.37	ErC-Ab-120221-11

TABLE 23

Antenna	Battery	Carry Accessory	Cable Accessory	Test Freq (MHz)	Init Pwr (W)	SAR Drift (dB)	Meas. 1g-SAR (mW/g)	Meas. 10g-SAR (mW/g)	Max Calc. 1g-SAR (mW/g)	Max Calc. 10g-SAR (mW/g)	Run#
FAF5260A	NNTN8128A	PMLN4651A	PMLN5101A	450.0	5.88	0.05	9.18	6.51	4.59	3.26	ErC-Ab-120221-12
				465.5	5.88	-0.48	10.90	7.71	6.09	4.31	ErC-Ab-120221-13
				481.0	5.87	-0.60	10.37	7.36	5.95	4.23	ErC-Ab-120221-14
				496.5	5.85	-0.63	7.94	5.65	4.59	3.27	ErC-Ab-120221-15
				502.5	5.85	-0.67	7.50	5.34	4.38	3.12	CM-Ab-120221-16
				512.0	5.86	-0.54	6.27	4.52	3.55	2.56	CM-Ab-120221-17

TABLE 24

Antenna	Battery	Carry Accessory	Cable Accessory	Test Freq (MHz)	Init Pwr (W)	SAR Drift (dB)	Meas. 1g-SAR (mW/g)	Meas. 10g-SAR (mW/g)	Max Calc. 1g-SAR (mW/g)	Max Calc. 10g-SAR (mW/g)	Run#
FAF5260A	NNTN8128A	PMLN4651A	PMLN5275C	450.0	5.88	-0.18	10.76	7.70	5.61	4.01	CM-Ab-120221-18
				465.5	5.87	-0.43	10.59	7.55	5.85	4.17	CM-Ab-120221-19
				481.0	5.88	-0.64	9.58	6.82	5.55	3.95	CM-Ab-120221-20
				496.5	5.88	-0.68	7.67	5.47	4.49	3.20	CM-Ab-120221-21
				502.5	5.85	-0.35	5.43	3.96	2.94	2.15	ErC-Ab-120222-02
				512.0	5.87	-0.47	5.97	4.35	3.33	2.42	ErC-Ab-120222-03

TABLE 25

Antenna	Battery	Carry Accessory	Cable Accessory	Test Freq (MHz)	Init Pwr (W)	SAR Drift (dB)	Meas. 1g-SAR (mW/g)	Meas. 10g-SAR (mW/g)	Max Calc. 1g-SAR (mW/g)	Max Calc. 10g-SAR (mW/g)	Run#
FAF5260A	NNTN8128A	PMLN4651A	RMN5058A	450.0	5.88	0.07	9.50	6.76	4.75	3.38	ErC-Ab-120222-04
				465.5	5.87	-0.53	10.67	4.61	6.03	2.60	ErC-Ab-120222-05
				481.0	5.83	-0.67	9.75	6.96	5.69	4.06	ErC-Ab-120222-06
				496.5	5.87	-0.86	7.86	5.60	4.79	3.41	ErC-Ab-120222-07
				502.5	5.88	-0.75	7.23	5.17	4.30	3.07	ErC-Ab-120222-08
				512.0	5.88	-0.60	6.38	4.59	3.66	2.64	ErC-Ab-120222-09

TABLE 26

Antenna	Battery	Carry Accessory	Cable Accessory	Test Freq (MHz)	Init Pwr (W)	SAR Drift (dB)	Meas. 1g-SAR (mW/g)	Meas. 10g-SAR (mW/g)	Max Calc. 1g-SAR (mW/g)	Max Calc. 10g-SAR (mW/g)	Run#
FAF5260A	NNTN8128A	PMLN4651A	PMMN4040A	450.0	5.88	-0.18	9.75	6.95	5.08	3.62	ErC-Ab-120222-10
				465.5	5.88	-0.50	10.87	7.73	6.10	4.34	ErC-Ab-120222-11
				481.0	5.88	-0.67	9.85	7.06	5.75	4.12	ErC-Ab-120222-12
				496.5	5.87	-0.66	7.80	5.56	4.54	3.24	ErC-Ab-120222-13
				502.5	5.86	-0.61	6.93	4.96	3.99	2.85	ErC-Ab-120222-14
				512.0	5.87	-0.49	6.28	4.54	3.52	2.54	ErC-Ab-120222-15

TABLE 27

Antenna	Battery	Carry Accessory	Cable Accessory	Test Freq (MHz)	Init Pwr (W)	SAR Drift (dB)	Meas. 1g-SAR (mW/g)	Meas. 10g-SAR (mW/g)	Max Calc. 1g-SAR (mW/g)	Max Calc. 10g-SAR (mW/g)	Run#
FAF5260A	NNTN8128A	PMLN4651A	PMMN4046A	450.0	5.88	0.047	8.94	6.37	4.47	3.19	CM-Ab-120222-16
				465.5	5.88	-0.51	10.37	7.37	5.83	4.14	CM-Ab-120222-17
				481.0	5.84	-0.58	9.82	6.98	5.61	3.99	CM-Ab-120222-18
				496.5	5.82	-0.64	10.14	7.17	5.88	4.15	CM-Ab-120222-19
				502.5	5.86	-0.69	7.02	4.98	4.11	2.92	CM-Ab-120222-20
				512.0	5.87	-0.32	5.00	3.65	2.69	1.96	CM-Ab-120222-21

TABLE 28

Antenna	Battery	Carry Accessory	Cable Accessory	Test Freq (MHz)	Init Pwr (W)	SAR Drift (dB)	Meas. 1g-SAR (mW/g)	Meas. 10g-SAR (mW/g)	Max Calc. 1g-SAR (mW/g)	Max Calc. 10g-SAR (mW/g)	Run#
FAF5260A	NNTN8128A	PMLN4651A	PMMN4050A	450.0	5.88	0.051	9.81	6.96	4.91	3.48	CM-Ab-120222-22
				465.5	5.88	-0.50	10.87	7.77	6.10	4.36	CM-Ab-120222-23
				481.0	5.83	-0.66	9.56	6.83	5.56	3.98	CM-Ab-120222-24
				496.5	5.87	-0.70	7.77	5.52	4.56	3.24	CM-Ab-120222-25
				502.5	5.85	-0.76	7.25	5.16	4.32	3.07	ErC-Ab-120223-02
				512.0	5.86	-0.48	6.29	4.51	3.51	2.52	ErC-Ab-120223-03

TABLE 29

Antenna	Battery	Carry Accessory	Cable Accessory	Test Freq (MHz)	Init Pwr (W)	SAR Drift (dB)	Meas. 1g-SAR (mW/g)	Meas. 10g-SAR (mW/g)	Max Calc. 1g-SAR (mW/g)	Max Calc. 10g-SAR (mW/g)	Run#
FAF5260A	NNTN8128A	PMLN4651A	PMLN5102A	450.0	5.88	-0.18	9.10	6.49	4.74	3.38	ErC-Ab-120223-04
				465.5	5.87	-0.49	9.96	7.09	5.57	3.97	ErC-Ab-120223-05
				481.0	5.88	-0.64	9.16	6.54	5.31	3.79	ErC-Ab-120223-06
				496.5	5.87	-0.70	7.77	5.55	4.56	3.26	ErC-Ab-120223-07
				502.5	5.87	-0.66	6.99	4.97	4.07	2.89	ErC-Ab-120223-08
				512.0	5.88	-0.51	6.14	4.42	3.45	2.49	ErC-Ab-120223-09

TABLE 30

Antenna	Battery	Carry Accessory	Cable Accessory	Test Freq (MHz)	Init Pwr (W)	SAR Drift (dB)	Meas. 1g-SAR (mW/g)	Meas. 10g-SAR (mW/g)	Max Calc. 1g-SAR (mW/g)	Max Calc. 10g-SAR (mW/g)	Run#
FAF5260A	NNTN8128A	PMLN4651A	PMLN5096B	450.0	5.88	-0.26	9.55	6.81	5.07	3.62	ErC-Ab-120223-10
				465.5	5.87	-0.71	8.43	6.10	4.96	3.59	ErC-Ab-120223-11
				481.0	5.88	-0.67	9.25	6.58	5.40	3.84	ErC-Ab-120223-12
				496.5	5.86	-0.79	7.64	5.44	4.58	3.26	ErC-Ab-120223-13
				502.5	5.88	-0.69	7.15	5.11	4.19	2.99	ErC-Ab-120223-14
				512.0	5.88	-0.55	6.00	4.32	3.41	2.45	ErC-Ab-120223-15

TABLE 31

Antenna	Battery	Carry Accessory	Cable Accessory	Test Freq (MHz)	Init Pwr (W)	SAR Drift (dB)	Meas. 1g-SAR (mW/g)	Meas. 10g-SAR (mW/g)	Max Calc. 1g-SAR (mW/g)	Max Calc. 10g-SAR (mW/g)	Run#
FAF5260A	NNTN8128A	PMLN4651A	PMLN5097A	450.0	5.88	-0.22	8.76	6.27	4.61	3.30	CM-Ab-120223-16
				465.5	5.88	-0.57	9.87	7.08	5.63	4.04	CM-Ab-120223-17
				481.0	5.88	-0.72	9.50	6.78	5.61	4.00	CM-Ab-120223-18
				496.5	5.87	-0.59	7.64	5.41	4.38	3.10	CM-Ab-120223-19
				502.5	5.86	-0.63	5.66	4.03	3.27	2.33	CM-Ab-120223-20
				512.0	5.86	-0.13	4.22	2.99	2.17	1.54	ErC-Ab-120224-02

TABLE 32

Antenna	Battery	Carry Accessory	Cable Accessory	Test Freq (MHz)	Init Pwr (W)	SAR Drift (dB)	Meas. 1g-SAR (mW/g)	Meas. 10g-SAR (mW/g)	Max Calc. 1g-SAR (mW/g)	Max Calc. 10g-SAR (mW/g)	Run#
FAF5260A	NNTN8128A	PMLN4651A	PMLN5106A	450.0	5.88	-0.37	10.46	7.56	5.70	4.12	ErC-Ab-120224-03
				465.5	5.88	-0.51	10.91	7.84	6.13	4.41	ErC-Ab-120224-04
				481.0	5.88	-0.70	9.73	6.96	5.72	4.09	ErC-Ab-120224-05
				496.5	5.85	-0.80	7.11	5.07	4.27	3.05	ErC-Ab-120224-06
				502.5	5.87	-0.60	6.66	4.75	3.82	2.73	ErC-Ab-120224-07
				512.0	5.88	-0.52	5.81	4.16	3.27	2.34	ErC-Ab-120224-08

TABLE 33

Antenna	Battery	Carry Accessory	Cable Accessory	Test Freq (MHz)	Init Pwr (W)	SAR Drift (dB)	Meas. 1g-SAR (mW/g)	Meas. 10g-SAR (mW/g)	Max Calc. 1g-SAR (mW/g)	Max Calc. 10g-SAR (mW/g)	Run#
FAF5260A	NNTN8128A	PMLN4651A	PMLN5653A	450.0	5.88	-0.11	9.93	7.10	5.09	3.64	ErC-Ab-120224-09
				465.5	5.87	-0.51	10.41	7.42	5.85	4.17	ErC-Ab-120224-10
				481.0	5.86	-0.70	9.84	7.00	5.78	4.11	ErC-Ab-120224-11
				496.5	5.87	-0.81	7.77	5.53	4.68	3.33	ErC-Ab-120224-12
				502.5	5.87	-0.78	7.01	4.99	4.19	2.99	ErC-Ab-120224-13
				512.0	5.88	-0.55	6.59	4.71	3.74	2.67	ErC-Ab-120224-14

13.7 Assessments of wireless BT configurations:

Not Applicable for this model

13.8 Assessment outside FCC Part 90 at the body (512-520 MHz):

Assessment at the Body for frequencies outside FCC part 90, using highest SAR test configuration from Part 90 assessments above with the offered antennas. SAR plots of the highest results per table (bolded) are presented in appendices E-G.

TABLE 34

Antenna	Battery	Carry Accessory	Cable Accessory	Test Freq (MHz)	Init Pwr (W)	SAR Drift (dB)	Meas. 1g-SAR (mW/g)	Meas. 10g-SAR (mW/g)	Max Calc. 1g-SAR (mW/g)	Max Calc. 10g-SAR (mW/g)	Run#
FAF5260A	NNTN8128A	PMLN4651A	PMLN5111A	512.5	5.88	-0.37	5.43	3.85	2.96	2.10	CM-Ab-120316-04
				516.0	5.88	-0.28	5.22	3.72	2.78	1.98	CM-Ab-120316-05
				520.0	5.87	-0.29	4.97	3.54	2.66	1.89	CM-Ab-120316-06
PMAE4065A	NNTN8128A	PMLN4651A	PMLN5111A	512.5	5.87	-0.23	4.10	2.92	2.16	1.54	CM-Ab-120316-07
				516.0	5.88	-0.23	4.15	2.95	2.19	1.56	CM-Ab-120316-08
				520.0	5.88	-0.21	3.98	2.84	2.09	1.49	CM-Ab-120316-09

13.9 Assessments at the Face (450-512 MHz band):

The highest capacity battery NNTN8129A was selected as the default battery. The conducted power measurement for all test channels within Part 90 frequency range using battery NNTN8129A is listed in the table below. The channel with highest conducted power was used as the default channel per KDB 643646 D01 SAR Test for PTT Radios v01r01. SAR plots of the highest results per table (bolded) are presented in appendices E-G.

TABLE 35

Test Freq (MHz)	Power (W)
450.0	5.63
465.5	5.59
481.0	5.61
496.5	5.60
502.5	5.61
512.0	5.62

Assessment of the offered antenna with the default and other offered batteries per KDB 643646 D01 SAR Test for PTT Radios v01r01 – Head SAR Test Considerations. Refer to the table above for highest output power channel.

TABLE 36

Antenna	Battery	Carry Accessory	Cable Accessory	Test Freq (MHz)	Init Pwr (W)	SAR Drift (dB)	Meas. 1g-SAR (mW/g)	Meas. 10g-SAR (mW/g)	Max Calc. 1g-SAR (mW/g)	Max Calc. 10g-SAR (mW/g)	Run#
PMAE4065A	NNTN8129A	None	None	450.0	5.87	-0.64	5.68	4.29	3.29	2.49	ErC-Face-120225-10
FAF5260A	NNTN8129A	None	None	450.0	5.88	-0.10	7.75	5.82	3.97	2.98	ErC-Face-120225-11
FAF5260A	NNTN8129A	None	None	512.0	5.85	-0.40	4.58	3.45	2.51	1.89	ErC-Face-120225-12
Assessment of other offered batteries											
FAF5260A	NNTN8128A	None	None	450.0	5.88	-0.13	7.90	5.93	4.07	3.06	ErC-Face-120225-13
FAF5260A	PMNN4424A	None	None	450.0	5.88	-0.09	7.70	5.80	3.93	2.96	ErC-Face-120225-14

13.10 Assessment outside FCC Part 90 at the face (512-520 MHz):

Assessment at the Face for frequencies outside FCC part 90, using highest SAR test configuration from Part 90 assessments above. SAR plots of the highest results per table (bolded) are presented in appendices E-G.

TABLE 37

Antenna	Battery	Carry Accessory	Cable Accessory	Test Freq (MHz)	Init Pwr (W)	SAR Drift (dB)	Meas. 1g-SAR (mW/g)	Meas. 10g-SAR (mW/g)	Max Calc. 1g-SAR (mW/g)	Max Calc. 10g-SAR (mW/g)	Run#
FAF5260A	NNTN8128A	None	None	512.5	5.88	-0.45	4.65	3.49	2.58	1.94	CM-Face-120225-15
				516.0	5.87	-0.36	4.35	3.27	2.36	1.78	CM-Face-120225-16
				520.0	5.86	-0.33	3.99	2.99	2.15	1.61	CM-Face-120225-17
PMAE4065A	NNTN8128A	None	None	512.5	5.87	-0.20	2.53	1.89	1.32	0.99	CM-Face-120305-05
				516.0	5.88	-0.14	2.45	1.84	1.27	0.95	CM-Face-120305-06
				520.0	5.88	-0.14	2.37	1.78	1.22	0.92	CM-Face-120305-07

13.11 Assessment of BT band:

Not applicable for this model

13.12 Shortened Scan Assessment:

A “shortened” scan was performed to validate the SAR drift of the full DASYS™ coarse and zoom scans. Note that the shortened scan represents the zoom scan performance result; this is obtained by first running a coarse scan to find the peak area and then, using a newly charged battery, a zoom scan only was performed. The results of the shortened cube scan presented in APPENDIX E demonstrate that the scaling methodology used to determine the calculated SAR results presented herein are valid. The SAR result from the table below is provided in APPENDIX E.

TABLE 38

Antenna	Battery	Carry Accessory	Cable Accessory	Test Freq (MHz)	Init Pwr (W)	SAR Drift (dB)	Meas. 1g-SAR (mW/g)	Meas. 10g-SAR (mW/g)	Max Calc. 1g-SAR (mW/g)	Max Calc. 10g-SAR (mW/g)	Run#
FAF5260A	NNTN8128A	PMLN4651A	PMLN5111A	465.5	5.88	0.28	11.81	8.38	5.91	4.19	CM-Ab-120316-03

14.0 Simultaneous Transmission Exclusion:

Not applicable for this model

15.0 Conclusion:

The highest Operational Maximum Calculated 1-gram and 10-gram average SAR values found for this filing: Model H51SDH9PW7AN (MUE3771)

TABLE 39

Designator	Frequency (MHz)	Max Calc at Body (mW/g)		Max Calc at Face (mW/g)	
		1g-SAR	10g-SAR	1g-SAR	10g-SAR
Overall	450-520	6.46	4.60	4.07	3.06
FCC	450-512	6.46	4.60	4.07	3.06

The test results clearly demonstrate compliance with FCC Occupational/Controlled RF Exposure limits of 8 W/kg averaged over 1 gram per the requirements of 47 CFR 2.1093(d). The 10 grams result is not applicable to FCC filing.

The test results clearly demonstrate compliance with the standards listed in section 3.0 for occupational/controlled RF Exposure limits of 10 W/kg averaged over 10 grams of contiguous tissue.

APPENDIX A

Measurement Uncertainty

The Measurement Uncertainty tables indicated in this APPENDIX are applicable to the DUT test frequencies ranging from 100MHz to 800MHz and for Dipole test frequencies ranging from 300MHz to 800MHz. Therefore, the highest tolerance for the probe calibration uncertainty is indicated.

Uncertainty Budget for Device Under Test, for 100 MHz to 800 MHz

<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	$e = f(d,k)$	<i>f</i>	<i>g</i>	$h = \frac{c \times f}{e}$	$i = \frac{c \times g}{e}$
Uncertainty Component	IEEE 1528 section	Tol. (\pm %)	Prob Dist	Div.	c_i (1 g)	c_i (10 g)	1 g u_i (\pm %)	10 g u_i (\pm %)
Measurement System								
Probe Calibration	E.2.1	10.0	N	1.00	1	1	10.0	10.0
Axial Isotropy	E.2.2	4.7	R	1.73	0.707	0.707	1.9	1.9
Hemispherical Isotropy	E.2.2	9.6	R	1.73	0.707	0.707	3.9	3.9
Boundary Effect	E.2.3	1.0	R	1.73	1	1	0.6	0.6
Linearity	E.2.4	4.7	R	1.73	1	1	2.7	2.7
System Detection Limits	E.2.5	1.0	R	1.73	1	1	0.6	0.6
Readout Electronics	E.2.6	0.3	N	1.00	1	1	0.3	0.3
Response Time	E.2.7	1.1	R	1.73	1	1	0.6	0.6
Integration Time	E.2.8	1.1	R	1.73	1	1	0.6	0.6
RF Ambient Conditions - Noise	E.6.1	3.0	R	1.73	1	1	1.7	1.7
RF Ambient Conditions - Reflections	E.6.1	0.0	R	1.73	1	1	0.0	0.0
Probe Positioner Mech. Tolerance	E.6.2	0.4	R	1.73	1	1	0.2	0.2
Probe Positioning w.r.t Phantom	E.6.3	1.4	R	1.73	1	1	0.8	0.8
Max. SAR Evaluation (ext., int., avg.)	E.5	3.4	R	1.73	1	1	2.0	2.0
Test sample Related								
Test Sample Positioning	E.4.2	3.2	N	1.00	1	1	3.2	3.2
Device Holder Uncertainty	E.4.1	4.0	N	1.00	1	1	4.0	4.0
SAR drift	6.6.2	5.0	R	1.73	1	1	2.9	2.9
Phantom and Tissue Parameters								
Phantom Uncertainty	E.3.1	4.0	R	1.73	1	1	2.3	2.3
Liquid Conductivity (target)	E.3.2	5.0	R	1.73	0.64	0.43	1.8	1.2
Liquid Conductivity (measurement)	E.3.3	3.3	N	1.00	0.64	0.43	2.1	1.4
Liquid Permittivity (target)	E.3.2	5.0	R	1.73	0.6	0.49	1.7	1.4
Liquid Permittivity (measurement)	E.3.3	1.9	N	1.00	0.6	0.49	1.1	0.9
Combined Standard Uncertainty			RSS				14	13
Expanded Uncertainty (95% CONFIDENCE LEVEL)			$k=2$				27	27

FCD-0558 Uncertainty Budget Rev.8

Uncertainty Budget for System Validation (dipole & flat phantom) for 300 MHz to 800 MHz

<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	$e = f(d,k)$	<i>f</i>	<i>g</i>	$h = c \times f / e$	$i = c \times g / e$	<i>k</i>
Uncertainty Component	IEEE 1528 section	Tol. ($\pm \%$)	Prob. Dist.	Div.	c_i (1 g)	c_i (10 g)	1 g u_i ($\pm \%$)	10 g u_i ($\pm \%$)	v_i
Measurement System									
Probe Calibration	E.2.1	9.0	N	1.00	1	1	9.0	9.0	∞
Axial Isotropy	E.2.2	4.7	R	1.73	1	1	2.7	2.7	∞
Spherical Isotropy	E.2.2	9.6	R	1.73	0	0	0.0	0.0	∞
Boundary Effect	E.2.3	1.0	R	1.73	1	1	0.6	0.6	∞
Linearity	E.2.4	4.7	R	1.73	1	1	2.7	2.7	∞
System Detection Limits	E.2.5	1.0	R	1.73	1	1	0.6	0.6	∞
Readout Electronics	E.2.6	0.3	N	1.00	1	1	0.3	0.3	∞
Response Time	E.2.7	1.1	R	1.73	1	1	0.6	0.6	∞
Integration Time	E.2.8	0.0	R	1.73	1	1	0.0	0.0	∞
RF Ambient Conditions - Noise	E.6.1	3.0	R	1.73	1	1	1.7	1.7	∞
RF Ambient Conditions - Reflections	E.6.1	0.0	R	1.73	1	1	0.0	0.0	∞
Probe Positioner Mechanical Tolerance	E.6.2	0.4	R	1.73	1	1	0.2	0.2	∞
Probe Positioning w.r.t. Phantom	E.6.3	1.4	R	1.73	1	1	0.8	0.8	∞
Max. SAR Evaluation (ext., int., avg.)	E.5	3.4	R	1.73	1	1	2.0	2.0	∞
Dipole									
Dipole Axis to Liquid Distance	8. E.4.2	2.0	R	1.73	1	1	1.2	1.2	∞
Input Power and SAR Drift Measurement	8. 6.6.2	5.0	R	1.73	1	1	2.9	2.9	∞
Phantom and Tissue Parameters									
Phantom Uncertainty	E.3.1	4.0	R	1.73	1	1	2.3	2.3	∞
Liquid Conductivity (target)	E.3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Conductivity (measurement)	E.3.3	3.3	R	1.73	0.64	0.43	1.2	0.8	∞
Liquid Permittivity (target)	E.3.2	5.0	R	1.73	0.6	0.49	1.7	1.4	∞
Liquid Permittivity (measurement)	E.3.3	1.9	R	1.73	0.6	0.49	0.6	0.5	∞
Combined Standard Uncertainty			RSS				11	11	99999
Expanded Uncertainty (95% CONFIDENCE LEVEL)			$k=2$				22	22	

FCD-0558 Uncertainty Budget Rev.8

Notes for uncertainty budget tables:

- Column headings *a-k* are given for reference.
- Tol. - tolerance in influence quantity.
- Prob. Dist. – Probability distribution
- N, R - normal, rectangular probability distributions
- Div. - divisor used to translate tolerance into normally distributed standard uncertainty
- c_i - sensitivity coefficient that should be applied to convert the variability of the uncertainty component into a variability of SAR.
- u_i – SAR uncertainty
- v_i - degrees of freedom for standard uncertainty and effective degrees of freedom for the expanded uncertainty

APPENDIX B
Probe Calibration Certificates

**Calibration Laboratory of
Schmid & Partner
Engineering AG**
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **Motorola EME**

Certificate No: **ES3-3163_Apr11**

CALIBRATION CERTIFICATE

Object **ES3DV3 - SN:3163**

Calibration procedure(s) **QA CAL-01.v7, QA CAL-12.v6, QA CAL-14.v3, QA CAL-23.v4, QA CAL-25.v3
Calibration procedure for dosimetric E-field probes**

Calibration date: **April 13, 2011**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	31-Mar-11 (No. 217-01372)	Apr-12
Power sensor E4412A	MY41495277	31-Mar-11 (No. 217-01372)	Apr-12
Power sensor E4412A	MY41498087	31-Mar-11 (No. 217-01372)	Apr-12
Reference 3 dB Attenuator	SN: S5054 (3c)	29-Mar-11 (No. 217-01369)	Apr-12
Reference 20 dB Attenuator	SN: S5086 (20b)	29-Mar-11 (No. 217-01367)	Apr-12
Reference 30 dB Attenuator	SN: S5129 (30b)	29-Mar-11 (No. 217-01370)	Apr-12
Reference Probe ES3DV2	SN: 3013	29-Dec-10 (No. ES3-3013_Dec10)	Dec-11
DAE4	SN: 654	23-Apr-10 (No. DAE4-654_Apr10)	Apr-11
Secondary Standards	ID	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (in house check Oct-09)	In house check: Oct-11
Network Analyzer HP 8753E	US37390585	18-Oct-01 (in house check Oct-10)	In house check: Oct-11

Calibrated by:	Name Katja Pokovic	Function Technical Manager	Signature
Approved by:	Name Niels Kuster	Function Quality Manager	Signature

Issued: April 13, 2011

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di tarature
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: SCS 108

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C	modulation dependent linearization parameters
Polarization φ	φ rotation around probe axis
Polarization θ	θ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\theta = 0$ is normal to probe axis

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}:** Assessed for E-field polarization $\theta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not affect the E²-field uncertainty inside TSL (see below ConvF).
- NORM(f)_{x,y,z} = NORM_{x,y,z} * frequency_response** (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP_{x,y,z}:** DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR:** PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}** are numerical linearization parameters in dB assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media.
- VR:** VR is the validity range of the calibration related to the average diode voltage or DAE voltage in mV.
- ConvF and Boundary Effect Parameters:** Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy):** in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset:** The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.

Probe ES3DV3

SN:3163

Manufactured: October 8, 2007
Calibrated: April 13, 2011

Calibrated for DASY/EASY Systems
(Note: non-compatible with DASY2 system!)

ES3DV3- SN:3163

April 13, 2011

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3163**Basic Calibration Parameters**

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu\text{V}/(\text{V}/\text{m})^2$) ^A	1.34	1.14	1.06	$\pm 10.1 \%$
DCP (mV) ^B	100.6	102.9	102.3	

Modulation Calibration Parameters

UID	Communication System Name	PAR		A dB	B dB	C dB	VR mV	Unc ^E (k=2)
10000	CW	0.00	X	0.00	0.00	1.00	112.6	$\pm 2.7 \%$
			Y	0.00	0.00	1.00	105.3	
			Z	0.00	0.00	1.00	98.4	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of NormX,Y,Z do not affect the E^2 -field uncertainty inside TSL (see Pages 5 and 6).

^B Numerical linearization parameter: uncertainty not required.

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3163

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^c	Relative Permittivity ^f	Conductivity (S/m) ^f	ConvF X	ConvF Y	ConvF Z	Alpha	Depth (mm)	Unct. (k=2)
300	45.3	0.87	6.88	6.88	6.88	0.25	1.08	± 13.4 %
450	43.5	0.87	6.53	6.53	6.53	0.17	1.84	± 13.4 %
750	41.9	0.89	6.39	6.39	6.39	0.99	1.10	± 12.0 %
900	41.5	0.97	6.04	6.04	6.04	0.99	1.08	± 12.0 %
1810	40.0	1.40	5.05	5.05	5.05	0.89	1.16	± 12.0 %
1950	40.0	1.40	4.88	4.88	4.88	0.87	1.17	± 12.0 %
2300	39.5	1.67	4.70	4.70	4.70	0.77	1.25	± 12.0 %
2450	39.2	1.80	4.44	4.44	4.44	0.77	1.25	± 12.0 %
2600	39.0	1.96	4.29	4.29	4.29	0.75	1.29	± 12.0 %
3500	37.9	2.91	4.06	4.06	4.06	0.99	1.26	± 13.1 %
3700	37.7	3.12	3.63	3.63	3.63	0.99	1.29	± 13.1 %

^c Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^f At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

DASY/EASY - Parameters of Probe: ES3DV3- SN:3163


Calibration Parameter Determined in Body Tissue Simulating Media

f (MHz) ^c	Relative Permittivity ^f	Conductivity (S/m) ^f	ConvF X	ConvF Y	ConvF Z	Alpha	Depth (mm)	Unct. (k=2)
300	58.2	0.92	6.83	6.83	6.83	0.22	1.69	± 13.4 %
450	56.7	0.94	7.01	7.01	7.01	0.09	1.00	± 13.4 %
750	55.5	0.96	6.13	6.13	6.13	0.99	1.14	± 12.0 %
900	55.0	1.05	5.99	5.99	5.99	0.99	1.14	± 12.0 %
1810	53.3	1.52	4.87	4.87	4.87	0.87	1.30	± 12.0 %
1950	53.3	1.52	4.81	4.81	4.81	0.77	1.37	± 12.0 %
2300	52.9	1.81	4.38	4.38	4.38	0.90	1.15	± 12.0 %
2450	52.7	1.95	4.20	4.20	4.20	0.99	1.05	± 12.0 %
2600	52.5	2.16	4.07	4.07	4.07	0.99	1.06	± 12.0 %
3500	51.3	3.31	3.47	3.47	3.47	0.99	1.37	± 13.1 %
3700	51.0	3.55	3.42	3.42	3.42	0.99	1.41	± 13.1 %

^c Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^f At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.


Frequency Response of E-Field (TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ ($k=2$)

Receiving Pattern (ϕ), $\vartheta = 0^\circ$

f=600 MHz,TEM





f=1800 MHz,R22




Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ (k=2)

Dynamic Range f(SAR_{head}) (TEM cell , f = 900 MHz)




Uncertainty of Linearity Assessment: ± 0.6% (k=2)

Conversion Factor Assessment



Deviation from Isotropy in Liquid Error (ϕ , θ), f = 900 MHz



DASY/EASY - Parameters of Probe: ES3DV3 - SN:3163**Other Probe Parameters**

Sensor Arrangement	Triangular
Connector Angle (°)	Not applicable
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	10 mm
Tip Diameter	4 mm
Probe Tip to Sensor X Calibration Point	2 mm
Probe Tip to Sensor Y Calibration Point	2 mm
Probe Tip to Sensor Z Calibration Point	2 mm
Recommended Measurement Distance from Surface	3 mm

Schmid & Partner Engineering AG

s p e a g

Zeughausstrasse 43, 8004 Zurich, Switzerland
 Phone +41 44 245 9700, Fax +41 44 245 9779
 info@speag.com, http://www.speag.com

Additional Conversion Factors

for Dosimetric E-Field Probe

Type:

ES3DV3

Serial Number:

3163

Place of Assessment:

Zurich

Date of Assessment:

April 15, 2011

Probe Calibration Date:

April 13, 2011

Schmid & Partner Engineering AG hereby certifies that conversion factor(s) of this probe have been evaluated on the date indicated above. The assessment was performed using the FDTD numerical code SEMCAD of Schmid & Partner Engineering AG. Since the evaluation is coupled with measured conversion factors, it has to be recalculated yearly, i.e., following the re-calibration schedule of the probe. The uncertainty of the numerical assessment is based on the extrapolation from measured value at 900 MHz or at 1810 MHz.

Assessed by:



Dosimetric E-Field Probe ES3DV3 SN:3163

Conversion factor (\pm standard deviation)

150 MHz	<i>ConvF</i>	$8.2 \pm 10\%$	$\epsilon_r = 52.3$ $\sigma = 0.76 \text{ mho/m}$ (head tissue)
250 MHz	<i>ConvF</i>	$7.7 \pm 10\%$	$\epsilon_r = 47.6$ $\sigma = 0.83 \text{ mho/m}$ (head tissue)
150 MHz	<i>ConvF</i>	$7.9 \pm 10\%$	$\epsilon_r = 61.9$ $\sigma = 0.80 \text{ mho/m}$ (body tissue)
250 MHz	<i>ConvF</i>	$7.5 \pm 10\%$	$\epsilon_r = 59.4$ $\sigma = 0.88 \text{ mho/m}$ (body tissue)

Important Note:

For numerically assessed probe conversion factors, parameters Alpha and Delta in the DASY software must have the following entries: Alpha = 0 and Delta = 1.

Please see also DASY Manual.

APPENDIX C
Dipole Calibration Certificates

**Calibration Laboratory of
Schmid & Partner
Engineering AG**
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **Motorola EME**

Certificate No: **D450V3-1077_Nov11**

CALIBRATION CERTIFICATE

Object: **D450V3 - SN: 1077**

Calibration procedure(s): **QA CAL-15.v6
Calibration procedure for dipole validation kits below 700 MHz**

Calibration date: **November 15, 2011**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	31-Mar-11 (No. 217-01372)	Apr-12
Power sensor E4412A	MY41498087	31-Mar-11 (No. 217-01372)	Apr-12
Reference 3 dB Attenuator	SN: S5054 (3c)	29-Mar-11 (No. 217-01369)	Apr-12
Reference 20 dB Attenuator	SN: S5086 (20b)	29-Mar-11 (No. 217-01367)	Apr-12
Type-N mismatch combination	SN: 5047.3 / 06327	29-Mar-11 (No. 217-01168)	Apr-12
Reference Probe ET3DV6	SN: 1507	29-Apr-11 (No. ET3-1507_Apr11)	May-12
DAE4	SN: 654	03-May-11 (No. DAE4-654_May11)	May-12

Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power sensor HP 8481A	MY41092317	18-Oct-02 (in house check Oct-11)	In house check: Oct-13
RF generator R&S SMT-06	100005	04-Aug-99 (in house check Oct-11)	In house check: Oct-13
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-11)	In house check: Oct-12

	Name	Function	Signature
Calibrated by:	Jeton Kastrati	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	

Issued: November 15, 2011

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

**Calibration Laboratory of
Schmid & Partner
Engineering AG**
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- Federal Communications Commission Office of Engineering & Technology (FCC OET), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields; Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", Supplement C (Edition 01-01) to Bulletin 65

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.6.2
Extrapolation	Advanced Extrapolation	
Phantom	ELI4 Flat Phantom	Shell thickness: 2 ± 0.2 mm
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	450 MHz \pm 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	43.5	0.87 mho/m
Measured Head TSL parameters	(22.0 \pm 0.2) °C	44.1 \pm 6 %	0.85 mho/m \pm 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	398 mW input power	1.82 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	4.67 mW / g \pm 18.1 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	398 mW input power	1.21 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	3.10 mW / g \pm 17.6 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	56.7	0.94 mho/m
Measured Body TSL parameters	(22.0 \pm 0.2) °C	55.0 \pm 6 %	0.92 mho/m \pm 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	398 mW input power	1.77 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	4.49 mW / g \pm 18.1 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	398 mW input power	1.18 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	2.99 mW / g \pm 17.6 % (k=2)

Appendix**Antenna Parameters with Head TSL**

Impedance, transformed to feed point	58.2 Ω - 5.0 j Ω
Return Loss	- 21.0 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	55.2 Ω - 7.3 j Ω
Return Loss	- 21.4 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.353 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	June 24, 2010

DASY5 Validation Report for Head TSL

Date: 15.11.2011

Test Laboratory: SPEAG

DUT: Dipole 450 MHz; Type: D450V3; Serial: D450V3 - SN: 1077

Communication System: CW; Frequency: 450 MHz

Medium parameters used: $f = 450$ MHz; $\sigma = 0.85$ mho/m; $\epsilon_r = 44.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ET3DV6 - SN1507; ConvF(6.59, 6.59, 6.59); Calibrated: 29.04.2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn654; Calibrated: 03.05.2011
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1003
- DASY52 52.6.2(482); SEMCAD X 14.4.5(3634)

Dipole Calibration for Head Tissue/d=15mm, Pin=398mW/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 49.455 V/m; Power Drift = -0.02 dB


Peak SAR (extrapolated) = 2.765 W/kg

SAR(1 g) = 1.82 mW/g; SAR(10 g) = 1.21 mW/g

Maximum value of SAR (measured) = 1.940 mW/g



Impedance Measurement Plot for Head TSL



DASY5 Validation Report for Body TSL

Date: 15.11.2011

Test Laboratory: SPEAG

DUT: Dipole 450 MHz; Type: D450V3; Serial: D450V3 - SN: 1077

Communication System: CW; Frequency: 450 MHz

Medium parameters used: $f = 450$ MHz; $\sigma = 0.92$ mho/m; $\epsilon_r = 55$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ET3DV6 - SN1507; ConvF(7.05, 7.05, 7.05); Calibrated: 29.04.2011
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn654; Calibrated: 03.05.2011
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1003
- DASY52 52.6.2(482); SEMCAD X 14.4.5(3634)

Dipole Calibration for Body Tissue/d=15mm, Pin=398mW/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 46.820 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 2.773 W/kg

SAR(1 g) = 1.77 mW/g; SAR(10 g) = 1.18 mW/g

Maximum value of SAR (measured) = 1.891 mW/g



Impedance Measurement Plot for Body TSL

