

—

Table of Contents

General Information	3
2.0 Summary of Test Results.....	4
3.0. Measurement Uncertainty	4
4.0 Equipment List	5
5.0 Test Mode Applicability and Test Channel Detail	6
6.0 Transmitter Test Parameters.....	7
6.1 6dB Channel Bandwidth.....	7
Test Setup	7
Test Limits:	7
Test Data:	7
6.2 Maximum Peak Conducted RF Output Power	9
Test Setup	9
Test Limits:	9
Test Data:	10
6.3 Maximum Peak Power Spectral Density	11
Test Setup	11
Test Limits:	11
Test Result	12
6.4 Conducted Spurious Emission.....	13
Test Setup	13
Test Limits:	13
Test Result	13
6.5 Band edge Conducted Spurious Emission.....	18
Test Setup	18
Test Limits:	18
Test Result	19
6.6 Radiated Emission within Restricted Bands.....	20
Test Setup	20
Test Limits:	21
Test Results:.....	22
6.7 AC Powerline Conducted Emission	40
Test Setup	40
Test Limits:	40
Test Result	41

REVISION HISTORY

Revision History	Description	Date	Originator
Rev. A	Initial Report	22-May-2018	Sharmila Jegatheesan

1.0 General Information

EUT Description:

Technologies	2.4GHz BT LE
TX Frequency range	2402MHz – 2480MHz
Modulation Type	GFSK
Input/Output	RF Port
Connector type	SPI INTERFACE & CSR USB-SPI
Antenna type	INTERNAL CHIP ANTENNA

Channel number and frequency information:

40 channels are provided to this EUT:

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

The EUT contains following accessory devices and data cable:

Item	Brand	Model or P/N
BATTERY PACK,LITHIUM POLYMER, BATT STD LIP 130M140T	MOTOROLA	DABF051230SA
POWER SUPPLY ADAPTOR,POWER- WALL CUBE AC,DC,SWITCH MODE, 5W, 100 V - 240 V, MICRO-USB	MOTOROLA	PS000042A16

General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, the EUT is to comply with the requirements of the following standards:

ANSI C63.10-2013

2.0 Summary of Test Results

FCC General Rules Part (47CFR)	IC General Rules Part	Test Item	Result	Remark
15.205, 15.209, 15.247 (d)	RSS247 5.5	Radiated Emission within Restricted Bands	Pass	NA
15.207	RSS-Gen 8.8	AC Power Line Conducted Spurious Emission	NA	NA
15.247 (b)(3)	RSS 247 5.4 (4)	Conducted RF Output Power (Peak)	Pass	NA
15.247 (a)(2)	RSS 247 5.2 (1)	6dB Channel Bandwidth	Pass	NA
15.247 (d)	RSS-247 5.5	Band-Edge Conducted Spurious Emission	Pass	NA
15.247 (b)	RSS-247 5.5	Conducted Spurious Emission	Pass	NA
15.247(e)	RSS 247 5.2 (2)	Maximum Power Spectral Density		NA
15.203	-	Antenna Requirement	NA	Internal antenna is not accessible to the end-user

3.0. Measurement Uncertainty

Measurement	Frequency	Expanded Uncertainty (k=1.96) (±)
AC Power Line Conducted Spurious Emission	150KHz ~ 30MHz	3.43
Radiated Emissions up to 1 GHz	30MHz ~ 200MHz	5.01
	200MHz ~ 1000MHz	5.01
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	5.01
	18GHz ~ 25GHz	5.01

4.0 Equipment List

Bluetooth ATE # 1 (SW Version: Ate Main_3.1.9_R1)

DESCRIPTION	MODEL	SERIAL NUMBER	CALIBRATION DATE	CALIBRATION DUE DATE
Bluetooth ATE # 1				
POWER SUPPLY	6652A	MY40001437	11-Aug-16	11-Aug-17
SPECTRUM ANALYZER	FSEK30	838495/014	13-Jul-17	13-Jul-18
SPECTRUM ANALYZER	E4445A	MY46181597	21-Dec-16	21-Dec-18

Radiated Emission Station (SW Version: EMC FCC RE v1.5.1)

DESCRIPTION	MODEL	SERIAL NUMBER	CALIBRATION DATE	CALIBRATION DUE DATE
Radiated Emmision Chamber # 1				
DRG HORN FREQ.	SAS-571	719	18-Jul-17	18-Jul-19
DRG HORN FREQ.	SAS-571	720	2-Mar-17	2-Mar-19
POWER SUPPLY	6032A	2615A01178	6-Jun-17	6-Jun-18
MICROWAVE SIGNAL GENERATOR	SMP04	100127	19-Jul-17	18-Jul-18
EMI TEST RECEIVER	ESIB26	100336	13-Jul-17	12-Jul-18
SIGNAL ANALYZER	FSV40	101103	18-Jul-17	17-Jul-18
5m SEMI-ANECHOIC CHAMBER	S800-HX	J2308	No Cal. Req'd	No Cal. Req'd
BILOG ANTENNA	CBL6112D	25224	22-Jul-17	22-Jul-18
BILOG ANTENNA	CBL6112B	2964	16-Feb-18	16-Feb-20
BROAD-BAND HORN ANTENNA	BBHA9170	BBHA9170255	7-Nov-17	7-Nov-18
DATA LOGGER	SDL500	A.016776	18-Mar-17	18-Mar-19
LOOP ANTENNA	6502	208416	27-Jul-17	27-Jul-18
SYSTEM CONTROLLER	SC104V	050806-1	No Cal. Req'd	No Cal. Req'd
TURNTABLE FLUSH MOUNT 2M	FM2011	NA	No Cal. Req'd	No Cal. Req'd
ANTENNA POSITIONING TOWER	TLT2	NA	No Cal. Req'd	No Cal. Req'd
18 - 40GHz PREAMPLIFIER	Miteq Hi Gain Sucoflex	2	No Cal. Req'd	No Cal. Req'd
PREAMPLIFIER	PAM-0118P	361	No Cal. Req'd	No Cal. Req'd
TEST SOFTWARE	EMC_FCC_IC_Bluetooth_RE_Test			
VERSION	EMC_FCC_RE_v1.5.1			

5.0 Test Mode Applicability and Test Channel Detail

Radiated Emission Test (Above 1GHz)

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Type
Test Mode	0 to 39	0,19,39	GFSK

Radiated Emission Test (Below 1GHz)

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Type
Test Mode	0 to 39	0,19,39	GFSK

Power Line Conducted Emission Test

☐ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☐ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Type
Application Mode	0 to 39	AUTO	AUTO

Antenna Port Conducted Measurement:

☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).


☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Type
Test Mode	0 to 39	0,19,39	GFSK

6.0 Transmitter Test Parameters

6.1 6dB Channel Bandwidth

Test Setup




- 1) Check and ensure the spectrum analyzer well calibrate.
- 2) Turn on the DUT and set DUT to transmit maximum power.
- 3) Connect DUT's antenna terminal to spectrum analyzer with a low loss cable.
- 4) Setting of Spectrum analyzer :
 - a. RBW = 100 kHz
 - b. VBW = 300 kHz
 - c. Detector mode = Peak
 - d. Trace = Max hold
 - e. Sweep = auto
- 5) Measure the freq different of two frequencies that were attenuated 6dB from peak of the emission & record the frequency difference as the emission bandwidth.

Test Limits:


Normal Condition (25 ° C)
≥500 kHz

Test Data:


Test Conditions		Test Frequency	Results		
Standard	Modulation Type	Tx (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Status
Bluetooth L.E	GFSK	2402	0.557	1.085	Pass
Bluetooth L.E	GFSK	2440	0.565	1.084	Pass
Bluetooth L.E	GFSK	2480	0.559	1.084	Pass




6dB Bandwidth.
Bluetooth LE Frequency 2402 MHz




99% Bandwidth.
Bluetooth LE Frequency 2402 MHz




6dB Bandwidth.
Bluetooth LE Frequency 2440 MHz



99% Bandwidth.
Bluetooth LE Frequency 2440 MHz




6dB Bandwidth.
Bluetooth LE Frequency 2480 MHz



99% Bandwidth.
Bluetooth LE Frequency 2480 MHz

6.2 Maximum Peak Conducted RF Output Power

Test Setup




- 1) Check and ensure the spectrum analyzer well calibrate.
- 2) Turn on the DUT and set DUT to transmit maximum power.
- 3) Connect DUT's antenna terminal to spectrum analyzer with a low loss cable.
- 4) Setting of Spectrum analyzer :
 - a. Set the RBW $\geq$ DTS bandwidth.
 - b. Set the VBW $\geq [3 \times \text{RBW}]$.
 - c. Set the span $\geq [3 \times \text{RBW}]$.
 - d. Detector = peak.
 - e. Sweep time = auto couple.
 - f. Trace mode = max hold.
 - g. Allow trace to fully stabilize.
 - h. Use peak marker function to determine the peak amplitude level.

Test Limits:


Normal Condition (25 ° C)
≤ 1 Watt(30 dBm)

Test Data:


Test Conditions			Test Frequency	Results
Standard	Modulation Type	Tx (MHz)	Output Power (dBm)	Status
Bluetooth L.E	GFSK	2402	4.211	Pass
Bluetooth L.E	GFSK	2440	3.922	Pass
Bluetooth L.E	GFSK	2480	4.564	Pass



**Maximum Peak Conducted RF Output Power.
Bluetooth LE Frequency 2402 MHz**




**Maximum Peak Conducted RF Output Power.
Bluetooth LE Frequency 2440 MHz**



**Maximum Peak Conducted RF Output Power.
Bluetooth LE Frequency 2480 MHz**

6.3 Maximum Peak Power Spectral Density

Test Setup



Maximum Peak


- 1) Check and ensure the spectrum analyzer well calibrate.
- 2) Turn on the DUT and set DUT to transmit maximum power.
- 3) Connect DUT's antenna terminal to spectrum analyzer with a low loss cable.
- 4) Setting of Spectrum analyzer :
 - a. Set analyzer center frequency to DTS channel center frequency.
 - b. Set the span to 1.5 times the DTS bandwidth.
 - c. Set the RBW to 3 kHz.
 - d. Set the VBW $\geq [3 \times \text{RBW}]$.
 - e. Detector = peak.
 - f. Sweep time = auto couple.
 - g. Trace mode = max hold.
 - h. Allow trace to fully stabilize.
 - i. Use the peak marker function to determine the maximum amplitude level within the RBW.
 - j. If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.

Test Limits:


Normal Condition (25 ° C)
$\leq 8 \text{ dBm/3kHz}$

Test Result


Test Conditions		Test Frequency	Results	
Standard	Modulation Type	Tx (MHz)	Power (dBm/3kHz)	Status
Bluetooth L.E.	GFSK	2402	-11.11	Pass
Bluetooth L.E.	GFSK	2440	-11.28	Pass
Bluetooth L.E.	GFSK	2480	-10.58	Pass



**Maximum Power Spectral Density.
Bluetooth LE Frequency 2402 MHz**




**Maximum Power Spectral Density.
Bluetooth LE Frequency 2440 MHz**



**Maximum Power Spectral Density.
Bluetooth LE Frequency 2480 MHz**

6.4 Conducted Spurious Emission

Test Setup




- 1) Check and ensure the spectrum analyzer well calibrate.
- 2) Turn on the DUT and set DUT to transmit maximum power.
- 3) Connect DUT's antenna terminal to spectrum analyzer with a low loss cable.
- 4) Setting of Spectrum analyzer :
 - a. RBW = 100 kHz
 - b. VBW = 300 kHz
 - c. Detector mode = Peak
 - d. Trace = Max Hold
 - e. Sweep = auto
- 5) Use the peak marker function to measure highest emission and scan up to 10th harmonic.

Test Limits:

Normal Condition (25 ° C)
Shall be at least 20 dB below peak (max) power.


Test Result

Test Conditions			Test Frequency	Results	
Standard	Modulation Type	Tx (MHz)	Spurs (MHz)	Level (dBm)	Status
Bluetooth L.E.	GFSK	2402	2507.01	-45.31	Pass
			2555.11	-45.97	Pass
			2643.29	-48.45	Pass
Bluetooth L.E.	GFSK	2440	2547.09	-44.87	Pass
			2595.19	-44.51	Pass
			4887.78	-47.09	Pass
Bluetooth L.E.	GFSK	2480	2635.27	-44.43	Pass
			2587.17	-44.76	Pass
			4967.94	-46.82	Pass




Date: 22.MAY 2018 09:26:19

Conducted Emissions. Bluetooth LE, Frequency 2402 MHz Reference Level




Date: 22.MAY 2018 09:27:14

Conducted Emissions. Bluetooth LE, Frequency 2402 MHz Emission Level, 30 MHz -> 1 GHz




Date: 22.MAY 2018 09:28:07

Conducted Emissions. Bluetooth LE, Frequency 2402 MHz Emission Level, 1 GHz -> 5 GHz




Date: 22.MAY 2018 09:29:02

Conducted Emissions. Bluetooth LE, Frequency 2402 MHz Emission Level, 5 GHz -> 10 GHz




Date: 22.MAY 2018 09:29:55

Conducted Emissions. Bluetooth LE, Frequency 2402 MHz Emission Level, 10 GHz -> 15 GHz




Date: 22.MAY 2018 09:30:49

Conducted Emissions. Bluetooth LE, Frequency 2402 MHz Emission Level, 15 GHz -> 20 GHz




Date: 22.MAY 2018 09:31:43

Conducted Emissions. Bluetooth LE, Frequency 2402 MHz Emission Level, 20 GHz -> 25 GHz




Date: 22.MAY 2018 09:01:26

Conducted Emissions. Bluetooth LE, Frequency 2440 MHz Reference Level




Date: 22.MAY 2018 09:02:20

Conducted Emissions. Bluetooth LE, Frequency 2440 MHz Emission Level, 30 MHz -> 1 GHz




Date: 22.MAY 2018 09:03:15

Conducted Emissions. Bluetooth LE, Frequency 2440 MHz Emission Level, 1 GHz -> 5 GHz




Date: 22.MAY 2018 09:04:08

Conducted Emissions. Bluetooth LE, Frequency 2440 MHz Emission Level, 5 GHz -> 10 GHz




Date: 22.MAY 2018 09:05:02

Conducted Emissions. Bluetooth LE, Frequency 2440 MHz Emission Level, 10 GHz -> 15 GHz




Date: 22.MAY 2018 09:05:55

Conducted Emissions. Bluetooth LE, Frequency 2440 MHz Emission Level, 15 GHz -> 20 GHz




Date: 22.MAY 2018 09:06:49

Conducted Emissions. Bluetooth LE, Frequency 2440 MHz Emission Level, 20 GHz -> 25 GHz




Date: 22.MAY 2018 09:08:15

Conducted Emissions. Bluetooth LE, Frequency 2480 MHz Reference Level




Date: 22.MAY 2018 09:09:09

Conducted Emissions. Bluetooth LE, Frequency 2480 MHz Emission Level, 30 MHz -> 1 GHz




Date: 22.MAY 2018 09:10:03

Conducted Emissions. Bluetooth LE, Frequency 2480 MHz Emission Level, 1 GHz -> 5 GHz




Date: 22.MAY 2018 09:10:56

Conducted Emissions. Bluetooth LE, Frequency 2480 MHz Emission Level, 5 GHz -> 10 GHz




Date: 22.MAY 2018 09:11:50

Conducted Emissions. Bluetooth LE, Frequency 2480 MHz Emission Level, 10 GHz -> 15 GHz



Date: 22.MAY 2018 09:12:44

Conducted Emissions. Bluetooth LE, Frequency 2480 MHz Emission Level, 15 GHz -> 20 GHz




Date: 22.MAY 2018 09:13:38

Conducted Emissions. Bluetooth LE, Frequency 2480 MHz Emission Level, 20 GHz -> 25 GHz

6.5 Band edge Conducted Spurious Emission

Test Setup




- a) Check and ensure the spectrum analyzer well calibrate.
- b) Turn on the DUT and set DUT to transmit maximum power.
- c) Connect DUT's antenna terminal to spectrum analyzer with a low loss cable.
- d) Setting of Spectrum analyzer :
 - a. RBW = 100 kHz
 - b. VBW = 300 kHz
 - c. Detector mode = Peak
 - d. Trace = Max Hold
 - e. Sweep = auto
- e) Use the peak marker function to measure highest emission.

Test Limits:


Normal Condition (25 ° C)
Shall be at least 20 dB below peak (max) power.

Test Result


Test Conditions		Test Frequency	Results		
Standard	Modulation Type	Tx (MHz)	Frequencies (MHz)	Power (dBm)	Status
Bluetooth L.E	GFSK	2402	2399.98	-44.26	Pass
Bluetooth L.E	GFSK	2480	2483.50	-54.40	Pass




Band Edge. Bluetooth LE
Frequency 2402 MHz Reference Level



Band Edge. Bluetooth LE
Frequency 2402 MHz Band Edge




Band Edge. Bluetooth LE
Frequency 2480 MHz Reference Level



Band Edge. Bluetooth LE
Frequency 2480 MHz Band Edge

6.6 Radiated Emission within Restricted Bands

Test Setup



- The EUT is placed on the top of a rotating table 0.8m (for frequencies < 1GHz) or 1.5m (for frequencies > 1GHz) above the ground at a 3m semi-anechoic chamber. The table is rotated 360 degrees to determine the position of the highest radiation.
- The EUT is set 3m away from the interference-receiving antenna, which is mounted on the top of a variable-height antenna tower.
- The antenna is Bilog/Horn antenna depend on which frequency range uses, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT is arranged to its worst case and then the antenna is tuned to heights from 1m to 4m and the rotatable table is turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system is set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode is fall within the range of 10dB from the limit specified, the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. Otherwise, the testing could be stopped and the peak values of the EUT would be reported.

NOTE:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection at frequency below 1GHz.
- The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3 MHz for Peak detection at frequency above 1 GHz.
- All modes of operation were investigated and the worst-case emissions are reported.

Test Limits:

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power.

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

NOTE:

- 1) The lower limit shall apply at the transition frequencies.
- 2) Emission level (dBuV/m) = 20 log Emission level (uV/m).
- 3) For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

Test: Bluetooth SAC Restricted Band Edge

Model Number: PMLN7851A	S/N: 12553-PMLN7851A-15	EMC SR ID#: 12553-EMC-00017
Battery: DABF051230SA	Accessory: NA	
Test Channel: Low	Test Frequency: 2402.0000 MHz	Test Standard: ANSI C63.10-2013
Worst Case Plane: X-Plane (BT LE)		

[illegible]


Remarks: Pass Result	Marginal Result	Fail Result
-------------------------	-----------------	-------------

Temperature (degC): 24.1
Test Performed by: Nazrin & Qawiman
System MU: 5.01dB

Humidity (%): 69.5
Test Date: Wed, May 16, 2018
Duty Cycle (%): 66%


22

Restricted Band Edge (Low Channel, Vertical, Peak) graphical screen shot




Date: 16.MAY.2018 03:20:33

Restricted Band Edge (Low Channel, Horizontal, Peak) graphical screen shot




Date: 16.MAY.2018 03:23:55

Restricted Band Edge (Low Channel, Vertical, Average) graphical screen shot



Date: 16.MAY.2018 05:19:30

Restricted Band Edge (Low Channel, Horizontal, Average) graphical screen shot



Date: 16.MAY.2018 05:23:50

Model Number: PMLN7851A	S/N: 12553-PMLN7851A-15	EMC SR ID#: 12553-EMC-00017
Battery: DABF051230SA	Accessory: NA	
Test Channel: High	Test Frequency: 2480.0000 MHz	Test Standard: ANSI C63.10-2013
Worst Case Plane: X-Plane (BT LE)		


[illegible]

Temperature (degC): 24.1
Test Performed by: Nazrin & Qawiman
System MU: 5.01dB

Humidity (%): 69.5
Test Date: Wed, May 16, 2018
Duty Cycle (%): 66%


25

Restricted Band Edge (High Channel, Vertical, Peak) graphical screen shot




Date: 16.MAY.2018 05:08:13

Restricted Band Edge (High Channel, Horizontal, Peak) graphical screen shot




Date: 16.MAY.2018 05:11:43

Restricted Band Edge (High Channel, Vertical, Average) graphical screen shot



Date: 16.MAY.2018 04:59:55

Restricted Band Edge (High Channel, Horizontal, Average) graphical screen shot



Date: 16.MAY.2018 05:04:08

Model Number: PMLN7851A	S/N: 12553-PMLN7851A-15	EMC SR ID#: 12553-EMC-00017
Battery: DABF051230SA	Accessory: NA	
Test Channel: Low	Test Frequency: 2402.0000 MHz	Test Standard: ANSI C63.10-2013
Worst Case Plane: X-Plane (BT LE)		


[illegible]

Remarks: Pass Result	Marginal Result	Fail Result
-------------------------	-----------------	-------------


Humidity (%): 69.5
Test Date: Fri, May 18, 2018
Duty Cycle (%): 66%

*Pursuant to CFR 47 Part 2.1057 (c), emissions attenuated more than 20 dB below the permissible limit are not reported.


VERTICAL, QPK




HORIZONTAL, QPK




VERTICAL, PK




HORIZONTAL, PK



VERTICAL, AV



HORIZONTAL, AV




Model Number: PMLN7851A	S/N: 12553-PMLN7851A-15	EMC SR ID#: 12553-EMC-00017
Battery: DABF051230SA	Accessory: NA	
Test Channel: Mid	Test Frequency: 2440.0000 MHz	Test Standard: ANSI C63.10-2013
Worst Case Plane: X-Plane (BT LE)		

[illegible]


Temperature (degC): 24.1	Humidity (%): 69.5
Test Performed by: Nazrin & Azil	Test Date: Fri, May 18, 2018
System MU: 5.01dB	Duty Cycle (%): 66%

*Pursuant to CFR 47 Part 2.1057 (c), emissions attenuated more than 20 dB below the permissible limit are not reported.


VERTICAL, QPK




HORIZONTAL, QPK




VERTICAL, PK




HORIZONTAL, PK



VERTICAL, AV



HORIZONTAL, AV



Model Number: PMLN7851A	S/N: 12553-PMLN7851A-15	EMC SR ID#: 12553-EMC-00017
Battery: DABF051230SA	Accessory: NA	
Test Channel: High	Test Frequency: 2480.0000 MHz	Test Standard: ANSI C63.10-2013
Worst Case Plane: X-Plane (BT LE)		


[illegible]

Remarks: Pass Result	Marginal Result	Fail Result
-------------------------	-----------------	-------------


Humidity (%): 69.5
Test Date: Fri, May 18, 2018
Duty Cycle (%): 66%

36


VERTICAL, QPK




HORIZONTAL, QPK




VERTICAL, PK




HORIZONTAL, PK



VERTICAL, AV




HORIZONTAL, AV



6.7 AC Powerline Conducted Emission

Test Setup



- 1) Tests were conducted for both Receive and Transmit Mode of the EUT.
- 2) The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/50uH of coupling impedance for the measuring instrument.
- 3) Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- 4) The frequency range from 150 kHz to 30MHz was measured.

Test Limits:

For AC Power Line Conducted Test Limit can be Class A or B depends on product classification.

Limits for conducted disturbance at the mains ports
of class A ITE

Frequency range MHz	Limits dB(μ V)	
	Quasi-peak	Average
0,15 to 0,50	79	66
0,50 to 30	73	60
NOTE The lower limit shall apply at the transition frequency.		

Table 1: Limits for Conducted Disturbance at the Mains Ports of Class A ITE.

**Limits for conducted disturbance at the mains ports
of class B ITE**

Frequency range MHz	Limits dB(μ V)	
	Quasi-peak	Average
0,15 to 0,50	66 to 56	56 to 46
0,50 to 5	56	46
5 to 30	60	50
NOTE 1 The lower limit shall apply at the transition frequencies. NOTE 2 The limit decreases linearly with the logarithm of the frequency in the range 0,15 MHz to 0,50 MHz.		

Table 2: Limits for Conducted Disturbance at the Mains Ports of Class B ITE

Test Result

Not Applicable. Testing is not required, radio shall turn off during charging mode.