



CERTIFICATE OF COMPLIANCE
(SAR EVALUATION)
Class II Permissive Change

APPLICANT NAME & ADDRESS:

MOTOROLA, INC.
8000 West Sunrise Blvd.
Ft. Lauderdale, FL 33322

DATE & LOCATION OF TESTING:

Dates of Tests: June 13-15, 2006
Test Report S/N: 0606060463-R1
Test Site: PCTEST Lab, Columbia MD

FCC ID:	AZ489FT7018
APPLICANT:	MOTOROLA, INC.

EUT Type: Handheld Computer with GSM, Bluetooth and WLAN Transceivers
Tx Frequency: 824.20 – 848.80MHz (GSM850) / 1850.20MHz – 1909.80MHz (GSM1900)
 2402 – 2480 MHz (Bluetooth) / 2412 – 2462 MHz (WLAN)
Rx Frequency: 869.20 – 893.80MHz (GSM850) / 1930.20MHz – 1989.80MHz (GSM1900)
 2402 – 2480 MHz (Bluetooth) / 2412 – 2462 MHz (WLAN)
Max. RF Output Power: 1.778 W GSM850 Conducted; 0.891 W PCS GSM Conducted;
 40 mW WLAN; 2.0 mW Bluetooth
Max. SAR Measurement: 0.068 W/kg GSM Head SAR; 0.603 W/kg GSM Body SAR;
 0.132 W/kg PCS GSM Head SAR; 0.326 W/kg PCS GSM Body SAR
 0.0044 W/kg Bluetooth Body SAR; 0.044 W/kg WLAN Body SAR
Trade Name/Model(s): HC700G/ F3133A
FCC Classification: Licensed Portable Transmitter Held to Ear (PCE)
 Digital Transmission System (DTS)
 Spread Spectrum Transceiver (DSS)
FCC Rule Part(s): §2.1093; FCC/OET Bulletin 65 Supplement C [July 2001]
Application Type: Certification
Test Device Serial No.: pilot vintage [S/N: #629SGJ3203]
Class II Change: Please see change document.
Original Grant Date: April 5, 2006

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE Std. C95.1-1992 and had been tested in accordance with the measurement procedures specified in FCC/OET Bulletin 65 Supplement C (2001) and IEEE Std. 1528 – 2003.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Grant Conditions: Power output listed is ERP for Part 22 and EIRP for Part 24. This device also contains a WLAN transmitter that may not transmit simultaneously with this transmitter. SAR compliance for body-worn operating configurations is limited to the specific configuration tested in this filing. End-users must be informed of the body-worn operating requirements for satisfying RF exposure compliance. SAR compliance was evaluated with the integral Bluetooth active.

*NOTE: This revised Test Report (S/N: 0606060463-R1) supercedes and replaces the previously issued test report on the same subject EUT for the same type of testing as indicated. Please discard or destroy the previously issued report (S/N: 0606060463) and dispose of it accordingly.

PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.

Randy Ortano
President



PCTEST SAR REPORT	FCC Class II Permissive Change		Reviewed by: Quality Manager
SAR Filename: 0606060463-R1	Test Dates: June 13-15, 2006	Phone Type: Handheld Computer with GSM, Bluetooth & WLAN Transceivers	FCC ID: AZ489FT7018 Page 1 of 37

TABLE OF CONTENTS

1.	INTRODUCTION / SAR DEFINITION	3
2.	SAR MEASUREMENT SETUP	4
3.	DASY4 E-FIELD PROBE SYSTEM	5
4.	PROBE CALIBRATION PROCESS	6
5.	PHANTOM & EQUIVALENT TISSUES	7
6.	TEST SYSTEM SPECIFICATIONS	8
7.	DOSIMETRIC ASSESSMENT & PHANTOM SPECS	9
8.	DEFINITION OF REFERENCE POINTS	10
9.	TEST CONFIGURATION POSITIONS	11
10.	ANSI/IEEE C95.1 - 1992 RF EXPOSURE LIMITS	14
11.	MEASUREMENT UNCERTAINTIES	15
12.	SYSTEM VERIFICATION	16-17
13.	SAR TEST DATA SUMMARY	18-34
15.	SAR TEST EQUIPMENT	35
16.	CONCLUSION	36
17.	REFERENCES	37

PCTEST SAR REPORT		FCC Class II Permissive Change		Reviewed by: Quality Manager
SAR Filename: 0606060463-R1	Test Dates: June 13-15, 2006	Phone Type: Handheld Computer with GSM, Bluetooth & WLAN Transceivers	FCC ID: AZ489FT7018	Page 2 of 37

1. INTRODUCTION / SAR DEFINITION

The FCC has adopted the guidelines for evaluating the environmental effects of radiofrequency radiation in ET Docket 93-62 on Aug. 6, 1996 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices.[1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in *IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz*. (c) 1992 by the Institute of Electrical and Electronics Engineers, Inc., New York, New York 10017.[2] The measurement procedure described in *IEEE/ANSI C95.3-1992 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave*[3] is used for guidance in measuring SAR due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the National Council on Radiation Protection and Measurements (NCRP) in *Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields*, NCRP Report No. 86 (c) NCRP, 1986, Bethesda, MD 20814.[6] SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

SAR Definition

Specific Absorption Rate (SAR) is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Fig. 1.1).

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dV} \right)$$

Figure 1.1
SAR Mathematical Equation

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = s E^2 / \rho$$

where:

- s = conductivity of the tissue-simulant material (S/m)
- ρ = mass density of the tissue-simulant material (kg/m³)
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relations to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

PCTEST SAR REPORT	 FCC Class II Permissive Change		Reviewed by: Quality Manager
SAR Filename: 0606060463-R1	Test Dates: June 13-15, 2006	Phone Type: Handheld Computer with GSM, Bluetooth & WLAN Transceivers	FCC ID: AZ489FT7018 Page 3 of 37

2. SAR MEASUREMENT SETUP

Robotic System

Measurements are performed using the DASY4 automated dosimetric assessment system. The DASY4 is made by Schmid & Partner Engineering AG (SPEAG) in Zurich, Switzerland and consists of high precision robotics system (Staubli), robot controller, Pentium III computer, near-field probe, probe alignment sensor, and the generic twin phantom containing the Head equivalent material. The robot is a six-axis industrial robot performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF) (see Fig. 2.1).

System Hardware

A cell controller system contains the power supply, robot controller, teach pendant (Joystick), and a remote control used to drive the robot motors. The PC consists of the Gateway Pentium 4 2.53 GHz computer with Windows XP system and SAR Measurement Software DASY4, A/D interface card, monitor, mouse, and keyboard. The Staubli Robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit that performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC plug-in card.

System Electronics




Figure 2.1 SAR Measurement System Setup

The DAE4 consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer. The system is described in detail in [7].

PCTEST SAR REPORT		FCC Class II Permissive Change		Reviewed by: Quality Manager
SAR Filename: 0606060463-R1	Test Dates: June 13-15, 2006	Phone Type: Handheld Computer with GSM, Bluetooth & WLAN Transceivers	FCC ID: AZ489FT7018	Page 4 of 37

3. DASY4 E-FIELD PROBE SYSTEM

Probe Measurement System



Figure 3.1 DAE System

The SAR measurements were conducted with the dosimetric probe EX3DV4, designed in the classical triangular configuration [7] (see Fig. 3.2) and optimized for dosimetric evaluation. The probe is constructed using the thick film technique; with printed resistive lines on ceramic substrates. The probe is equipped with an optical multifiber line ending at the front of the probe tip (see Fig. 3.3). It is connected to the EOC box on the robot arm and provides an automatic detection of the phantom surface. Half of the fibers are connected to a pulsed infrared transmitter, the other half to a synchronized receiver. As the probe approaches the surface, the reflection from the surface produces a coupling from the transmitting to the receiving fibers. This reflection increases first during the approach, reaches maximum and then decreases. If the probe is flatly touching the surface, the coupling is zero. The distance of the coupling maximum to the surface is independent of the surface reflectivity and largely independent of the surface to probe angle. The DASY4 software reads the reflection during a software approach and looks for the maximum using a 2nd order fitting (see Fig.3.1). The approach is stopped at reaching the maximum.

Probe Specifications

- Calibration: In air from 10 MHz to 6 GHz
In Head and Body simulating tissue at
Frequencies of 150 MHz, 450 MHz, 835 MHz,
900 MHz, 1900MHz, 2450MHz, 5300MHz,
& 5800MHz
- Frequency: 10 MHz to > 6 GHz; Linearity: ± 0.2 dB
(30 MHz to 6 GHz)
- Directivity: ± 0.2 dB in HSL (rotation around probe axis)
 ± 0.4 dB in HSL (rotation normal probe axis)
- Dynamic: 5 mW/g to > 100 mW/g;
- Range: Linearity: ± 0.2 dB
- Dimensions: Overall length: 330 mm
Tip length: 16 mm
Body diameter: 12 mm
Tip diameter: 3 mm
Distance from probe tip to dipole centers: 2 mm
- Application: General dosimetry up to 6 GHz
Compliance tests of mobile phones
Fast automatic scanning in arbitrary phantoms




Figure 3.1 Triangular Probe Configuration



Figure 3.2 Probe Thick-Film Technique

PCTEST SAR REPORT	 FCC Class II Permissive Change		Reviewed by: Quality Manager
SAR Filename: 0606060463-R1	Test Dates: June 13-15, 2006	Phone Type: Handheld Computer with GSM, Bluetooth & WLAN Transceivers	FCC ID: AZ489FT7018 Page 5 of 37

4. Probe Calibration Process

Dosimetric Assessment Procedure

Each probe is calibrated according to a dosimetric assessment procedure described in [8] with accuracy better than +/- 10%. The spherical isotropy was evaluated with the procedure described in [9] and found to be better than +/-0.25dB. The sensitivity parameters (NormX, NormY, NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe is tested.

Free Space Assessment

The free space E-field from amplified probe outputs is determined in a test chamber. This is performed in a TEM cell for frequencies below 1 GHz (see Fig. 4.1), and in a waveguide above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity at the proper orientation with the field. The probe is then rotated 360 degrees.

Temperature Assessment *

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated Head tissue. The measured free space Efield in the medium correlates to temperature rise in a dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe (see Fig. 4.2).

$$SAR = C \frac{\Delta T}{\Delta t}$$

where:

- Δt = exposure time (30 seconds),
- C = heat capacity of tissue (Head or Body),
- ΔT = temperature increase due to RF exposure.

SAR is proportional to $\Delta T / \Delta t$, the initial rate of tissue heating, before thermal diffusion takes place. Now it's possible to quantify the electric field in the simulated tissue by equating the thermally derived SAR to the E- field;

$$SAR = \frac{|E|^2 \cdot \sigma}{\rho}$$

where:

- σ = simulated tissue conductivity,
- ρ = Tissue density (1.25 g/cm³ for Head tissue)




Figure 4.1 E-Field and Temperature measurements at 900MHz [7]

*NOTE: The temperature calibration was not performed by PCTEST. For information use only.




Figure 4.2 E-Field and temperature measurements at 1.9GHz [7]

PCTEST SAR REPORT		FCC Class II Permissive Change		Reviewed by: Quality Manager
SAR Filename: 0606060463-R1	Test Dates: June 13-15, 2006	Phone Type: Handheld Computer with GSM, Bluetooth & WLAN Transceivers	FCC ID: AZ489FT7018	Page 6 of 37

5. PHANTOM & EQUIVALENT TISSUES

SAM Phantom




Figure 5.1 SAM Twin Phantom

The SAM Twin Phantom V4.0 is constructed of a fiberglass shell integrated in a wooden table. The shape of the shell is based on data from an anatomical study designed to determine the maximum exposure in at least 90% of all users [11][12]. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents the evaporation of the liquid. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot. (see Fig. 5.1)

Head & Body Simulating Mixture Characterization



Figure 5.2 Simulated Tissue

The Head and Body mixtures consist of a viscous gel using hydroxethylcellulose (HEC) gelling agent and saline solution (see Table 6.1). Preservation with a bactericide is added and visual inspection is made to make sure air bubbles are not trapped during the mixing process. The mixture is calibrated to obtain proper dielectric constant (permittivity) and conductivity of the desired tissue. The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 have been incorporated in the following table. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations. The mixture characterizations used for the Head and Body tissue simulating liquids are according to the data by C. Gabriel and G. Hartsgrove [13]. (see Fig. 5.2)

Table 5.1 Composition of the Head & Body Tissue Equivalent Matter

INGREDIENTS		SIMULATING TISSUE					
		835MHz Head	835MHz Body	1900MHz Head	1900MHz Body	2450MHz Head	2450MHz Body
Mixture Percentage							
WATER		41.45	52.50	54.90	59.98	62.70	73.2
DGBE		0.000	0.000	44.92	38.41	0.000	26.7
SUGAR		56.00	45.00	0.000	58.00	0.000	0.000
SALT		1.450	1.400	0.180	0.100	0.5	0.04
BACTERIACIDE		0.100	0.100	0.000	0.100	0.000	0.000
HEC		1.000	1.000	0.000	1.410	0.000	0.000
Dielectric Constant	Target	41.50	55.20	40.00	53.30	39.20	52.70
Conductivity (S/m)	Target	0.900	0.970	1.40	1.52	1.80	1.95

Device Holder for Transmitters



Figure 5.2 Mounting Device

In combination with the SAM Twin Phantom V4.0, the Mounting Device (see Fig. 5.2) enables the rotation of the mounted transmitter in spherical coordinates whereby the rotation point is the ear opening. The devices can be easily, accurately, and repeatably be positioned according to the FCC specifications. The device holder can be locked at different phantom locations (left head, right head, flat phantom).

* Note: A simulating human hand is not used due to the complex anatomical and geometrical structure of the hand that may produce infinite number of configurations [12]. To produce the worst-case condition (the hand absorbs antenna output power), the hand is omitted during the tests.

PCTEST SAR REPORT		FCC Class II Permissive Change		Reviewed by: Quality Manager
SAR Filename: 0606060463-R1	Test Dates: June 13-15, 2006	Phone Type: Handheld Computer with GSM, Bluetooth & WLAN Transceivers	FCC ID: AZ489FT7018	Page 7 of 37

6. TEST SYSTEM SPECIFICATIONS

Automated Test System Specifications

Positioner

Robot: Stäubli Unimation Corp. Robot Model: RX60L
Repeatability: 0.02 mm
No. of axis: 6



Figure 6.1 DASY4 Test System

Data Acquisition Electronic (DAE) System

Cell Controller

Processor: Pentium 4
Clock Speed: 2.53 GHz
Operating System: Windows XP Professional

Data Converter

Features: Signal Amplifier, multiplexer, A/D converter, & control logic
Software: DASY4 software
Connecting Lines: Optical downlink for data and status info.
 Optical uplink for commands and clock

PC Interface Card

Function: 24 bit (64 MHz) DSP for real time processing
 Link to DAE4
 16 bit A/D converter for surface detection system
 serial link to robot
 direct emergency stop output for robot

E-Field Probes

Model: EX3DV4 S/N: 3561
Construction: Triangular core
Frequency: 10 MHz to 6 GHz
Linearity: ± 0.2 dB (30 MHz to 6 GHz)

Phantom

Phantom: SAM Twin Phantom (V4.0)
Shell Material: VIVAC Composite
Thickness: 2.0 ± 0.2 mm

PCTEST SAR REPORT		FCC Class II Permissive Change		Reviewed by: Quality Manager
SAR Filename: 0606060463-R1	Test Dates: June 13-15, 2006	Phone Type: Handheld Computer with GSM, Bluetooth & WLAN Transceivers	FCC ID: AZ489FT7018	Page 8 of 37

7. DOSIMETRIC ASSESSMENT & PHANTOM SPECS

Measurement Procedure

The evaluation was performed using the following procedure:

1. The SAR measurement was taken at a selected spatial reference point to monitor power variations during testing. This fixed location point was measured and used as a reference value.
2. The SAR distribution at the exposed side of the head was measured at a distance of 3.9mm from the inner surface of the shell. The area covered the entire dimension of the head and the horizontal grid spacing was 15mm x 15mm.
3. Based on the area scan data, the area of the maximum absorption was determined by spline interpolation. Around this point, a volume of 32mm x 32mm x 34mm (fine resolution volume scan, zoom scan) was assessed by measuring 5 x 5 x 7 points. On this basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see Fig. 7.1):
 - a. The data at the surface was extrapolated, since the center of the dipoles is 2.7mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.2mm. The extrapolation was based on a least square algorithm [15]. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip.
 - b. The maximum interpolated value was searched with a straight-forward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1g or 10g) were computed using the 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions) [15][16]. The volume was integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were interpolated to calculate the average.
 - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as procedure #1, was re-measured. If the value changed by more than 5%, the evaluation is repeated.



Figure 7.1 Sample SAR Area Scan

Deviation from measurement procedure - None

Specific Anthropomorphic Mannequin (SAM) Specifications

The phantom for handset SAR assessment testing is a low-loss dielectric shell, with shape and dimensions derived from the anthropometric data of the 90th percentile adult male head dimensions as tabulated by the US Army. The SAM Twin Phantom shell is bisected along the mid-sagittal plane into right and left halves (see Fig. 7.2). The perimeter sidewalls of each phantom halves are extended to allow filling with liquid to a depth that is sufficient to minimized reflections from the upper surface. The liquid depth is maintained at a minimum depth of 15cm to minimize reflections from the upper surface.



Figure 7.2 SAM Twin Phantom shell

PCTEST SAR REPORT		FCC Class II Permissive Change		Reviewed by: Quality Manager
SAR Filename: 0606060463-R1	Test Dates: June 13-15, 2006	Phone Type: Handheld Computer with GSM, Bluetooth & WLAN Transceivers	FCC ID: AZ489FT7018	Page 9 of 37

8. DEFINITION OF REFERENCE POINTS

EAR Reference Point

Figure 8.1 shows the front, back and side views of the SAM Twin Phantom. The point “M” is the reference point for the center of the mouth, “LE” is the left ear reference point (ERP), and “RE” is the right ERP. The ERPs are 15mm posterior to the entrance to the ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 9.2. The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front) is perpendicular to the reference plane and passing through the RE (or LE) is called the Reference Pivoting Line (see Figure 8.2). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].




Figure 8.2 Close-up side view of ERPs




Figure 8.1 Front, back and side view of SAM Twin Phantom

Handset Reference Points

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the “test device reference point” located along the “vertical centerline” on the front of the device aligned to the “ear reference point” (See Fig. 8.3). The “test device reference point” was then located at the same level as the center of the ear reference point. The test device was positioned so that the “vertical centerline” was bisecting the front surface of the handset at its top and bottom edges, positioning the “ear reference point” on the outer surface of the both the left and right head phantoms on the ear reference point.




Figure 8.3 Handset Vertical Center & Horizontal Line Reference Points

PCTEST SAR REPORT		FCC Class II Permissive Change		Reviewed by: Quality Manager
SAR Filename: 0606060463-R1	Test Dates: June 13-15, 2006	Phone Type: Handheld Computer with GSM, Bluetooth & WLAN Transceivers	FCC ID: AZ489FT7018	Page 10 of 37

9. TEST CONFIGURATION POSITIONS

Positioning for Cheek/Touch

- The test device was positioned with the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 9.1), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.




Figure 9.1 Front, Side and Top View of Cheek/Touch Position

- The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the ear.
- While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the plane normal to MB-NF including the line MB (reference plane).
- The phone was then rotated around the vertical centerline until the phone (horizontal line) was symmetrical with respect to the line NF.
- While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the phone contact with the ear, the handset was rotated about the line NF until any point on the handset made contact with a phantom point below the ear (cheek). See Figure 9.2)




Figure 9.2 Side view w/ relevant markings

PCTEST SAR REPORT		FCC Class II Permissive Change		Reviewed by: Quality Manager
SAR Filename: 0606060463-R1	Test Dates: June 13-15, 2006	Phone Type: Handheld Computer with GSM, Bluetooth & WLAN Transceivers	FCC ID: AZ489FT7018	Page 11 of 37

9. TEST CONFIGURATION POSITIONS (Continued)

Positioning for Ear / 15° Tilt

With the test device aligned in the “Cheek/Touch Position”:

1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15 degree.
2. The phone was then rotated around the horizontal line by 15 degree.
3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the phone touches the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. The tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head (see Figure 9.3).



Figure 9.3 Front, Side and Top View of Ear/15° Tilt Position




Figure 9.4 Side view w/ relevant markings

PCTEST SAR REPORT		FCC Class II Permissive Change		Reviewed by: Quality Manager
SAR Filename: 0606060463-R1	Test Dates: June 13-15, 2006	Phone Type: Handheld Computer with GSM, Bluetooth & WLAN Transceivers	FCC ID: AZ489FT7018	Page 12 of 37

9. TEST CONFIGURATION POSITIONS (Continued)

Body Holster /Belt Clip Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 9.5). A device with a headset output is tested with a headset connected to the device. Body dielectric parameters are used.

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are supplied with the device, the device is tested with each accessory that contains a unique metallic component. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration where a separation distance between the back of the device and the flat phantom is used. All test position spacings are documented.

Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessory(ies), including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

In all cases SAR measurements are performed to investigate the worst-case positioning. Worst-case positioning is then documented and used to perform Body SAR testing.

In order for users to be aware of the body-worn operating requirements for meeting RF exposure compliance, operating instructions and cautions statements are included in the user's manual.



Figure 9.5 Typical Body Belt Clip & Holster Configurations
Example Photo Only
(Not Actual EUT)

PCTEST SAR REPORT		FCC Class II Permissive Change		Reviewed by: Quality Manager
SAR Filename: 0606060463-R1	Test Dates: June 13-15, 2006	Phone Type: Handheld Computer with GSM, Bluetooth & WLAN Transceivers	FCC ID: AZ489FT7018	Page 13 of 37

10. ANSI/IEEE C95.1 - 1992 RF EXPOSURE LIMITS

Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table 10.1. Safety Limits for Partial Body Exposure [2]

	HUMAN EXPOSURE LIMITS	
	UNCONTROLLED ENVIRONMENT General Population (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT Occupational (W/kg) or (mW/g)
SPATIAL PEAK SAR ¹ Head	1.60	8.00
SPATIAL AVERAGE SAR ² Whole Body	0.08	0.40
SPATIAL PEAK SAR ³ Hands, Feet, Ankles, Wrists	4.00	20.00

- 1 The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
- 2 The Spatial Average value of the SAR averaged over the whole body.
- 3 The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

PCTEST SAR REPORT		FCC Class II Permissive Change		Reviewed by: Quality Manager
SAR Filename: 0606060463-R1	Test Dates: June 13-15, 2006	Phone Type: Handheld Computer with GSM, Bluetooth & WLAN Transceivers	FCC ID: AZ489FT7018	Page 14 of 37

11. MEASUREMENT UNCERTAINTIES

a	b	c	d	e= f(d,k)	f	g	h = cx/e	i = cxg/e	k
Uncertainty Component	Sec.	Tol. (± %)	Prob. Dist.	Div.	c_i (1 - g)	c_i (10 - g)	1 - g u_i (± %)	10 - g u_i (± %)	v_i
Measurement System									
Probe Calibration	E1.1	5.9	N	1	1	1	5.9	5.9	∞
Axial Isotropy	E1.2	4.7	R	$\sqrt{3}$	0.7	0.7	1.9	1.9	∞
Hemishperical Isotropy	E1.2	9.6	R	$\sqrt{3}$	0.7	0.7	3.9	3.9	∞
Boundary Effect	E1.3	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
Linearity	E1.4	4.7	R	$\sqrt{3}$	1	1	2.7	2.7	∞
System Detection Limits	E1.5	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
Readout Electronics	E1.6	1.0	N	1	1	1	1.0	1.0	∞
Response Time	E1.7	0.8	R	$\sqrt{3}$	1	1	0.5	0.5	∞
Integration Time	E1.8	2.6	R	$\sqrt{3}$	1	1	1.5	1.5	∞
RF Ambient Conditions	E5.1	3.0	R	$\sqrt{3}$	1	1	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	E5.2	0.4	R	$\sqrt{3}$	1	1	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	E5.3	2.9	R	$\sqrt{3}$	1	1	1.7	1.7	∞
Extrapolation, Interpolation & Integration Algorithms for Max. SAR Evaluation	E4.2	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
Test Sample Related									
Test Sample Positioning	E3.2.1	2.9	N	1	1	1	2.9	2.9	145
Device Holder Uncertainty	E3.1.1	3.6	N	1	1	1	3.6	3.6	5
Output Power Variation - SAR drift measurement	5.6.2	5.0	R	$\sqrt{3}$	1	1	2.9	2.9	∞
Phantom & Tissue Parameters									
Phantom Uncertainty (Shape & Thickness tolerances)	E2.1	4.0	R	$\sqrt{3}$	1	1	2.3	2.3	∞
Liquid Conductivity - deviation from target values	E2.2	5.0	R	$\sqrt{3}$	0.64	0.43	1.8	1.2	∞
Liquid Conductivity - measurement uncertainty	E2.2	2.5	N	1	0.64	0.43	1.6	1.1	∞
Liquid Permittivity - deviation from target values	E2.2	5.0	R	$\sqrt{3}$	0.6	0.5	1.7	1.4	∞
Liquid Permittivity - measurement uncertainty	E2.2	2.5	N	1	0.6	0.5	1.5	1.2	∞
Combined Standard Uncertainty (k=1)				RSS			10.8	10.6	
Expanded Uncertainty (k=2) (95% CONFIDENCE LEVEL)							21.7	21.2	

The above measurement uncertainties are according to IEEE Std. P1528 D1.2 (April 2003).

PCTEST SAR REPORT		FCC Class II Permissive Change		Reviewed by: Quality Manager
SAR Filename: 0606060463-R1	Test Dates: June 13-15, 2006	Phone Type: Handheld Computer with GSM, Bluetooth & WLAN Transceivers	FCC ID: AZ489FT7018	Page 15 of 37

12. SYSTEM VERIFICATION

Tissue Verification

Table 12.1 Simulated Tissue Verification [5]

MEASURED TISSUE PARAMETERS									
Date(s)	06/13/2006 – 06/15/2006	835MHz Head		835MHz Body		1900MHz Head		1900MHz Body	
Liquid Temperature (°C)	21.4	Target	Measured	Target	Measured	Target	Measured	Target	Measured
Dielectric Constant: ϵ		41.50	41.67	55.20	53.98	40.00	41.43	53.30	52.61
Conductivity: σ		0.900	0.88	0.970	0.98	1.400	1.37	1.520	1.58
MEASURED TISSUE PARAMETERS									
Date(s)	06/13/2006 – 06/15/2006	2450MHz Head				2450MHz Body			
Liquid Temperature (°C)	21.4	Target		Measured		Target		Measured	
Dielectric Constant: ϵ		39.20		39.84		52.70		54.59	
Conductivity: σ		1.80		1.79		1.95		1.39	

Test System Validation

Prior to assessment, the system is verified to the $\pm 10\%$ of the specifications at 835MHz, 1900MHz and 2450 MHz by using the system validation kit(s). (Graphic Plots Attached)

Table 12.2 System Validation [5]

SYSTEM VALIDATION TARGET & MEASURED							
Date:	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Tissue	Targeted SAR_{1g} (mW/g)	Measured SAR_{1g} (mW/g)	Deviation (%)
06/13/2006	23.1	21.4	0.250	835 MHz Head	2.38	2.44	2.73
06/14/2006	23.1	21.4				2.39	0.63
06/15/2006	23.1	21.4				2.33	-1.89
06/14/2006	23.5	21.5	0.100	1900 MHz Head	3.97	3.83	-3.52
06/15/2006	23.5	21.5				3.73	-6.04
06/15/2006	23.4	21.2	0.100	2450MHz Head	5.240	4.88	-6.87




Figure 12.1 Dipole Validation Test Setup

PCTEST SAR REPORT		FCC Class II Permissive Change		Reviewed by: Quality Manager
SAR Filename: 0606060463-R1	Test Dates: June 13-15, 2006	Phone Type: Handheld Computer with GSM, Bluetooth & WLAN Transceivers	FCC ID: AZ489FT7018	Page 17 of 37

13. SAR TEST DATA SUMMARY

See Measurement Result Data Pages

Procedures Used To Establish Test Signal

The handset was placed into simulated call mode (Cellular GSM, PCS GSM, Bluetooth and WLAN modes) using manufacturers test codes. Such test signals offer a consistent means for testing SAR and are recommended for evaluating SAR [4]. When test modes are not available or inappropriate for testing a handset, the actual transmission is activated through a base station simulator or similar equipment. See data pages for actual procedure used in measurement.

Device Test Conditions

The handset is battery operated. Each SAR measurement was taken with a fully charged battery. In order to verify that the device was tested at full power, conducted output power measurements were performed before and after each SAR measurement to confirm the output power. If a conducted power deviation of more than 5% occurred, the test was repeated.

PCTEST SAR REPORT		FCC Class II Permissive Change		Reviewed by: Quality Manager
SAR Filename: 0606060463-R1	Test Dates: June 13-15, 2006	Phone Type: Handheld Computer with GSM, Bluetooth & WLAN Transceivers	FCC ID: AZ489FT7018	Page 18 of 37

SAR DATA SUMMARY (Continued)

Mixture Type: 835MHz Head

14.1 MEASUREMENT RESULTS (GSM850 Right Head SAR, Touch)												
FREQUENCY		Modulation	Begin / End POWER [‡]			w/ SD Card	w/ BT	Device Test Position	Antenna Position	SAR W/kg	Drift	Cal SAR W/kg
MHz	Ch.		(dBm)	Battery								
836.60	190	GSM	32.20	32.42	FNN7815A	-	-	Cheek / Touch	Internal	0.0710	0.220	0.0675
836.60	190	GSM	32.20	32.39	FNN7815A	Yes	2441	Cheek / Touch	Internal	0.0669	0.185	0.0641
836.60	190	GSM	32.20	32.28	FNN7826A	-	-	Cheek / Touch	Internal	0.0587	0.085	0.0576
ANSI / IEEE C95.1 1992 - SAFETY LIMIT						Head						
Spatial Peak						1.6 W/kg (mW/g)						
Uncontrolled Exposure/General Population						averaged over 1 gram						

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
 2. All modes of operation were investigated, and worst-case results are reported.
 3. Battery is fully charged for all readings.
- [‡]Power Measured Conducted ERP EIRP
 4. SAR Measurement System DASY4 IDX
 Phantom Configuration Left Head Flat Phantom Right Head
 5. SAR Configuration Head Body Hand
 6. Test Signal Call Mode Manu. Test Codes Base Station Simulator
7. Tissue parameters and temperatures are listed on the SAR plots.
 8. Liquid tissue depth is 15.1 cm. ± 0.1



Randy Ortanez
President

PCTEST SAR REPORT		FCC Class II Permissive Change		Reviewed by: Quality Manager
SAR Filename: 0606060463-R1	Test Dates: June 13-15, 2006	Phone Type: Handheld Computer with GSM, Bluetooth & WLAN Transceivers	FCC ID: AZ489FT7018	Page 19 of 37

SAR DATA SUMMARY (Continued)

Mixture Type: 835MHz Head

14.2 MEASUREMENT RESULTS (GSM850 Right Head SAR, Tilt)												
FREQUENCY		Modulation	Begin / End POWER [‡]			w/ SD Card	w/ BT	Device Test Position	Antenna Position	SAR W/kg	Drift	Cal SAR W/kg
MHz	Ch.		(dBm)	Battery								
836.60	190	GSM	32.20	32.41	FNN7815A	No	Off	Ear / 15° Tilt	Internal	0.0486	0.214	0.0463
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						Head 1.6 W/kg (mW/g) averaged over 1 gram						

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
 2. All modes of operation were investigated, and worst-case results are reported.
 3. Battery is fully charged for all readings.
- | | | | | | | |
|-----------------|-------------------------------------|-----------|--------------------------|-----|--------------------------|------|
| ‡Power Measured | <input checked="" type="checkbox"/> | Conducted | <input type="checkbox"/> | ERP | <input type="checkbox"/> | EIRP |
|-----------------|-------------------------------------|-----------|--------------------------|-----|--------------------------|------|
4. SAR Measurement System DASY4 IDX
 - Phantom Configuration Left Head Flat Phantom Right Head
 5. SAR Configuration Head Body Hand
 6. Test Signal Call Mode Manu. Test Codes Base Station Simulator
 7. Tissue parameters and temperatures are listed on the SAR plots.
 8. Liquid tissue depth is 15.1 cm. ± 0.1
 9. Justification for reduced test configurations: Per FCC/OET Bulletin 65 Supplement C (July, 2001), if the SAR measured at the middle channel for each test configuration (left, right, cheek/touch, tilt/ear, extended and retracted) is at least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).



Randy Ortanez
President

PCTEST SAR REPORT	FCC Class II Permissive Change		Reviewed by: Quality Manager
SAR Filename: 0606060463-R1	Test Dates: June 13-15, 2006	Phone Type: Handheld Computer with GSM, Bluetooth & WLAN Transceivers	FCC ID: AZ489FT7018 Page 20 of 37

SAR DATA SUMMARY (Continued)

Mixture Type: 835MHz Head

14.3 MEASUREMENT RESULTS (GSM850 Left Head SAR, Touch)												
FREQUENCY		Modulation	Begin / End POWER [‡]			w/ SD Card	w/ BT	Device Test Position	Antenna Position	SAR W/kg	Drift	Cal SAR W/kg
MHz	Ch.		(dBm)		Battery							
836.60	190	GSM	32.20	32.42	FNN7815A	-	-	Cheek / Touch	Internal	0.0214	0.222	0.0203
836.60	190	GSM	32.20	32.34	FNN7815A	Yes	2441	Cheek / Touch	Internal	0.0210	0.139	0.0203
836.60	190	GSM	32.20	32.27	FNN7826A	-	-	Cheek / Touch	Internal	0.0516	0.066	0.0508
ANSI / IEEE C95.1 1992 - SAFETY LIMIT						Head						
Spatial Peak						1.6 W/kg (mW/g)						
Uncontrolled Exposure/General Population						averaged over 1 gram						

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
 2. All modes of operation were investigated, and worst-case results are reported.
 3. Battery is fully charged for all readings.
- | | | | | | | |
|---------------------------|-------------------------------------|------------------|--------------------------|------------------------|--------------------------|------------|
| ‡Power Measured | <input checked="" type="checkbox"/> | Conducted | <input type="checkbox"/> | ERP | <input type="checkbox"/> | EIRP |
| 4. SAR Measurement System | <input checked="" type="checkbox"/> | DASY4 | <input type="checkbox"/> | IDX | | |
| Phantom Configuration | <input checked="" type="checkbox"/> | Left Head | <input type="checkbox"/> | Flat Phantom | <input type="checkbox"/> | Right Head |
| 5. SAR Configuration | <input checked="" type="checkbox"/> | Head | <input type="checkbox"/> | Body | <input type="checkbox"/> | Hand |
| 6. Test Signal Call Mode | <input checked="" type="checkbox"/> | Manu. Test Codes | <input type="checkbox"/> | Base Station Simulator | | |
7. Tissue parameters and temperatures are listed on the SAR plots.
 8. Liquid tissue depth is 15.1 cm. ± 0.1



Randy Ortanez
President

PCTEST SAR REPORT		FCC Class II Permissive Change		Reviewed by: Quality Manager
SAR Filename: 0606060463-R1	Test Dates: June 13-15, 2006	Phone Type: Handheld Computer with GSM, Bluetooth & WLAN Transceivers	FCC ID: AZ489FT7018	Page 21 of 37

SAR DATA SUMMARY (Continued)

Mixture Type: 835MHz Head

14.4 MEASUREMENT RESULTS (GSM850 Left Head SAR, Tilt)												
FREQUENCY		Modulation	Begin / End POWER [‡]			w/ SD Card	w/ BT	Device Test Position	Antenna Position	SAR W/kg	Drift	Cal SAR W/kg
MHz	Ch.		(dBm)		Battery							
836.60	190	GSM	32.20	32.44	FNN7815A	No	Off	Ear / 15° Tilt	Internal	0.0439	0.241	0.0415
ANSI / IEEE C95.1 1992 - SAFETY LIMIT						Head						
Spatial Peak						1.6 W/kg (mW/g)						
Uncontrolled Exposure/General Population						averaged over 1 gram						

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Battery is fully charged for all readings.

[‡] Power Measured	<input checked="" type="checkbox"/>	Conducted	<input type="checkbox"/>	ERP	<input type="checkbox"/>	EIRP
-----------------------------	-------------------------------------	-----------	--------------------------	-----	--------------------------	------
4. SAR Measurement System

	<input checked="" type="checkbox"/>	DASY4	<input type="checkbox"/>	IDX
--	-------------------------------------	-------	--------------------------	-----
- Phantom Configuration

<input checked="" type="checkbox"/>	Left Head	<input type="checkbox"/>	Flat Phantom	<input type="checkbox"/>	Right Head
-------------------------------------	-----------	--------------------------	--------------	--------------------------	------------
5. SAR Configuration

<input checked="" type="checkbox"/>	Head	<input type="checkbox"/>	Body	<input type="checkbox"/>	Hand
-------------------------------------	------	--------------------------	------	--------------------------	------
6. Test Signal Call Mode

<input checked="" type="checkbox"/>	Manu. Test Codes	<input type="checkbox"/>	Base Station Simulator
-------------------------------------	------------------	--------------------------	------------------------
7. Tissue parameters and temperatures are listed on the SAR plots.
8. Liquid tissue depth is 15.1 cm. ± 0.1
9. Justification for reduced test configurations: Per FCC/OET Bulletin 65 Supplement C (July, 2001), if the SAR measured at the middle channel for each test configuration (left, right, cheek/touch, tilt/ear, extended and retracted) is at least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).



Randy Orlanez
President

PCTEST SAR REPORT		FCC Class II Permissive Change		Reviewed by: Quality Manager
SAR Filename: 0606060463-R1	Test Dates: June 13-15, 2006	Phone Type: Handheld Computer with GSM, Bluetooth & WLAN Transceivers	FCC ID: AZ489FT7018	Page 22 of 37

SAR DATA SUMMARY (Continued)

Mixture Type: 1900MHz Head

14.5 MEASUREMENT RESULTS (GSM1900 Right Head SAR, Touch)												
FREQUENCY		Modulation	Begin / End POWER [‡]			w/ SD Card	w/ BT	Device Test Position	Antenna Position	SAR W/kg	Drift	Cal SAR W/kg
MHz	Ch.		dBm		Battery							
1880.00	661	PCS GSM	29.20	29.32	FNN7815A	-	-	Cheek / Touch	Internal	0.1350	0.119	0.1314
1880.00	661	PCS GSM	29.20	28.99	FNN7815A	Yes	2441	Cheek / Touch	Internal	0.1320	-0.215	0.1387
1880.00	661	PCS GSM	29.20	29.33	FNN7826A	-	-	Cheek / Touch	Internal	0.1360	0.126	0.1321
ANSI / IEEE C95.1 1992 - SAFETY LIMIT						Head						
Spatial Peak						1.6 W/kg (mW/g)						
Uncontrolled Exposure/General Population						averaged over 1 gram						

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
 2. All modes of operation were investigated, and worst-case results are reported.
 3. Battery is fully charged for all readings.
- [‡]Power Measured Conducted ERP EIRP
4. SAR Measurement System DASY4 IDX
- Phantom Configuration ? Left Head Flat Phantom Right Head
5. SAR Configuration Head Body Hand
6. Test Signal Call Mode Manu. Test Codes Base Station Simulator
7. Tissue parameters and temperatures are listed on the SAR plots.
 8. Liquid tissue depth is 15.1 cm. ± 0.1



Randy Ortanez
President

PCTEST SAR REPORT		FCC Class II Permissive Change		Reviewed by: Quality Manager
SAR Filename: 0606060463-R1	Test Dates: June 13-15, 2006	Phone Type: Handheld Computer with GSM, Bluetooth & WLAN Transceivers	FCC ID: AZ489FT7018	Page 23 of 37

SAR DATA SUMMARY (Continued)

Mixture Type: 1900MHz Head

14.6 MEASUREMENT RESULTS (GSM1900 Right Head SAR, Tilt)												
FREQUENCY		Modulation	Begin / End POWER [‡]			w/ SD Card	w/ BT	Device Test Position	Antenna Position	SAR W/kg	Drift	Cal SAR W/kg
MHz	Ch.		(dBm)	Battery								
1880.00	661	PCS GSM	29.20	29.41	FNN7815A	No	Off	Ear / 15° Tilt	Internal	0.1170	0.214	0.1114
ANSI / IEEE C95.1 1992 - SAFETY LIMIT						Head						
Spatial Peak						1.6 W/kg (mW/g)						
Uncontrolled Exposure/General Population						averaged over 1 gram						

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
 2. All modes of operation were investigated, and worst-case results are reported.
 3. Battery is fully charged for all readings.
- [‡]Power Measured Conducted ERP EIRP
4. SAR Measurement System DASY4 IDX
 Phantom Configuration Left Head Flat Phantom Right Head
 5. SAR Configuration Head Body Hand
 6. Test Signal Call Mode Manu. Test Codes Base Station Simulator
7. Tissue parameters and temperatures are listed on the SAR plots.
 8. Liquid tissue depth is 15.1 cm. ± 0.1
 9. Justification for reduced test configurations: Per FCC/OET Bulletin 65 Supplement C (July, 2001), if the SAR measured at the middle channel for each test configuration (left, right, cheek/touch, tilt/ear, extended and retracted) is at least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).



Randy Orlaniz
President

PCTEST SAR REPORT		FCC Class II Permissive Change		Reviewed by: Quality Manager
SAR Filename: 0606060463-R1	Test Dates: June 13-15, 2006	Phone Type: Handheld Computer with GSM, Bluetooth & WLAN Transceivers	FCC ID: AZ489FT7018	Page 24 of 37

SAR DATA SUMMARY (Continued)

Mixture Type: 1900MHz Head

14.7 MEASUREMENT RESULTS (GSM1900 Left Head SAR, Touch)												
FREQUENCY		Modulation	Begin / End POWER [‡]			w/ SD Card	w/ BT	Device Test Position	Antenna Position	SAR W/kg	Drift	Cal SAR W/kg
MHz	Ch.		(dBm)		Battery							
1880.00	661	PCS GSM	29.20	29.22	FNN7815A	-	-	Cheek / Touch	Internal	0.0950	0.020	0.0946
1880.00	661	PCS GSM	29.20	29.44	FNN7815A	Yes	2441	Cheek / Touch	Internal	0.0941	0.242	0.0890
1880.00	661	PCS GSM	29.20	29.33	FNN7826A	-	-	Cheek / Touch	Internal	0.0956	0.125	0.0929
ANSI / IEEE C95.1 1992 - SAFETY LIMIT						Head						
Spatial Peak						1.6 W/kg (mW/g)						
Uncontrolled Exposure/General Population						averaged over 1 gram						

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Battery is fully charged for all readings.

[‡] Power Measured	<input checked="" type="checkbox"/>	Conducted	<input type="checkbox"/>	ERP	<input type="checkbox"/>	EIRP
-----------------------------	-------------------------------------	-----------	--------------------------	-----	--------------------------	------
4. SAR Measurement System

	<input checked="" type="checkbox"/>	DASY4	<input type="checkbox"/>	IDX
--	-------------------------------------	-------	--------------------------	-----
- Phantom Configuration

	<input checked="" type="checkbox"/>	Left Head	<input type="checkbox"/>	Flat Phantom	<input type="checkbox"/>	Right Head
--	-------------------------------------	-----------	--------------------------	--------------	--------------------------	------------
5. SAR Configuration

	<input checked="" type="checkbox"/>	Head	<input type="checkbox"/>	Body	<input type="checkbox"/>	Hand
--	-------------------------------------	------	--------------------------	------	--------------------------	------
6. Test Signal Call Mode

	<input checked="" type="checkbox"/>	Manu. Test Codes	<input type="checkbox"/>	Base Station Simulator
--	-------------------------------------	------------------	--------------------------	------------------------
7. Tissue parameters and temperatures are listed on the SAR plots.
8. Liquid tissue depth is 15.1 cm. ± 0.1


 Randy Ortanez
 President

PCTEST SAR REPORT		FCC Class II Permissive Change		Reviewed by: Quality Manager
SAR Filename: 0606060463-R1	Test Dates: June 13-15, 2006	Phone Type: Handheld Computer with GSM, Bluetooth & WLAN Transceivers	FCC ID: AZ489FT7018	Page 25 of 37

SAR DATA SUMMARY (Continued)

Mixture Type: 1900MHz Head

14.8 MEASUREMENT RESULTS (GSM1900 Left Head SAR, Tilt)												
FREQUENCY		Modulation	Begin / End POWER [‡]			w/ SD Card	w/ BT	Device Test Position	Antenna Position	SAR W/kg	Drift	Cal SAR W/kg
MHz	Ch.		(dBm)		Battery							
1880.00	661	PCS GSM	29.20	29.40	FNN7815A	-	Off	Ear / 15° Tilt	Internal	0.0700	0.195	0.0669
ANSI / IEEE C95.1 1992 - SAFETY LIMIT						Head						
Spatial Peak						1.6 W/kg (mW/g)						
Uncontrolled Exposure/General Population						averaged over 1 gram						

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Battery is fully charged for all readings.

[‡] Power Measured	<input checked="" type="checkbox"/>	Conducted	<input type="checkbox"/>	ERP	<input type="checkbox"/>	EIRP
-----------------------------	-------------------------------------	-----------	--------------------------	-----	--------------------------	------
4. SAR Measurement System

	<input checked="" type="checkbox"/>	DASY4	<input type="checkbox"/>	IDX
--	-------------------------------------	-------	--------------------------	-----
- Phantom Configuration

	<input checked="" type="checkbox"/>	Left Head	<input type="checkbox"/>	Flat Phantom	<input type="checkbox"/>	Right Head
--	-------------------------------------	-----------	--------------------------	--------------	--------------------------	------------
5. SAR Configuration

	<input checked="" type="checkbox"/>	Head	<input type="checkbox"/>	Body	<input type="checkbox"/>	Hand
--	-------------------------------------	------	--------------------------	------	--------------------------	------
6. Test Signal Call Mode

	<input checked="" type="checkbox"/>	Manu. Test Codes	<input type="checkbox"/>	Base Station Simulator
--	-------------------------------------	------------------	--------------------------	------------------------
7. Tissue parameters and temperatures are listed on the SAR plots.
8. Liquid tissue depth is 15.1 cm. ± 0.1
9. Justification for reduced test configurations: Per FCC/OET Bulletin 65 Supplement C (July, 2001), if the SAR measured at the middle channel for each test configuration (left, right, cheek/touch, tilt/ear, extended and retracted) is at least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).



Randy Orlanez
President

PCTEST SAR REPORT		FCC Class II Permissive Change		Reviewed by: Quality Manager
SAR Filename: 0606060463-R1	Test Dates: June 13-15, 2006	Phone Type: Handheld Computer with GSM, Bluetooth & WLAN Transceivers	FCC ID: AZ489FT7018	Page 26 of 37

SAR DATA SUMMARY (Continued)

Mixture Type: 835MHz Body

14.9 MEASUREMENT RESULTS (GSM850 Body SAR, w/ Beltclip P/N: FTN6839A)												
FREQUENCY		Modulation	Begin / End POWER [‡]			w/ SD Card	w/ BT	Side	Antenna Position	SAR W/kg	Drift	Cal SAR W/kg
MHz	Ch.		(dBm)		Battery							
836.60	190	GSM	32.20	32.32	FNN7815A	-	-	Front	Internal	0.066	0.122	0.064
836.60	190	GSM	32.20	32.27	FNN7815A	Yes	2441	Front	Internal	0.065	0.068	0.064
836.60	190	GSM	32.20	32.16	FNN7826A	-	-	Front	Internal	0.066	-0.43	0.067
836.60	190	GSM	32.20	32.34	FNN7815A	-	-	Back	Internal	0.622	0.138	0.603
836.60	190	GSM	32.20	32.31	FNN7815A	Yes	2441	Back	Internal	0.618	0.109	0.603
836.60	190	GSM	32.20	32.24	FNN7826A	-	-	Back	Internal	0.617	0.045	0.611
ANSI / IEEE C95.1 1992 - SAFETY LIMIT						Body						
Spatial Peak						1.6 W/kg (mW/g)						
Uncontrolled Exposure/General Population						averaged over 1 gram						

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Battery is fully charged for all readings.
- | | | | |
|---------------------------|--|--|-------------------------------------|
| ‡Power Measured | <input checked="" type="checkbox"/> Conducted | <input type="checkbox"/> ERP | <input type="checkbox"/> EIRP |
| 4. SAR Measurement System | <input checked="" type="checkbox"/> DASY4 | <input type="checkbox"/> IDX | |
| Phantom Configuration | <input type="checkbox"/> Left Head | <input checked="" type="checkbox"/> Flat Phantom | <input type="checkbox"/> Right Head |
| 5. SAR Configuration | <input type="checkbox"/> Head | <input checked="" type="checkbox"/> Body | <input type="checkbox"/> Hand |
| 6. Test Signal Call Mode | <input checked="" type="checkbox"/> Manu. Test Codes | <input type="checkbox"/> Base Station Simulator | |
| 7. ‡‡Test Configuration | <input checked="" type="checkbox"/> With Beltclip | <input type="checkbox"/> Without Beltclip | |
8. Tissue parameters and temperatures are listed on the SAR plots.
9. Both sides of the EUT were tested and the worst-case side is reported.
10. Liquid tissue depth is 15.1 cm. ± 0.1



Randy Ortance
President

PCTEST SAR REPORT		FCC Class II Permissive Change		Reviewed by: Quality Manager
SAR Filename: 0606060463-R1	Test Dates: June 13-15, 2006	Phone Type: Handheld Computer with GSM, Bluetooth & WLAN Transceivers	FCC ID: AZ489FT7018	Page 27 of 37

SAR DATA SUMMARY (Continued)

Mixture Type: 835MHz Head

14.10 MEASUREMENT RESULTS (GSM850 Face SAR)												
FREQUENCY		Modulation	Begin / End POWER [‡]			w/ SD Card	w/ BT	Separation Distance (cm) ‡‡	Antenna Position	SAR W/kg	Drift	Cal SAR W/kg
MHz	Ch.		(dBm)	Battery								
836.60	190	GSM	32.20	32.25	FNN7815A	-	-	2.5 cm	Internal	0.0290	0.146	0.0208
836.60	190	GSM	32.20	32.30	FNN7815A	Yes	2441	2.5 cm	Internal	0.0300	0.153	0.0290
836.60	190	GSM	32.20	32.39	FNN7826A	-	-	2.5 cm	Internal	0.0305	0.202	0.0291
ANSI / IEEE C95.1 1992 - SAFETY LIMIT						Head						
Spatial Peak						1.6 W/kg (mW/g)						
Uncontrolled Exposure/General Population						averaged over 1 gram						

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
 2. All modes of operation were investigated, and worst-case results are reported.
 3. Battery is fully charged for all readings.
- | | | | | | | |
|---------------------------|-------------------------------------|------------------|-------------------------------------|------------------------|-------------------------------------|------------|
| ‡Power Measured | <input checked="" type="checkbox"/> | Conducted | <input type="checkbox"/> | ERP | <input type="checkbox"/> | EIRP |
| 4. SAR Measurement System | <input checked="" type="checkbox"/> | DASY4 | <input type="checkbox"/> | IDX | <input type="checkbox"/> | |
| Phantom Configuration | <input type="checkbox"/> | Left Head | <input checked="" type="checkbox"/> | Flat Phantom | <input type="checkbox"/> | Right Head |
| 5. SAR Configuration | <input type="checkbox"/> | Head | <input type="checkbox"/> | Body | <input checked="" type="checkbox"/> | Face |
| 6. Test Signal Call Mode | <input checked="" type="checkbox"/> | Manu. Test Codes | <input type="checkbox"/> | Base Station Simulator | | |
| 7. ‡‡Test Configuration | <input type="checkbox"/> | With Holster | <input type="checkbox"/> | Without Holster | | |
8. Tissue parameters and temperatures are listed on the SAR plots.
 9. Both sides of the EUT were tested and the worst-case side is reported.
 10. Liquid tissue depth is 15.1 cm. ± 0.1



Randy Ortance
President

PCTEST SAR REPORT		FCC Class II Permissive Change		Reviewed by: Quality Manager
SAR Filename: 0606060463-R1	Test Dates: June 13-15, 2006	Phone Type: Handheld Computer with GSM, Bluetooth & WLAN Transceivers	FCC ID: AZ489FT7018	Page 28 of 37

SAR DATA SUMMARY (Continued)

Mixture Type: 1900MHz Body

14.11 MEASUREMENT RESULTS (GSM1900 Body SAR, w/ Beltclip P/N: FTN6839A)												
FREQUENCY		Modulation	Begin / End POWER [‡]			w/ SD Card	w/ BT	Side	Antenna Position	SAR W/kg	Drift	Cal SAR W/kg
MHz	Ch.		(dBm)	Battery								
1880.00	661	PCS GSM	29.20	29.07	FNN7815A	-	-	Front	Internal	0.048	-0.134	0.050
1880.00	661	PCS GSM	29.20	29.35	FNN7815A	Yes	2441	Front	Internal	0.047	0.149	0.045
1880.00	661	PCS GSM	29.20	29.44	FNN7826A	-	-	Front	Internal	0.049	0.237	0.046
1880.00	661	PCS GSM	29.20	29.24	FNN7815A	-	-	Back	Internal	0.316	0.036	0.313
1880.00	661	PCS GSM	29.20	29.21	FNN7815A	Yes	2441	Back	Internal	0.315	0.008	0.314
1880.00	661	PCS GSM	29.20	29.07	FNN7826A	-	-	Back	Internal	0.317	-0.128	0.326
ANSI / IEEE C95.1 1992 - SAFETY LIMIT						Body						
Spatial Peak						1.6 W/kg (mW/g)						
Uncontrolled Exposure/General Population						averaged over 1 gram						

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Battery is fully charged for all readings.
- | | | |
|---------------------------|--|--|
| ‡Power Measured | <input checked="" type="checkbox"/> Conducted | <input type="checkbox"/> ERP |
| 4. SAR Measurement System | <input checked="" type="checkbox"/> DASY4 | <input type="checkbox"/> IDX |
| Phantom Configuration | <input type="checkbox"/> Left Head | <input checked="" type="checkbox"/> Flat Phantom |
| 5. SAR Configuration | <input type="checkbox"/> Head | <input checked="" type="checkbox"/> Body |
| 6. Test Signal Call Mode | <input checked="" type="checkbox"/> Manu. Test Codes | <input type="checkbox"/> Base Station Simulator |
| 7. ‡‡Test Configuration | <input checked="" type="checkbox"/> With Beltclip | <input type="checkbox"/> Without Beltclip |
8. Tissue parameters and temperatures are listed on the SAR plots.
9. Both sides of the EUT were tested and the worst-case side is reported.
10. Liquid tissue depth is 15.1 cm. ± 0.1



Randy Ortance
President

PCTEST SAR REPORT		FCC Class II Permissive Change		Reviewed by: Quality Manager
SAR Filename: 0606060463-R1	Test Dates: June 13-15, 2006	Phone Type: Handheld Computer with GSM, Bluetooth & WLAN Transceivers	FCC ID: AZ489FT7018	Page 29 of 37

SAR DATA SUMMARY (Continued)

Mixture Type: 1900MHz Head

14.12 MEASUREMENT RESULTS (GSM1900 Face SAR)												
FREQUENCY		Modulation	Begin / End POWER [‡]			w/ SD Card	w/ BT	Separation Distance (cm) ^{‡‡}	Antenna Position	SAR W/kg	Drift	Cal SAR W/kg
MHz	Ch.		(dBm)	Battery								
1880.00	661	PCS GSM	29.20	29.33	FNN7815A	-	-	2.5 cm	Internal	0.0175	0.130	0.0170
1880.00	661	PCS GSM	29.20	29.15	FNN7815A	Yes	2441	2.5 cm	Internal	0.0179	-0.053	0.0181
1880.00	661	PCS GSM	29.20	29.39	FNN7826A	-	-	2.5 cm	Internal	0.0170	0.189	0.0163
ANSI / IEEE C95.1 1992 - SAFETY LIMIT						Head						
Spatial Peak						1.6 W/kg (mW/g)						
Uncontrolled Exposure/General Population						averaged over 1 gram						

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
 2. All modes of operation were investigated, and worst-case results are reported.
 3. Battery is fully charged for all readings.
- | | | | |
|---------------------------|--|---|--|
| ‡Power Measured | <input checked="" type="checkbox"/> Conducted | <input type="checkbox"/> ERP | <input type="checkbox"/> EIRP |
| 4. SAR Measurement System | <input checked="" type="checkbox"/> DASY4 | <input type="checkbox"/> IDX | |
| Phantom Configuration | <input type="checkbox"/> Left Head | <input checked="" type="checkbox"/> Flat Phantom | <input type="checkbox"/> Right Head |
| 5. SAR Configuration | <input type="checkbox"/> Head | <input type="checkbox"/> Body | <input checked="" type="checkbox"/> Face |
| 6. Test Signal Call Mode | <input checked="" type="checkbox"/> Manu. Test Codes | <input type="checkbox"/> Base Station Simulator | |
| 7. ‡‡Test Configuration | <input type="checkbox"/> With Holster | <input checked="" type="checkbox"/> Without Holster | |
8. Tissue parameters and temperatures are listed on the SAR plots.
 9. Both sides of the EUT were tested and the worst-case side is reported.
 10. Liquid tissue depth is 15.1 cm. ± 0.1



Randy Ortance
President

PCTEST SAR REPORT		FCC Class II Permissive Change		Reviewed by: Quality Manager
SAR Filename: 0606060463-R1	Test Dates: June 13-15, 2006	Phone Type: Handheld Computer with GSM, Bluetooth & WLAN Transceivers	FCC ID: AZ489FT7018	Page 30 of 37

SAR DATA SUMMARY (Continued)

Mixture Type: 2450MHz Body

14.13 MEASUREMENT RESULTS (Bluetooth Body SAR w/ Beltclip P/N: FTN6839A)												
FREQUENCY		Modulation	Begin / End POWER [‡]			w/ SD Card	w/ BT	Side	Antenna Position	SAR W/kg	Drift	Cal SAR W/kg
MHz	Ch.		(dBm)		Battery							
2441	39	FHSS	2.80	2.63	FNN7815A	-	-	Front	Internal	0.0042	-0.172	0.0044
2441	39	FHSS	2.80	2.65	FNN7815A	-	-	Back	Internal	0.0041	-0.151	0.0042
2441	39	FHSS	2.80	2.67	FNN7815A	Yes	2441	Front	Internal	0.0007	-0.135	0.0008
2441	39	FHSS	2.80	2.65	FNN7826A	-	-	Front	Internal	0.0041	-0.150	0.0042
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						Body 1.6 W/kg (mW/g) <small>averaged over 1 gram</small>						

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Battery is fully charged for all readings.
- | | | | |
|-------------------------------------|--|--|-------------------------------------|
| [‡] Power Measured | <input checked="" type="checkbox"/> Conducted | <input type="checkbox"/> ERP | <input type="checkbox"/> EIRP |
| 4. SAR Measurement System | <input checked="" type="checkbox"/> DASY4 | <input type="checkbox"/> IDX | |
| Phantom Configuration | <input type="checkbox"/> Left Head | <input checked="" type="checkbox"/> Flat Phantom | <input type="checkbox"/> Right Head |
| 5. SAR Configuration | <input type="checkbox"/> Head | <input checked="" type="checkbox"/> Body | <input type="checkbox"/> Hand |
| 6. Test Signal Call Mode | <input checked="" type="checkbox"/> Manu. Test Codes | <input type="checkbox"/> Base Station Simulator | |
| 7. ^{**} Test Configuration | <input checked="" type="checkbox"/> With Beltclip | <input type="checkbox"/> Without Beltclip | |
8. Tissue parameters and temperatures are listed on the SAR plots.
9. Both sides of the EUT were tested and the worst-case side is reported.
10. Liquid tissue depth is 15.1 cm. ± 0.1



Randy Ortanez
President

PCTEST SAR REPORT		FCC Class II Permissive Change		Reviewed by: Quality Manager
SAR Filename: 0606060463-R1	Test Dates: June 13-15, 2006	Phone Type: Handheld Computer with GSM, Bluetooth & WLAN Transceivers	FCC ID: AZ489FT7018	Page 31 of 37

SAR DATA SUMMARY (Continued)

Mixture Type: 2450MHz Head

14.14 MEASUREMENT RESULTS (Bluetooth Face SAR)												
FREQUENCY		Modulation	Begin / End POWER [‡]			w/ SD Card	w/ BT	Separation Distance (cm) ^{**}	Antenna Position	SAR W/kg	Drift	Cal SAR W/kg
MHz	Ch.		(dBm)	Battery								
2441	39	FHSS	2.80	2.96	FNN7815A	Yes	-	2.5 cm	Internal	0.0035	0.159	0.0033
2441	39	FHSS	2.80	2.93	FNN7826A	-	-	2.5 cm	Internal	0.0037	0.135	0.0036
ANSI / IEEE C95.1 1992 - SAFETY LIMIT						Head						
Spatial Peak						1.6 W/kg (mW/g)						
Uncontrolled Exposure/General Population						averaged over 1 gram						

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
 2. All modes of operation were investigated, and worst-case results are reported.
 3. Battery is fully charged for all readings.
- | | | | |
|-------------------------------------|--|---|--|
| [‡] Power Measured | <input checked="" type="checkbox"/> Conducted | <input type="checkbox"/> ERP | <input type="checkbox"/> EIRP |
| 4. SAR Measurement System | <input checked="" type="checkbox"/> DASY4 | <input type="checkbox"/> IDX | |
| Phantom Configuration | <input type="checkbox"/> Left Head | <input checked="" type="checkbox"/> Flat Phantom | <input type="checkbox"/> Right Head |
| 5. SAR Configuration | <input type="checkbox"/> Head | <input type="checkbox"/> Body | <input checked="" type="checkbox"/> Face |
| 6. Test Signal Call Mode | <input checked="" type="checkbox"/> Manu. Test Codes | <input type="checkbox"/> Base Station Simulator | |
| 7. ^{**} Test Configuration | <input type="checkbox"/> With Holster | <input checked="" type="checkbox"/> Without Holster | |
8. Tissue parameters and temperatures are listed on the SAR plots.
 9. Both sides of the EUT were tested and the worst-case side is reported.
 10. Liquid tissue depth is 15.1 cm. ± 0.1



Randy Ortanez
President

PCTEST SAR REPORT		FCC Class II Permissive Change		Reviewed by: Quality Manager
SAR Filename: 0606060463-R1	Test Dates: June 13-15, 2006	Phone Type: Handheld Computer with GSM, Bluetooth & WLAN Transceivers	FCC ID: AZ489FT7018	Page 32 of 37

SAR DATA SUMMARY (Continued)

Mixture Type: 2450MHz Body

14.15 MEASUREMENT RESULTS (IEEE 802.11b Body SAR w/ Beltclip P/N: FTN6839A)													
FREQUENCY		Modulation	Begin / End POWER [‡]			w/ SD Card	w/ BT	Side	Data Bit Rate	Antenna Position	SAR W/kg	Drift	Cal SAR W/kg
MHz	Ch.		(dBm)	Battery									
2437	06	DSSS	16.20	16.40	FNN7815A	-	-	Back	1	Internal	0.0239	0.204	0.0228
2437	06	DSSS	16.20	16.07	FNN7815A	-	-	Back	2	Internal	0.0254	-0.131	0.0262
2437	06	DSSS	16.20	16.39	FNN7815A	-	-	Back	5.5	Internal	0.0249	0.187	0.0239
2437	06	DSSS	16.20	16.34	FNN7815A	-	-	Back	11	Internal	0.0262	0.136	0.0254
2437	06	DSSS	16.20	16.39	FNN7815A	-	-	Front	11	Internal	0.0424	0.189	0.0406
2437	06	DSSS	16.20	16.36	FNN7815A	Yes	2441	Front	11	Internal	0.0417	0.163	0.0402
2437	06	DSSS	16.20	16.35	FNN7826A	-	-	Front	11	Internal	0.0456	0.154	0.0440
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						Body 1.6 W/kg (mW/g) averaged over 1 gram							

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
2. All modes of operation were investigated including all data bit rates, and worst-case results are reported.
3. Battery is fully charged for all readings.
- | | | | |
|-------------------------------------|--|--|-------------------------------------|
| [‡] Power Measured | <input checked="" type="checkbox"/> Conducted | <input type="checkbox"/> ERP | <input type="checkbox"/> EIRP |
| 4. SAR Measurement System | <input checked="" type="checkbox"/> DASY4 | <input type="checkbox"/> IDX | |
| Phantom Configuration | <input type="checkbox"/> Left Head | <input checked="" type="checkbox"/> Flat Phantom | <input type="checkbox"/> Right Head |
| 5. SAR Configuration | <input type="checkbox"/> Head | <input checked="" type="checkbox"/> Body | <input type="checkbox"/> Hand |
| 6. Test Signal Call Mode | <input checked="" type="checkbox"/> Manu. Test Codes | <input type="checkbox"/> Base Station Simulator | |
| 7. ^{**} Test Configuration | <input checked="" type="checkbox"/> With Beltclip | <input type="checkbox"/> Without Beltclip | |
8. Tissue parameters and temperatures are listed on the SAR plots.
9. Both sides of the EUT were tested and the worst-case side is reported.
10. Liquid tissue depth is 15.1 cm. ± 0.1



Randy Ortanez
President

PCTEST SAR REPORT		FCC Class II Permissive Change		Reviewed by: Quality Manager
SAR Filename: 0606060463-R1	Test Dates: June 13-15, 2006	Phone Type: Handheld Computer with GSM, Bluetooth & WLAN Transceivers	FCC ID: AZ489FT7018	Page 33 of 37

SAR DATA SUMMARY (Continued)

Mixture Type: 2450MHz Head

14.16 MEASUREMENT RESULTS (IEEE 802.11b Face SAR)													
FREQUENCY		Modulation	Begin / End POWER [‡]			w/ SD Card	w/ BT	Separation Distance (cm) ^{**}	Data Bit Rate	Antenna Position	SAR W/kg	Drift	Cal SAR W/kg
MHz	Ch.		(dBm)		Battery								
2437	06	DSSS	16.20	16.27	FNN7815A	-	-	2.5	11	Internal	0.0957	0.066	0.0943
2437	06	DSSS	16.20	16.41	FNN7815A	Yes	2441	2.5	11	Internal	0.0932	0.210	0.0888
2437	06	DSSS	16.20	16.37	FNN7826A	-	-	2.5	11	Internal	0.0957	0.168	0.0921
ANSI / IEEE C95.1 1992 - SAFETY LIMIT						Head							
Spatial Peak						1.6 W/kg (mW/g)							
Uncontrolled Exposure/General Population						averaged over 1 gram							

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
2. All modes of operation were investigated including all data bit rates, and worst-case results are reported.
3. Battery is fully charged for all readings.
4. [‡]Power Measured

<input checked="" type="checkbox"/> Conducted	<input type="checkbox"/> ERP	<input type="checkbox"/> EIRP
<input checked="" type="checkbox"/> DASY4	<input type="checkbox"/> IDX	
5. SAR Measurement System Phantom Configuration

<input type="checkbox"/> Left Head	<input checked="" type="checkbox"/> Flat Phantom	<input type="checkbox"/> Right Head
<input type="checkbox"/> Head	<input type="checkbox"/> Body	<input checked="" type="checkbox"/> Face
6. SAR Configuration
7. Test Signal Call Mode

<input checked="" type="checkbox"/> Manu. Test Codes	<input type="checkbox"/> Base Station Simulator
--	---
8. ^{**}Test Configuration

<input type="checkbox"/> With Holster	<input checked="" type="checkbox"/> Without Holster
---------------------------------------	---
9. Tissue parameters and temperatures are listed on the SAR plots.
10. Both sides of the EUT were tested and the worst-case side is reported.
11. Liquid tissue depth is 15.1 cm. ± 0.1



Randy Ortance
President

PCTEST SAR REPORT		FCC Class II Permissive Change		Reviewed by: Quality Manager
SAR Filename: 0606060463-R1	Test Dates: June 13-15, 2006	Phone Type: Handheld Computer with GSM, Bluetooth & WLAN Transceivers	FCC ID: AZ489FT7018	Page 34 of 37

15. SAR TEST EQUIPMENT

Equipment Calibration

Type	Calibration Date	Serial Number
Staubli Robot RX60L	N/A	599131-01
Staubli Robot Controller	N/A	PCT592
Staubli Teach Pendant (Joystick)	N/A	3323-00161
Micron Computer, 450 MHz Pentium III, Windows NT	N/A	PCT577
SPEAG EDC3	N/A	321
SPEAG DAE4	Aug-06	665
SPEAG E-Field Probe EX3DV4	Aug-06	3561
SPEAG SAM Twin Phantom V4.0 (Main)	N/A	TP:1197
SPEAG SAM Twin Phantom V4.0 (Sub)	N/A	TP:1357
SPEAG Light Alignment Sensor	N/A	205
SPEAG Validation Dipole D835V2	Feb-07	4d026
SPEAG Validation Dipole D1900V2	Feb-07	502
SPEAG Validation Dipole D2450V2	Feb-07	719
Gigatronics 8651A Power Meter	Jan-07	1835299
HP-8648D (9kHz ~ 4GHz) Signal Generator	Jan-07	PCT530
Amplifier Research 5S1G4 Power Amp	N/A	PCT540
HP-8753E (30kHz ~ 6GHz) Network Analyzer	Jun-05	PCT552/ JP8020182
HP85070B Dielectric Probe Kit	N/A	PCT501
Ambient Noise/Reflection, etc. <12mW/kg/<3%of SAR	N/A	Anechoic Room PCT01

Table 15.1 Test Equipment Calibration

NOTE:

The E-field probe was calibrated by SPEAG, by waveguide technique procedure. Dipole Validation measurement is performed by PCTEST Lab. before each test. The Head simulating material is calibrated by PCTEST using the dielectric probe system and network analyzer to determine the conductivity and permittivity (dielectric constant) of the Head-equivalent material.

PCTEST SAR REPORT		FCC Class II Permissive Change		Reviewed by: Quality Manager
SAR Filename: 0606060463-R1	Test Dates: June 13-15, 2006	Phone Type: Handheld Computer with GSM, Bluetooth & WLAN Transceivers	FCC ID: AZ489FT7018	Page 35 of 37

16. CONCLUSION

Measurement Conclusion

The SAR measurement indicates that the EUT complies with the RF radiation exposure limits of the FCC. These measurements are taken to simulate the RF effects exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The tested device complies with the requirements in respect to all parameters subject to the test. The test results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because innumerable factors may interact to determine the specific biological outcome of an exposure to electromagnetic fields, any protection guide shall consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables.[3]

PCTEST SAR REPORT		FCC Class II Permissive Change		Reviewed by: Quality Manager
SAR Filename: 0606060463-R1	Test Dates: June 13-15, 2006	Phone Type: Handheld Computer with GSM, Bluetooth & WLAN Transceivers	FCC ID: AZ489FT7018	Page 36 of 37

17. REFERENCES

[1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.

[2] ANSI/IEEE C95.1 - 1991, *American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 300kHz to 100GHz*, New York: IEEE, Aug. 1992.

[3] ANSI/IEEE C95.3 - 1991, *IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave*, New York: IEEE, 1992.

[4] Federal Communications Commission, OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01), *Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields*, July 2001.

[5] IEEE Standards Coordinating Committee 34 – IEEE Std. 1528 – 2003, *Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices*.

[6] NCRP, National Council on Radiation Protection and Measurements, *Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields*, NCRP Report No. 86, 1986. Reprinted Feb. 1995.

[7] T. Schmid, O. Egger, N. Kuster, *Automated E-field scanning system for dosimetric assessments*, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.

[8] K. Pokovic, T. Schmid, N. Kuster, *Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies*, ICECOM97, Oct. 1997, pp. 120-124.

[9] K. Poković, T. Schmid, and N. Kuster, *E-field Probe with improved isotropy in Head simulating liquids*, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.

[10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.

[11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, *The Dependence of EM Energy Absorption upon Human Head Modeling at 900 MHz*, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.

[12] N. Kuster and Q. Balzano, *Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz*, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.

[13] G. Hartsgrove, A. Kraszewski, A. Surowiec, *Simulated Biological Materials for Electromagnetic Radiation Absorption Studies*, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.

[14] Q. Balzano, O. Garay, T. Manning Jr., *Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones*, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.

[15] W. Gander, *Computermathematick*, Birkhaeuser, Basel, 1992.

[16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, *Numerical Recipes in C, The Art of Scientific Computing*, Second edition, Cambridge University Press, 1992.

[17] Federal Communications Commission, OET Bulletin 65, Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields. Supplement C, Dec. 1997.

[18] N. Kuster, R. Kastle, T. Schmid, *Dosimetric evaluation of mobile communications equipment with known precision*, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.

[19] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), *Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz*, Jan. 1995.

[20] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, *Dosimetric Evaluation of the Cellular Phone*.

PCTEST SAR REPORT		FCC Class II Permissive Change		Reviewed by: Quality Manager
SAR Filename: 0606060463-R1	Test Dates: June 13-15, 2006	Phone Type: Handheld Computer with GSM, Bluetooth & WLAN Transceivers	FCC ID: AZ489FT7018	Page 37 of 37

APPENDIX A: SAR TEST DATA

PCTEST ENGINEERING LABORATORY, INC.

DUT: F3133A; Type: GSM Dual Band w/ WLAN & BT; SN: 629SGJ3203; Conducted Power: 32.2dBm

Communication System: GSM850 Motorola; Frequency: 836.6 MHz; Duty Cycle: 1:8

Medium: 835 Brain ($\sigma = 0.88$ mho/m, $\epsilon_r = 41.67$, $\rho = 1000$ kg/m³)

Phantom section: Right Section

Test Date: 06-13-2006; Ambient Temp: 23.2°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3561; ConvF(7.91, 7.91, 7.91); Calibrated: 8/24/2005

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 9/13/2005

Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197

Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 160

Mode: GSM850, Touch, Mid ch, FNN7815A Battery, Antenna Internal


Area Scan (9x17x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.21 V/m; Power Drift = 0.220 dB

Peak SAR (extrapolated) = 0.101 W/kg

SAR(1 g) = 0.071 mW/g; SAR(10 g) = 0.049 mW/g



0 dB = 0.081mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: F3133A; Type: GSM Dual Band w/ WLAN & BT; SN: 629SGJ3203; Conducted Power: 32.2dBm

Communication System: GSM850 Motorola; Frequency: 836.6 MHz; Duty Cycle: 1:8

Medium: 835 Brain ($\sigma = 0.88$ mho/m, $\epsilon_r = 41.67$, $\rho = 1000$ kg/m³)

Phantom section: Right Section

Test Date: 06-13-2006; Ambient Temp: 23.2°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3561; ConvF(7.91, 7.91, 7.91); Calibrated: 8/24/2005

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 9/13/2005

Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197

Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 160

Mode: GSM850, Tilt, Mid ch, FNN7815A Battery, Antenna Internal


Area Scan (9x17x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.25 V/m; Power Drift = 0.214 dB

Peak SAR (extrapolated) = 0.068 W/kg

SAR(1 g) = 0.049 mW/g; SAR(10 g) = 0.034 mW/g



0 dB = 0.055mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: F3133A; Type: GSM Dual Band w/ WLAN & BT; SN: 629SGJ3203; Conducted Power: 32.2dBm

Communication System: GSM850 Motorola; Frequency: 836.6 MHz; Duty Cycle: 1:8

Medium: 835 Brain ($\sigma = 0.88$ mho/m, $\epsilon_r = 41.67$, $\rho = 1000$ kg/m³)

Phantom section: Left Section

Test Date: 06-13-2006; Ambient Temp: 23.2°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3561; ConvF(7.91, 7.91, 7.91); Calibrated: 8/24/2005

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 9/13/2005

Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197

Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 160

Mode: GSM850, Touch, Mid ch, FNN7826A Battery, Antenna Internal


Area Scan (9x17x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.54 V/m; Power Drift = 0.066 dB

Peak SAR (extrapolated) = 0.077 W/kg

SAR(1 g) = 0.052 mW/g; SAR(10 g) = 0.038 mW/g



0 dB = 0.061mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: F3133A; Type: GSM Dual Band w/ WLAN & BT; SN: 629SGJ3203; Conducted Power: 32.2dBm

Communication System: GSM850 Motorola; Frequency: 836.6 MHz; Duty Cycle: 1:8

Medium: 835 Brain ($\sigma = 0.88$ mho/m, $\epsilon_r = 41.67$, $\rho = 1000$ kg/m³)

Phantom section: Left Section

Test Date: 06-13-2006; Ambient Temp: 23.2°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3561; ConvF(7.91, 7.91, 7.91); Calibrated: 8/24/2005

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 9/13/2005

Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197

Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 160

Mode: GSM850, Tilt, Mid ch, FNN7815A Battery, Antenna Internal


Area Scan (9x17x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.63 V/m; Power Drift = 0.241 dB

Peak SAR (extrapolated) = 0.062 W/kg

SAR(1 g) = 0.044 mW/g; SAR(10 g) = 0.031 mW/g



0 dB = 0.049mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: F3133A; Type: GSM Dual Band w/ WLAN & BT; SN: 629SGJ3203; Conducted Power: 29.2dBm

Communication System: GSM1900 Motorola; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium: 1900 Brain ($\sigma = 1.37$ mho/m, $\epsilon_r = 41.43$, $\rho = 1000$ kg/m³)

Phantom section: Right Section

Test Date: 06-14-2006; Ambient Temp: 23.5°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN3561; ConvF(7.04, 7.04, 7.04); Calibrated: 8/24/2005

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 9/13/2005

Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197

Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 160

Mode: GSM1900, Touch, Mid ch, FNN7826A Battery, Antenna Internal


Area Scan (9x16x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.18 V/m; Power Drift = 0.126 dB

Peak SAR (extrapolated) = 0.166 W/kg

SAR(1 g) = 0.136 mW/g; SAR(10 g) = 0.103 mW/g



0 dB = 0.151mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: F3133A; Type: GSM Dual Band w/ WLAN & BT; SN: 629SGJ3203; Conducted Power: 29.2dBm

Communication System: GSM1900 Motorola; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium: 1900 Brain ($\sigma = 1.37$ mho/m, $\epsilon_r = 41.43$, $\rho = 1000$ kg/m³)

Phantom section: Right Section

Test Date: 06-14-2006; Ambient Temp: 23.5°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN3561; ConvF(7.04, 7.04, 7.04); Calibrated: 8/24/2005

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 9/13/2005

Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197

Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 160

Mode: GSM1900, Tilt, Mid ch, FNN7815A Battery, Antenna Internal


Area Scan (9x17x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.80 V/m; Power Drift = 0.214 dB

Peak SAR (extrapolated) = 0.142 W/kg

SAR(1 g) = 0.117 mW/g; SAR(10 g) = 0.089 mW/g



0 dB = 0.129mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: F3133A; Type: GSM Dual Band w/ WLAN & BT; SN: 629SGJ3203; Conducted Power: 29.2dBm

Communication System: GSM1900 Motorola; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium: 1900 Brain ($\sigma = 1.37$ mho/m, $\epsilon_r = 41.43$, $\rho = 1000$ kg/m³)

Phantom section: Left Section

Test Date: 06-14-2006; Ambient Temp: 23.5°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN3561; ConvF(7.04, 7.04, 7.04); Calibrated: 8/24/2005

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 9/13/2005

Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197

Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 160

Mode: GSM1900, Touch, Mid ch, FNN7826A Battery, Antenna Internal


Area Scan (9x17x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.23 V/m; Power Drift = 0.125 dB

Peak SAR (extrapolated) = 0.150 W/kg

SAR(1 g) = 0.096 mW/g; SAR(10 g) = 0.058 mW/g



0 dB = 0.116mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: F3133A; Type: GSM Dual Band w/ WLAN & BT; SN: 629SGJ3203; Conducted Power: 29.2dBm

Communication System: GSM1900 Motorola; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium: 1900 Brain ($\sigma = 1.37$ mho/m, $\epsilon_r = 41.43$, $\rho = 1000$ kg/m³)

Phantom section: Left Section

Test Date: 06-14-2006; Ambient Temp: 23.5°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN3561; ConvF(7.04, 7.04, 7.04); Calibrated: 8/24/2005

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 9/13/2005

Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197

Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 160

Mode: GSM1900, Tilt, Mid ch, FNN7815A Battery, Antenna Internal


Area Scan (9x17x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.32 V/m; Power Drift = 0.195 dB

Peak SAR (extrapolated) = 0.106 W/kg

SAR(1 g) = 0.070 mW/g; SAR(10 g) = 0.044 mW/g



0 dB = 0.081mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: F3133A; Type: GSM Dual Band w/ WLAN & BT; SN: 629SGJ3203; Conducted Power: 32.2dBm

Communication System: GSM850 Motorola; Frequency: 836.6 MHz; Duty Cycle: 1:8

Medium: 835 Muscle ($\sigma = 0.98$ mho/m, $\epsilon_r = 53.98$, $\rho = 1000$ kg/m³)

Phantom section: Flat Section; Space: 1.8 cm; Tested with Belt-clip

Test Date: 06-15-2006; Ambient Temp: 23.6°C; Tissue Temp: 21.9°C

Probe: EX3DV4 - SN3561; ConvF(7.9, 7.9, 7.9); Calibrated: 8/24/2005

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 9/13/2005

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP:1357

Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 160

Mode: GSM850, Body w/ Beltclip, Mid.ch, FNN7815A Battery, Back, Antenna Interna


Area Scan (9x17x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 25.5 V/m; Power Drift = 0.138 dB

Peak SAR (extrapolated) = 0.830 W/kg

SAR(1 g) = 0.622 mW/g; SAR(10 g) = 0.439 mW/g



0 dB = 0.688mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: F3133A; Type: GSM Dual Band w/ WLAN & BT; SN: 629SGJ3203; Conducted Power: 32.2dBm

Communication System: GSM850 Motorola; Frequency: 836.6 MHz; Duty Cycle: 1:8

Medium: 835Brain ($\sigma = 0.88$ mho/m, $\epsilon_r = 41.67$, $\rho = 1000$ kg/m³)

Phantom section: Flat Section; Space: 2.5 cm

Test Date: 06-14-2006; Ambient Temp: 23.5°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN3561; ConvF(7.9, 7.9, 7.9); Calibrated: 8/24/2005

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 9/13/2005

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP:1357

Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 160

Mode: GSM850, Face, 2.5cm space, Mid.ch, FNN7826A Battery, Antenna Internal


Area Scan (9x17x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.62 V/m; Power Drift = 0.202 dB

Peak SAR (extrapolated) = 0.038 W/kg

SAR(1 g) = 0.030 mW/g; SAR(10 g) = 0.024 mW/g



0 dB = 0.033mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: F3133A; Type: GSM Dual Band w/ WLAN & BT; SN: 629SGJ3203; Conducted Power: 29.2dBm

Communication System: GSM1900 Motorola; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium: 1900 Muscle ($\sigma = 1.58$ mho/m, $\epsilon_r = 52.61$, $\rho = 1000$ kg/m³)

Phantom section: Flat Section; Space: 1.8 cm; Tested with Belt-clip

Test Date: 06-15-2006; Ambient Temp: 23.6°C; Tissue Temp: 21.9°C

Probe: EX3DV4 - SN3561; ConvF(6.48, 6.48, 6.48); Calibrated: 8/24/2005

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 9/13/2005

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP:1357

Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 160

Mode: GSM1900, Body w/ Beltclip, Mid.ch, FNN7826A Battery, Back, Antenna Internal


Area Scan (9x17x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.0 V/m; Power Drift = -0.128 dB

Peak SAR (extrapolated) = 0.551 W/kg

SAR(1 g) = 0.317 mW/g; SAR(10 g) = 0.177 mW/g



0 dB = 0.386mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: F3133A; Type: GSM Dual Band w/ WLAN & BT; SN: 629SGJ3203; Conducted Power: 29.2dBm

Communication System: GSM1900 Motorola; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium: 1900 Brain ($\sigma = 1.37$ mho/m, $\epsilon_r = 41.43$, $\rho = 1000$ kg/m³)

Phantom section: Flat Section; Space: 2.5 cm

Test Date: 06-15-2006; Ambient Temp: 23.6°C; Tissue Temp: 21.9°C

Probe: EX3DV4 - SN3561; ConvF(6.48, 6.48, 6.48); Calibrated: 8/24/2005

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 9/13/2005

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP:1357

Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 160

Mode: GSM1900, Face, 2.5cm space, Mid.ch, FNN7815A Battery, Antenna Internal w/BT and SD card


Area Scan (9x17x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.05 V/m; Power Drift = -0.053 dB

Peak SAR (extrapolated) = 0.027 W/kg

SAR(1 g) = 0.018 mW/g; SAR(10 g) = 0.012 mW/g



0 dB = 0.021mW/g