

APPENDIX A: SAR TEST DATA

PCTEST ENGINEERING LABORATORY, INC.

**DUT: Motorola F4708A; Type: GSM Dual Band w/ WLAN + Bluetooth Handheld Computer
SN: 629SHA4506; Conducted Power: 32.86 dBm**

Communication System: GSM850 Motorola; Frequency: 836.6 MHz; Duty Cycle: 1:8

Medium: 835 Brain ($\sigma = 0.90$ mho/m, $\epsilon_r = 40.91$, $\rho = 1000$ kg/m³)

Phantom section: Right Section

Test Date: 02-14-2007; Ambient Temp: 22.8°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3561; ConvF(7.94, 7.94, 7.94); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Right Touch, Mid ch, Battery FNN7826A, Antenna Internal


Area Scan (9x17x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.01 V/m; Power Drift = -0.088 dB

Peak SAR (extrapolated) = 0.105 W/kg

SAR(1 g) = 0.075 mW/g; SAR(10 g) = 0.051 mW/g



0 dB = 0.086mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: Motorola F4708A; Type: GSM Dual Band w/ WLAN + Bluetooth Handheld Computer
SN: 629SHA4506; Conducted Power: 32.86 dBm

Communication System: GSM850 Motorola; Frequency: 836.6 MHz; Duty Cycle: 1:8

Medium: 835 Brain ($\sigma = 0.90$ mho/m, $\epsilon_r = 40.91$, $\rho = 1000$ kg/m³)

Phantom section: Right Section

Test Date: 02-14-2007; Ambient Temp: 22.8°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3561; ConvF(7.94, 7.94, 7.94); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Right Tilt, Mid ch, Battery FNN7826A, Antenna Internal


Area Scan (9x17x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.19 V/m; Power Drift = 0.004 dB

Peak SAR (extrapolated) = 0.087 W/kg

SAR(1 g) = 0.061 mW/g; SAR(10 g) = 0.042 mW/g



0 dB = 0.070mW/g

PCTEST ENGINEERING LABORATORY, INC.

**DUT: Motorola F4708A; Type: GSM Dual Band w/ WLAN + Bluetooth Handheld Computer
SN: 629SHA4506; Conducted Power: 32.86 dBm**

Communication System: GSM850 Motorola; Frequency: 836.6 MHz; Duty Cycle: 1:8

Medium: 835 Brain ($\sigma = 0.90$ mho/m, $\epsilon_r = 40.91$, $\rho = 1000$ kg/m³)

Phantom section: Left Section

Test Date: 02-14-2007; Ambient Temp: 22.8°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3561; ConvF(7.94, 7.94, 7.94); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Left Touch, Mid ch, Battery FNN7826A, Antenna Internal


Area Scan (9x17x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.47 V/m; Power Drift = 0.233 dB

Peak SAR (extrapolated) = 0.093 W/kg

SAR(1 g) = 0.067 mW/g; SAR(10 g) = 0.049 mW/g



0 dB = 0.077mW/g

PCTEST ENGINEERING LABORATORY, INC.

**DUT: Motorola F4708A; Type: GSM Dual Band w/ WLAN + Bluetooth Handheld Computer
SN:629SHA4506; Conducted Power: 32.86 dBm**

Communication System: GSM850 Motorola; Frequency: 836.6 MHz; Duty Cycle: 1:8

Medium: 835 Brain ($\sigma = 0.90$ mho/m, $\epsilon_r = 40.91$, $\rho = 1000$ kg/m³)

Phantom section: Left Section

Test Date: 02-14-2007; Ambient Temp: 22.8°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3561; ConvF(7.94, 7.94, 7.94); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Left Tilt, Mid ch, Battery FNN7826A, Antenna Internal


Area Scan (9x17x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.56 V/m; Power Drift = 0.126 dB

Peak SAR (extrapolated) = 0.077 W/kg

SAR(1 g) = 0.056 mW/g; SAR(10 g) = 0.039 mW/g



0 dB = 0.063mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: Motorola F4708A; Type: GSM Dual Band w/ WLAN + Bluetooth Handheld Computer
SN: 629SHA4506; Conducted Power: 29.54 dBm

Communication System: GSM1900 Motorola; Frequency: 1880 MHz; Duty Cycle: 1:8
Medium: 1900 Brain ($\sigma = 1.42$ mho/m, $\epsilon_r = 39.23$, $\rho = 1000$ kg/m³)
Phantom section: Right Section

Test Date: 02-15-2007; Ambient Temp: 23.2°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN3561; ConvF(6.99, 6.99, 6.99); Calibrated: 11/23/2006
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn649; Calibrated: 1/23/2007
Phantom: SAM Sub; Type: SAM 4.0; Serial: TP:1357

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Right Touch, Mid ch, Battery FNN7826A, Antenna Internal


Area Scan (9x17x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.70 V/m; Power Drift = -0.010 dB

Peak SAR (extrapolated) = 0.251 W/kg

SAR(1 g) = 0.140 mW/g; SAR(10 g) = 0.083 mW/g



0 dB = 0.175mW/g

PCTEST ENGINEERING LABORATORY, INC.

**DUT: Motorola F4708A; Type: GSM Dual Band w/ WLAN + Bluetooth Handheld Computer
SN: 629SHA4506; Conducted Power: 29.54 dBm**

Communication System: GSM1900 Motorola; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium: 1900 Brain ($\sigma = 1.42$ mho/m, $\epsilon_r = 39.23$, $\rho = 1000$ kg/m³)

Phantom section: Right Section

Test Date: 02-15-2007; Ambient Temp: 23.2°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN3561; ConvF(6.99, 6.99, 6.99); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP:1357

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Right Tilt, Mid ch, Battery FNN7826A , Antenna Internal


Area Scan (9x17x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.37 V/m; Power Drift = 0.063 dB

Peak SAR (extrapolated) = 0.231 W/kg

SAR(1 g) = 0.133 mW/g; SAR(10 g) = 0.080 mW/g



0 dB = 0.163mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: Motorola F4708A; Type: GSM Dual Band w/ WLAN + Bluetooth Handheld Computer
SN: 629SHA4506; Conducted Power: 29.54 dBm


Communication System: GSM1900 Motorola; Frequency: 1880 MHz; Duty Cycle: 1:8
Medium: 1900 Brain ($\sigma = 1.42$ mho/m, $\epsilon_r = 39.23$, $\rho = 1000$ kg/m³)
Phantom section: Left Section

Test Date: 02-15-2007; Ambient Temp: 23.2°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN3561; ConvF(6.99, 6.99, 6.99); Calibrated: 11/23/2006
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn649; Calibrated: 1/23/2007
Phantom: SAM Sub; Type: SAM 4.0; Serial: TP:1357
Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Left Touch, Mid ch, Battery FNN7826A, Antenna Internal

Area Scan (9x17x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 9.57 V/m; Power Drift = -0.083 dB
Peak SAR (extrapolated) = 0.316 W/kg
SAR(1 g) = 0.193 mW/g; SAR(10 g) = 0.113 mW/g



0 dB = 0.234mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: Motorola F4708A; Type: GSM Dual Band w/ WLAN + Bluetooth Handheld Computer
SN: 629SHA4506; Conducted Power: 29.54 dBm

Communication System: GSM1900 Motorola; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium: 1900 Brain ($\sigma = 1.42 \text{ mho/m}$, $\epsilon_r = 39.23$, $\rho = 1000 \text{ kg/m}^3$)

Phantom section: Left Section

Test Date: 02-15-2007; Ambient Temp: 23.2°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN3561; ConvF(6.99, 6.99, 6.99); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP:1357

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Left Tilt, Mid ch, Battery FNN7826A, Antenna Internal


Area Scan (9x17x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.51 V/m; Power Drift = 0.058 dB

Peak SAR (extrapolated) = 0.207 W/kg

SAR(1 g) = 0.131 mW/g; SAR(10 g) = 0.080 mW/g



0 dB = 0.156mW/g

PCTEST ENGINEERING LABORATORY, INC.

**DUT: Motorola F4708A; Type: GSM Dual Band w/ WLAN + Bluetooth Handheld Computer
SN: 629SHA4506; Conducted Power: 32.86 dBm**

Communication System: GSM850 GPRS; 2 Tx slots; Frequency: 836.6 MHz; Duty Cycle: 1:4.15

Medium: 835 Muscle ($\sigma = 0.97$ mho/m, $\epsilon_r = 53.81$, $\rho = 1000$ kg/m³)

Phantom section: Flat Section; Space: 2.5 cm from DUT to Flat Phantom

Test Date: 02-14-2007; Ambient Temp: 23.0°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN3561; ConvF(7.92, 7.92, 7.92); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Body, No Holster, Mid.ch, Battery FNN7826A, Antenna Internal


Area Scan (9x17x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.92 V/m; Power Drift = -0.124 dB

Peak SAR (extrapolated) = 0.207 W/kg

SAR(1 g) = 0.155 mW/g; SAR(10 g) = 0.111 mW/g



0 dB = 0.174mW/g

PCTEST ENGINEERING LABORATORY, INC.

**DUT: Motorola F4708A; Type: GSM Dual Band w/ WLAN + Bluetooth Handheld Computer
SN: 629SHA4506 Conducted Power: 32.86 dBm**

Communication System: GSM850 Motorola; Frequency: 836.6 MHz; Duty Cycle: 1:8

Medium: 835 Brain ($\sigma = 0.90$ mho/m, $\epsilon_r = 40.91$, $\rho = 1000$ kg/m³)

Phantom section: Flat Section; Space: 2.5cm from DUT to Flat Phantom

Test Date: 02-14-2007; Ambient Temp: 22.8°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3561; ConvF(7.94, 7.94, 7.94); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Face, Mid.ch, Battery FNN7826A, Antenna Internal


Area Scan (9x17x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.04 V/m; Power Drift = -0.231 dB

Peak SAR (extrapolated) = 0.056 W/kg

SAR(1 g) = 0.043 mW/g; SAR(10 g) = 0.032 mW/g



0 dB = 0.048mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: Motorola F4708A; Type: GSM Dual Band w/ WLAN + Bluetooth Handheld Computer
SN: 629SHA4506; Conducted Power: 29.54 dBm

Communication System: GSM1900 GPRS; 2 Tx slots; Frequency: 1880 MHz; Duty Cycle: 1:4.15

Medium: 1900 Muscle ($\sigma = 1.54$ mho/m, $\epsilon_r = 53.72$, $\rho = 1000$ kg/m³)

Phantom section: Flat Section; Space: 2.5 cm from DUT to Flat Phantom

Test Date: 02-15-2007; Ambient Temp: 22.9°C; Tissue Temp: 21.4°C

Probe: EX3DV4 - SN3561; ConvF(6.47, 6.47, 6.47); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Body, No Holster, Mid.ch, Battery FNN7826A, Antenna Internal


Area Scan (9x17x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.77 V/m; Power Drift = 0.149 dB

Peak SAR (extrapolated) = 0.698 W/kg

SAR(1 g) = 0.353 mW/g; SAR(10 g) = 0.164 mW/g



0 dB = 0.501mW/g

PCTEST ENGINEERING LABORATORY, INC.

**DUT: Motorola F4708A; Type: GSM Dual Band w/ WLAN + Bluetooth Handheld Computer
SN: 629SHA4506; Conducted Power: 29.54 dBm**

Communication System: GSM1900 Motorola; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium: 1900 Brain ($\sigma = 1.42$ mho/m, $\epsilon_r = 39.23$, $\rho = 1000$ kg/m³)

Phantom section: Flat Section: Space: 2.5cm from DUT to Flat Phantom

Test Date: 02-15-2007; Ambient Temp: 23.2°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN3561; ConvF(6.99, 6.99, 6.99); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP:1357

Measurement SW: DASYS4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Face, Mid.ch, Battery FNN7826A, Antenna Internal


Area Scan (9x17x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.80 V/m; Power Drift = 0.045 dB

Peak SAR (extrapolated) = 0.052 W/kg

SAR(1 g) = 0.032 mW/g; SAR(10 g) = 0.020 mW/g



0 dB = 0.039mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: Motorola F4708A; Type: GSM Dual Band w/WLAN + Bluetooth Handheld Computer
SN: 629SHA4506; Conducted Power: 3.01 dBm

Communication System: Bluetooth; Frequency: 2441 MHz; Duty Cycle: 1:1

Medium: 2450 Muscle ($\sigma = 1.91$ mho/m, $\epsilon_r = 52.23$, $\rho = 1000$ kg/m³)

Phantom section: Flat Section; Space: 2.5 cm from DUT to Flat Phantom

Test Date: 02-16-2007; Ambient Temp: 23.4°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3561; ConvF(6.33, 6.33, 6.33); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP:1357

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Body, No Holster, Mid.ch, Battery FNN7826A, Antenna Internal


Area Scan (9x17x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.23 V/m; Power Drift = -0.173 dB

Peak SAR (extrapolated) = 0.009 W/kg

SAR(1 g) = 0.00416 mW/g; SAR(10 g) = 0.00225 mW/g



0 dB = 0.006mW/g

PCTEST ENGINEERING LABORATORY, INC.

**DUT: Motorola F4708A; Type: GSM Dual Band w/WLAN + Bluetooth Handheld Computer
SN: 629SHA4506; Conducted Power: 3.01 dBm**

Communication System: Bluetooth; Frequency: 2441 MHz; Duty Cycle: 1:1
Medium: 2450 Brain ($\sigma = 1.82 \text{ mho/m}$, $\epsilon_r = 40.14$, $\rho = 1000 \text{ kg/m}^3$)
Phantom section: Flat Section; Space: 2.5cm from DUT to Flat Phantom

Test Date: 02-16-2007; Ambient Temp: 22.9°C; Tissue Temp: 20.8°C

Probe: EX3DV4 - SN3561; ConvF(6.32, 6.32, 6.32); Calibrated: 11/23/2006
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn649; Calibrated: 1/23/2007
Phantom: SAM Sub; Type: SAM 4.0; Serial: TP:1357

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Face, Mid.ch, Battery FNN7826A , Antenna Internal


Area Scan (9x17x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 0.803 V/m; Power Drift = 0.149 dB

Peak SAR (extrapolated) = 0.008 W/kg

SAR(1 g) = 0.00338 mW/g; SAR(10 g) = 0.00253 mW/g



0 dB = 0.010mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: Motorola F4708A; Type: GSM Dual Band w/ WLAN + Bluetooth Handheld Computer
SN: 629SHA4506; Conducted Power: 15.94 dBm


Communication System: IEEE 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1
Medium: 2450 Muscle ($\sigma = 1.91$ mho/m, $\epsilon_r = 52.23$, $\rho = 1000$ kg/m³)
Phantom section: Flat Section

Test Date: 02-16-2007; Ambient Temp: 23.4°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3561; ConvF(6.33, 6.33, 6.33); Calibrated: 11/23/2006
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn649; Calibrated: 1/23/2007
Phantom: SAM Sub; Type: SAM 4.0; Serial: TP:1357
Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Body w/ Holster, Mid.ch, Battery FNN7826A, Antenna Internal, 1Mbps

Area Scan (9x17x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 2.93 V/m; Power Drift = 0.032 dB
Peak SAR (extrapolated) = 0.110 W/kg
SAR(1 g) = 0.072 mW/g; SAR(10 g) = 0.036 mW/g



0 dB = 0.093mW/g

PCTEST ENGINEERING LABORATORY, INC.

**DUT: Motorola F4708A; Type: GSM Dual Band w/ WLAN + Bluetooth Handheld Computer
SN: 629SHA4506; Conducted Power: 15.94 dBm**

Communication System: IEEE 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: 2450 Brain ($\sigma = 1.82$ mho/m, $\epsilon_r = 40.14$, $\rho = 1000$ kg/m³)

Phantom section: Flat Section; Space: 2.5cm from DUT to Flat Phantom

Test Date: 02-16-2007; Ambient Temp: 22.9°C; Tissue Temp: 20.8°C

Probe: EX3DV4 - SN3561; ConvF(6.32, 6.32, 6.32); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP:1357

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Face, Mid.ch, Battery FNN7826A, Antenna Internal, 1Mbps


Area Scan (9x17x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.52 V/m; Power Drift = 0.176 dB

Peak SAR (extrapolated) = 0.100 W/kg

SAR(1 g) = 0.057 mW/g; SAR(10 g) = 0.034 mW/g



0 dB = 0.069mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: Motorola F4708A; Type: GSM Dual Band w/ WLAN + Bluetooth Handheld Computer
SN: 629SHA4506; Conducted Power: 32.86 dBm


Communication System: GSM850 Motorola; Frequency: 836.6 MHz; Duty Cycle: 1:8
Medium: 835 Brain ($\sigma = 0.90$ mho/m, $\epsilon_r = 40.91$, $\rho = 1000$ kg/m³)
Phantom section: Right Section

Test Date: 02-14-2007; Ambient Temp: 22.8°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3561; ConvF(7.94, 7.94, 7.94); Calibrated: 11/23/2006
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn649; Calibrated: 1/23/2007
Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197
Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Right Touch, Mid ch, Battery FNN7826A, Antenna Internal

Area Scan (9x17x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 8.01 V/m; Power Drift = -0.088 dB
Peak SAR (extrapolated) = 0.105 W/kg
SAR(1 g) = 0.075 mW/g; SAR(10 g) = 0.051 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: Motorola F4708A; Type: GSM Dual Band w/ WLAN + Bluetooth Handheld Computer
SN: 629SHA4506; Conducted Power: 32.86 dBm**

Communication System: GSM850 GPRS; 2 Tx slots; Frequency: 836.6 MHz; Duty Cycle: 1:4.15

Medium: 835 Muscle ($\sigma = 0.97$ mho/m, $\epsilon_r = 53.81$, $\rho = 1000$ kg/m³)

Phantom section: Flat Section; Space: 2.5 cm from DUT to Flat Phantom

Test Date: 02-14-2007; Ambient Temp: 23.0°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN3561; ConvF(7.92, 7.92, 7.92); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Body, No Holster, Mid.ch, Battery FNN7826A, Antenna Internal


Area Scan (9x17x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.92 V/m; Power Drift = -0.124 dB

Peak SAR (extrapolated) = 0.207 W/kg

SAR(1 g) = 0.155 mW/g; SAR(10 g) = 0.111 mW/g



PCTEST ENGINEERING LABORATORY, INC.

DUT: Motorola F4708A; Type: GSM Dual Band w/ WLAN + Bluetooth Handheld Computer
SN: 629SHA4506; Conducted Power: 29.54 dBm

Communication System: GSM1900 Motorola; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium: 1900 Brain ($\sigma = 1.42$ mho/m, $\epsilon_r = 39.23$, $\rho = 1000$ kg/m³)

Phantom section: Left Section

Test Date: 02-15-2007; Ambient Temp: 23.2°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN3561; ConvF(6.99, 6.99, 6.99); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP:1357

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Left Touch, Mid ch, Battery FNN7826A, Antenna Internal


Area Scan (9x17x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.57 V/m; Power Drift = -0.083 dB

Peak SAR (extrapolated) = 0.316 W/kg

SAR(1 g) = 0.193 mW/g; SAR(10 g) = 0.113 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: Motorola F4708A; Type: GSM Dual Band w/ WLAN + Bluetooth Handheld Computer
SN: 629SHA4506; Conducted Power: 29.54 dBm**

Communication System: GSM1900 GPRS; 2 Tx slots; Frequency: 1880 MHz; Duty Cycle: 1:4.15

Medium: 1900 Muscle ($\sigma = 1.54$ mho/m, $\epsilon_r = 53.72$, $\rho = 1000$ kg/m³)

Phantom section: Flat Section; Space: 2.5cm from DUT to Flat Phantom

Test Date: 02-15-2007; Ambient Temp: 22.9°C; Tissue Temp: 21.4°C

Probe: EX3DV4 - SN3561; ConvF(6.47, 6.47, 6.47); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Body, No Holster, Mid.ch, Battery FNN7826A, Antenna Internal


Area Scan (9x17x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.77 V/m; Power Drift = 0.149 dB

Peak SAR (extrapolated) = 0.698 W/kg

SAR(1 g) = 0.353 mW/g; SAR(10 g) = 0.164 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: Motorola F4708A; Type: GSM Dual Band w/ WLAN + Bluetooth Handheld Computer
SN: 629SHA4506; Conducted Power: 15.94 dBm**

Communication System: IEEE 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: 2450 Brain ($\sigma = 1.82$ mho/m, $\epsilon_r = 40.14$, $\rho = 1000$ kg/m³)

Phantom section: Flat Section; Space: 2.5cm from DUT to Flat Phantom

Test Date: 02-16-2007; Ambient Temp: 22.9°C; Tissue Temp: 20.8°C

Probe: EX3DV4 - SN3561; ConvF(6.32, 6.32, 6.32); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP:1357

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Face, Mid.ch, Battery FNN7826A, Antenna Internal, 1Mbps


Area Scan (9x17x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.52 V/m; Power Drift = 0.176 dB

Peak SAR (extrapolated) = 0.100 W/kg

SAR(1 g) = 0.057 mW/g; SAR(10 g) = 0.034 mW/g



PCTEST ENGINEERING LABORATORY, INC.

DUT: Motorola F4708A; Type: GSM Dual Band w/ WLAN + Bluetooth Handheld Computer
SN: 629SHA4506; Conducted Power: 15.94 dBm


Communication System: IEEE 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1
Medium: 2450 Muscle ($\sigma = 1.91$ mho/m, $\epsilon_r = 52.23$, $\rho = 1000$ kg/m³)
Phantom section: Flat Section

Test Date: 02-16-2007; Ambient Temp: 23.4°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3561; ConvF(6.33, 6.33, 6.33); Calibrated: 11/23/2006
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn649; Calibrated: 1/23/2007
Phantom: SAM Sub; Type: SAM 4.0; Serial: TP:1357
Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Body, w/ Holster, Mid.ch, Battery FNN7826A, Antenna Internal, 1Mbps

Area Scan (9x17x1): Measurement grid: dx=15mm, dy=15mm
Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 2.93 V/m; Power Drift = 0.032 dB
Peak SAR (extrapolated) = 0.110 W/kg
SAR(1 g) = 0.072 mW/g; SAR(10 g) = 0.036 mW/g



APPENDIX B: DIPOLE VALIDATION

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d026

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Brain ($\sigma = 0.90$ mho/m, $\epsilon_r = 40.91$, $\rho = 1000$ kg/m³)

Phantom section: Flat Section

Test Date: 02-14-2007; Ambient Temp: 22.8°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3561; ConvF(7.94, 7.94, 7.94); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Main; Type: SAM 4.0; Serial: TP:1197

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

835MHz Dipole Validation


Area Scan (7x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power = 24.0 dBm (250 mW)

SAR(1 g) = 2.33 mW/g; SAR(10 g) = 1.57 mW/g

Target SAR(1g) = 2.25 mW/g; Deviation = + 3.55 %



0 dB = 2.68mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 502

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Brain ($\sigma = 1.42$ mho/m, $\epsilon_r = 39.23$, $\rho = 1000$ kg/m³)

Phantom section: Flat Section

Test Date: 02-15-2007; Ambient Temp: 23.2°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN3561; ConvF(6.99, 6.99, 6.99); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP:1357

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

1900MHz Dipole Validation


Area Scan (5x7x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power = 20.0 dBm (100 mW)

SAR(1 g) = 3.94 mW/g; SAR(10 g) = 2.18 mW/g

Target SAR(1g) = 3.75 mW/g; Deviation = +5.06 %



0 dB = 4.97mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; SN:719

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Brain ($\sigma = 1.82$ mho/m, $\epsilon_r = 40.14$, $\rho = 1000$ kg/m³)

Phantom section: Flat Section

Test Date: 02-16-2007; Ambient Temp: 22.9°C; Tissue Temp: 20.8°C

Probe: EX3DV4 - SN3561; ConvF(6.32, 6.32, 6.32); Calibrated: 11/23/2006

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/23/2007

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP:1357

Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

2450MHz Dipole Validation


Area Scan (5x7x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power = 20.0 dBm (100 mW)

SAR(1 g) = 5.59 mW/g; SAR(10 g) = 2.73 mW/g

Target SAR(1g) = 5.40 mW/g; Deviation = +3.51 %



0 dB = 7.22mW/g

APPENDIX C: PROBE CALIBRATION



Accredited by the Swiss Federal Office of Metrology and Accreditation
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **PC Test**

Certificate No: **EX3-3561_Nov06**

CALIBRATION CERTIFICATE

Object **EX3DV4 - SN:3561**

Calibration procedure(s) **QA CAL-01.v5 and QA CAL-14.v3
Calibration procedure for dosimetric E-field probes**

Calibration date: **November 23, 2006**

Condition of the calibrated item **In Tolerance**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Calibrated by, Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	5-Apr-06 (METAS, No. 251-00557)	Apr-07
Power sensor E4412A	MY41495277	5-Apr-06 (METAS, No. 251-00557)	Apr-07
Power sensor E4412A	MY41498087	5-Apr-06 (METAS, No. 251-00557)	Apr-07
Reference 3 dB Attenuator	SN: S5054 (3c)	10-Aug-06 (METAS, No. 217-00592)	Aug-07
Reference 20 dB Attenuator	SN: S5086 (20b)	4-Apr-06 (METAS, No. 251-00558)	Apr-07
Reference 30 dB Attenuator	SN: S5129 (30b)	10-Aug-06 (METAS, No. 217-00593)	Aug-07
Reference Probe ES3DV2	SN: 3013	2-Jan-06 (SPEAG, No. ES3-3013_Jan06)	Jan-07
DAE4	SN: 654	21-Jun-06 (SPEAG, No. DAE4-654_Jun06)	Jun-07

Secondary Standards	ID #	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (SPEAG, in house check Nov-05)	In house check: Nov-07
Network Analyzer HP 8753E	US37390585	18-Oct-01 (SPEAG, in house check Oct-06)	In house check: Oct-07

	Name	Function	Signature
Calibrated by:	Katja Pokovic	Technical Manager	
Approved by:	Niels Kuster	Quality Manager	

Issued: November 23, 2006

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Federal Office of Metrology and Accreditation
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
Polarization φ	φ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- CENELEC EN 50361, "Basic standard for the measurement of Specific Absorption Rate related to human exposure to electromagnetic fields from mobile phones (300 MHz - 3 GHz), July 2001

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}**: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not effect the E²-field uncertainty inside TSL (see below *ConvF*).
- NORM(f)_{x,y,z}** = NORM_{x,y,z} * *frequency_response* (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of *ConvF*.
- DCP_{x,y,z}**: DCP are numerical linearization parameters assessed based on the data of power sweep (no uncertainty required). DCP does not depend on frequency nor media.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * *ConvF* whereby the uncertainty corresponds to that given for *ConvF*. A frequency dependent *ConvF* is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.

Probe EX3DV4

SN:3561

Manufactured:	February 14, 2005
Last calibrated:	August 24, 2005
Recalibrated:	November 23, 2006

Calibrated for DASYS Systems

(Note: non-compatible with DASYS2 system!)

DASY - Parameters of Probe: EX3DV4 SN:3561

Sensitivity in Free Space^A

NormX	0.450 ± 10.1%	$\mu\text{V}/(\text{V}/\text{m})^2$
NormY	0.490 ± 10.1%	$\mu\text{V}/(\text{V}/\text{m})^2$
NormZ	0.420 ± 10.1%	$\mu\text{V}/(\text{V}/\text{m})^2$

Diode Compression^B

DCP X	87 mV
DCP Y	91 mV
DCP Z	89 mV

Sensitivity in Tissue Simulating Liquid (Conversion Factors)

Please see Page 8.

Boundary Effect

TSL **900 MHz** **Typical SAR gradient: 5 % per mm**

Sensor Center to Phantom Surface Distance		2.0 mm	3.0 mm
SAR _{be} [%]	Without Correction Algorithm	3.8	1.5
SAR _{be} [%]	With Correction Algorithm	0.0	0.0

TSL **1810 MHz** **Typical SAR gradient: 10 % per mm**

Sensor Center to Phantom Surface Distance		2.0 mm	3.0 mm
SAR _{be} [%]	Without Correction Algorithm	4.7	2.8
SAR _{be} [%]	With Correction Algorithm	1.1	0.8

Sensor Offset

Probe Tip to Sensor Center **1.0 mm**


The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of NormX,Y,Z do not affect the E²-field uncertainty inside TSL (see Page 8).

^B Numerical linearization parameter: uncertainty not required.




Frequency Response of E-Field

(TEM-Cell:ifi1110 EXX, Waveguide: R22)




Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ ($k=2$)

Receiving Pattern (ϕ), $\vartheta = 0^\circ$





Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ ($k=2$)

Dynamic Range $f(\text{SAR}_{\text{head}})$ (Waveguide R22, $f = 1800 \text{ MHz}$)



Uncertainty of Linearity Assessment: $\pm 0.6\%$ ($k=2$)

Conversion Factor Assessment




f [MHz]	Validity [MHz] ^c	TSL	Permittivity	Conductivity	Alpha	Depth	ConvF Uncertainty
900	± 50 / ± 100	Head	41.5 ± 5%	0.97 ± 5%	0.35	1.30	7.94 ± 11.0% (k=2)
1810	± 50 / ± 100	Head	40.0 ± 5%	1.40 ± 5%	0.19	1.20	6.99 ± 11.0% (k=2)
2450	± 50 / ± 100	Head	39.2 ± 5%	1.80 ± 5%	0.44	1.00	6.32 ± 11.8% (k=2)
5200	± 50 / ± 100	Head	36.0 ± 5%	4.66 ± 5%	0.45	1.36	4.34 ± 13.1% (k=2)
5300	± 50 / ± 100	Head	35.9 ± 5%	4.76 ± 5%	0.45	1.40	4.23 ± 13.1% (k=2)
5800	± 50 / ± 100	Head	35.3 ± 5%	5.27 ± 5%	0.45	1.42	4.01 ± 13.1% (k=2)
900	± 50 / ± 100	Body	55.0 ± 5%	1.05 ± 5%	0.40	1.25	7.92 ± 11.0% (k=2)
1810	± 50 / ± 100	Body	53.3 ± 5%	1.52 ± 5%	0.21	1.20	6.47 ± 11.0% (k=2)
2450	± 50 / ± 100	Body	52.7 ± 5%	1.95 ± 5%	0.47	1.00	6.33 ± 11.8% (k=2)
5200	± 50 / ± 100	Body	49.0 ± 5%	5.30 ± 5%	0.40	1.50	3.89 ± 13.1% (k=2)
5300	± 50 / ± 100	Body	48.5 ± 5%	5.42 ± 5%	0.45	1.50	3.63 ± 13.1% (k=2)
5800	± 50 / ± 100	Body	48.2 ± 5%	6.00 ± 5%	0.45	1.70	3.59 ± 13.1% (k=2)

^c The validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2). The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

Deviation from Isotropy in HSL

Error (ϕ, ϑ), $f = 900$ MHz



Uncertainty of Spherical Isotropy Assessment: $\pm 2.6\%$ ($k=2$)