



Electromagnetic Compatibility Test Report

Test Report No: MOT 030208

Issued on: February 03, 2008

Product Name

VoWLAN SR

Tested According to

**FCC 47 CFR, Part 15, Subparts B
IC RSS-210**

Tests Performed for

Motorola Israel Ltd.

3, Kremenitski Street, Tel Aviv, Israel

Tel: (972) 03-5658888

QualiTech EMC Laboratory

30 Hasivim Street,

Petah-Tikva, 49517, Israel

Tel: 972-3-926 8443

Fax: 972-3-928 7490



Regis. No: 102724



1633.01

The information contained herein is the property of QualiTech, EMC Lab and is supplied without liability for errors or omissions.

*The copyright for this document vests in QualiTech, EMC Lab.
All rights reserved.*

This Test Report may not be reproduced, by any method, without the written permission of the QualiTech, EMC Lab.

If and when such permission is granted, the report must be reproduced only in the full format.


Test personnel



Tests Performed By: -----
Rami Nataf



Report Prepared By: -----
Bina Talkar



Report Reviewed By: -----
Y. Zucker
QA and Lab. Manager
QualiTech EMC Laboratory



1633.01

Test Report details:

Test commencement date: 05.01.2008
Test completion date: 15.01.2008
Customer's Representative: Teddy Neeman
Issued on: 03.02.2008

Assessment information:

This report contains an assessment of the EUT against Electromagnetic Compatibility based upon tests carried out on the samples submitted. The results contained in this report relate only to the items tested. Manufactured products will not necessarily give identical results due to production and measurement tolerances. QualiTech, EMC Lab does not assume responsibility for any conclusion and generalization drawn from the test results with regards to other specimens or samples of type of the equipment represented by test item.

The EUT was set up and exercised using the configuration, modes of operation and arrangements defined in this report only.

Modifications:

Modifications made to the EUT

None

Modifications made to the Test Standard

None

Summary of Compliance Status

Unintentional Radiations

Test Spec. Clause	Test Case	Remarks
47 CFR §15.407(b)(6) & §15.109/209, ICES-003 RSS-GEN section 7.2.3.2	Radiated Emission- (Receive mode)	Comply
47 CFR §15.407(b)(6) & §15.107/207, ICES-003 RSS-GEN section 7.2.3.2	Power line Emission measurements	Comply

Table of Content

1. GENERAL DESCRIPTION	5
2. METHOD OF MEASUREMENTS	6
2.1. Radiated Emission measurements:	6
2.2. Power Line Emission measurements:	6
2.3. Configurations for measurements:	6
3. TEST FACILITY & UNCERTAINTY OF MEASUREMENT	7
3.1. Accreditation/ Registration reference:	7
3.2. Test Facility description	7
3.3. Uncertainty of Measurement:	8
4. UNINTENTIONAL RADIATIONS: REPORT OF MEASUREMENTS AND EXAMINATIONS	9
4.1. Radiated Emission, Receive Mode	9
4.2. Power Line Emissions measurements	12
5. APPENDIX	16

1. General Description

Description of the EUT system/test Item:

Product name: VoWLAN SR

Model: F2978A

FCC ID: AZ489FT7032

IC: 109U-89FT7032

Description:

Single Mode VoWLAN 802.11a/b/g semi-rugged phone

2. Method of Measurements

2.1. Radiated Emission measurements:

Measurements were performed at a 3-meter measurement distance in the semi-anechoic chamber in order to evaluate the radiated electromagnetic interference characteristics of the EUT. The EUT was placed on a non-metallic table/support, 0.8m above the turntable, was configured, arranged and operated in a manner consistent with typical application and load conditions. The test program of exercising the equipment ensured that various parts of the EUT were exercised to permit detection of all EUT disturbances. An appropriate antenna depending upon the frequency range, per ANSI C63.4-2003 clause 4.1.5 was used. While the turntable was being rotated, the height of the antenna was varied from 1 to 4m for the frequency range of 30MHz to 1GHz. The highest radiated emission was detected by manipulating the system cables to the worst-case position. This process was repeated for both antenna polarizations. The spectrum up to 10GHz was investigated for emissions, using a band-reject filter where appropriate. The amplitudes of worst-case emission were measured with the detector modes and resolution bandwidths over various frequency ranges according to the requirements of ANSI C63.4-2003 clause 4.2.


2.2. Power Line Emission measurements:

The EUT was placed on a non-conductive table/support 80 cm above the reference ground plane. The EUT was configured in accordance with ANSI C63.4-2003 using a 50 μ H/50 ohm LISN.

Compliance with the provisions was based on the measurements of the radio frequency voltage between each line and the ground at the power terminal.


2.3. Configurations for measurements:

Charger configuration:



Note: Refer to Appendix B for SPN5202C FCC Declaration of Conformity

PC configuration (attached to USB port):



3. Test Facility & Uncertainty of Measurement

3.1. Accreditation/ Registration reference:

- A2LA Certificate Number: 1633.01

3.2. Test Facility description

The tests were performed at the EMC Laboratory, QualiTech Division, ECI Telecom Group

Address: 30, Hasivim St., Petah Tikva, Israel.
Tel: 972-3-926-8443

3m Anechoic Chamber:

The 3m-screened chamber is used in two configurations: the semi-anechoic configuration for Radiated Emission measurements and the full-anechoic configuration for Radiated Immunity tests.

Semi Anechoic Configuration:

Measurement distance	3m
Chamber dimensions	9.5m x 6.5m x 5.2m
Antenna height	1 - 4m
Shielding Effectiveness	Magnetic field ≥ 80 dB at 15 kHz ≥ 90 dB at 100 kHz Electric field > 120 dB from 1MHz to 1GHz > 110 dB from 1GHz to 10GHz
Absorbing material	Ferrite tiles on the walls and ceiling Frankonia hybrid absorbing material in selected positions on the walls
Normalized Site Attenuation measured at 5 positions	± 3.49 dB, 30MHz to 1GHz
Transmission Loss measured at 5 positions, at 1.5m height	± 3 dB, 1GHz to 18GHz

Full-Anechoic Configuration:

Measurement distance	3m
Chamber dimensions	7m x 4m x 3m
Antenna height	1.55m at Horizontal & Vertical polarizations
Shielding Effectiveness	Magnetic field ≥ 80 dB at 15 kHz ≥ 90 dB at 100 kHz Electric field > 120 dB from 1MHz to 1GHz > 110 dB from 1GHz to 10GHz
Absorbing material	Ferrite tiles on the walls and ceiling Frankonia hybrid absorbing material in selected positions on the walls and floor
Field Uniformity to EN61000-4-3	± 3 dB 80MHz to 18GHz

3.3. Uncertainty of Measurement:

Test Name	Test Method & Range	Uncertainty	
		Combined std. Uc(y) [dB]	Expanded U [dB]
Radiated Emission	30MHz÷230MHz, Horiz. polar.	1.8	3.6
	30MHz÷230MHz, Ver. polar.	2.0	3.9
	230MHz÷1000MHz, Horiz. polar.	1.5	3.0
	230MHz÷1000MHz, Vert. polar.	1.5	3.0
Conducted Emission	9 kHz÷150 kHz	1.4	2.8
	150 kHz÷30MHz	1.1	2.2

4. Unintentional Radiations: Report of Measurements and Examinations

4.1. Radiated Emission, Receive Mode

Reference document:	47 CFR §15.109/209		
Test Requirements:	Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in Sec.15.209. Emission Level shall not exceed the limits of §15.109.		
Test setup:	See sec 2.1	Pass	
Method of testing:	Radiated		
Operating conditions:	Under normal test conditions		
S.A. Settings:	f <1GHz: RBW: 120kHz, VBW: 300kHz f >1GHz: RBW: 1MHz, VBW: 3MHz		
Mode of operation:	Receive		
Environment conditions:	Ambient Temperature: 22°C	Relative Humidity: 48%	Atmospheric Pressure: 1011.4 hPa
Test Result:	See below	See Plot 4.1.1 – Plot 4.1.4	

Test result:


Frequency [MHz]	Emission Level [dBμV/m]	Detector Type	Polarization V/H	Limit [dBμV/m]	Margin [dB]
43.28	29.67	QP	V	40	10.33
All other emission at least 15 dB below the limit					

Note: Radiated Emission [dBμV/m] = measured [dBμV] + Correction-factor [dB(1/m)]
Correction Factor = Antenna factor + Cable Loss

Receive mode
Vertical Polarization
Plot 4.1.1




ACTV DET: PEAK
MEAS DET: PEAK OP AVG
MKR 962.1 MHz
36.13 dB μ V/m



Horizontal Polarization
Plot 4.1.2




ACTV DET: PEAK
MEAS DET: PEAK OP AVG
MKR 994.2 MHz
35.82 dB μ V/m



Horizontal Polarization
Plot 4.1.3




ACTV DET: PEAK
MEAS DET: PEAK QP AVG
MKR 216.4 MHz
32.18 dB μ V/m



Vertical Polarization
Plot 4.1.4



ACTV DET: PEAK
MEAS DET: PEAK QP AVG
MKR 43.2 MHz
34.67 dB μ V/m



4.2. Power Line Emissions measurements

Reference document:	47 CFR §15.107/207		
Test Requirements:	Any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in Sec.15.207.		
Test setup:	See Sec. 2.2	Pass	
Operating conditions:	Under normal test conditions		
Method of testing:	Conducted Emissions		
S.A. Settings:	f <30MHz: RBW: 9kHz, VBW:30kHz		
Radio device:	Idle & Transmit modes		
Environment conditions:	Ambient Temperature: 21°C	Relative Humidity: 54%	Atmospheric Pressure: 1011.4 hPa
Test Result:	See below	See Plot 4.2.1 - Plot 4.2.4	

Test Results:

Measured at the charger 110VAC port. Measured in idle and various transmit modes, worst case results presented.

“Phase” Lead

Frequency [MHz]	Measured Result [dBμV]		Class B Limits [dBμV]		Margin [dB]		Pass/Fail
	QP	AVR	QP	AVR	QP	AVR	
0.278923	32	15.2	60.9	50.9	-28.9	-35.7	Pass
0.613292	31.7	15.9	56	46	-24.3	-30.1	Pass
0.723431	29.4	15.9	56	46	-26.6	-30.1	Pass
1.26273	29.4	17.1	56	46	-26.6	-28.9	Pass
1.737101	27.9	17.1	56	46	-28.1	-28.9	Pass
5.313335	23.3	13.9	60	50	-36.7	-36.1	Pass

“Neutral” Lead

Frequency [MHz]	Measured Result [dBμV]		Class B Limits [dBμV]		Margin [dB]		Pass/Fail
	QP	AVR	QP	AVR	QP	AVR	
0.278923	23.8	8.2	60.9	50.9	-37.1	-42.7	Pass
0.613292	34.1	22.5	56	46	-21.9	-23.5	Pass
0.723431	30.5	20.2	56	46	-25.5	-25.8	Pass
1.26273	30.2	18.5	56	46	-25.8	-27.5	Pass
1.737101	26.8	14.4	56	46	-29.2	-31.6	Pass
5.313335	25.5	13.9	60	50	-34.5	-36.1	Pass

Measured at the PC 110VAC port

“Phase” Lead


Frequency [MHz]	Measured Result [dBμV]		Class B Limits [dBμV]		Margin [dB]		Pass/Fail
	QP	AVR	QP	AVR	QP	AVR	
0.154575	55	23.7	65.75	55.75	-10.75	-32.05	Pass
0.481094	27.9	13.2	56.32	46.32	-28.42	-33.12	Pass
3.026568	28.1	21.6	56.00	46.00	-27.90	-24.40	Pass
9.448107	29.3	23.1	60.00	50.00	-30.70	-26.90	Pass
21.093965	37.7	31.8	60.00	50.00	-22.30	-18.20	Pass
27.484612	29.5	22.6	60.00	50.00	-30.50	-27.40	Pass

“Neutral” Lead


Frequency [MHz]	Measured Result [dBμV]		Class B Limits [dBμV]		Margin [dB]		Pass/Fail
	QP	AVR	QP	AVR	QP	AVR	
0.154575	55.1	24.6	65.75	55.75	-10.65	-31.15	Pass
0.481094	29.8	12.9	56.32	46.32	-26.52	-33.42	Pass
3.026568	26.8	20.3	56.00	46.00	-29.20	-25.70	Pass
9.448107	26.4	18.7	60.00	50.00	-33.60	-31.30	Pass
21.093965	34.8	28.9	60.00	50.00	-25.20	-21.10	Pass
27.484612	27.7	20.4	60.00	50.00	-32.30	-29.60	Pass

Measured at the charger 110VAC port

Phase Lead
Plot 4.2.1




Neutral Lead
Plot 4.2.2




Measured at the PC 110VAC port

Phase Lead
Plot 4.2.3



Neutral Lead
Plot 4.2.4



5. Appendix

Appendix A: List of Measuring Equipment used:

Equipment	Manufacturer/ Model	Serial Number	Due date
CISPR16 EMI Receiver	HP8546A	3710A00392	30-06-08
Spectrum Analyzer 9kHz ÷ 22 GHz	HP 8593EM	3536A00131	30-06-08
Spectrum Analyzer 100 Hz ÷ 26.5 GHz	Agilent E7405A	US41160436	30-06-08
LNA Amplifier 1 GHz ÷ 18 GHz	AMP – 5D-010180-30-10P-GW	618653	30-06-08
Power meter	Agilent N1911A	MY45100784	23-02-08
Dual Ridged Guide Ant.1-18 GHz	EMCO 3115	9602-4677	30-06-08
Antenna 18 GHz ÷ 26.5 GHz	Alpha Industry 861A/599	505	30-06-08
Turn table	HD100	100/693	-
Antenna Mast	HD 100	100/693	-
Biconical 20 – 200 MHz	Schwarzbeck VHBB9124	9124/0255	16-05-08
Log-Periodic 200 – 1000 MHz	Schwarzbeck VUSLP9111	VUSLP9111184	16-05-08
Pre-Amplifier	MiTeq, AMF-5F-18002650-30-10P	945372	30-06-08
LISN	Fischer 50/250-25-2	-	30-06-08
Transient Limiter	HP11947A	-	30-06-08
Notch Filter	Micro-Tronics BRM50702-05	0001	30-06-08

Appendix B: FCC Declaration of Conformity

SPN5202C



FRIWO ELECTRICAL(SHENZHEN) COMPANY LTD.
Hangcheng Industrial Zone,XiXiang,
Bao An District,ShenZhen,518102,China
Tel:+86 755 27695268 Fax: +86 755 27479461

Our Ref: SDC070914U-FMP5202C

FCC Declaration of Conformity

We, **FRIWO ELECTRICAL (SHENZHEN) COMPANY LTD.**,
Hangcheng Industrial Zone,XiXiang,
Bao An District,ShenZhen,518102,CHINA.

Declare under our sole responsibility that the designated product



AC/DC Adapter type : FMP5202C
(Motorola Kit No. SPN5202C)
Input: 100-240Vac ~50-60Hz/0.12A
Output: 5.0Vdc / 850mA

1) Is in conformity with the requirements of Electromagnetic Compatibility Directive and the tested according to the following standard:

FCC 47 CFR PART 15,SUBPART,CLASS B :2006

Stuart.Mitchell
Engineering Manager
Date: 14 th Sep, 2007




Page 1 of 1

Support Equipment, IBM ThinkPad T43Type 1871



Support Equipment, 2nd device



Appendix C: Accreditation Certificate



End of the Test Report