

Exhibit 2. Statements of Certification -- Pursuant to 47 CFR 2.907

2.1. Specification Compliance

Transceiver type described herein (AZ489FT7078) has been tested in accordance with the requirements contained in the appropriate Commission regulations. To the best of my knowledge, these tests were performed using measurement procedures consistent with industry or Commission standards, and demonstrate that this equipment complies with the appropriate standards. Each unit manufactured, imported, or marketed will conform to the samples tested herein, within the statistical variations that can be expected due to high volume production and test measurement error.

NAME: Roy Tong

SIGNATURE: 

DATE: 12 February 2016


TITLE: RF Engineer

2.2. Statement of Certification

I hereby certify that the above application was prepared under my direction and that to the best of my knowledge and belief, the facts set forth in this application and accompanying technical data are true and correct.

The technical data supplied with this application was taken under my supervision and is hereby duly certified. I also certify that this transmit equipment (AZ489FT7078) is in compliance with all applicable parts of the FCC Rules.

NAME:

SIGNATURE: 

DATE: 12 February 2016

TITLE: 

2.3. Attestation Statement (Equipment Class DTS and DSS - Bluetooth/Wi-Fi)

This device contains an embedded Bluetooth device and Wi-Fi device that Motorola Solutions confirms are compliant with the applicable Part 15C regulations. Personal Hotspot operation is only supported in the 2.4 GHz band.

15.247(a)(1)

- The hopping sequence must be pseudorandom.
- All Channels are used equally on average.
- The receiver input bandwidth is approximately equal to the transmit bandwidth.
- The receiver hops in sequence with the transmitted signal.

15.247(g)

The system is designed to comply with all of the regulations in Section 15.247 when the transmitter is presented with a continuous data (or information).

15.247(h)

The system does not coordinate its channel selection/hopping sequence with other frequency hopping systems for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters.

2.4. Attestation Statement (Equipment class NII - WLAN)**15.407(c)**

The system will automatically discontinue transmission in case of absence of information to transmit or operational failure.

15.407(h)(1)

Maximum EIRP of the device is less than 500mW, therefore a TPC mechanism is not required.

15.407(h)(2)

This device, the client software and associated drivers will not initiate any transmission on DFS frequencies without initiation by a master. This included restriction on transmission for beacons and support for ad-hoc peer-to-peer modes.

Ad-hoc operation is restricted in this device

NAME: Roy Tong

SIGNATURE: 

DATE: 12 February 2016

TITLE: RF Engineer