



**BUREAU
VERITAS**

Test Report No.: RF170103W004-2



FCC TEST REPORT

(Part 15, Subpart C)

Product: LTE mission critical hand held

Model Name: LEX F10

FCC ID: AZ489FT7101

Applicant: Motorola Solutions, Inc.

Address: 8000 West Sunrise Blvd Ft Lauderdale, FL 33322

Manufacturer: Motorola Solutions, Inc.

Address: 8000 West Sunrise Blvd Ft Lauderdale, FL 33322

Prepared by: Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch

Lab Location: No. 34, Chenwulu Section, Guantai Rd., Houjie Town, Dongguan City, Guangdong 523942, China

TEL: +86 769 8593 5656

FAX: +86 769 8593 1080

E-MAIL: customerservice.dg@cn.bureauveritas.com

Report No.: RF170103W004-2

Received Date: Jan. 03, 2017

Test Date: Feb. 02, 2017 ~ Feb. 24, 2017

Issued Date: Feb. 27, 2017

This report should not be used by the client to claim product certification, approval, or endorsement by A2LA or any government agencies.

Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specifically mentioned, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.



TABLE OF CONTENTS

RELEASE CONTROL RECORD 4

1 CERTIFICATION 5

2 SUMMARY OF TEST RESULTS..... 6

2.1 MEASUREMENT UNCERTAINTY 6

3 GENERAL INFORMATION 7

3.1 GENERAL DESCRIPTION OF EUT 7

3.2 DESCRIPTION OF TEST MODES 9

3.2.1 CONFIGURATION OF SYSTEM UNDER TEST 10

3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL..... 10

3.3 DUTY CYCLE OF TEST SIGNAL 13

3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS 14

3.5 DESCRIPTION OF SUPPORT UNITS 14

4 TEST TYPES AND RESULTS..... 15

4.1 CONDUCTED EMISSION MEASUREMENT 15

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT 15

4.1.2 TEST INSTRUMENTS..... 15

4.1.3 TEST PROCEDURES 16

4.1.4 DEVIATION FROM TEST STANDARD 16

4.1.5 TEST SETUP 17

4.1.6 EUT OPERATING CONDITIONS 17

4.1.7 TEST RESULTS 18

4.2 RADIATED EMISSION MEASUREMENT 20

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT 20

4.2.2 TEST INSTRUMENTS..... 21

4.2.3 TEST PROCEDURES 22

4.2.4 DEVIATION FROM TEST STANDARD 22

4.2.5 TEST SETUP 23

4.2.6 EUT OPERATING CONDITIONS 24

4.2.7 TEST RESULTS 25

4.3 6 DB BANDWIDTH MEASUREMENT 44

4.3.1 LIMITS OF 6DB BANDWIDTH MEASUREMENT 44

4.3.2 TEST INSTRUMENTS..... 44

4.3.3 TEST PROCEDURE..... 44

4.3.4 DEVIATION FROM TEST STANDARD 45

4.3.5 TEST SETUP 45



4.3.6	EUT OPERATING CONDITIONS	45
4.3.7	TEST RESULTS	46
4.4	CONDUCTED OUTPUT POWER.....	51
4.4.1	LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT	51
4.4.2	TEST SETUP	51
4.4.3	TEST INSTRUMENTS.....	51
4.4.4	TEST PROCEDURES	51
4.4.5	DEVIATION FROM TEST STANDARD	51
4.4.6	EUT OPERATING CONDITIONS	51
4.4.7	TEST RESULTS	52
4.4.7.1	MAXIMUM PEAK OUTPUT POWER	52
4.4.7.2	AVERAGE OUTPUT POWER (FOR REFERENCE).....	54
4.5	POWER SPECTRAL DENSITY MEASUREMENT	56
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	56
4.5.2	TEST SETUP	56
4.5.3	TEST INSTRUMENTS.....	56
4.5.4	TEST PROCEDURE.....	56
4.5.5	DEVIATION FROM TEST STANDARD	56
4.5.6	EUT OPERATING CONDITION	56
4.5.7	TEST RESULTS	57
4.6	OUT OF BAND EMISSION MEASUREMENT	62
4.6.1	LIMITS OF OUT OF BAND EMISSION MEASUREMENT	62
4.6.2	TEST SETUP	62
4.6.3	TEST INSTRUMENTS.....	62
4.6.4	TEST PROCEDURE.....	62
4.6.5	DEVIATION FROM TEST STANDARD	63
4.6.6	EUT OPERATING CONDITION	63
4.6.7	TEST RESULTS	63
5	PHOTOGRAPHS OF THE TEST CONFIGURATION	74
6	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT	
	BY THE LAB	75



BUREAU
VERITAS

Test Report No.: RF170103W004-2

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF170103W004-2	Original release	Feb. 27, 2017



1 CERTIFICATION

PRODUCT: LTE mission critical hand held
BRAND NAME: Motorola Solutions, Inc.
MODEL NAME: LEX F10
APPLICANT: Motorola Solutions, Inc.
TESTED: Feb. 02, 2017 ~ Feb. 24, 2017
TEST SAMPLE: Identical Prototype
STANDARDS: **FCC Part 15, Subpart C. Section 15.247**
ANSI C63.10-2013

The above equipment has been tested by **Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch** and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : _____ , **DATE:** Feb. 27, 2017
(Harry Li/ Engineer)

APPROVED BY : _____ , **DATE:** Feb. 27, 2017
(Sam Tung / Manager)



2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -24.79dB at 0.150000MHz.
15.205 15.209	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -1.67dB at 2483.5MHz.
15.247(d)	Out of band Emission Measurement	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted Output power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.70dB
Radiated emissions	9KHz ~ 30MHz	2.90dB
	30MHz ~ 1GMHz	4.06dB
	1GHz ~ 18GHz	4.58dB
	18GHz ~ 40GHz	1.94dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.



3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	LTE mission critical hand held
MODEL NAME	LEX F10
TYPE NUMBER	NA
NOMINAL VOLTAGE	5.0Vdc (adapter or host equipment) 3.8Vdc (Li-ion, battery)
MODULATION TECHNOLOGY	DSSS, OFDM, DTS
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM BT-LE(GFSK) for DTS
TRANSMISSION RATE	802.11b: 11/ 5.5/ 2.0 / 1.0 Mbps 802.11g: 54/ 48/ 36 / 24 / 18 / 9/ 6 Mbps 802.11n: up to 135 Mbps BT_LE: 1 Mbps
OPERATING FREQUENCY	2412-2462MHz for 11b/g/n(HT20) 2422-2452MHz for 11n(HT40) 2402-2480MHz for BT-LE(GFSK)
MAX. OUTPUT POWER	WLAN: 223.872mW (Maximum) BT-LE: 2.48mW (Maximum)
ANTENNA TYPE	PCB Antenna with -1dBi gain
HW VERSION	C
SW VERSION	7A.0.0-07-5.1.1-21.00.15
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	USB cable: non-shielded, detachable, 1.1m

NOTE:

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- The EUT incorporates a SISO function. Physically, the EUT provides one transmitter and one receiver.

MODULATION MODE	TX/RX FUNCTION
802.11b	1TX /1RX
802.11g	1TX /1RX
802.11n (20MHz)	1TX /1RX
802.11n (40MHz)	1TX /1RX



3. The EUT was powered by the following adapter:

ADAPTER	
BRAND:	Motorola Solutions, Inc.
MODEL:	S24A02
INPUT:	AC 100-240V, 450mA
OUTPUT:	DC 5V, 2100mA

4. The EUT matched the following USB cable:

USB CABLE	
BRAND:	Sunway
MODEL:	TBD
SIGNAL LINE:	1.1 METER

5. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.



3.2 DESCRIPTION OF TEST MODES

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

7 channels are provided for 802.11n (HT40):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
3	2422MHz	7	2442MHz
4	2427MHz	8	2447MHz
5	2432MHz	9	2452MHz
6	2437MHz		

40 channels are provided for BT-LE (GFSK):

CHANNEL	FREQ. (MHZ)						
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480



3.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photographs of the test configuration for reference.

3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports.

The worst case was found when positioned on Y axis for radiated emission. Following test modes were selected for the final test, and the final worst case is marked in boldface and recorded in the report:

EUT CONFIGURE MODE	APPLICABLE TO				MODE
	RE<1G	RE≥1G	PLC	APCM	
-	√	√	√	√	-

Where **RE<1G**: Radiated Emission below 1GHz **RE≥1G**: Radiated Emission above 1GHz
PLC: Power Line Conducted Emission **APCM**: Antenna Port Conducted Measurement

NOTE: No need to concern of Conducted Emission due to the EUT is powered by battery.

RADIATED EMISSION TEST (BELOW 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11g	1 to 11	11	OFDM	BPSK	6.0
BT-LE	0 to 39	39	DTS	GFSK	1



RADIATED EMISSION TEST (ABOVE 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	CCK	DBPSK	1.0
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
802.11n HT20	1 to 11	1, 6, 11	OFDM	BPSK	6.5
802.11n HT40	3 to 9	3, 6, 9	OFDM	BPSK	13.5
BT-LE	0 to 39	0,19, 39	DTS	GFSK	1

POWER LINE CONDUCTED EMISSION TEST:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11g	1 to 11	11	OFDM	BPSK	6.0

BANDEDGE MEASUREMENT:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 11	CCK	DBPSK	1.0
802.11g	1 to 11	1, 11	OFDM	BPSK	6.0
802.11n HT20	1 to 11	1, 11	OFDM	BPSK	6.5
802.11n HT40	3 to 9	3, 9	OFDM	BPSK	13.5
BT-LE	0 to 39	0, 39	DTS	GFSK	1



ANTENNA PORT CONDUCTED MEASUREMENT:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	CCK	DBPSK	1.0
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
802.11n HT20	1 to 11	1, 6, 11	OFDM	BPSK	6.5
802.11n HT40	3 to 9	3,6, 9	OFDM	BPSK	13.5
BT-LE	0 to 39	0, 19, 39	DTS	GFSK	1

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE	TESTED BY
RE<1G	22deg. C, 54%RH	DC 5V from adaptor	Tony Zou
RE≥1G	22deg. C, 54%RH	DC 5V from adaptor	Tony Zou
PLC	25deg. C, 60%RH	3.8Vdc from battery	Alex Chen
APCM	25deg. C, 60%RH	3.8Vdc from battery	Wenliang Wu



3.3 DUTY CYCLE OF TEST SIGNAL

WIFI 2.4GHz

802.11b: Duty cycle = 0.565/0.569 = 0.993 > 98%, Duty factor is not required.

802.11g: Duty cycle = 1.363/1.563 = 0.872 < 98%, Duty factor = 10 * log(1/0.872) = 0.595

802.11n (HT20): Duty cycle = 1.275/1.484 = 0.859 < 98%, Duty factor = 10 * log(1/0.859) = 0.659

802.11n (HT40): Duty cycle = 0.634/0.845 = 0.750 < 98%, Duty factor = 10 * log(1/0.750) = 1.248





3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C, Section 15.247

KDB 558074 D01 DTS Meas Guidance v03r05

ANSI C63.10-2013

Note:

1. All test items have been performed and recorded as per the above standards.
2. The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (Certification). The test report has been issued separately.

3.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	DC source	LONG WEI	PS-6403D	010934269	N/A
2	PC	HP	A6608CN	3CR83825X3	N/A
3	Earphone	Minami	ME-816B5-E	N/A	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	DC Line: Unshielded, Detachable 1.0m
2	AC Line: Unshielded, Detachable 1.5m
3	Earphone Cable: Shielded, Detachable, 1.2m



4 TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBµV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR7	101494	Apr. 05,16	Apr. 04,17
Artificial Mains Network	Rohde&Schwarz	ENV216	101173	Mar. 04,16	Mar. 03,17
Artificial Mains Network	Rohde&Schwarz	ESH3-Z5	100317	Apr. 05,16	Apr. 04,17
Voltage probe	SCHWARZBECK	TK 9421	TK 9421-176	Nov. 25,16	Nov. 24,17
Test software	ADT	ADT_Cond_V7.3.7	N/A	N/A	N/A

- NOTE:**
1. The test was performed in shielded room 553.
 2. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.


NOTE: All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation.



4.1.5 TEST SETUP



- Note:**
- 1.Support units were connected to second LISN.
 - 2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.



4.1.7 TEST RESULTS


CONDUCTED WORST-CASE DATA:

Frequency Range	150KHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120Vac, 60Hz	Environmental Conditions	24deg. C, 55RH
Tested By	Alex Chen	TEST DATE	2017/02/09

Frequency (MHz)	QuasiPeak (dB μ V)	CAverage (dB μ V)	Limit (dB μ V)	Margin (dB)	Line	Filter	Corr. (dB)
0.150000	---	26.82	56.00	-29.18	L	ON	9.6
0.150000	41.21	---	66.00	-24.79	L	ON	9.6
0.216000	---	23.60	52.97	-29.37	L	ON	9.7
0.216000	37.80	---	62.97	-25.17	L	ON	9.7
0.488000	---	12.29	46.20	-33.91	L	ON	9.7
0.488000	24.02	---	56.20	-32.18	L	ON	9.7
1.224000	26.60	---	56.00	-29.40	L	ON	9.7
1.224000	---	9.34	46.00	-36.66	L	ON	9.7
1.236000	26.60	---	56.00	-29.40	L	ON	9.7
1.236000	---	12.33	46.00	-33.67	L	ON	9.7
4.308000	---	13.13	46.00	-32.87	L	ON	9.7
4.308000	24.27	---	56.00	-31.73	L	ON	9.7

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.

Full Spectrum






Frequency Range	150KHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120Vac, 60Hz	Environmental Conditions	24deg. C, 55RH
Tested By	Alex Chen	TEST DATE	2017/02/09

Frequency (MHz)	QuasiPeak (dB μ V)	CAverage (dB μ V)	Limit (dB μ V)	Margin (dB)	Line	Filter	Corr. (dB)
0.158000	---	22.29	55.57	-33.28	N	ON	10.1
0.158000	35.43	---	65.57	-30.14	N	ON	10.1
0.588000	---	19.20	46.00	-26.80	N	ON	10.1
0.588000	28.27	---	56.00	-27.73	N	ON	10.1
1.228000	---	14.75	46.00	-31.25	N	ON	9.9
1.228000	28.58	---	56.00	-27.42	N	ON	9.9
1.824000	---	16.42	46.00	-29.58	N	ON	9.8
1.824000	29.58	---	56.00	-26.42	N	ON	9.8
3.044000	---	14.01	46.00	-31.99	N	ON	9.8
3.044000	26.24	---	56.00	-29.76	N	ON	9.8
4.240000	---	15.30	46.00	-30.70	N	ON	9.8
4.240000	26.77	---	56.00	-29.23	N	ON	9.8

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.

Full Spectrum





4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



4.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR7	101494	Apr. 05,16	Apr. 04,17
Signal and Spectrum Analyzer	Rohde&Schwarz	FSV7	102331	Nov. 04,16	Nov. 03,17
Bilog Antenna	Teseq	CBL 6111D	30643	Jul. 14, 16	Jul. 13, 17
Loop antenna	Daze	ZN30900A	0708	Nov. 28, 16	Nov. 27, 17
Horn Antenna (1GHz -18GHz)	ETS -Lindgren	3117	00062558	May 18,16	May 17,17
10m Semi-anechoic Chamber	CHANGLING	21.4m*12.1m*8.8m	NSEMC006	Mar. 12,16	Mar. 11,18
Test Software	E3	V 9.160323	N/A	N/A	N/A
Horn Antenna (15GHz-40GHz)	SCHWARZBECK	BBHA 9170	BBHA9170242	Mar. 12,16	Mar. 11,17
Amplifier (9kHz-1GHz)	SONOMA	310D	186955	Mar. 04,16	Mar. 03, 17
Pre-Amplifier(1-18G)	HP	8449B	3008A00409	Apr. 25,16	Apr. 24,17
Pre-Amplifier (18GHz-40GHz)	EMCI	EMC 184045	980102	Nov. 04,16	Nov. 03,17
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	Aug. 08,16	Aug. 07,17

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in 10m Chamber.
3. The FCC Site Registration No. is 502831.



4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 10 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor ($10 \log(1/\text{duty cycle})$).
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.


4.2.4 DEVIATION FROM TEST STANDARD

No deviation




4.2.5 TEST SETUP

< Frequency Range below 30MHz >




< Frequency Range 30MHz~1GHz >





<Frequency Range above 1GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT OPERATING CONDITIONS

- a. Set the EUT under full load condition and placed them on a testing table.
- b. Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- c. The necessary accessories enable the EUT in full functions.



4.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA:

9 KHz – 30 KHz data: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

30 MHz – 1GHz data:


802.11g

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
96.93	25.89	53.72	43.50	-17.61	7.66	1.52	37.01	200	45	QP
161.92	27.73	52.36	43.50	-15.77	10.17	1.94	36.74	200	69	QP
191.99	34.48	58.93	43.50	-9.02	10.02	2.13	36.60	200	125	QP
225.94	34.84	57.76	46.00	-11.16	11.29	2.32	36.53	200	248	QP
294.81	32.21	53.08	46.00	-13.79	12.94	2.69	36.50	200	300	QP
332.64	28.57	47.91	46.00	-17.43	14.37	2.86	36.57	200	98	QP

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.






CHANNEL	TX Channel 11	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
79.47	26.66	55.83	40.00	-13.34	6.62	1.37	37.16	100	65	QP
187.14	28.66	53.23	43.50	-14.84	9.97	2.10	36.64	100	80	QP
248.25	33.11	54.87	46.00	-12.89	12.32	2.44	36.52	100	116	QP
296.75	32.77	53.61	46.00	-13.23	12.96	2.70	36.50	100	248	QP
412.18	26.79	43.00	46.00	-19.21	17.35	3.19	36.75	100	180	QP
467.47	25.94	41.45	46.00	-20.06	18.01	3.36	36.88	100	175	QP

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.





ABOVE 1GHZ WORST-CASE DATA:

Note: For higher frequency, the emission is too low to be detected.

802.11b

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	41.16	49.03	54.00	-12.84	32.29	8.15	48.31	105	80	Average
2390	48.80	56.67	74.00	-25.20	32.29	8.15	48.31	105	80	Peak
2412	100.40	108.21			32.31	8.19	48.31	105	80	Average
2412	103.03	110.84			32.31	8.19	48.31	105	80	Peak
2483.5	34.33	41.93	54.00	-19.67	32.38	8.32	48.30	105	80	Average
2483.5	47.97	55.57	74.00	-26.03	32.38	8.32	48.30	105	80	Peak
4824	51.24	53.21	54.00	-2.76	34.30	12.63	48.90	110	2	Average
4824	56.77	58.74	74.00	-17.23	34.30	12.63	48.90	110	2	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	36.58	44.45	54.00	-17.42	32.29	8.15	48.31	150	325	Average
2390	49.80	57.67	74.00	-24.20	32.29	8.15	48.31	150	325	Peak
2412	98.44	106.25			32.31	8.19	48.31	150	325	Average
2412	101.14	108.95			32.31	8.19	48.31	150	325	Peak
2483.5	35.10	42.70	54.00	-18.90	32.38	8.32	48.30	150	325	Average
2483.5	47.72	55.32	74.00	-26.28	32.38	8.32	48.30	150	325	Peak
4824	47.39	49.36	54.00	-6.61	34.30	12.63	48.90	100	320	Average
4824	55.15	57.12	74.00	-18.85	34.30	12.63	48.90	100	320	Peak

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 2412MHz: Fundamental frequency.



CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	34.48	42.35	54.00	-19.52	32.29	8.15	48.31	102	80	Average
2390	45.71	53.58	74.00	-28.29	32.29	8.15	48.31	102	80	Peak
2437	100.59	108.32			32.34	8.24	48.31	102	80	Average
2437	102.52	110.25			32.34	8.24	48.31	102	80	Peak
2485	40.07	47.66	54.00	-13.93	32.39	8.32	48.30	102	80	Average
2485	49.36	56.95	74.00	-24.64	32.39	8.32	48.30	102	80	Peak
4874	51.45	53.26	54.00	-2.55	34.30	12.81	48.92	100	5	Average
4874	57.15	58.96	74.00	-16.85	34.30	12.81	48.92	100	5	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	34.81	42.68	54.00	-19.19	32.29	8.15	48.31	142	325	Average
2390	46.27	54.14	74.00	-27.73	32.29	8.15	48.31	142	325	Peak
2437	99.83	107.56			32.34	8.24	48.31	142	325	Average
2437	102.37	110.10			32.34	8.24	48.31	142	325	Peak
2483.5	39.78	47.38	54.00	-14.22	32.38	8.32	48.30	142	325	Average
2483.5	49.90	57.50	74.00	-24.10	32.38	8.32	48.30	142	325	Peak
4874	44.51	46.32	54.00	-9.49	34.30	12.81	48.92	100	350	Average
4874	54.07	55.88	74.00	-19.93	34.30	12.81	48.92	100	350	Peak

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 2437MHz: Fundamental frequency.



CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	33.85	41.72	54.00	-20.15	32.29	8.15	48.31	100	80	Average
2390	46.29	54.16	74.00	-27.71	32.29	8.15	48.31	100	80	Peak
2462	99.70	107.36			32.36	8.28	48.30	100	80	Average
2462	102.02	109.68			32.36	8.28	48.30	100	80	Peak
2483.5	44.89	52.49	54.00	-9.11	32.38	8.32	48.30	100	80	Average
2483.5	54.33	61.93	74.00	-19.67	32.38	8.32	48.30	100	80	Peak
4924	46.45	48.09	54.00	-7.55	34.30	13.00	48.94	100	10	Average
4924	54.78	56.42	74.00	-19.22	34.30	13.00	48.94	100	10	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	34.95	42.82	54.00	-19.05	32.29	8.15	48.31	165	324	Average
2390	47.50	55.37	74.00	-26.50	32.29	8.15	48.31	165	324	Peak
2462	98.91	106.57			32.36	8.28	48.30	165	324	Average
2462	101.04	108.70			32.36	8.28	48.30	165	324	Peak
2483.5	37.72	45.32	54.00	-16.28	32.38	8.32	48.30	165	324	Average
2483.5	49.83	57.43	74.00	-24.17	32.38	8.32	48.30	165	324	Peak
4924	41.34	42.98	54.00	-12.66	34.30	13.00	48.94	100	345	Average
4924	52.23	53.87	74.00	-21.77	34.30	13.00	48.94	100	345	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2462MHz: Fundamental frequency.



802.11g

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	50.59	58.46	54.00	-3.41	32.29	8.15	48.31	105	80	Average
2390	67.40	75.27	74.00	-6.60	32.29	8.15	48.31	105	80	Peak
2412	94.12	101.93			32.31	8.19	48.31	105	80	Average
2412	105.18	112.99			32.31	8.19	48.31	105	80	Peak
2483.5	34.34	41.94	54.00	-19.66	32.38	8.32	48.30	105	80	Average
2483.5	46.05	53.65	74.00	-27.95	32.38	8.32	48.30	105	80	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	41.08	48.95	54.00	-12.92	32.29	8.15	48.31	100	325	Average
2390	57.70	65.57	74.00	-16.30	32.29	8.15	48.31	100	325	Peak
2412	91.21	99.02			32.31	8.19	48.31	100	325	Average
2412	100.88	108.69			32.31	8.19	48.31	100	325	Peak
2483.5	35.20	42.80	54.00	-18.80	32.38	8.32	48.30	100	325	Average
2483.5	47.27	54.87	74.00	-26.73	32.38	8.32	48.30	100	325	Peak

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 2412MHz: Fundamental frequency.



CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	34.50	42.37	54.00	-19.50	32.29	8.15	48.31	100	80	Average
2390	45.35	53.22	74.00	-28.65	32.29	8.15	48.31	100	80	Peak
2437	93.79	101.52			32.34	8.24	48.31	100	80	Average
2437	104.12	111.85			32.34	8.24	48.31	100	80	Peak
2485	41.57	49.16	54.00	-12.43	32.39	8.32	48.30	100	80	Average
2485	50.36	57.95	74.00	-23.64	32.39	8.32	48.30	100	80	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	35.97	43.84	54.00	-18.03	32.29	8.15	48.31	100	325	Average
2390	49.20	57.07	74.00	-24.80	32.29	8.15	48.31	100	325	Peak
2437	90.49	98.22			32.34	8.24	48.31	100	325	Average
2437	100.80	108.53			32.34	8.24	48.31	100	325	Peak
2485	38.18	45.77	54.00	-15.82	32.39	8.32	48.30	100	325	Average
2485	48.55	56.14	74.00	-25.45	32.39	8.32	48.30	100	325	Peak

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 2437MHz: Fundamental frequency.



CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	34.39	42.26	54.00	-19.61	32.29	8.15	48.31	100	80	Average
2390	45.60	53.47	74.00	-28.40	32.29	8.15	48.31	100	80	Peak
2462	93.73	101.39			32.36	8.28	48.30	100	80	Average
2462	104.14	111.80			32.36	8.28	48.30	100	80	Peak
2483.5	52.33	59.93	54.00	-1.67	32.38	8.32	48.30	100	80	Average
2483.5	70.34	77.94	74.00	-3.66	32.38	8.32	48.30	100	80	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	37.53	45.40	54.00	-16.47	32.29	8.15	48.31	100	325	Average
2390	50.84	58.71	74.00	-23.16	32.29	8.15	48.31	100	325	Peak
2462	88.50	96.16			32.36	8.28	48.30	100	325	Average
2462	99.28	106.94			32.36	8.28	48.30	100	325	Peak
2483.5	43.92	51.52	54.00	-10.08	32.38	8.32	48.30	100	325	Average
2483.5	60.41	68.01	74.00	-13.59	32.38	8.32	48.30	100	325	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2462MHz: Fundamental frequency.



802.11n (20MHz)

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	46.08	53.95	54.00	-7.92	32.29	8.15	48.31	102	80	Average
2390	62.28	70.15	74.00	-11.72	32.29	8.15	48.31	102	80	Peak
2412	92.49	100.30			32.31	8.19	48.31	102	80	Average
2412	102.73	110.54			32.31	8.19	48.31	102	80	Peak
2483.5	35.19	42.79	54.00	-18.81	32.38	8.32	48.30	102	80	Average
2483.5	46.52	54.12	74.00	-27.48	32.38	8.32	48.30	102	80	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	40.45	48.32	54.00	-13.55	32.29	8.15	48.31	100	325	Average
2390	58.62	66.49	74.00	-15.38	32.29	8.15	48.31	100	325	Peak
2412	89.24	97.05			32.31	8.19	48.31	100	325	Average
2412	99.93	107.74			32.31	8.19	48.31	100	325	Peak
2483.5	34.19	41.79	54.00	-19.81	32.38	8.32	48.30	100	325	Average
2483.5	46.77	54.37	74.00	-27.23	32.38	8.32	48.30	100	325	Peak

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 2412MHz: Fundamental frequency.



CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	34.52	42.39	54.00	-19.48	32.29	8.15	48.31	102	70	Average
2390	47.65	55.52	74.00	-26.35	32.29	8.15	48.31	102	70	Peak
2437	93.77	101.50			32.34	8.24	48.31	102	70	Average
2437	103.49	111.22			32.34	8.24	48.31	102	70	Peak
2485	40.73	48.32	54.00	-13.27	32.39	8.32	48.30	102	70	Average
2485	50.46	58.05	74.00	-23.54	32.39	8.32	48.30	102	70	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	35.16	43.03	54.00	-18.84	32.29	8.15	48.31	160	290	Average
2390	48.05	55.92	74.00	-25.95	32.29	8.15	48.31	160	290	Peak
2437	90.19	97.92			32.34	8.24	48.31	160	290	Average
2437	101.39	109.12			32.34	8.24	48.31	160	290	Peak
2485	38.25	45.84	54.00	-15.75	32.39	8.32	48.30	160	290	Average
2485	47.77	55.36	74.00	-26.23	32.39	8.32	48.30	160	290	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2437MHz: Fundamental frequency.



CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	34.22	42.09	54.00	-19.78	32.29	8.15	48.31	100	70	Average
2390	45.69	53.56	74.00	-28.31	32.29	8.15	48.31	100	70	Peak
2462	91.33	98.99			32.36	8.28	48.30	100	70	Average
2462	101.96	109.62			32.36	8.28	48.30	100	70	Peak
2483.5	51.82	59.42	54.00	-2.18	32.38	8.32	48.30	100	70	Average
2483.5	70.03	77.63	74.00	-3.97	32.38	8.32	48.30	100	70	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	37.67	45.54	54.00	-16.33	32.29	8.15	48.31	155	290	Average
2390	49.81	57.68	74.00	-24.19	32.29	8.15	48.31	155	290	Peak
2462	89.45	97.11			32.36	8.28	48.30	155	290	Average
2462	99.89	107.55			32.36	8.28	48.30	155	290	Peak
2483.5	47.79	55.39	54.00	-6.21	32.38	8.32	48.30	155	290	Average
2483.5	66.29	73.89	74.00	-7.71	32.38	8.32	48.30	155	290	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2462MHz: Fundamental frequency.



802.11n (40MHz)

CHANNEL	TX Channel 3	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	50.15	58.02	54.00	-3.85	32.29	8.15	48.31	105	80	Average
2390	63.47	71.34	74.00	-10.53	32.29	8.15	48.31	105	80	Peak
2422	87.50	95.28			32.32	8.21	48.31	105	80	Average
2422	98.93	106.71			32.32	8.21	48.31	105	80	Peak
2483.5	38.84	46.44	54.00	-15.16	32.38	8.32	48.30	105	80	Average
2483.5	53.89	61.49	74.00	-20.11	32.38	8.32	48.30	105	80	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	44.54	52.41	54.00	-9.46	32.29	8.15	48.31	160	295	Average
2390	60.58	68.45	74.00	-13.42	32.29	8.15	48.31	160	295	Peak
2422	85.51	93.29			32.32	8.21	48.31	160	295	Average
2422	97.64	105.42			32.32	8.21	48.31	160	295	Peak
2483.5	38.94	46.54	54.00	-15.06	32.38	8.32	48.30	160	295	Average
2483.5	53.48	61.08	74.00	-20.52	32.38	8.32	48.30	160	295	Peak

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 2422MHz: Fundamental frequency.



CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	43.31	51.18	54.00	-10.69	32.29	8.15	48.31	105	80	Average
2390	59.42	67.29	74.00	-14.58	32.29	8.15	48.31	105	80	Peak
2437	88.00	95.73			32.34	8.24	48.31	105	80	Average
2437	98.74	106.47			32.34	8.24	48.31	105	80	Peak
2485	50.21	57.80	54.00	-3.79	32.39	8.32	48.30	105	80	Average
2485	61.64	69.23	74.00	-12.36	32.39	8.32	48.30	105	80	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	40.27	48.14	54.00	-13.73	32.29	8.15	48.31	115	280	Average
2390	50.69	58.56	74.00	-23.31	32.29	8.15	48.31	115	280	Peak
2437	84.83	92.56			32.34	8.24	48.31	115	280	Average
2437	97.04	104.77			32.34	8.24	48.31	115	280	Peak
2485	49.80	57.39	54.00	-4.20	32.39	8.32	48.30	115	280	Average
2485	58.72	66.31	74.00	-15.28	32.39	8.32	48.30	115	280	Peak

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 2437MHz: Fundamental frequency.



CHANNEL	TX Channel 9	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	38.84	46.71	54.00	-15.16	32.29	8.15	48.31	102	70	Average
2390	52.09	59.96	74.00	-21.91	32.29	8.15	48.31	102	70	Peak
2452	87.94	95.63			32.35	8.26	48.30	102	70	Average
2452	99.32	107.01			32.35	8.26	48.30	102	70	Peak
2483.5	52.05	59.65	54.00	-1.95	32.38	8.32	48.30	102	70	Average
2483.5	68.69	76.29	74.00	-5.31	32.38	8.32	48.30	102	70	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	35.28	43.15	54.00	-18.72	32.29	8.15	48.31	112	280	Average
2390	47.41	55.28	74.00	-26.59	32.29	8.15	48.31	112	280	Peak
2452	84.64	92.33			32.35	8.26	48.30	112	280	Average
2452	96.06	103.75			32.35	8.26	48.30	112	280	Peak
2483.5	46.51	54.11	54.00	-7.49	32.38	8.32	48.30	112	280	Average
2483.5	61.58	69.18	74.00	-12.42	32.38	8.32	48.30	112	280	Peak

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 2452MHz: Fundamental frequency.



BELOW 1GHz WORST-CASE DATA:

9 KHz – 30 KHz data: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

30 MHz – 1GHz data:


BT-LE (GFSK)

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
97.9	23.69	51.40	43.50	-19.81	7.77	1.52	37.00	200	30	QP
161.92	26.12	50.75	43.50	-17.38	10.17	1.94	36.74	200	54	QP
187.14	31.95	56.52	43.50	-11.55	9.97	2.10	36.64	200	96	QP
222.06	31.82	54.95	46.00	-14.18	11.11	2.29	36.53	200	163	QP
334.58	25.54	44.80	46.00	-20.46	14.45	2.87	36.58	200	240	QP
464.56	23.85	39.40	46.00	-22.15	17.97	3.35	36.87	200	312	QP

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value






CHANNEL	TX Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
37.76	24.87	49.71	40.00	-15.13	11.75	0.91	37.50	100	15	QP
79.47	24.75	53.92	40.00	-15.25	6.62	1.37	37.16	100	248	QP
187.14	27.56	52.13	43.50	-15.94	9.97	2.10	36.64	100	148	QP
251.16	31.33	52.98	46.00	-14.67	12.41	2.46	36.52	100	64	QP
294.81	32.01	52.88	46.00	-13.99	12.94	2.69	36.50	100	180	QP
416.06	26.26	42.43	46.00	-19.74	17.39	3.20	36.76	100	84	QP

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value





ABOVE 1GHz TEST DATA:

Note: For higher frequency, the emission is too low to be detected.

BT-LE (GFSK)

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	32.10	39.97	54.00	-21.90	32.29	8.15	48.31	106	56	Average
2390	43.92	51.79	74.00	-30.08	32.29	8.15	48.31	106	56	Peak
2402	85.06	92.90			32.30	8.17	48.31	106	56	Average
2402	90.37	98.21			32.30	8.17	48.31	106	56	Peak
2483.5	32.19	39.79	54.00	-21.81	32.38	8.32	48.30	106	56	Average
2483.5	44.47	52.07	74.00	-29.53	32.38	8.32	48.30	106	56	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	32.15	40.02	54.00	-21.85	32.29	8.15	48.31	100	120	Average
2390	44.07	51.94	74.00	-29.93	32.29	8.15	48.31	100	120	Peak
2402	85.89	93.73			32.30	8.17	48.31	100	120	Average
2402	91.20	99.04			32.30	8.17	48.31	100	120	Peak
2483.5	32.46	40.06	54.00	-21.54	32.38	8.32	48.30	100	120	Average
2483.5	45.10	52.70	74.00	-28.90	32.38	8.32	48.30	100	120	Peak

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 2402MHz: Fundamental frequency.



CHANNEL	TX Channel 19	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	32.16	40.03	54.00	-21.84	32.29	8.15	48.31	105	100	Average
2390	43.98	51.85	74.00	-30.02	32.29	8.15	48.31	105	100	Peak
2440	88.68	96.41			32.34	8.24	48.31	105	100	Average
2440	94.23	101.96			32.34	8.24	48.31	105	100	Peak
2483.5	32.22	39.82	54.00	-21.78	32.38	8.32	48.30	105	100	Average
2483.5	44.93	52.53	74.00	-29.07	32.38	8.32	48.30	105	100	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	32.24	40.11	54.00	-21.76	32.29	8.15	48.31	112	120	Average
2390	44.11	51.98	74.00	-29.89	32.29	8.15	48.31	112	120	Peak
2440	89.38	97.11			32.34	8.24	48.31	112	120	Average
2440	94.28	102.01			32.34	8.24	48.31	112	120	Peak
2483.5	32.23	39.83	54.00	-21.77	32.38	8.32	48.30	112	120	Average
2483.5	45.62	53.22	74.00	-28.38	32.38	8.32	48.30	112	120	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2440MHz: Fundamental frequency.



CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	32.07	39.94	54.00	-21.93	32.29	8.15	48.31	150	56	Average
2390	44.25	52.12	74.00	-29.75	32.29	8.15	48.31	150	56	Peak
2480	89.27	96.88			32.38	8.31	48.30	150	56	Average
2480	94.52	102.13			32.38	8.31	48.30	150	56	Peak
2483.5	32.52	40.12	54.00	-21.48	32.38	8.32	48.30	150	56	Average
2483.5	45.05	52.65	74.00	-28.95	32.38	8.32	48.30	150	56	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	32.28	40.15	54.00	-21.72	32.29	8.15	48.31	110	140	Average
2390	45.39	53.26	74.00	-28.61	32.29	8.15	48.31	110	140	Peak
2480	90.52	98.13			32.38	8.31	48.30	110	140	Average
2480	95.71	103.32			32.38	8.31	48.30	110	140	Peak
2483.5	32.66	40.26	54.00	-21.34	32.38	8.32	48.30	110	140	Average
2483.5	45.08	52.68	74.00	-28.92	32.38	8.32	48.30	110	140	Peak

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 2480MHz: Fundamental frequency.



4.3 6 dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Power Sensor	Keysight	U2021XA	MY55060016	May 04,16	May 03,17
Power Sensor	Keysight	U2021XA	MY55060018	May 04,16	May 03,17
10dB Attenuator	JFW/USA	50HF-010-SMA	1505	Jul. 27, 16	Jul. 26, 17
Digital Multimeter	FLUKE	15B	A1220010DG	Oct. 13, 16	Oct.12, 17
Humid & Temp Programmable Tester	Haida	HD-2257	110807201	Sep.05,16	Sep. 04,17
Oscilloscope	Agilent	DSO9254A	MY51260160	Nov. 04,16	Nov. 03,17
Signal Analyzer	Rohde & Schwarz	FSV7	102331	Nov. 04,16	Nov. 03,17
Signal Generator	Agilent	N5183A	MY50140980	Nov. 04,16	Nov. 03,17
Agile Signal Generator	Agilent	8645A	Agilent	Aug.08, 16	Aug.07, 17
ESG Vector Signal Generator	Agilent	E4438C	MY49072505	Apr. 22, 16	Apr. 21, 17
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	Aug.08, 16	Aug. 07, 17

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in RF Oven room.

4.3.3 TEST PROCEDURE


1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) ≥ 3 RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



4.3.4 DEVIATION FROM TEST STANDARD

No deviation.

4.3.5 TEST SETUP



4.3.6 EUT OPERATING CONDITIONS


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



4.3.7 TEST RESULTS

802.11b

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	8.56	0.5	PASS
6	2437	9.03	0.5	PASS
11	2462	9.04	0.5	PASS






BUREAU VERITAS

Test Report No.: RF170103W004-2

802.11g

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	16.31	0.5	PASS
6	2437	16.34	0.5	PASS
11	2462	16.36	0.5	PASS






BUREAU VERITAS

Test Report No.: RF170103W004-2

802.11n (20MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	17.18	0.5	PASS
6	2437	17.57	0.5	PASS
11	2462	17.57	0.5	PASS






**BUREAU
VERITAS**

Test Report No.: RF170103W004-2

802.11n (40MHz)


CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
3	2422	35.43	0.5	PASS
6	2437	35.17	0.5	PASS
9	2452	35.38	0.5	PASS





BT-LE (GFSK)

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	0.66	0.5	PASS
19	2440	0.65	0.5	PASS
39	2480	0.67	0.5	PASS






4.4 CONDUCTED OUTPUT POWER

4.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz band: 1 Watt (30dBm)

4.4.2 TEST SETUP



4.4.3 TEST INSTRUMENTS

Refer to section 4.3.2 to get information of above instrument.

4.4.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

4.4.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



4.4.7 TEST RESULTS

4.4.7.1 MAXIMUM PEAK OUTPUT POWER

802.11b

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT(W)	PASS/FAIL
1	2412	19.31	85.310	1	PASS
6	2437	20.70	117.490	1	PASS
11	2462	20.41	109.901	1	PASS

802.11g

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT(W)	PASS/FAIL
1	2412	22.76	188.799	1	PASS
6	2437	23.50	223.872	1	PASS
11	2462	21.09	128.529	1	PASS

802.11n (20MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT(W)	PASS/FAIL
1	2412	22.93	196.336	1	PASS
6	2437	23.18	207.970	1	PASS
11	2462	21.33	135.831	1	PASS

802.11n (40MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT(W)	PASS/FAIL
3	2422	21.76	149.968	1	PASS
6	2437	22.51	178.238	1	PASS
9	2452	19.11	81.470	1	PASS



BT-LE (GFSK)

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT(W)	PASS/FAIL
0	2402	2.22	1.667	1	PASS
19	2440	2.48	1.770	1	PASS
39	2480	0.96	1.247	1	PASS



4.4.7.2 AVERAGE OUTPUT POWER (FOR REFERENCE)

The average power sensor was used on the output port of the EUT. A power meter was used to read the response of the power sensor. Record the power level.

802.11b

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
1	2412	16.29	N/A
6	2437	17.69	N/A
11	2462	17.35	N/A

802.11g

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
1	2412	14.76	N/A
6	2437	15.50	N/A
11	2462	13.08	N/A

802.11n (20MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
1	2412	14.82	N/A
6	2437	15.35	N/A
11	2462	13.18	N/A

802.11n (40MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
3	2422	13.55	N/A
6	2437	14.25	N/A
9	2452	10.55	N/A



**BUREAU
VERITAS**

Test Report No.: RF170103W004-2

BT-LE (GFSK)

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
0	2402	0.61	N/A
19	2440	0.85	N/A
39	2480	-0.58	N/A




4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm/3KHz.

4.5.2 TEST SETUP



4.5.3 TEST INSTRUMENTS

Refer to section 4.3.2 to get information of above instrument.

4.5.4 TEST PROCEDURE

1. Set the span to 1.5 times the DTS bandwidth
2. Set the RBW = 3 kHz, VBW \geq 3 x RBW, Detector = peak.
3. Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
4. Use the peak marker function to determine the maximum amplitude level.

4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

4.5.6 EUT OPERATING CONDITION


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



4.5.7 TEST RESULTS

802.11b

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-6.42	8	PASS
6	2437	-4.81	8	PASS
11	2462	-5.41	8	PASS






**BUREAU
VERITAS**

Test Report No.: RF170103W004-2

802.11g

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-10.58	8	PASS
6	2437	-10.46	8	PASS
11	2462	-12.86	8	PASS






**BUREAU
VERITAS**

Test Report No.: RF170103W004-2

802.11n (20MHz)

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-11.43	8	PASS
6	2437	-10.69	8	PASS
11	2462	-12.16	8	PASS






**BUREAU
VERITAS**

Test Report No.: RF170103W004-2

802.11n (40MHz)

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
3	2422	-14.55	8	PASS
6	2437	-13.95	8	PASS
9	2452	-18.51	8	PASS






**BUREAU
VERITAS**

Test Report No.: RF170103W004-2

BT-LE (GFSK)

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
0	2402	-16.90	8	PASS
19	2440	-13.19	8	PASS
39	2480	-16.09	8	PASS






4.6 OUT OF BAND EMISSION MEASUREMENT

4.6.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST SETUP



4.6.3 TEST INSTRUMENTS

Refer to section 4.3.2 to get information of above instrument.

4.6.4 TEST PROCEDURE

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW \geq 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.



MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW \geq 300 kHz.
3. Set span to encompass the spectrum to be examined
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

4.6.5 DEVIATION FROM TEST STANDARD

No deviation.

4.6.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.6.7 TEST RESULTS

The spectrum plots are attached on the following images. D1 line indicates the highest level. D2 line indicates the 20dB offset below D1. It shows compliance to the requirement.





BUREAU VERITAS



Test Report No.: RF170103W004-2

802.11b



CH 1



CH 6



CH 11







**BUREAU
VERITAS**

Test Report No.: RF170103W004-2

CH 1 Band Edge



CH 11 Band Edge






BUREAU VERITAS


Test Report No.: RF170103W004-2

802.11g


CH 1



CH 6




CH 11





**BUREAU
VERITAS**

Test Report No.: RF170103W004-2







BUREAU VERITAS



Test Report No.: RF170103W004-2

802.11n (20MHz)



CH 1



CH 6



CH 11







BUREAU VERITAS

Test Report No.: RF170103W004-2

CH 1 Band Edge



CH 11 Band Edge







BUREAU VERITAS



Test Report No.: RF170103W004-2

802.11n (40MHz)



CH 3



CH 6




CH 9





BUREAU VERITAS

Test Report No.: RF170103W004-2



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City, Guangdong 523942, China

Tel: +86 769 8593 5656
 Fax: +86 769 8593 1080
 Email: customerservice.dg@cn.bureauveritas.com





BUREAU VERITAS



Test Report No.: RF170103W004-2

BT-LE (GFSK)



CH 0



CH 19




CH 39





**BUREAU
VERITAS**

Test Report No.: RF170103W004-2





5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---