

LIST OF EXHIBITS

|      | DESCRIPTION                                           | EXHIBIT | REFERENCE   |
|------|-------------------------------------------------------|---------|-------------|
| I.   | Identification Label Information                      | 1       | 2.983-(f)   |
|      | General Information                                   | 1A      |             |
|      | 1. Production Plans                                   |         | 2.981-(a)   |
|      | 2. Application References                             |         | 2.1061      |
|      | 3. Data Submittal Procedure                           |         |             |
| II.  | Certification of Data                                 | 2       |             |
| III. | External Photographs                                  | 3       | 2.983-(g)   |
| IV.  | Circuit Descriptions                                  | 4       |             |
|      | 1. Means for Frequency Stabilization                  | 4A      |             |
|      | 2. Means for Limiting Modulation                      |         | 4B          |
|      | 3. Means for Attenuation of Higher Audio Frequencies  | 4C      |             |
|      | 4. Means for Attenuation of Spurious Emissions        | 4D      |             |
|      | 5. Means for Limiting Power Output                    | 4E      |             |
|      | 6. Modulation Techniques                              | 4F      |             |
|      | 7. Means for Controlling Transient Frequency Behavior | 4G      |             |
| V.   | Schematic Diagrams                                    | 5       | 2.983-(d)-7 |
|      | 1. Transmitter Audio, PL/DPL/DTMF Generation          | 5A      |             |
|      | 2. Microprocessor/Controller                          | 5B      |             |
|      | 3. Fractional-N Synthesizer, Reference Oscillator     | 5C      |             |
|      | 4. Voltage-Controlled Oscillators and Buffers         | 5D      |             |
|      | 5. RF Power Amp, Low-Pass Filter, Antenna Switch      | 5E      |             |
|      | 6. Transmitter Power Control                          | 5F      |             |
| VI.  | Test Report                                           | 6       |             |
|      | 1. Data Index                                         | 6       |             |
|      | 2. RF Output Data                                     | 6A      | 2.985       |
|      | 3. Modulation Characteristics                         |         | 2.987       |
|      | A. Audio Response & Low Pass Filter Response          | 6B, 6C  |             |
|      | B. Modulation Limiting                                | 6D      |             |
|      | 4. Occupied Bandwidth                                 | 6E      | 2.989       |
|      | 5. Conducted Spurious Emissions                       | 6F      | 2.991       |
|      | 6. Radiated Spurious Emissions                        | 6G      | 2.993       |
|      | 7. Frequency Stability                                |         |             |
|      | A. Frequency Stability vs. Temperature                | 6H-1    | 2.995       |
|      | B. Frequency Stability vs. Voltage                    | 6H-2    | 2.995       |

**LIST OF EXHIBITS (CONTINUED)**

|       | DESCRIPTION                                         | EXHIBIT | REFERENCE                  |
|-------|-----------------------------------------------------|---------|----------------------------|
| VII.  | Test Set-up Procedures                              | 7       | 2.999                      |
| VIII. | Instruction Manual                                  | 8       | 2.983-(d)-8                |
| IX.   | Internal Photographs                                | 9       | 2.983-(g)                  |
| X.    | Parts List and Tune Up Procedures                   | 10      | 2-983-(d)-6, 9             |
|       | 1. Function of RF Semiconductors & Active Devices   | 10A     |                            |
|       | 2. List of Recommended Test Equipment for Servicing | 10B     |                            |
|       | 3. Tune Up Information                              | 10C     |                            |
| XI.   | RF Exposure Information                             | 11      | 2.1093                     |
| XII.  | Operational Description                             | 12      | 2.983-(d)-1, 2,<br>3, 4, 5 |
|       | 1. Technical Characteristics                        |         |                            |
|       | 2. Application                                      |         |                            |
| XIII. | Cover Letter                                        | 13      |                            |

**IDENTIFICATION LABEL**

LOCATION

A nameplate of the type presented below will be affixed to every transmitter. It will be placed on the outside of the housing at the bottom back of the transmitter.

TYPE

The label is a paper polyester film laminate with a pressure sensitive adhesive backing. The adhesive is a permanent type acrylic with a minimum peel strength of 40 oz/inch.

**MODEL : AAM25BKD9AA2AN**  
**FCC ID : AZ492FT1627**  
**CAN TYPE :**  
**2 YEAR WARRANTY**  
**Covered by one or more US patents**  
**See operator manual.**  
**Made in Malaysia by MOTOROLA**  


**EXHIBIT 1A - GENERAL INFORMATION**

1. Production Plans -- Pursuant 2.981 (c)

Quantity production is planned.

2. Application References:

EIA/TIA-603 Land Mobile FM or PM Communications Equipment Measurement and Performance Standards

Code of Federal Regulations Title 47, Part 2, Sec. 2.983-2.999 and Part 90, Sec.90.210

3. Data Submittal Procedure:

Data is supplied in accordance with Part 2, Sub-part J of the Commissions' rules.

The intended use of this transceiver includes applications covered in the Code of Federal Regulations Title 47, Parts 22 and 90. Transmitter power shall not exceed 60 watts for use in applications covered by Part 22, and this power level shall **not** be adjustable by the user.