



25th July 2006

Authorization & Evaluation Division
Federal Communications Commission Laboratory
7435 Oakland Mills Road
Columbia, MD 21046

Subject: Application for Certification of transmitter with FCC ID: AZ492FT5854.

Gentlemen;

Motorola Inc., 8000 West Sunrise Boulevard, Fort Lauderdale, Florida 33322, herein submits its application for Certification of the transmitter with FCC ID: AZ492FT5854. This variable output power (0.062 to 490 milliwatt) transmitter is part of a handheld transceiver used in a SMR and EA SMR trunking system operating in the United States 806-821/851-866MHz and 896-901/935-940 MHz frequency band. Certification is sought for this transceiver, and performance data is provided for that purpose.

Motorola Inc., 8000 West Sunrise Boulevard, Fort Lauderdale, Florida 33322, herein submits its application for Certification of the transmitter with FCC ID AZ489FT5854. This variable output power (490 and to 427 milliWatt) transmitter is part of a mobile transceiver used in a SMR and EA SMR trunking system operating in the United States 806-821/851-866MHz frequency band.

The first transceiver is of the receive-first type described in International Telecommunications Union Recommendation ITU-R M.1221 entitled Technical And Operational Requirements For Cellular Multimode Mobile Radio Stations. It must first find, acquire and lock onto a control channel from a predefined set of control channel frequencies assigned to a companion Authorized base station (e.g. – FCC ID: AZ492FT5854). Transmission is not possible until lock to a base station control channel has been achieved, then transmission is limited to digitally modulated service request bursts on the reverse control channel. Upon recognition of a proper request, the control channel base station transmitter will then assign the transceiver a traffic channel for transmission of digital voice or circuit-switched data from the set of frequencies for which the trunking system is licensed. Attached Exhibit 12 provides additional descriptive details.

To facilitate global roaming it is kindly requested that a note be provided in the Grant for Equipment Authorization, which states that this 'receive first' type of equipment is compliant for transmitter operation over the broader range 806-825 MHz when used with a compatible Authorized Base Station. This will aid equipment authorization in foreign countries, which accept a United States FCC Grant for Equipment Authorization, yet not jeopardize United States public safety or cellular systems licensed to operate in the 821-825 MHz frequency band since no compatible base station may be authorized on those frequencies in the United States.

It is also expected that this transceiver type will be marketed outside the United States and brought into the United States for itinerant "roaming" operation on compatible 806 - 821 MHz base stations located within the United States. Consequently, upon receipt of Authorization, only those units of this equipment type authorized for marketing in countries outside the United States will also bear a label with the specified FCC identifier.

In accordance with 47 CFR 2.1093(c) this transmitter may be used in "covered" SMR service so it has been subjected to routine environmental evaluation for RF exposure and found to be compliant with the limits specified in 47 CFR 2.1093(d)(2).

The subject transmitter complies with 47 CFR 90.203 of the rules in that the operator cannot directly program transmit frequencies using only the unit's normally accessible external controls.

Enclosed is a complete Certification Application comprised of 12 Exhibits. Contact me at (954) 723-5793 if you require any additional information.

Sincerely,

/s/ Mike Ramnath (signed)

Manager, Regulatory Compliance

Email: Mike.Ramnath@motorola.com