

	 	  <p style="color: blue; font-weight: bold; font-size: small;">CERTIFICATE 2518.05</p>
---	---	--


DECLARATION OF COMPLIANCE: MPE ASSESSMENT PCII Report Part 2 of 2

<p style="text-align: center;">Motorola Solutions Inc. EME Test Laboratory Motorola Solutions Malaysia Sdn Bhd Plot 2A, Medan Bayan Lepas, Mukim 12 SWD 11900 Bayan Lepas Penang, Malaysia.</p>	<p>Date of Report: 4/23/2020 Report Revision: B</p>
---	--

Responsible Engineer:	Saw Sun Hock (EME Engineer)
Report author:	Saw Sun Hock (EME Engineer)
Date(s) Tested:	2/17/2017-3/17/2017; 4/23/2019 - 4/24/2019, 5/7/2019, 5/9/2019, 5/13/2019 - 5/14/2019, 5/29/2019
Manufacturer:	Futurecom Systems Group (DVR), Motorola Solutions. Inc (Mobile)
Date submitted for test:	01/13/2017; 04/12/2019
DUT Description:	APX6500 7/800 MHz: Multiple HW Encryption WiFi Interoperability Data Modem Tethering via WiFi or Cable Companion Device: DVR 700 (764-776 MHz; 794-806MHz), Digital Vehicular Repeater
Test TX mode(s):	CW
Max. Power output:	APX6500 7/800 MHz: 36W (762-805 MHz), 42W (806-870 MHz); 11.22 mW (Bluetooth); 6.3 mW (Bluetooth LE); 39.8 mW (WLAN 2.4GHz 802.11b), 15.8 mW (WLAN 2.4GHz 802.11g), 12.6mW (WLAN 2.4GHz 802.11n); 15.8mW (WLAN 5GHz 802.11a/n/ac) Companion Device: 5W (DVR 700)
TX Frequency Bands:	APX6500 7/800 MHz: 762-806 MHz; 806-870 MHz; WLAN 2412-2462 MHz; WLAN 5180-5825 MHz; BT 2402-2480 MHz Companion Device: 764-776 MHz; 794-806MHz
Signaling type:	FM, TDMA, FHSS (Bluetooth), 802.11b/g/n (WLAN 2.4 GHz), 802.11 a/n/ac (WLAN 5 GHz)
Model(s) Tested:	APX6500 7/800 MHz: M25URS9PW1BN (PMUF1969A) Companion Device: MOBEXCOM DVRS 700 (DQPMDVR7000P)
Model(s) Certified:	M25URS9PW1BN (PMUF1969A), MOBEXCOM DVRS 700 (DQPMDVR7000P)
Serial Number(s):	471TVF3314 (APX6500 7/800MHz) , 16092663 (DVR 700)
Classification:	Occupational/Controlled Environment
Applicant Name:	Motorola Solutions Inc.
Applicant Address:	8000 West Sunrise Boulevard, Fort Lauderdale, Florida 33322
FCC ID:	APX6500 7/800 MHz: AZ492FT7124 (769-775 MHz, 799-824 MHz, 851-869 MHz, 2402-2480 MHz, 2412-2462 MHz; 5180-5825 MHz) Companion Device: LO6-DVRS700 (769-775 MHz; 799-806MHz) This report contains results that are immaterial for FCC equipment approval, which are clearly identified.
IC:	APX6500 7/800 MHz: 109U-92FT7124 Companion Device: 2098B-DVRS700 This report contains results that are immaterial for ISED Canada equipment approval, which are clearly identified.

The MPE results clearly demonstrate compliance with FCC Occupational/Controlled RF Exposure limits. FCC rules require compliance for Passengers and Bystanders to the FCC General Population/Uncontrolled limits.

Based on the information and the testing results provided herein, the undersigned certifies that when used as stated in the operating instructions supplied, said product complies with the national and international reference standards and guidelines listed in section 4.0 of this report (no deviation from standard methods). This report shall not be reproduced without written approval from an officially designated representative of the Motorola Solutions Inc. EME Laboratory. I attest to the accuracy of the data and assume full responsibility for the completeness of these measurements. This reporting format is consistent with the suggested guidelines of the TIA TSB-159 April 2006
 The results and statements contained in this report pertain only to the device(s) evaluated herein.

 Tiong Nguk Ing Deputy Technical Manager (Approved Signatory) Approval Date: 4/23/2020	
--	--

Appendix D – MPE Test Results Summary for APX6500 7/800MHz

Table D.1

MPE assessment for APX6500 7/800MHz - roof mounted antenna – Bystander

Note:

Blue fonts: Frequencies not regulated by FCC.

Trunk / Roof	Test Post.	E/H Field	Antenna No.	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm ²)	FCC Limit	% To FCC Spec Limit	ISED Limit	% To ISED Spec Limit
Roof	BS1	E	1	HAF4013A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.04	0.51	8.4	0.24	17.5
						35.2	769.0125	0.04	0.51	8.4	0.25	17.5
						35.0	772.0000	0.05	0.51	9.2	0.25	19.1
						34.9	774.9875	0.04	0.52	8.2	0.25	17.1
						34.6	794.0125	0.05	0.53	9.3	0.25	19.6
					35.5	799.0125	0.05	0.53	9.6	0.25	20.3	
					42	42.0	811.5000	0.04	0.54	7.3	0.25	15.6
						40.8	823.9875	0.04	0.55	6.8	0.26	14.5
						41.8	851.0125	0.03	0.57	5.1	0.26	11.0
						41.1	860.5000	0.04	0.57	6.9	0.27	14.8
41.1	868.9875	0.03	0.58	5.4		0.27	11.8					
Roof	BS2	E	1	HAF4013A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.03	0.51	5.9	0.24	12.2
						35.2	769.0125	0.03	0.51	5.9	0.25	12.2
						35.0	772.0000	0.03	0.51	5.9	0.25	12.3
						34.9	774.9875	0.03	0.52	5.2	0.25	11.0
						34.6	794.0125	0.03	0.53	5.2	0.25	10.9
					35.5	799.0125	0.03	0.53	4.9	0.25	10.4	
					42	42.0	811.5000	0.02	0.54	4.4	0.25	9.3
						40.8	823.9875	0.03	0.55	5.4	0.26	11.6
						41.8	851.0125	0.03	0.57	5.0	0.26	10.7
						41.1	860.5000	0.03	0.57	5.7	0.27	12.3
41.1	868.9875	0.03	0.58	4.5		0.27	9.7					

Table D.1 (Continued)

MPE assessment for APX6500 7/800MHz - roof mounted antenna – Bystander

Note:

Blue fonts: Frequencies not regulated by FCC.

Trunk / Roof	Test Post.	E/H Field	Antenna No.	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm ²)	FCC Limit	% To FCC Spec Limit	ISED Limit	% To ISED Spec Limit
Roof	BS3	E	1	HAF4013A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.01	0.51	2.3	0.24	4.8
						35.2	769.0125	0.01	0.51	2.3	0.25	4.8
						35.0	772.0000	0.01	0.51	2.2	0.25	4.7
						34.9	774.9875	0.01	0.52	1.9	0.25	4.1
						34.6	794.0125	0.02	0.53	2.9	0.25	6.2
					35.5	799.0125	0.02	0.53	2.8	0.25	6.0	
					42	42.0	811.5000	0.01	0.54	2.5	0.25	5.2
						40.8	823.9875	0.02	0.55	2.9	0.26	6.1
						41.8	851.0125	0.01	0.57	2.3	0.26	5.1
						41.1	860.5000	0.01	0.57	2.3	0.27	4.9
41.1	868.9875	0.01	0.58	2.5		0.27	5.4					
Roof	BS4	E	1	HAF4013A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.01	0.51	1.4	0.24	2.9
						35.2	769.0125	0.01	0.51	1.4	0.25	2.9
						35.0	772.0000	0.01	0.51	1.3	0.25	2.7
						34.9	774.9875	0.01	0.52	1.3	0.25	2.8
						34.6	794.0125	0.01	0.53	1.2	0.25	2.5
					35.5	799.0125	0.01	0.53	1.2	0.25	2.4	
					42	42.0	811.5000	0.01	0.54	1.0	0.25	2.1
						40.8	823.9875	0.01	0.55	1.2	0.26	2.6
						41.8	851.0125	0.01	0.57	1.1	0.26	2.3
						41.1	860.5000	0.01	0.57	1.4	0.27	3.1
41.1	868.9875	0.01	0.58	1.1		0.27	2.5					

Table D.1 (Continued)

MPE assessment for APX6500 7/800MHz - roof mounted antenna – Bystander

Note:

Blue fonts: Frequencies not regulated by FCC.

Results in bold font are configurations with highest percentage of limits.

Trunk / Roof	Test Post.	E/H Field	Antenna No.	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm ²)	FCC Limit	% To FCC Spec Limit	ISED Limit	% To ISED Spec Limit
Roof	BS5	E	1	HAF4013A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.01	0.51	1.1	0.24	2.2
						35.2	769.0125	0.01	0.51	1.1	0.25	2.2
						35.0	772.0000	0.01	0.51	1.4	0.25	2.9
						34.9	774.9875	0.01	0.52	1.4	0.25	3.0
						34.6	794.0125	0.01	0.53	1.5	0.25	3.1
					35.5	799.0125	0.01	0.53	1.9	0.25	3.9	
					42	42.0	811.5000	0.01	0.54	1.8	0.25	3.9
						40.8	823.9875	0.01	0.55	1.0	0.26	2.2
						41.8	851.0125	0.004	0.57	0.7	0.26	1.6
						41.1	860.5000	0.01	0.57	0.9	0.27	1.9
41.1	868.9875	0.004	0.58	0.7		0.27	1.5					
Roof	BS1	E	2	HAF4014A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.03	0.51	5.8	0.24	12.1
						35.2	769.0125	0.03	0.51	5.8	0.25	12.1
						35.0	772.0000	0.03	0.51	6.6	0.25	13.7
						34.9	774.9875	0.03	0.52	6.2	0.25	13.0
						34.6	794.0125	0.05	0.53	8.7	0.25	18.4
					35.5	799.0125	0.05	0.53	9.7	0.25	20.5	
					42	42.0	811.5000	0.04	0.54	7.9	0.25	16.8
						40.8	823.9875	0.04	0.55	6.7	0.26	14.4
						41.8	851.0125	0.02	0.57	4.1	0.26	8.9
						41.1	860.5000	0.03	0.57	5.0	0.27	10.8
41.1	868.9875	0.03	0.58	4.4		0.27	9.6					

Table D.1 (Continued)

MPE assessment for APX6500 7/800MHz - roof mounted antenna – Bystander

Note:

Blue fonts: Frequencies not regulated by FCC.

Trunk / Roof	Test Post.	E/H Field	Antenna No.	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm ²)	FCC Limit	% To FCC Spec Limit	ISED Limit	% To ISED Spec Limit
Roof	BS2	E	2	HAF4014A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.02	0.51	3.5	0.24	7.2
						35.2	769.0125	0.02	0.51	3.3	0.25	7.0
						35.0	772.0000	0.02	0.51	3.6	0.25	7.6
						34.9	774.9875	0.02	0.52	3.8	0.25	8.0
						34.6	794.0125	0.02	0.53	3.9	0.25	8.2
					35.5	799.0125	0.02	0.53	4.0	0.25	8.4	
					42	42.0	811.5000	0.02	0.54	3.6	0.25	7.7
						40.8	823.9875	0.03	0.55	5.3	0.26	11.2
						41.8	851.0125	0.03	0.57	4.7	0.26	10.1
						41.1	860.5000	0.03	0.57	5.1	0.27	11.1
41.1	868.9875	0.02	0.58	3.7		0.27	8.1					
Roof	BS3	E	2	HAF4014A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.01	0.51	1.4	0.24	2.9
						35.2	769.0125	0.01	0.51	1.4	0.25	2.9
						35.0	772.0000	0.01	0.51	1.4	0.25	3.0
						34.9	774.9875	0.01	0.52	1.3	0.25	2.6
						34.6	794.0125	0.02	0.53	3.4	0.25	7.2
					35.5	799.0125	0.02	0.53	3.4	0.25	7.2	
					42	42.0	811.5000	0.02	0.54	4.6	0.25	9.8
						40.8	823.9875	0.02	0.55	4.2	0.26	8.9
						41.8	851.0125	0.02	0.57	3.9	0.26	8.4
						41.1	860.5000	0.02	0.57	3.0	0.27	6.5
41.1	868.9875	0.02	0.58	3.7		0.27	8.1					

Table D.1 (Continued)

MPE assessment for APX6500 7/800MHz - roof mounted antenna – Bystander

Note:

Blue fonts: Frequencies not regulated by FCC.

Trunk / Roof	Test Post.	E/H Field	Antenna No.	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm ²)	FCC Limit	% To FCC Spec Limit	ISED Limit	% To ISED Spec Limit
Roof	BS4	E	2	HAF4014A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.004	0.51	0.9	0.24	1.8
						35.2	769.0125	0.004	0.51	0.9	0.25	1.8
						35.0	772.0000	0.004	0.51	0.8	0.25	1.8
						34.9	774.9875	0.01	0.52	1.2	0.25	2.5
						34.6	794.0125	0.01	0.53	1.4	0.25	3.0
					35.5	799.0125	0.01	0.53	1.3	0.25	2.7	
					42	42.0	811.5000	0.01	0.54	1.3	0.25	2.8
						40.8	823.9875	0.01	0.55	1.7	0.26	3.7
						41.8	851.0125	0.01	0.57	2.1	0.26	4.6
						41.1	860.5000	0.01	0.57	2.4	0.27	5.2
41.1	868.9875	0.01	0.58	1.8		0.27	3.8					
Roof	BS5	E	2	HAF4014A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.004	0.51	0.8	0.24	1.8
						35.2	769.0125	0.004	0.51	0.8	0.25	1.7
						35.0	772.0000	0.01	0.51	1.3	0.25	2.7
						34.9	774.9875	0.01	0.52	1.3	0.25	2.8
						34.6	794.0125	0.01	0.53	1.8	0.25	3.8
					35.5	799.0125	0.01	0.53	2.7	0.25	5.6	
					42	42.0	811.5000	0.01	0.54	2.2	0.25	4.7
						40.8	823.9875	0.01	0.55	2.2	0.26	4.6
						41.8	851.0125	0.01	0.57	1.4	0.26	3.0
						41.1	860.5000	0.01	0.57	1.4	0.27	2.9
41.1	868.9875	0.01	0.58	1.3		0.27	2.8					

Table D.1 (Continued)

MPE assessment for APX6500 7/800MHz - roof mounted antenna – Bystander

Note:

Blue fonts: Frequencies not regulated by FCC.

Trunk / Roof	Test Post.	E/H Field	Antenna No.	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm ²)	FCC Limit	% To FCC Spec Limit	ISED Limit	% To ISED Spec Limit
Roof	BS1	E	3	HAF4016A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.04	0.51	8.2	0.24	17.1
						35.2	769.0125	0.04	0.51	8.1	0.25	16.9
						35.0	772.0000	0.04	0.51	8.1	0.25	17.0
						34.9	774.9875	0.04	0.52	8.0	0.25	16.8
						34.6	794.0125	0.05	0.53	9.2	0.25	19.4
					35.5	799.0125	0.05	0.53	9.7	0.25	20.5	
					42	42.0	811.5000	0.04	0.54	7.4	0.25	15.6
						40.8	823.9875	0.04	0.55	6.8	0.26	14.5
						41.8	851.0125	0.03	0.57	4.6	0.26	9.9
						41.1	860.5000	0.04	0.57	6.2	0.27	13.5
41.1	868.9875	0.03	0.58	4.9		0.27	10.6					
Roof	BS2	E	3	HAF4016A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.03	0.51	5.6	0.24	11.7
						35.2	769.0125	0.03	0.51	5.6	0.25	11.7
						35.0	772.0000	0.03	0.51	5.6	0.25	11.7
						34.9	774.9875	0.03	0.52	5.0	0.25	10.5
						34.6	794.0125	0.03	0.53	5.0	0.25	10.6
					35.5	799.0125	0.03	0.53	4.7	0.25	10.0	
					42	42.0	811.5000	0.02	0.54	3.9	0.25	8.4
						40.8	823.9875	0.03	0.55	5.0	0.26	10.7
						41.8	851.0125	0.02	0.57	4.1	0.26	8.9
						41.1	860.5000	0.03	0.57	4.8	0.27	10.3
41.1	868.9875	0.02	0.58	3.7		0.27	8.0					

Table D.1 (Continued)

MPE assessment for APX6500 7/800MHz - roof mounted antenna – Bystander

Note:

Blue fonts: Frequencies not regulated by FCC.

Trunk / Roof	Test Post.	E/H Field	Antenna No.	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm ²)	FCC Limit	% To FCC Spec Limit	ISED Limit	% To ISED Spec Limit
Roof	BS3	E	3	HAF4016A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.01	0.51	2.4	0.24	5.0
						35.2	769.0125	0.01	0.51	2.4	0.25	5.0
						35.0	772.0000	0.01	0.51	2.4	0.25	5.0
						34.9	774.9875	0.01	0.52	2.1	0.25	4.5
						34.6	794.0125	0.02	0.53	2.9	0.25	6.2
					35.5	799.0125	0.01	0.53	2.7	0.25	5.8	
					42	42.0	811.5000	0.01	0.54	2.5	0.25	5.3
						40.8	823.9875	0.02	0.55	3.0	0.26	6.3
						41.8	851.0125	0.01	0.57	2.1	0.26	4.6
						41.1	860.5000	0.01	0.57	2.4	0.27	5.1
41.1	868.9875	0.01	0.58	2.5		0.27	5.3					
Roof	BS4	E	3	HAF4016A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.01	0.51	1.5	0.24	3.1
						35.2	769.0125	0.01	0.51	1.5	0.25	3.0
						35.0	772.0000	0.01	0.51	1.3	0.25	2.8
						34.9	774.9875	0.01	0.52	1.5	0.25	3.0
						34.6	794.0125	0.01	0.53	1.2	0.25	2.5
					35.5	799.0125	0.01	0.53	1.2	0.25	2.6	
					42	42.0	811.5000	0.005	0.54	0.9	0.25	2.0
						40.8	823.9875	0.01	0.55	1.1	0.26	2.4
						41.8	851.0125	0.01	0.57	1.1	0.26	2.3
						41.1	860.5000	0.01	0.57	1.3	0.27	2.9
41.1	868.9875	0.01	0.58	1.1		0.27	2.4					

Table D.1 (Continued)

MPE assessment for APX6500 7/800MHz - roof mounted antenna – Bystander

Note:

Blue fonts: Frequencies not regulated by FCC.

Trunk / Roof	Test Post.	E/H Field	Antenna No.	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm ²)	FCC Limit	% To FCC Spec Limit	ISED Limit	% To ISED Spec Limit
Roof	BS5	E	3	HAF4016A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.01	0.51	1.4	0.24	3.0
						35.2	769.0125	0.01	0.51	1.4	0.25	2.9
						35.0	772.0000	0.01	0.51	1.9	0.25	3.9
						34.9	774.9875	0.01	0.52	1.9	0.25	3.9
						34.6	794.0125	0.01	0.53	1.7	0.25	3.5
					35.5	799.0125	0.01	0.53	2.1	0.25	4.5	
					42	42.0	811.5000	0.01	0.54	1.4	0.25	3.1
						40.8	823.9875	0.01	0.55	1.3	0.26	2.8
						41.8	851.0125	0.004	0.57	0.8	0.26	1.6
						41.1	860.5000	0.01	0.57	0.9	0.27	2.0
41.1	868.9875	0.004	0.58	0.7		0.27	1.6					
Roof	BS1	E	4	HAF4017A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.05	0.51	9.2	0.24	19.2
						35.2	769.0125	0.05	0.51	9.2	0.25	19.1
						35.0	772.0000	0.05	0.51	10.2	0.25	21.4
						34.9	774.9875	0.05	0.52	9.2	0.25	19.2
						34.6	794.0125	0.06	0.53	11.4	0.25	24.1
					35.5	799.0125	0.07	0.53	12.2	0.25	25.8	
					42	42.0	811.5000	0.05	0.54	8.4	0.25	17.8
						40.8	823.9875	0.04	0.55	8.0	0.26	17.0
						41.8	851.0125	0.02	0.57	4.3	0.26	9.3
						41.1	860.5000	0.04	0.57	6.2	0.27	13.4
41.1	868.9875	0.03	0.58	4.4		0.27	9.6					

Table D.1 (Continued)

MPE assessment for APX6500 7/800MHz - roof mounted antenna – Bystander

Note:

Blue fonts: Frequencies not regulated by FCC.

Trunk / Roof	Test Post.	E/H Field	Antenna No.	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm ²)	FCC Limit	% To FCC Spec Limit	ISED Limit	% To ISED Spec Limit
Roof	BS2	E	4	HAF4017A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.04	0.51	7.5	0.24	15.6
						35.2	769.0125	0.04	0.51	7.4	0.25	15.4
						35.0	772.0000	0.04	0.51	7.4	0.25	15.5
						34.9	774.9875	0.04	0.52	6.9	0.25	14.3
						34.6	794.0125	0.03	0.53	6.3	0.25	13.2
					35.5	799.0125	0.03	0.53	6.2	0.25	13.1	
					42	42.0	811.5000	0.03	0.54	4.8	0.25	10.2
						40.8	823.9875	0.04	0.55	6.5	0.26	14.0
						41.8	851.0125	0.03	0.57	4.6	0.26	10.0
						41.1	860.5000	0.03	0.57	5.9	0.27	12.7
41.1	868.9875	0.02	0.58	4.1		0.27	9.0					
Roof	BS3	E	4	HAF4017A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.02	0.51	4.2	0.24	8.7
						35.2	769.0125	0.02	0.51	4.2	0.25	8.9
						35.0	772.0000	0.02	0.51	4.0	0.25	8.3
						34.9	774.9875	0.02	0.52	3.6	0.25	7.6
						34.6	794.0125	0.03	0.53	5.1	0.25	10.8
					35.5	799.0125	0.02	0.53	4.7	0.25	9.9	
					42	42.0	811.5000	0.02	0.54	4.1	0.25	8.6
						40.8	823.9875	0.03	0.55	4.9	0.26	10.4
						41.8	851.0125	0.02	0.57	3.1	0.26	6.7
						41.1	860.5000	0.02	0.57	3.6	0.27	7.7
41.1	868.9875	0.02	0.58	3.2		0.27	7.0					

Table D.1 (Continued)

MPE assessment for APX6500 7/800MHz - roof mounted antenna – Bystander

Note:

Blue fonts: Frequencies not regulated by FCC.

Trunk / Roof	Test Post.	E/H Field	Antenna No.	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm ²)	FCC Limit	% To FCC Spec Limit	ISED Limit	% To ISED Spec Limit
Roof	BS4	E	4	HAF4017A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.01	0.51	2.9	0.24	6.1
						35.2	769.0125	0.01	0.51	2.9	0.25	6.0
						35.0	772.0000	0.01	0.51	2.6	0.25	5.4
						34.9	774.9875	0.02	0.52	2.9	0.25	6.1
						34.6	794.0125	0.01	0.53	2.7	0.25	5.7
					35.5	799.0125	0.01	0.53	2.7	0.25	5.8	
					42	42.0	811.5000	0.01	0.54	1.6	0.25	3.4
						40.8	823.9875	0.01	0.55	2.0	0.26	4.3
						41.8	851.0125	0.01	0.57	1.7	0.26	3.6
						41.1	860.5000	0.01	0.57	2.2	0.27	4.7
41.1	868.9875	0.01	0.58	1.7		0.27	3.6					
Roof	BS5	E	4	HAF4017A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.01	0.51	2.6	0.24	5.3
						35.2	769.0125	0.01	0.51	2.6	0.25	5.4
						35.0	772.0000	0.02	0.51	3.6	0.25	7.5
						34.9	774.9875	0.02	0.52	3.4	0.25	7.2
						34.6	794.0125	0.02	0.53	3.0	0.25	6.4
					35.5	799.0125	0.02	0.53	3.8	0.25	8.0	
					42	42.0	811.5000	0.01	0.54	2.5	0.25	5.3
						40.8	823.9875	0.01	0.55	2.5	0.26	5.3
						41.8	851.0125	0.01	0.57	1.2	0.26	2.6
						41.1	860.5000	0.01	0.57	1.5	0.27	3.2
41.1	868.9875	0.01	0.58	1.2		0.27	2.7					

Table D.2

MPE assessment for APX6500 7/800MHz - roof mounted antenna – Passenger

Note:

Blue fonts: Frequencies not regulated by FCC.

Trunk / Roof	Test Post.	E/H Field	Antenna No.	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm ²)	FCC Limit	% To FCC Spec Limit	ISED Limit	% To ISED Spec Limit
Roof	PB	E	1	HAF4013A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.02	0.51	3.2	0.24	6.7
						35.2	769.0125	0.02	0.51	3.2	0.25	6.6
						35.0	772.0000	0.02	0.51	3.5	0.25	7.4
						34.9	774.9875	0.02	0.52	3.6	0.25	7.4
						34.6	794.0125	0.02	0.53	3.3	0.25	7.0
					35.5	799.0125	0.02	0.53	2.9	0.25	6.2	
					42	42.0	811.5000	0.01	0.54	2.5	0.25	5.2
						40.8	823.9875	0.02	0.55	2.9	0.26	6.1
						41.8	851.0125	0.01	0.57	1.2	0.26	2.7
						41.1	860.5000	0.01	0.57	1.8	0.27	3.9
41.1	868.9875	0.01	0.58	1.4		0.27	3.1					
Roof	PB	E	2	HAF4014A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.001	0.51	0.3	0.24	0.6
						35.2	769.0125	0.002	0.51	0.3	0.25	0.6
						35.0	772.0000	0.001	0.51	0.3	0.25	0.6
						34.9	774.9875	0.001	0.52	0.2	0.25	0.5
						34.6	794.0125	0.004	0.53	0.8	0.25	1.6
					35.5	799.0125	0.01	0.53	1.0	0.25	2.2	
					42	42.0	811.5000	0.01	0.54	1.9	0.25	4.1
						40.8	823.9875	0.01	0.55	2.3	0.26	5.0
						41.8	851.0125	0.01	0.57	1.9	0.26	4.0
						41.1	860.5000	0.01	0.57	1.3	0.27	2.8
41.1	868.9875	0.01	0.58	1.8		0.27	4.0					

Table D.2 (Continued)

MPE assessment for APX6500 7/800MHz - roof mounted antenna – Passenger

Note:

Blue fonts: Frequencies not regulated by FCC.

Trunk / Roof	Test Post.	E/H Field	Antenna No.	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm ²)	FCC Limit	% To FCC Spec Limit	ISED Limit	% To ISED Spec Limit
Roof	PB	E	3	HAF4016A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.02	0.51	3.1	0.24	6.5
						35.2	769.0125	0.02	0.51	3.5	0.25	7.3
						35.0	772.0000	0.02	0.51	3.3	0.25	6.8
						34.9	774.9875	0.02	0.52	3.3	0.25	6.8
						34.6	794.0125	0.02	0.53	3.6	0.25	7.6
					35.5	799.0125	0.02	0.53	2.9	0.25	6.2	
					42	42.0	811.5000	0.01	0.54	2.2	0.25	4.6
						40.8	823.9875	0.02	0.55	3.4	0.26	7.2
						41.8	851.0125	0.01	0.57	1.6	0.26	3.5
						41.1	860.5000	0.01	0.57	1.5	0.27	3.3
41.1	868.9875	0.01	0.58	1.6		0.27	3.4					
Roof	PB	E	4	HAF4017A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.03	0.51	5.8	0.24	12.1
						35.2	769.0125	0.03	0.51	5.2	0.25	10.9
						35.0	772.0000	0.03	0.51	5.5	0.25	11.5
						34.9	774.9875	0.03	0.52	5.5	0.25	11.6
						34.6	794.0125	0.03	0.53	5.4	0.25	11.3
					35.5	799.0125	0.03	0.53	5.0	0.25	10.6	
					42	42.0	811.5000	0.02	0.54	3.8	0.25	8.1
						40.8	823.9875	0.02	0.55	3.9	0.26	8.4
						41.8	851.0125	0.01	0.57	2.1	0.26	4.6
						41.1	860.5000	0.02	0.57	3.3	0.27	7.2
41.1	868.9875	0.01	0.58	2.0		0.27	4.4					

Table D.2 (Continued)

MPE assessment for APX6500 7/800MHz - roof mounted antenna – Passenger

Note:

Blue fonts: Frequencies not regulated by FCC.

Trunk / Roof	Test Post.	E/H Field	Antenna No.	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm ²)	FCC Limit	% To FCC Spec Limit	ISED Limit	% To ISED Spec Limit
Roof	PF	E	1	HAF4013A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.01	0.51	1.7	0.24	3.4
						35.2	769.0125	0.01	0.51	2.0	0.25	4.1
						35.0	772.0000	0.01	0.51	1.8	0.25	3.9
						34.9	774.9875	0.01	0.52	1.9	0.25	4.1
						34.6	794.0125	0.01	0.53	1.4	0.25	3.0
					35.5	799.0125	0.01	0.53	1.3	0.25	2.7	
					42	42.0	811.5000	0.01	0.54	1.4	0.25	3.0
						40.8	823.9875	0.01	0.55	1.8	0.26	3.9
						41.8	851.0125	0.01	0.57	1.5	0.26	3.2
						41.1	860.5000	0.01	0.57	1.6	0.27	3.4
41.1	868.9875	0.01	0.58	1.3		0.27	2.8					
Roof	PF	E	2	HAF4014A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.002	0.51	0.3	0.24	0.6
						35.2	769.0125	0.002	0.51	0.3	0.25	0.7
						35.0	772.0000	0.002	0.51	0.4	0.25	0.8
						34.9	774.9875	0.002	0.52	0.3	0.25	0.6
						34.6	794.0125	0.003	0.53	0.6	0.25	1.2
					35.5	799.0125	0.004	0.53	0.7	0.25	1.4	
					42	42.0	811.5000	0.01	0.54	1.1	0.25	2.4
						40.8	823.9875	0.01	0.55	1.5	0.26	3.2
						41.8	851.0125	0.01	0.57	2.0	0.26	4.4
						41.1	860.5000	0.01	0.57	1.8	0.27	4.0
41.1	868.9875	0.01	0.58	1.4		0.27	3.1					

Table D.2 (Continued)

MPE assessment for APX6500 7/800MHz - roof mounted antenna – Passenger

Note:

Blue fonts: Frequencies not regulated by FCC.

Trunk / Roof	Test Post.	E/H Field	Antenna No.	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm ²)	FCC Limit	% To FCC Spec Limit	ISED Limit	% To ISED Spec Limit
Roof	PF	E	3	HAF4016A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.01	0.51	1.8	0.24	3.7
						35.2	769.0125	0.01	0.51	1.9	0.25	4.0
						35.0	772.0000	0.01	0.51	1.4	0.25	3.0
						34.9	774.9875	0.01	0.52	1.6	0.25	3.4
						34.6	794.0125	0.01	0.53	1.3	0.25	2.8
					35.5	799.0125	0.01	0.53	1.3	0.25	2.8	
					42	42.0	811.5000	0.01	0.54	1.4	0.25	3.0
						40.8	823.9875	0.01	0.55	1.9	0.26	4.1
						41.8	851.0125	0.01	0.57	1.4	0.26	3.1
						41.1	860.5000	0.01	0.57	1.4	0.27	3.1
41.1	868.9875	0.01	0.58	1.2		0.27	2.5					
Roof	PF	E	4	HAF4017A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.02	0.51	3.5	0.24	7.4
						35.2	769.0125	0.02	0.51	3.4	0.25	7.2
						35.0	772.0000	0.02	0.51	3.3	0.25	6.9
						34.9	774.9875	0.01	0.52	2.8	0.25	5.9
						34.6	794.0125	0.01	0.53	2.8	0.25	5.9
					35.5	799.0125	0.01	0.53	2.3	0.25	4.8	
					42	42.0	811.5000	0.01	0.54	2.1	0.25	4.4
						40.8	823.9875	0.02	0.55	3.0	0.26	6.4
						41.8	851.0125	0.01	0.57	2.1	0.26	4.5
						41.1	860.5000	0.01	0.57	2.0	0.27	4.3
41.1	868.9875	0.01	0.58	1.5		0.27	3.3					

Table E.3

Companion Device LMR VHF MPE Results for FCC

Note:

Blue fonts: Frequencies not regulated by FCC.

Pmax (W)
36, 52

Pinitial (W)

FCCLimit (mW/cm²)

35.2	35.2	35.0	34.9	34.6	35.5	42.0	40.8	41.8	41.1	41.1
0.51	0.51	0.51	0.52	0.53	0.53	0.54	0.55	0.57	0.57	0.58

Table	Test Post.	Trunk / Roof	E/H Field	Antenna No.	F1	F2	F3	F4	F5	F6	F7	F8	F9	F10	F11
					762.0125	769.0125	772.0000	774.9875	794.0125	799.0125	811.5000	823.9875	851.0125	860.5000	868.9875
D.1	BS1	Roof	E	1	0.04	0.04	0.05	0.04	0.05	0.05	0.04	0.04	0.03	0.04	0.03
D.1	BS2	Roof	E	1	0.03	0.03	0.03	0.03	0.03	0.03	0.02	0.03	0.03	0.03	0.03
D.1	BS3	Roof	E	1	0.01	0.01	0.01	0.01	0.02	0.02	0.01	0.02	0.01	0.01	0.01
D.1	BS4	Roof	E	1	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01
D.1	BS5	Roof	E	1	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.004	0.01	0.004
D.1	BS1	Roof	E	2	0.03	0.03	0.03	0.03	0.05	0.05	0.04	0.04	0.02	0.03	0.03
D.1	BS2	Roof	E	2	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.03	0.03	0.03	0.02
D.1	BS3	Roof	E	2	0.01	0.01	0.01	0.01	0.02	0.02	0.02	0.02	0.02	0.02	0.02
D.1	BS4	Roof	E	2	0.004	0.004	0.004	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01
D.1	BS5	Roof	E	2	0.004	0.004	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01
D.1	BS1	Roof	E	3	0.04	0.04	0.04	0.04	0.05	0.05	0.04	0.04	0.03	0.04	0.03
D.1	BS2	Roof	E	3	0.03	0.03	0.03	0.03	0.03	0.03	0.02	0.03	0.02	0.03	0.02
D.1	BS3	Roof	E	3	0.01	0.01	0.01	0.01	0.02	0.01	0.01	0.02	0.01	0.01	0.01
D.1	BS4	Roof	E	3	0.01	0.01	0.01	0.01	0.01	0.01	0.005	0.01	0.01	0.01	0.01
D.1	BS5	Roof	E	3	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.004	0.01	0.004
D.1	BS1	Roof	E	4	0.05	0.05	0.05	0.05	0.06	0.07	0.05	0.04	0.02	0.04	0.03
D.1	BS2	Roof	E	4	0.04	0.04	0.04	0.04	0.03	0.03	0.03	0.04	0.03	0.03	0.02
D.1	BS3	Roof	E	4	0.02	0.02	0.02	0.02	0.03	0.02	0.02	0.03	0.02	0.02	0.02
D.1	BS4	Roof	E	4	0.01	0.01	0.01	0.02	0.01	0.01	0.01	0.01	0.01	0.01	0.01
D.1	BS5	Roof	E	4	0.01	0.01	0.02	0.02	0.02	0.02	0.01	0.01	0.01	0.01	0.01
D.2	PB	Roof	E	1	0.02	0.02	0.02	0.02	0.02	0.02	0.01	0.02	0.01	0.01	0.01
D.2	PB	Roof	E	2	0.001	0.002	0.001	0.001	0.004	0.01	0.01	0.01	0.01	0.01	0.01
D.2	PB	Roof	E	3	0.02	0.02	0.02	0.02	0.02	0.02	0.01	0.02	0.01	0.01	0.01
D.2	PB	Roof	E	4	0.03	0.03	0.03	0.03	0.03	0.03	0.02	0.02	0.01	0.02	0.01
D.2	PF	Roof	E	1	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01
D.2	PF	Roof	E	2	0.002	0.002	0.002	0.002	0.003	0.004	0.01	0.01	0.01	0.01	0.01
D.2	PF	Roof	E	3	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01
D.2	PF	Roof	E	4	0.02	0.02	0.02	0.01	0.01	0.01	0.01	0.02	0.01	0.01	0.01

Appendix E – MPE Test Results Summary for Companion Device (DVR 700)

Table E.1

MPE assessment for Companion Device (DVR 700) - trunk mounted antenna - Bystander

Trunk / Roof	Test Post.	E/H Field	Antenna No.	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm ²)	FCC Limit	% To FCC Spec Limit	ISED Limit	% To ISED Spec Limit
Trunk	BS1	E	9	HAF4016A, 1/4 Wave (764-870MHz)	5.0	4.82	770.0000	0.004	0.51	0.8	0.25	1.6
						4.79	775.0000	0.003	0.52	0.6	0.25	1.3
						4.86	800.0000	0.002	0.53	0.4	0.25	0.8
						4.88	806.0000	0.002	0.54	0.4	0.25	0.7
Trunk	BS2	E	9	HAF4016A, 1/4 Wave (764-870MHz)	5.0	4.82	770.0000	0.011	0.51	2.1	0.25	4.5
						4.79	775.0000	0.011	0.52	2.0	0.25	4.3
						4.86	800.0000	0.008	0.53	1.5	0.25	3.1
						4.88	806.0000	0.008	0.54	1.4	0.25	3.0
Trunk	BS3	E	9	HAF4016A, 1/4 Wave (764-870MHz)	5.0	4.82	770.0000	0.015	0.51	2.9	0.25	6.0
						4.79	775.0000	0.018	0.52	3.6	0.25	7.5
						4.86	800.0000	0.008	0.53	1.4	0.25	3.0
						4.88	806.0000	0.007	0.54	1.3	0.25	2.7
Trunk	BS4	E	9	HAF4016A, 1/4 Wave (764-870MHz)	5.0	4.82	770.0000	0.017	0.51	3.3	0.25	6.9
						4.79	775.0000	0.017	0.52	3.2	0.25	6.8
						4.86	800.0000	0.011	0.53	2.1	0.25	4.4
						4.88	806.0000	0.009	0.54	1.7	0.25	3.7
Trunk	BS5	E	9	HAF4016A, 1/4 Wave (764-870MHz)	5.0	4.82	770.0000	0.020	0.51	3.9	0.25	8.1
						4.79	775.0000	0.020	0.52	3.9	0.25	8.1
						4.86	800.0000	0.008	0.53	1.5	0.25	3.1
						4.88	806.0000	0.007	0.54	1.3	0.25	2.9

Note:
Results in bold font are configurations with highest percentage of limits.

Table E.2

MPE assessment for Companion Device (DVR 700) – trunk mounted antenna - Passenger

Trunk / Roof	Test Post.	E/H Field	Antenna No.	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm ²)	FCC Limit	% To FCC Spec Limit	ISED Limit	% To ISED Spec Limit
Trunk	PB	E	9	HAF4016A, 1/4 Wave (764-870MHz)	5.0	4.82	770.0000	0.035	0.51	6.8	0.25	14.2
						4.79	775.0000	0.038	0.52	7.3	0.25	15.4
						4.86	800.0000	0.022	0.53	4.1	0.25	8.7
						4.88	806.0000	0.021	0.54	3.8	0.25	8.1
Trunk	PF	E	9	HAF4016A, 1/4 Wave (764-870MHz)	5.0	4.82	770.0000	0.022	0.51	4.3	0.25	9.0
						4.79	775.0000	0.031	0.52	6.1	0.25	12.7
						4.86	800.0000	0.013	0.53	2.4	0.25	5.1
						4.88	806.0000	0.011	0.54	2.1	0.25	4.4

Note:

Results in bold font are configurations with highest percentage of limits.

Table E.3
Companion Device (DVR 700) MPE Results for FCC

Pmax (W)	5	Pinitial (W)	4.82	4.79	4.86	4.88
			FCCLimit (mW/cm ²)	0.51	0.52	0.53

Table	Test Post.	Angle	Trunk / Roof	E/H Field	Antenna No.	f1	f2	f3	f4
						770.0000	775.0000	800.0000	806.0000
E.1	BS1		Trunk	E	9	0.004	0.003	0.002	0.002
E.1	BS2		Trunk	E	9	0.011	0.011	0.008	0.008
E.1	BS3		Trunk	E	9	0.015	0.018	0.008	0.007
E.1	BS4		Trunk	E	9	0.017	0.017	0.011	0.009
E.1	BS5		Trunk	E	9	0.020	0.020	0.008	0.007
E.2	PB		Trunk	E	9	0.035	0.038	0.022	0.021
E.2	PF		Trunk	E	9	0.022	0.031	0.013	0.011

Appendix F – MPE Test Results Summary for APX6500 7/800MHz

Table F.1

APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35	CW	E	0.98	BS1	0.0030	0.0120	0.0110	0.0130	0.0210	0.0450	0.0780	0.2120	0.2480	0.2030	0.5	0.083	0.04	0.04
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36.0	35	CW	E	0.99	BS1	0.0030	0.0120	0.0110	0.0130	0.0220	0.0440	0.0780	0.2110	0.2500	0.2060	0.5	0.084	0.04	0.04
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35	CW	E	0.99	BS1	0.0030	0.0090	0.0070	0.0110	0.0200	0.0610	0.0990	0.2360	0.2640	0.2170	0.5	0.092	0.05	0.05
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	35	CW	E	0.99	BS1	0.0030	0.0070	0.0060	0.0170	0.0190	0.0570	0.0900	0.2200	0.2300	0.1800	0.5	0.082	0.04	0.04
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	35	CW	E	1.00	BS1	0.0050	0.0060	0.0100	0.0120	0.0120	0.0440	0.0810	0.2700	0.3100	0.1980	0.5	0.095	0.05	0.05
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	36	CW	E	1.00	BS1	0.0040	0.0060	0.0080	0.0100	0.0180	0.0560	0.1110	0.2660	0.3240	0.2050	0.5	0.101	0.05	0.05
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42	CW	E	1.01	BS1	0.0020	0.0070	0.0090	0.0120	0.0110	0.0280	0.0890	0.2080	0.2460	0.1770	0.5	0.079	0.04	0.04
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	41	CW	E	1.01	BS1	0.0020	0.0040	0.0050	0.0080	0.0080	0.0300	0.0740	0.1660	0.2280	0.1890	0.5	0.072	0.04	0.04
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	42	CW	E	1.03	BS1	0.0010	0.0020	0.0050	0.0110	0.0250	0.0280	0.0300	0.1040	0.1770	0.1760	0.5	0.058	0.03	0.03
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41	CW	E	1.04	BS1	0.0040	0.0030	0.0040	0.0120	0.0220	0.0390	0.0560	0.1670	0.2170	0.2180	0.5	0.077	0.04	0.04
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41	CW	E	1.04	BS1	0.0030	0.0040	0.0080	0.0150	0.0180	0.0150	0.0480	0.1440	0.1830	0.1550	0.5	0.062	0.03	0.03

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.1 (Continued)

APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35	CW	E	0.98	BS2	0.0020	0.0010	0.0080	0.0130	0.0260	0.0310	0.0670	0.1090	0.1590	0.1750	0.5	0.058	0.03	0.03
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36.0	35	CW	E	0.99	BS2	0.0020	0.0010	0.0080	0.0130	0.0260	0.0300	0.0670	0.1110	0.1610	0.1750	0.5	0.059	0.03	0.03
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35	CW	E	0.99	BS2	0.0010	0.0030	0.0090	0.0180	0.0250	0.0260	0.0650	0.1260	0.1820	0.1410	0.5	0.059	0.03	0.03
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	35	CW	E	0.99	BS2	0.0000	0.0040	0.0080	0.0130	0.0160	0.0230	0.0520	0.0930	0.1800	0.1410	0.5	0.052	0.03	0.03
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	35	CW	E	1.00	BS2	0.0000	0.0090	0.0080	0.0150	0.0240	0.0200	0.0400	0.0850	0.1480	0.1790	0.5	0.053	0.03	0.03
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	36	CW	E	1.00	BS2	0.0010	0.0060	0.0060	0.0140	0.0280	0.0200	0.0480	0.0940	0.1510	0.1510	0.5	0.052	0.03	0.03
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42	CW	E	1.01	BS2	0.0010	0.0030	0.0030	0.0070	0.0180	0.0210	0.0450	0.0900	0.1250	0.1560	0.5	0.047	0.02	0.02
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	41	CW	E	1.01	BS2	0.0010	0.0020	0.0030	0.0080	0.0140	0.0230	0.0660	0.1400	0.1660	0.1470	0.5	0.058	0.03	0.03
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	42	CW	E	1.03	BS2	0.0010	0.0030	0.0080	0.0090	0.0090	0.0390	0.0620	0.1250	0.1520	0.1350	0.5	0.056	0.03	0.03
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41	CW	E	1.04	BS2	0.0010	0.0020	0.0060	0.0110	0.0060	0.0280	0.0530	0.1600	0.2010	0.1470	0.5	0.064	0.03	0.03
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41	CW	E	1.04	BS2	0.0000	0.0010	0.0020	0.0050	0.0100	0.0320	0.0560	0.1180	0.1440	0.1210	0.5	0.051	0.03	0.03

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.1 (Continued)

APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35	CW	E	0.98	BS3	0.0050	0.0090	0.0110	0.0160	0.0100	0.0070	0.0290	0.0410	0.0430	0.0630	0.5	0.023	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36.0	35	CW	E	0.99	BS3	0.0050	0.0100	0.0110	0.0150	0.0110	0.0070	0.0280	0.0410	0.0430	0.0620	0.5	0.023	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35	CW	E	0.99	BS3	0.0060	0.0070	0.0120	0.0130	0.0140	0.0080	0.0210	0.0310	0.0390	0.0760	0.5	0.022	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	35	CW	E	0.99	BS3	0.0020	0.0050	0.0110	0.0110	0.0140	0.0110	0.0280	0.0300	0.0330	0.0510	0.5	0.019	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	35	CW	E	1.00	BS3	0.0020	0.0080	0.0080	0.0090	0.0100	0.0160	0.0390	0.0560	0.0770	0.0760	0.5	0.030	0.02	0.02
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	36	CW	E	1.00	BS3	0.0020	0.0030	0.0060	0.0060	0.0060	0.0150	0.0420	0.0490	0.0720	0.0980	0.5	0.030	0.01	0.02
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42	CW	E	1.01	BS3	0.0030	0.0050	0.0060	0.0060	0.0090	0.0120	0.0330	0.0460	0.0630	0.0820	0.5	0.027	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	41	CW	E	1.01	BS3	0.0040	0.0070	0.0100	0.0100	0.0140	0.0170	0.0340	0.0570	0.0710	0.0770	0.5	0.031	0.02	0.02
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	42	CW	E	1.03	BS3	0.0030	0.0030	0.0080	0.0130	0.0080	0.0130	0.0310	0.0420	0.0730	0.0630	0.5	0.026	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41	CW	E	1.04	BS3	0.0030	0.0040	0.0070	0.0180	0.0170	0.0160	0.0280	0.0310	0.0580	0.0630	0.5	0.025	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41	CW	E	1.04	BS3	0.0020	0.0040	0.0080	0.0150	0.0120	0.0120	0.0260	0.0310	0.0650	0.0950	0.5	0.028	0.01	0.01

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.1 (Continued)

APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35	CW	E	0.98	BS4	0.0030	0.0060	0.0050	0.0100	0.0110	0.0090	0.0080	0.0240	0.0320	0.0330	0.5	0.014	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36.0	35	CW	E	0.99	BS4	0.0030	0.0060	0.0050	0.0100	0.0110	0.0090	0.0080	0.0230	0.0330	0.0320	0.5	0.014	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35	CW	E	0.99	BS4	0.0020	0.0050	0.0070	0.0090	0.0100	0.0110	0.0120	0.0230	0.0250	0.0260	0.5	0.013	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	35	CW	E	0.99	BS4	0.0030	0.0040	0.0040	0.0090	0.0100	0.0110	0.0120	0.0230	0.0300	0.0300	0.5	0.013	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	35	CW	E	1.00	BS4	0.0020	0.0040	0.0040	0.0060	0.0110	0.0120	0.0100	0.0180	0.0230	0.0300	0.5	0.012	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	36	CW	E	1.00	BS4	0.0010	0.0060	0.0020	0.0090	0.0100	0.0090	0.0090	0.0260	0.0250	0.0240	0.5	0.012	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42	CW	E	1.01	BS4	0.0010	0.0030	0.0020	0.0050	0.0090	0.0070	0.0110	0.0240	0.0190	0.0260	0.5	0.011	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	41	CW	E	1.01	BS4	0.0020	0.0040	0.0040	0.0070	0.0090	0.0050	0.0120	0.0330	0.0270	0.0260	0.5	0.013	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	42	CW	E	1.03	BS4	0.0020	0.0030	0.0020	0.0040	0.0100	0.0080	0.0100	0.0270	0.0260	0.0250	0.5	0.012	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41	CW	E	1.04	BS4	0.0020	0.0020	0.0000	0.0040	0.0100	0.0140	0.0130	0.0320	0.0370	0.0400	0.5	0.016	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41	CW	E	1.04	BS4	0.0010	0.0030	0.0040	0.0070	0.0090	0.0080	0.0150	0.0300	0.0240	0.0240	0.5	0.013	0.01	0.01

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.1 (Continued)

APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35	CW	E	0.98	BS5	0.0000	0.0030	0.0030	0.0030	0.0060	0.0070	0.0100	0.0230	0.0330	0.0190	0.5	0.011	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36.0	35	CW	E	0.99	BS5	0.0000	0.0030	0.0030	0.0030	0.0060	0.0070	0.0100	0.0230	0.0340	0.0180	0.5	0.011	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35	CW	E	0.99	BS5	0.0010	0.0020	0.0010	0.0030	0.0080	0.0130	0.0130	0.0210	0.0450	0.0330	0.5	0.014	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	35	CW	E	0.99	BS5	0.0020	0.0010	0.0020	0.0080	0.0130	0.0140	0.0130	0.0170	0.0390	0.0360	0.5	0.014	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	35	CW	E	1.00	BS5	0.0010	0.0010	0.0010	0.0050	0.0120	0.0160	0.0140	0.0320	0.0400	0.0290	0.5	0.015	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	36	CW	E	1.00	BS5	0.0000	0.0010	0.0020	0.0050	0.0120	0.0180	0.0210	0.0470	0.0540	0.0350	0.5	0.019	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42	CW	E	1.01	BS5	0.0000	0.0010	0.0020	0.0050	0.0120	0.0180	0.0210	0.0470	0.0540	0.0350	0.5	0.020	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	41	CW	E	1.01	BS5	0.0000	0.0010	0.0020	0.0090	0.0130	0.0110	0.0090	0.0210	0.0260	0.0180	0.5	0.011	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	42	CW	E	1.03	BS5	0.0020	0.0010	0.0010	0.0060	0.0090	0.0110	0.0070	0.0130	0.0170	0.0140	0.5	0.008	0.00	0.00
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41	CW	E	1.04	BS5	0.0010	0.0000	0.0000	0.0040	0.0070	0.0120	0.0050	0.0160	0.0310	0.0190	0.5	0.010	0.00	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41	CW	E	1.04	BS5	0.0010	0.0000	0.0010	0.0030	0.0040	0.0060	0.0060	0.0170	0.0220	0.0150	0.5	0.008	0.00	0.00

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.1 (Continued)

APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35	CW	E	0.98	BS1	0.0000	0.0000	0.0000	0.0000	0.0040	0.0000	0.0070	0.0830	0.2440	0.2470	0.5	0.058	0.03	0.03
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36.0	35	CW	E	0.99	BS1	0.0000	0.0000	0.0000	0.0000	0.0040	0.0010	0.0070	0.0820	0.2460	0.2480	0.5	0.058	0.03	0.03
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35	CW	E	0.99	BS1	0.0000	0.0000	0.0000	0.0000	0.0020	0.0010	0.0130	0.1020	0.2690	0.2780	0.5	0.066	0.03	0.03
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	35	CW	E	0.99	BS1	0.0000	0.0000	0.0000	0.0010	0.0010	0.0020	0.0170	0.1170	0.2600	0.2320	0.5	0.062	0.03	0.03
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	35	CW	E	1.00	BS1	0.0000	0.0010	0.0010	0.0010	0.0040	0.0110	0.0540	0.2500	0.3200	0.2500	0.5	0.089	0.04	0.05
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	36	CW	E	1.00	BS1	0.0010	0.0000	0.0000	0.0030	0.0020	0.0130	0.0710	0.2790	0.3750	0.2780	0.5	0.102	0.05	0.05
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42	CW	E	1.01	BS1	0.0010	0.0010	0.0010	0.0060	0.0060	0.0130	0.0790	0.2440	0.2760	0.2250	0.5	0.086	0.04	0.04
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	41	CW	E	1.01	BS1	0.0010	0.0020	0.0020	0.0050	0.0100	0.0320	0.1000	0.1990	0.2000	0.1570	0.5	0.072	0.04	0.04
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	42	CW	E	1.03	BS1	0.0030	0.0030	0.0100	0.0080	0.0300	0.0380	0.0480	0.1250	0.0870	0.1010	0.5	0.047	0.02	0.02
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41	CW	E	1.04	BS1	0.0060	0.0030	0.0040	0.0130	0.0190	0.0390	0.0730	0.1460	0.1080	0.1280	0.5	0.056	0.03	0.03
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41	CW	E	1.04	BS1	0.0020	0.0020	0.0080	0.0150	0.0300	0.0290	0.0600	0.1390	0.0920	0.1070	0.5	0.050	0.03	0.03

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.1 (Continued)

APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35	CW	E	0.98	BS2	0.0000	0.0000	0.0000	0.0000	0.0000	0.0020	0.0100	0.0380	0.1130	0.1870	0.5	0.034	0.02	0.02
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36.0	35	CW	E	0.99	BS2	0.0000	0.0000	0.0000	0.0000	0.0000	0.0020	0.0090	0.0370	0.1100	0.1820	0.5	0.034	0.02	0.02
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35	CW	E	0.99	BS2	0.0000	0.0000	0.0000	0.0010	0.0010	0.0030	0.0130	0.0560	0.1300	0.1620	0.5	0.036	0.02	0.02
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	35	CW	E	0.99	BS2	0.0000	0.0000	0.0000	0.0010	0.0020	0.0030	0.0160	0.0590	0.1400	0.1650	0.5	0.038	0.02	0.02
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	35	CW	E	1.00	BS2	0.0000	0.0010	0.0020	0.0030	0.0090	0.0140	0.0360	0.0730	0.1220	0.1380	0.5	0.040	0.02	0.02
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	36	CW	E	1.00	BS2	0.0000	0.0020	0.0020	0.0050	0.0150	0.0140	0.0330	0.0860	0.1420	0.1200	0.5	0.042	0.02	0.02
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42	CW	E	1.01	BS2	0.0000	0.0010	0.0020	0.0030	0.0090	0.0160	0.0490	0.0900	0.1260	0.0930	0.5	0.039	0.02	0.02
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	41	CW	E	1.01	BS2	0.0000	0.0030	0.0050	0.0060	0.0100	0.0250	0.0730	0.1430	0.1730	0.1150	0.5	0.056	0.03	0.03
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	42	CW	E	1.03	BS2	0.0010	0.0010	0.0030	0.0100	0.0070	0.0380	0.0910	0.1660	0.1160	0.0820	0.5	0.053	0.03	0.03
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41	CW	E	1.04	BS2	0.0010	0.0020	0.0030	0.0100	0.0070	0.0330	0.0950	0.1890	0.1280	0.0870	0.5	0.058	0.03	0.03
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41	CW	E	1.04	BS2	0.0000	0.0020	0.0090	0.0040	0.0110	0.0400	0.0760	0.1320	0.0820	0.0500	0.5	0.042	0.02	0.02

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.1 (Continued)

APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35	CW	E	0.98	BS3	0.0000	0.0000	0.0000	0.0020	0.0010	0.0030	0.0120	0.0230	0.0380	0.0610	0.5	0.014	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36.0	35	CW	E	0.99	BS3	0.0000	0.0000	0.0000	0.0020	0.0010	0.0030	0.0120	0.0230	0.0390	0.0590	0.5	0.014	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35	CW	E	0.99	BS3	0.0000	0.0000	0.0000	0.0010	0.0000	0.0030	0.0110	0.0220	0.0420	0.0640	0.5	0.014	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	35	CW	E	0.99	BS3	0.0010	0.0010	0.0020	0.0020	0.0030	0.0040	0.0110	0.0190	0.0350	0.0490	0.5	0.013	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	35	CW	E	1.00	BS3	0.0010	0.0040	0.0050	0.0060	0.0060	0.0130	0.0460	0.0820	0.1090	0.0790	0.5	0.035	0.02	0.02
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	36	CW	E	1.00	BS3	0.0010	0.0030	0.0050	0.0060	0.0070	0.0180	0.0490	0.0690	0.1080	0.0940	0.5	0.036	0.02	0.02
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42	CW	E	1.01	BS3	0.0020	0.0040	0.0100	0.0080	0.0180	0.0320	0.0660	0.0990	0.1500	0.1060	0.5	0.050	0.02	0.02
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	41	CW	E	1.01	BS3	0.0030	0.0030	0.0090	0.0120	0.0180	0.0380	0.0910	0.0900	0.1110	0.0630	0.5	0.044	0.02	0.02
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	42	CW	E	1.03	BS3	0.0030	0.0060	0.0140	0.0340	0.0210	0.0260	0.0820	0.0970	0.0950	0.0510	0.5	0.044	0.02	0.02
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41	CW	E	1.04	BS3	0.0050	0.0040	0.0100	0.0190	0.0310	0.0330	0.0580	0.0580	0.0700	0.0370	0.5	0.034	0.02	0.02
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41	CW	E	1.04	BS3	0.0030	0.0040	0.0110	0.0190	0.0220	0.0370	0.0680	0.0790	0.1140	0.0510	0.5	0.043	0.02	0.02

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.1 (Continued)

APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35	CW	E	0.98	BS4	0.0010	0.0000	0.0010	0.0000	0.0010	0.0010	0.0050	0.0160	0.0260	0.0360	0.5	0.009	0.00	0.00
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36.0	35	CW	E	0.99	BS4	0.0010	0.0000	0.0000	0.0000	0.0010	0.0010	0.0050	0.0160	0.0270	0.0370	0.5	0.009	0.00	0.00
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35	CW	E	0.99	BS4	0.0010	0.0010	0.0020	0.0020	0.0010	0.0020	0.0070	0.0150	0.0200	0.0350	0.5	0.009	0.00	0.00
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	35	CW	E	0.99	BS4	0.0010	0.0020	0.0010	0.0050	0.0070	0.0090	0.0130	0.0190	0.0240	0.0390	0.5	0.012	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	35	CW	E	1.00	BS4	0.0020	0.0030	0.0030	0.0070	0.0110	0.0130	0.0160	0.0260	0.0280	0.0370	0.5	0.015	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	36	CW	E	1.00	BS4	0.0010	0.0040	0.0020	0.0040	0.0100	0.0110	0.0180	0.0250	0.0270	0.0300	0.5	0.013	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42	CW	E	1.01	BS4	0.0030	0.0040	0.0040	0.0050	0.0100	0.0090	0.0150	0.0320	0.0280	0.0330	0.5	0.014	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	41	CW	E	1.01	BS4	0.0010	0.0020	0.0040	0.0070	0.0070	0.0060	0.0230	0.0520	0.0400	0.0410	0.5	0.019	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	42	CW	E	1.03	BS4	0.0020	0.0060	0.0020	0.0110	0.0180	0.0150	0.0360	0.0690	0.0360	0.0400	0.5	0.024	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41	CW	E	1.04	BS4	0.0010	0.0030	0.0030	0.0090	0.0180	0.0230	0.0430	0.0710	0.0430	0.0480	0.5	0.027	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41	CW	E	1.04	BS4	0.0020	0.0030	0.0020	0.0090	0.0130	0.0150	0.0310	0.0530	0.0340	0.0310	0.5	0.020	0.01	0.01

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.1 (Continued)

APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35	CW	E	0.98	BS5	0.0000	0.0000	0.0010	0.0010	0.0010	0.0010	0.0080	0.0230	0.0250	0.0250	0.5	0.008	0.00	0.00
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36.0	35	CW	E	0.99	BS5	0.0000	0.0000	0.0010	0.0010	0.0000	0.0020	0.0080	0.0220	0.0250	0.0250	0.5	0.008	0.00	0.00
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35	CW	E	0.99	BS5	0.0000	0.0000	0.0010	0.0010	0.0020	0.0060	0.0150	0.0300	0.0390	0.0380	0.5	0.013	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	35	CW	E	0.99	BS5	0.0000	0.0020	0.0010	0.0020	0.0070	0.0130	0.0170	0.0250	0.0340	0.0330	0.5	0.013	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	35	CW	E	1.00	BS5	0.0020	0.0010	0.0000	0.0050	0.0120	0.0160	0.0210	0.0530	0.0430	0.0300	0.5	0.018	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	36	CW	E	1.00	BS5	0.0010	0.0000	0.0020	0.0080	0.0150	0.0230	0.0390	0.0760	0.0650	0.0500	0.5	0.028	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42	CW	E	1.01	BS5	0.0000	0.0000	0.0020	0.0090	0.0160	0.0200	0.0270	0.0650	0.0550	0.0430	0.5	0.024	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	41	CW	E	1.01	BS5	0.0020	0.0010	0.0050	0.0170	0.0220	0.0220	0.0230	0.0540	0.0460	0.0350	0.5	0.023	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	42	CW	E	1.03	BS5	0.0020	0.0020	0.0070	0.0130	0.0110	0.0150	0.0130	0.0360	0.0330	0.0220	0.5	0.016	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41	CW	E	1.04	BS5	0.0020	0.0030	0.0050	0.0080	0.0120	0.0150	0.0160	0.0380	0.0280	0.0200	0.5	0.015	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41	CW	E	1.04	BS5	0.0010	0.0030	0.0040	0.0100	0.0100	0.0140	0.0160	0.0380	0.0260	0.0190	0.5	0.015	0.01	0.01

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.1 (Continued)

APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	762.0125	36.0	35	CW	E	0.98	BS1	0.0030	0.0130	0.0100	0.0140	0.0220	0.0440	0.0770	0.1980	0.2460	0.2000	0.5	0.081	0.04	0.04
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	769.0125	36	35.2	CW	E	0.99	BS1	0.0030	0.0130	0.0100	0.0140	0.0220	0.0450	0.0760	0.1960	0.2450	0.1990	0.5	0.081	0.04	0.04
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	772.0000	36.0	35	CW	E	0.99	BS1	0.0030	0.0130	0.0100	0.0140	0.0220	0.0450	0.0760	0.1960	0.2450	0.1990	0.5	0.081	0.04	0.04
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	774.9875	36.0	35	CW	E	0.99	BS1	0.0020	0.0070	0.0050	0.0170	0.0200	0.0580	0.0860	0.2170	0.2240	0.1760	0.5	0.080	0.04	0.04
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	794.0125	36.0	35	CW	E	1.00	BS1	0.0060	0.0050	0.0110	0.0130	0.0120	0.0400	0.0810	0.2690	0.3020	0.2020	0.5	0.094	0.05	0.05
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	799.0125	36.0	36	CW	E	1.00	BS1	0.0030	0.0060	0.0090	0.0110	0.0160	0.0560	0.1190	0.2750	0.3200	0.2060	0.5	0.102	0.05	0.05
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	811.5000	42.0	42	CW	E	1.01	BS1	0.0020	0.0060	0.0090	0.0130	0.0110	0.0270	0.0910	0.2070	0.2480	0.1760	0.5	0.080	0.04	0.04
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	823.9875	42.0	41	CW	E	1.01	BS1	0.0020	0.0040	0.0060	0.0090	0.0070	0.0320	0.0800	0.1670	0.2290	0.1770	0.5	0.072	0.04	0.04
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	851.0125	42.0	42	CW	E	1.03	BS1	0.0010	0.0010	0.0050	0.0110	0.0240	0.0300	0.0270	0.0970	0.1560	0.1510	0.5	0.052	0.03	0.03
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	860.5000	42.0	41	CW	E	1.04	BS1	0.0040	0.0030	0.0040	0.0120	0.0220	0.0410	0.0490	0.1540	0.1940	0.1930	0.5	0.070	0.04	0.04
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	868.9875	42.0	41	CW	E	1.04	BS1	0.0030	0.0030	0.0060	0.0130	0.0170	0.0130	0.0410	0.1260	0.1700	0.1420	0.5	0.056	0.03	0.03

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.1 (Continued)

APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	762.0125	36.0	35	CW	E	0.98	BS2	0.0020	0.0010	0.0060	0.0130	0.0250	0.0320	0.0670	0.1050	0.1520	0.1630	0.5	0.056	0.03	0.03
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	769.0125	36	35.2	CW	E	0.99	BS2	0.0020	0.0010	0.0060	0.0120	0.0260	0.0340	0.0660	0.1070	0.1520	0.1640	0.5	0.056	0.03	0.03
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	772.0000	36.0	35	CW	E	0.99	BS2	0.0010	0.0030	0.0080	0.0180	0.0270	0.0280	0.0600	0.1190	0.1760	0.1280	0.5	0.056	0.03	0.03
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	774.9875	36.0	35	CW	E	0.99	BS2	0.0000	0.0040	0.0080	0.0120	0.0160	0.0220	0.0490	0.0940	0.1750	0.1300	0.5	0.050	0.03	0.03
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	794.0125	36.0	35	CW	E	1.00	BS2	0.0000	0.0080	0.0090	0.0170	0.0250	0.0190	0.0420	0.0800	0.1360	0.1750	0.5	0.051	0.03	0.03
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	799.0125	36.0	36	CW	E	1.00	BS2	0.0010	0.0060	0.0080	0.0150	0.0270	0.0170	0.0460	0.0910	0.1460	0.1420	0.5	0.050	0.02	0.03
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	811.5000	42.0	42	CW	E	1.01	BS2	0.0010	0.0030	0.0030	0.0090	0.0160	0.0160	0.0410	0.0810	0.1140	0.1400	0.5	0.043	0.02	0.02
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	823.9875	42.0	41	CW	E	1.01	BS2	0.0010	0.0030	0.0020	0.0070	0.0110	0.0250	0.0630	0.1300	0.1540	0.1310	0.5	0.053	0.03	0.03
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	851.0125	42.0	42	CW	E	1.03	BS2	0.0010	0.0020	0.0060	0.0070	0.0070	0.0330	0.0550	0.1040	0.1230	0.1150	0.5	0.047	0.02	0.02
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	860.5000	42.0	41	CW	E	1.04	BS2	0.0000	0.0020	0.0040	0.0090	0.0050	0.0250	0.0480	0.1360	0.1700	0.1170	0.5	0.053	0.03	0.03
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	868.9875	42.0	41	CW	E	1.04	BS2	0.0000	0.0000	0.0020	0.0030	0.0100	0.0280	0.0480	0.0900	0.1180	0.1020	0.5	0.042	0.02	0.02

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.1 (Continued)
APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	762.0125	36.0	35	CW	E	0.98	BS3	0.0060	0.0100	0.0110	0.0160	0.0110	0.0070	0.0280	0.0440	0.0470	0.0630	0.5	0.024	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	769.0125	36	35.2	CW	E	0.99	BS3	0.0060	0.0100	0.0110	0.0150	0.0110	0.0060	0.0280	0.0440	0.0470	0.0630	0.5	0.024	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	772.0000	36.0	35	CW	E	0.99	BS3	0.0080	0.0080	0.0110	0.0120	0.0130	0.0060	0.0230	0.0350	0.0460	0.0790	0.5	0.024	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	774.9875	36.0	35	CW	E	0.99	BS3	0.0040	0.0040	0.0130	0.0130	0.0140	0.0100	0.0310	0.0340	0.0380	0.0560	0.5	0.021	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	794.0125	36.0	35	CW	E	1.00	BS3	0.0030	0.0080	0.0120	0.0100	0.0100	0.0170	0.0360	0.0550	0.0760	0.0720	0.5	0.030	0.01	0.02
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	799.0125	36.0	36	CW	E	1.00	BS3	0.0030	0.0040	0.0070	0.0050	0.0080	0.0160	0.0380	0.0460	0.0690	0.0920	0.5	0.029	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	811.5000	42.0	42	CW	E	1.01	BS3	0.0040	0.0050	0.0070	0.0060	0.0060	0.0120	0.0360	0.0510	0.0650	0.0750	0.5	0.027	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	823.9875	42.0	41	CW	E	1.01	BS3	0.0030	0.0070	0.0090	0.0100	0.0130	0.0180	0.0410	0.0590	0.0740	0.0770	0.5	0.032	0.02	0.02
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	851.0125	42.0	42	CW	E	1.03	BS3	0.0030	0.0040	0.0080	0.0130	0.0100	0.0110	0.0280	0.0360	0.0620	0.0590	0.5	0.024	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	860.5000	42.0	41	CW	E	1.04	BS3	0.0030	0.0060	0.0080	0.0170	0.0160	0.0150	0.0300	0.0350	0.0600	0.0660	0.5	0.027	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	868.9875	42.0	41	CW	E	1.04	BS3	0.0020	0.0040	0.0070	0.0130	0.0100	0.0120	0.0290	0.0330	0.0640	0.0940	0.5	0.028	0.01	0.01

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.1 (Continued)

APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	762.0125	36.0	35	CW	E	0.98	BS4	0.0030	0.0070	0.0050	0.0110	0.0130	0.0090	0.0090	0.0250	0.0330	0.0330	0.5	0.015	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	769.0125	36	35.2	CW	E	0.99	BS4	0.0030	0.0070	0.0050	0.0110	0.0120	0.0100	0.0080	0.0250	0.0330	0.0340	0.5	0.015	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	772.0000	36.0	35	CW	E	0.99	BS4	0.0020	0.0050	0.0070	0.0100	0.0120	0.0110	0.0120	0.0230	0.0250	0.0280	0.5	0.013	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	774.9875	36.0	35	CW	E	0.99	BS4	0.0030	0.0040	0.0040	0.0100	0.0110	0.0110	0.0120	0.0260	0.0330	0.0330	0.5	0.015	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	794.0125	36.0	35	CW	E	1.00	BS4	0.0020	0.0040	0.0040	0.0070	0.0120	0.0120	0.0100	0.0190	0.0210	0.0320	0.5	0.012	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	799.0125	36.0	36	CW	E	1.00	BS4	0.0020	0.0070	0.0030	0.0100	0.0110	0.0090	0.0100	0.0270	0.0250	0.0250	0.5	0.013	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	811.5000	42.0	42	CW	E	1.01	BS4	0.0010	0.0020	0.0020	0.0040	0.0080	0.0050	0.0100	0.0240	0.0180	0.0250	0.5	0.010	0.00	0.00
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	823.9875	42.0	41	CW	E	1.01	BS4	0.0020	0.0040	0.0040	0.0060	0.0070	0.0050	0.0120	0.0280	0.0240	0.0240	0.5	0.012	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	851.0125	42.0	42	CW	E	1.03	BS4	0.0010	0.0030	0.0010	0.0050	0.0110	0.0090	0.0110	0.0290	0.0240	0.0240	0.5	0.012	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	860.5000	42.0	41	CW	E	1.04	BS4	0.0010	0.0020	0.0000	0.0030	0.0090	0.0120	0.0110	0.0310	0.0370	0.0390	0.5	0.015	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	868.9875	42.0	41	CW	E	1.04	BS4	0.0010	0.0020	0.0040	0.0070	0.0090	0.0070	0.0140	0.0290	0.0230	0.0220	0.5	0.012	0.01	0.01

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.1 (Continued)

APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	762.0125	36.0	35	CW	E	0.98	BS5	0.0010	0.0040	0.0050	0.0030	0.0070	0.0100	0.0130	0.0320	0.0440	0.0250	0.5	0.014	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	769.0125	36	35.2	CW	E	0.99	BS5	0.0010	0.0040	0.0040	0.0030	0.0070	0.0100	0.0130	0.0320	0.0420	0.0240	0.5	0.014	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	772.0000	36.0	35	CW	E	0.99	BS5	0.0010	0.0040	0.0020	0.0040	0.0120	0.0160	0.0170	0.0310	0.0570	0.0450	0.5	0.019	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	774.9875	36.0	35	CW	E	0.99	BS5	0.0030	0.0030	0.0030	0.0100	0.0150	0.0180	0.0160	0.0230	0.0490	0.0490	0.5	0.019	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	794.0125	36.0	35	CW	E	1.00	BS5	0.0020	0.0010	0.0010	0.0070	0.0130	0.0180	0.0150	0.0360	0.0470	0.0300	0.5	0.017	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	799.0125	36.0	36	CW	E	1.00	BS5	0.0000	0.0010	0.0020	0.0070	0.0150	0.0200	0.0230	0.0540	0.0620	0.0400	0.5	0.022	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	811.5000	42.0	42	CW	E	1.01	BS5	0.0010	0.0000	0.0030	0.0100	0.0150	0.0150	0.0140	0.0370	0.0400	0.0200	0.5	0.016	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	823.9875	42.0	41	CW	E	1.01	BS5	0.0010	0.0020	0.0030	0.0110	0.0140	0.0140	0.0110	0.0250	0.0320	0.0240	0.5	0.014	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	851.0125	42.0	42	CW	E	1.03	BS5	0.0020	0.0010	0.0020	0.0060	0.0090	0.0110	0.0060	0.0140	0.0180	0.0140	0.5	0.009	0.00	0.00
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	860.5000	42.0	41	CW	E	1.04	BS5	0.0000	0.0010	0.0000	0.0040	0.0060	0.0120	0.0060	0.0170	0.0350	0.0190	0.5	0.010	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	868.9875	42.0	41	CW	E	1.04	BS5	0.0010	0.0000	0.0010	0.0030	0.0050	0.0070	0.0060	0.0180	0.0220	0.0170	0.5	0.008	0.00	0.00

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.1 (Continued)

APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35	CW	E	0.98	BS1	0.0040	0.0160	0.0150	0.0270	0.0390	0.0920	0.1520	0.2960	0.2290	0.0590	0.5	0.091	0.05	0.05
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36	35.2	CW	E	0.99	BS1	0.0040	0.0160	0.0150	0.0270	0.0400	0.0920	0.1530	0.2930	0.2290	0.0600	0.5	0.092	0.05	0.05
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35	CW	E	0.99	BS1	0.0040	0.0180	0.0120	0.0210	0.0340	0.1170	0.1850	0.3320	0.2420	0.0700	0.5	0.102	0.05	0.05
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	35	CW	E	0.99	BS1	0.0050	0.0150	0.0100	0.0230	0.0340	0.1070	0.1600	0.3280	0.2010	0.0470	0.5	0.092	0.05	0.05
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	35	CW	E	1.00	BS1	0.0100	0.0110	0.0180	0.0250	0.0250	0.0740	0.1720	0.4320	0.3160	0.0830	0.5	0.116	0.06	0.06
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	36	CW	E	1.00	BS1	0.0070	0.0100	0.0130	0.0190	0.0230	0.0870	0.2260	0.4670	0.3340	0.0970	0.5	0.128	0.06	0.07
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42	CW	E	1.01	BS1	0.0030	0.0090	0.0130	0.0190	0.0180	0.0420	0.1570	0.3250	0.2410	0.0760	0.5	0.091	0.05	0.05
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	41	CW	E	1.01	BS1	0.0040	0.0060	0.0090	0.0130	0.0140	0.0620	0.1560	0.2680	0.2240	0.0850	0.5	0.085	0.04	0.04
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	42	CW	E	1.03	BS1	0.0020	0.0020	0.0070	0.0110	0.0350	0.0470	0.0480	0.1320	0.1320	0.0550	0.5	0.049	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41	CW	E	1.04	BS1	0.0060	0.0030	0.0050	0.0150	0.0310	0.0620	0.0830	0.2020	0.1860	0.0780	0.5	0.070	0.03	0.04
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41	CW	E	1.04	BS1	0.0030	0.0030	0.0070	0.0160	0.0230	0.0220	0.0600	0.1620	0.1330	0.0520	0.5	0.050	0.03	0.03

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.1 (Continued)

APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35	CW	E	0.98	BS2	0.0010	0.0030	0.0140	0.0200	0.0490	0.0640	0.1250	0.1990	0.1880	0.0930	0.5	0.074	0.04	0.04
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36	35.2	CW	E	0.99	BS2	0.0010	0.0030	0.0140	0.0200	0.0480	0.0640	0.1250	0.1980	0.1860	0.0900	0.5	0.074	0.04	0.04
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35	CW	E	0.99	BS2	0.0020	0.0050	0.0130	0.0300	0.0490	0.0600	0.1190	0.1990	0.2050	0.0690	0.5	0.074	0.04	0.04
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	35	CW	E	0.99	BS2	0.0000	0.0040	0.0140	0.0220	0.0330	0.0490	0.1040	0.1850	0.2040	0.0790	0.5	0.069	0.03	0.04
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	35	CW	E	1.00	BS2	0.0000	0.0110	0.0150	0.0260	0.0480	0.0410	0.0830	0.1390	0.1630	0.1150	0.5	0.064	0.03	0.03
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	36	CW	E	1.00	BS2	0.0010	0.0100	0.0140	0.0250	0.0480	0.0330	0.0910	0.1690	0.1680	0.0910	0.5	0.065	0.03	0.03
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42	CW	E	1.01	BS2	0.0010	0.0040	0.0060	0.0120	0.0240	0.0320	0.0760	0.1350	0.1400	0.0860	0.5	0.052	0.03	0.03
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	41	CW	E	1.01	BS2	0.0010	0.0050	0.0070	0.0130	0.0180	0.0460	0.1160	0.2080	0.1940	0.0810	0.5	0.070	0.03	0.04
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	42	CW	E	1.03	BS2	0.0010	0.0030	0.0080	0.0110	0.0090	0.0470	0.0880	0.1530	0.1320	0.0570	0.5	0.052	0.03	0.03
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41	CW	E	1.04	BS2	0.0010	0.0020	0.0050	0.0150	0.0080	0.0390	0.0900	0.2170	0.1870	0.0700	0.5	0.066	0.03	0.03
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41	CW	E	1.04	BS2	0.0000	0.0010	0.0050	0.0040	0.0140	0.0420	0.0760	0.1370	0.1180	0.0530	0.5	0.047	0.02	0.02

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.1 (Continued)

APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35	CW	E	0.98	BS3	0.0130	0.0200	0.0250	0.0320	0.0220	0.0170	0.0590	0.0800	0.0830	0.0730	0.5	0.042	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36	35.2	CW	E	0.99	BS3	0.0130	0.0200	0.0240	0.0310	0.0230	0.0170	0.0600	0.0830	0.0860	0.0740	0.5	0.043	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35	CW	E	0.99	BS3	0.0130	0.0160	0.0240	0.0260	0.0250	0.0170	0.0520	0.0630	0.0730	0.0920	0.5	0.040	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	35	CW	E	0.99	BS3	0.0080	0.0090	0.0250	0.0250	0.0230	0.0220	0.0680	0.0670	0.0560	0.0660	0.5	0.037	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	35	CW	E	1.00	BS3	0.0060	0.0120	0.0220	0.0160	0.0160	0.0350	0.0830	0.1110	0.1310	0.0900	0.5	0.052	0.03	0.03
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	36	CW	E	1.00	BS3	0.0060	0.0100	0.0150	0.0110	0.0180	0.0350	0.0800	0.0910	0.1120	0.1130	0.5	0.049	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42	CW	E	1.01	BS3	0.0060	0.0080	0.0120	0.0120	0.0130	0.0280	0.0740	0.0890	0.1090	0.0850	0.5	0.044	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	41	CW	E	1.01	BS3	0.0050	0.0100	0.0160	0.0200	0.0270	0.0400	0.0800	0.1020	0.1220	0.0900	0.5	0.052	0.03	0.03
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	42	CW	E	1.03	BS3	0.0040	0.0060	0.0140	0.0220	0.0210	0.0210	0.0500	0.0580	0.0840	0.0590	0.5	0.035	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41	CW	E	1.04	BS3	0.0040	0.0080	0.0140	0.0240	0.0250	0.0270	0.0580	0.0610	0.0900	0.0760	0.5	0.040	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41	CW	E	1.04	BS3	0.0030	0.0050	0.0110	0.0170	0.0160	0.0240	0.0480	0.0540	0.0910	0.0840	0.5	0.037	0.02	0.02

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.1 (Continued)

APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35	CW	E	0.98	BS4	0.0090	0.0110	0.0130	0.0220	0.0310	0.0250	0.0250	0.0550	0.0570	0.0470	0.5	0.029	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36	35.2	CW	E	0.99	BS4	0.0090	0.0110	0.0110	0.0220	0.0310	0.0240	0.0250	0.0530	0.0570	0.0470	0.5	0.029	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35	CW	E	0.99	BS4	0.0070	0.0110	0.0130	0.0160	0.0260	0.0270	0.0300	0.0480	0.0450	0.0390	0.5	0.026	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	35	CW	E	0.99	BS4	0.0070	0.0140	0.0120	0.0170	0.0260	0.0270	0.0320	0.0610	0.0530	0.0450	0.5	0.029	0.01	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	35	CW	E	1.00	BS4	0.0060	0.0110	0.0100	0.0230	0.0270	0.0200	0.0270	0.0540	0.0530	0.0470	0.5	0.028	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	36	CW	E	1.00	BS4	0.0060	0.0130	0.0120	0.0220	0.0250	0.0230	0.0270	0.0540	0.0540	0.0510	0.5	0.029	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42	CW	E	1.01	BS4	0.0030	0.0070	0.0040	0.0110	0.0180	0.0130	0.0230	0.0400	0.0260	0.0260	0.5	0.017	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	41	CW	E	1.01	BS4	0.0050	0.0070	0.0040	0.0100	0.0170	0.0100	0.0250	0.0470	0.0400	0.0450	0.5	0.021	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	42	CW	E	1.03	BS4	0.0020	0.0060	0.0020	0.0070	0.0170	0.0110	0.0220	0.0480	0.0330	0.0340	0.5	0.019	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41	CW	E	1.04	BS4	0.0020	0.0040	0.0030	0.0050	0.0100	0.0160	0.0340	0.0650	0.0500	0.0480	0.5	0.025	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41	CW	E	1.04	BS4	0.0020	0.0050	0.0030	0.0080	0.0160	0.0140	0.0240	0.0440	0.0330	0.0340	0.5	0.019	0.01	0.01

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.1 (Continued)

APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35	CW	E	0.98	BS5	0.0030	0.0080	0.0090	0.0100	0.0150	0.0180	0.0230	0.0620	0.0760	0.0340	0.5	0.025	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36	35.2	CW	E	0.99	BS5	0.0030	0.0090	0.0090	0.0090	0.0140	0.0190	0.0240	0.0650	0.0770	0.0340	0.5	0.026	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35	CW	E	0.99	BS5	0.0030	0.0090	0.0060	0.0120	0.0220	0.0310	0.0330	0.0720	0.1120	0.0630	0.5	0.036	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	35	CW	E	0.99	BS5	0.0060	0.0100	0.0070	0.0200	0.0310	0.0350	0.0260	0.0550	0.0940	0.0630	0.5	0.034	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	35	CW	E	1.00	BS5	0.0040	0.0030	0.0040	0.0180	0.0280	0.0330	0.0310	0.0770	0.0770	0.0340	0.5	0.031	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	36	CW	E	1.00	BS5	0.0010	0.0020	0.0050	0.0170	0.0300	0.0410	0.0440	0.1070	0.1050	0.0460	0.5	0.040	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42	CW	E	1.01	BS5	0.0020	0.0010	0.0050	0.0170	0.0240	0.0270	0.0270	0.0700	0.0650	0.0280	0.5	0.027	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	41	CW	E	1.01	BS5	0.0020	0.0030	0.0070	0.0190	0.0280	0.0300	0.0220	0.0500	0.0620	0.0360	0.5	0.026	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	42	CW	E	1.03	BS5	0.0050	0.0020	0.0050	0.0150	0.0130	0.0140	0.0090	0.0250	0.0300	0.0150	0.5	0.014	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41	CW	E	1.04	BS5	0.0030	0.0010	0.0030	0.0080	0.0110	0.0180	0.0130	0.0340	0.0460	0.0220	0.5	0.016	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41	CW	E	1.04	BS5	0.0020	0.0010	0.0030	0.0060	0.0090	0.0130	0.0140	0.0330	0.0340	0.0210	0.5	0.014	0.01	0.01

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.2

APX6500 7/800MHz - MPE measurement data for Passenger

D.U.T. Info.							Probe Info.			MPE Measurements			DUT Max. TX Factor	Avg. over Body (mW/cm ²)	Calc. P.D. (mW/cm ²)	Max Calc. P.D. (mW/cm ²)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Passenger/Operator (MC) Positions						
										Head/ Top 1/3	Chest/ Middle 1/3	Lower Trunk/ Bottom 1/3				
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35.2	CW	E	0.98	PB	0.036	0.024	0.038	0.5	0.032	0.02	0.02
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36.0	35.2	CW	E	0.99	PB	0.033	0.026	0.038	0.5	0.032	0.02	0.02
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35.0	CW	E	0.99	PB	0.035	0.031	0.041	0.5	0.035	0.02	0.02
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	34.9	CW	E	0.99	PB	0.036	0.035	0.037	0.5	0.036	0.02	0.02
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	34.6	CW	E	1.00	PB	0.042	0.036	0.024	0.5	0.034	0.02	0.02
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	35.5	CW	E	1.00	PB	0.034	0.033	0.025	0.5	0.031	0.02	0.02
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42.0	CW	E	1.01	PB	0.024	0.031	0.024	0.5	0.027	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	40.8	CW	E	1.01	PB	0.024	0.015	0.052	0.5	0.031	0.02	0.02
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	41.8	CW	E	1.03	PB	0.016	0.012	0.013	0.5	0.014	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41.1	CW	E	1.04	PB	0.021	0.022	0.016	0.5	0.020	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41.1	CW	E	1.04	PB	0.016	0.018	0.013	0.5	0.016	0.01	0.01

Notes:

MPE calculations are defined in section 15.0

Blue fonts: Frequencies not regulated by FCC.

Table F.2 (Continued)

APX6500 7/800MHz - MPE measurement data for Passenger

D.U.T. Info.							Probe Info.			MPE Measurements			DUT Max. TX Factor	Avg. over Body (mW/cm ²)	Calc. P.D. (mW/cm ²)	Max Calc. P.D. (mW/cm ²)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Passenger/Operator (MC) Positions						
										Head/ Top 1/3	Chest/ Middle 1/3	Lower Trunk/ Bottom 1/3				
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35.2	CW	E	0.98	PB	0.002	0.004	0.002	0.5	0.003	0.00	0.00
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36.0	35.2	CW	E	0.99	PB	0.002	0.004	0.003	0.5	0.003	0.00	0.00
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35.0	CW	E	0.99	PB	0.002	0.003	0.003	0.5	0.003	0.00	0.00
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	34.9	CW	E	0.99	PB	0.002	0.003	0.002	0.5	0.002	0.00	0.00
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	34.6	CW	E	1.00	PB	0.013	0.005	0.005	0.5	0.008	0.00	0.00
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	35.5	CW	E	1.00	PB	0.01	0.013	0.01	0.5	0.011	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42.0	CW	E	1.01	PB	0.018	0.027	0.017	0.5	0.021	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	40.8	CW	E	1.01	PB	0.018	0.013	0.043	0.5	0.025	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	41.8	CW	E	1.03	PB	0.024	0.015	0.022	0.5	0.021	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41.1	CW	E	1.04	PB	0.012	0.016	0.014	0.5	0.015	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41.1	CW	E	1.04	PB	0.028	0.017	0.015	0.5	0.021	0.01	0.01

Notes:

MPE calculations are defined in section 15.0

Blue fonts: Frequencies not regulated by FCC.

Table F.2 (Continued)

APX6500 7/800MHz - MPE measurement data for Passenger

D.U.T. Info.							Probe Info.			MPE Measurements			DUT Max. TX Factor	Avg. over Body (mW/cm ²)	Calc. P.D. (mW/cm ²)	Max Calc. P.D. (mW/cm ²)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Passenger/Operator (MC) Positions						
										Head/ Top 1/3	Chest/ Middle 1/3	Lower Trunk/ Bottom 1/3				
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	762.0125	36.0	35.2	CW	E	0.98	PB	0.037	0.031	0.027	0.5	0.031	0.02	0.02
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	769.0125	36.0	35.2	CW	E	0.99	PB	0.04	0.027	0.04	0.5	0.035	0.02	0.02
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	772.0000	36.0	35.0	CW	E	0.99	PB	0.033	0.027	0.039	0.5	0.033	0.02	0.02
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	774.9875	36.0	34.9	CW	E	0.99	PB	0.035	0.022	0.042	0.5	0.033	0.02	0.02
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	794.0125	36.0	34.6	CW	E	1.00	PB	0.046	0.034	0.031	0.5	0.037	0.02	0.02
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	799.0125	36.0	35.5	CW	E	1.00	PB	0.035	0.03	0.028	0.5	0.031	0.02	0.02
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	811.5000	42.0	42.0	CW	E	1.01	PB	0.02	0.026	0.024	0.5	0.023	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	823.9875	42.0	40.8	CW	E	1.01	PB	0.022	0.017	0.067	0.5	0.036	0.02	0.02
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	851.0125	42.0	41.8	CW	E	1.03	PB	0.022	0.015	0.016	0.5	0.018	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	860.5000	42.0	41.1	CW	E	1.04	PB	0.02	0.019	0.01	0.5	0.017	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	868.9875	42.0	41.1	CW	E	1.04	PB	0.025	0.014	0.012	0.5	0.018	0.01	0.01

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.2 (Continued)

APX6500 7/800MHz - MPE measurement data for Passenger

D.U.T. Info.							Probe Info.			MPE Measurements			DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Passenger/Operator (MC) Positions						
										Head/ Top 1/3	Chest/ Middle 1/3	Lower Trunk/ Bottom 1/3				
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35.2	CW	E	0.98	PB	0.066	0.04	0.07	0.5	0.058	0.03	0.03
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36.0	35.2	CW	E	0.99	PB	0.066	0.041	0.052	0.5	0.052	0.03	0.03
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35.0	CW	E	0.99	PB	0.054	0.04	0.073	0.5	0.055	0.03	0.03
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	34.9	CW	E	0.99	PB	0.055	0.041	0.072	0.5	0.055	0.03	0.03
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	34.6	CW	E	1.00	PB	0.053	0.058	0.053	0.5	0.055	0.03	0.03
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	35.5	CW	E	1.00	PB	0.06	0.053	0.045	0.5	0.053	0.03	0.03
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42.0	CW	E	1.01	PB	0.039	0.043	0.041	0.5	0.041	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	40.8	CW	E	1.01	PB	0.055	0.029	0.040	0.5	0.042	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	41.8	CW	E	1.03	PB	0.035	0.019	0.016	0.5	0.024	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41.1	CW	E	1.04	PB	0.040	0.043	0.025	0.5	0.037	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41.1	CW	E	1.04	PB	0.03	0.018	0.018	0.5	0.023	0.01	0.01

Notes:

MPE calculations are defined in section 15.0

Blue fonts: Frequencies not regulated by FCC.

Table F.2 (Continued)

APX6500 7/800MHz - MPE measurement data for Passenger

D.U.T. Info.							Probe Info.			MPE Measurements			DUT Max. TX Factor	Avg. over Body (mW/cm ²)	Calc. P.D. (mW/cm ²)	Max Calc. P.D. (mW/cm ²)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Passenger/Operator (MC) Positions						
										Head/ Top 1/3	Chest/ Middle 1/3	Lower Trunk/ Bottom 1/3				
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35.2	CW	E	0.98	PF	0.014	0.019	0.017	0.5	0.016	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36.0	35.2	CW	E	0.99	PF	0.016	0.025	0.019	0.5	0.020	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35.0	CW	E	0.99	PF	0.011	0.028	0.017	0.5	0.018	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	34.9	CW	E	0.99	PF	0.018	0.029	0.012	0.5	0.019	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	34.6	CW	E	1.00	PF	0.011	0.025	0.008	0.5	0.015	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	35.5	CW	E	1.00	PF	0.018	0.012	0.01	0.5	0.013	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42.0	CW	E	1.01	PF	0.013	0.018	0.015	0.5	0.015	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	40.8	CW	E	1.01	PF	0.024	0.017	0.017	0.5	0.020	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	41.8	CW	E	1.03	PF	0.02	0.016	0.013	0.5	0.017	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41.1	CW	E	1.04	PF	0.014	0.018	0.019	0.5	0.018	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41.1	CW	E	1.04	PF	0.018	0.014	0.01	0.5	0.015	0.01	0.01

Notes:

MPE calculations are defined in section 15.0

Blue fonts: Frequencies not regulated by FCC.

Table F.2 (Continued)

APX6500 7/800MHz - MPE measurement data for Passenger

D.U.T. Info.							Probe Info.			MPE Measurements			DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Passenger/Operator (MC) Positions						
										Head/ Top 1/3	Chest/ Middle 1/3	Lower Trunk/ Bottom 1/3				
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35.2	CW	E	0.98	PF	0.002	0.004	0.003	0.5	0.003	0.00	0.00
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36.0	35.2	CW	E	0.99	PF	0.003	0.004	0.003	0.5	0.003	0.00	0.00
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35.0	CW	E	0.99	PF	0.004	0.004	0.003	0.5	0.004	0.00	0.00
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	34.9	CW	E	0.99	PF	0.004	0.003	0.002	0.5	0.003	0.00	0.00
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	34.6	CW	E	1.00	PF	0.006	0.008	0.004	0.5	0.006	0.00	0.00
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	35.5	CW	E	1.00	PF	0.004	0.010	0.007	0.5	0.007	0.00	0.00
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42.0	CW	E	1.01	PF	0.009	0.019	0.009	0.5	0.012	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	40.8	CW	E	1.01	PF	0.023	0.010	0.014	0.5	0.016	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	41.8	CW	E	1.03	PF	0.029	0.030	0.008	0.5	0.023	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41.1	CW	E	1.04	PF	0.020	0.025	0.015	0.5	0.021	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41.1	CW	E	1.04	PF	0.021	0.014	0.011	0.5	0.016	0.01	0.01

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.2 (Continued)

APX6500 7/800MHz - MPE measurement data for Passenger

D.U.T. Info.							Probe Info.			MPE Measurements			DUT Max. TX Factor	Avg. over Body (mW/cm ²)	Calc. P.D. (mW/cm ²)	Max Calc. P.D. (mW/cm ²)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Passenger/Operator (MC) Positions						
										Head/ Top 1/3	Chest/ Middle 1/3	Lower Trunk/ Bottom 1/3				
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	762.0125	36.0	35.2	CW	E	0.98	PF	0.015	0.022	0.017	0.5	0.018	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	769.0125	36.0	35.2	CW	E	0.99	PF	0.017	0.024	0.018	0.5	0.019	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	772.0000	36.0	35.0	CW	E	0.99	PF	0.013	0.016	0.014	0.5	0.014	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	774.9875	36.0	34.9	CW	E	0.99	PF	0.01	0.026	0.013	0.5	0.016	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	794.0125	36.0	34.6	CW	E	1.00	PF	0.013	0.021	0.007	0.5	0.014	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	799.0125	36.0	35.5	CW	E	1.00	PF	0.016	0.016	0.01	0.5	0.014	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	811.5000	42.0	42.0	CW	E	1.01	PF	0.01	0.025	0.011	0.5	0.015	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	823.9875	42.0	40.8	CW	E	1.01	PF	0.023	0.018	0.019	0.5	0.020	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	851.0125	42.0	41.8	CW	E	1.03	PF	0.021	0.016	0.01	0.5	0.016	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	860.5000	42.0	41.1	CW	E	1.04	PF	0.017	0.016	0.014	0.5	0.016	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	868.9875	42.0	41.1	CW	E	1.04	PF	0.016	0.014	0.008	0.5	0.013	0.01	0.01

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.2 (Continued)

APX6500 7/800MHz - MPE measurement data for Passenger

D.U.T. Info.							Probe Info.			MPE Measurements			DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Passenger/Operator (MC) Positions						
										Head/ Top 1/3	Chest/ Middle 1/3	Lower Trunk/ Bottom 1/3				
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35.2	CW	E	0.98	PF	0.032	0.042	0.033	0.5	0.035	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36.0	35.2	CW	E	0.99	PF	0.033	0.038	0.034	0.5	0.035	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35.0	CW	E	0.99	PF	0.029	0.038	0.033	0.5	0.033	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	34.9	CW	E	0.99	PF	0.016	0.049	0.021	0.5	0.028	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	34.6	CW	E	1.00	PF	0.026	0.044	0.015	0.5	0.028	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	35.5	CW	E	1.00	PF	0.026	0.027	0.019	0.5	0.024	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42.0	CW	E	1.01	PF	0.014	0.035	0.018	0.5	0.022	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	40.8	CW	E	1.01	PF	0.046	0.028	0.021	0.5	0.032	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	41.8	CW	E	1.03	PF	0.034	0.024	0.011	0.5	0.024	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41.1	CW	E	1.04	PF	0.022	0.026	0.016	0.5	0.022	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41.1	CW	E	1.04	PF	0.021	0.017	0.011	0.5	0.017	0.01	0.01

Notes:

MPE calculations are defined in section 15.0

Blue fonts: Frequencies not regulated by FCC.

Appendix G – MPE Test Results Summary for Companion Device (DVR 700)

Table G.1

Companion Device (DVR 700) - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm ²)	Calc. P.D. (mW/cm ²)	Max Calc. P.D. (mW/cm ²)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Trunk	HAF4016A, 1/4 Wave (764-870MHz)	2.15	770.0000	5.00	4.82	CW	E	1.16	BS1	0.001	0.001	0.002	0.003	0.003	0.004	0.006	0.003	0.006	0.004	1.0	0.003	0.004	0.004
Trunk	HAF4016A, 1/4 Wave (764-870MHz)	2.15	775.0000	5.00	4.79	CW	E	1.16	BS1	0.001	0.001	0.001	0.001	0.003	0.004	0.004	0.003	0.003	0.005	1.0	0.003	0.003	0.003
Trunk	HAF4016A, 1/4 Wave (764-870MHz)	2.15	800.0000	5.00	4.86	CW	E	1.17	BS1	0.001	0.001	0.001	0.001	0.001	0.001	0.002	0.002	0.003	0.004	1.0	0.002	0.002	0.002
Trunk	HAF4016A, 1/4 Wave (764-870MHz)	2.15	806.0000	5.00	4.88	CW	E	1.16	BS1	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.004	0.004	1.0	0.002	0.002	0.002
Trunk	HAF4016A, 1/4 Wave (764-870MHz)	2.15	770.0000	5.00	4.82	CW	E	1.16	BS2	0.003	0.002	0.004	0.003	0.006	0.010	0.015	0.015	0.016	0.017	1.0	0.009	0.011	0.011
Trunk	HAF4016A, 1/4 Wave (764-870MHz)	2.15	775.0000	5.00	4.79	CW	E	1.16	BS2	0.002	0.002	0.003	0.004	0.007	0.006	0.014	0.015	0.017	0.017	1.0	0.009	0.010	0.011
Trunk	HAF4016A, 1/4 Wave (764-870MHz)	2.15	800.0000	5.00	4.86	CW	E	1.17	BS2	0.001	0.001	0.001	0.002	0.005	0.009	0.008	0.014	0.012	0.012	1.0	0.007	0.008	0.008
Trunk	HAF4016A, 1/4 Wave (764-870MHz)	2.15	806.0000	5.00	4.88	CW	E	1.16	BS2	0.001	0.001	0.001	0.003	0.005	0.009	0.010	0.013	0.013	0.009	1.0	0.007	0.008	0.008
Trunk	HAF4016A, 1/4 Wave (764-870MHz)	2.15	770.0000	5.00	4.82	CW	E	1.16	BS3	0.002	0.003	0.005	0.006	0.011	0.020	0.020	0.020	0.018	0.017	1.0	0.012	0.014	0.015
Trunk	HAF4016A, 1/4 Wave (764-870MHz)	2.15	775.0000	5.00	4.79	CW	E	1.16	BS3	0.003	0.004	0.007	0.009	0.015	0.016	0.028	0.025	0.025	0.020	1.0	0.015	0.018	0.018
Trunk	HAF4016A, 1/4 Wave (764-870MHz)	2.15	800.0000	5.00	4.86	CW	E	1.17	BS3	0.001	0.002	0.003	0.003	0.003	0.006	0.010	0.011	0.013	0.011	1.0	0.006	0.007	0.008
Trunk	HAF4016A, 1/4 Wave (764-870MHz)	2.15	806.0000	5.00	4.88	CW	E	1.16	BS3	0.001	0.001	0.002	0.002	0.004	0.006	0.009	0.012	0.011	0.009	1.0	0.006	0.007	0.007

MPE calculations are defined in section 15.0.

Table G.1 (Continued)
Companion Device (DVR 700) - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Trunk	HAF4016A, 1/4 Wave (764-870MHz)	2.15	770.0000	5.00	4.82	CW	E	1.16	BS4	0.003	0.003	0.007	0.014	0.018	0.027	0.026	0.017	0.015	0.010	1.0	0.014	0.016	0.017
Trunk	HAF4016A, 1/4 Wave (764-870MHz)	2.15	775.0000	5.00	4.79	CW	E	1.16	BS4	0.004	0.004	0.004	0.015	0.023	0.022	0.021	0.022	0.012	0.011	1.0	0.014	0.016	0.017
Trunk	HAF4016A, 1/4 Wave (764-870MHz)	2.15	800.0000	5.00	4.86	CW	E	1.17	BS4	0.001	0.002	0.003	0.009	0.012	0.018	0.014	0.011	0.011	0.012	1.0	0.009	0.011	0.011
Trunk	HAF4016A, 1/4 Wave (764-870MHz)	2.15	806.0000	5.00	4.88	CW	E	1.16	BS4	0.001	0.002	0.004	0.007	0.008	0.013	0.009	0.011	0.013	0.011	1.0	0.008	0.009	0.009
Trunk	HAF4016A, 1/4 Wave (764-870MHz)	2.15	770.0000	5.00	4.82	CW	E	1.16	BS5	0.004	0.004	0.006	0.015	0.021	0.025	0.028	0.023	0.021	0.018	1.0	0.017	0.019	0.020
Trunk	HAF4016A, 1/4 Wave (764-870MHz)	2.15	775.0000	5.00	4.79	CW	E	1.16	BS5	0.005	0.005	0.006	0.012	0.015	0.027	0.026	0.023	0.024	0.022	1.0	0.017	0.019	0.020
Trunk	HAF4016A, 1/4 Wave (764-870MHz)	2.15	800.0000	5.00	4.86	CW	E	1.17	BS5	0.002	0.002	0.002	0.006	0.007	0.009	0.006	0.008	0.009	0.015	1.0	0.007	0.008	0.008
Trunk	HAF4016A, 1/4 Wave (764-870MHz)	2.15	806.0000	5.00	4.88	CW	E	1.16	BS5	0.001	0.002	0.002	0.006	0.008	0.009	0.007	0.008	0.009	0.009	1.0	0.006	0.007	0.007

MPE calculations are defined in section 15.0.

Table G.2
Companion Device (DVR 700) - MPE measurement data for Passenger

D.U.T. Info.							Probe Info.		Test Pos.	MPE Measurements			DUT Max. TX Factor	Avg. over Body (mW/cm ²)	Calc. P.D. (mW/cm ²)	Max Calc. P.D. (mW/cm ²)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor		Passenger/Operator (MC) Positions						
										Head/ Top 1/3	Chest/ Middle 1/3	Lower Trunk/ Bottom 1/3				
Trunk	HAF4016A, 1/4 Wave (764-870MHz)	2.15	770.0000	5.00	4.82	CW	E	1.16	PB	0.049	0.018	0.020	1.0	0.029	0.034	0.035
Trunk	HAF4016A, 1/4 Wave (764-870MHz)	2.15	775.0000	5.00	4.79	CW	E	1.16	PB	0.044	0.024	0.026	1.0	0.031	0.036	0.038
Trunk	HAF4016A, 1/4 Wave (764-870MHz)	2.15	800.0000	5.00	4.86	CW	E	1.17	PB	0.015	0.016	0.024	1.0	0.018	0.021	0.022
Trunk	HAF4016A, 1/4 Wave (764-870MHz)	2.15	806.0000	5.00	4.88	CW	E	1.16	PB	0.023	0.018	0.011	1.0	0.017	0.020	0.021
Trunk	HAF4016A, 1/4 Wave (764-870MHz)	2.15	770.0000	5.00	4.82	CW	E	1.16	PF	0.017	0.027	0.011	1.0	0.018	0.021	0.022
Trunk	HAF4016A, 1/4 Wave (764-870MHz)	2.15	775.0000	5.00	4.79	CW	E	1.16	PF	0.024	0.037	0.017	1.0	0.026	0.030	0.031
Trunk	HAF4016A, 1/4 Wave (764-870MHz)	2.15	800.0000	5.00	4.86	CW	E	1.17	PF	0.013	0.012	0.007	1.0	0.011	0.012	0.013
Trunk	HAF4016A, 1/4 Wave (764-870MHz)	2.15	806.0000	5.00	4.88	CW	E	1.16	PF	0.011	0.011	0.006	1.0	0.009	0.011	0.011

MPE calculations are defined in section 15.0.