

RF Exposure / MPE Calculation

No. : 30KE0260-HO-02

Applicant : Canon Inc.
Type of Equipment : Wireless Microphone
Model No. : DV840210
FCC ID : AZD210
IC Number :

Canon Inc. declares that Model : DV840210
complies with FCC radiation exposure requirement specified in the FCC Rules 2.1093(for portable).

The “DV840210“ has 11.27 mW of conducted Peak Output power and 12.65 mW of EIRP.
This kind of equipment is below 60/frequency[GHz] mW(TCB Exclusion List)
so that SAR testing is excluded. The Following calculation is the reference data for 20cm distance.

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided with the “DV840210“ as calculated from FCC OET Bulletin 65 Appendix A, Table (B) Limits for General Population / Uncontrolled Exposure. This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1.0mW/cm² uncontrolled exposure limit. The Friis formula used was:

$$S = (P * G) / (4 * \pi * r^2)$$

Where

P = 11.27 mW (Maximum peak output power)
G = 1.12 Numerical Antenna gain; equal to 0.50 dBi
r = 20.0 cm

For: DV840210

S = 0.00252 mW/cm²

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124