



# SAR TEST REPORT

## Test Report No.: 10004211S-A

**Applicant** : Canon Inc.  
**Type of Equipment** : Wireless Module  
**Model No.** : WM222 (\*. Installed into the WM222's platform (1))  
**FCC ID** : AZD222  
**Test Standard** : FCC 47CFR §2.1093,  
Supplement C (Edition 01-01) to OET Bulletin 65  
**Test Result** : Complied

Highest Reported SAR(1g) Value	Platform #	Platform type	Platform model	Remarks
0.89 W/kg	Platform (1)	Digital camera (1)	PC2035	(DTS) 2437MHz, IEEE 802.11b, (1Mbps, DBPSK/DSSS) *. Highest measured SAR(1g) value: 0.62 W/kg

\*. **Highest reported SAR (1g) across exposure conditions for a platform (1) = 0.89 W/kg = grant listing.**  
\*. Since highest reported SAR (1g) on the platform (1) which obtained in accordance with KDB447498 (v05) was under 1.2 W/kg, this EUT was approved to operate a single platform which was tested in this report.

1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the limits of the above regulation.
4. The test results in this test report are traceable to the national or international standards.
5. This test report must not be used by the customer to claim product certification, approval, or endorsement by any agency of the Federal Government.
6. The opinions and the interpretations to the result of the description in this report are outside scopes where UL Japan has been accredited.

**Date of test:** April 9, 2013

**Test engineer:** *Hiroshi Naka*

Hiroshi Naka  
Engineer of WiSE Japan, UL Verification Service

**Approved by:** *Toyokazu Imamura*

Toyokazu Imamura  
Leader of WiSE Japan, UL Verification Service

The testing in which "Non-accreditation" is displayed is outside the accreditation scopes in UL Japan.  
 There is no testing item of "Non-accreditation".



## **REVISION HISTORY**

Revision	Test report No.	Date	Page revised	Contents
Original	10004211S-A	May 13, 2013	-	
1	10004211S-A	June 28, 2013	P1,2,12	Clerical error correction.
2	10004211S-A	July 2, 2013	P1,2,9	Clerical error correction.

\* By issue of new revision report, the report of an old revision becomes invalid.

## **CONTENTS**

	<b>PAGE</b>	
<b>REVISION HISTORY</b>	2	
<b>CONTENTS</b>	2	
<b>SECTION 1:</b>	<b>Customer information</b> .....	<b>3</b>
<b>SECTION 2:</b>	<b>Equipment under test (EUT)</b> .....	<b>3</b>
2.1	Identification of EUT .....	3
2.2	Product Description .....	3
2.3	Tx output power specification (antenna port terminal conducted) .....	4
2.4	Maximum output power which may possible .....	4
<b>SECTION 3:</b>	<b>Test specification, procedures and results</b> .....	<b>5</b>
3.1	Test specification .....	5
3.2	Exposure limit .....	5
3.3	Procedure and result .....	5
3.4	Test location .....	5
3.5	Confirmation before SAR testing .....	6
3.6	Confirmation after SAR testing .....	6
3.7	Test setup of EUT and SAR measurement procedure .....	7
<b>SECTION 4:</b>	<b>Operation of EUT during testing</b> .....	<b>7</b>
<b>SECTION 5:</b>	<b>Uncertainty assessment (SAR measurement)</b> .....	<b>8</b>
<b>SECTION 6:</b>	<b>Confirmation before testing</b> .....	<b>9</b>
6.1	Assessment for the conducted power of EUT .....	9
<b>SECTION 7:</b>	<b>Measurement results</b> .....	<b>10</b>
7.1	SAR (Body) test results of platform (1) .....	10

## **Contents of appendixes**

<b>APPENDIX 1:</b>	<b>Photographs of test setup</b> .....	<b>11</b>
Appendix 1-1	Photograph of Platform (1) .....	11
Appendix 1-2	EUT and support equipment .....	12
Appendix 1-3	Photograph of test setup / Platform (1) .....	13
<b>APPENDIX 2:</b>	<b>SAR Measurement data</b> .....	<b>16</b>
Appendix 2-1	Evaluation procedure .....	16
Appendix 2-2	Measurement data / Platform (1) .....	17
<b>APPENDIX 3:</b>	<b>Test instruments</b> .....	<b>25</b>
Appendix 3-1	Equipment used .....	25
Appendix 3-2	Configuration and peripherals .....	26
Appendix 3-3	Test system specification .....	27
Appendix 3-4	Simulated tissues composition and parameter confirmation .....	28
Appendix 3-5	Daily check data .....	28
Appendix 3-6	Daily check measurement data .....	29
Appendix 3-7	Daily check uncertainty .....	29
Appendix 3-8	Calibration certificate: E-Field Probe (EX3DV4) .....	30
Appendix 3-9	Calibration certificate: Dipole (D2450V2) .....	41

## **SECTION 1: Customer information**

Company Name	Canon Inc.
Brand Name	Canon
Address	30-2, Shimomaruko 3-chome, Ohta-ku, Tokyo 146-8501 Japan
Telephone Number	+81-3-5482-8070
Facsimile Number	+81-3-3757-8431
Contact Person	Hironobu Saida

## **SECTION 2: Equipment under test (EUT)**

### **2.1 Identification of EUT**

Type of Equipment	Wireless Module
Model Number	WM222
Serial Number	4EE (WM222)
Condition of EUT	WM222: Production model Platform (1): Engineering prototype (Digital camera (1), model: PC2035) (*. Not for sale: This sample is equivalent to mass-produced items.)
Receipt Date of Sample	January 30, 2013 (*. EUT for the power measurement.) March 21, 2013 (*. EUT for the SAR test. The EUT that had been measured the power of SAR test reference, was installed into the Platform (1)-Digital camera (1) from the beginning.) *. After power measurement, the EUT was returned to the customer, and the RF wiring was changed to the original antenna line form the antenna conducted power measurement line of the SAR test. The EUT was installed into a Platform (1) which SAR tested, by the customer. *. No modification by the Lab.
Country of Mass-production	WM222: Philippines / Platform (1): Japan
Category Identified	Portable device *. Since EUT may contact and/or very close to a human body during Wi-Fi operation, the partial-body SAR (1g) shall be observed.
Rating	DC3.3V supplied form the platform equipment. *. The EUT is installed into the specified the platform that was operated by the re-chargeable Li-ion battery. Therefore, each SAR test, the platform which had built-in EUT was operated with full-charged battery.
Feature of EUT	The EUT is a Wireless Module which installs into the specified platform.
Platform model of EUT	Platform (1) - Digital camera (1), model: PC2035

### **2.2 Product Description (Wireless module: WM222)**

Equipment type	Transceiver
Frequency of operation	2412-2462MHz (11b,11g,,11n(20HT)), 2422-2452MHz (11n(40HT))
Channel spacing	5MHz
Bandwidth	20MHz(11b,11g,,11n(20HT)), 40MHz(11n(40HT))
ITU code	G1D(11b), D1D(11g,11n(20HT),11n(40HT))
Type of modulation	DSSS(11b); CCK, DQPSK, DBPSK OFDM(11g,11n(20HT),11n(40HT)): 64QAM, 16QAM, QPSK, BPSK
Q'ty of Antenna	1 pc.
Antenna type	Monopole type chip antenna
Antenna gain (peak)	-0.94dBi
Transmit power and tolerance (Manufacture variation)	11b: 14dBm $\pm 2.5$ dBm 11n(20HT): 12dBm $\pm 2.5$ dBm 11g: 12dBm $\pm 2.5$ dBm 11n(40HT): 11dBm $\pm 2.5$ dBm *. Refer to clause 2.3 for more detail. *. The measured Tx output power (conducted) refers to section 6 in this report.
Maximum output power which may possible	11b: 16.5dBm 11n(20HT): 14.5dBm 11g: 14.5dBm 11n(40HT): 13.5dBm *. Refer to clause 2.4 for more detail.
Power supply	DC 3.3V (*. The power of DC3.3V is supplied from the platform via constant voltage circuit.)
Operation temperature range	-20 to +55 deg.C

\*. The EUT do not use the special transmitting technique such as "beam-forming" and "time-space code diversity."

### 2.3 Tx output power specification (antenna port terminal conducted)

[MHz]	CH	Target Power [dBm] (average)																										
		11b				11g								11n(20HT)														
		1	2	5.5	11	6	9	12	18	24	36	48	54	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14
2412	1	14	14	14	14	14	14	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12
2417	2	14	14	14	14	14	14	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12
2422	3	14	14	14	14	14	14	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12
2427	4	14	14	14	14	14	14	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12
2432	5	14	14	14	14	14	14	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12
2437	6	14	14	14	14	14	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12
2442	7	14	14	14	14	14	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12
2447	8	14	14	14	14	14	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12
2452	9	14	14	14	14	14	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12
2457	10	14	14	14	14	14	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12
2462	11	14	14	14	14	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12

[MHz]	CH	Target Power [dBm] (average)													
		11n(40HT)													
MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15
2422	3	11	11	11	11	11	11	11	11	11	11	11	11	11	11
2427	4	11	11	11	11	11	11	11	11	11	11	11	11	11	11
2432	5	11	11	11	11	11	11	11	11	11	11	11	11	11	11
2437	6	11	11	11	11	11	11	11	11	11	11	11	11	11	11
2442	7	11	11	11	11	11	11	11	11	11	11	11	11	11	11
2447	8	11	11	11	11	11	11	11	11	11	11	11	11	11	11
2452	9	11	11	11	11	11	11	11	11	11	11	11	11	11	11

### 2.4 Maximum output power which may possible

[MHz]	CH	Target Power [dBm] (average)																									
		11b				11g								11n(20HT)													
		1	2	5.5	11	6	9	12	18	24	36	48	54	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9	MCS10	MCS11	MCS12	MCS13
2412	1	16.5	16.5	16.5	16.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	
2417	2	16.5	16.5	16.5	16.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	
2422	3	16.5	16.5	16.5	16.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	
2427	4	16.5	16.5	16.5	16.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	
2432	5	16.5	16.5	16.5	16.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	
2437	6	16.5	16.5	16.5	16.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	
2442	7	16.5	16.5	16.5	16.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	
2447	8	16.5	16.5	16.5	16.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	
2452	9	16.5	16.5	16.5	16.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	
2457	10	16.5	16.5	16.5	16.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	
2462	11	16.5	16.5	16.5	16.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	

[MHz]	CH	Target Power [dBm] (average)														
		11n(40HT)														
MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15	
2422	3	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	
2427	4	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5
2432	5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5
2437	6	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5
2442	7	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5
2447	8	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5
2452	9	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5

## SECTION 3: Test specification, procedures and results

### 3.1 Requirements for compliance testing defined by the FCC / Test specification

The US Federal Communications Commission has released the report and order "Guidelines for Evaluating the Environmental Effects of RF Radiation", ET Docket No. 93-62 in August 1996. The order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 mW/g for an uncontrolled environment and 8.0 mW/g for an occupational/controlled environment as recommended by the ANSI/IEEE standard C95.1-1992. According to the Supplement C of OET Bulletin 65 "Evaluating Compliance with FCC Guide-lines for Human Exposure to Radio frequency Electromagnetic Fields", released on Jun 29, 2001 by the FCC, the device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.

1. Specific Absorption Rate (SAR) is a measure of the rate of energy absorption due to exposure to an RF transmitting source (wireless portable device).
2. IEEE/ANSI Std. C95.1-1992 limits are used to determine compliance with FCC ET Docket 93-62.

### Supplement C (Edition 01-01) to OET Bulletin 65 (Edition 97-01):

Supplement C (Edition 01-01) - Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions

OET Bulletin 65 (Edition 97-01) - Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields

### IEEE Std. 1528-2003:

IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques Supplement C

In additions:

- KDB 447498 D01 (v05):** General RF exposure guidance
- KDB 865664 D01 (v01):** SAR measurement 100MHz to 6GHz
- KDB 248227 D01 (v01r02):** SAR measurement procedures for 802.11a/b/g transmitters

\*. In this report, IEC 62209-1:2005 and IEC 62209-2:2010-03 are also considered as reference. The comment is attached to the portion to which IEC 62209-1 and IEC 62209-2 were referred to specially.

### 3.2 Exposure limit

Environments of exposure limit	Whole-Body (averaged over the entire body)	Partial-Body (averaged over any 1g of tissue)	Hands, Wrists, Feet and Ankles (averaged over any 10g of tissue)
<b>(A) Limits for Occupational /Controlled Exposure (W/kg)</b>	0.4	8.0	20.0
<b>(B) Limits for General population /Uncontrolled Exposure (W/kg)</b>	0.08	1.6	4.0

\*.Occupational/Controlled Environments: are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

\*.General Population/Uncontrolled Environments: are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

The limit applied in this test report is;

General population / uncontrolled exposure, Partial-Body (averaged over any 1g of tissue) limit: 1.6 W/kg

### 3.3 Procedures and Results

	Wi-Fi (DTS) / in Platform (1)
Test Procedure	FCC OET Bulletin 65, Supplement C SAR
Category	FCC 47CFR §2.1093
Results (SAR(1g))	Complied
Reported SAR value (* Scaled)	<b>0.89 W/kg</b>
Measured SAR value	<b>0.615 W/kg</b>
Operation mode	11b, 1Mbps, DSSS, 2437 MHz (6ch)
Output power (scaled factor)	14.89 dBm (x1.45)

Note: UL Japan's SAR Work Procedures No.13-EM-W0429 and 13-EM-W0430. No addition, deviation nor exclusion has been made from standards

**Test outline:** Where this product is built into a new platform, it was verified whether multiplatform conditions can be suited in according with section 2) of 5.2.2 in KDB447498 D01 (v05).

**Consideration of the test results:** The highest reported SAR (1g) of Platform (1) was kept  $\leq 1.2\text{W/kg}$ .

Since highest reported SAR (1g) on the platform (1) which obtained in accordance with KDB447498 (v05) was under 1.2 W/kg, this EUT was approved to operate a single platform which was tested in this report.

### 3.4 Test Location

No.7 shielded room (2.76m (Width)  $\times$  3.76m (Depth)  $\times$  2.4m (Height)) for SAR testing.

#### UL Japan, Inc., Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken 259-1220 JAPAN

Telephone number: +81 463 50 6400 / Facsimile number: +81 463 50 6401

---

#### UL Japan, Inc. Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN  
Telephone: +81 463 50 6400 / Facsimile: +81 463 50 6401

### 3.5 Confirmation before SAR testing

#### 3.5.1 Correlation of Output Power between EMC and SAR tests

It was checked that the antenna port power was correlated within 0~+5% (FCC requirements). The result is shown in Section 6.

Test	Remarks	Serial number
<b>SAR</b>	Before SAR test, the RF wiring for the sample that was actually used for the SAR test, had been switched to the antenna conducted power measurement line from the antenna line, and then the average power was measured. The average and peak power of specified operation mode(s) were measured at default channel. After power measurement, the EUT was returned to the customer. Then, the EUT was installed in a Platform (1) which SAR tested, by the customer. *. Refer to the Section 6 in this report for the power measurement of SAR sample result. *. The power was measured by the calibrated power sensor and power meter (65MHz measurement bandwidth).	4EE
<b>EMC</b>	The EUT of the EMC test was measured for the peak power. The average power that was reference of SAR test was also measured additionally.	34F

#### 3.5.2 Average power for SAR tests

##### Step.1 Data rate check

The EUT supported the following data rate in each operation mode.

Even if the target power of 11b mode was more than 2dB higher than other operation mode (11g, 11n(20HT), 11n(40HT)), the average powers related with all data rate were measured for all operation mode.

11b		11g		11n(20HT)			11n(40HT)		
Modulation	Data rate [Mbps]	Modulation	Data rate [Mbps]	MCS Index	Spatial Stream	Modulation	MCS Index	Spatial Stream	Modulation
DBPSK/DSSS	1	BPSK/OFDM	6	MCS0	1	BPSK/OFDM	MCS0	1	BPSK/OFDM
DQPSK/DSSS	2	BPSK/OFDM	9	MCS1	1	QPSK/OFDM	MCS1	1	QPSK/OFDM
CCK/DSSS	5.5	QPSK/OFDM	12	MCS2	1	QPSK/OFDM	MCS2	1	QPSK/OFDM
CCK/DSSS	11	QPSK/OFDM	18	MCS3	1	16QAM/OFDM	MCS3	1	16QAM/OFDM
		16QAM/OFDM	24	MCS4	1	16QAM/OFDM	MCS4	1	16QAM/OFDM
		16QAM/OFDM	36	MCS5	1	64QAM/OFDM	MCS5	1	64QAM/OFDM
		64QAM/OFDM	48	MCS6	1	64QAM/OFDM	MCS6	1	64QAM/OFDM
		64QAM/OFDM	54	MCS7	1	64QAM/OFDM	MCS7	1	64QAM/OFDM

##### Step.2 Decision of SAR test channel

The following operation mode, data rate and channels were determined by the SAR reference power measured.

Mode	MHz	Channel	SAR tested channel				Remarks
			default	11b/g/n(20HT)	11b	11g	
802.11 b/g/n	2412	1 (*1)	✓	#	n/a (*2)	n/a (*2)	SAR test was only applied to 11b mode, in lowest data rate. (*2)
	2422	3					
	2437	6	✓	#	n/a (*2)	n/a (*2)	
	2452	9					
	2462	11 (*1)	✓	#	n/a (*2)	n/a (*2)	

✓ = "default test channels of requested by KDB248227", n/a: SAR test was not applied, # = SAR test was applied.

\*1. Any output power reducing for channel 1 and 11 to meet restricted band requirements was not observed. Therefore channel 1 and 11 was selected for the default channels and SAR test was applied.

\*2. Since the target average power of 11g, 11n(20HT) and 11n(40HT) were more than 2dB lower than the corresponded 11b power, SAR test was not applied to the 11g, 11n(20HT) and 11n(40HT) mode. In 11b mode, the average power of higher data rate was less than 0.25dB higher than the lowest data rate. Therefore, SAR test was only applied to the lowest data rate. (KDB248227) (Refer to Section 6.)

### 3.6 Confirmation after SAR testing

It was checked that the power drift [W] is within  $\pm 5\%$  in the evaluation procedure of SAR testing. The verification of power drift during the SAR test is that DASY5 system calculates the power drift by measuring the e-filed at the same location at beginning and the end of the scan measurement for each test position.

The result is shown in APPENDIX 2.

\*. DASY5 system calculation Power drift value[dB] =  $20\log(Ea)/(Eb)$  (where, Before SAR testing: Eb[V/m] / After SAR testing: Ea[V/m])

Limit of power drift[W] =  $\pm 5\%$

Power drift limit (X) [dB] =  $10\log(P_{\text{drift}}) = 10\log(1.05/1) = 10\log(1.05) - 10\log(1) = 0.21\text{dB}$   
from E-filed relations with power.

$S = E \times H = E^2 / \eta = P / (4 \times \pi \times r^2)$  ( $\eta$ : Space impedance)  $\rightarrow P = (E^2 \times 4 \times \pi \times r^2) / \eta$

Therefore, The correlation of power and the E-filed

Power drift limit (X) dB =  $10\log(P_{\text{drift}}) = 10\log(E_{\text{drift}})^2 = 20\log(E_{\text{drift}})$

From the above mentioned, the calculated power drift of DASY5 system must be the less than  $\pm 0.21\text{dB}$ .

### 3.7 Test setup of EUT and SAR measurement procedure

After considering the outline of EUT, the SAR test was carried out on the following setup conditions.

\*. Refer to Appendix 1 for test setup photographs.

Setup	Explanation of EUT setup position	Antenna to user distance	Applied SAR test?	SAR type
<b>Left-top</b>	The portion with inclination of the left-hand side upper part of EUT was touched to the Flat phantom.	5.62mm	applied	Body (touch)
<b>Rear-top</b>	The portion near the antenna of the rear side (LCD side) of EUT was touched to the Flat phantom.	1.86mm	applied	
<b>Left-rear-top</b>	The portion near the antenna of the upper part of the rear side (LCD side) of EUT was touched to the Flat phantom.	1.86mm	applied	
<b>Rear(LCD)</b>	The rear surface (LCD side) of EUT was touched to the Flat phantom.	1.42mm	applied	
<b>Top</b>	The portion near the antenna of the upper part (top) of EUT was touched to the Flat phantom.	2.15mm	applied	
<b>Left</b>	The left surface of EUT was touched to the Flat phantom.	3.65mm	applied	
<b>Front(Lens)</b>	The front surface (Lens side) of EUT was touched to the Flat phantom.	21.9mm	applied	
<b>Right</b>	The right surface of EUT was touched to the Flat phantom.	94.4mm	applied	
<b>Bottom</b>	The bottom surface of EUT was touched to the Flat phantom.	68.0mm	applied	

\*. Antenna to user distance: this means the distance from the antenna inside a product to the surface of the product which an operator touches.

\*. Size of EUT: 108.8 mm (width) × 40.3 mm (depth) × 75.9 mm (height) (manufacture's specification, when lens was closed.)

By the determined test setup shown above, the SAR test was applied in the following procedures.

Step 1	Change the positions.
Step 2	Change the channels. (at the worst position.)

\*. During SAR test, the radiated power is always monitored by Spectrum Analyzer.

## SECTION 4: Operation of EUT during testing

### 4.1 Operating modes for SAR testing

This EUT has IEEE.802.11b, 11g, 11n(20HT) and 11n(40HT) continuous transmitting modes.

The frequency and the modulation used in the SAR testing are shown as a following.

Operation mode	11b (*1)	The example of a software screen
<b>Tx frequency band</b>	2412-2462MHz	
<b>Tested frequency</b>	2412, 2437, 2462MHz (*2)	
<b>Modulation</b>	DBPSK/DSSS	
<b>Data rate</b>	1Mbps (*3)	
<b>Crest factor</b>	1.0 (100% duty cycle)	
<b>Controlled software</b>	“RF TEST” mode; During SAR test, the EUT was operated by pre-installed “RF TEST” mode software. The operation screen of this software is shown in the right.	

\*1. Since the target average power of 11g, 11n(20HT) and 11n(40HT) were more than 2dB lower than the corresponded 11b power, SAR test was not applied to the 11g, 11n(20HT) and 11n(40HT) mode. In 11b mode, the average power of higher data rate was less than 0.25dB higher than the lowest data rate. Therefore, SAR test was only applied to the lowest data rate. (KDB248227) (Refer to Section 6.)

\*2. Any output power reducing for channel 1 and 11 to meet restricted band requirements was not observed. Therefore channel 1 and 11 was selected for the default channels and SAR test was applied.

\*3. In 11b mode, the average power of higher data rate was less than 0.25dB higher than the lowest data rate. Therefore, SAR test was only applied to the lowest data rate. (KDB248227) (Refer to Section 6.)

## SECTION 5: Uncertainty Assessment (SAR measurement)

Uncertainty of SAR measurement(v06) (*. Body tissue, $\epsilon$ & $\sigma$ tolerance: $\leq \pm 5\%$ , Tx: $\approx 100\%$ duty cycle)		Under 3 GHz	
		1g SAR	10g SAR
Combined measurement uncertainty of the measurement system (k=1)		$\pm 12.5\%$	$\pm 12.2\%$
Expanded uncertainty (k=2)		$\pm 25.0\%$	$\pm 24.4\%$

	Error Description (Under 3GHz) (v06)	Uncertainty Value	Probability distribution	Divisor	$ci$ (1g)	$ci$ (10g)	$ui$ (1g)	$ui$ (10g)	$Vi, v_{eff}$
<b>A</b>	<b>Measurement System (DASY5)</b>						(std. uncertainty)	(std. uncertainty)	
1	Probe Calibration Error	$\pm 6.0\%$	Normal	1	1	1	$\pm 6.0\%$	$\pm 6.0\%$	$\infty$
2	Axial isotropy Error	$\pm 4.7\%$	Rectangular	$\sqrt{3}$	0.7	0.7	$\pm 1.9\%$	$\pm 1.9\%$	$\infty$
3	Hemispherical isotropy Error (<5deg, flat phantom)	$\pm 9.6\%$	Rectangular	$\sqrt{3}$	0.7	0.7	$\pm 3.9\%$	$\pm 3.9\%$	$\infty$
4	Boundary effects Error	$\pm 1.4\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 0.8\%$	$\pm 0.8\%$	$\infty$
5	Linearity Error	$\pm 4.7\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 2.7\%$	$\pm 2.7\%$	$\infty$
6	Probe modulation response (CW)	$\pm 0.0\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 0.0\%$	$\pm 0.0\%$	$\infty$
7	Sensitivity Error (detection limit)	$\pm 1.0\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 0.6\%$	$\pm 0.6\%$	$\infty$
8	Response Time Error (<5ms/100ms wait)	$\pm 0.0\%$	Normal	1	1	1	$\pm 0.0\%$	$\pm 0.0\%$	$\infty$
9	Integration Time Error (100% duty cycle)	$\pm 0.0\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 0.0\%$	$\pm 0.0\%$	$\infty$
10	Readout Electronics Error(DAE)	$\pm 0.3\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 0.3\%$	$\pm 0.3\%$	$\infty$
11	RF ambient conditions-noise	$\pm 3.0\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 1.7\%$	$\pm 1.7\%$	$\infty$
12	RF ambient conditions-reflections	$\pm 3.0\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 1.7\%$	$\pm 1.7\%$	$\infty$
13	Probe positioner mechanical tolerance	$\pm 1.1\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 0.6\%$	$\pm 0.6\%$	$\infty$
14	Probe Positioning with respect to phantom shell	$\pm 2.9\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 1.7\%$	$\pm 1.7\%$	$\infty$
15	Errors: Extrapol., Interpol. & Integration Algorithms	$\pm 1.0\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 0.6\%$	$\pm 0.6\%$	$\infty$
<b>B</b>	<b>Test Sample Related</b>								
16	Test Sample Positioning Error	$\pm 5.0\%$	Normal	1	1	1	$\pm 5.0\%$	$\pm 5.0\%$	145
17	Device Holder or Positioner Tolerance	$\pm 3.6\%$	Normal	1	1	1	$\pm 3.6\%$	$\pm 3.6\%$	5
18	Test Sample Output Power Drift Error	$\pm 5.0\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 2.9\%$	$\pm 2.9\%$	$\infty$
<b>C</b>	<b>Phantom and Setup</b>								
19	Phantom uncertainty (shape, thickness tolerances)	$\pm 7.5\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 4.3\%$	$\pm 4.3\%$	$\infty$
20	Target Liquid Conductivity Tolerance ( $\leq 5\%$ )	$\pm 5.0\%$	Rectangular	$\sqrt{3}$	0.64	0.43	$\pm 1.8\%$	$\pm 1.2\%$	$\infty$
21	Measurement Liquid Conductivity Error	$\pm 2.9\%$	Normal	1	0.64	0.43	$\pm 1.9\%$	$\pm 1.2\%$	3
22	Target Liquid Permittivity Tolerance ( $\leq 5\%$ )	$\pm 5.0\%$	Rectangular	$\sqrt{3}$	0.6	0.49	$\pm 1.7\%$	$\pm 1.4\%$	$\infty$
23	Measurement Liquid Permittivity Error	$\pm 2.9\%$	Normal	1	0.6	0.49	$\pm 1.7\%$	$\pm 1.4\%$	3
24	Liquid Conductivity-temp.uncertainty ( $\leq 2\text{deg.C.}$ )	$\pm 5.2\%$	Rectangular	$\sqrt{3}$	0.78	0.71	$\pm 2.3\%$	$\pm 2.1\%$	$\infty$
25	Liquid Permittivity-temp.uncertainty ( $\leq 2\text{deg.C.}$ )	$\pm 0.8\%$	Rectangular	$\sqrt{3}$	0.23	0.26	$\pm 0.1\%$	$\pm 0.1\%$	$\infty$
	<b>Combined Standard Uncertainty</b>						$\pm 12.5\%$	$\pm 12.2\%$	479
	<b>Expanded Uncertainty (k=2)</b>						$\pm 25.0\%$	$\pm 24.4\%$	

\*: This measurement uncertainty budget is suggested by IEEE 1528, IEC 62209-2 and determined by Schmid & Partner Engineering AG (DASY5 Uncertainty Budget).

## SECTION 6: Confirmation before testing

### 6.1 Assessment for the conducted power of EUT

#### 6.1.1 Comparison with EMC data (rated power)

Mode	Freq. [MHz]	D/R [Mbps]	Cable Loss [dB]	Att. [dB]	D/F [dB]	Average power		PAR [dB]	Power tolerance & correction				Apply SAR test? (Y: yes)	Output power of EMC test		Remarks		
						P/M Reading [dBm]	Result		Target & tolerance [dBm]	Deviation from max. [dB]	Scaled Factor [-]	$\leq 2$ dB? (Y: yes)		Aver. [dBm]	$\Delta$ SAR [dB]			
							[dBm]	[mW]										
11b (Pwr. Setting =14)	2412	1	1.00	10.00	0.00	3.23	14.23	26.49	2.62	14.0±2.5	-2.27	-	-	-	14.17	0.06		
	2412	2	1.00	10.00	0.00	3.25	14.25	26.61	2.61	14.0±2.5	-2.25	-	-	-	14.19	0.06		
	2412	5.5	1.00	10.00	0.00	3.28	14.28	26.79	1.98	14.0±2.5	-2.22	-	-	-	14.28	0.00		
	2412	11	1.00	10.00	0.00	3.24	14.24	26.55	2.56	14.0±2.5	-2.26	-	-	-	14.24	0.00		
	2437	1	1.00	10.00	0.00	3.32	14.32	27.04	2.58	14.0±2.5	-2.18	-	-	-	-	-		
	2462	1	1.00	10.00	0.00	3.35	14.35	27.23	2.57	14.0±2.5	-2.15	-	-	-	-	-	Highest CH(11b)	
11g (*1) (Pwr. Setting =12)	2412	6	1.00	10.00	0.00	1.13	12.13	16.33	9.29	12.0±2.5	-2.37	-	-	-	12.13	0.00		
	2412	9	1.00	10.00	0.00	1.11	12.11	16.26	8.75	12.0±2.5	-2.39	-	-	-	12.08	0.03		
	2412	12	1.00	10.00	0.00	1.08	12.08	16.14	9.25	12.0±2.5	-2.42	-	-	-	12.05	0.03		
	2412	18	1.00	10.00	0.00	1.16	12.16	16.44	8.66	12.0±2.5	-2.34	-	-	-	12.14	0.02		
	2412	24	1.00	10.00	0.00	1.11	12.11	16.26	9.39	12.0±2.5	-2.39	-	-	-	12.03	0.08		
	2412	36	1.00	10.00	0.00	1.05	12.05	16.03	9.20	12.0±2.5	-2.45	-	-	-	11.95	0.10		
	2412	48	1.00	10.00	0.00	1.03	12.03	15.96	9.17	12.0±2.5	-2.47	-	-	-	12.02	0.01		
	2412	56	1.00	10.00	0.00	1.02	12.02	15.92	9.35	12.0±2.5	-2.48	-	-	-	12.01	0.01		
	2437	6	1.00	10.00	0.00	1.30	12.30	16.98	9.21	12.0±2.5	-2.20	-	-	-	-	-		
	2462	6	1.00	10.00	0.00	1.54	12.54	17.95	9.17	12.0±2.5	-1.96	-	-	-	-	-		
11n (20HT) (*1) (Pwr. Setting =12)	2412	MCS0	1.00	10.00	0.00	1.17	12.17	16.48	8.66	12.0±2.5	-2.33	-	-	-	12.03	0.14		
	2412	MCS1	1.00	10.00	0.00	1.12	12.12	16.29	8.64	12.0±2.5	-2.38	-	-	-	12.06	0.06		
	2412	MCS2	1.00	10.00	0.00	1.10	12.10	16.22	8.67	12.0±2.5	-2.40	-	-	-	12.05	0.05		
	2412	MCS3	1.00	10.00	0.00	1.14	12.14	16.37	8.67	12.0±2.5	-2.36	-	-	-	12.08	0.06		
	2412	MCS4	1.00	10.00	0.00	1.13	12.13	16.33	8.69	12.0±2.5	-2.37	-	-	-	12.04	0.09		
	2412	MCS5	1.00	10.00	0.00	1.13	12.13	16.33	8.62	12.0±2.5	-2.37	-	-	-	12.11	0.02		
	2412	MCS6	1.00	10.00	0.00	1.14	12.14	16.37	8.61	12.0±2.5	-2.36	-	-	-	12.13	0.01		
	2412	MCS7	1.00	10.00	0.00	1.10	12.10	16.22	8.61	12.0±2.5	-2.40	-	-	-	12.10	0.00		
	2437	MCS0	1.00	10.00	0.00	1.24	12.24	16.75	8.62	12.0±2.5	-2.26	-	-	-	-	-		
	2462	MCS0	1.00	10.00	0.00	1.63	12.63	18.32	8.32	12.0±2.5	-1.87	-	-	-	-	-		
11n (40HT) (Pwr. Setting =11)	2422	MCS0	1.00	10.00	0.00	0.31	11.31	13.52	9.05	11.0±2.5	-2.19	-	-	-	11.27	0.04		
	2422	MCS1	1.00	10.00	0.00	0.36	11.36	13.68	8.82	11.0±2.5	-2.14	-	-	-	11.32	0.04		
	2422	MCS2	1.00	10.00	0.00	0.29	11.29	13.46	9.45	11.0±2.5	-2.21	-	-	-	11.20	0.09		
	2422	MCS3	1.00	10.00	0.00	0.27	11.27	13.40	9.67	11.0±2.5	-2.23	-	-	-	11.25	0.02		
	2422	MCS4	1.00	10.00	0.00	0.27	11.27	13.40	9.74	11.0±2.5	-2.23	-	-	-	11.26	0.01		
	2422	MCS5	1.00	10.00	0.00	0.25	11.25	13.34	9.83	11.0±2.5	-2.25	-	-	-	11.25	0.00		
	2422	MCS6	1.00	10.00	0.00	0.30	11.30	13.49	9.34	11.0±2.5	-2.20	-	-	-	11.30	0.00		
	2422	MCS7	1.00	10.00	0.00	0.27	11.27	13.40	9.12	11.0±2.5	-2.23	-	-	-	11.17	0.10		
	2437	MCS0	1.00	10.00	0.00	0.54	11.54	14.26	9.01	11.0±2.5	-1.96	-	-	-	-	-		
	2452	MCS0	1.00	10.00	0.00	0.43	11.43	13.90	8.87	11.0±2.5	-2.07	-	-	-	-	-		

\*. The difference between the SAR reference power and the power of EMC test was not less than 0dB and not higher than 0.21dB.

Therefore it was judged that EUT that was used for SAR test was equivalent to the EUT used for EMC test.

#### 6.1.2 SAR reference power data: Worst data rate / worst channel determination

Mode	Freq. [MHz]	D/R [Mbps]	Cable Loss [dB]	Att. [dB]	D/F [dB]	Average power		PAR [dB]	Power tolerance & correction				Apply SAR test? (Y: yes)	Output power of EMC test		Remarks		
						P/M Reading [dBm]	Result		Target & tolerance [dBm]	Deviation from max. [dB]	Scaled Factor [-]	$\leq 2$ dB? (Y: yes)		Aver. [dBm]	$\Delta$ SAR [dB]			
							[dBm]	[mW]										
11b (Pwr. Setting =14)	2412	1	1.00	10.00	0.00	3.76	14.76	29.92	2.51	14.0±2.5	-1.74	$\times 1.49$	Y	Y	(*)1	n/a	n/a	
	2412	2	1.00	10.00	0.00	3.76	14.76	29.92	2.53	14.0±2.5	-1.74	$\times 1.49$	Y	Y	(*)1	n/a	n/a	
	2412	5.5	1.00	10.00	0.00	3.82	14.82	30.34	1.94	14.0±2.5	-1.68	$\times 1.47$	Y	Y	(*)1	n/a	n/a	
	2412	11	1.00	10.00	0.00	3.74	14.74	29.79	2.50	14.0±2.5	-1.76	$\times 1.50$	Y	-	n/a	n/a	n/a	
	2437	1	1.00	10.00	0.00	3.89	14.89	30.83	2.52	14.0±2.5	-1.61	$\times 1.45$	Y	Y	n/a	n/a	n/a	Highest CH(11b)
	2462	1	1.00	10.00	0.00	3.75	14.75	29.85	2.51	14.0±2.5	-1.75	$\times 1.50$	Y	Y	n/a	n/a	n/a	

\*. Freq: Frequency, D/R: Data Rate, Att: Attenuator loss, D/F: Duty Factor (0dB=100% duty cycle), n/a: not applied.

\*. Calculating formula: Results (Ave) = [P/M Reading] + [Cable loss] + [Attenuator] + [duty factor]

Deviation form max.: Power deviation (Deviation [dB]) = "results power (average)" - "Max.-specification output power (average)"

Scaled Factor: Power scaled factor for obtained SAR value, Scaled Factor [-] = 1 / (10^(Deviation from max. / 10))

\*1. Since the target average power of 11g, 11n(20HT) and 11n(40HT) were more than 2dB lower than the corresponded 11b power, the power measurement and SAR test were not applied to the 11g, 11n(20HT) and 11n(40HT) mode. (KDB248227) The average power of higher data rate was less than 0.25dB higher than the lowest data rate. Therefore, SAR test was only applied to the lowest data rate. (KDB248227)

\*. Uncertainty of antenna port conducted test: Power measurement uncertainty above 1GHz for this test was: (±) 1.5dB

\*. SAR reference: Date measured: February 21, 2013 / Measured by: Hiroshi Naka / Place: preparation room of No. 7 shielded room. (23 deg C. / 33 %RH)

"Power of EMC test"; this reference is described in the test report of 32IE0081-SH-02-C.

\*. EUT serial number: "4EE" for SAR test / "34F" for EMC test.

## SECTION 7: Measurement results

### 7.1 SAR (Body) in the Platform (1)-Digital camera (1) (model: PC2035)

Measurement date: April 9, 2013

Measurement by: Hiroshi Naka

#### [Liquid measurement (Body simulated tissue)]

Target Frequency [MHz]	Liquid parameters						ΔSAR Coefficients (*1)		Remarks / Environment
	Permittivity (εr) [-]		Conductivity [S/m]		Temp. [deg.C.]	Depth [mm]	ΔSAR (1g) [%]	Correction required?	
	Target	Measured (Δεr)	Target	Measured (Δσ)			(+2.20) (*1)	not required.	
2450	52.7	50.18 (-4.8%)	1.95	1.996 (+2.3%)	22.0	155	(+1.69) (*1)	not required.	April 9, 2013, before SAR test / ambient; 22.9deg.C., 38%RH
2412	52.75	50.30 (-4.7%)	1.914	1.939 (+1.3%)			(+1.93) (*1)	not required.	
2437	52.72	50.22 (-4.8%)	1.938	1.972 (+1.8%)			(+2.06) (*1)	not required.	
2462	52.68	50.17 (-4.8%)	1.967	2.008 (+2.1%)					

\* The target value is a parameter defined in OET65 Supplement C. In the current standards (e.g. IEEE 1528, OET 65 Supplement C), the dielectric parameters suggested for head and body tissue simulating liquid are given at 1800-2000, 2450, and 3000MHz. As an intermediate solution, dielectric parameters for the frequencies between 2000 to 3000 MHz were obtained using linear interpolation. (Refer to Appendix 3-4)

\*1. The number of ΔSAR(1g) of body simulated tissue was reference purpose only. ΔSAR coefficients are parameters defined in Annex F, IEC 62209-2:2010 (head tissue). In accordance with clause 6.1.1 of IEC62209-2; "If the correction ΔSAR has a negative sign, the measured SAR results shall not be corrected", the calculated ΔSAR values of the tested liquid had shown negative correction. Therefore the measured SAR was not required ΔSAR correction.

$$\Delta\text{SAR}(1g) = C_{\text{er}} \times \Delta\epsilon_r + C_{\sigma} \times \Delta\sigma, C_{\text{er}} = -7.854E-4 \times f^3 + 9.402E-3 \times f^2 - 2.742E-2 \times f + 0.2026 / C_{\sigma} = 9.804E-3 \times f^3 - 8.661E-2 \times f^2 + 2.981E-2 \times f + 0.7829$$

#### [SAR measurement results (Partial-Body)]

Mode	[MHz] (CH)	Modulation /Data rate /Crest factor	SAR measurement results (Body simulated tissue)								Reported SAR			
			EUT setup conditions			Liquid temp. [deg.C.]		Power drift [dB]	SAR (1g) [W/kg]			Data# in Appendix 2-2	SAR (1g) [W/kg]	
			Position	Gap [mm]	Battery ID	Before	After		Observed	ΔSAR [%]	ΔSAR corrected			
<b>Step 1: Change the positions</b>														
11b	2437(6)	BPSK &DSSS /1Mbps/1.0	Left-top	0	#1	22.1	22.2	-0.20	0.419	-	-	Step 1-1	×1.45 0.61 -	
			Rear-top	0	#2	22.2	22.2	0.08	0.512	-	-	Step 1-2	×1.45 0.74 -	
			Left-rear-top	0	#1	22.2	22.2	-0.10	0.447	-	-	Step 1-3	×1.45 0.65 -	
			Rear (LCD)	0	#2	22.2	22.3	0.14	0.360	-	-	Step 1-4	×1.45 0.52 -	
			Top	0	#1	22.4	22.4	0.20	0.186	-	-	Step 1-5	×1.45 0.27 -	
			Left	0	#2	22.4	22.4	-0.01	0.615	-	-	Step 1-6	×1.45 0.89 →Highest SAR.	
			Front (Lens)	0	#1	22.3	22.4	-	(0.0532)	*. Fast SAR (*1)	-	n/a	n/a	*.Polynomial-fit
			Right	0	#1	22.5	22.6	-	(0.0270)	*. Fast SAR (*1)	-	n/a	n/a	*.Polynomial-fit
			Bottom	0	#1	22.6	22.6	-	(0.0132)	*. Fast SAR (*1)	-	n/a	n/a	*.Polynomial-fit
<b>Step 2: Changed the channels</b>														
11b	2412(1)	BPSK &DSSS /1Mbps/1.0	Left	0	#1	22.4	22.5	-0.03	0.590	-	-	Step 2-1	×1.49 0.88 -	
	2462(11)			0	#2	22.5	22.5	0.10	0.580	-	-	Step 2-2	×1.50 0.87 -	

#### Notes:

- \* Gap: It is the separation distance between the nearest position of EUT outer surface and the bottom outer surface of phantom; n/a: not applied.
- \*1. Algorithm: Douglas, M.G., Chou, C-K.; Accurate and Fast Estimation of Volumetric SAR from Planner Scans from 30 MHz to 6 GHz," Bioelectromagnetics Society 29th Annual Meeting, June 2007.
- \*. Battery No.#1 and #2 were same model.; Refer to Appendix 1.
- \*. Since the target average power of 11g, 11n(20HT) and 11n(40HT) were more than 2dB lower than the corresponded 11b power, the power measurement and SAR test were not applied to the 11g, 11n(20HT) and 11n(40HT) mode. (KDB248227)
- \*. During test, the EUT was operated with full-charged battery and without all signal interface cables.
- \*. Calibration frequency of the SAR measurement probe (and used conversion factors)

SAR test frequency	Probe calibration frequency	Validity [MHz]	Used conversion factor	Uncertainty
2412 MHz	2450 MHz	-38MHz, within ±50 of calibration frequency	6.77	±12.0%
2437 MHz	2450 MHz	-13MHz, within ±50 of calibration frequency	6.77	±12.0%
2462 MHz	2450 MHz	+12MHz, within ±50 of calibration frequency	6.77	±12.0%

\*. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.