



SAR TEST REPORT

Test Report No.: 11355753S-A

Applicant : Canon Inc.
Type of Equipment : Wireless LAN module in Digital Radiography
Model No. : BM72065 (Wireless LAN module) (*. Installed into the platform (1))
FCC ID : AZDBM72065
Test Standard : FCC 47CFR §2.1093
Test Result : Complied

Highest Reported SAR Value [W/kg]				SAR Limit			Platform			Remarks			Output power (average) [dBm]	
Tune-up value DTS band		(Measured) UNII band		Type	1g /10g	Limit [W/kg]	No.	Type	Model	Band	Frequency [MHz]	Mode	Measured	Max.
0.32	0.67	0.205	0.498	Body-worn	1g	1.6	#1	Digital Radiography	CXDI-710C Wireless (WM5A11)	DTS	2462	11b (1Mbps, DSSS)	12.07	14
0.35	0.66	0.223	0.490	Next-of-head	1g	1.6				UNII	5825	11n(20HT) (MCS0, OFDM)	11.74	13
0.62	0.91	0.394	0.691	Hand	10g	4				DTS	2462	11b (1Mbps, DSSS)	12.07	14
										UNII	5825	11n(20HT) (MCS0, OFDM)	11.74	13
										DTS	2462	11g (6Mbps, OFDM)	12.03	14
										UNII	5240	11a (6Mbps, OFDM)	11.78	13

*: Highest reported SAR of this device for body-worn, next-of-head and hand holding are "0.67 W/kg", "0.66 W/kg" and "0.91 W/kg".

*: Since highest reported SAR on this EUT's platform obtained in accordance with KDB447498 D01 (v06) was kept under 50% of SAR limit, this EUT was approved to operate multi-platform.

1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the limits of the above regulation.
4. The test results in this test report are traceable to the national or international standards.
5. This test report must not be used by the customer to claim product certification, approval, or endorsement by any agency of the Federal Government.
6. The opinions and the interpretations to the result of the description in this report are outside scopes where UL Japan has been accredited.
7. This test report covers Radio technical requirements. It does not cover administrative issues such as Manual or non-Radio test related Requirements. (if applicable)

Date of test: October 19~November 21, 2016

Test engineer:

Hiroshi Naka
Engineer, Consumer Technology Division

Approved by:

Toyokazu Imamura
Leader, Consumer Technology Division

The testing in which "Non-accreditation" is displayed is outside the accreditation scopes in UL Japan.
 There is no testing item of "Non-accreditation".



REVISION HISTORY

Revision	Test report No.	Date	Page revised	Contents
Original	11355753S-A	December 2, 2016	-	-
-r01	11355753S-A	December 14, 2016	P1,2,3	(p3) Error correction.
-r02	11355753S-A	December 16, 2016	P1,2,25,28,35~37,46,47,72~74	(p1,25,28,35~37,46,47,72~74) Error correction.

*. By issue of new revision report, the report of an old revision becomes invalid.

CONTENTS

PAGE

REVISION HISTORY.....	2
CONTENTS	2
SECTION 1: Customer information	3
SECTION 2: Equipment under test (EUT).....	3
2.1 Identification of EUT	3
2.2 Product Description (Wireless LAN Module: BM72065).....	3
2.3 SAR test consideration of this platform: CXDI-710C Wireless (WM5A11)	4
SECTION 3: Test specification, procedures and results	5
3.1 Test specification.....	5
3.2 Exposure limit	5
3.3 Procedure and result.....	5
3.4 Test location	6
3.5 Confirmation before SAR testing.....	6
3.6 Confirmation after SAR testing.....	6
3.7 Test setup of EUT and SAR measurement procedure	7
SECTION 4: Uncertainty assessment (SAR measurement).....	8
SECTION 5: Operation of EUT during SAR testing.....	8
SECTION 6: Confirmation before testing	10
6.1 Assessment for the antenna terminal port conducted power of EUT	10
SECTION 7: SAR Measurement results.....	12
7.1 Liquid measurement	12
7.2 SAR measurement results (2.4GHz, SAR for Body/Head/Hand)	13
7.3 SAR measurement results (5GHz band, SAR for Body/Head/Hand).....	14

Contents of appendixes

APPENDIX 1: Photographs of test setup	16
Appendix 1-1 Photograph of Platform, EUT and antenna position.....	16
Appendix 1-2 EUT, platform and support equipment	17
Appendix 1-3 Usage example	17
Appendix 1-4 Photograph of SAR test setup	18
APPENDIX 2: SAR Measurement data.....	22
Evaluation procedure.....	22
Measurement data.....	23
APPENDIX 3: Test instruments	75
Equipment used	75
Configuration and peripherals	76
Test system specification.....	77
Simulated tissues composition and parameter confirmation	78
Daily check results	78
Daily check uncertainty	79
Daily check measurement data	80
Calibration certificate: E-Field Probe (EX3DV4)	86
Calibration certificate: Dipole (D2450V2).....	97
Calibration certificate: Dipole (D5GHzV2)	105

SECTION 1: Customer information

Company Name	Canon Inc.
Address	9-1, Imaikami-cho, Nakahara-ku, Kawasaki-shi, Kanagawa 211-8501, Japan
Telephone Number	81-3-3758-2111
Facsimile Number	81-44-739-5495
Contact Person	Yasuhiko Minakawa

SECTION 2: Equipment under test (EUT)

2.1 Identification of EUT

	EUT	Platform
Type of Equipment	Wireless LAN Module	Platform (1): Digital Radiography
Model Number	BM72065	CXDI-710C Wireless (WM5A11)
Serial Number	60128BCC1DCA	16DR-272
Condition of EUT	Engineering prototype	Engineering prototype
	(*. Not for sale: These samples are equivalent to mass-produced items.)	
Receipt Date of Sample	September 20, 2016 (*. EUT for power measurement.) *. No modification by the Lab. October 18, 2016 (*. EUT for SAR test.) *. No modification by the Lab. (*. The EUT that had been measured the power of SAR test reference, was installed into the platform from the beginning. After power measurement, the EUT was returned to the customer and was installed into a platform which SAR tested by the customer.)	
Country of Mass-production	Japan	Japan
Category Identified	Portable device	
Rating	DC3.3V supplied from the platform *. The EUT is installed into the specified the platform that was operated by the re-chargeable Li-ion battery. Therefore, each SAR test, the platform which had built-in EUT was operated with full-charged battery.	
Feature of EUT	The EUT is a Wireless Module which installs into the specified platform: Digital Radiography.	
SAR Accessory	None	

2.2 Product Description (Wireless LAN Module: BM72065)

Frequency band	2.4GHz band		5GHz band				
			-	U-NII-1 (W52)	U-NII-2A (W53)	U-NII-2C (W56)	U-NII-3 (W58)
Frequency of operation (MHz) (*.ch.: channel)	11b,g, n(20HT)	2412~2462 (ch.1~11)	11a,	5180~5240 (ch.36~48)	5260~5320 (ch.52~64)	5500~5700 (ch.100~140)	5745~5825 (ch.149~165)
	n(40HT)	2412~2452 (ch.1~9)	n(40HT)	5190~5230 (ch.38~46)	5270~5310 (ch.54~62)	5510~5670 (ch.102~134)	5755, 5795 (ch.151,159)
Channel spacing (MHz)	5 (11b,g,n(20HT))						
Bandwidth (MHz)	20 (11b,g,n(20HT)) / 40 (11n(40HT))						
Type of modulation	DSSS: DBPSK, DQPSK, CCK (11b), OFDM: BPSK, QPSK, 16QAM, 64QAM (11g,a,n(20HT),n(40HT))						
Transmit power (typical, maximum channel and data rate) and tolerance (as manufacture variation) (dBm) (*.ch.: channel)	11b	12.0 ±2 (ch.1~11, 1~11Mbps)	11a:	11.0 ±2 (ch.36~48, 6~54Mbps)	11.0 ±2 (ch.52~64, 6~54Mbps)	11.0 ±2 (ch.100~140, 6~54Mbps)	11.0 ±2 (ch.149~165, 6~54Mbps)
	11g, n(20HT)	12.0 ±2 (ch.1~11, 6~54Mbps, MCS0~7)	n(20HT)	11.0 ±2 (ch.36~48, MCS0~7)	11.0 ±2 (ch.52~64, MCS0~7)	11.0 ±2 (ch.100~140, MCS0~7)	11.0 ±2 (ch.149~165, MCS0~7)
	n(40HT)	11.0 ±2 (ch.3~9, MCS0~7)	n(40HT)	11.0 ±2 (ch.38~46, MCS0~7)	11.0 ±2 (ch.54~62, MCS0~7)	11.0 ±2 (ch.102~134, MCS0~7)	11.0 ±2 (ch.151,159, MCS0~7)
* The measured Tx output power (conducted) refers to Section 6 in this report.							
Power supply	DC 3.3V *. The dc power of BM72065 is supplied from the constant voltage circuit of the platform.						
Radio type	Transceiver						
Antenna quantity / model	1 pc.	146153-100 (cable length: 100 mm) <molex>					
Antenna type / connector type	Pattern antenna (34.9mm × 9mm) / Connector, RF module side: U-FL connector compatible, Antenna side: soldered						
Antenna gain (max,peak)	3.0 dBi (2.4GHz ~ 2.5 GHz) / 4.5 dBi (5.15GHz ~ 5.85 GHz), *including cable loss.						

*. The EUT do not use the special transmitting technique such as "beam-forming" and "time-space code diversity."

**UL Japan, Inc.
Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN
 Telephone: +81 463 50 6400 / Facsimile: +81 463 50 6401

2.3 SAR test consideration of this platform: CXDI-710C Wireless (WM5A11)

This platform is a large-sized transportable equipment and has a part coming in contact directly with a patient. An operator (a patient become an operator uncommonly) maintains EUT by hand. (Refer to photographs of Appendix 1-3: Usage example)

Because there is not the KDB for the product which is such a design specifications, we decide the SAR test method in below.

Physical characteristics of platform: CXDI-710C Wireless (WM5A11)

Dimensions: 384 × 460 × 15.7 mm, Weight: 2.3 kg

- This platform is a transportable equipment, but, because it is a large-sized equipment, an operator (or a patient) fixes the edge of platform to stands and pushes or supports platform to a patient's body part (head, body, arm, hand, foot, etc.) by hand at the time of use.

The X-ray imaging by platform changes the imaging part of the patient's body at every imaging after having needed several minutes for setting.

- The image transfer time (continuous transfer time) per one imaging is two or three seconds, it is short enough. The imaging of the same part can be performed consecutively several times.
In the case of serial imaging, the image transfer time (continuous transfer time) occupies two or three seconds among the image intervals of 15 seconds. (Duty Cycle: < 20 %)
- On this account, the time when an operator (or patient) is really exposed to RF energy is short.
- In addition, an operator is only a doctor or a legally certified person because platform is medical equipment.
- Explanatory note in the manual-
“Only a physician or a legally certified operation should use the product.”

In consideration of the terms of use mentioned above, we decide the SAR examination as the following contents.

- a) The front (imaging area side) and side edge of platform carries out the Partial-body SAR examination.
The front of platform comes in contact with a patient directly. In addition, consecutive RF energy may be exposed to the same neighborhood part of the patient although duty cycle is less than 20%.
Because the front of platform comes in contact with a patient directly, we measure the Partial-body SAR at the position of the touch to a phantom around the antenna of the front and side-edge of platform with continuous transmission in 100% duty cycle as a worse condition.
- b) The back of platform carries out the Hand SAR examination.
An operator (or a patient) fixes the edge of platform to stands and pushes or supports platform to a patient's body part (head, body, arm, hand, foot, etc.) by hand and by holding back of platform at the time of use.
In addition, consecutive RF energy may be exposed to the same neighborhood part of the patient although duty cycle is less than 20%.
We measure the Hand SAR at the position of the touch to a phantom around the antenna of the back of platform with continuous transmission in 100% duty cycle as a worse condition.

*. In addition, because the following instructions for the operator are mentioned in a manual, the physical part of the operator does not touch directly the antenna part of the back.
- Explanatory note in the manual -
“Please do not adhere to your hands and body to an antenna part to restrain exposure of the RF energy when conducting an X-ray examination.”

SECTION 3: Test specification, procedures and results

3.1 Test specification

The US Federal Communications Commission has released the report and order "Guidelines for Evaluating the Environmental Effects of RF Radiation", ET Docket No. 93-62 in August 1996. The order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 mW/g for an uncontrolled environment and 8.0 mW/g for an occupational/controlled environment as recommended by the ANSI/IEEE standard C95.1-1992. The device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling in accordance with the following measurement procedures..

KDB 447498 D01 (v06): General RF exposure guidance

KDB 248227 D01 (v02r02): SAR Guidance for IEEE 802.11 (Wi-Fi) transmitters

KDB 865664 D01 (v01r04): SAR measurement 100MHz to 6GHz

IEEE Std. 1528-2013: IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.

3.2 Exposure limit

Environments of exposure limit	Whole-Body (averaged over the entire body)	Partial-Body (averaged over any 1g of tissue)	Hands, Wrists, Feet and Ankles (averaged over any 10g of tissue)
(A) Limits for Occupational /Controlled Exposure (W/kg)	0.4	8.0	20.0
(B) Limits for General population /Uncontrolled Exposure (W/kg)	0.08	1.6	4.0

*. **Occupational/Controlled Environments:** are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

*. **General Population/Uncontrolled Environments:** are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

The limit applied in this test report is:

General population / uncontrolled exposure, Partial-Body (averaged over any 1g of tissue) limit: **1.6 W/kg**
General population / uncontrolled exposure, Hands (averaged over any 10g of tissue) limit: **4 W/kg**

3.3 Procedures and Results

Band (Frequency [MHz])	Wi-Fi (DTS) (2412-2462)	Wi-Fi (U-NII-1) (5180~5240)(W52)	Wi-Fi (U-NII-2A) (5260~5320)(W53)	Wi-Fi (U-NII-2C) (5500~5700)(W50)	Wi-Fi (U-NII-3) (5745~5825)(W58)
Test Procedure	SAR measurement; KDB 447498, KDB 248227, KDB 865664, IEEE Std.1528				
Category	FCC 47CFR §2.1093 (Portable device)				
Results (SAR(1g) limit)	Complied ($\leq 1.6 \text{ W/kg}$)	Complied ($\leq 1.6 \text{ W/kg}$)	Complied ($\leq 1.6 \text{ W/kg}$)	Complied ($\leq 1.6 \text{ W/kg}$)	Complied ($\leq 1.6 \text{ W/kg}$)
SAR type	Body touch	Next of head	Body touch	Next of head	Body touch
Liquid type	Body	Head	Body	Head	Body
Reported SAR value	0.32 W/kg	0.35 W/kg	0.42 W/kg	0.39 W/kg	0.39 W/kg
Measured SAR value	0.205 W/kg	0.223 W/kg	0.326 W/kg	0.302 W/kg	0.291 W/kg
Operation mode, frequency [MHz]	11b(1Mbps), 2462	11b(1Mbps), 2462	n40(MCS0), 5190	n40(MCS0), 5230	n40(MCS0), 5310
Duty cycle [%] (scaled factor)	100 ($\times 1.00$)	100 ($\times 1.00$)	100 ($\times 1.00$)	100 ($\times 1.00$)	100 ($\times 1.00$)
Output power [dBm] (max. power, scaled factor)	12.07 (14, $\times 1.56$)	12.07 (14, $\times 1.56$)	11.86 (13, $\times 1.30$)	11.88 (13, $\times 1.29$)	11.70 (13, $\times 1.35$)
Results (SAR(10g) limit)	Complied ($\leq 4 \text{ W/kg}$)	Complied ($\leq 4 \text{ W/kg}$)	Complied ($\leq 4 \text{ W/kg}$)	Complied ($\leq 4 \text{ W/kg}$)	Complied ($\leq 4 \text{ W/kg}$)
SAR type	Hand holding	Hand holding	Hand holding	Hand holding	Hand holding
Liquid type	Body	Body	Body	Body	Body
Reported SAR value	0.62 W/kg	0.91 W/kg	0.89 W/kg	0.74 W/kg	0.75 W/kg
Measured SAR value	0.394 W/kg	0.691 W/kg	1.04 W/kg	0.651 W/kg	0.563 W/kg
Operation mode, frequency [MHz]	11g(6Mbps), 2462	11a(6Mbps), 5240	11a(6Mbps), 5300	n40(MCS0), 5510	11a(6Mbps), 5825
Duty cycle [%] (scaled factor)	100 ($\times 1.00$)	100 ($\times 1.00$)	100 ($\times 1.00$)	100 ($\times 1.00$)	100 ($\times 1.00$)
Output power [dBm] (max. power, scaled factor)	12.03 (14, $\times 1.57$)	11.78 (13, $\times 1.32$)	11.81 (13, $\times 1.32$)	12.43 (13, $\times 1.14$)	11.76 (13, $\times 1.33$)

Note: UL Japan's SAR Work Procedures No.13-EM-W0429 and 13-EM-W0430. No addition, deviation nor exclusion has been made from standards

*. (Calculating formula) Corrected SAR to max.power (W/kg) = (Measured SAR (W/kg)) \times (Duty scaled) \times (Tune-up factor)
where; Tune-up factor [-] = $1 / (10^{\Delta \text{max}} (\text{max.power} - \text{burst average power}, \text{dB}^{\Delta \text{max}} / 10))$, Duty scaled factor [-] = $100(\%) / (\text{duty cycle, \%})$

Test outline: Where this product is built into a platform (1), it was verified whether multiplatform conditions can be suited in according with section 2) of 5.2.2 in KDB447498 D01 (v06).

Consideration of the test results: The highest reported SAR (1g) of this platform (1) was kept; $\leq 0.8 \text{ W/kg}$ (SAR(1g)), $\leq 2 \text{ W/kg}$ (SAR(10g)).
Since highest reported SAR on this EUT's platform obtained in accordance with KDB447498 D01 (v06) was kept under 50% of SAR limit, this EUT was approved to operate multi-platform.

UL Japan, Inc.
Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN
Telephone: +81 463 50 6400 / Facsimile: +81 463 50 6401

3.4 Test Location

No.7 shielded room (2.76m (Width) \times 3.76m (Depth) \times 2.4m (Height)) for SAR testing.

UL Japan, Inc., Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken 259-1220 JAPAN

Telephone number: +81 463 50 6400 / Facsimile number: +81 463 50 6401

3.5 Confirmation before SAR testing

3.5.1 Average power for SAR tests

Before SAR test, the RF wiring for the sample had been switched to the antenna conducted power measurement line from the antenna line and the average power was measured. The result is shown in Section 6.

*. The platform transmission power was verified that it was within 2dB lower than the maximum tune-up tolerance limit when it was set the rated power. (Clause 4.1, KDB447498 D01 (v06))

Step.1 Data rate check (*. The platform supported the following data rate in each operation mode.)

11b		11g		11a		11n(20HT)			11n(40HT)		
Mod (DSSS)	Data rate	Mod (OFDM)	Data rate	Mod (OFDM)	Data rate	MCS Index	Spatial Stream	Mod (OFDM)	MCS Index	Spatial Stream	Mod (OFDM)
DBPSK	1 Mbps	BPSK	6 Mbps	BPSK	6 Mbps	MCS0	1	BPSK	MCS0	1	BPSK
DQPSK	2 Mbps	BPSK	9 Mbps	BPSK	9 Mbps	MCS1	1	QPSK	MCS1	1	QPSK
CCK	5.5 Mbps	QPSK	12 Mbps	QPSK	12 Mbps	MCS2	1	QPSK	MCS2	1	QPSK
CCK	11 Mbps	QPSK	18 Mbps	QPSK	18 Mbps	MCS3	1	16QAM	MCS3	1	16QAM
*Mod; Modulation		16QAM	24 Mbps	16QAM	24 Mbps	MCS4	1	16QAM	MCS4	1	16QAM
16QAM		36 Mbps	16QAM	36 Mbps	MCS5	1	64QAM	MCS5	1	64QAM	
64QAM		48 Mbps	64QAM	48 Mbps	MCS6	1	64QAM	MCS6	1	64QAM	
64QAM		54 Mbps	64QAM	54 Mbps	MCS7	1	64QAM	MCS7	1	64QAM	

Step.2 Consideration of SAR test channel

For the SAR test reference, on each operation band, the average output power was measured on the lower/middle/upper and specified channels with the worst data rate condition in step 1 in the above.

3.6 Confirmation after SAR testing

It was checked that the power drift [W] is within $\pm 5\%$ in the evaluation procedure of SAR testing. The verification of power drift during the SAR test is that DASY5 system calculates the power drift by measuring the E-filed at the same location at beginning and the end of the scan measurement for each test position.

The result is shown in APPENDIX 2.

*. DASY5 system calculation Power drift value[dB] = $20\log(E_a)/(E_b)$ (where, Before SAR testing: E_b [V/m] / After SAR testing: E_a [V/m])

Limit of power drift[W] = $\pm 5\%$

Power drift limit (X) [dB] = $10\log(P_{drift}) = 10\log(1.05/1) = 10\log(1.05) - 10\log(1) = 0.21\text{dB}$
from E-filed relations with power.

$S = E \times H = E^2 / \eta = P / (4 \times \pi \times r^2)$ (η : Space impedance) $\rightarrow P = (E^2 \times 4 \times \pi \times r^2) / \eta$

Therefore, The correlation of power and the E-filed

Power drift limit (X) dB = $10\log(P_{drift}) = 10\log(E_{drift})^2 = 20\log(E_{drift})$

From the above mentioned, the calculated power drift of DASY5 system must be the less than $\pm 0.21\text{dB}$.

3.7 Test setup of platform and SAR measurement procedure

After considering the outline of Flat Panel Sensor, the SAR test was carried out on the following setup conditions.

Setup	Explanation of platform setup position (* Refer to Appendix 1 for test setup photographs.)	Antenna separation [mm]	SAR Tested /Reduced	SAR type
Front	When test is required, the front surface (patient side) of platform was touched to the Flat phantom.	10.8	Tested	Body /Head touch
Long side (Right)	When test is required, the long side edge surface (right, near an antenna side) of platform was touched to the Flat phantom.	10	Tested	
Long side (Left)	When test is required, the long side edge surface (left) of platform was touched to the Flat phantom.	365	Reduced (>200 mm)	
Short side (Top)	When test is required, the short side edge surface (top) of platform was touched to the Flat phantom.	168	Reduced (>150 mm)	
Short side (Bottom)	When test is required, the short side edge surface (bottom) of platform was touched to the Flat phantom.	257	Reduced (>200 mm)	
Back	When test is required, the back surface (operator side) of platform was touched to the Flat phantom.	2.1	Tested	Hand holding

*. Separation: Antenna separation distance. It is the distance from the antenna to the outer surface of platform which a human may touch.

. Size of platform: 460 (W) × 384 (D) × 15.7 (thickness) [mm] (. Size of EUT: 28 (W) × 32 (D) × 2.8 (thickness) [mm])

Consideration for SAR evaluation exemption

KDB 447498 D01 (v06) was taken into consideration to reduce SAR test.

Consideration of SAR test reduction by the antenna separation distance (100MHz~6GHz, ≤50mm)										
Band, Mode	Setup Position	Minimum distance	Upper frequency [GHz]	Maximum power		Calculation of exclusion (*1)	SAR type	SAR test exclusion		Remarks
		[mm]		[mm] (rounded)	[dBm]	[mW]		[mW] (rounded)	Judge for Exclusion	
WLAN 2.4GHz b,g,n(20HT)	Front	10.8	11	2.462	14.0	25.12	25	3.9	1g ≤ 3.0	Required
	Long side (Right)	10	10		5.32	13.0		20	3.6 1g ≤ 3.0	Required
	Back	2.1	2 (≤5)		5.7	13.0		20	7.8 10g ≤ 7.5	Required
WLAN W52&53 a,n(20/40HT)	Front	10.8	11	5.32	13.0	19.95	20	4.6	1g ≤ 3.0	Required
	Long side (Right)	10	10		5.7	13.0		20	4.2 1g ≤ 3.0	Required
	Back	2.1	2 (≤5)		5.7	13.0		20	23.1 10g ≤ 7.5	Required
WLAN W56 a,n(20/40HT)	Front	10.8	11	5.825	13.0	19.95	20	4.8	1g ≤ 3.0	Required
	Long side (Right)	10	10		5.825	13.0		20	4.3 1g ≤ 3.0	Required
	Back	2.1	2 (≤5)		5.825	13.0		20	23.9 10g ≤ 7.5	Required
WLAN W58 a,n(20/40HT)	Front	10.8	11	5.825	13.0	19.95	20	4.8	1g ≤ 3.0	Required
	Long side (Right)	10	10		5.825	13.0		20	4.4 1g ≤ 3.0	Required
	Back	2.1	2 (≤5)		5.825	13.0		20	24.1 10g ≤ 7.5	Required

*1. Parenthesis 1), Clause 4.3.1, KDB 447498 D01 (v06) gives the following formula to calculate the SAR(1g) test exclusion thresholds for 100MHz~6GHz at test separation distance ≤50mm.

$[(\text{max.power of channel, including tune-up tolerance, mW}) / (\text{min.test separation distance, mm})] \times [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ (for SAR(1g))}, 7.5 \text{ (for SAR(10g))}$ formula (1)
 If power is calculated from the upper formula (1),

$[\text{SAR(1g) test exclusion thresholds, mW}] = 3 \times [\text{test separation distance, mm}] / [\sqrt{f(\text{GHz})}] \dots \dots \dots \text{formula (2a)}$

$[\text{SAR(10g) test exclusion thresholds, mW}] = 7.5 \times [\text{test separation distance, mm}] / [\sqrt{f(\text{GHz})}] \dots \dots \dots \text{formula (2b)}$

By the determined test setup shown above, the SAR test was applied in the following procedures.

Step 1	On 2.4GHz band, in body liquid, worst SAR (for both body touching and for hand-holding) search by DSSS mode. Add test for OFDM mode, if it's necessary. Repeat test in head liquid for SAR of head touching.
Step 2	On W52/53 band, in body liquid, worst SAR (for both body touching and for hand-holding) search by largest channel bandwidth mode with highest power. Repeat test in head liquid for SAR of head touching.
Step 3	On W56 band, in body liquid, worst SAR (for both body touching and for hand-holding) search by largest channel bandwidth mode with highest power. Repeat test in head liquid for SAR of head touching.
Step 4	On W58 band, in body liquid, worst SAR (for both body touching and for hand-holding) search by largest channel bandwidth mode with highest power. Repeat test in head liquid for SAR of head touching.

*. During SAR test, the radiated power is always monitored by Spectrum Analyzer.

SECTION 4: Uncertainty Assessment (SAR measurement)

Uncertainty of SAR measurement (2.4-6GHz) (* ϵ & σ : $\leq\pm 5\%$, DAK3.5, Tx: $\approx 100\%$ duty cycle) (v08)							1g SAR	10g SAR
Combined measurement uncertainty of the measurement system (k=1)							$\pm 13.7\%$	$\pm 13.6\%$
Expanded uncertainty (k=2)							$\pm 27.4\%$	$\pm 27.2\%$
	Error Description (2.4-6GHz) (v08)	Uncertainty Value	Probability distribution	Divisor	ci (1g)	ci (10g)	ui (1g)	ui (10g)
A	Measurement System (DASY5)						(std. uncertainty)	(std. uncertainty)
1	Probe Calibration Error	$\pm 6.55\%$	Normal	1	1	1	$\pm 6.55\%$	$\pm 6.55\%$
2	Axial isotropy Error	$\pm 4.7\%$	Rectangular	$\sqrt{3}$	$\sqrt{0.5}$	$\sqrt{0.5}$	$\pm 1.9\%$	$\pm 1.9\%$
3	Hemispherical isotropy Error	$\pm 9.6\%$	Rectangular	$\sqrt{3}$	$\sqrt{0.5}$	$\sqrt{0.5}$	$\pm 3.9\%$	$\pm 3.9\%$
4	Linearity Error	$\pm 4.7\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 2.7\%$	$\pm 2.7\%$
5	Probe modulation response	$\pm 2.4\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 1.4\%$	$\pm 1.4\%$
6	Sensitivity Error (detection limit)	$\pm 1.0\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 0.6\%$	$\pm 0.6\%$
7	Boundary effects Error	$\pm 4.3\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 2.5\%$	$\pm 2.5\%$
8	Readout Electronics Error(DAE)	$\pm 0.3\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 0.3\%$	$\pm 0.3\%$
9	Response Time Error	$\pm 0.8\%$	Normal	1	1	1	$\pm 0.8\%$	$\pm 0.8\%$
10	Integration Time Error ($\approx 100\%$ duty cycle)	$\pm 0\%$	Rectangular	$\sqrt{3}$	1	1	0%	0%
11	RF ambient conditions-noise	$\pm 3.0\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 1.7\%$	$\pm 1.7\%$
12	RF ambient conditions-reflections	$\pm 3.0\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 1.7\%$	$\pm 1.7\%$
13	Probe positioner mechanical tolerance	$\pm 3.3\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 1.9\%$	$\pm 1.9\%$
14	Probe Positioning with respect to phantom shell	$\pm 6.7\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 3.9\%$	$\pm 3.9\%$
15	Max. SAR evaluation (Post-processing)	$\pm 4.0\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 2.3\%$	$\pm 2.3\%$
B	Test Sample Related							
16	Device Holder or Positioner Tolerance	$\pm 3.6\%$	Normal	1	1	1	$\pm 3.6\%$	$\pm 3.6\%$
17	Test Sample Positioning Error	$\pm 5.0\%$	Normal	1	1	1	$\pm 5.0\%$	$\pm 5.0\%$
18	Power scaling	$\pm 0\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 0\%$	$\pm 0\%$
19	Drift of output power (measured, $<0.2\text{dB}$)	$\pm 2.3\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 2.9\%$	$\pm 2.9\%$
C	Phantom and Setup							
20	Phantom uncertainty (shape, thickness tolerances)	$\pm 7.5\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 4.3\%$	$\pm 4.3\%$
21	Algorithm for correcting SAR ($\epsilon', \sigma' \leq 5\%$)	$\pm 1.2\%$	Normal	1	1	0.84	$\pm 1.2\%$	$\pm 0.97\%$
22	Measurement Liquid Conductivity Error (DAK3.5)	$\pm 3.0\%$	Normal	1	0.78	0.71	$\pm 2.3\%$	$\pm 2.1\%$
23	Measurement Liquid Permittivity Error (DAK3.5)	$\pm 3.1\%$	Normal	1	0.23	0.26	$\pm 0.7\%$	$\pm 0.8\%$
24	Liquid Conductivity-temp.uncertainty ($\leq 2\text{deg.C.}$)	$\pm 5.3\%$	Rectangular	$\sqrt{3}$	0.78	0.71	$\pm 2.4\%$	$\pm 2.2\%$
25	Liquid Permittivity-temp.uncertainty ($\leq 2\text{deg.C.}$)	$\pm 0.9\%$	Rectangular	$\sqrt{3}$	0.23	0.26	$\pm 0.1\%$	$\pm 0.1\%$
	Combined Standard Uncertainty						$\pm 13.7\%$	$\pm 13.6\%$
	Expanded Uncertainty (k=2)						$\pm 27.4\%$	$\pm 27.2\%$

*. Table of uncertainties are listed for ISO/IEC 17025.

*. This measurement uncertainty budget is suggested by IEEE Std.1528(2013) and determined by Schmid & Partner Engineering AG (DASY5 Uncertainty Budget). Per KDB 865664 D01 (v01r04) SAR Measurement 100 MHz to 6 GHz Section 2.8.1., when the highest measured SAR(1g) within a frequency band is $< 1.5\text{W/kg}$, the extensive SAR measurement uncertainty analysis described in IEEE Std.1528 (2013) is not required in SAR reports submitted for equipment approval.

SECTION 5: Operation of platform during testing

5.1 Operating modes for SAR testing

The EUT has IEEE 802.11b, g, a, n(20HT) and n(40HT) continuous transmitting modes. The frequency and the modulation used in the SAR testing are shown as a following.

Operation mode	b	g	n20	n40	a	n20	n40	a	n20	n40	a	n20	n40	a	n20	n40
band	DTS			U-NII-1(W52)			U-NII-2A(W53)			U-NII-2C(W56)			U-NII-3(W58)			
Tx band [MHz]	2412~2462	2422~2452	5180~5240	5190, 5230	5260~5320	5270, 5310	5500~5700	5510, 5670	5745~5825	5755, 5795						
Bandwidth [MHz]	20	20	20	40	20	20	40	20	20	40	20	20	40	20	20	40
Max.power [dBm]	14	14	14	13	13	13	13	13	13	13	13	13	13	13	13	13
Modulation	DSSS	OFDM	OFDM	OFDM	OFDM	OFDM	OFDM	OFDM	OFDM	OFDM	OFDM	OFDM	OFDM	OFDM	OFDM	OFDM
Data rate [Mbps]	1	6	MCS0	MCS0	6	MCS0	MCS0	6	MCS0	MCS0	6	MCS0	MCS0	6	MCS0	MCS0
Frequency [MHz]	S	Body	*1	*1	*1	*1	*1	*1	*1	*1	*1	*1	*1	*1	*1	*1
	A	Head	*2	*2	*2	*2	Reduced	Reduced	*2	*2	*2	*2	*2	*2	*2	*2
	R	Hand	*3	*3	*3	*3	*3	*3	*3	*3	*3	*3	*3	*3	*3	*3
Controlled software	"W8787 (802.11a/g/b/n) Test Menu of Labtool" mode (for antenna terminal conducted power measurement) Set Tx parameters which includes; "band (2.4G/5G)", "band width (20MHz/40MHz)", "channel", "Power", "modulation method(DSSS/OFDM)", "data rate", "start/stop" by host PC via SD card board. "rftest" mode (for SAR test) Set Tx parameters which includes; "antenna# (1)", "channel", "BW(0:20MHz, 1:40MHz)", "Power(dBm, 12 or 11)", "data rate (0: 1Mbps, 5:6Mbps, 14:MCS0)", "on/off (2:on/18:off)" by host PC via LAN cable.															

(cont'd)

5.1 Operating modes for SAR testing (cont'd)

SAR test reduction consideration

*1. [Table 1. Output power and Body-SAR test channel selection and Reported SAR(1g) [W/kg] (Results) and test reduction plan]

802.11 Modes	b	g	n(20HT)	n(40HT)	a	n(20HT)	n(40HT)
Data rate [Mbps]	1 (lowest)	6 (lowest)	MCS0 (lowest)	MCS0 (lowest)	6 (lowest)	MCS0 (lowest)	MCS0 (lowest)
2.4GHz, Ch.	1/6/11	1/6/11	1/6/11	1/6/11			
Max. power [mW]	25/25/25	25/25/25	25/25/25	20/20/20			
Measured Ave. [mW]	18 / 17 / 16	18 / 17 / 16	17 / 17 / 16	15 / 15 / 14			
Reported SAR 1g	0.18 / 0.29 / 0.32	0.32 (*1)	0.32 (*1)	0.24 (*1)			
W52, Ch.					36/40/44/48	36/40/44/48	38/46
Max. power [mW]					20/20/20/20	20/20/20/20	20/20
Measured Ave. [mW]					15/15/16/15	15/15/16/15	15 / 15
Reported SAR 1g					Reduced (W53<1.2W/kg)	0.39	0.42 / 0.35
W53, Ch.					52/56/60/64	52/56/60/64	54/62
Max. power [mW]					20/20/20/20	20/20/20/20	20/20/20
Measured Ave. [mW]					15 / 15 / 15 / 16	16 / 16 / 16 / 16	15 / 15
Reported SAR 1g					0.31	0.41 / 0.40 / 0.41	0.29 / 0.39
W56, Ch.					100/116/120/140	100/116/120/140	102/110/118/134
Max. power [mW]					20/20/20/20	20/20/20/20	20/20/20/20
Measured Ave. [mW]					18 / 19 / 18 / 19	18 / 19 / 18 / 19	18 / 17 / 18 / 20
Reported SAR 1g					0.31	0.27 / 0.30 / 0.32 / 0.45	0.28 / 0.29 / 0.32 / 0.24
W58, Ch.					149/157/165	149/157/165	151/159
Max. power [mW]					20/20/20	20/20/20	20/20
Measured Ave. [mW]					17 / 15 / 15	16 / 15 / 15	16 / 14
Reported SAR 1g					0.66	0.51 / 0.42 / 0.67	0.32 / 0.57

*2. [Table 2. Output power and Head-SAR test channel selection and Reported SAR(1g) [W/kg] (Results) and test reduction plan]

802.11 Modes	b	g	n(20HT)	n(40HT)	a	n(20HT)	n(40HT)
Data rate [Mbps]	1 (lowest)	6 (lowest)	MCS0 (lowest)	MCS0 (lowest)	6 (lowest)	MCS0 (lowest)	MCS0 (lowest)
2.4GHz, Ch.	1/6/11	1/6/11	1/6/11	1/6/11			
Max. power [mW]	25/25/25	25/25/25	25/25/25	20/20/20			
Measured Ave. [mW]	18 / 17 / 16	18 / 17 / 16	17 / 17 / 16	15 / 15 / 14			
Reported SAR 1g	0.24 / 0.31 / 0.35	0.34	0.34	0.26			
W52, Ch.					36/40/44/48	36/40/44/48	38/46
Max. power [mW]					20/20/20/20	20/20/20/20	20/20
Measured Ave. [mW]					15/15/16/15	15/15/16/15	15 / 15
Reported SAR 1g					Reduced (W53<1.2W/kg)	Reduced (W53<1.2W/kg)	0.39 / 0.38
W53, Ch.					52/56/60/64	52/56/60/64	54/62
Max. power [mW]					20/20/20/20	20/20/20/20	20/20/20
Measured Ave. [mW]					15 / 15 / 15 / 16	16 / 16 / 16 / 16	15 / 15
Reported SAR 1g					Reduced (n(40HT)<0.8W/kg, Head SAR(1g)<Body SAR(1g))	0.26 / 0.39	
W56, Ch.					100/116/120/140	100/116/120/140	102/110/118/134
Max. power [mW]					20/20/20/20	20/20/20/20	20/20/20/20
Measured Ave. [mW]					18 / 19 / 18 / 19	18 / 19 / 18 / 19	18 / 17 / 18 / 20
Reported SAR 1g					0.23 / 0.28 / 0.29 / 0.42	0.39	0.24 / 0.26 / 0.28 / 0.30
W58, Ch.					149/157/165	149/157/165	151/159
Max. power [mW]					20/20/20	20/20/20	20/20
Measured Ave. [mW]					17 / 15 / 15	16 / 15 / 15	16 / 14
Reported SAR 1g					0.50	0.51 / 0.58 / 0.66	0.51 / 0.61

*3. [Table 3. Output power and Hand-SAR test channel selection and Reported SAR(10g) [W/kg] (Results) and test reduction plan]

802.11 Modes	b	g	n(20HT)	n(40HT)	a	n(20HT)	n(40HT)
Data rate [Mbps]	1 (lowest)	6 (lowest)	MCS0 (lowest)	MCS0 (lowest)	6 (lowest)	MCS0 (lowest)	MCS0 (lowest)
2.4GHz, Ch.	1/6/11	1/6/11	1/6/11	1/6/11			
Max. power [mW]	25/25/25	25/25/25	25/25/25	20/20/20			
Measured Ave. [mW]	18 / 17 / 16	18 / 17 / 16	17 / 17 / 16	15 / 15 / 14			
Reported SAR 10g	0.35 / 0.50 / 0.62	0.62	0.62	0.47			
W52, Ch.					36/40/44/48	36/40/44/48	38/46
Max. power [mW]					20/20/20/20	20/20/20/20	20/20
Measured Ave. [mW]					15 / 15 / 16 / 15	15 / 15 / 16 / 15	15 / 15
Reported SAR 10g					0.85 / 0.85 / 0.91	Reduced (W53<1.2W/kg)	0.83 / 0.90
W53, Ch.					52/56/60/64	52/56/60/64	54/62
Max. power [mW]					20/20/20/20	20/20/20/20	20/20/20
Measured Ave. [mW]					15 / 15 / 15 / 16	16 / 16 / 16 / 16	15 / 15
Reported SAR 10g					0.87 / 0.89 / 0.81	0.72	0.80 / 0.61
W56, Ch.					100/116/120/140	100/116/120/140	102/110/118/134
Max. power [mW]					20/20/20/20	20/20/20/20	20/20/20/20
Measured Ave. [mW]					18 / 19 / 18 / 19	18 / 19 / 18 / 19	18 / 17 / 18 / 20
Reported SAR 10g					0.72	0.74 / 0.45 / 0.60 / 0.61	0.74 / 0.68 / 0.51 / 0.37
W58, Ch.					149/157/165	149/157/165	151/159
Max. power [mW]					20/20/20	20/20/20	20/20
Measured Ave. [mW]					17 / 15 / 15	16 / 15 / 15	16 / 14
Reported SAR 10g					0.64 / 0.65 / 0.75	0.62	0.53 / 0.53

* Ch: Channel, Max: Maximum power in specification, AT: Antenna terminal conducted average power measured, SAR(1g): Reported SAR(1g) [W/kg] with tuned-up

*1. (KDB248227 D01) Since the reported SAR(1g) value of 11b mode was ≤0.8 W/kg, SAR test was only applied the worst SAR channel of 11b for OFDM mode.

*. The SAR testing was applied to lower, middle and upper channels for the worst SAR condition in each operation band.

SECTION 6: Confirmation before testing

6.1 Assessment for the antenna terminal port conducted power of platform (Worst data rate, worst channel determination)

*. Antenna gain (peak): 3.0 dBi (2.4~2.5 GHz) / 4.5 dBi (5.15~5.85 GHz)

Mode	Frequency		Data rate	Power Setting	Duty cycle	Duty factor	Duty scaled factor	Time average power		Power tolerance & correction			Power Tune-up?	Remarks
	[MHz]	CH	[Mbps]	[dBm]	[%]	[dB]	[$\times 1.00$]	[dBm]	[mW]	PAR [dB]	Target & (+/-)tolerance [dBm]	Deviation from max (-2≤x<0) [dB]	Tune-up factor [-]	
11b	2412	1	1	12	100	0.00	$\times 1.00$	12.50	17.78	2.56	12.0+2	-1.50	$\times 1.41$	default
	2437	6	1	12	100	0.00	$\times 1.00$	12.30	16.98	2.64	12.0+2	-1.70	$\times 1.48$	default
	2462	11	1	12	100	0.00	$\times 1.00$	12.07	16.11	2.62	12.0+2	-1.93	$\times 1.56$	default
11g	2412	1	6	12	100	0.00	$\times 1.00$	12.44	17.54	9.67	12.0+2	-1.56	$\times 1.43$	default
	2437	6	6	12	100	0.00	$\times 1.00$	12.37	17.26	9.74	12.0+2	-1.63	$\times 1.46$	default
	2462	11	6	12	100	0.00	$\times 1.00$	12.03	15.96	9.84	12.0+2	-1.97	$\times 1.57$	default
11n (20HT)	2412	1	MCS0	12	100	0.00	$\times 1.00$	12.36	17.22	8.56	12.0+2	-1.64	$\times 1.46$	default
	2437	6	MCS0	12	100	0.00	$\times 1.00$	12.23	16.71	8.55	12.0+2	-1.77	$\times 1.50$	default
	2462	11	MCS0	12	100	0.00	$\times 1.00$	12.03	15.96	8.12	12.0+2	-1.97	$\times 1.57$	default
11n (40HT)	2422	3	MCS0	11	100	0.00	$\times 1.00$	11.81	15.17	8.91	11.0+2	-1.19	$\times 1.32$	default
	2437	6	MCS0	11	100	0.00	$\times 1.00$	11.81	15.17	8.83	11.0+2	-1.19	$\times 1.32$	default
	2452	9	MCS0	11	100	0.00	$\times 1.00$	11.31	13.52	8.57	11.0+2	-1.69	$\times 1.48$	default
11a	5180	36	6	11	100	0.00	$\times 1.00$	11.86	15.35	9.52	11.0+2	-1.14	$\times 1.30$	default
	5200	40	6	11	100	0.00	$\times 1.00$	11.68	14.72	9.46	11.0+2	-1.32	$\times 1.36$	default
	5220	44	6	11	100	0.00	$\times 1.00$	11.95	15.67	9.65	11.0+2	-1.05	$\times 1.27$	default
	5240	48	6	11	100	0.00	$\times 1.00$	11.78	15.07	9.47	11.0+2	-1.22	$\times 1.32$	default
	5260	52	6	11	100	0.00	$\times 1.00$	11.89	15.45	9.35	11.0+2	-1.11	$\times 1.29$	default
	5280	56	6	11	100	0.00	$\times 1.00$	11.86	15.35	9.50	11.0+2	-1.14	$\times 1.30$	default
	5300	60	6	11	100	0.00	$\times 1.00$	11.81	15.17	9.54	11.0+2	-1.19	$\times 1.32$	default
	5320	64	6	11	100	0.00	$\times 1.00$	12.00	15.85	9.78	11.0+2	-1.00	$\times 1.26$	default
	5500	100	6	11	100	0.00	$\times 1.00$	12.60	18.20	9.26	11.0+2	-0.40	$\times 1.10$	default
	5580	116	6	11	100	0.00	$\times 1.00$	12.68	18.54	9.19	11.0+2	-0.32	$\times 1.08$	default
	5600	120	6	11	100	0.00	$\times 1.00$	12.59	18.16	9.26	11.0+2	-0.41	$\times 1.10$	default
	5700	140	6	11	100	0.00	$\times 1.00$	12.84	19.23	9.12	11.0+2	-0.16	$\times 1.04$	default
	5745	149	6	11	100	0.00	$\times 1.00$	12.26	16.83	9.06	11.0+2	-0.74	$\times 1.19$	default
	5785	157	6	11	100	0.00	$\times 1.00$	11.84	15.28	9.29	11.0+2	-1.16	$\times 1.31$	default
	5825	165	6	11	100	0.00	$\times 1.00$	11.76	15.00	9.20	11.0+2	-1.24	$\times 1.33$	default
11n (20HT)	5180	36	MCS0	11	100	0.00	$\times 1.00$	11.89	15.45	8.70	11.0+2	-1.11	$\times 1.29$	default
	5200	40	MCS0	11	100	0.00	$\times 1.00$	11.74	14.93	8.73	11.0+2	-1.26	$\times 1.34$	default
	5220	44	MCS0	11	100	0.00	$\times 1.00$	12.00	15.85	8.87	11.0+2	-1.00	$\times 1.26$	default
	5240	48	MCS0	11	100	0.00	$\times 1.00$	11.78	15.07	8.86	11.0+2	-1.22	$\times 1.32$	default
	5260	52	MCS0	11	100	0.00	$\times 1.00$	12.02	15.92	8.82	11.0+2	-0.98	$\times 1.25$	default
	5280	56	MCS0	11	100	0.00	$\times 1.00$	12.04	16.00	8.88	11.0+2	-0.96	$\times 1.25$	default
	5300	60	MCS0	11	100	0.00	$\times 1.00$	11.95	15.67	8.59	11.0+2	-1.05	$\times 1.27$	default
	5320	64	MCS0	11	100	0.00	$\times 1.00$	12.09	16.18	8.82	11.0+2	-0.91	$\times 1.23$	default
	5500	100	MCS0	11	100	0.00	$\times 1.00$	12.48	17.70	8.68	11.0+2	-0.52	$\times 1.13$	default
	5580	116	MCS0	11	100	0.00	$\times 1.00$	12.72	18.71	8.45	11.0+2	-0.28	$\times 1.07$	default
	5600	120	MCS0	11	100	0.00	$\times 1.00$	12.64	18.37	8.61	11.0+2	-0.36	$\times 1.09$	default
	5700	140	MCS0	11	100	0.00	$\times 1.00$	12.84	19.23	8.53	11.0+2	-0.16	$\times 1.04$	default
	5745	149	MCS0	11	100	0.00	$\times 1.00$	12.14	16.37	8.55	11.0+2	-0.86	$\times 1.22$	default
	5785	157	MCS0	11	100	0.00	$\times 1.00$	11.79	15.10	8.44	11.0+2	-1.21	$\times 1.32$	default
	5825	165	MCS0	11	100	0.00	$\times 1.00$	11.74	14.93	8.42	11.0+2	-1.26	$\times 1.34$	default
11n (40HT)	5190	38	MCS0	11	100	0.00	$\times 1.00$	11.86	15.35	9.10	11.0+2	-1.14	$\times 1.30$	default
	5230	46	MCS0	11	100	0.00	$\times 1.00$	11.88	15.42	9.02	11.0+2	-1.12	$\times 1.29$	default
	5270	54	MCS0	11	100	0.00	$\times 1.00$	11.89	15.45	8.83	11.0+2	-1.11	$\times 1.29$	default
	5310	62	MCS0	11	100	0.00	$\times 1.00$	11.70	14.79	8.85	11.0+2	-1.30	$\times 1.35$	default
	5510	102	MCS0	11	100	0.00	$\times 1.00$	12.43	17.50	8.90	11.0+2	-0.57	$\times 1.14$	default
	5550	110	MCS0	11	100	0.00	$\times 1.00$	12.36	17.22	8.81	11.0+2	-0.64	$\times 1.16$	default
	5590	118	MCS0	11	100	0.00	$\times 1.00$	12.54	17.95	8.84	11.0+2	-0.46	$\times 1.11$	default
	5670	134	MCS0	11	100	0.00	$\times 1.00$	12.92	19.59	8.62	11.0+2	-0.08	$\times 1.02$	default
	5745	149	MCS0	11	100	0.00	$\times 1.00$	12.15	16.41	8.36	11.0+2	-0.85	$\times 1.22$	default
	5825	165	MCS0	11	100	0.00	$\times 1.00$	11.58	14.39	8.52	11.0+2	-1.42	$\times 1.39$	default

*. Preliminary tests were performed in different data rate and data rate associated with the highest power were chosen for full test in following tables.

Data rate (D/R) vs Time average power (dBm)												11b (2412MHz)			11g (2412MHz)		
Duty cycle: 100%			Duty cycle: 100%			Duty cycle: 100%			Duty cycle: 100%			Duty cycle: 100%			Duty cycle: 100%		
D/R	Power	D/R	Power	D/R	Power	D/R	Power	D/R	Power	D/R	Power	D/R	Power	D/R	Power	D/R	Power
1	12.50	6	12.44	MCS0	12.36	6	11.81	MCS0	12.60	MCS0	12.48	MCS0	12.49				
2	12.48	9	12.34	MCS1	12.12	9	11.70	MCS1	12.54	MCS1	12.46	MCS1	12.42				
5.5	12.36	12	12.30	MCS2	12.32	12	11.62	MCS2	12.55	MCS2	12.45	MCS2	12.39				
11	12.34	18	12.38	MCS3	12.34	18	11.58	MCS3	12.56	MCS3	12.46	MCS3	12.35				
		24	12.23	MCS4	12.31	24	11.68	MCS4	12.57	MCS4	12.45	MCS4	12.37				
		36	12.24	MCS5	12.35	36	11.68	MCS5	12.44	MCS5	12.45	MCS5	12.36				
		48	12.34	MCS6	12.33	48	11.64	MCS6	12.54	MCS6	12.45	MCS6	12.41				
		56	12.29	MCS7	12.32	56	11.59	MCS7	12.39	MCS7	12.46	MCS7	12.36				

- *. The EUT (Wireless LAN module) used in SAR test (serial number: 42) is identical with the one in which EMC (Radio) was measured.
- *. PAR: Peak average ratio ("Peak power"-"Average power", in dBm), CH: channel, Max: Maximum.
- *. Calculating formula: Time average power-result: Results (dBm) = (P/M Reading, dBm)+(Cable loss, dB)+(Attenuator, dB)+(duty factor, dB)
Duty factor: (duty factor, dBm) = $10 \times \log (100 / (\text{duty cycle, \%}))$
Deviation from max.: (Power deviation, dB) = (results power (average, dBm)) - (Max.-specification output power (average, dBm))
Duty scaled factor: Duty cycle correction factor for obtained SAR value, Duty scaled factor [-] = $100(\%) / (\text{duty cycle, \%})$
Tune-up factor: Power tune-up factor for obtained SAR value, Tune-up factor [-] = $1 / (10^{(\text{Deviation from max, dB} / 10)})$
- *. Date measured: September 30, 2016 / Measured by: Hiroshi Naka / Place: preparation room of No. 7 shielded room. (24 deg C. / 58 %RH)
- *. Uncertainty of antenna port conducted test; Power measurement uncertainty above 1GHz for this test was: (\pm) 0.76 dB(Average)(\pm) 0.79 dB(Peak).
- *. Uncertainty of antenna port conducted test; Duty cycle and time measurement: (\pm) 0.012 %.

SECTION 7: SAR Measurement results

Measurement date: October 19 ~ November 21, 2016

Measurement by: Hiroshi Naka

7.1 Liquid measurement

Target Frequency [MHz]	Liquid type	Liquid parameters (*a)								ΔSAR Coefficients(*b)			Date measured	
		Permittivity (εr) [-]			Conductivity [S/m]			Temp. [deg.C.]	Depth [mm]	ΔSAR		Correction required?		
		Target	Measured	Limit	Target	Measured	Limit			1g [%]	10g [%]			
2412	Body	52.75	50.48	-4.3	-5% ≤ Δε _{meas} ≤ 0%	1.914	1.954	+2.1	0% ≤ σ _{meas} ≤ +5%	22.4	152	+2.00	+1.24	not required.
2437		52.72	50.39	-4.4		1.938	1.963	+2.4				+2.13	+1.32	not required.
2452		52.70	50.33	-4.5		1.953	2.005	+2.7				+2.28	+1.40	not required.
2462		52.68	50.29	-4.5		1.967	2.015	+2.4				+2.19	+1.35	not required.
5180	Body	49.04	47.18	-3.8	-5% ≤ Δε _{meas} ≤ 0%	5.276	5.416	+2.7	0% ≤ σ _{meas} ≤ +5%	23.8	151	+0.70	+0.83	not required.
5190		49.03	47.21	-3.7		5.288	5.414	+2.4				+0.69	+0.82	not required.
5220		48.99	47.04	-4.0		5.323	5.485	+3.1				+0.72	+0.86	not required.
5230		48.99	46.91	-4.2		5.334	5.483	+2.8				+0.77	+0.93	not required.
5240		48.96	46.96	-4.1		5.346	5.489	+2.7				+0.74	+0.90	not required.
5260		48.93	46.93	-4.1		5.369	5.501	+2.5				+0.75	+0.92	not required.
5270		48.92	47.01	-3.9		5.381	5.535	+2.9				+0.70	+0.85	not required.
5300		48.88	46.98	-3.9		5.416	5.539	+2.3				+0.71	+0.88	not required.
5310		48.87	46.83	-4.2		5.428	5.561	+2.5				+0.76	+0.94	not required.
5320		48.85	46.88	-4.0		5.439	5.601	+3.0				+0.71	+0.88	not required.
5500	Body	48.61	46.54	-4.3	-5% ≤ Δε _{meas} ≤ 0%	5.650	5.786	+2.4	0% ≤ σ _{meas} ≤ +5%	23.8	151	+0.75	+0.98	not required.
5510		48.59	46.53	-4.3		5.661	5.852	+3.4				+0.71	+0.93	not required.
5550		48.54	46.42	-4.4		5.708	5.855	+2.6				+0.76	+1.00	not required.
5580		48.50	46.33	-4.5		5.743	5.921	+3.1				+0.75	+1.01	not required.
5590		48.49	46.40	-4.3		5.755	5.948	+3.4				+0.71	+0.96	not required.
5600		48.47	46.39	-4.3		5.766	5.978	+3.7				+0.69	+0.94	not required.
5670		48.38	46.24	-4.4		5.848	6.057	+3.6				+0.72	+0.99	not required.
5700		48.34	46.29	-4.2		5.883	6.092	+3.5				+0.68	+0.95	not required.
5745	Body	48.27	46.07	-4.6	-5% ≤ Δε _{meas} ≤ 0%	5.936	6.143	+3.5	0% ≤ σ _{meas} ≤ +5%	23.8	151	+0.75	+1.04	not required.
5755		48.26	46.23	-4.2		5.947	6.179	+3.9				+0.66	+0.94	not required.
5785		48.22	46.04	-4.5		5.982	6.209	+3.8				+0.73	+1.03	not required.
5795		48.21	46.07	-4.4		5.994	6.221	+3.8				+0.71	+1.01	not required.
5825		48.17	46.07	-4.4		6.029	6.312	+4.7				+0.65	+0.96	not required.
2412	Head	39.27	37.91	-3.5	-5% ≤ Δε _{meas} ≤ 0%	1.766	1.823	+3.2	0% ≤ σ _{meas} ≤ +5%	23.4	152	+2.35	+1.40	not required.
2437		39.22	37.84	-3.5		1.788	1.850	+3.5				+2.47	+1.47	not required.
2462		39.18	37.67	-3.9		1.813	1.874	+3.3				+2.47	+1.48	not required.
2412	Head	39.27	38.05	-3.1	-5% ≤ Δε _{meas} ≤ 0%	1.766	1.832	+3.7	0% ≤ σ _{meas} ≤ +5%	23.8	152	+2.51	+1.48	not required.
2437		39.22	37.90	-3.4		1.788	1.858	+3.9				+2.64	+1.56	not required.
2452		39.20	37.85	-3.4		1.802	1.870	+3.8				+2.58	+1.52	not required.
2462		39.18	37.82	-3.5		1.813	1.884	+3.9				+2.65	+1.56	not required.
5190	Head	36.00	35.89	-0.3	-5% ≤ Δε _{meas} ≤ +5%	4.645	4.477	-3.6	-5% ≤ σ _{meas} ≤ +5%	22.8	151	+0.15	+0.26	not required.
5230		35.95	35.86	-0.3		4.686	4.522	-3.5				+0.15	+0.25	not required.
5270		35.91	35.75	-0.4		4.727	4.590	-2.9				+0.18	+0.27	not required.
5310		35.86	35.74	-0.3		4.768	4.606	-3.4				+0.18	+0.26	not required.
5500	Head	35.64	35.43	-0.6	-5% ≤ Δε _{meas} ≤ +5%	4.963	4.777	-3.8	-5% ≤ σ _{meas} ≤ +5%	22.8	151	+0.28	+0.34	not required.
5510		35.63	35.47	-0.5		4.973	4.800	-3.5				+0.24	+0.28	not required.
5550		35.59	35.55	-0.1		5.014	4.866	-3.0				+0.15	+0.16	not required.
5580		35.55	35.40	-0.4		5.045	4.887	-3.1				+0.22	+0.25	not required.
5590		35.54	35.32	-0.6		5.055	4.860	-3.9				+0.29	+0.33	not required.
5600		35.53	35.29	-0.7		5.065	4.899	-3.3				+0.28	+0.31	not required.
5670		35.45	35.22	-0.7		5.137	4.988	-2.9				+0.26	+0.28	not required.
5700		35.41	35.16	-0.7		5.168	5.014	-3.0				+0.28	+0.29	not required.
5745	Head	35.36	35.29	-0.2	-5% ≤ Δε _{meas} ≤ +5%	5.214	5.033	-3.5	-5% ≤ σ _{meas} ≤ +5%	22.8	151	+0.20	+0.18	not required.
5755		35.35	35.29	-0.2		5.224	5.054	-3.3				+0.18	+0.16	not required.
5785		35.32	35.16	-0.5		5.255	5.039	-4.1				+0.27	+0.25	not required.
5795		35.31	35.21	-0.3		5.265	5.053	-4.0				+0.23	+0.20	not required.
5825		35.27	35.16	-0.3		5.296	5.059	-4.5				+0.26	+0.21	not required.

*1. On Nov.9, it was within 24 hours from measurement on Nov. 8 and same liquid temperature, so measured parameters of Nov.8 were used continuously
 *2. On Nov.17, it was within 24 hours from measurement on Nov. 16 and same liquid temperature, so measured parameters of Nov.16 were used continuously

- *a. The target value is a parameter defined in Appendix A of KDB865664 D01 (v01r04), the dielectric parameters suggested for head and body tissue simulating liquid are given at 2000, 2450, 3000 and 5800MHz. (*The parameters of the head liquid are the same value as IEEE Std. 1528-2013.) Parameters for the frequencies between 2000-3000, 3000-5800MHz were obtained using linear interpolation. Above 5800MHz were obtained using linear extrapolation.
- *b. Calculating formula: $\Delta\text{SAR}(1g) = C_{\epsilon} \times \Delta\epsilon + C_{\sigma} \times \Delta\sigma$, $C_{\epsilon} = 7.854E-4 \times f^3 + 9.402E-3 \times f^2 - 2.742E-2 \times f + 0.2026$ / $C_{\sigma} = 9.804E-3 \times f^3 - 8.661E-2 \times f^2 + 2.981E-2 \times f + 0.7829$
 $\Delta\text{SAR}(10g) = C_{\epsilon} \times \Delta\epsilon + C_{\sigma} \times \Delta\sigma$, $C_{\epsilon} = 3.456 \times 10^{-3} \times f^3 - 3.531 \times 10^{-2} \times f^2 + 7.675 \times 10^{-2} \times f + 0.1860$ / $C_{\sigma} = 4.479 \times 10^{-3} \times f^3 - 1.586 \times 10^{-2} \times f^2 - 0.1972 \times f + 0.7717$

7.2 SAR measurement results (2.4GHz band, SAR for Body/Head/Hand)

[Measured and Reported (Scaled) SAR results]

Mode	Freq. [MHz] (Channel)	Data rate [Mbps]	SAR measurement results						SAR plot # in Appendix 2-2	Reported SAR [W/kg]						SAR Corrected (Scaled) (*b)	SAR type (1g /10g)	SAR limit	Remarks					
			platform setup			SAR [W/kg]				Duty cycle correction		Output average power correction												
			Position	Gap [mm]	Bty. ID	Meas.	ASAR [%]	ASAR corrected		Duty [%]	Duty scaled	Meas. [dBm]	Max. [dBm]	Tune-up factor										
Step 1a: 2.4GHz Band (Body-SAR, by body liquid)																								
11b	2412(1)	1	Right	0	352	0.125	+2.00	n/a(*a)	Plot 1a-1	100	×1.00	12.50	14	×1.41	0.176	1g	1.6	-						
	2437(6)			0	352	0.194	+2.13	n/a(*a)	Plot 1a-2	100	×1.00	12.30	14	×1.48	0.287	1g	1.6	-						
	2462(11)			0	352	0.205	+2.19	n/a(*a)	Plot 1a-3	100	×1.00	12.07	14	×1.56	0.320	1g	1.6	body-worst 2.4GHz						
	2462(11)		Front	0	351	0.010	+2.19	n/a(*a)	Plot 1a-4	100	×1.00	12.07	14	×1.56	0.016	1g	1.6	-						
11g	2462(11)	6	Right	0	352	0.202	+2.19	n/a(*a)	Plot 1a-5	100	×1.00	12.03	14	×1.57	0.317	1g	1.6	-						
n(20HT)	2462(11)	MCS0		0	352	0.201	+2.19	n/a(*a)	Plot 1a-6	100	×1.00	12.01	14	×1.58	0.318	1g	1.6	-						
n(40HT)	2452(9)	MCS0		0	352	0.162	+2.28	n/a(*a)	Plot 1a-7	100	×1.00	11.31	13	×1.48	0.240	1g	1.6	-						
Step 1b: 2.4GHz Band (Head-SAR, by head liquid)																								
11b	2412(1)	1	Right	0	350	0.172	+2.51	n/a(*a)	Plot 1b-1	100	×1.00	12.50	14	×1.41	0.243	1g	1.6	-						
	2437(6)			0	350	0.212	+2.64	n/a(*a)	Plot 1b-2	100	×1.00	12.30	14	×1.48	0.314	1g	1.6	-						
	2462(11)			0	350	0.223	+2.65	n/a(*a)	Plot 1b-3	100	×1.00	12.07	14	×1.56	0.348	1g	1.6	head-worst 2.4GHz						
	2462(11)		Front	0	350	0.014	+2.65	n/a(*a)	Plot 1b-4	100	×1.00	12.07	14	×1.56	0.022	1g	1.6	-						
11g	2462(11)	6	Right	0	350	0.218	+2.65	n/a(*a)	Plot 1b-5	100	×1.00	12.03	14	×1.57	0.342	1g	1.6	-						
n(20HT)	2462(11)	MCS0		0	350	0.218	+2.65	n/a(*a)	Plot 1b-6	100	×1.00	12.01	14	×1.58	0.344	1g	1.6	-						
n(40HT)	2452(9)	MCS0		0	351	0.175	+2.58	n/a(*a)	Plot 1b-7	100	×1.00	11.31	13	×1.48	0.259	1g	1.6	-						
Step 1c: 2.4GHz Band (Hand-SAR, by body liquid)																								
11b	2412(1)	1	Back	0	350	0.252	+1.24	n/a(*a)	Plot 1c-1	100	×1.00	12.50	14	×1.41	0.355	10g	4	-						
	2437(6)			0	350	0.336	+1.32	n/a(*a)	Plot 1c-2	100	×1.00	12.30	14	×1.48	0.497	10g	4	-						
	2462(11)			0	350	0.394	+1.35	n/a(*a)	Plot 1c-3	100	×1.00	12.07	14	×1.56	0.615	10g	4	-						
	2462(11)			0	350	0.394	+1.35	n/a(*a)	Plot 1c-4	100	×1.00	12.03	14	×1.57	0.619	10g	4	hand-worst 2.4GHz						
11g	2462(11)	6	Back	0	350	0.392	+1.35	n/a(*a)	Plot 1c-5	100	×1.00	12.03	14	×1.57	0.617	10g	4	-						
n(20HT)	2462(11)	MCS0		0	350	0.317	+1.40	n/a(*a)	Plot 1c-6	100	×1.00	11.31	13	×1.48	0.469	10g	4	-						

Notes:

- *. Gap: It is the separation distance between the platform outer surface and the bottom outer surface of phantom; Freq.: Frequency; Max.: Maximum; Meas.: Measured value; n/a: not applied; Bty.ID: Battery ID (*: Battery ID No.350, 351 and 352 are same. Refer to Appendix 1 for more detail.)
- *. During test, the platform was operated with full charged battery and was connected a control interface cable to host PC.
- *. Calibration frequency of the SAR measurement probe (and used conversion factors)

Liquid	SAR test frequency	Probe calibration frequency	Validity	Conversion factor	Uncertainty
Body	2412, 2437, 2452, 2462 MHz	2450 MHz	within ±50MHz of calibration frequency	7.30	±12.0%
Head	2412, 2437, 252, 2462 MHz	2450 MHz	within ±50MHz of calibration frequency	7.15	±12.0%

*. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

*a. Since the calculated ΔSAR values of the tested liquid had shown positive correction, the measured SAR was not converted by ΔSAR correction.

Calculating formula: ASAR corrected SAR (W/kg) = (Meas. SAR (W/kg) × (100 - (ΔSAR(%))) / 100

*b. Calculating formula: Reported SAR (W/kg) = (Measured SAR (W/kg) × (Duty scaled) × (Tune-up factor))

Duty scaled = Duty scaled factor: Duty cycle correction factor for obtained SAR value, Duty scaled factor [-] = 100(%) / (duty cycle, %)

Tune-up factor: Power tune-up factor for obtained SAR value, Tune-up factor [-] = 1 / (10^(Deviation from max., dB) / 10)

(Clause 5.2, 2.4GHz SAR Procedures for 2.4GHz band DSSS and OFDM, in KDB248227 D01 (v02r02))

5.2.1 802.11b DSSS SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either a fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) When the reported SAR of the highest measured maximum output power channel (section 3.1) for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) When the reported SAR is > 0.8 W/kg, SAR is required for that exposure configuration using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

5.2.2 2.4 GHz 802.11g/n OFDM SAR Test Exclusion Requirements

When SAR measurement is required for 2.4 GHz 802.11g/n OFDM configurations, the measurement and test reduction procedures for OFDM are applied (section 5.3, including sub-sections). SAR is not required for the following 2.4 GHz OFDM conditions.

- 1) When KDB Publication 447498 SAR test exclusion applies to the OFDM configuration.

- 2) When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

- *. Result of hand SAR was judged after "0.8 W/kg" in the document above-mentioned was changed for "2 W/kg" and "1.2 W/kg" in the document above-mentioned was changed for "3 W/kg".

7.3 SAR measurement results (5GHz band, SAR for Body/Head/Hand)

[Measured and Reported (Scaled) SAR results]

Mode	Freq. [MHz] (Channel)	Data rate [Mbps]	SAR measurement results						Reported SAR [W/kg]						SAR type (1g /10g)	SAR limit	Remarks		
			platform setup			SAR [W/kg]			SAR plot # in Appendix 2-2	Duty cycle correction		Output average power correction		SAR Corrected (Scaled) (*b)					
			Position	Gap [mm]	Bty. ID	Meas.	ASAR [%]	ASAR corrected		Duty [%]	Duty scaled	Meas. [dBm]	Max. [dBm]	Tune-up factor					
Step 2a: W52/53 Band (Body-SAR, by body liquid)																			
n(40HT)	5270(54)	MCS0	Right	0	351	0.226	+0.70	n/a(*a)	Plot 2a-1	100	×1.00	11.89	13	×1.29	0.292	1g	1.6	-	
	5310(62)			0	351	0.291	+0.76	n/a(*a)	Plot 2a-2	100	×1.00	11.70	13	×1.35	0.393	1g	1.6	-	
	5230(46)			0	351	0.270	+0.77	n/a(*a)	Plot 2a-3	100	×1.00	11.88	13	×1.29	0.348	1g	1.6	-	
	5190(38)			0	351	0.326	+0.69	n/a(*a)	Plot 2a-4	100	×1.00	11.86	13	×1.30	0.424	1g	1.6	body-worst, W52.	
	5270(54)		Front	0	350	0.017	+0.70	n/a(*a)	Plot 2a-5	100	×1.00	11.89	13	×1.29	0.022	1g	1.6	(Patient side)	
11a	5320(64)	6	Right	0	352	0.244	+0.71	n/a(*a)	Plot 2a-6	100	×1.00	12.00	13	×1.26	0.307	1g	1.6	a < n(20HT)	
n(20HT)	5320(64)	MCS0		0	352	0.332	+0.71	n/a(*a)	Plot 2a-7	100	×1.00	12.09	13	×1.23	0.408	1g	1.6	body-worst, W53.	
	5300(60)			0	352	0.313	+0.71	n/a(*a)	Plot 2a-8	100	×1.00	11.95	13	×1.27	0.398	1g	1.6	-	
	5260(52)			0	352	0.324	+0.75	n/a(*a)	Plot 2a-9	100	×1.00	12.02	13	×1.25	0.405	1g	1.6	-	
	5180(36)			0	352	0.300	+0.70	n/a(*a)	Plot 2a-10	100	×1.00	11.89	13	×1.29	0.387	1g	1.6	-	
Step 2b: W52/53 Band (Head-SAR, by head liquid)																			
n(40HT)	5270(54)	MCS0	Right	0	352	0.198	+0.18	n/a(*a)	Plot 2b-1	100	×1.00	11.89	13	×1.29	0.255	1g	1.6	-	
	5310(62)			0	352	0.289	+0.18	n/a(*a)	Plot 2b-2	100	×1.00	11.70	13	×1.35	0.3902	1g	1.6	head-worst, W53.	
	5230(46)			0	352	0.302	+0.15	n/a(*a)	Plot 2b-3	100	×1.00	11.88	13	×1.29	0.3896	1g	1.6	head-worst, W52.	
	5190(38)			0	352	0.293	+0.15	n/a(*a)	Plot 2b-4	100	×1.00	11.86	13	×1.30	0.381	1g	1.6	-	
	5270(54)		Front	0	351	0.00524	+0.18	n/a(*a)	Plot 2b-5	100	×1.00	11.89	13	×1.29	0.007	1g	1.6	(Patient side)	
Step 2c: W52/53 Band (Hand-SAR, by body liquid)																			
n(40HT)	5270(54)	MCS0	Right	0	352	0.476	+0.85	n/a(*a)	Plot 2c-1	100	×1.00	11.89	13	×1.29	0.614	10g	4	-	
	5310(62)			0	352	0.590	+0.94	n/a(*a)	Plot 2c-2	100	×1.00	11.70	13	×1.35	0.797	10g	4	-	
	5230(46)			0	352	0.698	+0.93	n/a(*a)	Plot 2c-3	100	×1.00	11.88	13	×1.29	0.900	10g	4	-	
	5190(38)			0	352	0.639	+0.82	n/a(*a)	Plot 2c-4	100	×1.00	11.86	13	×1.30	0.831	10g	4	-	
	5270(54)		Front	0	350	0.683	+0.88	n/a(*a)	Plot 2c-5	100	×1.00	11.95	13	×1.27	0.867	10g	4	a > n(20HT)	
n(20HT)	5300(60)	MCS0	Back	0	352	0.672	+0.88	n/a(*a)	Plot 2c-6	100	×1.00	11.81	13	×1.32	0.887	10g	4	hand-worst, W53.	
	5320(64)			0	352	0.641	+0.88	n/a(*a)	Plot 2c-7	100	×1.00	12.00	13	×1.26	0.808	10g	4	-	
	5260(52)			0	352	0.675	+0.92	n/a(*a)	Plot 2c-8	100	×1.00	11.89	13	×1.29	0.871	10g	4	-	
	5240(48)			0	352	0.691	+0.90	n/a(*a)	Plot 2c-9	100	×1.00	11.78	13	×1.32	0.912	10g	4	hand-worst, W52(5GHz)	
	5220(44)			0	350	0.672	+0.86	n/a(*a)	Plot 2c-10	100	×1.00	11.95	13	×1.27	0.853	10g	4	-	
	5180(36)			0	350	0.656	+0.83	n/a(*a)	Plot 2c-11	100	×1.00	11.86	13	×1.30	0.853	10g	4	-	
Step 3a: W56 Band (Body-SAR, by body liquid)																			
n(40HT)	5670(134)	MCS0	Right	0	351	0.238	+0.72	n/a(*a)	Plot 3a-1	100	×1.00	12.92	13	×1.02	0.243	1g	1.6	-	
	5590(118)			0	351	0.291	+0.96	n/a(*a)	Plot 3a-2	100	×1.00	12.54	13	×1.11	0.323	1g	1.6	-	
	5550(110)			0	351	0.248	+1.00	n/a(*a)	Plot 3a-3	100	×1.00	12.36	13	×1.16	0.288	1g	1.6	-	
	5510(102)			0	351	0.241	+0.93	n/a(*a)	Plot 3a-4	100	×1.00	12.43	13	×1.14	0.275	1g	1.6	-	
	5670(134)		Front	0	350	0.026	+0.72	n/a(*a)	Plot 3a-5	100	×1.00	12.92	13	×1.02	0.027	1g	1.6	(Patient side)	
11a	5700(140)	6	Right	0	350	0.295	+0.95	n/a(*a)	Plot 3a-6	100	×1.00	12.84	13	×1.04	0.307	1g	1.6	a < n(20HT)	
n(20HT)	5700(140)	MCS0		0	350	0.432	+0.95	n/a(*a)	Plot 3a-7	100	×1.00	12.84	13	×1.04	0.449	1g	1.6	body-worst, W56.	
	5600(120)			0	350	0.289	+0.94	n/a(*a)	Plot 3a-8	100	×1.00	12.64	13	×1.09	0.315	1g	1.6	-	
	5580(116)			0	350	0.283	+1.01	n/a(*a)	Plot 3a-9	100	×1.00	12.72	13	×1.07	0.303	1g	1.6	-	
	5500(100)			0	350	0.237	+0.98	n/a(*a)	Plot 3a-10	100	×1.00	12.48	13	×1.13	0.268	1g	1.6	-	
Step 3b: W56 Band (Head-SAR, by head liquid)																			
n(40HT)	5670(134)	MCS0	Right	0	351	0.289	+0.26	n/a(*a)	Plot 3b-1	100	×1.00	12.92	13	×1.02	0.295	1g	1.6	-	
	5590(118)			0	351	0.254	+0.29	n/a(*a)	Plot 3b-2	100	×1.00	12.54	13	×1.11	0.282	1g	1.6	-	
	5550(110)			0	351	0.220	+0.15	n/a(*a)	Plot 3b-3	100	×1.00	12.36	13	×1.16	0.255	1g	1.6	-	
	5510(102)			0	351	0.210	+0.24	n/a(*a)	Plot 3b-4	100	×1.00	12.43	13	×1.14	0.239	1g	1.6	-	
	5700(140)		Front	0	352	0.373	+0.28	n/a(*a)	Plot 3b-5	100	×1.00	12.84	13	×1.04	0.388	1g	1.6	a > n(20HT)	
n(20HT)	5700(140)	MCS0	Right	0	351	0.407	+0.28	n/a(*a)	Plot 3b-6	100	×1.00	12.84	13	×1.04	0.423	1g	1.6	head-worst, W56.	
	5600(120)			0	352	0.263	+0.28	n/a(*a)	Plot 3b-7	100	×1.00	12.59	13	×1.10	0.289	1g	1.6	-	
	5580(116)			0	352	0.257	+0.22	n/a(*a)	Plot 3b-8	100	×1.00	12.68	13	×1.08	0.278	1g	1.6	-	
	5500(100)			0	352	0.208	+0.28	n/a(*a)	Plot 3b-9	100	×1.00	12.60	13	×1.10	0.229	1g	1.6	-	
	5700(140)			0	350	0.00572	+0.28	n/a(*a)	Plot 3b-10	100	×1.00	12.84	13	×1.04	0.006	1g	1.6	(Patient side)	
Step 3c: W56 Band (Hand-SAR, by body liquid)																			
n(40HT)	5670(134)	MCS0	Back	0	351	0.358	+0.99	n/a(*a)	Plot 3c-1	100	×1.00	12.92	13	×1.02	0.365	10g	4	-	
	5590(118)			0	351	0.459	+0.96	n/a(*a)	Plot 3c-2	100	×1.00	12.54	13	×1.					

7.3 SAR measurement results (5GHz band, SAR for Body/Head/Hand) (cont'd)

[Measured and Reported (Scaled) SAR results] (cont'd)

Mode	Freq. [MHz] (Channel)	Data rate [Mbps]	SAR measurement results						Reported SAR [W/kg]								
			platform setup			SAR [W/kg]			SAR plot # in Appendix 2-2	Duty cycle correction		Output average power correction		SAR Corrected (Scaled) (*b)	SAR type (1g / 10g)	SAR limit	
			Position	Gap [mm]	Bty. ID	Max. value of multi-peak	Meas.	ΔSAR [%]		Duty [%]	Duty scaled	Meas. [dBm]	Max. [dBm]	Tune-up factor			
Step 4a: W58 Band (Body-SAR, by body liquid)																	
n(40HT)	5755(151)	MCS0	Right	0	350	0.260	+0.66	n/a (*a)	Plot 4a-1	100	×1.00	12.15	13	×1.22	0.317	1g	1.6
	5795(159)			0	350	0.407	+0.71	n/a (*a)	Plot 4a-2	100	×1.00	11.58	13	×1.39	0.566	1g	1.6
	5825(165)			0	350	0.495	+0.65	n/a (*a)	Plot 4a-3	100	×1.00	11.76	13	×1.33	0.658	1g	1.6 a < n(20HT)
	5825(165)			0	350	0.498	+0.65	n/a (*a)	Plot 4a-4	100	×1.00	11.74	13	×1.34	0.667	1g	1.6 body-worst, W58,(5GHz)
	5785(157)			0	351	0.320	+0.71	n/a (*a)	Plot 4a-5	100	×1.00	11.79	13	×1.32	0.422	1g	1.6
	5745(149)			0	351	0.414	+0.75	n/a (*a)	Plot 4a-6	100	×1.00	12.14	13	×1.22	0.505	1g	1.6
	5825(165)			Front	0	0.031	+0.65	n/a (*a)	Plot 4a-7	100	×1.00	11.74	13	×1.34	0.042	1g	1.6 (Patient side)
Step 4b: W58 Band (Head-SAR, by head liquid)																	
n(40HT)	5755(151)	MCS0	Right	0	350	0.420	+0.18	n/a (*a)	Plot 4b-1	100	×1.00	12.15	13	×1.22	0.512	1g	1.6
	5795(159)			0	350	0.440	+0.23	n/a (*a)	Plot 4b-2	100	×1.00	11.58	13	×1.39	0.612	1g	1.6
	5825(165)			0	351	0.378	+0.26	n/a (*a)	Plot 4b-3	100	×1.00	11.76	13	×1.33	0.503	1g	1.6 a < n(20HT)
	5825(165)			0	351	0.490	+0.26	n/a (*a)	Plot 4b-4	100	×1.00	11.74	13	×1.34	0.657	1g	1.6 head-worst, W58,(5GHz)
	5785(157)			0	351	0.439	+0.27	n/a (*a)	Plot 4b-5	100	×1.00	11.79	13	×1.32	0.579	1g	1.6
	5745(149)			0	351	0.420	+0.20	n/a (*a)	Plot 4b-6	100	×1.00	12.14	13	×1.22	0.512	1g	1.6
	5825(165)			Front	0	0.020	+0.26	n/a (*a)	Plot 4b-7	100	×1.00	11.74	13	×1.34	0.027	1g	1.6 (Patient side)
Step 4c: W58 Band (Hand-SAR, by body liquid)																	
n(40HT)	5755(151)	MCS0	Back	0	352	0.434	+0.94	n/a (*a)	Plot 4c-1	100	×1.00	12.15	13	×1.22	0.529	10g	4
	5795(159)			0	352	0.381	+1.01	n/a (*a)	Plot 4c-2	100	×1.00	11.58	13	×1.39	0.530	10g	4
	5825(165)			0	350	0.461	+0.96	n/a (*a)	Plot 4c-3	100	×1.00	11.74	13	×1.34	0.618	10g	4 a > n(20HT)
	5825(165)			0	351	0.563	+0.96	n/a (*a)	Plot 4c-4	100	×1.00	11.76	13	×1.33	0.749	10g	4 hand-worst, W58.
	5785(157)			0	350	0.496	+1.03	n/a (*a)	Plot 4c-5	100	×1.00	11.84	13	×1.31	0.650	10g	4
	5745(149)			0	351	0.534	+1.04	n/a (*a)	Plot 4c-6	100	×1.00	12.26	13	×1.19	0.635	10g	4
	5825(165)																

Notes:

- *. Gap: It is the separation distance between the platform outer surface and the bottom outer surface of phantom; Freq.: Frequency; Max.: Maximum; Meas.: Measured value; n/a: not applied; Bty.ID: Battery ID (*, Battery ID No.350, 351 and 352 are same. Refer to Appendix 1 for more detail.)
- *. During test, the platform was operated with full charged battery and was connected a control interface cable to host PC.
- *. Calibration frequency of the SAR measurement probe (and used conversion factors)

Liquid	SAR test frequency [MHz]	Probe calibration frequency [MHz]	Validity	Conversion factor	Uncertainty
Body	5180, 5190, 5220, 5230, 5240, 5260, 5270, 5300, 5310, 5320	5250	within ±110 MHz of calibration frequency	4.30	±13.1 %
	5500, 5510, 5550, 5580, 5590, 5600, 5670, 5700	5600	within ±110 MHz of calibration frequency	3.52	±13.1 %
	5745, 5755, 5785, 5795, 5825	5750	within ±110 MHz of calibration frequency	3.74	±13.1 %
Head	5190, 5270, 5310, 5320	5250	within ±110 MHz of calibration frequency	4.67	±13.1 %
	5500, 5510, 5550, 5580, 5590, 5600, 5670, 5700	5600	within ±110 MHz of calibration frequency	4.17	±13.1 %
	5745, 5755, 5785, 5795, 5825	5800	within ±110 MHz of calibration frequency	4.10	±13.1 %

- *. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.
- a. Since the calculated ΔSAR values of the tested liquid had shown positive correction, the measured SAR was not converted by ΔSAR correction.
 Calculating formula: ΔSAR corrected SAR (W/kg) = (Meas. SAR (W/kg)) × (100 - (ΔSAR(%)) / 100)
- b. Calculating formula: Reported SAR (W/kg) = (Measured SAR (W/kg)) × (Duty scaled) × (Tune-up factor)
 Duty scaled = Duty scaled factor: Duty cycle correction factor for obtained SAR value, Duty scaled factor [-] = 100% / (duty cycle, %)
 Tune-up factor: Power tune-up factor for obtained SAR value, Tune-up factor [-] = 1 / (10 ^ ("Deviation from max, dB" / 10))

(Clause 5: SAR TEST PROCEDURE for 5GHz OFDM band, in KDB248227 D01 (v02r02))

5.1.1 Initial Test Position SAR Test Reduction Procedure

- 1) When the reported SAR of the initial test position is ≤ 0.4 W/kg, further SAR measurement is not required for the other (remaining) test positions in that exposure configuration and 802.11 transmission mode combination within the frequency band or aggregated band. SAR is also not required for that exposure configuration in the subsequent test configuration(s).
- 2) When the reported SAR of the initial test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position using subsequent highest extrapolated or estimated 1-g SAR conditions determined by area scans or next closest/smallest test separation distance and maximum RF coupling test positions based on manufacturer justification, on the highest maximum output power channel, until the reported SAR is ≤ 0.8 W/kg or all required test positions (left, right, touch, tilt or subsequent surfaces and edges) are tested.
- 3) For all positions/configurations tested using the initial test position and subsequent test positions, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is < 1.2 W/kg or all required channels are tested.
- *. Result of hand SAR was judged after "0.4 W/kg" in the document above-mentioned was changed for "1 W/kg", "0.8 W/kg" in the document above-mentioned was changed for "2 W/kg" and "1.2 W/kg" in the document above-mentioned was changed for "3 W/kg".