

FCC 15.247 & RSS-247 2.4 GHz Test Report

for

FUTABA Corporation

**1080 Yabutsuka Chosei-son Chosei-gun,
Chiba-ken, 299-4395 Japan.**

Product Name : Module
Model Name : RA-53
Brand : Futaba
FCC ID : AZPRA53
IC : 2914D-RA53

**Prepared by: : AUDIX Technology Corporation,
EMC Department**



The test report is based on a single evaluation of one sample of the above-mentioned products. It does not imply an assessment of the whole production and does not permit the use of the test lab logo.

TABLE OF CONTENTS

Description	Page
TEST REPORT.....	4
1. REVISION RECORD OF TEST REPORT	5
2. SUMMARY OF TEST RESULTS	6
3. GENERAL INFORMATION	7
3.1. Description of Application	7
3.2. Description of EUT	7
3.3. Description of EUT	8
3.4. Description of Key Components	8
3.5. Antenna Information	8
3.6. EUT Specifications Assessed in Current Report	8
3.7. Test Configuration	9
3.8. Output Power Setting	10
3.9. Tested Supporting System List	10
3.10. Setup Configuration	11
3.11. Operating Condition of EUT	11
3.12. Description of Test Facility	12
3.13. Measurement Uncertainty	13
4. MEASUREMENT EQUIPMENT LIST	15
4.1. Radiated Emission Measurement	15
4.2. RF Conducted Measurement	15
5. CONDUCTED EMISSION	16
6. RADIATED EMISSION	17
6.1. Block Diagram of Test Setup	17
6.2. Radiated Emission Limits	18
6.3. Test Procedure	19
6.4. Measurement Result Explanation	20
6.5. Test Results	20
7. 20dB/OCCUPIED BANDWIDTH	21
7.1. Block Diagram of Test Setup	21
7.2. Specification Limits	21
7.3. Test Procedure	21
7.4. Test Results	21
8. CARRIER FREQUENCY SEPARATION	22
8.1. Block Diagram of Test Setup	22
8.2. Specification Limits	22
8.3. Test Procedure	22
8.4. Test Results	22
9. TIME OF OCCUPANCY	23
9.1. Block Diagram of Test Setup	23
9.2. Specification Limits	23
9.3. Test Procedure	23
9.4. Test Results	23
10. NUMBER OF HOPPING CHANNELS	24
10.1. Block Diagram of Test Setup	24
10.2. Specification Limits	24
10.3. Test Procedure	24



Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

10.4. Test Results	24
11. MAXIMUM PEAK OUTPUT POWER	25
11.1. Block Diagram of Test Setup	25
11.2. Specification Limits.....	25
11.3. Test Procedure	25
11.4. Test Results	25
12. EMISSION LIMITATIONS	26
12.1. Block Diagram of Test Setup	26
12.2. Specification Limits.....	26
12.3. Test Procedure	26
12.4. Test Results	26
13. DEVIATION TO TEST SPECIFICATIONS	27

APPENDIX A TEST DATA AND PLOTS

APPENDIX B TEST PHOTOGRAPHS



Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

TEST REPORT

Applicant : FUTABA Corporation
Manufacturer : FUTABA Corporation
EUT Description
(1) Product : Module
(2) Model : RA-53
(3) Brand : Futaba
(4) Power Supply : DC 3.3V

Applicable Standards:

Title 47 CFR FCC Part 15 Subpart C
RSS-Gen (Issue 5), Amendment 2, February 2021
RSS-247 (Issue 3), August 2023

Audix Technology Corp. tested the equipment mentioned in accordance with the requirements set forth in the above standards. Test results indicate that the equipment tested is capable of demonstrating compliance with the requirements as documented within this report.

Audix Technology Corp. does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens and samples.

Date of Report: 2024. 10. 08

Reviewed by:

(Tina Huang/Deputy Manager)

Approved by:

(Johnny Hsueh/Section Manager)



Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

1. REVISION RECORD OF TEST REPORT

Edition No	Issued Date	Revision Summary	Report Number
0	2024. 10. 08	Original Report	EM-F240432

2. SUMMARY OF TEST RESULTS

Rule		Description	Results
FCC	IC		
15.207	RSS-Gen §8.8	Conducted Emission	N/A, NOTE 3
15.247(d)/15.205	RSS-Gen §8.9 RSS-247 §5.5	Radiated Band Edge and Radiated Spurious Emission	PASS
15.247(a)(1)	RSS-247 §5.1(2)	20dB Bandwidth	PASS
15.247(a)(1)	RSS-247 §5.1(2)	Carrier Frequency Separation	PASS
15.247(a)(1)(iii)	RSS-247 §5.1(4)	Time of Occupancy	PASS
15.247(a)(1)(iii)	RSS-247 §5.1(4)	Number of Hopping Channels	PASS
15.247(b)(1)	RSS-247 §5.1(2)	Maximum Peak Output Power	PASS
15.247(d)	RSS-247 §5.5	Conducted Band Edges and Conducted Spurious Emission	PASS
15.203	---	Antenna Requirement	Compliance
Note: 1. Decision rule according to the limit of the test standard chapter, the test value is lower than the limit specified in the test chapter, and it is judged as Pass. 2. The uncertainties value is not used in determining the result. 3. The EUT only employs DC power for operation, so it is unnecessary to test.			

3. GENERAL INFORMATION

3.1. Description of Application

Applicant	FUTABA Corporation 1080 Yabutsuka Chosei-mura Chosei-gun Chiba-ken, 299-4395 Japan.
Manufacturer	FUTABA Corporation 1080 Yabutsuka Chosei-mura Chosei-gun Chiba-ken, 299-4395 Japan.
Product	Module
Model	RA-53
Brand	Futaba

3.2. Description of EUT

Test Model	RA-53		
Serial Number	N/A		
Software Version	N/A		
Power Rating	DC 3.3V		
RF Features	T-FHSS: 1T1R		
Transmit Type	1T1R		
Test Sample	Sample No.	Test Item	Firmware
	01	RSE, RF Conducted	N/A
Sample Status	Trial sample		
Date of Receipt	2024. 08. 16		
Date of Test	2024. 09. 06 ~ 09		
Interface Ports of EUT	None		
Accessories Supplied	None		

Note: Pursuant ISO 17025:2017 section 7.8.2, Audix Technology Corp. does not assume responsibility for all EUT's information including RF features, transmit type, antenna information...etc are provided by customer.

3.3. Description of EUT

ANSI C63.10:2013

3.4. Description of Key Components

None

3.5. Antenna Information

No.	Antenna Type	Manufacturer	Antenna Part Number	Frequency (MHz)	Max Gain (dBi)
1.	Copper Wire (length 30mm)	TAIWAN MASUTOMI ELECTRONIC CO., LTD.	C-WIRE 0.08/30(0-2)BLACK 30	2400 - 2500	-7.2

3.6. EUT Specifications Assessed in Current Report

Mode	Fundamental Range (MHz)	Channel Number	Modulation	Data Rate (kbps)
T-FHSS	2407.500 to 2467.500	31	Frequency Hopping	128


Mode: T-FHSS							
Channel List							
Channel Number	Frequency (MHz)	Channel Number	Frequency (MHz)	Channel Number	Frequency (MHz)	Channel Number	Frequency (MHz)
01	2407.5	09	2423.5	17	2439.5	25	2455.5
02	2409.5	10	2425.5	18	2441.5	26	2457.5
03	2411.5	11	2427.5	19	2443.5	27	2459.5
04	2413.5	12	2429.5	20	2445.5	28	2461.5
05	2415.5	13	2431.5	21	2447.5	29	2463.5
06	2417.5	14	2433.5	22	2449.5	30	2465.5
07	2419.5	15	2435.5	23	2451.5	31	2467.5
08	2421.5	16	2437.5	24	2453.5		

Note: Test modes are presented at section 3.7.

3.7. Test Configuration

Mode	TX _{on} (ms)	TX _{on+off} (ms)	1/ TX _{on} (kHz)	Duty Cycle (x)	Duty Cycle Factor [10log(1/x)] (dB)
T-FHSS	0.42	3.030	2.381	0.139	1.857

Note: When duty cycle is less than 98% (0.98) that duty cycle factor 10log(1/x) is needed to add in conducted test items measured in average detector.



Item	Test Voltage	Mode	Test Channel
Radiated Test Case	DC 3.3V (Via DC Power Supply)	T-FHSS	1
Radiated Spurious Emission (30MHz~1GHz)			1/31
Radiated Band Edge ^{Note1}			1/16/31
Radiated Spurious Emission ^{Note1} (Above 1GHz)			

Item	Test Voltage	Mode	Test Channel
Conducted Test Case	DC 3.3V (Via DC Power Supply)	T-FHSS	1/16/31
20dB Bandwidth		T-FHSS	1/16/31
Carrier Frequency Separation		T-FHSS	1/16/31
Time of Occupancy		T-FHSS	1/16/31
Number of Hopping Channels		T-FHSS	1/16/31
Maximum Peak Output Power		T-FHSS	1/16/31
Band Edges		T-FHSS	1/31
Spurious Emission		T-FHSS	1/16/31

Note 1: ☒ Mobile Device ☐ Portable Device
and 3 axis were assessed. The worst scenario for Radiated Spurious Emission as follow: ☒ Lie ☐ Side ☐ Stand

3.8. Output Power Setting

Centre Frequency (MHz)	Power Setting
2407.5	Default
2437.5	Default
2467.5	Default

3.9. Tested Supporting System List

3.9.1. Support Peripheral Unit

No.	Product	Brand	Model No.	Serial No.	Approval
1.	DC Power Supply	TOP WARD	3303A	N/A	N/A
2.	Notebook PC	ASUS	X1403Z	R1NOLP02A95005F	Contains FCC ID: RAS-MT-7921
3.	Test Jig	O.S. ENGINES	U2S-2	N/A	N/A

3.9.2. Cable Lists

No.	Cable Description Of The Above Support Units
1.	Cable: Unshielded, Detectable, 0.1m DC Power Cord: Unshielded, Detachable, 2.0m AC Power Cord: Unshielded, Undetectable, 1.8m
2.	Adapter: ASUS, M/N A19-090P2A DC Cord : Shielded, Undetachable, 1.5m, Bonded a ferrite core AC Power Cord : Unshielded, Detachable, 0.8m
3.	Cable: Unshielded, Detectable, 0.5m

3.10. Setup Configuration

3.10.1. EUT Configuration for Radiated Emission



3.10.2. EUT Configuration for RF Conducted Test Items



3.11. Operating Condition of EUT

Test program “Futaba Term” is used for enabling EUT RF function under continue transmitting and choosing channel.

3.12. Description of Test Facility

Name of Test Firm	Audix Technology Corporation / EMC Department No. 491, Zhongfu Rd., Linkou Dist., New Taipei City 244, Taiwan Tel: +886-2-26092133 Fax: +886-2-26099303 Website : www.audixtech.com Contact e-mail: attemc_report@audixtech.com
Accreditations	The laboratory is accredited by following organizations under ISO/IEC 17025:2017 (1) NVLAP(USA) NVLAP Lab Code 200077-0 (2) TAF(Taiwan) No. 1724
Test Facilities	FCC OET Designation Number under APEC MRA by NCC is : TW1724 ISED CAB Identifier Number under APEC TEL MRA by NCC is TW1724 (1) No.1 3m Semi Anechoic Chamber

3.13.Measurement Uncertainty

The measurement uncertainty levels have been estimated as specified in ETSI TR 100 028-2001

Test Items/Facilities			Frequency Range	Uncertainty
Conduction Test	☐	No. 7 Shielded Room	9kHz-150kHz	±3.6dB
			150kHz-30MHz	±3.3dB
	☐	No. 8 Shielded Room	9kHz-150kHz	±3.7dB
			150kHz-30MHz	±3.4dB
Radiation Test	☒	No.1 3m Semi Anechoic Chamber	30MHz-200MHz, 3m, Horizontal	±3.8dB
			200MHz-1000MHz, 3m, Horizontal	±4.2dB
			30MHz-200MHz, 3m, Vertical	±4.7dB
			200MHz-1000MHz, 3m, Vertical	±4.8dB
			1GHz-6GHz, 3m	±4.8dB
			6GHz-18GHz, 3m	±4.3dB
	☐	No.3 3m Semi Anechoic Chamber	30MHz-200MHz, 3m, Horizontal	±3.9dB
			200MHz-1000MHz, 3m, Horizontal	±4.2dB
			30MHz-200MHz, 3m, Vertical	±4.7dB
			200MHz-1000MHz, 3m, Vertical	±4.8dB
			1GHz-6GHz, 3m	±4.5dB
			6GHz-18GHz, 3m	±4.0dB
	☐	No.4 3m Semi Anechoic Chamber	30MHz-200MHz, 3m, Horizontal	±3.9dB
			200MHz-1000MHz, 3m, Horizontal	±4.3dB
			30MHz-200MHz, 3m, Vertical	±4.8dB
			200MHz-1000MHz, 3m, Vertical	±4.9dB
			1GHz-6GHz, 3m	±4.2dB
			6GHz-18GHz, 3m	±3.8dB
	☐	No.5 3m Semi Anechoic Chamber	30MHz-200MHz, 3m, Horizontal	±3.9dB
			200MHz-1000MHz, 3m, Horizontal	±4.1dB
			30MHz-200MHz, 3m, Vertical	±4.8dB
			200MHz-1000MHz, 3m, Vertical	±4.7dB
			1GHz-6GHz, 3m	±4.8dB
			6GHz-18GHz, 3m	±4.6dB
	Radiated emissions (18GHz-40GHz)		18GHz-40GHz, 3m	±3.4dB

Remark : Uncertainty = $ku_c(y)$

Test Item	Uncertainty
20dB Bandwidth	$\pm 0.2\text{kHz}$
6dB Bandwidth	$\pm 0.05\text{kHz}$
99% Occupied Bandwidth	$\pm 0.38\%$
Carrier Frequency Separation	$\pm 0.2\text{kHz}$
Time of Occupancy	$\pm 0.03\text{sec}$
Maximum peak Output power	$\pm 0.52\text{dB}$
Conducted Emission Limitations	$\pm 0.13\text{dB}$
Power spectral density	$\pm 0.13\text{dB}$

4. MEASUREMENT EQUIPMENT LIST

4.1. Radiated Emission Measurement

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9010A-526	MY53400071	2024.08.12	1 Year
2.	Spectrum Analyzer	Keysight	N9010B-544	MY55460198	2024.03.21	1 Year
3.	Test Receiver	R&S	ESCS30	100338	2024.06.18	1 Year
4.	Amplifier	HP	8447D	2944A06305	2023.12.20	1 Year
5.	Microwave Preamplifier	HP	8449B	3008A01284	2024.06.11	1 Year
6.	Microwave Amplifier	Keysight	83051A	MY56480113	2023.09.11	1 Year
7.	Loop Antenna	ROHDE & SCHWARZ	HFH2-Z2	100315	2024.02.27	1 Year
8.	Bilog Antenna	TESEQ	CBL6112D	33821	2024.02.17	1 Year
9.	Double-Ridged Waveguide Horn	EMCO	3115	9112-3775	2024.04.30	1 Year
10.	Horn Antenna	COM-POWER	AH-840	101092	2024.01.12	1 Year
11.	2.4GHz Notch Filter	K&L	7NSL10-2441.5/E130.5-O/O	2	2024.04.11	1 Year
12.	High-Pass Filter	Microwave	H3G018G1	484796	2024.04.11	1 Year
13.	Coaxial Cable	MIYAZAKI	5D2W	RE-11	2024.01.05	1 Year
14.	Coaxial Cable	HUBER+SUHNER	SUCOFLEX 106	RE-14	2024.01.05	1 Year
15.	Coaxial Cable	HUBER+SUHNER	SUCOFLEX 102	RE-30	2024.08.20	1 Year
16.	Digital Thermo-Hygro Meter	iMax	HTC-1	No.1 3m A/C	2024.04.11	1 Year
17.	Test Software	Audix	e3	V9 18621a	N.C.R.	N.C.R.

4.2. RF Conducted Measurement

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Spectrum Analyzer	Keysight	N9010B	MY59071380	2024.03.29	1 Year
2.	Digital Thermo-Hygro Meter	iMax	HTC-1	RF-03	2024.04.11	1 Year



5. CONDUCTED EMISSION

【The EUT only employs uses DC power for operation, no conductive emission limits are required according to FCC Part 15 Section §15.207 and RSS-Gen §8.8】


6. RADIATED EMISSION

6.1. Block Diagram of Test Setup


6.1.1. Block Diagram of EUT

Indicated as section 3.10


6.1.2. Setup Diagram for 9kHz-30MHz



6.1.3. Setup Diagram for 30-1000MHz



6.1.4. Setup Diagram for above 1GHz



6.2. Radiated Emission Limits

In any 100kHz bandwidth outside the frequency band, the radio frequency power produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level. In addition, radiated emissions which fall in restricted bands, as defined in Section 15.205/ RSS-Gen Section 8.10 table 6, must also comply with the radiated emission limits specified as below.

Frequency (MHz)	Distance(m)	Limits	
		dBμV/m	μV/m
0.009 - 0.490	300	67.6-20 log f(kHz)	2400/f kHz
0.490 - 1.705	30	87.6-20 log f(kHz)	24000/f kHz
1.705 - 30	30	29.5	30
30 - 88	3	40.0	100
88- 216	3	43.5	150
216- 960	3	46.0	200
Above 960	3	54.0	500
Above 1000	3	74.0 dBμV/m (Peak) 54.0 dBμV/m (Average)	

Remark : (1) $\text{dB}\mu\text{V/m} = 20 \log (\mu\text{V/m})$

- (2) The tighter limit applies to the edge between two frequency bands.
- (3) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
- (4) Fundamental and emission fall within operation band are exempted from this section.
- (5) Pursuant to ANSI C63.10: 6.6.4.3, if the maximized peak measured value complies with the average limit, then it is unnecessary to perform an average measurement.

6.3. Test Procedure

Frequency Range 9kHz~30MHz:

The EUT setup on the turntable which has 0.8 m height to the ground. The turn table rotated 360 degrees and antenna fixed to 1 m to find the maximum emission level. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10-2013 regulation.

- (1) RBW = 9kHz with peak and average detector.
- (2) Detector: average and peak (9kHz-490kHz)
Q.P. (490kHz-30MHz)

Frequency Range 30MHz ~ 25GHz:

The EUT setup on the turn table which has 80cm (for 30-1000MHz) and 1.5m (for above 1GHz) height to the ground. The turn table rotated 360 degrees and antenna varied from 1 m to 4 m to find the maximum emission level. Both horizontal and vertical polarization are required. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10-2013 regulation.

Frequency below 1GHz:

Spectrum Analyzer is used for pre-testing with following setting:

- (1) RBW = 120KHz
- (2) VBW $\geq 3 \times$ RBW.
- (3) Detector = Peak.
- (4) Sweep time = auto.
- (5) Trace mode = max hold.
- (6) Allow sweeps to continue until the trace stabilizes.

Note 1: When peak-detected value is lower than limit that the measurement using the Q.P. detector is not required, otherwise using Q.P. for final measurement.

Note 2: When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds.

Frequency above 1GHz to 10th harmonic(up to 25 GHz):

Peak Detector:

- (1) RBW = 1MHz
- (2) VBW $\geq 3 \times$ RBW.
- (3) Detector = Peak.
- (4) Sweep time = auto.
- (5) Trace mode = max hold.
- (6) Allow sweeps to continue until the trace stabilizes.

Note: When peak-detected value is lower than limit that the measurement using the average detector is not required, otherwise using average detector for final measurement.

Average Detector:**■ Option 1**

(1) RBW = 1MHz

(2) VBW $\geq 1/T$. (Duty Cycle < 98%)

(3) VBW = 10Hz (Duty Cycle $\geq 98\%$, when duty cycle presented in section 3.7)

Modulation Type	VBW Setting (VBW $\geq 1/T$)
T-FHSS	3kHz

(4) Detector = Peak.

(5) Sweep time = auto.

(6) Trace mode = max hold.

(7) Allow sweeps to continue until the trace stabilizes.

□ Option 2:

Average Emission Level = Peak Emission Level + D.C.C.F.

6.4. Measurement Result Explanation

■ Peak Emission Level (dB μ V/m) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamp Gain (dB) + Reading (dB μ V).

■ Average Emission Level (dB μ V/m) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamp Gain (dB) + Reading (dB μ V).

□ Average Emission Level (dB μ V/m) = Peak Emission Level (dB μ V/m) + DCCF (dB)
Duty Cycle Correction Factor (DCCF) (dB) = $20\log(TX_{on}/TX_{on+off})$ presented in section 3.7.


□ ERP (dBm) = Peak Emission Level (dB μ V/m) - 95.2dB - 2.14dB

6.5. Test Results

Please refer to Appendix A.

7. 20dB/OCCUPIED BANDWIDTH

7.1. Block Diagram of Test Setup



7.2. Specification Limits

Alternatively, frequency hopping systems operating in the 2400-2483.5MHz band may have hopping channel carrier frequencies that are separated by 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.

7.3. Test Procedure

Following measurement procedure is reference to ANSI C63.10:2013:

For 20dB Bandwidth

- (1) Set Span range 2~5 times the OBW
- (2) Set $VBW \geq 3 \times RBW$.
- (3) Detector = Peak.
- (4) Trace mode = Max hold.
- (5) Sweep = Auto couple.
- (6) Allow the trace to stabilize.
- (7) Setting channel bandwidth function x dB to -20 dB to record the final bandwidth.

For 99% Occupied Bandwidth


- (8) Set Span range 1.5~5 times the OBW
- (9) Set RBW close to 1% to 5% of OBW.
- (10) Set $VBW \geq 3 \times RBW$.
- (11) Detector = Peak.
- (12) Trace mode = Max hold
- (13) Sweep = Auto couple.
- (14) Allow the trace to stabilize.

7.4. Test Results

Please refer to Appendix A

8. CARRIER FREQUENCY SEPARATION

8.1. Block Diagram of Test Setup



8.2. Specification Limits

Alternatively, frequency hopping systems operating in the 2400-2483.5MHz band may have hopping channel carrier frequencies that are separated by 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output no greater than 125mW.

8.3. Test Procedure

Following measurement procedure is reference to ANSI C63.10:2013:


- (1) Span = Wide enough to capture the peaks of two adjacent channels
- (2) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- (3) $VBW \geq RBW$
- (4) Sweep = Auto
- (5) Detector function = Peak
- (6) Trace = Max hold
- (7) Allow the trace to stabilize.

8.4. Test Results

Please refer to Appendix A

9. TIME OF OCCUPANCY

9.1. Block Diagram of Test Setup



9.2. Specification Limits

Frequency hopping systems in the 2400-2483.5MHz shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by number of hopping channels employed.

9.3. Test Procedure

Following measurement procedure is reference to ANSI C63.10:2013:


- (1) Span: Zero span, centered on a hopping channel.
- (2) RBW shall be $\leq$ channel spacing and where possible RBW should be set $\gg 1/T$, where T is the expected dwell time per channel.
- (3) Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
- (4) Detector function = Peak
- (5) Trace = Max hold

9.4. Test Results

Please refer to Appendix A

10. NUMBER OF HOPPING CHANNELS

10.1. Block Diagram of Test Setup



10.2. Specification Limits

Frequency hopping systems which use fewer than 20 hopping frequencies may employ intelligent hopping techniques to avoid interference to other transmissions. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 non-overlapping channels.

10.3. Test Procedure

Following measurement procedure is reference to ANSI C63.10:2013:


- (1) Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- (2) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- (3) VBW $\geq$ RBW
- (4) Sweep = Auto
- (5) Detector function = Peak
- (6) Trace = m=Max hold
- (7) Allow the trace to stabilize.

10.4. Test Results

Please refer to Appendix A

11. MAXIMUM PEAK OUTPUT POWER

11.1. Block Diagram of Test Setup



11.2. Specification Limits

The Limits of maximum Peak Output Power for frequency hopping systems in 2400-2483.5MHz is: 0.125Watt. (21dBm)

11.3. Test Procedure

Following measurement procedure is reference to ANSI C63.10:2013:


- (a) Use the following spectrum analyzer settings
 - (1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
 - (2) RBW > 20 dB bandwidth of the emission being measured.
 - (3) VBW $\geq$ RBW
 - (4) Sweep: Auto
 - (5) Detector function: Peak
 - (6) Trace: Max hold
- (b) Allow trace to stabilize.
- (c) Use the marker-to-peak function to set the marker to the peak of the emission.

11.4. Test Results

Please refer to Appendix A

12. EMISSION LIMITATIONS

12.1. Block Diagram of Test Setup



12.2. Specification Limits

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, that the required attenuation shall be 30 dB instead of 20 dB.

Attenuation below the general limits specified in Section 15.209(a)/ RSS-Gen Section 8.9 table 4 is not required. In addition, radiated emissions which fall in restricted bands, as defined in Section 15.205(a)/RSS-Gen Section 8.10 table 6, must also comply with the radiated emission limits specified in Section 15.209(a)/RSS-Gen Section 8.9 table 4. (See Section 15.205(c)).

12.3. Test Procedure

Following measurement procedure is reference to ANSI C63.10:2013:

- (1) Set span wide enough to capture the peak level of the in-band emission and all spurious emissions; up to 10th harmonic.
- (2) RBW = 100 kHz
- (3) VBW $\geq$ RBW
- (4) Sweep = Auto
- (5) Detector function = Peak
- (6) Trace = Max hold

12.4. Test Results

Please refer to Appendix A



Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

13.DEVIATION TO TEST SPECIFICATIONS

【NONE】



Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

APPENDIX A

TEST DATA AND PLOTS

(Model: RA-53)

TABLE OF CONTENTS

A.1	RADIATED EMISSION	2
A.1.1	Emissions within Restricted Frequency Bands.....	2
A.1.2	Emissions outside the frequency band:.....	7
A.1.3	Emissions in Non-restricted Frequency Bands:.....	8
A.2	20dB/OCCUPIED BANDWIDTH	9
A.2.1	Emission Bandwidth Result.....	9
A.2.2	Measurement Plots	9
A.3	CARRIER FREQUENCY SEPARATION.....	10
A.4	TIME OF OCCUPANCY.....	11
A.4.1	Time of Occupancy.....	11
A.4.2	Measurement Plots	12
A.5	NUMBER OF HOPPING CHANNELS	13
A.6	MAXIMUM PEAK OUTPUT POWER.....	14
A.6.1	Maximum Peak Output Power.....	14
A.6.2	Measurement Plots	14
A.7	EMISSION LIMITATIONS MEASUREMENT	15
A.7.1	Band Edge	15
A.7.2	Spurious Emission	16

A.1 RADIATED EMISSION

Test Date	2024/09/09	Temp./Hum.	23°C/57%
Test Voltage	DC 3.3V (Via DC Power Supply)	Tested By	Hua Wu

A.1.1 Emissions within Restricted Frequency Bands

A.2.1.1 Frequency 9kHz~30MHz

The emissions (9kHz~30MHz) not reported for there is no emission be found.

A.2.1.2 Frequency Below 1 GHz

Mode	T-FHSS	Frequency	TX 2407.500MHz
------	--------	-----------	----------------

Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Gain (dB)	Read Level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
32.000	23.14	1.46	26.48	30.71	28.82	40.00	11.18	Peak
127.000	17.60	2.94	26.12	31.09	25.51	43.50	17.99	Peak
303.500	18.69	4.74	25.64	30.89	28.68	46.00	17.32	Peak
434.500	21.75	6.24	26.70	31.89	33.18	46.00	12.82	Peak
549.000	23.47	6.93	27.27	32.55	35.68	46.00	10.32	Peak
575.000	23.77	7.02	27.34	33.35	36.81	46.00	9.19	Peak


Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Gain (dB)	Read Level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
30.000	24.02	1.41	26.49	30.55	29.49	40.00	10.51	Peak
121.500	17.85	2.87	26.15	30.68	25.25	43.50	18.25	Peak
286.000	18.41	4.58	25.63	31.68	29.03	46.00	16.97	Peak
455.000	22.08	6.41	26.84	33.90	35.55	46.00	10.45	Peak
592.000	23.98	7.07	27.38	33.23	36.90	46.00	9.10	Peak
707.500	24.56	7.68	27.42	34.39	39.21	46.00	6.79	Peak

A.2.1.3 Frequency Above 1 GHz to 10th harmonics


Band Edge:

Mode	T-FHSS	Frequency	TX 2407.500MHz
------	--------	-----------	----------------



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Gain (dB)	Read Level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2389.300	28.14	6.03	39.88	53.99	48.29	74.00	25.71	Peak
2390.000	28.14	6.03	39.88	53.80	48.10	74.00	25.90	Peak
@ 2407.400	28.13	6.06	39.88	94.45	88.77	---	---	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Gain (dB)	Read Level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2372.500	28.21	6.01	39.88	42.06	36.40	54.00	17.60	Average
2390.000	28.14	6.03	39.88	41.52	35.81	54.00	18.19	Average
@ 2407.600	28.13	6.06	39.88	94.19	88.51	---	---	Average


Remark: The “@” means fundamental frequency, it is ignored in this section.

Mode	T-FHSS	Frequency	TX 2407.500MHz
------	--------	-----------	----------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Gain (dB)	Read Level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2375.600	28.20	6.01	39.88	52.63	46.97	74.00	27.03	Peak
2390.000	28.14	6.03	39.88	50.28	44.58	74.00	29.42	Peak
@ 2407.500	28.13	6.06	39.88	93.31	87.63	---	---	Peak




Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Gain (dB)	Read Level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2363.600	28.25	6.00	39.88	42.47	36.83	54.00	17.17	Average
2390.000	28.14	6.03	39.88	41.41	35.70	54.00	18.30	Average
@ 2407.500	28.13	6.06	39.88	92.98	87.30	---	---	Average


Remark: The “@” means fundamental frequency, it is ignored in this section.

Mode	T-FHSS	Frequency	TX 2467.500MHz
------	--------	-----------	----------------



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Gain (dB)	Read Level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2467.600	28.34	6.14	39.87	93.26	87.87	---	---	Peak
2483.500	28.37	6.17	39.87	51.46	46.13	74.00	27.87	Peak
2490.250	28.38	6.18	39.87	53.76	48.45	74.00	25.55	Peak




Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Gain (dB)	Read Level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2467.450	28.34	6.14	39.87	92.89	87.50	---	---	Average
2483.500	28.37	6.17	39.87	41.48	36.14	54.00	17.86	Average
2523.600	28.54	6.22	39.88	42.44	37.33	54.00	16.67	Average


Remark: The “@” means fundamental frequency, it is ignored in this section.

Mode	T-FHSS	Frequency	TX 2467.5MHz
------	--------	-----------	--------------



Antenna at Vertical Polarization

	Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Gain (dB)	Read Level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@	2467.600	28.34	6.14	39.87	93.51	88.12	---	---	Peak
	2483.500	28.37	6.17	39.87	52.12	46.79	74.00	27.21	Peak
	2529.350	28.58	6.22	39.88	55.72	50.65	74.00	23.35	Peak



Antenna at Vertical Polarization

	Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Gain (dB)	Read Level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@	2467.550	28.34	6.14	39.87	93.41	88.01	---	---	Average
	2483.500	28.37	6.17	39.87	41.64	36.30	54.00	17.70	Average
	2525.250	28.55	6.22	39.88	42.45	37.34	54.00	16.66	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.

A.1.2 Emissions outside the frequency band:

The emissions (up to 25GHz) not reported for there is no emission be found.

Mode	T-FHSS	Frequency	TX 2407.500MHz
------	--------	-----------	----------------

Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Gain (dB)	Reading level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4815.000	32.96	8.33	39.37	46.61	48.54	54.00	5.46	Peak

Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Gain (dB)	Reading level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4815.000	32.96	8.33	39.37	43.06	44.99	54.00	9.01	Peak

Mode	T-FHSS	Frequency	TX 2437.500MHz
------	--------	-----------	----------------

Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Gain (dB)	Reading level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4875.000	33.15	8.37	39.34	46.78	48.96	54.00	5.04	Peak

Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Gain (dB)	Reading level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4875.000	33.15	8.37	39.34	45.67	47.85	54.00	6.15	Peak

Mode	T-FHSS	Frequency	TX 2467.500MHz
------	--------	-----------	----------------

Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Gain (dB)	Reading level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4935.000	33.20	8.41	39.31	46.56	48.86	54.00	5.14	Peak

Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Gain (dB)	Reading level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4935.000	33.20	8.41	39.31	46.96	49.26	54.00	4.74	Peak

A.1.3 Emissions in Non-restricted Frequency Bands:

All emission levels below the FCC 15.209(a)/RSS-Gen Section 8.9 table 4 general radiated emissions limits is not required.

A.2 20dB/OCCUPIED BANDWIDTH


Test Date	2024/09/06	Temp./Hum.	23°C/58%
Cable Loss	0.5 dB	Tested By	Hua Wu
Test Voltage	DC 3.3V (Via DC Power Supply)		

A.2.1 Emission Bandwidth Result

Mode	Centre Frequency (MHz)	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit 2/3 (20dB Bandwidth)
T-FHSS	2407.500	0.78	0.85	0.520
	2437.500	0.64	0.82	0.427
	2467.500	0.88	0.86	0.587


Remark: The maximum two-thirds of the 20dB bandwidth shall be at maximum 0.584MHz.

A.2.2 Measurement Plots



A.3 CARRIER FREQUENCY SEPARATION

Test Date	2024/09/06	Temp./Hum.	23°C/58%
Cable Loss	0.5 dB	Tested By	Hua Wu
Test Voltage	DC 3.3V (Via DC Power Supply)		



A.4 TIME OF OCCUPANCY

Test Date	2024/09/06	Temp./Hum.	23°C/58%
Cable Loss	0.5 dB	Tested By	Hua Wu
Test Voltage	DC 3.3V (Via DC Power Supply)		

A.4.1 Time of Occupancy

Mode	Centre Frequency (MHz)	Each second appearance transmission	Time of Occupancy (ms)	Maximum accumulated Time of Occupancy (ms)	Limit (ms)
T-FHSS	2407.50	10	0.420	52.0800	<400
	2437.50	10	0.420	52.0800	<400
	2467.50	10	0.420	52.0800	<400

Observation Period:

31 channels* 0.4 seconds= 12.4 seconds

Centre Frequency: 2407.50MHz

For each second of 10 transmission appearance,the longest time of occupancy is
10 channels* 12.4 /1* 0.4200 ms= 52.0800 ms (<400ms)

Centre Frequency: 2437.50MHz

For each second of 10 transmission appearance,the longest time of occupancy is
10 channels* 12.4 /1* 0.4200 ms= 52.0800 ms (<400ms)

Centre Frequency: 2467.50MHz

For each second of 10 transmission appearance,the longest time of occupancy is
10 channels* 12.4 /1* 0.4200 ms= 52.0800 ms (<400ms)

A.4.2 Measurement Plots




Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

A.5 NUMBER OF HOPPING CHANNELS

Test Date	2024/09/06	Temp./Hum.	23°C/58%
Cable Loss	0.5 dB	Tested By	Hua Wu
Test Voltage	DC 3.3V (Via DC Power Supply)		




A.6 MAXIMUM PEAK OUTPUT POWER

Test Date	2024/09/06	Temp./Hum.	23°C/58%
Cable Loss	0.5 dB	Tested By	Hua Wu
Test Voltage	DC 3.3V (Via DC Power Supply)		

A.6.1 Maximum Peak Output Power

Mode	Centre Frequency (MHz)	Peak Output Power		Limit
		dBm	W	
T-FHSS	2407.500	-3.14	0.000485	21dBm (0.125W)
	2437.500	-3.28	0.000470	
	2467.500	-3.27	0.000471	


A.6.2 Measurement Plots



A.7 EMISSION LIMITATIONS MEASUREMENT

A.7.1 Band Edge

Test Date	2024/09/06	Temp./Hum.	23°C/58%
Cable Loss	0.5 dB	Tested By	Hua Wu
Test Voltage	DC 3.3V (Via DC Power Supply)		




Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

A.7.2 Spurious Emission

Test Date	2024/09/06	Temp./Hum.	23°C/58%
Cable Loss	0.5 dB	Tested By	Hua Wu
Test Voltage	DC 3.3V (Via DC Power Supply)		



Note: All results have been included cable loss.



Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City 244, Taiwan

APPENDIX B

Tel: +886 2 26099301
Fax: +886 2 26099303

APPENDIX B

TEST PHOTOGRAPHS

(Model: RA-53)