



FCC TEST REPORT

according to

FCC Rules and Regulations Part 15 Subpart C

Applicant	: Kibano AS
Address	: Grønland 58 Papirbredden, 3045 Drammen, Norway
Equipment	: R1 digireader
Model No.	: R1
FCC ID	: AZVKAS-R1

- The test result refers exclusively to the test presented test model / sample.,
- Without written approval of **Cerpass Technology Corp.** the test report shall not be reproduced except in full.
- The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



Contents

1. Report of Measurements and Examinations.....	6
1.1 List of Measurements and Examinations	6
2. Test Configuration of Equipment under Test.....	7
2.1 Feature of Equipment under Test.....	7
2.2 Test Mode & Test Software	8
2.3 Description of Test System.....	8
2.4 General Information of Test.....	9
2.5 Measurement Uncertainty	9
3. Antenna Requirements.....	10
3.1 Standard Applicable	10
3.2 Antenna Construction and Directional Gain.....	10
4. Test of Conducted Emission.....	11
4.1 Test Limit.....	11
4.2 Test Procedures.....	11
4.3 Typical Test Setup	12
4.4 Measurement equipment	12
4.5 Test Result and Data.....	13
4.6 Test Photographs	19
5. Test of Radiated Emission	20
5.1 Test Limit.....	20
5.2 Test Procedures.....	20
5.3 Typical Test Setup	21
5.4 Measurement equipment	21
5.5 Test Result and Data.....	22
5.6 Test Photographs (30MHz ~ 1GHz)	52
5.7 Test Photographs (1GHz ~ 25GHz)	53
6. 20dB Bandwidth Measurement Data.....	54
6.1 Test Limit	54
6.2 Test Procedures	54
6.3 Test Setup Layout	54
6.4 Measurement equipment	54
6.5 Test Result and Data.....	55
7. Frequencies Separation	61
7.1 Test Limit	61
7.2 Test Procedures	61
7.3 Test Setup Layout	61
7.4 Measurement equipment	61
7.5 Test Result and Data.....	62
8. Dwell Time on each channel	68
8.1 Test Limit	68
8.2 Test Procedures	68
8.3 Test Setup Layout	68
8.4 Measurement equipment	68
8.5 Test Result and Data.....	68



9. Number of Hopping Channels	78
9.1 Test Limit	78
9.2 Test Procedures	78
9.3 Test Setup Layout	78
9.4 Measurement equipment	78
9.5 Test Result and Data	78
10. Maximum Peak Output Power	81
10.1 Test Limit	81
10.2 Test Procedures	81
10.3 Test Setup Layout	81
10.4 Measurement equipment	81
10.5 Test Result and Data	81
11. Band Edges Measurement	87
11.1 Test Limit	87
11.2 Test Procedure :	87
11.3 Test Setup Layout	87
11.4 List of Measuring Equipment Used	87
11.5 Test Result and Data	87
11.6 Restrict band emission Measurement Data	94
12. Restricted Bands of Operation	97
12.1 Labeling Requirement	97
Appendix A. Photographs of EUT	A1 ~ A9



History of this test report

■ ORIGINAL.

□ Additional attachment as following record:

Attachment No.	Issue Date	Description
TEFB1109153	Mar. 09, 2012	Original.



CERTIFICATE OF COMPLIANCE

according to

FCC Rules and Regulations Part 15 Subpart C

Applicant	: Kibano AS
Address	: Grønland 58 Papirbredden, 3045 Drammen, Norway
Equipment	: R1 digireader
Model No.	: R1
FCC ID	: AZVKAS-R1

I HEREBY CERTIFY THAT :

The measurements shown in this test report were made in accordance with the procedures given in **ANSI C63.4** The equipment was ***passed*** the test performed according to **FCC Rules and Regulations Part 15 Subpart C (2010)**.

The test was carried out on Oct. 20, 2011 at ***CerpPASS Technology Corp.***

Signature

Hill Chen
EMC/RF B.U. Assistant Manager



1. Report of Measurements and Examinations

1.1 List of Measurements and Examinations

FCC Rule	Description of Test	Result
15.203	Antenna Requirement	Pass
15.207	Conducted Emission	Pass
15.209	Radiated Emission	Pass
15.247(a)(1)	Channel Carrier Frequencies Separation	Pass
15.247(a)(1)	20dB Bandwidth Measurement	Pass
15.247(a)(1)	Dwell Time	Pass
15.247(b)	Number of Hopping Channels	Pass
15.247(b)	Peak Output Power Measurement Data	Pass
15.247(d)	Band Edges Measurement Data	Pass



2. Test Configuration of Equipment under Test

2.1 Feature of Equipment under Test

CPU	Marvell PXA 166e, 800 MHz
Memory	256MB SLC NAND FLASH for boot code 256MB LP-DDR1-200 for working memory
Buttons & Navigation Controls	6" Capacitive Single Touch screen Home, Menu, Back, Power, Reset, Volume up/down keys, < , > G-sensor
Display	6" e-INK EPD, 800 x 600, 16 Level Grey Scale
Battery & Adapter	3.7V, 1,530 mAh, rechargeable Lithium-Polymer AC-DC power adapter, 5V/1A, USB Type-B connector
Connectivity	USB 2.0 device and power connection SD memory card slot X1 Menca Card slot X1 WiFi 802.11 b/g/n Bluetooth 2.1+EDR FM Transmitter: SILICON LABS Si4710
Audio	Speaker Internal 1.0W x1 3.5mm headphone jack X1
Dimension	170x118x11.7mm
Weight	205 +- 5 gm
Operating System	Android 2.1
Content formats	eBook: ePub, PDF Music: MP3, AAC, OGG, WAV, WMA Audio Book: MP3, WMA
3rd Party Integration Required	Danish, Finnish, Norwegian, Swedish, Germany, English software keyboard apk. files
Localization for build-in applications	English, German, Danish, Finish, Norwegian, Swedish, French, Spanish



2.2 Test Mode & Test Software

- a. During testing, the interface cables and equipment positions were varied according to ANSI C63.4
- b. The complete test system included Notebook and EUT for EMC test.
- c. An executive program, "Hyper Terminal" under WIN XP was executed to transmit and receive data to the remote workstation through Bluetooth.
- d. The following test mode was performed for conduction and radiation test:
 - GFSK: CH 00: 2402MHz, CH 39: 2441MHz, CH 78: 2480MHz.
 - $\pi/4$ -DQPSK: CH 00: 2402MHz, CH 39: 2441MHz, CH 78: 2480MHz.
 - 8DPSK: CH 00: 2402MHz, CH 39: 2441MHz, CH 78: 2480MHz.

2.3 Description of Test System

Device	Manufacturer	Model No.	Description
Mouse	Logitech	OF-2854	Data Cable, USB Shielding 1.85 m



2.4 General Information of Test

Test Site :	Cerpass Technology Corp. 2F-11, No. 3, Yuan Qu St., (Nankang Software Park), Taipei, Taiwan 115, R.O.C.
Test Site Location (OATS2-SD) :	No.68-1, Shihbachongsi, Shihding Township, Taipei City 223, Taiwan, R.O.C.
FCC Registration Number :	TW1049, TW1061, 390316, 488071
IC Registration Number :	4934B-1, 4934D-1
VCCI Registration Number :	T-1173 for Telecommunication Test C-4139 for Conducted emission test R-3428 for Radiated emission test G-97 for Radiated emission test above 1GHz
Test in Compliance with:	ANSI C63.4-2009 FCC Part 15 Subpart C
Frequency Range Investigated:	Conducted: from 150kHz to 30 MHz Radiation: from 30 MHz to 24800 MHz
Test Distance:	The test distance of radiated emission from antenna to EUT is 3 M.

2.5 Measurement Uncertainty

Measurement Item	Measurement Frequency	Polarization	Uncertainty
Conducted Emission	9 kHz ~ 30 MHz	LINE/NEUTRAL	3.25 dB
Radiated Emission	30 MHz ~ 1GHz	Vertical	3.93 dB
		Horizontal	3.93 dB
6 dB Bandwidth	---	---	7500 Hz
Maximum Peak Output Power	---	---	1.4 dB
100kHz Bandwidth of Frequency Band Edges	---	---	2.2 dB
Power Spectral Density	---	---	2.2 dB



3. Antenna Requirements

3.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

3.2 Antenna Construction and Directional Gain

Antenna type: PCB Antenna

Antenna Gain: 2.49 dBi



4. Test of Conducted Emission

4.1 Test Limit

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz on the 120 VAC power and return leads of the EUT according to the methods defined in ANSI C63.4-2009 Section 3.1. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane as shown in section 2.2. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.

Frequency (MHz)	Quasi Peak (dB μ V)	Average (dB μ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50


*Decreases with the logarithm of the frequency.

4.2 Test Procedures

- The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- Connect EUT to the power mains through a line impedance stabilization network (LISN).
- All the support units are connecting to the other LISN.
- The LISN provides 50 ohm coupling impedance for the measuring instrument.
- The FCC states that a 50 ohm, 50 micro-Henry LISN should be used.
- Both sides of AC line were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched.
- Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.



4.3 Typical Test Setup




4.4 Measurement equipment

Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date.
EMI Receiver	R&S	ESCI	100443	2012/01/12	2013/01/11
LISN	Schwarzbeck	NSLK 8127	8127-516	2011/05/05	2012/05/04
LISN	Schwarzbeck	NSLK 8127	8127-568	2011/08/24	2012/08/23



4.5 Test Result and Data

Power	: AC 120V	Pol/Phase	: LINE
Test Mode 1	: GFSK CH0	Temperature	: 24 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	0.201	43.14	0.12	43.26	53.58	-10.32	Average
2	0.201	48.65	0.12	48.77	63.58	-14.81	QP
3	0.267	38.94	0.12	39.06	51.20	-12.14	Average
4	0.267	43.09	0.12	43.21	61.20	-17.99	QP
5	0.402	35.34	0.13	35.47	47.81	-12.34	Average
6	0.402	37.21	0.13	37.34	57.81	-20.47	QP
7	0.804	31.45	0.18	31.63	46.00	-14.37	Average
8	0.804	32.97	0.18	33.15	56.00	-22.85	QP
9	1.338	30.49	0.22	30.71	46.00	-15.29	Average
10	1.338	31.77	0.22	31.99	56.00	-24.01	QP
11	4.802	16.63	0.38	17.01	46.00	-28.99	Average
12	4.802	22.89	0.38	23.27	56.00	-32.73	QP

Notes:

1. Result = Read Value + Factor
2. Factor = LISN Factor + Cable Loss
3. According to technical experiences, all spurious emission of BT mode at channel 0,39,78 are almost the same below 1GHz, so that the channel 0 was chosen as representative in final test.
4. The data is worst case.



Power	: AC 120V	Pol/Phase	: NEUTRAL
Test Mode 1	: GFSK CH0	Temperature	: 24 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	0.203	37.08	0.10	37.18	53.49	-16.31	Average
2	0.203	45.61	0.10	45.71	63.49	-17.78	QP
3	0.267	37.36	0.10	37.46	51.20	-13.74	Average
4	0.267	41.33	0.10	41.43	61.20	-19.77	QP
5	0.402	31.78	0.12	31.90	47.81	-15.91	Average
6	0.402	34.96	0.12	35.08	57.81	-22.73	QP
7	1.338	28.67	0.20	28.87	46.00	-17.13	Average
8	1.338	31.44	0.20	31.64	56.00	-24.36	QP
9	4.525	16.40	0.34	16.74	46.00	-29.26	Average
10	4.525	23.25	0.34	23.59	56.00	-32.41	QP
11	17.590	22.28	0.69	22.97	50.00	-27.03	Average
12	17.590	28.45	0.69	29.14	60.00	-30.86	QP

Notes:

1. Result = Read Value + Factor
2. Factor = LISN Factor + Cable Loss
3. According to technical experiences, all spurious emission of BT mode at channel 0,39,78 are almost the same below 1GHz, so that the channel 0 was chosen as representative in final test.
4. The data is worst case.



Power	: AC 120V	Pol/Phase	: LINE
Test Mode 1	: $\pi/4$ -DQPSK CH0	Temperature	: 24 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	0.201	41.45	0.12	41.57	53.58	-12.01	Average
2	0.201	48.69	0.12	48.81	63.58	-14.77	QP
3	0.267	37.54	0.12	37.66	51.20	-13.54	Average
4	0.267	43.45	0.12	43.57	61.20	-17.63	QP
5	0.402	32.63	0.13	32.76	47.81	-15.05	Average
6	0.402	37.00	0.13	37.13	57.81	-20.68	QP
7	0.736	28.37	0.17	28.54	46.00	-17.46	Average
8	0.736	31.60	0.17	31.77	56.00	-24.23	QP
9	1.339	31.64	0.22	31.86	46.00	-14.14	Average
10	1.339	32.60	0.22	32.82	56.00	-23.18	QP
11	17.661	21.27	0.90	22.17	50.00	-27.83	Average
12	17.661	27.48	0.90	28.38	60.00	-31.62	QP

Notes:

1. Result = Read Value + Factor
2. Factor = LISN Factor + Cable Loss
3. According to technical experiences, all spurious emission of BT mode at channel 0,39,78 are almost the same below 1GHz, so that the channel 0 was chosen as representative in final test.
4. The data is worst case.



Power	: AC 120V	Pol/Phase	: NEUTRAL
Test Mode 1	: $\pi/4$ -DQPSK CH0	Temperature	: 24 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	0.201	39.74	0.10	39.84	53.58	-13.74	Average
2	0.201	46.36	0.10	46.46	63.58	-17.12	QP
3	0.267	34.28	0.10	34.38	51.20	-16.82	Average
4	0.267	41.55	0.10	41.65	61.20	-19.55	QP
5	0.402	30.77	0.12	30.89	47.81	-16.92	Average
6	0.402	35.53	0.12	35.65	57.81	-22.16	QP
7	0.804	28.45	0.16	28.61	46.00	-17.39	Average
8	0.804	31.17	0.16	31.33	56.00	-24.67	QP
9	1.338	28.25	0.20	28.45	46.00	-17.55	Average
10	1.338	31.79	0.20	31.99	56.00	-24.01	QP
11	4.525	17.21	0.34	17.55	46.00	-28.45	Average
12	4.525	23.51	0.34	23.85	56.00	-32.15	QP

Notes:

1. Result = Read Value + Factor
2. Factor = LISN Factor + Cable Loss
3. According to technical experiences, all spurious emission of BT mode at channel 0, 39.78 are almost the same below 1GHz, so that the channel 0 was chosen as representative in final test.
4. The data is worst case.



Power	: AC 120V	Pol/Phase	: LINE
Test Mode 1	: 8DPSK CH0	Temperature	: 24 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	0.201	42.29	0.12	42.41	53.58	-11.17	Average
2	0.201	48.70	0.12	48.82	63.58	-14.76	QP
3	0.267	38.70	0.12	38.82	51.20	-12.38	Average
4	0.267	43.19	0.12	43.31	61.20	-17.89	QP
5	0.402	35.31	0.13	35.44	47.81	-12.37	Average
6	0.402	37.59	0.13	37.72	57.81	-20.09	QP
7	0.804	31.39	0.18	31.57	46.00	-14.43	Average
8	0.804	32.53	0.18	32.71	56.00	-23.29	QP
9	1.338	30.61	0.22	30.83	46.00	-15.17	Average
10	1.338	31.89	0.22	32.11	56.00	-23.89	QP
11	4.802	16.54	0.38	16.92	46.00	-29.08	Average
12	4.802	22.80	0.38	23.18	56.00	-32.82	QP

Notes:

1. Result = Read Value + Factor
2. Factor = LISN Factor + Cable Loss
3. According to technical experiences, all spurious emission of BT mode at channel 0,39,78 are almost the same below 1GHz, so that the channel 0 was chosen as representative in final test.
4. The data is worst case.



Power	: AC 120V	Pol/Phase	: NEUTRAL
Test Mode 1	: 8DPSK CH0	Temperature	: 24 °C
Memo	:	Humidity	: 65 %



Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	0.203	37.50	0.10	37.60	53.49	-15.89	Average
2	0.203	45.45	0.10	45.55	63.49	-17.94	QP
3	0.267	37.57	0.10	37.67	51.20	-13.53	Average
4	0.267	41.77	0.10	41.87	61.20	-19.33	QP
5	0.402	31.47	0.12	31.59	47.81	-16.22	Average
6	0.402	34.46	0.12	34.58	57.81	-23.23	QP
7	1.338	28.39	0.20	28.59	46.00	-17.41	Average
8	1.338	31.52	0.20	31.72	56.00	-24.28	QP
9	4.525	16.19	0.34	16.53	46.00	-29.47	Average
10	4.525	23.53	0.34	23.87	56.00	-32.13	QP
11	17.590	22.44	0.69	23.13	50.00	-26.87	Average
12	17.590	28.31	0.69	29.00	60.00	-31.00	QP

Notes:

1. Result = Read Value + Factor
2. Factor = LISN Factor + Cable Loss
3. According to technical experiences, all spurious emission of BT mode at channel 0,39,78 are almost the same below 1GHz, so that the channel 0 was chosen as representative in final test.
4. The data is worst case.

Test engineer:



5. Test of Radiated Emission

5.1 Test Limit

Radiated emissions from 30 MHz to 25 GHz were measured according to the methods defines in ANSI C63.4-2009. The EUT was placed, 0.8 meter above the ground plane, as shown in section 5.6.3. The interface cables and equipment positions were varied within limits of reasonable applications to determine the positions producing maximum radiated emissions. For unintentional device, according to § 15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency (MHz)	Distance Meters	Radiated (μ V / M)	Radiated (dB μ V / M)
30-88	3	100	40.0
88-216	3	150	43.5
216-960	3	200	46.0
Above 960	3	500	54.0

For unintentional device, according to CISPR PUB.22, for Class B digital devices, the general requirement of field strength of radiated emissions from intentional radiators at a distance of 10 meters shall not exceed the above table.

Frequency (MHz)	Distance Meters	Radiated (dB μ V / M)
30-230	10	30
230-1000	10	37


5.2 Test Procedures

- The EUT was placed on a rotatable table top 0.8 meter above ground.
- The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- The table was rotated 360 degrees to determine the position of the highest radiation.
- The antenna is a broadband antenna and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- Set the test-receiver system to Peak or CISPR quasi-peak Detect Function and specified bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.
- For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.




5.3 Typical Test Setup

Below 1GHz Test Setup



Above 1GHz Test Setup




5.4 Measurement equipment

Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date
Amplifier	Agilent	8447D	2944A10531	2012/01/13	2013/01/12
Bilog Antenna	Schaffner	CBL6112D	22242	2012/01/12	2013/01/11
EMI Receiver	R&S	ESCI	101200	2011/07/26	2012/07/25
Spectrum Analyzer	R&S	FSP40	100047	2011/05/05	2012/05/04
Horn Antenna	EMCO	3115	31589	2011/05/02	2012/05/01
Preamplifier	Agilent	8449B	3008A01954	2011/03/02	2012/03/01



5.5 Test Result and Data

Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 1	: Transmit / Receive	Temperature	: 23 °C
Operation Channel	: 0	Humidity	: 65 %
Modulation Type	: GFSK	Atmospheric Pressure	: 1020 hPa
Rate	: 1 Mbps		




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	58.88	37.01	-14.46	22.55	40.00	-17.45	Peak	100	360
2	89.13	35.64	-12.39	23.25	43.50	-20.25	Peak	100	360
3	122.13	30.64	-3.39	27.25	43.50	-16.25	Peak	100	360
4	195.55	39.75	-9.95	29.80	43.50	-13.70	QP	100	360
5	261.00	35.37	-15.01	20.36	46.00	-25.64	Peak	100	360
6	293.45	38.74	-13.45	25.29	46.00	-20.71	Peak	100	360

Remarks: 1. Result = Read Value + Factor
 2. Factor = Antenna Factor + Cable Loss - Amplifier
 3. According to technical experiences, all spurious emission of BT mode at channel 0,39,78 are almost the same below 1GHz, so that the channel 0 was chosen as representative in final test.
 4. The data is worst case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 1	: Transmit / Receive	Temperature	: 23 °C
Operation Channel	: 0	Humidity	: 65 %
Modulation Type	: GFSK	Atmospheric Pressure	: 1020 hPa
Rate	: 1 Mbps		




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	357.40	41.56	-13.63	27.93	46.00	-18.07	Peak	100	0
2	455.40	42.44	-13.80	28.64	46.00	-17.36	Peak	100	0
3	553.40	30.01	-0.45	29.56	46.00	-16.44	Peak	100	0
4	618.50	34.72	-6.77	27.95	46.00	-18.05	Peak	100	0
5	685.00	29.55	-4.27	25.28	46.00	-20.72	Peak	100	0
6	912.50	29.20	3.07	32.27	46.00	-13.73	QP	100	0

Remarks: 1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. According to technical experiences, all spurious emission of BT mode at channel 0,39,78 are almost the same below 1GHz, so that the channel 0 was chosen as representative in final test.
4. The data is worst case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 1	: Transmit / Receive	Temperature	: 23 °C
Operation Channel	: 0	Humidity	: 65 %
Modulation Type	: GFSK	Atmospheric Pressure	: 1020 hPa
Rate	: 1 Mbps		




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	56.13	33.62	-18.97	14.65	40.00	-25.35	Peak	100	360
2	96.00	35.98	-20.26	15.72	43.50	-27.78	Peak	100	360
3	120.75	39.27	-20.20	19.07	43.50	-24.43	Peak	100	360
4	195.55	39.10	-21.66	17.44	43.50	-26.06	Peak	100	360
5	240.38	35.06	-16.01	19.05	46.00	-26.95	Peak	100	360
6	293.45	34.85	-15.82	19.03	46.00	-26.97	Peak	100	360

Remarks: 1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. According to technical experiences, all spurious emission of BT mode at channel 0,39,78 are almost the same below 1GHz, so that the channel 0 was chosen as representative in final test.
4. The data is worst case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 1	: Transmit / Receive	Temperature	: 23 °C
Operation Channel	: 0	Humidity	: 65 %
Modulation Type	: GFSK	Atmospheric Pressure	: 1020 hPa
Rate	: 1 Mbps		




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	357.40	42.37	-17.03	25.34	46.00	-20.66	Peak	100	0
2	455.40	35.06	-9.17	25.89	46.00	-20.11	Peak	100	0
3	553.40	27.18	-2.17	25.01	46.00	-20.99	Peak	100	0
4	618.50	32.49	-3.24	29.25	46.00	-16.75	Peak	100	0
5	685.00	27.18	-3.59	23.59	46.00	-22.41	Peak	100	0
6	912.50	26.53	1.28	27.81	46.00	-18.19	Peak	100	0

- Remarks:
1. Result = Read Value + Factor
 2. Factor = Antenna Factor + Cable Loss - Amplifier
 3. According to technical experiences, all spurious emission of BT mode at channel 0,39,78 are almost the same below 1GHz, so that the channel 0 was chosen as representative in final test.
 4. The data is worst case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 1	: Transmit / Receive	Temperature	: 23 °C
Operation Channel	: 0	Humidity	: 65 %
Modulation Type	: GFSK	Atmospheric Pressure	: 1020 hPa
Rate	: 1 Mbps		




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4804.00	40.14	5.59	45.73	74.00	-28.27	Peak	100	161

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 1	: Transmit / Receive	Temperature	: 23 °C
Operation Channel	: 0	Humidity	: 65 %
Modulation Type	: GFSK	Atmospheric Pressure	: 1020 hPa
Rate	: 1 Mbps		




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4804.00	40.24	5.59	45.83	74.00	-28.17	Peak	100	161

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 1	: Transmit / Receive	Temperature	: 23 °C
Operation Channel	: 39	Humidity	: 65 %
Modulation Type	: GFSK	Atmospheric Pressure	: 1020 hPa
Rate	: 1 Mbps		




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4882.00	38.66	5.88	44.54	74.00	-29.46	Peak	100	161

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 1	: Transmit / Receive	Temperature	: 23 °C
Operation Channel	: 39	Humidity	: 65 %
Modulation Type	: GFSK	Atmospheric Pressure	: 1020 hPa
Rate	: 1 Mbps		




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4882.00	40.87	5.88	46.75	74.00	-27.25	Peak	100	161

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 1	: Transmit / Receive	Temperature	: 23 °C
Operation Channel	: 78	Humidity	: 65 %
Modulation Type	: GFSK	Atmospheric Pressure	: 1020 hPa
Rate	: 1 Mbps		




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4960.00	39.85	6.15	46.00	74.00	-28.00	Peak	100	161

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 1	: Transmit / Receive	Temperature	: 23 °C
Operation Channel	: 78	Humidity	: 65 %
Modulation Type	: GFSK	Atmospheric Pressure	: 1020 hPa
Rate	: 1 Mbps		




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4960.00	38.60	6.15	44.75	74.00	-29.25	Peak	100	161

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 1	: Transmit / Receive	Temperature	: 23 °C
Operation Channel	: 0	Humidity	: 65 %
Modulation Type	: $\pi/4$ -DQPSK	Atmospheric Pressure	: 1020 hPa
Rate	: 2 Mbps		




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	357.40	42.06	-13.63	28.43	46.00	-17.57	Peak	100	0
2	455.40	40.98	-13.80	27.18	46.00	-18.82	Peak	100	0
3	520.50	37.75	-8.43	29.32	46.00	-16.68	Peak	100	0
4	587.00	36.36	-4.42	31.94	46.00	-14.06	QP	100	0
5	651.40	34.61	-6.37	28.24	46.00	-17.76	Peak	100	0
6	847.40	24.99	4.47	29.46	46.00	-16.54	Peak	100	0

- Remarks:
1. Result = Read Value + Factor
 2. Factor = Antenna Factor + Cable Loss - Amplifier
 3. According to technical experiences, all spurious emission of BT mode at channel 0,39,78 are almost the same below 1GHz, so that the channel 0 was chosen as representative in final test.
 4. The data is worst case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 1	: Transmit / Receive	Temperature	: 23 °C
Operation Channel	: 0	Humidity	: 65 %
Modulation Type	: $\pi/4$ -DQPSK	Atmospheric Pressure	: 1020 hPa
Rate	: 2 Mbps		



Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	44.30	29.08	-15.29	13.79	40.00	-26.21	Peak	100	360
2	96.00	36.66	-20.26	16.40	43.50	-27.10	Peak	100	360
3	120.75	40.82	-20.20	20.62	43.50	-22.88	Peak	100	360
4	195.55	39.52	-21.66	17.86	43.50	-25.64	Peak	100	360
5	237.63	36.94	-16.01	20.93	46.00	-25.07	Peak	100	360
6	293.45	34.62	-15.82	18.80	46.00	-27.20	Peak	100	360

Remarks: 1. Result = Read Value + Factor


2. Factor = Antenna Factor + Cable Loss - Amplifier

3. According to technical experiences, all spurious emission of BT mode at channel 0,39,78 are almost the same below 1GHz, so that the channel 0 was chosen as representative in final test.

4. The data is worst case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 1	: Transmit / Receive	Temperature	: 23 °C
Operation Channel	: 0	Humidity	: 65 %
Modulation Type	: $\pi/4$ -DQPSK	Atmospheric Pressure	: 1020 hPa
Rate	: 2 Mbps		




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	326.60	42.51	-16.86	25.65	46.00	-20.35	Peak	100	0
2	357.40	39.88	-17.03	22.85	46.00	-23.15	Peak	100	0
3	391.00	38.54	-13.51	25.03	46.00	-20.97	Peak	100	0
4	522.60	30.37	-6.19	24.18	46.00	-21.82	Peak	100	0
5	587.00	34.15	-2.42	31.73	46.00	-14.27	QP	100	0
6	651.40	34.00	-5.96	28.04	46.00	-17.96	Peak	100	0

Remarks: 1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. According to technical experiences, all spurious emission of BT mode at channel 0,39,78 are almost the same below 1GHz, so that the channel 0 was chosen as representative in final test.
4. The data is worst case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 1	: Transmit / Receive	Temperature	: 23 °C
Operation Channel	: 0	Humidity	: 65 %
Modulation Type	: $\pi/4$ -DQPSK	Atmospheric Pressure	: 1020 hPa
Rate	: 2 Mbps		




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	399.40	48.46	-9.28	39.18	46.00	-6.82	Peak	100	0
2	615.00	34.95	3.76	38.71	46.00	-7.29	Peak	100	0
3	714.40	34.56	3.26	37.82	46.00	-8.18	Peak	100	0
4	797.00	35.54	5.98	41.52	46.00	-4.48	QP	100	0
5	834.80	30.64	8.91	39.55	46.00	-6.45	Peak	100	0
6	931.40	35.40	6.64	42.04	46.00	-3.96	QP	100	0

Remarks: 1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. According to technical experiences, all spurious emission of BT mode at channel 0,39,78 are almost the same below 1GHz, so that the channel 0 was chosen as representative in final test.
4. The data is worst case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 1	: Transmit / Receive	Temperature	: 23 °C
Operation Channel	: 0	Humidity	: 65 %
Modulation Type	: $\pi/4$ -DQPSK	Atmospheric Pressure	: 1020 hPa
Rate	: 2 Mbps		




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4804.00	40.08	5.59	45.67	74.00	-28.33	Peak	100	179

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 1	: Transmit / Receive	Temperature	: 23 °C
Operation Channel	: 0	Humidity	: 65 %
Modulation Type	: $\pi/4$ -DQPSK	Atmospheric Pressure	: 1020 hPa
Rate	: 2 Mbps		




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4804.00	39.87	5.59	45.46	74.00	-28.54	Peak	100	179

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 1	: Transmit / Receive	Temperature	: 23 °C
Operation Channel	: 39	Humidity	: 65 %
Modulation Type	: $\pi/4$ -DQPSK	Atmospheric Pressure	: 1020 hPa
Rate	: 2 Mbps		




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4882.00	39.27	5.88	45.15	74.00	-28.85	Peak	100	179

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 1	: Transmit / Receive	Temperature	: 23 °C
Operation Channel	: 39	Humidity	: 65 %
Modulation Type	: $\pi/4$ -DQPSK	Atmospheric Pressure	: 1020 hPa
Rate	: 2 Mbps		




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4882.00	39.45	5.88	45.33	74.00	-28.67	Peak	100	179

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 1	: Transmit / Receive	Temperature	: 23 °C
Operation Channel	: 78	Humidity	: 65 %
Modulation Type	: $\pi/4$ -DQPSK	Atmospheric Pressure	: 1020 hPa
Rate	: 2 Mbps		




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4960.00	38.64	6.15	44.79	74.00	-29.21	Peak	100	161

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 1	: Transmit / Receive	Temperature	: 23 °C
Operation Channel	: 78	Humidity	: 65 %
Modulation Type	: $\pi/4$ -DQPSK	Atmospheric Pressure	: 1020 hPa
Rate	: 2 Mbps		




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4960.00	39.52	6.15	45.67	74.00	-28.33	Peak	100	161

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 1	: Transmit / Receive	Temperature	: 23 °C
Operation Channel	: 0	Humidity	: 65 %
Modulation Type	: 8DPSK	Atmospheric Pressure	: 1020 hPa
Rate	: 3 Mbps		




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	59.70	36.42	-14.74	21.68	40.00	-18.32	Peak	100	360
2	88.30	35.50	-12.62	22.88	43.50	-20.62	Peak	100	360
3	120.75	31.73	-2.54	29.19	43.50	-14.31	QP	100	360
4	195.55	38.65	-9.95	28.70	43.50	-14.80	QP	100	360
5	260.45	33.39	-15.16	18.23	46.00	-27.77	Peak	100	360
6	293.45	37.33	-13.45	23.88	46.00	-22.12	Peak	100	360

- Remarks:
1. Result = Read Value + Factor
 2. Factor = Antenna Factor + Cable Loss - Amplifier
 3. According to technical experiences, all spurious emission of BT mode at channel 0,39,78 are almost the same below 1GHz, so that the channel 0 was chosen as representative in final test.
 4. The data is worst case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 1	: Transmit / Receive	Temperature	: 23 °C
Operation Channel	: 0	Humidity	: 65 %
Modulation Type	: 8DPSK	Atmospheric Pressure	: 1020 hPa
Rate	: 3 Mbps		




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	357.40	42.18	-13.63	28.55	46.00	-17.45	Peak	100	0
2	455.40	42.26	-13.80	28.46	46.00	-17.54	Peak	100	0
3	520.50	38.36	-8.43	29.93	46.00	-16.07	QP	100	0
4	587.00	36.18	-4.42	31.76	46.00	-14.24	QP	100	0
5	651.40	34.00	-6.37	27.63	46.00	-18.37	Peak	100	0
6	839.00	23.07	5.21	28.28	46.00	-17.72	Peak	100	0

Remarks: 1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. According to technical experiences, all spurious emission of BT mode at channel 0,39,78 are almost the same below 1GHz, so that the channel 0 was chosen as representative in final test.
4. The data is worst case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 1	: Transmit / Receive	Temperature	: 23 °C
Operation Channel	: 0	Humidity	: 65 %
Modulation Type	: 8DPSK	Atmospheric Pressure	: 1020 hPa
Rate	: 3 Mbps		




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	56.95	33.48	-19.99	13.49	40.00	-26.51	Peak	100	360
2	96.00	36.75	-20.26	16.49	43.50	-27.01	Peak	100	360
3	120.75	40.20	-20.20	20.00	43.50	-23.50	Peak	100	360
4	195.55	38.70	-21.66	17.04	43.50	-26.46	Peak	100	360
5	260.45	32.49	-16.87	15.62	46.00	-30.38	Peak	100	360
6	293.45	33.55	-15.82	17.73	46.00	-28.27	Peak	100	360

Remarks: 1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. According to technical experiences, all spurious emission of BT mode at channel 0,39,78 are almost the same below 1GHz, so that the channel 0 was chosen as representative in final test.
4. The data is worst case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 1	: Transmit / Receive	Temperature	: 23 °C
Operation Channel	: 0	Humidity	: 65 %
Modulation Type	: 8DPSK	Atmospheric Pressure	: 1020 hPa
Rate	: 3 Mbps		




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	357.40	39.36	-17.03	22.33	46.00	-23.67	Peak	100	0
2	391.00	37.03	-13.51	23.52	46.00	-22.48	Peak	100	0
3	520.50	33.18	-6.48	26.70	46.00	-19.30	Peak	100	0
4	587.00	34.95	-2.42	32.53	46.00	-13.47	QP	100	0
5	618.50	30.63	-3.24	27.39	46.00	-18.61	Peak	100	0
6	716.50	26.28	-3.75	22.53	46.00	-23.47	Peak	100	0

Remarks: 1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. According to technical experiences, all spurious emission of BT mode at channel 0,39,78 are almost the same below 1GHz, so that the channel 0 was chosen as representative in final test.
4. The data is worst case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 1	: Transmit / Receive	Temperature	: 23 °C
Operation Channel	: 0	Humidity	: 65 %
Modulation Type	: 8DPSK	Atmospheric Pressure	: 1020 hPa
Rate	: 3 Mbps		




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4804.00	39.27	5.59	44.86	74.00	-29.14	Peak	100	161

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 1	: Transmit / Receive	Temperature	: 23 °C
Operation Channel	: 0	Humidity	: 65 %
Modulation Type	: 8DPSK	Atmospheric Pressure	: 1020 hPa
Rate	: 3 Mbps		




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4804.00	39.85	5.59	45.44	74.00	-28.56	Peak	100	174

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 1	: Transmit / Receive	Temperature	: 23 °C
Operation Channel	: 39	Humidity	: 65 %
Modulation Type	: 8DPSK	Atmospheric Pressure	: 1020 hPa
Rate	: 3 Mbps		




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4882.00	39.24	5.88	45.12	74.00	-28.88	Peak	100	174

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 1	: Transmit / Receive	Temperature	: 23 °C
Operation Channel	: 39	Humidity	: 65 %
Modulation Type	: 8DPSK	Atmospheric Pressure	: 1020 hPa
Rate	: 3 Mbps		




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4882.00	39.37	5.88	45.25	74.00	-28.75	Peak	100	174

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 1	: Transmit / Receive	Temperature	: 23 °C
Operation Channel	: 78	Humidity	: 65 %
Modulation Type	: 8DPSK	Atmospheric Pressure	: 1020 hPa
Rate	: 3 Mbps		




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4960.00	39.18	6.15	45.33	74.00	-28.67	Peak	100	174

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 1	: Transmit / Receive	Temperature	: 23 °C
Operation Channel	: 78	Humidity	: 65 %
Modulation Type	: 8DPSK	Atmospheric Pressure	: 1020 hPa
Rate	: 3 Mbps		



Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4960.00	40.00	6.15	46.15	74.00	-27.85	Peak	100	174

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300KHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.

Test engineer: Ben



6. 20dB Bandwidth Measurement Data


6.1 Test Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

6.2 Test Procedures

- The transmitter output was connected to the spectrum analyzer.
- Set RBW of spectrum analyzer to 30 KHz and VBW to 100 KHz.
- The 20 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20 dB.

6.3 Test Setup Layout



6.4 Measurement equipment

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Calibration Date	Valid Date
Spectrum Analyzer	R&S	FSP40	100047	2011/05/05	2012/05/04



6.5 Test Result and Data

Test Date: Feb. 08, 2012

Temperature: 20°C

Atmospheric pressure: 1020 hPa


Humidity: 68%

Modulation Standard	Channel	Frequency (MHz)	20dB Bandwidth (KHz)
GFSK (1Mbps)	00	2402	796.00
	39	2441	800.00
	78	2480	796.00
$\pi/4$ -DQPSK (2Mbps)	00	2402	1294.00
	39	2441	1222.00
	78	2480	1250.00
8DPSK (3Mbps)	00	2402	1264.00
	39	2441	1272.00
	78	2480	1260.00




Modulation Standard: GFSK (1Mbps)

Channel: 00




Modulation Standard: GFSK (1Mbps)

Channel: 39







Modulation Standard: GFSK (1Mbps)
Channel: 78




Modulation Standard: $\pi/4$ -DQPSK (2Mbps)
Channel: 00



Modulation Standard: $\pi/4$ -DQPSK (2Mbps)
Channel: 39




Modulation Standard: $\pi/4$ -DQPSK (2Mbps)
Channel: 78






Modulation Standard: 8DPSK (3Mbps)

Channel: 00




Modulation Standard: 8DPSK (3Mbps)

Channel: 39





Modulation Standard: 8DPSK (3Mbps)
Channel: 78





7. Frequencies Separation


7.1 Test Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

7.2 Test Procedures

- The transmitter output was connected to the spectrum analyzer.
- Set RBW of spectrum analyzer to 100 KHz and VBW to 100 KHz.
- By using the MaxHold function record the separation of two adjacent channels.
- Measure the frequency difference of these two adjacent channels.

7.3 Test Setup Layout



7.4 Measurement equipment

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Calibration Date	Valid Date
Spectrum Analyzer	R&S	FSP40	100047	2011/05/05	2012/05/04



7.5 Test Result and Data

Test Date: Oct. 20, 2011

Temperature: 24°C

Atmospheric pressure: 1018 hPa


Humidity: 64%

Modulation Standard	Channel	Frequency (MHz)	Channel Separation (MHz)
GFSK (1Mbps)	00	2402	1.004
	39	2441	1.000
	78	2480	1.004
$\pi/4$ -DQPSK (2Mbps)	00	2402	1.002
	39	2441	1.004
	78	2480	1.009
8DPSK (3Mbps)	00	2402	1.008
	39	2441	0.996
	78	2480	1.008




Modulation Standard: GFSK (1Mbps)

Channel: 00



Modulation Standard: GFSK (1Mbps)


Channel: 39






Modulation Standard: GFSK (1Mbps)

Channel: 78


Modulation Standard: $\pi/4$ -DQPSK (2Mbps)

Channel: 00






Modulation Standard: $\pi/4$ -DQPSK (2Mbps)
Channel: 39




Modulation Standard: $\pi/4$ -DQPSK (2Mbps)
Channel: 78






Modulation Standard: 8DQPSK (3Mbps)
Channel: 00




Modulation Standard: 8DQPSK (3Mbps)
Channel: 39





Modulation Standard: 8DQPSK (3Mbps)
Channel: 78





8. Dwell Time on each channel


8.1 Test Limit

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

8.2 Test Procedures

1. The transmitter output was connected to the spectrum analyzer.
2. Adjust the center frequency to measure frequency, then set zero span mode.
2. Set RBW of spectrum analyzer to 100 KHz and VBW to 100 KHz.
4. Measure the time duration of one transmission on the measured frequency.

8.3 Test Setup Layout



8.4 Measurement equipment

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Calibration Date	Valid Date
Spectrum Analyzer	R&S	FSP40	100047	2011/05/05	2012/05/04

8.5 Test Result and Data

Test Date: Oct. 20, 2011

Temperature: 24°C

Atmospheric pressure: 1018 hPa



Humidity: 64%

Modulation Standard	Channel	Frequency (MHz)	Dwell Time (ms)
GFSK (1Mbps)	00	2402	132.48
	39	2441	132.48
	78	2480	130.56
$\pi/4$ -DQPSK (2Mbps)	00	2402	323.84
	39	2441	322.96
	78	2480	323.84
8DPSK (3Mbps)	00	2402	323.84
	39	2441	324.72
	78	2480	323.84



Modulation Standard: GFSK (1Mbps)



Channel: 00







Modulation Standard: GFSK (1Mbps)

Channel: 39







Modulation Standard: GFSK (1Mbps)
Channel: 78





Modulation Standard: $\pi/4$ -DQPSK (2Mbps)

Channel: 00





Modulation Standard: $\pi/4$ -DQPSK (2Mbps)

Channel: 39



Modulation Standard: $\pi/4$ -DQPSK (2Mbps)



Channel: 78







Modulation Standard: 8DPSK (3Mbps)

Channel: 00







Modulation Standard: 8DPSK (3Mbps)
Channel: 39





Modulation Standard: 8DPSK (3Mbps)
Channel: 78





9. Number of Hopping Channels


9.1 Test Limit

Frequency hopping systems in the 2400 ~ 2483.5 MHz band shall use at least 15 channels.

9.2 Test Procedures

- a. The transmitter output was connected to the spectrum analyzer.
- b. 2. Set RBW of spectrum analyzer to 100 KHz and VBW to 100 KHz.
- c. 3. Set the MaxHold function, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been record.

9.3 Test Setup Layout



9.4 Measurement equipment

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Calibration Date	Valid Date
Spectrum Analyzer	R&S	FSP40	100047	2011/05/05	2012/05/04

9.5 Test Result and Data

Test Date: Oct. 20, 2011

Temperature: 24°C



Atmospheric pressure: 1018 hPa

Humidity: 64%

Modulation Standard	Number of hopping channels
GFSK(1Mbps)	79
$\pi/4$ -DQPSK (2Mbps)	79
8DPSK (3Mbps)	79




Modulation Standard: GFSK (1Mbps)

Modulation Standard: $\pi/4$ -DQPSK (2Mbps)



Modulation Standard: 8DPSK (3Mbps)





10. Maximum Peak Output Power


10.1 Test Limit

The Maximum Peak Output Power Measurement is 30dBm.

10.2 Test Procedures

The antenna port(RF output)of the EUT was connected to the input(RF input)of a power meter. Power was read directly from the meter and cable loss connection was added to the reading to obtain power at the EUT antenna terminal. The EUT Output Power was set to maximum to produce the worse case test result.

10.3 Test Setup Layout



10.4 Measurement equipment

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Calibration Date	Valid Date
Spectrum Analyzer	R&S	FSP40	100047	2011/05/05	2012/05/04

10.5 Test Result and Data

Test Date: Oct. 20 2011

Temperature: 24℃


Atmospheric pressure: 1018 hPa

Humidity: 64%


Modulation Type	Channel	Frequency (MHz)	Peak Power Output (dBm)	Peak Power Output (mW)
GFSK (1Mbps)	00	2402	-0.04	1.0
	39	2441	-0.90	0.8
	78	2478	-1.77	0.7
$\pi/4$ -DQPSK (2Mbps)	00	2402	-5.13	0.3
	39	2441	-5.95	0.3
	78	2478	-4.33	0.4
8DPSK (3Mbps)	00	2402	-4.32	0.4
	39	2441	-3.87	0.4
	78	2478	-4.33	0.4



Modulation Standard: GFSK (1Mbps)
Channel: 00




Modulation Standard: GFSK (1Mbps)
Channel: 39






Modulation Standard: GFSK (1Mbps)
Channel: 78




Modulation Standard: $\pi/4$ -DQPSK (2Mbps)
Channel: 00






Modulation Standard: $\pi/4$ -DQPSK (2Mbps)
Channel: 39




Modulation Standard: $\pi/4$ -DQPSK (2Mbps)
Channel: 78






Modulation Standard: 8DPSK (3Mbps)
Channel: 00




Modulation Standard: 8DPSK (3Mbps)
Channel: 39





Modulation Standard: 8DPSK (3Mbps)
Channel: 78





11. Band Edges Measurement


11.1 Test Limit

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

11.2 Test Procedure :

- The transmitter output was connected to the spectrum analyzer via a low lose cable.
- Set both RBW and VBW of spectrum analyzer to 100 KHz with convenient frequency span including 100 KHz bandwidth from band edge.
- The band edges was measured and recorded.

11.3 Test Setup Layout



11.4 List of Measuring Equipment Used

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Calibration Date	Valid Date
Spectrum Analyzer	R&S	FSP40	100047	2011/05/05	2012/05/04

11.5 Test Result and Data

Test Date: Oct. 20, 2011

Temperature: 24°C

Atmospheric pressure: 1018 hPa

Humidity: 64%


Modulation Standard	Channel	Frequency	maximum value in frequency (MHz)	maximum value (dBm)
GFSK (1Mbps)	00	2402	2399.92	-43.08
	78	2480	2484.46	-48.09
$\pi/4$ -DQPSK (2Mbps)	00	2402	2399.40	-52.97
	78	2480	2483.79	-51.15
8DPSK (3Mbps)	00	2402	2399.60	-52.05
	78	2480	2483.58	-51.17




Modulation Standard: GFSK (1Mbps)
Channel: 00



*RBW 100 kHz Marker 1 [T1]
*VEW 300 kHz -43.08 dBm
*SWT 115 ms 2.399920000 GHz





*RBW 100 kHz Marker 1 [T1]
*VEW 300 kHz -45.25 dBm
*SWT 2.5 s 4.777040000 GHz







Modulation Standard: GFSK (1Mbps)
Channel: 78





Modulation Standard: $\pi/4$ -DQPSK (2Mbps)

Channel: 00







Modulation Standard: $\pi/4$ -DQPSK (2Mbps)
Channel: 78







Modulation Standard: 8DPSK (3Mbps)

Channel: 00





Modulation Standard: 8DPSK (3Mbps)
Channel: 78



**11.6 Restrict band emission Measurement Data**

Test Date : Sep. 13, 2011
Temperature : 23°C
Humidity : 65%
Atmospheric Pressure : 1020 hPa
Modulation Standard : GFSK (1Mbps)

Channel 0						Fundamental Frequency: 2402 MHz				
Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2351.82	H	46.14	-2.78	43.36	Peak	74	54	-30.64	360	1.00
---	H	---	---	---	Ave	74	54	---	---	1.00
2351.62	V	47.05	-2.78	44.27	Peak	74	54	-29.73	0	1.00
---	V	---	---	---	Ave	74	54	---	---	1.00
Channel 78						Fundamental Frequency: 2480 MHz				
2492.78	H	46.26	-2.32	43.94	Peak	74	54	-30.06	0	1.00
---	H	---	---	---	Ave	74	54	---	---	1.00
2489.82	V	47.24	-2.33	44.91	Peak	74	54	-29.09	0	1.00
---	V	---	---	---	Ave	74	54	---	---	1.00

Notes:

1. Result = Meter Reading + Factor
2. Factor = Antenna Factor + Cable Loss – Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3 MHz for Peak detection at frequency above 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz



Test Date : Sep. 13, 2011
Temperature : 23°C
Humidity : 65%
Atmospheric Pressure : 1020 hPa
Modulation Standard : $\pi/4$ -DQPSK (2Mbps)

Channel 0						Fundamental Frequency: 2402 MHz				
Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2365.59	H	45.42	-2.73	42.69	Peak	74	54	-31.31	0	1.00
---	H	---	---	---	Ave	74	54	---	---	1.00
2335.30	V	46.47	-2.83	43.64	Peak	74	54	-30.36	360	1.00
---	V	---	---	---	Ave	74	54	---	---	1.00
Channel 78						Fundamental Frequency: 2480 MHz				
2489.74	H	46.17	-2.33	43.84	Peak	74	54	-30.16	0	1.00
---	H	---	---	---	Ave	74	54	---	---	1.00
2495.25	V	47.14	-2.32	44.82	Peak	74	54	-29.18	360	1.00
---	V	---	---	---	Ave	74	54	---	---	1.00

Notes:

1. Result = Meter Reading + Factor
2. Factor = Antenna Factor + Cable Loss – Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3 MHz for Peak detection at frequency above 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz



Test Date : Sep. 13, 2011
Temperature : 23°C
Humidity : 65%
Atmospheric Pressure : 1020 hPa
Modulation Standard : 8DPSK (3Mbps)

Channel 0						Fundamental Frequency: 2402 MHz				
Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2362.22	H	45.68	-2.75	42.93	Peak	74	54	-31.07	0	1.00
---	H	---	---	---	Ave	74	54	---	---	1.00
2374.77	V	45.42	-2.70	42.72	Peak	74	54	-31.28	360	1.00
---	V	---	---	---	Ave	74	54	---	---	1.00
Channel 78						Fundamental Frequency: 2480 MHz				
2489.82	H	45.41	-2.33	43.08	Peak	74	54	-30.92	208	1.00
---	H	---	---	---	Ave	74	54	---	---	1.00
2499.54	V	47.29	-2.30	44.99	Peak	74	54	-29.01	360	1.00
---	V	---	---	---	Ave	74	54	---	---	1.00

Notes:

1. Result = Meter Reading + Factor
2. Factor = Antenna Factor + Cable Loss – Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3 MHz for Peak detection at frequency above 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz



12. Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.09000 – 0.11000	16.42000 – 16.42300	399.9 – 410.0	4.500 – 5.250
0.49500 – 0.505**	16.69475 – 16.69525	608.0 – 614.0	5.350 – 5.460
2.17350 – 2.19050	16.80425 – 16.80475	960.0 – 1240.0	7.250 – 7.750
4.12500 – 4.12800	25.50000 – 25.67000	1300.0 – 1427.0	8.025 – 8.500
4.17725 – 4.17775	37.50000 – 38.25000	1435.0 – 1626.5	9.000 – 9.200
4.20725 – 4.20775	73.00000 – 74.60000	1645.5 – 1646.5	9.300 – 9.500
6.21500 – 6.21800	74.80000 – 75.20000	1660.0 – 1710.0	10.600 – 12.700
6.26775 – 6.26825	108.00000 – 121.94000	1718.8 – 1722.2	13.250 – 13.400
6.31175 – 6.31225	123.00000 – 138.00000	2200.0 – 2300.0	14.470 – 14.500
8.29100 – 8.29400	149.90000 – 150.05000	2310.0 – 2390.0	15.350 – 16.200
8.36200 – 8.36600	156.52475 – 156.52525	2483.5 – 2500.0	17.700 – 21.400
8.37625 – 8.38675	156.70000 – 156.90000	2655.0 – 2900.0	22.010 – 23.120
8.41425 – 8.41475	162.01250 – 167.17000	3260.0 – 3267.0	23.600 – 24.000
12.29000 – 12.29300	167.72000 – 173.20000	3332.0 – 3339.0	31.200 – 31.800
12.51975 – 12.52025	240.00000 – 285.00000	3345.8 – 3358.0	36.430 – 36.500
12.57675 – 12.57725	322.00000 – 335.40000	3600.0 – 4400.0	Above 38.6
13.36000 – 13.41000			

** : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

12.1 Labeling Requirement

The device shall bear the following statement in a conspicuous location on the device:

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.