



FCC RF Test Report

APPLICANT : VeriFone, Inc.
EQUIPMENT : Point of Sale Terminal
BRAND NAME : Verifone or VERIFONE or verifone
MODEL NAME : P630 Plus-A
FCC ID : B32P630PLUSA
STANDARD : FCC Part 15 Subpart E §15.407
CLASSIFICATION : (NII) Unlicensed National Information Infrastructure
TEST DATE(S) : Oct. 26, 2024 ~ Dec. 18, 2024

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (Kunshan)

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	6
1.5 Modification of EUT	7
1.6 Testing Location	8
1.7 Test Software.....	8
1.8 Applicable Standards.....	8
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	9
2.1 Carrier Frequency and Channel	9
2.2 Test Mode.....	10
2.3 Connection Diagram of Test System.....	12
2.4 Support Unit used in test configuration and system	13
2.5 EUT Operation Test Setup	13
2.6 Measurement Results Explanation Example.....	13
3 TEST RESULT	14
3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement	14
3.2 Maximum Conducted Output Power Measurement	16
3.3 Power Spectral Density Measurement	21
3.4 Unwanted Emissions Measurement	24
3.5 AC Conducted Emission Measurement.....	29
3.6 Antenna Requirements	31
4 LIST OF MEASURING EQUIPMENT	32
5 MEASUREMENT UNCERTAINTY	33
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT	
APPENDIX C. RADIATED SPURIOUS EMISSION	
APPENDIX D. DUTY CYCLE PLOTS	
APPENDIX E. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR4O1616E	Rev. 01	Initial issue of report	Jan. 06, 2025

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit for U-NII-1/2A/2C	Limit for U-NII-3	Result	Remark
3.1	2.1049 & 15.403(i)	6dB, 26dB & 99% Bandwidth	-	6dB Bandwidth > 500kHz	Pass	-
3.2	15.407(a)	Maximum Conducted Output Power	≤ 24 dBm	≤ 30 dBm	Pass	-
3.3	15.407(a)	Power Spectral Density	≤ 11 dBm/MHz	≤ 30 dBm/500kHz	Pass	-
3.4	15.407(b)	Unwanted Emissions	15.407(b) & 15.209(a)	15.407(b)(4)(i) & 15.209(a)	Pass	Under limit 3.26 dB at 5351.70 MHz
3.5	15.207	AC Conducted Emission	15.207(a)	15.207(a)	Pass	Under limit 12.78 dB at 0.406 MHz
3.6	15.203 & 15.407(a)	Antenna Requirement	15.203 & 15.407(a)	15.203 & 15.407(a)	Pass	-

Conformity Assessment Condition:

- The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
- The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

VeriFone, Inc.

1400 West Stanford Ranch Road Suite 150 Rocklin CA 95765 USA

1.2 Manufacturer

VeriFone, Inc.

1400 West Stanford Ranch Road Suite 150 Rocklin CA 95765 USA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Point of Sale Terminal
Brand Name	Verifone or VERIFONE or verifone
Model Name	P630 Plus-A
FCC ID	B32P630PLUSA
SN Code	Conducted: 552-000-214 Conduction: 552-000-025 Radiation: 552-000-235
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	5180 MHz ~ 5240 MHz 5260 MHz ~ 5320 MHz 5500 MHz ~ 5720 MHz 5745 MHz ~ 5825 MHz
Maximum Output Power to Antenna	<5180 MHz ~ 5240 MHz> 802.11a : 17.23 dBm / 0.0528 W 802.11n HT20 : 16.77 dBm / 0.0475 W 802.11n HT40 : 17.05 dBm / 0.0507 W 802.11ac VHT20: 16.85 dBm / 0.0484 W 802.11ac VHT40: 17.10 dBm / 0.0513 W 802.11ac VHT80: 12.46 dBm / 0.0176 W <5260 MHz ~ 5320 MHz> 802.11a : 17.23 dBm / 0.0528 W 802.11n HT20 : 16.81 dBm / 0.0480 W 802.11n HT40 : 17.56 dBm / 0.0570 W 802.11ac VHT20: 16.88 dBm / 0.0488 W 802.11ac VHT40: 17.60 dBm / 0.0575 W 802.11ac VHT80: 13.28 dBm / 0.0213 W <5500 MHz ~ 5720 MHz > 802.11a : 17.12 dBm / 0.0515 W 802.11n HT20 : 16.87 dBm / 0.0486 W 802.11n HT40 : 17.63 dBm / 0.0579 W 802.11ac VHT20: 16.95 dBm / 0.0495 W 802.11ac VHT40: 17.68 dBm / 0.0586 W 802.11ac VHT80: 16.41 dBm / 0.0438 W <5745 MHz ~ 5825 MHz> 802.11a : 16.73 dBm / 0.0471 W 802.11n HT20 : 16.55 dBm / 0.0452 W 802.11n HT40 : 17.00 dBm / 0.0501 W 802.11ac VHT20: 16.62 dBm / 0.0459 W 802.11ac VHT40: 17.04 dBm / 0.0506 W 802.11ac VHT80: 15.63 dBm / 0.0366 W

99% Occupied Bandwidth	<5180 MHz ~ 5240 MHz> 802.11a : 17.183 MHz 802.11ac VHT20 : 18.302 MHz 802.11ac VHT40 : 36.523 MHz 802.11ac VHT80 : 76.563 MHz <5260 MHz ~ 5320 MHz> 802.11a : 17.223 MHz 802.11ac VHT20 : 18.302 MHz 802.11ac VHT40 : 36.603 MHz 802.11ac VHT80 : 76.563 MHz <5500 MHz ~ 5720 MHz> 802.11a : 17.223 MHz 802.11ac VHT20 : 18.302 MHz 802.11ac VHT40 : 36.603 MHz 802.11ac VHT80 : 76.404 MHz <5745 MHz ~ 5825 MHz> 802.11a : 17.183 MHz 802.11ac VHT20 : 18.302 MHz 802.11ac VHT40 : 36.683 MHz 802.11ac VHT80 : 76.404 MHz
Antenna Type / Gain	<5180 MHz ~ 5240 MHz> PIFA Antenna type with gain -0.93 dBi <5260 MHz ~ 5320 MHz> PIFA Antenna type with gain -0.93 dBi <5500 MHz ~ 5720 MHz> PIFA Antenna type with gain 0.32 dBi <5745 MHz ~ 5825 MHz> PIFA Antenna type with gain 0.46 dBi
Type of Modulation	802.11a/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)

Note: For 802.11n HT20 / ac VHT20 and 802.11n HT40 / ac VHT40 mode, the whole testing has assessed only 802.11ac VHT20/ VHT40 by referring to their higher conducted power.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-KS 03CH05-KS TH01-KS	CN1257	314309

1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	TH01-KS	Tonscend	JS1120-3 test system China_210602	3.3.10
2.	03CH05-KS	AUDIX	E3	210616
3.	CO01-KS	AUDIX	E3	6.2009-8-24

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart E
- FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq.(MHz)	Channel	Freq. (MHz)
5180-5240 MHz U-NII-1	36	5180	44	5220
	38*	5190	46*	5230
	40	5200	48	5240
	42 [#]	5210	-	-

Frequency Band	Channel	Freq.(MHz)	Channel	Freq. (MHz)
5260-5320 MHz U-NII-2A	52	5260	60	5300
	54*	5270	62*	5310
	56	5280	64	5320
	58 [#]	5290	-	-

Frequency Band	Channel	Freq.(MHz)	Channel	Freq. (MHz)
5500-5720MHz U-NII-2C	100	5500	112	5560
	102*	5510	116	5580
	104	5520	132	5660
	106 [#]	5530	134*	5670
	108	5540	136	5680
	110*	5550	140	5700

Frequency Band	Channel	Freq.(MHz)	Channel	Freq. (MHz)
5745-5825 MHz U-NII-3	149	5745	157	5785
	151*	5755	159*	5795
	153	5765	161	5805
	155 [#]	5775	165	5825

Frequency Band	Channel	Freq.(MHz)	Channel	Freq. (MHz)
TDWR Channel	118*	5590	124	5620
	120	5600	126*	5630
	122 [#]	5610	128	5640

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
Straddle Channel	138 [#]	5690	144	5720
	142*	5710	-	-

Note:

1. The above Frequency and Channel in "*" are 40MHz bandwidth.
2. The above Frequency and Channel in "[#]" are 80MHz bandwidth.

2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20 (Covered by VHT20)	MCS0
802.11n HT40 (Covered by VHT40)	MCS0
802.11ac VHT20	MCS0
802.11ac VHT40	MCS0
802.11ac VHT80	MCS0

AC Conducted Emission	Mode 1 : BT Link + WLAN Link(5G) + Earphone + Adaptor 2 + ORANGE Cable + Orange D2
Remark: For Radiated Test Cases, the tests were performance with Adaptor and Earphone.	

RSE Co-location
Bluetooth LE(1 Mbps) CH39_TX + 802.11ac VHT80 CH58 5290




Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		20M BW	20M BW	20M BW	20M BW
L	Low	36	52	100	149
M	Middle	44	60	116	157
H	High	48	64	140	165
Straddle		-	-	144	-

Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		40M BW	40M BW	40M BW	40M BW
L	Low	38	54	102	151
M	Middle	-	-	110	-
H	High	46	62	134	159
Straddle		-	-	142	-


Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		80M BW	80M BW	80M BW	80M BW
L	Low	-	-	106	-
M	Middle	42	58	-	155
H	High	-	-	-	-
Straddle		-	-	138	-

2.3 Connection Diagram of Test System

AC Conducted Emission:



Radiated Emission:



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Earphone	Lenovo	thinkplus-BH3	N/A	N/A	N/A
2.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded,1.8m
3.	WLAN AP	TP-Link	TL-WDR5600	N/A	N/A	Unshielded,1.8m
4.	U Disk	SanDisk	SDCZ50-008G	N/A	N/A	N/A
5.	Earphone	Lenovo	P121	N/A	N/A	Unshielded,1.2m
6.	SD Card	N/A	N/A	N/A	N/A	N/A
7.	NFC Card	N/A	N/A	N/A	N/A	N/A
8.	MAG Card	N/A	N/A	N/A	N/A	N/A
9.	IC Card	N/A	N/A	N/A	N/A	N/A

2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuously transmit.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 14.38 dB and 10dB attenuator.

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\
 &= 14.38 + 10 = 24.38 \text{ (dB)}
 \end{aligned}$$

3 Test Result

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.

3.1.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

☒	Section C) Bandwidth Measurement 1. Emission Bandwidth (EBW) and 99% OBW
	1. Set RBW = approximately 1% of the emission bandwidth. 2. Set the VBW > RBW. 3. Detector = Peak. 4. Trace mode = max hold 5. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%. 6. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set to 1%~5% of the OBW and set the Video bandwidth (VBW) $\geq 3 \times$ RBW. 7. Measure and record the results in the test report.
☒	Section C) Bandwidth Measurement 2. Minimum Emission Bandwidth for the band 5.725 - 5.85 GHz
	1. Set RBW = 100kHz. 2. Set the VBW $\geq 3 \times$ RBW. 3. Detector = Peak. 4. Trace mode = max hold 5. Measure the maximum width of the emission that is 6 dB down from the peak of the emission. 6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.



3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

<FCC 14-30 CFR 15.407>

For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW.

For the 5.25–5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm +10 log₁₀ B, where B is the 26 dB emission bandwidth in megahertz.

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

For Straddle Channel, According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, If the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Note that U-NII-2 band, devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures


The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor, $10 \log(1/x)$, where x is the duty cycle.

For Straddle Channel, According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, If the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

3.2.4 Test Setup





3.2.5 Test Result of Maximum Conducted Output Power

<5180 MHz ~ 5240 MHz>										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power with duty factor (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)	Pass/Fail	Power Setting
					Ant 1	Ant 1	Ant 1	Ant 1		Ant 1
11a	6Mbps	1	36	5180	0.09	16.43	24.00	-0.93	Pass	17
11a	6Mbps	1	44	5220	0.09	16.75	24.00	-0.93	Pass	17
11a	6Mbps	1	48	5240	0.09	17.23	24.00	-0.93	Pass	17
HT20	MCS0	1	36	5180	0.10	16.02	24.00	-0.93	Pass	17
HT20	MCS0	1	44	5220	0.10	16.29	24.00	-0.93	Pass	17
HT20	MCS0	1	48	5240	0.10	16.77	24.00	-0.93	Pass	17
HT40	MCS0	1	38	5190	0.16	16.88	24.00	-0.93	Pass	17
HT40	MCS0	1	46	5230	0.16	17.05	24.00	-0.93	Pass	17
VHT20	MCS0	1	36	5180	0.07	16.08	24.00	-0.93	Pass	17
VHT20	MCS0	1	44	5220	0.07	16.39	24.00	-0.93	Pass	17
VHT20	MCS0	1	48	5240	0.07	16.85	24.00	-0.93	Pass	17
VHT40	MCS0	1	38	5190	0.16	16.92	24.00	-0.93	Pass	17
VHT40	MCS0	1	46	5230	0.16	17.10	24.00	-0.93	Pass	17
VHT80	MCS0	1	42	5210	0.30	12.46	24.00	-0.93	Pass	12

<5260 MHz ~ 5320 MHz>											
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power with duty factor (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)	EIRP Power Limit (dBm)	Pass/Fail	Power Setting
					Ant 1	Ant 1	Ant 1	Ant 1			Ant 1
11a	6Mbps	1	52	5260	0.09	17.23	23.98	-0.93	26.99	Pass	17
11a	6Mbps	1	60	5300	0.09	16.96	23.98	-0.93	26.99	Pass	17
11a	6Mbps	1	64	5320	0.09	17.00	23.98	-0.93	26.99	Pass	17
HT20	MCS0	1	52	5260	0.10	16.77	23.98	-0.93	26.99	Pass	17
HT20	MCS0	1	60	5300	0.10	16.81	23.98	-0.93	26.99	Pass	17
HT20	MCS0	1	64	5320	0.10	16.69	23.98	-0.93	26.99	Pass	17
HT40	MCS0	1	54	5270	0.16	17.56	23.98	-0.93	26.99	Pass	17
HT40	MCS0	1	62	5310	0.16	15.28	23.98	-0.93	26.99	Pass	15
VHT20	MCS0	1	52	5260	0.07	16.83	23.98	-0.93	26.99	Pass	17
VHT20	MCS0	1	60	5300	0.07	16.88	23.98	-0.93	26.99	Pass	17
VHT20	MCS0	1	64	5320	0.07	16.75	23.98	-0.93	26.99	Pass	17
VHT40	MCS0	1	54	5270	0.16	17.60	23.98	-0.93	26.99	Pass	17
VHT40	MCS0	1	62	5310	0.16	15.32	23.98	-0.93	26.99	Pass	15
VHT80	MCS0	1	58	5290	0.30	13.28	23.98	-0.93	26.99	Pass	12.5



<5500 MHz ~ 5720 MHz											
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power with duty factor (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)	EIRP Power Limit (dBm)	Pass/Fail	Power Setting
					Ant 1	Ant 1	Ant 1	Ant 1			Ant 1
11a	6Mbps	1	100	5500	0.09	16.84	23.98	0.32	26.99	Pass	17
11a	6Mbps	1	116	5580	0.09	17.12	23.98	0.32	26.99	Pass	17
11a	6Mbps	1	140	5700	0.09	16.82	23.98	0.32	26.99	Pass	17
HT20	MCS0	1	100	5500	0.10	16.65	23.98	0.32	26.99	Pass	17
HT20	MCS0	1	116	5580	0.10	16.87	23.98	0.32	26.99	Pass	17
HT20	MCS0	1	140	5700	0.10	16.65	23.98	0.32	26.99	Pass	17
HT40	MCS0	1	102	5510	0.16	17.36	23.98	0.32	26.99	Pass	17
HT40	MCS0	1	110	5550	0.16	17.45	23.98	0.32	26.99	Pass	17
HT40	MCS0	1	134	5670	0.16	17.63	23.98	0.32	26.99	Pass	17
VHT20	MCS0	1	100	5500	0.07	16.70	23.98	0.32	26.99	Pass	17
VHT20	MCS0	1	116	5580	0.07	16.95	23.98	0.32	26.99	Pass	17
VHT20	MCS0	1	140	5700	0.07	16.72	23.98	0.32	26.99	Pass	17
VHT40	MCS0	1	102	5510	0.16	17.41	23.98	0.32	26.99	Pass	17
VHT40	MCS0	1	110	5550	0.16	17.50	23.98	0.32	26.99	Pass	17
VHT40	MCS0	1	134	5670	0.16	17.68	23.98	0.32	26.99	Pass	17
VHT80	MCS0	1	106	5530	0.30	16.17	23.98	0.32	26.99	Pass	16
VHT80	MCS0	1	122	5610	0.30	16.41	23.98	0.32	26.99	Pass	16

<5500 MHz ~ 5720 MHz straddle channel											
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power with duty factor (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)	EIRP Power Limit (dBm)	Pass/Fail	Power Setting
					Ant 1	Ant 1	Ant 1	Ant 1			Ant 1
11a	6Mbps	1	144	5720	0.09	16.65	23.98	0.32	26.99	Pass	17
HT20	MCS0	1	144	5720	0.10	16.58	23.98	0.32	26.99	Pass	17
HT40	MCS0	1	142	5710	0.16	17.16	23.98	0.32	26.99	Pass	17
VHT20	MCS0	1	144	5720	0.07	16.63	23.98	0.32	26.99	Pass	17
VHT40	MCS0	1	142	5710	0.16	17.22	23.98	0.32	26.99	Pass	17
VHT80	MCS0	1	138	5690	0.30	16.35	23.98	0.32	26.99	Pass	16



<5745 MHz ~ 5825 MHz>										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power with duty factor (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)	Pass/Fail	Power Setting
					Ant 1	Ant 1	Ant 1	Ant 1		Ant 1
11a	6Mbps	1	149	5745	0.09	16.73	30.00	0.46	Pass	17
11a	6Mbps	1	157	5785	0.09	16.32	30.00	0.46	Pass	17
11a	6Mbps	1	165	5825	0.09	16.02	30.00	0.46	Pass	17
HT20	MCS0	1	149	5745	0.10	16.55	30.00	0.46	Pass	17
HT20	MCS0	1	157	5785	0.10	16.11	30.00	0.46	Pass	17
HT20	MCS0	1	165	5825	0.10	16.03	30.00	0.46	Pass	17
HT40	MCS0	1	151	5755	0.16	17.00	30.00	0.46	Pass	17
HT40	MCS0	1	159	5795	0.16	16.56	30.00	0.46	Pass	17
VHT20	MCS0	1	149	5745	0.07	16.62	30.00	0.46	Pass	17
VHT20	MCS0	1	157	5785	0.07	16.20	30.00	0.46	Pass	17
VHT20	MCS0	1	165	5825	0.07	16.09	30.00	0.46	Pass	17
VHT40	MCS0	1	151	5755	0.16	17.04	30.00	0.46	Pass	17
VHT40	MCS0	1	159	5795	0.16	16.63	30.00	0.46	Pass	17
VHT80	MCS0	1	155	5775	0.30	15.63	30.00	0.46	Pass	16

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

<FCC 14-30 CFR 15.407>

For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band.

For the 5.25–5.725 GHz bands, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band.

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

For Straddle Channel, According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, If the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04.

Section F) Maximum power spectral density.

For devices operating in the bands UNII-1/2A/2C

Method SA-2

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 1 MHz.
- Set VBW $\geq$ 3 MHz.
- Number of points in sweep $\geq$ 2 Span / RBW.
- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6$ dB if the duty cycle is 25 percent.

For devices operating in the band UNII-3


Method SA-2

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 500KHz (or 300 kHz if the SA can't set RBW=500KHz).
- Set VBW $\geq$ 1 MHz.
- Number of points in sweep $\geq$ 2 Span / RBW.
- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- If the SA can't set RBW=500KHz, then add $10 \log(500\text{kHz}/\text{RBW})$ to the test result.
- Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6$ dB if the duty cycle is 25 percent.

1. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Unwanted Emissions Measurement

This section as specified in FCC Part 15.407(b) is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement. The unwanted emissions shall comply with 15.407(b)(1) to (6), and restricted bands per FCC Part 15.205.

3.4.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5150-5250 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of -27dBm/MHz.

For transmitters operating in the 5250-5350 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of -27 dBm/MHz. Devices operating in the 5250-5350 MHz band that generate emissions in the 5150-5250 MHz band must meet all applicable technical requirements for operation in the 5150-5250 MHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of -27 dBm/MHz in the 5150-5250 MHz band.

For transmitters operating in the 5470-5600 MHz and 5650-5725MHz band: all emissions outside of the 5470-5600 MHz and 5650-5725MHz band shall not exceed an EIRP of -27 dBm/MHz.

- (2) For transmitters operating in the 5.725-5.85 GHz band:
- 15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

(3) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

(4) EIRP (dBm)	Field Strength at 3m (dBμV/m)
- 27	68.2

Note: The following formula is used to convert the EIRP to field strength.

$$\text{EIRP} = E_{\text{Meas}} + 20\log (d_{\text{Meas}}) - 104.7$$

where

EIRP is the equivalent isotropically radiated power, in dBm

E_{Meas} is the field strength of the emission at the measurement distance, in dBμV/m

d_{Meas} is the measurement distance, in m

3.4.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures


1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04.
Section G) Unwanted emissions measurement.
(1) Procedure for Unwanted Emissions Measurements Below 1000MHz
 - RBW = 120 kHz
 - VBW = 300 kHz
 - Detector = Peak
 - Trace mode = max hold(2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
 - RBW = 1 MHz
 - VBW $\geq$ 3 MHz
 - Detector = Peak
 - Sweep time = auto
 - Trace mode = max hold(3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz
 - RBW = 1 MHz
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on.
2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.4.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz





3.4.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.4.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.4.7 Duty Cycle

Please refer to Appendix D.

3.4.8 Test Result of Radiated Spurious Emissions (30MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.6 Antenna Requirements

3.6.1 Standard Applicable

According to FCC 47 CFR Section 15.407(a)(1)(2), if transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.6.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver	Keysight	N9038A	MY57290151	3Hz~8.5GHz;Ma x 30dBm	Jul. 04, 2024	Oct. 26, 2024	Jul. 03, 2025	Radiation (03CH05-KS)
EXA Spectrum Analyzer	Keysight	N9010B	MY60242126	10Hz-44G,MAX 30dB	Oct. 10, 2024	Oct. 26, 2024	Oct. 09, 2025	Radiation (03CH05-KS)
Loop Antenna	R&S	HFH2-Z2E	101125	9kHz~30MHz	Sep. 08, 2024	Oct. 26, 2024	Sep. 07, 2025	Radiation (03CH05-KS)
Bilog Antenna	TeseQ	CBL6111D	49921	30MHz-1GHz	Apr. 18, 2024	Oct. 26, 2024	Apr. 17, 2025	Radiation (03CH05-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00218642	1GHz~18GHz	Apr. 11, 2024	Oct. 26, 2024	Apr. 10, 2025	Radiation (03CH05-KS)
SHF-EHF Horn	Com-power	AH-840	101093	18GHz~40GHz	Jan. 06, 2024	Oct. 26, 2024	Jan. 05, 2025	Radiation (03CH05-KS)
Amplifier	SONOMA	310N	381512	9KHz-1GHz	Jan. 02, 2024	Oct. 26, 2024	Jan. 01, 2025	Radiation (03CH05-KS)
Amplifier	EM	EM18G40GA	060852	18~40GHz	Jan. 02, 2024	Oct. 26, 2024	Jan. 01, 2025	Radiation (03CH05-KS)
high gain Amplifier	EM	EM01G18GA	060843	1Ghz-18Ghz	Jan. 03, 2024	Oct. 26, 2024	Jan. 02, 2025	Radiation (03CH05-KS)
Amplifier	EM	EM01G18GA	060833	1Ghz-18Ghz	Jan. 03, 2024	Oct. 26, 2024	Jan. 02, 2025	Radiation (03CH05-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Oct. 26, 2024	NCR	Radiation (03CH05-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Oct. 26, 2024	NCR	Radiation (03CH05-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Oct. 26, 2024	NCR	Radiation (03CH05-KS)
EMI Receiver	R&S	ESC17	100768	9kHz~7GHz;	Apr 18, 2024	Dec. 18, 2024	Apr 17, 2025	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Aug. 20, 2024	Dec. 18, 2024	Aug. 19, 2025	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	Apr. 18, 2024	Dec. 18, 2024	Apr. 17, 2025	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 09, 2024	Dec. 18, 2024	Oct. 08, 2025	Conduction (CO01-KS)
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 10, 2024	Nov. 07, 2024~Nov. 13, 2024	Oct. 09, 2025	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 02, 2024	Nov. 07, 2024~Nov. 13, 2024	Jan. 01, 2025	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 02, 2024	Nov. 07, 2024~Nov. 13, 2024	Jan. 01, 2025	Conducted (TH01-KS)

NCR: No Calibration Required

5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Conducted Spurious Emission & Bandedge	±2.22 dB
Occupied Channel Bandwidth	±0.1%
Conducted Power	±0.50 dB
Conducted Power Spectral Density	±0.90 dB
Frequency	±0.04 Hz

Uncertainty of AC Conducted Emission Measurement (0.15 MHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.84 dB
---	---------

Uncertainty of Radiated Emission Measurement (9 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.30 dB
---	---------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	6.02 dB
---	---------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.22 dB
---	---------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.34 dB
---	---------

----- THE END -----



Appendix A. Conducted Test Results



Ambient Condition: 25 °C, 45 %RH

Test Date: 2024/11/07~2024/11/13

Test Engineer: Jacob Zhang


Emission Bandwidth

Test Result

TestMode	Antenna	Freq(MHz)	26dB EBW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11A	Ant1	5180	22.32	5168.88	5191.20	---	---
		5220	21.68	5209.56	5231.24	---	---
		5240	22.68	5229.00	5251.68	---	---
		5260	22.28	5249.00	5271.28	---	---
		5300	22.40	5288.92	5311.32	---	---
		5320	22.92	5308.60	5331.52	---	---
		5500	22.24	5489.04	5511.28	---	---
		5580	22.32	5569.04	5591.36	---	---
		5700	21.44	5689.60	5711.04	---	---
		5745	22.84	5733.64	5756.48	---	---
		5785	21.76	5774.24	5796.00	---	---
11AC20SISO	Ant1	5825	22.04	5814.08	5836.12	---	---
		5180	22.32	5169.24	5191.56	---	---
		5220	22.88	5208.64	5231.52	---	---
		5240	22.36	5228.76	5251.12	---	---
		5260	22.52	5248.76	5271.28	---	---
		5300	22.52	5288.76	5311.28	---	---
		5320	22.48	5308.72	5331.20	---	---
		5500	22.96	5488.72	5511.68	---	---
		5580	21.88	5569.28	5591.16	---	---
		5700	22.04	5688.96	5711.00	---	---
		5745	22.32	5733.88	5756.20	---	---
11AC40SISO	Ant1	5785	21.76	5774.44	5796.20	---	---
		5825	22.56	5813.44	5836.00	---	---
		5190	41.68	5169.68	5211.36	---	---
		5230	41.20	5209.52	5250.72	---	---
		5270	41.52	5249.44	5290.96	---	---
		5310	41.76	5289.28	5331.04	---	---
		5510	41.52	5489.36	5530.88	---	---
		5550	41.60	5529.28	5570.88	---	---
11AC80SISO	Ant1	5670	41.60	5649.20	5690.80	---	---
		5755	41.84	5734.12	5775.96	---	---
		5795	42.24	5773.88	5816.12	---	---
		5210	99.52	5161.20	5260.72	---	---
		5290	100.64	5239.60	5340.24	---	---
	Ant1	5530	100.48	5479.92	5580.40	---	---
		5610	108.16	5551.92	5660.08	---	---
		5775	107.84	5717.08	5824.92	---	---




Test Graphs






11A_Ant1_5240




11A_Ant1_5260






11A_Ant1_5300




11A_Ant1_5320






11A_Ant1_5500




11A_Ant1_5580






11A_Ant1_5700




11A_Ant1_5745







11A_Ant1_5785



11A_Ant1_5825








11AC20SISO_Ant1_5260






11AC20SISO_Ant1_5300




11AC20SISO_Ant1_5320






11AC20SISO_Ant1_5500




11AC20SISO_Ant1_5580







11AC20SISO_Ant1_5700




11AC20SISO_Ant1_5745









11AC40SISO_Ant1_5190




11AC40SISO_Ant1_5230








11AC40SISO_Ant1_5510




11AC40SISO_Ant1_5550






11AC40SISO_Ant1_5670




11AC40SISO_Ant1_5755







11AC40SISO_Ant1_5795




11AC80SISO_Ant1_5210








11AC80SISO_Ant1_5610



11AC80SISO_Ant1_5775






Occupied channel bandwidth

Test Result

TestMode	Antenna	Freq(MHz)	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11A	Ant1	5180	17.143	5171.4486	5188.5914	---	---
		5220	17.183	5211.4086	5228.5914	---	---
		5240	17.183	5231.4486	5248.6314	---	---
		5260	17.183	5251.3686	5268.5514	---	---
		5300	17.143	5291.4086	5308.5514	---	---
		5320	17.223	5311.3686	5328.5914	---	---
		5500	17.223	5491.3686	5508.5914	---	---
		5580	17.183	5571.3686	5588.5514	---	---
		5700	17.183	5691.3287	5708.5115	---	---
		5745	17.143	5736.3686	5753.5115	---	---
		5785	17.143	5776.3686	5793.5115	---	---
		5825	17.183	5816.3287	5833.5115	---	---
11AC20SISO	Ant1	5180	18.302	5170.8492	5189.1508	---	---
		5220	18.302	5210.8492	5229.1508	---	---
		5240	18.302	5230.8492	5249.1508	---	---
		5260	18.262	5250.8492	5269.1109	---	---
		5300	18.302	5290.8492	5309.1508	---	---
		5320	18.302	5310.8492	5329.1508	---	---
		5500	18.302	5490.8492	5509.1508	---	---
		5580	18.262	5570.8492	5589.1109	---	---
		5700	18.262	5690.8092	5709.0709	---	---
		5745	18.302	5735.8092	5754.1109	---	---
		5785	18.302	5775.8092	5794.1109	---	---
		5825	18.302	5815.8092	5834.1109	---	---
11AC40SISO	Ant1	5190	36.523	5171.7782	5208.3017	---	---
		5230	36.523	5211.7782	5248.3017	---	---
		5270	36.523	5251.7782	5288.3017	---	---
		5310	36.603	5291.6983	5328.3017	---	---
		5510	36.603	5491.6983	5528.3017	---	---
		5550	36.444	5531.7782	5568.2218	---	---
		5670	36.523	5651.6983	5688.2218	---	---
		5755	36.683	5736.6184	5773.3017	---	---
		5795	36.603	5776.6184	5813.2218	---	---
11AC80SISO	Ant1	5210	76.563	5171.9580	5248.5215	---	---
		5290	76.563	5251.7982	5328.3616	---	---
		5530	76.084	5491.9580	5568.0420	---	---
		5610	76.404	5571.6384	5648.0420	---	---
		5775	76.404	5736.6384	5813.0420	---	---




Test Graphs








11A_Ant1_5240



11A_Ant1_5260











11A_Ant1_5700




11A_Ant1_5745






11A_Ant1_5785




11A_Ant1_5825







11AC20SISO_Ant1_5180




11AC20SISO_Ant1_5220








11AC20SISO_Ant1_5300




11AC20SISO_Ant1_5320






11AC20SISO_Ant1_5500




11AC20SISO_Ant1_5580






11AC20SISO_Ant1_5700




11AC20SISO_Ant1_5745







11AC20SISO_Ant1_5785




11AC20SISO_Ant1_5825








11AC40SISO_Ant1_5270




11AC40SISO_Ant1_5310







11AC40SISO_Ant1_5510




11AC40SISO_Ant1_5550










11AC40SISO_Ant1_5795



11AC80SISO_Ant1_5210










Min emission bandwidth

Test Result B4

TestMode	Antenna	Freq(MHz)	6dB EBW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11A	Ant1	5745	15.16	5737.40	5752.56	0.5	PASS
		5785	15.76	5777.08	5792.84	0.5	PASS
		5825	15.64	5817.08	5832.72	0.5	PASS
11AC20SISO	Ant1	5745	15.36	5737.20	5752.56	0.5	PASS
		5785	15.08	5777.48	5792.56	0.5	PASS
		5825	15.88	5816.60	5832.48	0.5	PASS
11AC40SISO	Ant1	5755	35.12	5737.40	5772.52	0.5	PASS
		5795	35.52	5777.24	5812.76	0.5	PASS
11AC80SISO	Ant1	5775	75.20	5737.40	5812.60	0.5	PASS




Test Graphs B4





11A_Ant1_5825



11AC20SISO_Ant1_5745

