

FCC Test Report

(PART 27)

Report No.: RF181205C03

FCC ID: B32V400M4GWW

Test Model: V400m Plus 4G WW

Received Date: Dec. 05, 2018

Test Date: Dec. 22, 2018 ~ Jan. 07, 2019

Issued Date: Jan. 14, 2019

Applicant: Verifone, Inc.

Address: 1400 West Stanford Ranch Road Suite 200 Rocklin CA 95765 USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan
(R.O.C)

Test Location : No. 19, Hwa Ya 2nd Rd, Wen Hwa Vil, Kwei Shan Dist., Taoyuan City
33383, Taiwan (R.O.C)

FCC Registration /
Designation Number: 788550 / TW0003



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies

Table of Contents

Release Control Record	4
1 Certificate of Conformity	5
2 Summary of Test Results.....	6
2.1 Measurement Uncertainty.....	6
2.2 Test Site and Instruments	7
3 General Information	9
3.1 General Description of EUT	9
3.2 Configuration of System under Test.....	10
3.2.1 Description of Support Units.....	10
3.3 Test Mode Applicability and Tested Channel Detail	11
3.4 EUT Operating Conditions	12
3.5 General Description of Applied Standards.....	12
4 Test Types and Results.....	13
4.1 Output Power Measurement.....	13
4.1.1 Limits of Output Power Measurement	13
4.1.2 Test Procedures.....	13
4.1.3 Test Setup.....	14
4.1.4 Test Results	15
4.2 Modulation Characteristics Measurement	20
4.2.1 Limits of Modulation Characteristics	20
4.2.2 Test Setup.....	20
4.2.3 Test Procedure	20
4.2.4 Test Results	21
4.3 Frequency Stability Measurement	22
4.3.1 Limits of Frequency Stability Measurement	22
4.3.2 Test Procedure	22
4.3.3 Test Setup.....	22
4.3.4 Test Results	23
4.4 Occupied Bandwidth Measurement.....	27
4.4.1 Limits of Occupied Bandwidth Measurement	27
4.4.2 Test Procedure	27
4.4.3 Test Setup.....	27
4.4.4 Test Results	28
4.5 Out-of-Band Emissions Measurement.....	30
4.5.1 Limits of Out-of-Band Emissions Measurement	30
4.5.2 Test Setup.....	30
4.5.3 Test Procedures.....	30
4.5.4 Test Results	31
4.6 Peak to Average Ratio	39
4.6.1 Limits of Peak to Average Ratio Measurement	39
4.6.2 Test Setup.....	39
4.6.3 Test Procedures.....	39
4.6.4 Test Results	40
4.7 Conducted Spurious Emissions.....	42
4.7.1 Limits of Conducted Spurious Emissions Measurement.....	42
4.7.2 Test Setup.....	42
4.7.3 Test Procedure	42
4.7.4 Test Results	43
4.8 Radiated Emission Measurement.....	55
4.8.1 Limits of Radiated Emission Measurement	55
4.8.2 Test Procedure	55
4.8.3 Deviation from Test Standard	55
4.8.4 Test Setup.....	56

4.8.5 Test Results	57
5 Pictures of Test Arrangements	69
Appendix – Information of the Testing Laboratories	70

Release Control Record

Issue No.	Description	Date Issued
RF181205C03	Original Release	Jan. 14, 2019

1 Certificate of Conformity

Product: Point of Sale Terminal

Brand: Verifone

Test Model: V400m Plus 4G WW

Sample Status: Identical Prototype

Applicant: Verifone, Inc.

Test Date: Dec. 22, 2018 ~ Jan. 07, 2019

Standards: FCC Part 27, Subpart C, M

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Flora Huang, **Date:** Jan. 14, 2019
Flora Huang / Specialist

Approved by : Dylan Chiou, **Date:** Jan. 14, 2019
Dylan Chiou / Project Engineer

2 Summary of Test Results

Applied Standard: FCC Part 27 & Part 2			
FCC Clause	Test Item	Result	Remarks
2.1046 27.50(h)(2)	Equivalent Isotropic Radiated Power	Pass	Meet the requirement of limit.
2.1047	Modulation Characteristics	Pass	Meet the requirement.
2.1055 27.54	Frequency Stability	Pass	Meet the requirement of limit.
2.1049 27.53(m)(6)	Occupied Bandwidth	Pass	Meet the requirement of limit.
--	Peak to Average Ratio	Pass	Meet the requirement of limit.
2.1051 27.53(l)(m)(4)(6)	Out-of-Band Emissions Measurements	Pass	Meet the requirement of limit.
2.1051 27.53(m)(4)(6)	Conducted Spurious Emissions	Pass	Meet the requirement of limit.
2.1053 27.53(m)(4)(6)	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -14.67 dB at 7680.00 MHz.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Radiated Emissions up to 1 GHz	30 MHz ~ 200 MHz	2.93 dB
	200 MHz ~ 1000 MHz	2.95 dB
Radiated Emissions above 1 GHz	1 GHz ~ 18 GHz	2.26 dB
	18 GHz ~ 40 GHz	1.94 dB

2.2 Test Site and Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver Agilent	N9038A	MY51210203	Mar. 16, 2018	Mar. 15, 2019
Spectrum Analyzer Agilent	N9010A	MY52220314	Dec. 13, 2018	Dec. 12, 2019
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Jan. 11, 2018	Jan. 10, 2019
HORN Antenna SCHWARZBECK	BBHA 9170	148	Nov. 25, 2018	Nov. 24, 2019
HORN Antenna SCHWARZBECK	BBHA 9120D	9120D-969	Nov. 25, 2018	Nov. 24, 2019
BILOG Antenna SCHWARZBECK	VULB 9168	9168-472	Nov. 23, 2018	Nov. 22, 2019
Fixed Attenuator Mini-Circuits	MDCS18N-10	MDCS18N-10-01	Apr. 16, 2018	Apr. 15, 2019
MXG Vector signal generator Agilent	N5182B	MY53050430	Nov. 19, 2018	Nov. 18, 2019
Preamplifier EMCI	EMC 330H	980112	Oct. 12, 2018	Oct. 11, 2019
Preamplifier EMCI	EMC 012645	980115	Oct. 12, 2018	Oct. 11, 2019
Preamplifier EMCI	EMC 184045	980116	Oct. 12, 2018	Oct. 11, 2019
Power Meter Anritsu	ML2495A	1012010	Sep. 05, 2018	Sep. 04, 2019
Power Sensor Anritsu	MA2411B	1315050	Sep. 04, 2018	Sep. 03, 2019
RF Coaxial Cable HUBER+SUHNNER	EMC104-SM-SM- 8000&3000	140811+170717	Oct. 12, 2018	Oct. 11, 2019
RF Coaxial Cable HUBER+SUHNNER	SUCOFLEX 104	EMC104-SM-SM- 1000(140807)	Oct. 12, 2018	Oct. 11, 2019
RF Coaxial Cable WOKEN	8D-FB	Cable-Ch10-01	Oct. 12, 2018	Oct. 11, 2019
Boresight Antenna Fixture	FBA-01	FBA-SIP01	NA	NA
Software BV ADT	E3 6.120103	NA	NA	NA
Antenna Tower MF	MFA-440H	NA	NA	NA
Turn Table MF	MFT-201SS	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA

Radio Communication Analyzer Anritsu	MT8820C	6201300640	Aug. 16, 2017	Aug. 15, 2019
Temperature & Humidity Chamber	GTH-120-40-CP-AR	MAA1306-019	Sep. 05, 2018	Sep. 04, 2019

- Note:
1. The calibration interval of the above test instruments is 12 / 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The calibration interval of the loop antenna is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
 3. The test was performed in HwaYa Chamber 10.
 4. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
 5. The FCC Site Registration No. is 690701.
 6. The IC Site Registration No. is 7450F-10.

3 General Information

3.1 General Description of EUT

Product	Point of Sale Terminal	
Brand	Verifone	
Test Model	V400m Plus 4G WW	
Status of EUT	Identical Prototype	
Power Supply Rating	5.0 Vdc (Adapter) 3.85 Vdc (Li-ion battery)	
Modulation Type	QPSK, 16QAM	
Frequency Range	LTE Band 7 (Channel Bandwidth: 5 MHz)	2502.5 ~ 2567.5 MHz
	LTE Band 7 (Channel Bandwidth: 10 MHz)	2505 ~ 2565 MHz
	LTE Band 7 (Channel Bandwidth: 15 MHz)	2507.5 ~ 2562.5 MHz
	LTE Band 7 (Channel Bandwidth: 20 MHz)	2510 ~ 2560 MHz
Max. EIRP Power	LTE Band 7 (Channel Bandwidth: 5 MHz)	272.27 mW
	LTE Band 7 (Channel Bandwidth: 10 MHz)	291.07 mW
	LTE Band 7 (Channel Bandwidth: 15 MHz)	309.74 mW
	LTE Band 7 (Channel Bandwidth: 20 MHz)	326.59 mW
Emission Designator	LTE Band 7 (Channel Bandwidth: 5 MHz)	4M50G7D
	LTE Band 7 (Channel Bandwidth: 10 MHz)	9M00G7D
	LTE Band 7 (Channel Bandwidth: 15 MHz)	13M5G7D
	LTE Band 7 (Channel Bandwidth: 20 MHz)	18M0W7D
Antenna Type	Fixed Internal Antenna	
Antenna Gain	2.5 dBi	
Accessory Device	Refer to Note as below	
Data Cable Supplied	Refer to Note as below	

Note:


1. The EUT contains following accessory devices.

Product	Brand	Model	Description
Adapter 1	Verifone	AM11A-050A	I/P: 100-240 Vac, 50/60 Hz, 500 mA O/P: 5 Vdc, 2.2 A 1.75m non-shielded cable w/o core Manufacturer: Pihong
Adapter 2	Verifone	VF0402	I/P: 100-240 Vac, 50/60 Hz, 500 mA O/P: 5 Vdc, 2.2 A 1.75m non-shielded cable w/o core Manufacturer: Salcomp
Battery 1	Verifone	BPK475-001	3.85 Vdc, 2890 mAh
Battery 2	Verifone	BPK475-001	3.85 Vdc, 2900 mAh


2. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.

3.2 Configuration of System under Test

<Radiated Emission Test>



<E.R.P. Test>



3.2.1 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units.

3.3 Test Mode Applicability and Tested Channel Detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis, and antenna ports.

The worst case was found when positioned as the table below. Following channel(s) was (were) selected for the final test as listed below:

Band	EIRP	Radiated Emission
LTE Band 7	X-plane	Z-axis

LTE Band 7

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
-	EIRP	20775 to 21425	20775, 21100, 21425	5 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20800 to 21400	20800, 21100, 21400	10 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20825 to 21375	20825, 21100, 21375	15 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20850 to 21350	20850, 21100 21350	20 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
-	Modulation Characteristics	20850 to 21350	21110	20 MHz	QPSK, 16QAM	100 RB / 0 RB Offset
-	Frequency Stability	20775 to 21425	20775, 21425	5 MHz	QPSK	1 RB / 0 RB Offset
		20800 to 21400	20800, 21400	10 MHz	QPSK	1 RB / 0 RB Offset
		20825 to 21375	20825, 21375	15 MHz	QPSK	1 RB / 0 RB Offset
		20850 to 21350	20850, 21350	20 MHz	QPSK	1 RB / 0 RB Offset
-	Occupied Bandwidth	20775 to 21425	20775, 21100, 21425	5 MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		20800 to 21400	20800, 21100, 21400	10 MHz	QPSK, 16QAM	50 RB / 0 RB Offset
		20825 to 21375	20825, 21100, 21375	15 MHz	QPSK, 16QAM	75 RB / 0 RB Offset
		20850 to 21350	20850, 21100 21350	20 MHz	QPSK, 16QAM	100 RB / 0 RB Offset
-	Peak to Average Ratio	20775 to 21425	20775, 21100, 21425	5 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20800 to 21400	20800, 21100, 21400	10 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20825 to 21375	20825, 21100, 21375	15 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20850 to 21350	20850, 21100 21350	20 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
-	Out-of-Band Emissions	20775 to 21425	20775, 21425	5 MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		20800 to 21400	20800, 21400	10 MHz	QPSK, 16QAM	50 RB / 0 RB Offset
		20825 to 21375	20825, 21375	15 MHz	QPSK, 16QAM	75 RB / 0 RB Offset
		20850 to 21350	20850, 21350	20 MHz	QPSK, 16QAM	100 RB / 0 RB Offset
-	Conducted Emission	20775 to 21425	20775, 21100, 21425	5 MHz	QPSK	1 RB / 0 RB Offset
		20800 to 21400	20800, 21100, 21400	10 MHz	QPSK	1 RB / 0 RB Offset
		20825 to 21375	20825, 21100, 21375	15 MHz	QPSK	1 RB / 0 RB Offset
		20850 to 21350	20850, 21100 21350	20 MHz	QPSK	1 RB / 0 RB Offset
-	Radiated Emission	20775 to 21425	20775, 21100, 21425	5 MHz	QPSK	1 RB / 0 RB Offset
		20850 to 21350	20850, 21100 21350	20 MHz	QPSK	1 RB / 0 RB Offset

Note: This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

Test Condition:

Test Item	Environmental Conditions	Input Power	Tested By
EIRP	25 deg. C, 65 % RH	120 Vac, 60 Hz	Jisyong Wang
Modulation Characteristics	25 deg. C, 65 % RH	3.85 Vdc	Getaz Yang
Frequency Stability	25 deg. C, 65 % RH	3.85 Vdc	Getaz Yang
Occupied Bandwidth	25 deg. C, 65 % RH	3.85 Vdc	Getaz Yang
Out-of-Band Emissions	25 deg. C, 65 % RH	3.85 Vdc	Getaz Yang
Peak to Average Ratio	25 deg. C, 65 % RH	3.85 Vdc	Getaz Yang
Conducted Emission	25 deg. C, 65 % RH	3.85 Vdc	Getaz Yang
Radiated Emission	25 deg. C, 65 % RH	120 Vac, 60 Hz	Jisyong Wang

3.4 EUT Operating Conditions

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 27

KDB 971168 D01 Power Meas License Digital Systems v03r01

ANSI/TIA/EIA-603-E 2016

ANSI 63.26-2015

Note: All test items have been performed and recorded as per the above standards.

4 Test Types and Results

4.1 Output Power Measurement

4.1.1 Limits of Output Power Measurement

The radiated peak output power shall be according to the specific rule Part 27.50(h)(2) that “Mobile stations are limited to 2.0 watts EIRP. All user stations are limited to 2 watts transmitter output power” and 27.50(i) specific that “Peak transmit power must be measure over any interval of continuous transmission using instrumentation calibration in terms of rms-equivalent voltage.”

4.1.2 Test Procedures

EIRP Measurement:

- a. All measurements were done at low, middle and high operational frequency range. RBW and VBW is 10 MHz for LTE mode.
- b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m (below or equal 1 GHz) and/or 1.5 m (above 1 GHz) height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.
- c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value” of step b. Record the power level of S.G.
- d. $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}.$


Conducted Power Measurement:

- a. The EUT was set up for the maximum power with LTE link data modulation and link up with simulator.
- b. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.


4.1.3 Test Setup

EIRP / ERP Measurement:

<Radiated Emission below or equal 1 GHz>




<Radiated Emission above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

Conducted Power Measurement:



4.1.4 Test Results

Conducted Output Power (dBm)

LTE Band 7															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		20850	21100	21350				Channel		20825	21100	21375	
		Frequency (MHz)		2510.0	2535.0	2560.0				Frequency (MHz)		2507.5	2535.0	2562.5	
20M	QPSK	1	0	23.02	23.07	23.16	0	15M	QPSK	1	0	22.93	23.05	23.14	0
		1	50	22.16	22.21	22.30	0			1	37	22.16	22.15	22.20	0
		1	99	22.26	22.31	22.40	0			1	74	22.17	22.23	22.39	0
		50	0	21.98	22.03	22.12	1			36	0	21.91	22.02	22.08	1
		50	25	21.60	21.65	21.74	1			36	19	21.55	21.63	21.71	1
		50	50	21.68	21.73	21.82	1			36	39	21.61	21.66	21.82	1
		100	0	21.88	21.93	22.02	1			75	0	21.81	21.83	22.02	1
	16QAM	1	0	22.03	22.08	22.17	1		16QAM	1	0	22.00	22.05	22.15	1
		1	50	21.17	21.22	21.31	1			1	37	21.10	21.16	21.28	1
		1	99	21.27	21.32	21.41	1			1	74	21.20	21.32	21.41	1
		50	0	20.99	21.04	21.13	2			36	0	20.90	21.00	21.05	2
		50	25	20.61	20.66	20.75	2			36	19	20.56	20.56	20.66	2
		50	50	20.69	20.74	20.83	2			36	39	20.69	20.67	20.75	2
		100	0	20.89	20.94	21.03	2			75	0	20.85	20.88	21.02	2
10M	QPSK	1	0	22.86	22.94	22.96	0	5M	QPSK	1	0	22.92	22.90	22.92	0
		1	24	22.08	22.03	22.12	0			1	12	22.09	22.05	22.18	0
		1	49	22.16	22.24	22.32	0			1	24	22.19	22.17	22.23	0
		25	0	21.82	21.88	22.04	1			12	0	21.94	21.79	21.92	1
		25	12	21.50	21.58	21.63	1			12	6	21.56	21.61	21.54	1
		25	25	21.54	21.53	21.72	1			12	13	21.60	21.55	21.66	1
		50	0	21.84	21.77	21.83	1			25	0	21.80	21.87	21.79	1
	16QAM	1	0	21.91	21.98	22.10	1		16QAM	1	0	21.99	21.94	22.01	1
		1	24	21.16	21.14	21.19	1			1	12	21.01	21.03	21.30	1
		1	49	21.06	21.27	21.30	1			1	24	21.20	21.20	21.28	1
		25	0	20.87	20.88	20.95	2			12	0	20.75	20.97	21.10	2
		25	12	20.52	20.52	20.59	2			12	6	20.50	20.52	20.60	2
		25	25	20.61	20.57	20.66	2			12	13	20.59	20.63	20.75	2
		50	0	20.81	20.85	20.88	2			25	0	20.71	20.81	21.00	2

EIRP Power (dBm)

LTE Band 7							
Channel Bandwidth: 5 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
X	20775	2502.5	-14.31	38.52	24.21	263.63	H
	21100	2535.0	-14.60	38.36	23.76	237.68	
	21425	2567.5	-14.23	38.58	24.35	272.27	
	20775	2502.5	-20.06	38.92	18.86	76.91	V
	21100	2535.0	-20.68	39.26	18.58	72.11	
	21425	2567.5	-20.16	39.22	19.06	80.54	
Channel Bandwidth: 5 MHz / 16QAM							
X	20775	2502.5	-15.34	38.52	23.18	207.97	H
	21100	2535.0	-15.63	38.36	22.73	187.50	
	21425	2567.5	-15.26	38.58	23.32	214.78	
	20775	2502.5	-21.09	38.92	17.83	60.67	V
	21100	2535.0	-21.71	39.26	17.55	56.89	
	21425	2567.5	-21.19	39.22	18.03	63.53	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

LTE Band 7							
Channel Bandwidth: 10 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
X	20800	2505.0	-14.15	38.65	24.50	281.84	H
	21100	2535.0	-14.31	38.36	24.05	254.10	
	21400	2565.0	-13.85	38.49	24.64	291.07	
	20800	2505.0	-19.69	38.84	19.15	82.22	V
	21100	2535.0	-20.39	39.26	18.87	77.09	
	21400	2565.0	-19.75	39.10	19.35	86.10	
Channel Bandwidth: 10 MHz / 16QAM							
X	20800	2505.0	-15.20	38.65	23.45	221.31	H
	21100	2535.0	-15.36	38.36	23.00	199.53	
	21400	2565.0	-14.90	38.49	23.59	228.56	
	20800	2505.0	-20.74	38.84	18.10	64.57	V
	21100	2535.0	-21.44	39.26	17.82	60.53	
	21400	2565.0	-20.80	39.10	18.30	67.61	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

LTE Band 7							
Channel Bandwidth: 15 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
X	20825	2507.5	-13.75	38.52	24.77	299.92	H
	21100	2535.0	-14.04	38.36	24.32	270.40	
	21375	2562.5	-13.67	38.58	24.91	309.74	
	20825	2507.5	-19.50	38.92	19.42	87.50	V
	21100	2535.0	-20.12	39.26	19.14	82.04	
	21375	2562.5	-19.60	39.22	19.62	91.62	
Channel Bandwidth: 15 MHz / 16QAM							
X	20825	2507.5	-14.81	38.52	23.71	234.96	H
	21100	2535.0	-15.10	38.36	23.26	211.84	
	21375	2562.5	-14.73	38.58	23.85	242.66	
	20825	2507.5	-20.56	38.92	18.36	68.55	V
	21100	2535.0	-21.18	39.26	18.08	64.27	
	21375	2562.5	-20.66	39.22	18.56	71.78	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

LTE Band 7							
Channel Bandwidth: 20 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
X	20850	2510.0	-13.52	38.52	25.00	316.23	H
	21100	2535.0	-13.81	38.36	24.55	285.10	
	21350	2560.0	-13.44	38.58	25.14	326.59	
	20850	2510.0	-19.27	38.92	19.65	92.26	V
	21100	2535.0	-19.89	39.26	19.37	86.50	
	21350	2560.0	-19.37	39.22	19.85	96.61	
Channel Bandwidth: 20 MHz / 16QAM							
X	20850	2510.0	-14.54	38.52	23.98	250.03	H
	21100	2535.0	-14.83	38.36	23.53	225.42	
	21350	2560.0	-14.46	38.58	24.12	258.23	
	20850	2510.0	-20.29	38.92	18.63	72.95	V
	21100	2535.0	-20.91	39.26	18.35	68.39	
	21350	2560.0	-20.39	39.22	18.83	76.38	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

4.2 Modulation Characteristics Measurement

4.2.1 Limits of Modulation Characteristics

N/A


4.2.2 Test Setup



4.2.3 Test Procedure

Connect the EUT to Communication Simulator via the antenna connector. The frequency band is set as EUT supported Modulation and Channels, the EUT output is matched with 50 ohm load, the waveform quality and constellation of the EUT was tested.

4.2.4 Test Results



4.3 Frequency Stability Measurement

4.3.1 Limits of Frequency Stability Measurement


According to the FCC part 2.1055 shall be tested the frequency stability. The rule is defined that "The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block." The test extreme voltage is according to the 2.1055(d)(1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment and the extreme temperature rule is comply with specification of EUT $-30^{\circ}\text{C} \sim 50^{\circ}\text{C}$.

4.3.2 Test Procedure

- Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the $\pm 0.5^{\circ}\text{C}$ during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

4.3.3 Test Setup



4.3.4 Test Results

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 7			
	Channel Bandwidth: 5 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
3.85	2502.500002	0.001	2567.500001	0.001
3.27	2502.500002	0.001	2567.500002	0.001
4.23	2502.500004	0.001	2567.500002	0.001

Note: The applicant defined the normal working voltage of the battery is from 3.27 Vdc to 4.23 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 7			
	Channel Bandwidth: 5 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-30	2502.500002	0.001	2567.500003	0.001
-20	2502.500004	0.001	2567.500003	0.001
-10	2502.500001	0.001	2567.500001	0.001
0	2502.500003	0.001	2567.500003	0.001
10	2502.500002	0.001	2567.500001	0.000
20	2502.499997	-0.001	2567.499998	-0.001
30	2502.499996	-0.001	2567.499997	-0.001
40	2502.499997	-0.001	2567.499997	-0.001
50	2502.499997	-0.001	2567.499997	-0.001

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 7			
	Channel Bandwidth: 10 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
3.85	2505.000004	0.002	2565.000003	0.001
3.27	2505.000002	0.001	2565.000004	0.001
4.23	2505.000001	0.000	2565.000003	0.001

Note: The applicant defined the normal working voltage of the battery is from 3.27 Vdc to 4.23 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 7			
	Channel Bandwidth: 10 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-30	2505.000002	0.001	2565.000001	0.000
-20	2505.000003	0.001	2565.000002	0.001
-10	2505.000002	0.001	2565.000001	0.000
0	2505.000002	0.001	2565.000002	0.001
10	2505.000003	0.001	2565.000002	0.001
20	2504.999997	-0.001	2564.999997	-0.001
30	2504.999997	-0.001	2564.999996	-0.002
40	2504.999998	-0.001	2564.999999	-0.001
50	2504.999997	-0.001	2564.999998	-0.001

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 7			
	Channel Bandwidth: 15 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
3.85	2507.500003	0.001	2562.500002	0.001
3.27	2507.500002	0.001	2562.500004	0.001
4.23	2507.500003	0.001	2562.500003	0.001

Note: The applicant defined the normal working voltage of the battery is from 3.27 Vdc to 4.23 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 7			
	Channel Bandwidth: 15 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-30	2507.500002	0.001	2562.500002	0.001
-20	2507.500004	0.002	2562.500001	0.000
-10	2507.500003	0.001	2562.500002	0.001
0	2507.500003	0.001	2562.500001	0.000
10	2507.500003	0.001	2562.500004	0.001
20	2507.499998	-0.001	2562.499997	-0.001
30	2507.499997	-0.001	2562.499999	-0.001
40	2507.499997	-0.001	2562.499996	-0.002
50	2507.499996	-0.002	2562.499996	-0.001

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 7			
	Channel Bandwidth: 20 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
3.85	2510.000003	0.001	2560.000001	0.000
3.27	2510.000002	0.001	2560.000001	0.001
4.23	2510.000002	0.001	2560.000004	0.001

Note: The applicant defined the normal working voltage of the battery is from 3.27 Vdc to 4.23 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 7			
	Channel Bandwidth: 20 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-30	2510.000004	0.002	2560.000004	0.001
-20	2510.000001	0.000	2560.000003	0.001
-10	2510.000004	0.001	2560.000004	0.001
0	2510.000004	0.001	2560.000004	0.001
10	2510.000003	0.001	2560.000004	0.001
20	2509.999998	-0.001	2559.999998	-0.001
30	2509.999998	-0.001	2559.999997	-0.001
40	2509.999999	-0.001	2559.999999	0.000
50	2509.999998	-0.001	2559.999998	-0.001

4.4 Occupied Bandwidth Measurement


4.4.1 Limits of Occupied Bandwidth Measurement

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

4.4.2 Test Procedure


- The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
- Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

4.4.3 Test Setup




4.4.4 Test Results

LTE Band 7							
Channel Bandwidth: 5 MHz				Channel Bandwidth: 10 MHz			
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
20775	2502.5	4.4975	4.4967	20800	2505.0	9.0045	8.9998
21100	2535.0	4.4870	4.4909	21100	2535.0	8.9848	8.9860
21425	2567.5	4.4879	4.4893	21400	2565.0	8.9868	8.9846



LTE Band 7							
Channel Bandwidth: 15 MHz				Channel Bandwidth: 20 MHz			
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
20825	2507.5	13.4980	13.4673	20850	2510.0	17.9484	17.9465
21100	2535.0	13.4933	13.4819	21100	2535.0	17.9877	18.0055
21375	2562.5	13.4979	13.4785	21350	2560.0	17.9919	17.9947




4.5 Out-of-Band Emissions Measurement

4.5.1 Limits of Out-of-Band Emissions Measurement

According to FCC 27.53(m)(4)&(6) specified that power of any emission outside of the channel edge must be attenuated below the transmitting power (P) by a factor shall be not less than $40 + 10 \log (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth. In addition, the attenuation factor shall not be less than $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least two percent may be employed, except when the 1 megahertz band is 2495-2496 MHz, in which case a resolution bandwidth of at least one percent may be employed.


4.5.2 Test Setup





4.5.3 Test Procedures


- The EUT was set up for the maximum peak power with LTE link data modulation. The power was measured with R&S Spectrum Analyzer. All measurements were done at 2 channels (low and high operational frequency range.).
- The out-of-band emissions measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
- Record the max. trace plot into the test report.


4.5.4 Test Results





















4.6 Peak to Average Ratio

4.6.1 Limits of Peak to Average Ratio Measurement

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB.

4.6.2 Test Setup




4.6.3 Test Procedures


1. Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1 %.

4.6.4 Test Results

LTE Band 7							
Channel Bandwidth: 5 MHz				Channel Bandwidth: 10 MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
20775	2502.5	4.09	4.80	20800	2505.0	3.82	4.32
21100	2535.0	4.82	5.62	21100	2535.0	4.67	5.27
21425	2567.5	4.23	4.91	21400	2565.0	3.84	4.43



LTE Band 7							
Channel Bandwidth: 15 MHz				Channel Bandwidth: 20 MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
20825	2507.5	3.46	4.23	20850	2510.0	3.38	4.22
21100	2535.0	4.42	5.22	21100	2535.0	4.26	5.02
21375	2562.5	3.28	4.00	21350	2560.0	3.10	3.95




4.7 Conducted Spurious Emissions

4.7.1 Limits of Conducted Spurious Emissions Measurement

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $55 + 10 \log (P)$ dB. The limit of emission is equal to -25 dBm.


4.7.2 Test Setup




4.7.3 Test Procedure

- The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- Measuring frequency range is from 9 kHz to 1 GHz. 10 dB attenuation pad is connected with spectrum. RBW = 100 kHz and VBW = 300 kHz are used for conducted emission measurement.
- Measuring frequency range is from 1 GHz to 27 GHz. 10 dB attenuation pad is connected with spectrum. RBW = 1 MHz and VBW = 3 MHz are used for conducted emission measurement.


4.7.4 Test Results




Note: The signal over the limit in 9 kHz is from spectrum analyzer.




Note: The signal over the limit in 9 kHz is from spectrum analyzer.




Note: The signal over the limit in 9 kHz is from spectrum analyzer.




Note: The signal over the limit in 9 kHz is from spectrum analyzer.




Note: The signal over the limit in 9 kHz is from spectrum analyzer.




Note: The signal over the limit in 9 kHz is from spectrum analyzer.




Note: The signal over the limit in 9 kHz is from spectrum analyzer.




Note: The signal over the limit in 9 kHz is from spectrum analyzer.




Note: The signal over the limit in 9 kHz is from spectrum analyzer.



Note: The signal over the limit in 9 kHz is from spectrum analyzer.



Note: The signal over the limit in 9 kHz is from spectrum analyzer.



Note: The signal over the limit in 9 kHz is from spectrum analyzer.

4.8 Radiated Emission Measurement

4.8.1 Limits of Radiated Emission Measurement

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $55 + 10 \log (P)$ dB. The limit of emission is equal to -25 dBm.

4.8.2 Test Procedure

- Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m (below or equal 1 GHz) and/or 1.5 m (above 1 GHz) height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step a. Record the power level of S.G.
- $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$.
- E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, $E.R.P \text{ power} = E.I.R.P \text{ power} - 2.15 \text{ dB}$.


NOTE: The resolution bandwidth of spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz.

4.8.3 Deviation from Test Standard


No deviation.

4.8.4 Test Setup

<Radiated Emission below or equal 1 GHz>



<Radiated Emission above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.8.5 Test Results

LTE Band 7

Channel Bandwidth: 5 MHz / QPSK

Low Channel


Bureau Veritas Consumer Products Services Ltd., Taoyuan



A D T

Data: 3

Date: 01-07-2019



Site : 966 Chamber 5

Condition: PART 27(B7) HORIZONTAL

Remak : LTE Band 7 QPSK_5M Link_L-CH

Tested by: Jisyong Wang

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	


1 pp 5005.00 -50.98 -48.52 -25.00 -25.98 -2.46 Peak

Bureau Veritas Consumer Products Services Ltd., Taoyuan



A D T

Data: 4



Site : 966 Chamber 5

Condition: PART 27(B7) VERTICAL

Remak : LTE Band 7 QPSK_5M Link_L-CH

Tested by: Jisyong Wang

Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	

1 pp 5005.00 -50.36 -47.90 -25.00 -25.36 -2.46 Peak

Middle Channel


Bureau Veritas Consumer Products Services Ltd., Taoyuan



A D T

Data: 3

Date: 01-07-2019



Site : 966 Chamber 5

Condition: PART 27(B7) HORIZONTAL

Remak : LTE Band 7 QPSK_5M Link_M-CH

Tested by: Jisyong Wang


		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	

1 pp 5070.00 -50.85 -48.98 -25.00 -25.85 -1.87 Peak



Data: 4

Date: 01-07-2019



Site : 966 Chamber 5

Condition: PART 27(B7) VERTICAL

Remak : LTE Band 7 QPSK_5M Link_M-CH

Tested by: Jisyong Wang

Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	

1 pp 5070.00 -50.99 -49.12 -25.00 -25.99 -1.87 Peak

High Channel


Bureau Veritas Consumer Products Services Ltd., Taoyuan



A D T

Data: 3

Date: 01-07-2019



Site : 966 Chamber 5

Condition: PART 27(B7) HORIZONTAL

Remak : LTE Band 7 QPSK_5M Link_H-CH

Tested by: Jisyong Wang

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	


1 pp 5135.00 -50.52 -48.78 -25.00 -25.52 -1.74 Peak

Bureau Veritas Consumer Products Services Ltd., Taoyuan



A D T

Data: 4



Site : 966 Chamber 5

Condition: PART 27(B7) VERTICAL

Remak : LTE Band 7 QPSK_5M Link_H-CH

Tested by: Jisyong Wang

Freq	Level	Read	Limit	Over	Factor	Remark
		Level	Line	Limit		
MHz	dBm	dBm	dBm	dB	dB	

1 pp 5135.00 -50.32 -48.58 -25.00 -25.32 -1.74 Peak

Channel Bandwidth: 20 MHz / QPSK
Low Channel


Bureau Veritas Consumer Products Services Ltd., Taoyuan



A D T

Data: 1

Date: 01-07-2019



Site : 966 Chamber 5
Condition: PART 27(B7) HORIZONTAL
Remak : LTE Band 7 QPSK_20M Link_L-CH
Tested by: Jisyong Wang

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	


1 pp 5020.00 -50.24 -47.92 -25.00 -25.24 -2.32 Peak

Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch



A D T

Data: 2



Site : 966 Chamber 5

Condition: PART 27(B7) VERTICAL

Remak : LTE Band 7 QPSK_20M Link_L-CH

Tested by: Jisyong Wang

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	

1 pp 5020.00 -50.18 -47.86 -25.00 -25.18 -2.32 Peak

Middle Channel


Bureau Veritas Consumer Products Services Ltd., Taoyuan



A D T

Data: 3

Date: 01-07-2019



Site : 966 Chamber 5

Condition: PART 27(B7) HORIZONTAL

Remak : LTE Band 7 QPSK_20M Link_M-CH

Tested by: Jisyong Wang

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	


1 pp 5070.00 -50.34 -48.47 -25.00 -25.34 -1.87 Peak

Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch



A D T

Data: 4



Site : 966 Chamber 5

Condition: PART 27(B7) VERTICAL

Remak : LTE Band 7 QPSK_20M Link_M-CH

Tested by: Jisyong Wang

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	

1 pp 5070.00 -50.71 -48.84 -25.00 -25.71 -1.87 Peak

High Channel


Bureau Veritas Consumer Products Services Ltd., Taoyuan



A D T

Data: 5

Date: 01-07-2019



Site : 966 Chamber 5

Condition: PART 27(B7) HORIZONTAL

Remak : LTE Band 7 QPSK_20M Link_H-CH

Tested by: Jisyong Wang


			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	43.58	-45.03	-43.56	-25.00	-20.03	-1.47	Peak
2	52.31	-55.57	-50.03	-25.00	-30.57	-5.54	Peak
3	178.41	-55.05	-47.99	-25.00	-30.05	-7.06	Peak
4	286.08	-57.03	-50.30	-25.00	-32.03	-6.73	Peak
5	401.51	-61.18	-55.25	-25.00	-36.18	-5.93	Peak
6	726.46	-63.96	-64.38	-25.00	-38.96	0.42	Peak
7	5120.00	-50.31	-48.65	-25.00	-25.31	-1.66	Peak
8 pp	7680.00	-39.67	-44.29	-25.00	-14.67	4.62	Peak

Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch



A D T

Data: 6



Site : 966 Chamber 5

Condition: PART 27(B7) VERTICAL

Remak : LTE Band 7 QPSK_20M Link_H-CH

Tested by: Jisyong Wang

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	30.00	-43.58	-43.96	-25.00	-18.58	0.38	Peak
2	43.58	-46.11	-44.64	-25.00	-21.11	-1.47	Peak
3	52.31	-55.72	-50.18	-25.00	-30.72	-5.54	Peak
4	176.47	-62.57	-55.85	-25.00	-37.57	-6.72	Peak
5	427.70	-64.68	-58.95	-25.00	-39.68	-5.73	Peak
6	896.21	-62.78	-63.33	-25.00	-37.78	0.55	Peak
7	5120.00	-49.96	-48.30	-25.00	-24.96	-1.66	Peak
8 pp	7680.00	-39.94	-44.56	-25.00	-14.94	4.62	Peak

5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---