

FCC RF Test Report

APPLICANT : VeriFone Inc.
EQUIPMENT : POS
BRAND NAME : VeriFone
MODEL NAME : VX680-B-BTC
FCC ID : B32VX680-B-BTC
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : Digital Spread Spectrum (DSS)

The product was received on Jul. 01, 2011 and completely tested on Aug. 04, 2011. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.4-2003 and shown the compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:



Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

SPORTON INTERNATIONAL INC.

TEL : 886-3-327-3456

FAX : 886-3-328-4978

FCC ID : B32VX680-B-BTC

Page Number : 1 of 51

Report Issued Date : Aug. 17, 2011

Report Version : Rev. 01



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Feature of Equipment Under Test	5
1.4 Testing Site	6
1.5 Applied Standards	6
1.6 Ancillary Equipment List	6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	7
2.1 RF Output Power	7
2.2 Test Mode	8
2.3 Connection Diagram of Test System	9
2.4 RF Utility	9
3 TEST RESULT	10
3.1 Number of Channel Measurement	10
3.2 20dB Bandwidth Measurement	12
3.3 Hopping Channel Separation Measurement	19
3.4 Dwell Time Measurement	22
3.5 Peak Output Power Measurement	24
3.6 Band Edges Measurement	27
3.7 Spurious Emission Measurement	31
3.8 AC Conducted Emission Measurement	35
3.9 Radiated Emission Measurement	39
3.10 Antenna Requirements	48
4 LIST OF MEASURING EQUIPMENT	49
5 UNCERTAINTY OF EVALUATION	50
APPENDIX A. PHOTOGRAPHS OF EUT	
APPENDIX B. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR170108-04	Rev. 01	Initial issue of report	Aug. 17, 2011

SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(1)	A8.4(2)	Number of Channels	$\geq 15\text{Chs}$	Pass	-
3.2	15.247(a)(1)	A8.1(a)	20dB Bandwidth	NA	Pass	-
3.3	15.247(a)(1)	A8.1(b)	Channel Separation	$\geq 2/3$ of 20dB BW	Pass	-
3.4	15.247(a)(1)	A8.1(d)	Dwell Time of Each Channel	$\leq 0.4\text{sec}$ in 31.6sec period	Pass	-
3.5	15.247(b)(1)	A8.1(b)	Peak Output Power	$\leq 125\text{ mW}$	Pass	-
3.6	15.247(d)	A8.5	Frequency Band Edges	$\leq 20\text{dBc}$	Pass	-
3.7	15.247(d)	A8.5	Spurious Emission	$< 20\text{ dBc}$	Pass	-
3.8	15.207	Gen 7.2.2	AC Conducted Emission	15.207(a)	Pass	Under limit 10.7 dB at 27.126 MHz
3.9	15.247(d)	A8.5	Transmitter Radiated Emission	15.209(a) & 15.247(d)	Pass	Under limit 3.06 dB at 2483.5 MHz
3.10	15.203 & 15.247(b)	A8.4	Antenna Requirement	N/A	Pass	-

1 General Description

1.1 Applicant

VeriFone Inc.

1400 West Stanford Ranch Road Suit 200 Rocklin CA 95765 USA

1.2 Manufacturer

Inventec Appliances (Pudong) Co., Ltd.

No. 789 Pu Xing Road, Shanghai, P.R.C.

1.3 Feature of Equipment Under Test

Product Feature & Specification	
Equipment	POS
Brand Name	VeriFone
Model Name	VX680-B-BTC
FCC ID	B32VX680-B-BTC
Tx/Rx Frequency Range	2400 MHz ~ 2483.5 MHz
Number of Channels	79
Carrier Frequency of Each Channel	2402+n*1 MHz; n=0~78
Channel Spacing	1 MHz
Maximum Output Power to Antenna	Bluetooth (1Mbps) : 1.98 dBm (0.0016 W) Bluetooth EDR (2Mbps) : 2.36 dBm (0.0017 W) Bluetooth EDR (3Mbps) : 2.89 dBm (0.0019 W)
Antenna Type	PIFA Antenna with gain 3.75 dBi
Type of Modulation	Bluetooth (1Mbps) : GFSK Bluetooth EDR (2Mbps) : π /4-DQPSK Bluetooth EDR (3Mbps) : 8-DPSK
EUT Stage	Identical Prototype

Remark:

1. For other wireless features of this EUT, test report will be issued separately.
2. This test report recorded only product characteristics and test results of Digital Spread Spectrum (DSS).
3. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Testing Site

Test Site	SPORTON INTERNATIONAL INC.		
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-3273456 / FAX: +886-3-3284978		
Test Site No.	Sporton Site No.		FCC/IC Registration No.
	CO05-HY	03CH07-HY	722060/4086B-1

1.5 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC Public Notice DA 00-705
- ♦ ANSI C63.4-2003
- ♦ IC RSS-210 Issue 8

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B (DoC), recorded in a separate test report.

1.6 Ancillary Equipment List

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Base Station	R&S	CBT32	N/A	N/A	Unshielded, 1.8 m
2.	Terminal	VireFone	VX570	N/A	N/A	N/A

2 Test Configuration of Equipment Under Test

2.1 RF Output Power

Preliminary tests were performed in different data rate and recorded the RF output power in the following table:

Channel	Frequency	Bluetooth RF Output Power		
		Data Rate / Modulation		
		GFSK	$\pi/4$ -DQPSK	8-DPSK
		1Mbps	2Mbps	3Mbps
Ch00	2402MHz	1.39 dBm	1.71 dBm	2.25 dBm
Ch39	2441MHz	1.98 dBm	2.36 dBm	2.89 dBm
Ch78	2480MHz	1.52 dBm	1.86 dBm	2.44 dBm

Remark:

1. The data rate was set in 3Mbps for all the test items due to the highest RF output power.
2. The EUT is programmed to transmit signals continuously for all testing.

2.2 Test Mode


The EUT has been associated with peripherals pursuant to ANSI C63.4-2003 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz), radiated emission (30 MHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

Pre-scanned tests were conducted to determine the final configuration from all possible combinations.

The following tables are showing the test modes as the worst cases and recorded in this report.

Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth 1Mbps GFSK	Bluetooth EDR 2Mbps $\pi/4$ -DQPSK	Bluetooth EDR 3Mbps 8-DPSK
Conducted TCs	Mode 1: Bluetooth CH00 Mode 2: Bluetooth CH39 Mode 3: Bluetooth CH78	Mode 4: Bluetooth CH00 Mode 5: Bluetooth CH39 Mode 6: Bluetooth CH78	Mode 7: Bluetooth CH00 Mode 8: Bluetooth CH39 Mode 9: Bluetooth CH78
Radiated TCs	N/A	N/A	Mode 1: Bluetooth CH00 Mode 2: Bluetooth CH39 Mode 3: Bluetooth CH78
AC Conducted Emission	Mode 1 :EUT with Terminal + Bluetooth Link + Adapter 1		

2.3 Connection Diagram of Test System



2.4 RF Utility

The Terminal was linked with Bluetooth Base Station during the test. At the same time, execute "Hyperterminal" to link with the Terminal and Bluetooth Station.

3 Test Result

3.1 Number of Channel Measurement

3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedure


1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The modulation types of EUT are irrelevant to number of hopping channels deviation.
4. The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:
Span = the frequency band of operation; RBW $\geq$ 1% of the span; VBW $\geq$ RBW; Sweep = auto;
Detector function = peak; Trace = max hold.
5. The number of hopping frequency used is defined as the device has the numbers of total channel.

3.1.4 Test Setup




3.1.5 Test Result of Number of Hopping Frequency

Test Mode :	Mode 7~9	Temperature :	24~26°C
Test Engineer :	Hank Yu	Relative Humidity :	54~58%
Number of Hopping Channels (Channel)		Limits (Channel)	Pass/Fail
79		> 15	Pass

Number of Hopping Channel Plot on Channel 00 - 78


Date: 26.JUL.2011 00:14:29



Date: 26.JUL.2011 00:22:25

3.2 20dB Bandwidth Measurement

3.2.1 Limit of 20dB Bandwidth

N/A


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The EUT should be transmitting at its maximum data rate as the worst cases.
4. Use the following spectrum analyzer settings:
Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel;
RBW $\geq$ 1% of the 20 dB bandwidth; VBW $\geq$ RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
5. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

3.2.4 Test Setup




3.2.5 Test Result of 20dB Bandwidth

Test Mode :	Mode 1, 2, 3	Temperature :	24~26℃
Test Engineer :	Hank Yu	Relative Humidity :	54~58%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	0.924
39	2441	0.908
78	2480	0.936


20 dB Bandwidth Plot on Channel 00



Date: 25.JUL.2011 23:15:09




20 dB Bandwidth Plot on Channel 39



Date: 25.JUL.2011 23:15:25


20 dB Bandwidth Plot on Channel 78




Date: 25.JUL.2011 23:16:04

Test Mode :	Mode 4, 5, 6	Temperature :	24~26°C
Test Engineer :	Hank Yu	Relative Humidity :	54~58%


Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.260
39	2441	1.260
78	2480	1.254

20 dB Bandwidth Plot on Channel 00


Date: 25.JUL.2011 23:16:50

20 dB Bandwidth Plot on Channel 39



Date: 25.JUL.2011 23:17:19

20 dB Bandwidth Plot on Channel 78


Date: 25.JUL.2011 23:17:39

Test Mode :	Mode 7, 8, 9	Temperature :	24~26°C
Test Engineer :	Hank Yu	Relative Humidity :	54~58%


Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.224
39	2441	1.224
78	2480	1.230

20 dB Bandwidth Plot on Channel 00


Date: 25.JUL.2011 23:18:23




20 dB Bandwidth Plot on Channel 39



Date: 25.JUL.2011 23:18:58

20 dB Bandwidth Plot on Channel 78



Date: 25.JUL.2011 23:19:22

3.3 Hopping Channel Separation Measurement

3.3.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

1. Please refer FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The EUT should be transmitting at its maximum data rate as the worst cases.
4. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels; $RBW \geq 1\%$ of the span;
VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
5. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

3.3.4 Test Setup




3.3.5 Test Result of Hopping Channel Separation

Test Mode :	Mode 7, 8, 9	Temperature :	24~26℃
Test Engineer :	Hank Yu	Relative Humidity :	54~58%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.616	Pass
39	2441	1.002	0.605	Pass
78	2480	1.002	0.624	Pass


Channel Separation Plot on Channel 00 - 01



Date: 25.JUL.2011 23:11:14




Channel Separation Plot on Channel 39 - 40



Date: 25.JUL.2011 23:11:56

Channel Separation Plot on Channel 77 - 78



Date: 25.JUL.2011 23:12:37

3.4 Dwell Time Measurement

3.4.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

3.4.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The EUT should be transmitting at its maximum data rate as the worst cases.
4. The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:
Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW $\geq$ RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
5. Use the marker-delta function to calculate the dwell time.

3.4.4 Test Setup



3.4.5 Test Result of Dwell Time

Test Mode :	Mode 8	Temperature :	24~26°C
Test Engineer :	Hank Yu	Relative Humidity :	54~58%

Package Mode	Average Hopping Channel	Package Transfer Time (usec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
3DH5	3.40	3060.00	0.33	3.40	Pass

Remark:

1. Dwell Time=79(channels) x 0.4(s) x average hopping channel x package transfer time
2. 79 channels come from the Hopping Channel number.
3. Average Hopping Channel = hops/sweep time
4. t: Package Transfer Time(us)



RBW 1 MHz Delta 3 [T1] 0.19 dB
 VBW 1 MHz 3.760000 ms
 Ref 20 dBm Att 20 dB SWT 10 ms

1 PK MARK

Marker 1 [T1] -50.89 dBm
 2.920000 ms
 Delta 2 [T1] -0.17 dB

Center 2.441 GHz 1 ms/

Date: 22.JUL.2011 20:41:05

RBW 1 MHz
VBW 1 MHz
SWT 10 s

Ref 20 dBm
Att 20 dB

20 Offset 19.6 dB

1.99
MAX

20
-10
0
-1
-2
-3
-4
-50
-60
-70
-80

Center 2.441 GHz
1 s

A
SGL
LVL
3DB

Date: 25.JUL.2011 23:35:33

3.5 Peak Output Power Measurement

3.5.1 Limit of Peak Output Power

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW (20.97dBm).


3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.

3.5.4 Test Setup




3.5.5 Test Result of Peak Output Power

Test Mode :	Mode 7, 8, 9	Temperature :	24~26℃	
Test Engineer :	Hank Yu	Relative Humidity :	54~58%	


Channel	Frequency (MHz)	RF Power (dBm)		
		8-DPSK	Max. Limits (dBm)	Pass/Fail
		3 Mbps		
00	2402	2.25	20.97	Pass
39	2441	2.89	20.97	Pass
78	2480	2.44	20.97	Pass

Peak Output Power Plot on Channel 00



Date: 25.JUL.2011 22:52:36


Peak Output Power Plot on Channel 39



Date: 25.JUL.2011 22:53:51



Peak Output Power Plot on Channel 78



Date: 25.JUL.2011 22:55:06

3.6 Band Edges Measurement

3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

3.6.2 Measuring Instruments


See list of measuring instruments of this test report.

3.6.3 Test Procedures


1. The testing follows the guidelines in ANSI C63.4-2003 and FCC Public Notice DA 00-705 Measurement Guidelines.
2. RF antenna conducted test: Set RBW = 300kHz, Video bandwidth (VBW) $\geq$ RBW. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 300k Hz RBW. Note: If the device complies with the use of power option 2 the attenuation under this paragraph shall be 30 dB instead of 20 dB.
3. Radiated emission test: Applies to band edge emissions that fall in the restricted bands listed in FCC Section 15.205. The maximum permitted average field strength is listed in FCC Section 15.209. A pre-amp is necessary for this measurement. For measurements above 1 GHz, set RBW = 1MHz, VBW = 1MHz, Sweep: Auto for Peak; set RBW = 1MHz, VBW = 10 Hz, Sweep: Auto for Average. If the emission is pulsed, modify the unit for continuous operation; use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation. See FCC Section 15.35(b) and (c).
4. In case the emission is fail due to the used RBW / VBW is too wide, marker-delta method of FCC Public Notice DA 00-705 will be followed.

3.6.4 Test Setup

<Radiated Band Edges>



<Conducted Band Edges>



3.6.5 Test Result of Radiated Band Edges

Test Mode :	Mode 1	Temperature :	23~24°C
Test Channel :	00	Relative Humidity :	48~49%
		Test Engineer :	David Yang

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2388.85	46.41	-27.59	74	42.05	32.18	6.03	33.85	120	0	Peak
2388.85	35.03	-18.97	54	30.67	32.18	6.03	33.85	120	0	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2385.05	47.09	-26.91	74	42.75	32.16	6.03	33.85	100	336	Peak
2385.05	35.47	-18.53	54	31.13	32.16	6.03	33.85	100	336	Average


Test Mode :	Mode 3	Temperature :	23~24°C
Test Channel :	78	Relative Humidity :	48~49%
		Test Engineer :	David Yang

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.5	64.26	-9.74	74	59.7	32.28	6.18	33.9	113	30	Peak
2483.5	50.94	-3.06	54	46.38	32.28	6.18	33.9	113	30	Average


ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.5	62.07	-11.93	74	57.51	32.28	6.18	33.9	154	328	Peak
2483.5	50.15	-3.85	54	45.59	32.28	6.18	33.9	154	328	Average



Test Mode :	Mode 7 and 9	Temperature :	24~26℃
Test Channel :	00 and 78	Relative Humidity :	54~58%
		Test Engineer :	Hank Yu



Date: 25.JUL.2011 23:26:05



Date: 25.JUL.2011 23:27:08

3.7 Spurious Emission Measurement

3.7.1 Limit of Spurious Emission Measurement

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


3.7.2 Measuring Instruments

See list of measuring instruments of this test report.

3.7.3 Test Procedure

1. The transmitter output was connected to the spectrum analyzer via a low lose cable.
2. Set RBW = 100 kHz, Video bandwidth (VBW) $\geq$ RBW, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.


3.7.4 Test Setup



3.7.5 Test Result


Test Mode :	Mode 7	Temperature :	24~26℃
Test Channel :	00	Relative Humidity :	54~58%
		Test Engineer :	Hank Yu

Conducted Spurious Emission Plot between 30MHz ~ 3 GHz



Date: 25.JUL.2011 23:55:42

Conducted Spurious Emission Plot between 3 GHz ~ 25 GHz




Date: 25.JUL.2011 23:56:04




Test Mode :	Mode 8	Temperature :	24~26°C
Test Channel :	39	Relative Humidity :	54~58%
		Test Engineer :	Hank Yu

Conducted Spurious Emission Plot between 30MHz ~ 3 GHz




Date: 25.JUL.2011 23:56:33

Conducted Spurious Emission Plot between 3 GHz ~ 25 GHz




Date: 25.JUL.2011 23:56:55

Test Mode :	Mode 9	Temperature :	24~26°C
Test Channel :	78	Relative Humidity :	54~58%
		Test Engineer :	Hank Yu

Conducted Spurious Emission Plot between 30MHz ~ 3 GHz


Date: 25.JUL.2011 23:53:26

Conducted Spurious Emission Plot between 3 GHz ~ 25 GHz


Date: 25.JUL.2011 23:54:00

3.8 AC Conducted Emission Measurement

3.8.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.8.2 Measuring Instruments

See list of measuring instruments of this test report.

3.8.3 Test Procedures


1. Please follow the guidelines in ANSI C63.4-2003.
2. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN).
4. All the support units are connecting to the other LISN.
5. The LISN provides 50 ohm coupling impedance for the measuring instrument.
6. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
7. Both sides of AC line were checked for maximum conducted interference.
8. The frequency range from 150 kHz to 30 MHz was searched.
9. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.8.4 Test Setup



3.8.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	21~23°C
Test Engineer :	Novic Chiang	Relative Humidity :	41~43%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	EUT with Terminal + Bluetooth Link + Adapter 1		
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		




Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.158000	52.8	Off	L1	19.4	12.8	65.6
0.222000	42.9	Off	L1	19.4	19.8	62.7
0.286000	34.9	Off	L1	19.4	25.7	60.6
0.358000	29.6	Off	L1	19.4	29.2	58.8
0.446000	33.9	Off	L1	19.4	23.0	56.9
6.702000	30.1	Off	L1	19.7	29.9	60.0

Final Result 2

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.158000	31.4	Off	L1	19.4	24.2	55.6
0.222000	24.1	Off	L1	19.4	28.6	52.7
0.286000	20.4	Off	L1	19.4	30.2	50.6
0.358000	18.7	Off	L1	19.4	30.1	48.8
0.446000	21.4	Off	L1	19.4	25.5	46.9
6.702000	26.3	Off	L1	19.7	23.7	50.0

Test Mode :	Mode 1	Temperature :	21~23°C
Test Engineer :	Novic Chiang	Relative Humidity :	41~43%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	EUT with Terminal + Bluetooth Link + Adapter 1		
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		


Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	51.3	Off	N	19.4	14.7	66.0
0.190000	45.0	Off	N	19.4	19.0	64.0
0.246000	36.7	Off	N	19.4	25.2	61.9
0.286000	33.2	Off	N	19.4	27.4	60.6
0.454000	35.3	Off	N	19.4	21.5	56.8
9.006000	29.6	Off	N	19.8	30.4	60.0

Final Result 2

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	30.6	Off	N	19.4	25.4	56.0
0.190000	23.6	Off	N	19.4	30.4	54.0
0.246000	18.4	Off	N	19.4	33.5	51.9
0.286000	17.2	Off	N	19.4	33.4	50.6
0.454000	24.4	Off	N	19.4	22.4	46.8
9.006000	23.7	Off	N	19.8	26.3	50.0

3.9 Radiated Emission Measurement

3.9.1 Limit of Radiated Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.9.2 Measuring Instruments


See list of measuring instruments of this test report.

3.9.3 Test Procedures


- The testing follows the guidelines in FCC Public Notice DA 00-705 Measurement Guidelines.
- Use the following spectrum analyzer settings:
 - Span = wide enough to fully capture the emission being measured; RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
 - Above 18 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.
Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1m]})$ (dB)
- Follow the guidelines in ANSI C63.4-2003 with respect to maximizing the emission by rotating the EUT, measuring the emission for three EUT orthogonal planes, and adjusting the measurement antenna height and polarization. A pre-amp and a high pass filter are used for this test in order to get the good signal level.
- Measured average value for the peak value is greater than 54 dBuV/m

3.9.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.9.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

Test Engineer :	David Yang	Temperature :	23~24°C	
		Relative Humidity :	48~49%	

Frequency (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

3.9.6 Test Result of Radiated Emission (30 MHz ~ 10th Harmonic)

Test Mode :	Mode 1	Temperature :	23~24°C
Test Channel :	00	Relative Humidity :	48~49%
Test Engineer :	David Yang	Polarization :	Horizontal
Remark :	2402 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
31.62	19.27	-20.73	40	34.14	16.04	0.55	31.46	126	310	Peak
165.81	18.88	-24.62	43.5	39.15	10.02	1.23	31.52	-	-	Peak
278.94	19.21	-26.79	46	35.79	13.13	1.64	31.35	-	-	Peak
330.1	17.6	-28.4	46	32.67	14.39	1.85	31.31	-	-	Peak
582.1	20.83	-25.17	46	29.64	19.49	2.64	30.94	-	-	Peak
803.3	24.85	-21.15	46	29.88	22.5	3.15	30.68	-	-	Peak
2388.85	46.41	-27.59	74	42.05	32.18	6.03	33.85	120	0	Peak
2388.85	35.03	-18.97	54	30.67	32.18	6.03	33.85	120	0	Average
2402	98.2	-	-	93.82	32.2	6.03	33.85	120	0	Peak
2402	80.95	-	-	76.59	32.18	6.03	33.85	120	0	Average
2486	32.78	-21.22	54	28.22	32.28	6.18	33.9	120	0	Average
2486	44.4	-29.6	74	39.84	32.28	6.18	33.9	120	0	Peak
4804	47.88	-26.12	74	63.84	34.06	9.12	59.14	100	0	Peak

Test Mode :	Mode 1	Temperature :	23~24°C
Test Channel :	00	Relative Humidity :	48~49%
Test Engineer :	David Yang	Polarization :	Vertical
Remark :	2402 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
34.05	23.56	-16.44	40	38.89	15.57	0.57	31.47	109	346	Peak
106.41	20.93	-22.57	43.5	41.08	10.37	1.03	31.55	-	-	Peak
204.42	23.12	-20.38	43.5	43.82	9.44	1.34	31.48	-	-	Peak
438.6	18.55	-27.45	46	30.2	17.2	2.27	31.12	-	-	Peak
663.3	26.84	-19.16	46	34.35	20.48	2.87	30.86	-	-	Peak
825	25.33	-20.67	46	30.07	22.76	3.21	30.71	-	-	Peak
2385.05	47.09	-26.91	74	42.75	32.16	6.03	33.85	100	336	Peak
2385.05	35.47	-18.53	54	31.13	32.16	6.03	33.85	100	336	Average
2402	97.78	-	-	93.4	32.2	6.03	33.85	100	336	Peak
2402	80.45	-	-	76.09	32.18	6.03	33.85	100	336	Average
2492	32.8	-21.2	54	28.22	32.3	6.18	33.9	100	336	Average
2492	45	-29	74	40.42	32.3	6.18	33.9	100	336	Peak
4804	45.61	-28.39	74	61.57	34.06	9.12	59.14	100	0	Peak

Test Mode :	Mode 2	Temperature :	23~24°C
Test Channel :	39	Relative Humidity :	48~49%
Test Engineer :	David Yang	Polarization :	Horizontal
Remark :	2441 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
30.81	19.48	-20.52	40	34.13	16.27	0.54	31.46	-	-	Peak
130.17	25.2	-18.3	43.5	44.05	11.57	1.15	31.57	127	183	Peak
165.81	20.8	-22.7	43.5	41.07	10.02	1.23	31.52	-	-	Peak
405	17.29	-28.71	46	29.64	16.66	2.16	31.17	-	-	Peak
603.8	22.15	-23.85	46	30.56	19.81	2.7	30.92	-	-	Peak
799.8	25.33	-20.67	46	30.4	22.47	3.14	30.68	-	-	Peak
2324	46.07	-27.93	74	41.88	32.09	5.92	33.82	115	8	Peak
2324	33.44	-20.56	54	29.25	32.09	5.92	33.82	115	8	Average
2441	99	-	-	94.53	32.24	6.11	33.88	115	8	Peak
2441	82.19	-	-	77.72	32.24	6.11	33.88	115	8	Average
2492	46.07	-27.93	74	41.49	32.3	6.18	33.9	115	8	Peak
2492	33.03	-20.97	54	28.45	32.3	6.18	33.9	115	8	Average
4882	49.09	-24.91	74	64.91	34.08	9.14	59.04	100	0	Peak

Test Mode :	Mode 2	Temperature :	23~24°C
Test Channel :	39	Relative Humidity :	48~49%
Test Engineer :	David Yang	Polarization :	Vertical
Remark :	2441 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
34.05	24.02	-15.98	40	39.35	15.57	0.57	31.47	105	78	Peak
106.41	20.13	-23.37	43.5	40.28	10.37	1.03	31.55	-	-	Peak
261.66	26.26	-19.74	46	43.21	12.86	1.6	31.41	-	-	Peak
330.1	20.72	-25.28	46	35.79	14.39	1.85	31.31	-	-	Peak
500.2	23.45	-22.55	46	33.84	18.23	2.45	31.07	-	-	Peak
699.7	25.12	-20.88	46	32.12	20.88	2.94	30.82	-	-	Peak
2390	45.37	-28.63	74	41.01	32.18	6.03	33.85	100	331	Peak
2390	33.56	-20.44	54	29.2	32.18	6.03	33.85	100	331	Average
2441	98.4	-	-	93.93	32.24	6.11	33.88	100	331	Peak
2441	81.97	-	-	77.5	32.24	6.11	33.88	100	331	Average
2484	45.6	-28.4	74	41.04	32.28	6.18	33.9	100	331	Peak
2484	32.94	-21.06	54	28.38	32.28	6.18	33.9	100	331	Average
4882	46.88	-27.12	74	62.7	34.08	9.14	59.04	100	0	Peak

Test Mode :	Mode 3	Temperature :	23~24°C
Test Channel :	78	Relative Humidity :	48~49%
Test Engineer :	David Yang	Polarization :	Horizontal
Remark :	2480 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
30.81	19.49	-20.51	40	34.14	16.27	0.54	31.46	-	-	Peak
165.81	20.69	-22.81	43.5	40.96	10.02	1.23	31.52	-	-	Peak
270.3	19.78	-26.22	46	36.51	13	1.64	31.37	-	-	Peak
391.7	17.68	-28.32	46	30.45	16.32	2.12	31.21	-	-	Peak
626.2	21.74	-24.26	46	29.8	20.06	2.77	30.89	-	-	Peak
825	27.74	-18.26	46	32.48	22.76	3.21	30.71	137	263	Peak
2342	45.95	-28.05	74	41.72	32.11	5.95	33.83	113	30	Peak
2342	33.43	-20.57	54	29.2	32.11	5.95	33.83	113	30	Average
2480	83.04	-	-	78.48	32.28	6.18	33.9	113	30	Average
2480	99.74	-	-	95.18	32.28	6.18	33.9	113	30	Peak
2483.5	64.26	-9.74	74	59.7	32.28	6.18	33.9	113	30	Peak
2483.5	50.94	-3.06	54	46.38	32.28	6.18	33.9	113	30	Average
4960	51.99	-22.01	74	67.65	34.09	9.16	58.91	140	39	Peak
4960	43.25	-10.75	54	58.91	34.09	9.16	58.91	140	39	Average

Test Mode :	Mode 3	Temperature :	23~24°C
Test Channel :	78	Relative Humidity :	48~49%
Test Engineer :	David Yang	Polarization :	Vertical
Remark :	2480 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
33.78	23.52	-16.48	40	38.85	15.57	0.57	31.47	100	293	Peak
106.41	21.65	-21.85	43.5	41.8	10.37	1.03	31.55	-	-	Peak
265.98	26	-20	46	42.85	12.92	1.62	31.39	-	-	Peak
340.6	19.38	-26.62	46	34.07	14.72	1.89	31.3	-	-	Peak
500.2	22.57	-23.43	46	32.96	18.23	2.45	31.07	-	-	Peak
663.3	26.84	-19.16	46	34.35	20.48	2.87	30.86	-	-	Peak
2324	45.26	-28.74	74	41.07	32.09	5.92	33.82	154	328	Peak
2324	34.25	-19.75	54	30.06	32.09	5.92	33.82	154	328	Average
2480	97.6	-	-	93.04	32.28	6.18	33.9	154	328	Peak
2480	81.27	-	-	76.71	32.28	6.18	33.9	154	328	Average
2483.5	62.07	-11.93	74	57.51	32.28	6.18	33.9	154	328	Peak
2483.5	50.15	-3.85	54	45.59	32.28	6.18	33.9	154	328	Average
4960	51.69	-22.31	74	67.35	34.09	9.16	58.91	100	35	Peak
4960	42.21	-11.79	54	57.87	34.09	9.16	58.91	100	35	Average

3.10 Antenna Requirements

3.10.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.10.2 Antenna Connected Construction

The antennas type used in this product is PIFA Antenna without connector and it is considered to meet antenna requirement.

3.10.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Due Date	Remark
Bilog Antenna	SCHAFFNER	CBL6111C	2726	30MHz ~ 1GHz	Oct. 31, 2010	Oct. 30, 2011	Radiation (03CH07-HY)
Spectrum Analyzer	R&S	FSP30	101067	9KHz ~ 30GHz	Dec. 03, 2010	Dec. 02, 2011	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	00075962	1GHz ~ 18GHz	Aug. 19, 2010	Aug. 18, 2011	Radiation (03CH07-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170251	15GHz- 40GHz	Oct. 18, 2010	Oct. 17, 2011	Radiation (03CH07-HY)
Pre Amplifier	Agilent	8449B	3008A02362	1GHz~ 26.5GHz	Dec. 06, 2010	Dec. 05, 2011	Radiation (03CH07-HY)
Pre Amplifier	COM-POWER	PA-103A	161241	10-1000MHz.32dB.GAIN	Mar. 29, 2011	Mar. 28, 2012	Radiation (03CH07-HY)
Bluetooth Base Station	R&S	CBT32	100522	N/A	Jan.13, 2011	Jan.13, 2013	Radiation (03CH07-HY)
EMI Test Receive	R&S	ESCS 30	100356	9KHz – 2.75GHz	Aug. 16, 2010	Aug. 15, 2011	Conduction (CO05-HY)
Two-LISN	R&S	ENV216	11-100081	9KHz – 30MHz	Dec. 03, 2010	Dec. 02, 2011	Conduction (CO05-HY)
Two-LISN	R&S	ENV216	11-100080	9KHz – 30MHz	Dec. 01, 2010	Nov. 30, 2011	Conduction (CO05-HY)
AC Power Source	APC	APC-1000W	N/A	N/A	N/A	N/A	Conduction (CO05-HY)
System Simulator	R&S	CMU200	117995	N/A	Aug. 11, 2010	Aug.10, 2011	Conducted (TH02-HY)
Spectrum Analyzer	R&S	FSP40	100055	9kHz~40GHz	Jun. 13, 2011	Jun. 12, 2012	Conducted (TH02-HY)
Power Meter	Anritsu	ML2495A	0932001	N/A	Sep. 13, 2010	Sep. 12, 2011	Conducted (TH02-HY)
Power Sensor	Anritsu	MA2411B	0846202	N/A	Sep. 14, 2010	Sep. 13, 2011	Conducted (TH02-HY)
Thermal Chamber	Ten Billion	TTH-D35P	TBN-930701	N/A	Jul. 30, 2010	Jul. 29, 2011	Conducted (TH02-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Contribution	Uncertainty of X_i		$u(X_i)$
	dB	Probability Distribution	
Receiver Reading	0.10	Normal (k=2)	0.05
Cable Loss	0.10	Normal (k=2)	0.05
AMN Insertion Loss	2.50	Rectangular	0.63
Receiver Specification	1.50	Rectangular	0.43
Site Imperfection	1.39	Rectangular	0.80
Mismatch	+0.34 / -0.35	U-Shape	0.24
Combined Standard Uncertainty $U_c(y)$	1.13		
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.26		

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Contribution	Uncertainty of X_i		$u(X_i)$
	dB	Probability Distribution	
Receiver Reading	0.41	Normal (k=2)	0.21
Antenna Factor Calibration	0.83	Normal (k=2)	0.42
Cable Loss Calibration	0.25	Normal (k=2)	0.13
Pre-Amplifier Gain Calibration	0.27	Normal (k=2)	0.14
RCV/SPA Specification	2.50	Rectangular	0.72
Antenna Factor Interpolation for Frequency	1.00	Rectangular	0.29
Site Imperfection	1.43	Rectangular	0.83
Mismatch	+0.39 / -0.41	U-Shape	0.28
Combined Standard Uncertainty $U_c(y)$	1.27		
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.54		

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Contribution	Uncertainty of X_i		$u(X_i)$	C_i	$C_i * u(X_i)$
	dB	Probability Distribution			
Receiver Reading	± 0.10	Normal (k=2)	0.10	1	0.10
Antenna Factor Calibration	± 1.70	Normal (k=2)	0.85	1	0.85
Cable Loss Calibration	± 0.50	Normal (k=2)	0.25	1	0.25
Receiver Correction	± 2.00	Rectangular	1.15	1	1.15
Antenna Factor Directional	± 1.50	Rectangular	0.87	1	0.87
Site Imperfection	± 2.80	Triangular	1.14	1	1.14
Mismatch Receiver VSWR $\Gamma_1 = 0.197$ Antenna VSWR $\Gamma_2 = 0.194$ Uncertainty = $20\text{Log}(1-\Gamma_1*\Gamma_2)$	+0.34 / -0.35	U-Shape	0.244	1	0.244
Combined Standard Uncertainty $U_c(y)$	2.36				
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.72				



Appendix A. Photographs of EUT

Please refer to Sporton report number EP170108-04 as below.