

4 FCC §15.247 (i) & §2.1091 - RF Exposure Information

4.1 Applicable Standards

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

4.2 MPE Prediction

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

4.3 MPE Results

Maximum peak output power at antenna input terminal (dBm):	24.91
Maximum peak output power at antenna input terminal (mW):	309.74
Prediction distance (cm):	20
Prediction frequency (MHz):	927.59
Maximum Antenna Gain, typical (dBi):	0
Maximum Antenna Gain (numeric):	1
Power density of prediction frequency at 20 cm (mW/cm ²):	0.062
MPE limit for uncontrolled exposure at prediction frequency (mW/cm ²):	0.62

The device meets FCC MPE limit for uncontrolled exposure. The maximum power density at the distance of 20 cm is 0.062 mW/cm², limit is 0.62 mW/cm².