


TEST REPORT

Applicant: GT-tronics HK Limited
Address: Unit 10, 2/F., Block B, Tonic Industrial Center 19
Lam Hing Street, Kowloon Bay, Kowloon, Hong Kong
Equipment Type: GT-tronics QCC Bluetooth Module
Model Name: QC356FNB-S (refer to section 2.3)
Brand Name: GT-tronics
FCC ID: B4O-QC35XFNX
Test Standard: 47 CFR Part 2.1091
KDB 447498 D04 v01
Sample Arrival Date: Dec. 30, 2022
Test Date: Jan. 05, 2023 - Jul. 13, 2023
Date of Issue: Aug. 22, 2023

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

Tested by: Xiong Lining**Checked by:** Xu Rui**Approved by:** Tolan Tu

(Testing Director)



Revision History

Version	Issue Date	Revisions Content
<u>Rev. 01</u>	<u>Aug. 09, 2023</u>	<u>Initial Issue</u>
<u>Rev. 02</u>	<u>Aug. 22, 2023</u>	<u>1. Updated applicant address in the home page and Section 2.1.</u> <u>2. Updated the note in Section 5.1.</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION	3
1.1	Test Laboratory	3
1.2	Test Location.....	3
2	PRODUCT INFORMATION.....	4
2.1	Applicant Information.....	4
2.2	Manufacturer Information	4
2.3	General Description for Equipment under Test (EUT)	4
2.4	Ancillary Equipment.....	4
2.5	Technical Information	5
3	SUMMARY OF TEST RESULT	6
3.1	Test Standards	6
4	DEVICE CATEGORY AND LEVELS LIMITS	7
5	ASSESSMENT RESULT	9
5.1	Output Power	9
5.2	Tune-up power	9
5.3	RF Exposure Evaluation Result	9
5.4	Conclusion.....	9

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	<input checked="" type="checkbox"/> Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
	<input type="checkbox"/> 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	GT-tronics HK Limited
Address	Unit 10, 2/F., Block B, Tonic Industrial Center 19 Lam Hing Street, Kowloon Bay, Kowloon, Hong Kong

2.2 Manufacturer Information

Manufacturer	GT-tronics HK Limited
Address	B210, Tonic Industrial Center, 19 Lam Hing Street, Kowloon Bay, Hong Kong

2.3 General Description for Equipment under Test (EUT)

EUT Name	GT-tronics QCC Bluetooth Module
Model Name Under Test	QC356FNB-S
Series Model Name	QC356FNA, QC356FNB, QC350FNA, QC350FNB, QCC350FNB-S, QC551FNA, QCC551FNB, QC551FNB-S, QCCx5xFNx, QCCx4xFNx, QCCx5xFPx, QCCx4xFPx, QCCx5xFCx, QCCx4xFCx, QCCx5xFEx, QCCx4xFEx
Description of Model name differentiation	All models are same with electrical parameters and internal circuit structure, but only differ in model name. (this information provided by the applicant)
Hardware Version	v1.0
Software Version	v1.0
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.4 Ancillary Equipment

Note: Not applicable.

2.5 Technical Information

Network and Wireless connectivity	Bluetooth (BR+EDR+BLE)
-----------------------------------	------------------------

The requirement for the following technical information of the EUT was tested in this report:

Operating Mode	Bluetooth	
Frequency Range	Bluetooth	2402 MHz ~ 2480 MHz
Antenna Type	Bluetooth	Ceramic Chip Antenna
		Metal Antenna
		PCB Antenna
		Dipole Antenna 1
		Dipole Antenna 2
		Dipole Antenna 3
Exposure Category	General Population/Uncontrolled Exposure	
EUT Type	Mobile Device	

3 SUMMARY OF TEST RESULT

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 2.1091	Radiofrequency radiation exposure evaluation: mobile devices
2	KDB 447498 D04 v01	447498 D04 Interim General RF Exposure Guidance v01

4 DEVICE CATEGORY AND LEVELS LIMITS

Mobile Device:

CFR Title 47 §2.1091(b)

(b) For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons.

FCC KDB 447498 D04 General RF Exposure Guidance v01 Limit

Evaluation of compliance with the exposure limits in § 1.1310 is necessary if the ERP of the device is greater than ERP_{20cm} in Formula (B.1) [repeated from § 2.1091(c)(1) and § 1.1307(b)(1)(i)(B)].

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i. e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole).

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold P_{th} (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula (B.2).

$$P_{th} (\text{mW}) = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B.2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20\text{cm}}$ is per Formula (B.1). The example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

5 ASSESSMENT RESULT

5.1 Output Power

Mode	Bluetooth					
	Ceramic Chip Antenna	Metal Antenna	PCB Antenna	Antenna Type		
				Dipole Antenna 1	Dipole Antenna 2	Dipole Antenna 3
Conducted Power (dBm)	6.80	6.80	6.80	6.80	6.80	6.80
Antenna Gain (dBi)	2.00	2.71	-0.30	3.00	2.00	2.00
EIRP (dBm)	8.80	9.51	6.50	9.80	8.80	8.80

Note: This report listed the worst case power value, please refer to BL-SZ2310035-603& BL-SZ2310035-604 report for more details.

5.2 Tune-up power

Mode		Conducted Power Range (dBm)	EIRP Range (dBm)	ERP Range (dBm)
Bluetooth	Ceramic Chip Antenna	[5.00, 7.00]	[7.00, 9.00]	[4.85, 6.85]
	Metal Antenna	[5.00, 7.00]	[7.71, 9.71]	[5.56, 7.56]
	PCB Antenna	[5.00, 7.00]	[4.70, 6.70]	[2.55, 4.65]
	Dipole Antenna 1	[5.00, 7.00]	[8.00, 10.00]	[5.85, 7.85]
	Dipole Antenna 2	[5.00, 7.00]	[7.00, 9.00]	[4.85, 6.85]
	Dipole Antenna 3	[5.00, 7.00]	[7.00, 9.00]	[4.85, 6.85]

Note 1: ERP= EIRP -2.15dB.

Note 2: According KDB 447498 D04, used the greater of maximum conducted power and ERP to compare with the threshold value Pth.

5.3 RF Exposure Evaluation Result

Mode	Distance (mm)	Calculation Frequency (MHz)	Maximum Tune-up limit power (dBm)	Maximum Tune-up limit power (mW)	Threshold Power (mW)	Verdict
Bluetooth	200	2480	7.85	6.10	3060.00	Pass

5.4 Conclusion

This EUT is deemed to comply with the reference level limits, therefore the basic restrictions are compliant with human exposure limits.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--