



Shenzhen CTL Testing Technology Co., Ltd.
Tel: +86-755-89486194 Fax: +86-755-26636041

FCC PART 15 SUBPART C TEST REPORT

FCC Part 15.247

Report Reference No......: **CTL1408212034-WF02**

Compiled by

(position+printed name+signature)..
File administrators Jacky Chen

Jacky Chen

Name of the organization performing
the tests
Test Engineer Tracy Qi

Tracy Qi

(position+printed name+signature)..
Approved by

(position+printed name+signature)..
Manager Tracy Qi

Tracy Qi

Date of issue.....: Oct. 09, 2014

Test Firm.....: **Shenzhen CTL Testing Technology Co., Ltd.**

Address.....: Floor 1-A, Baisha Technology Park, No.3011, Shahexi Road,
Nanshan District, Shenzhen, China 518055

Applicant's name.....: **GT-tronics HK Ltd**

Address.....: B202, Tonic Industrial Center, 19 Lam Hing Street, Kowloon Bay,
Hong Kong

Test specification:

Standard: FCC Part 15.247: Operation within the bands 902–928 MHz, 2400–
2483.5 MHz, and 5725–5850 MHz.

Master TRF.....: Dated 2011-01

Shenzhen CTL Testing Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the
Shenzhen CTL Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the
material. Shenzhen CTL Testing Technology Co., Ltd. takes no responsibility for and will not assume
liability for damages resulting from the reader's interpretation of the reproduced material due to its
placement and context.

Test item description: Bluetooth Module

FCC ID.....: B4OBC86XRPX

Trade Mark: N/A

Model/Type reference.....: BC815RPA, BC835RPA, BC805RPA, BC830RPA, BC863RPA

Work frequency: 2402~2480MHz

Version.....: V4.0

Type of modulation: GFSK

Antenna Gain: 0 dBi

Antenna type: Internal

Result.....: **Positive**

TEST REPORT

Test Report No. :	CTL1408212034-WF02	Oct. 09, 2014
		Date of issue

Equipment under Test : Bluetooth Module

Model /Type : BC815RPA

Listed Modes : BC835RPA, BC805RPA, BC830RPA, BC863RPA

Difference Description : Only the color and model's name is different

Applicant : **GT-tronics HK Ltd**

Address : B202, Tonic Industrial Center, 19 Lam Hing Street, Kowloon Bay, Hong Kong

Manufacturer : **GT-tronics HK Ltd**

Address : B202, Tonic Industrial Center, 19 Lam Hing Street, Kowloon Bay, Hong Kong

Test Result according to the standards on page 4:	Positive
--	-----------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

_Toc400790371

<u>1.</u>	<u>TEST STANDARDS</u>	4
<u>2.</u>	<u>SUMMARY</u>	5
2.1.	General Remarks	5
2.2.	Equipment Under Test	5
2.3.	Short description of the Equipment under Test (EUT)	5
2.4.	EUT operation mode	5
2.5.	EUT configuration	6
2.6.	Configuration of Tested System	6
2.7.	Related Submittal(s) / Grant (s)	6
2.8.	Modifications	6
2.9.	NOTE	6
2.10.	Channel list	7
2.11.	Mode of Operation	7
<u>3.</u>	<u>TEST ENVIRONMENT</u>	8
3.1.	Address of the test laboratory	8
3.2.	Test Facility	8
3.3.	Environmental conditions	8
3.4.	Statement of the measurement uncertainty	8
3.5.	Test Description	9
3.6.	Equipments Used during the Test	10
<u>4.</u>	<u>TEST CONDITIONS AND RESULTS</u>	11
4.1.	AC Power Conducted Emission	11
4.2.	Radiated Emission	14
4.3.	Maximum Peak Output Power	17
4.4.	6dB Bandwidth	19
4.5.	Band Edge	21
4.6.	Power Spectral Density Measurement	30
4.7.	Spurious RF Conducted Emission	32
4.8.	Antenna Requirement	36
4.9.	RF Exposure	37
<u>5.</u>	<u>TEST SETUP PHOTOS OF THE EUT</u>	38
<u>6.</u>	<u>EXTERNAL AND INTERNAL PHOTOS OF THE EUT</u>	40

1. TEST STANDARDS

The tests were performed according to following standards:

FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

ANSI C63.10-2009: American National Standard for Testing Unlicensed Wireless Devices

KDB Publication No. KDB 558074 D01 v03r02 Guidance on Measurements for Digital Transmission Systems

ANSI C63.4-2009



2. SUMMARY

2.1. General Remarks

Date of receipt of test sample	:	Sept. 05, 2014
Testing commenced on	:	Sept. 05, 2014
Testing concluded on	:	Oct. 09, 2014

2.2. Equipment Under Test

Power supply system utilised

Power supply voltage	:	<input type="radio"/> 120V / 60 Hz	<input type="radio"/> 115V / 60Hz
		<input type="radio"/> 12 V DC	<input type="radio"/> 24 V DC
		<input checked="" type="radio"/> Other (specified in blank below)	

DC 1.8V

2.3. Short description of the Equipment under Test (EUT)

A Bluetooth Module with Bluetooth 4.0 function.

For more details, refer to the user's manual of the EUT.

Serial number: Prototype

2.4. EUT operation mode

The EUT has been tested under typical operating condition. The Applicant provides communication tools software to control the EUT for staying in continuous transmitting and receiving mode for testing. There are 40 channels of EUT, and the test carried out at the lowest channel, middle channel and highest channel.

Frequency Range:	2400-2483.5MHz
Channel number:	40 channels
Modulation type:	GFSK
Antenna:	internal

Test Channel	Test Frequency
Low Channel	2402 MHz
Middle Channel	2440 MHz
High Channel	2480 MHz

2.5. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- supplied by the manufacturer
- supplied by the lab

<input checked="" type="radio"/>	PC	Manufacturer :	JIETUO
		Model No. :	D310
<input type="radio"/>	Test Frame	Manufacturer :	GT-tronics HK Ltd
		Model No. :	-----

2.6. Configuration of Tested System

Fig. 2-1 Configuration of Tested System



Table 2-1 Equipment Used in Tested System

No.	Product	Manufacturer	Model No.	Serial No.	FCC
1	PC	JIETUO	D310	47538967 5000422	FCC DOC

2.7. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for **FCC ID: B4OBC86XRPX** filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

2.8. Modifications

No modifications were implemented to meet testing criteria.

2.9. NOTE

1. The EUT have Bluetooth 4.0 functions, The functions of the EUT listed as below:

	Test Standards	Reference Report
Radio	FCC Part 15 Subpart C (Section15.247)	CTL1408212034-WF01
		CTL1408212034-WF02

2. The frequency bands used in this EUT are listed as follows:

Frequency Band(MHz)	2400-2483.5	5150-5350	5470-5725	5725-5850
Bluetooth 4.0	✓	—	—	—

3. The EUT provides one completed transmitter and receiver.

Modulation Mode	TX Function
GFSK	1TX

2.10. Channel list

Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	20	2442
01	2404	21	2444
02	2406	22	2446
03	2408	23	2448
04	2410	24	2450
05	2412	25	2452
06	2414	26	2454
07	2416	27	2456
08	2418	28	2458
09	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

2.11. Mode of Operation

1. The EUT has been tested under normal operating condition.
2. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Channel low (2402MHz), mid (2440MHz) and high (2480MHz) with highest data rate are chosen for full testing.

3. TEST ENVIRONMENT

3.1. Address of the test laboratory

Shenzhen CTL Testing Technology Co., Ltd.
Floor 1-A, Baisha Technology Park, No.3011, Shahexi Road, Nanshan District, Shenzhen, China 518055

The sites are constructed in conformance with the requirements of ANSI C6230, ANSI C63.4 (2003) and CISPR Publication 22.

3.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

IC Registration No.: 9618B

The 3m alternate test site of Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration No.: 9618B on November 13, 2013.

FCC-Registration No.: 970318

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 970318, December 19, 2013.

3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

3.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen CTL Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CTL laboratory is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10dB	(1)
Radiated Emission	Above 1GHz	4.32dB	(1)
Conducted Disturbance	0.15~30MHz	3.20dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3.5. Test Description

FCC PART 15		
FCC Part 15.207	AC Power Conducted Emission	PASS
FCC Part 15.247(a)(2)	6dB Bandwidth	PASS
FCC Part 15.247(d)	Spurious RF Conducted Emission	PASS
FCC Part 15.247(b)	Maximum Peak Output Power	PASS
FCC Part 15.247(e)	Power Spectral Density	PASS
FCC Part 15.109/ 15.205/ 15.209	Radiated Emissions	PASS
FCC Part 15.247(d)	Band Edge Compliance of RF Emission	PASS
FCC Part 15.203/15.247 (b)	Antenna Requirement	PASS
FCC Per 47 CFR 2.1091(b)	MPE Evaluation	PASS

Remark: The measurement uncertainty is not included in the test result.




3.6. Equipments Used during the Test

Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
Bilog Antenna	Sunol Sciences Corp.	JB1	A061713	2014/07/12	2015/07/11
EMI Test Receiver	R&S	ESCI	103710	2014/07/10	2015/07/09
Spectrum Analyzer	Agilent	E4407B	MY45108355	2014/07/06	2015/07/05
Controller	EM Electronics	Controller EM 1000	N/A	2014/07/06	2015/07/05
Horn Antenna	Sunol Sciences Corp.	DRH-118	A062013	2014/07/12	2015/07/11
Horn Antenna	SCHWARZBECK	BBHA9170	1562	2014/07/12	2015/07/11
Active Loop Antenna	SCHWARZBECK	FMZB1519	1519-037	2014/07/12	2015/07/11
LISN	R&S	ENV216	101316	2014/07/10	2015/07/09
LISN	SCHWARZBECK	NSLK8127	8127687	2014/07/10	2015/07/09
Microwave Preamplifier	HP	8349B	3155A00882	2014/07/10	2015/07/09
Amplifier	HP	8447D	3113A07663	2014/07/10	2015/07/09
Transient Limiter	Com-Power	LIT-153	532226	2014/07/10	2015/07/09
Radio Communication Tester	R&S	CMU200	3655A03522	2014/07/06	2015/07/05
Temperature/Humidity Meter	zhicheng	ZC1-2	22522	2014/07/10	2015/07/09
SIGNAL GENERATOR	HP	8647A	3200A00852	2014/07/10	2015/07/09
Wideband Peak Power Meter	Anritsu	ML2495A	220.23.35	2014/07/06	2015/07/05
Climate Chamber	ESPEC	EL-10KA	A20120523	2014/07/06	2015/07/05
High-Pass Filter	K&L	9SH10-2700/X12750-O/O	/	2014/07/06	2015/07/05
High-Pass Filter	K&L	41H10-1375/U12750-O/O	/	2014/07/06	2015/07/05
RF Cable	HUBER+SUHNER	RG214	/	2014/07/09	2015/07/08

4. TEST CONDITIONS AND RESULTS

4.1. AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2009.
- 2 Support equipment, if needed, was placed as per ANSI C63.10-2009
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2009
- 4 The EUT received DC5V power from the adapter, the adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

AC Power Conducted Emission Limit


For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following :

Frequency (MHz)	Maximum RF Line Voltage (dB μ V)			
	CLASS A		CLASS B	
	Q.P.	Ave.	Q.P.	Ave.
0.15 - 0.50	79	66	66-56*	56-46*
0.50 - 5.00	73	60	56	46
5.00 - 30.0	73	60	60	50

* Decreasing linearly with the logarithm of the frequency

TEST RESULTS

SCAN TABLE: "Voltage (9K-30M) FIN"
 Short Description: 150K-30M Voltage


**MEASUREMENT RESULT:**

Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE
0.150000	53.40	10.2	66	12.6	QP	L1	GND
0.158000	52.10	10.2	66	13.5	QP	L1	GND
2.096000	43.30	10.4	56	12.7	QP	L1	GND
2.294000	46.20	10.4	56	9.8	QP	L1	GND
2.390000	43.90	10.4	56	12.1	QP	L1	GND
2.492000	46.00	10.4	56	10.0	QP	L1	GND

MEASUREMENT RESULT:

Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE
0.198000	49.20	10.2	54	4.5	AV	L1	GND
2.096000	41.30	10.4	46	4.7	AV	L1	GND
2.192000	41.80	10.4	46	4.2	AV	L1	GND
2.294000	44.10	10.4	46	1.9	AV	L1	GND
2.390000	41.80	10.4	46	4.2	AV	L1	GND
2.492000	43.90	10.4	46	2.1	AV	L1	GND

SCAN TABLE: "Voltage (9K-30M) FIN"
 Short Description: 150K-30M Voltage



MEASUREMENT RESULT:

Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE
0.154000	53.10	10.2	66	12.7	QP	N	GND
0.158000	52.00	10.2	66	13.6	QP	N	GND
2.096000	42.50	10.4	56	13.5	QP	N	GND
2.192000	44.30	10.4	56	11.7	QP	N	GND
2.294000	46.10	10.4	56	9.9	QP	N	GND
2.390000	45.10	10.4	56	10.9	QP	N	GND


MEASUREMENT RESULT:

Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE
0.896000	40.70	10.2	46	5.3	AV	N	GND
2.096000	40.60	10.4	46	5.4	AV	N	GND
2.192000	42.50	10.4	46	3.5	AV	N	GND
2.294000	44.00	10.4	46	2.0	AV	N	GND
2.390000	43.20	10.4	46	2.8	AV	N	GND
2.492000	44.50	10.4	46	1.5	AV	N	GND


4.2. Radiated Emission

TEST CONFIGURATION


Radiated Emission Test Set-Up
Frequency range 9KHz – 30MHz



Frequency range 30MHz – 1000MHz



Frequency range above 1GHz-25GHz



TEST PROCEDURE

- 1 The EUT was placed on a turn table which is 0.8m above ground plane.
- 2 Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0°C to 360°C to acquire the highest emissions from EUT
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. the fundamental frequency is 2400-2483.5MHz, So the radiation emissions frequency range were tested from 9KHz to 25GHz.

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

For example

Frequency (MHz)	FS (dB μ V/m)	RA (dB μ V/m)	AF (dB)	CL (dB)	AG (dB)	Transd (dB)
300.00	40	58.1	12.2	1.6	31.90	-18.1

$$Transd = AF + CL - AG$$

RADIATION LIMIT

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission from intentional radiators at a distance of 3 meters shall not exceed the following table. According to § 15.247(d), in any 100kHz bandwidth outside the frequency band in which the EUT is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the100kHz bandwidth within the band that contains the highest level of desired power.

Frequency (MHz)	Distance (Meters)	Radiated (dB μ V/m)	Radiated (μ V/m)
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST RESULTS

CH	Antenna	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
0	H	2401.9	63.0	31.2	94.2	Fundamental	/	PK
	V	354.0	18.7	16.4	35.1	46	-10.9	QP
	V	539.3	7.8	20.9	28.7	46	-17.3	QP
	H	3122.5	61.3	-16.0	45.3	54(Note)	-8.7	PK
	V	4804.0	59.4	-11.7	47.7	54(Note)	-6.3	PK
	V	7213.5	47.5	-3.5	44.0	54(Note)	-10	PK
	H	24000.0	61.1	-8.9	52.2	54(Note)	-1.8	PK
19	H	2440.1	63.8	31.2	95.0	Fundamental	/	PK
	V	365.1	10.4	16.7	27.1	46	-18.9	QP
	V	539.3	10.4	21.0	31.4	46	-14.6	QP
	H	3122.5	58.6	-16.0	42.6	54(Note)	-11.4	PK
	H	4880.0	59.6	-11.7	47.9	54(Note)	-6.1	PK
	V	7321.0	47.8	-3.0	44.8	54(Note)	-9.2	PK
	H	24000.0	61.9	-8.9	53.0	54(Note)	-1	PK
39	H	2480.0	63.5	31.2	94.7	Fundamental	/	PK
	V	439.8	10.9	18.5	29.4	46	-16.6	QP
	V	539.3	10.5	20.9	31.4	46	-14.6	QP
	H	3122.5	59.8	-16.2	43.6	54(Note)	-10.4	PK
	H	4944.0	59.1	-11.4	47.7	54(Note)	-6.3	PK
	V	7434.5	45.9	-2.6	43.3	54(Note)	-10.7	PK
	H	24000.0	61.1	-8.9	52.2	54(Note)	-1.8	PK

Note

1: The test trace is same as the ambient noise (the test frequency range: 9kHz~30MHz, 18GHz~25GHz), therefore no data appear in the report.


2: This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.

3: According to FCC Part15.247(d). Radiated emission which don't fall in the restricted bands, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

4. For 30MHz to 1GHz , RMB 120kHz VBW 300kHz QP detector; for above 1GHz , RBW 1MHz VBW 3MHz , Peak detector for PK value , RMS detector for AV value.

4.3. Maximum Peak Output Power

TEST CONFIGURATION



TEST PROCEDURE

According to C63.10 -2009 and KDB 558074 D01 v03r02, The EUT was directly connected to the power meter / spectrum analyzer and antenna output port as show in the block diagram as TEST CONFIGURATION shows.

Use the wideband power meter to test peak power and record the result.

LIMIT


The Maximum Peak Output Power Measurement limit is 30dBm.

TEST RESULTS


Channel Frequency (MHz)	Peak Power Output (dBm)	Peak Power Limit (dBm)	Pass / Fail
2402	-1.087	30	PASS
2440	-0.437	30	PASS
2480	-0.825	30	PASS

Note: The test results including the cable lose.


Low channel



Middle channel



High channel



4.4. 6dB Bandwidth

TEST CONFIGURATION



TEST PROCEDURE


1. The testing follows FCC KDB Publication No. 558074 D01 v03r02 (Measurement Guidelines of DTS).
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW. The 6 dB bandwidth must be greater than 500 kHz.
4. The marker-delta reading at this point is the 6 dB bandwidth of the emission.

LIMIT


For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

TEST RESULTS


CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (KHz)	LIMIT (KHz)	PASS/FAIL
2402	740.437	500	PASS
2440	745.121	500	PASS
2480	732.784	500	PASS



Middle Channel



High Channel



4.5. Band Edge

TEST CONFIGURATION



TEST PROCEDURE

The band edge compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10 and FCC KDB Publication No. 558074 D01 v03r02 (Measurement Guidelines of DTS) with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=1MHz and VBM= 3MHz to measure the peak field strength and set RBW to 1MHz and VBW to 3MHz RMS detector to measure the average radiated field strength.


LIMIT

1. Below -20dB of the highest emission level in operating band.
2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209(see Section 15.205(c)).

Frequency (MHz)	Limit Average (dB _{uv} /m)	Limit Peak (dB _{uv} /m)
Below 2390 or Above 2483.5	54	74

TEST RESULTS


Engineer: Happy	
Site: AC5	Time: 2014/10/09
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_DRH-118 (1-18GHz)	Polarity: Horizontal
EUT: BLUETOOTH MODULE	Power: By USB
Note: Transmit at channel 2402MHz	



Site no. : 3m Chamber Data no. : 648
 Dis. / Ant. : 3m DRH-118 Ant. pol. : HORIZONTAL
 Limit : 74DB
 Env. / Ins. : 23°C/54%
 Engineer :
 EUT :
 Power :
 M/N :
 Test Mode :

Freq. (MHz)	Ant. Factor (dB)	Cable Loss (dB)	Emission		Limits (dBuV/m)	Margin (dB)	Remark
			Reading (dBuV)	Level (dBuV/m)			
1 2390.00	28.78	4.61	51.60	49.63	74.00	24.37	Peak


Engineer: Happy	
Site: AC5	Time: 2014/10/09
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_DRH-118 (1-18GHz)	Polarity: Horizontal
EUT: BLUETOOTH MODULE	Power: By USB
Note: Transmit at channel 2402MHz	



Site no. : 3m Chamber Data no. : 649
 Dis. / Ant. : 3m DRH-118 Ant. pol. : HORIZONTAL
 Limit : 54DB
 Env. / Ins. : 23*C/54%
 Engineer :
 EUT :
 Power :
 M/N :
 Test Mode :

Freq. (MHz)	Ant. Factor (dB)	Cable Loss (dB)	Emission				
			Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
<hr/>							
1 2390.00	28.78	4.61	29.47	27.50	54.00	26.50	Average


Engineer: Happy	
Site: AC5	Time: 2014/10/09
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_DRH-118 (1-18GHz)	Polarity: Vertical
EUT: BLUETOOTH MODULE	Power: By USB
Note: Transmit at channel 2402MHz	



Site no. : 3m Chamber Data no. : 646
 Dis. / Ant. : 3m DRH-118 Ant. pol. : VERTICAL
 Limit : 74DB
 Env. / Ins. : 23°C/54%
 Engineer :
 EUT :
 Power :
 M/N :
 Test Mode :

Freq. (MHz)	Ant. Factor (dB)	Cable Loss (dB)	Emission					
			Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark	
<hr/>								
1 2390.00	28.78	4.61	51.01	49.04	74.00	24.96	Peak	


Engineer: Happy	
Site: AC5	Time: 2014/10/09
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_988(1-18GHz)	Polarity: Vertical
EUT: BLUETOOTH MODULE	Power: By USB
Note: Transmit at channel 2402MHz	



Site no. : 3m Chamber Data no. : 650
 Dis. / Ant. : 3m DRH-118 Ant. pol. : VERTICAL
 Limit : 54DB
 Env. / Ins. : 23°C/54%
 Engineer :
 EUT :
 Power :
 M/N :
 Test Mode :

Freq. (MHz)	Factor (dB)	Cable Loss (dB)	Emission		Margin (dB)	Remark
			Reading (dBuV)	Level (dBuV/m)		
<hr/>						
1 2390.00	28.78	4.61	29.94	27.97	54.00	26.03 Average

Engineer: Happy	
Site: AC5	Time: 2014/10/09
Limit: FCC_Part15.209 RE(3m)	Margin: 0
Probe: Horn_DRH-118 (1-18GHz)	Polarity: Horizontal
EUT: BLUETOOTH MODULE	Power: By USB
Note: Transmit at channel 2480MHz	



Site no. : 3m Chamber Data no. : 656
 Dis. / Ant. : 3m DRH-118 Ant. pol. : HORIZONTAL
 Limit : 74DB
 Env. / Ins. : 23°C/54%
 Engineer :
 EUT :
 Power :
 M/N :
 Test Mode :

Freq. (MHz)	Ant. Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission			
				Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 2479.80	28.93	4.70	94.50	92.75	74.00	-18.75	Peak
2 2483.50	28.93	4.70	62.80	61.05	74.00	12.95	Peak

Engineer: Happy

Site: AC5

Time: 2014/10/09

Limit: FCC_Part15.209_RE(3m)

Margin: 0


Probe: Horn_DRH-118 (1-18GHz)

Polarity: Horizontal

EUT: BLUETOOTH MODULE

Power: By USB

Note: Transmit at channel 2480MHz




Site no. : 3m Chamber
 Dis. / Ant. : 3m DRH-118
 Limit : 54DB
 Env. / Ins. : 23°C/54%
 Engineer :
 EUT :
 Power :
 M/N :
 Test Mode :

Data no. : 660
 Ant. pol. : HORIZONTAL

Freq. (MHz)	Ant. Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission				Remark
				Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)		
1 2479.93	28.93	4.70	81.97	80.22	54.00	-26.22	Average	
2 2483.50	28.93	4.70	52.11	50.36	54.00	3.64	Average	


Engineer: Happy	
Site: AC5	Time: 2014/10/09
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_DRH-118 (1-18GHz)	Polarity: Vertical
EUT: BLUETOOTH MODULE	Power: By USB
Note: Transmit at channel 2480MHz	



Site no. : 3m Chamber Data no. : 658
 Dis. / Ant. : 3m DRH-118 Ant. pol. : VERTICAL
 Limit : 74DB
 Env. / Ins. : 23*C/54%
 Engineer :
 EUT :
 Power :
 M/N :
 Test Mode :

Freq. (MHz)	Ant. Factor (dB)	Cable Loss (dB)	Emission				
			Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
<hr/>							
1 2479.73	28.93	4.70	96.36	94.61	74.00	-20.61	Peak
2 2483.50	28.93	4.70	64.91	63.16	74.00	10.84	Peak

Engineer: Happy	
Site: AC5	Time: 2014/10/09
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_DRH-118 (1-18GHz)	Polarity: Vertical
EUT: BLUETOOTH MODULE	Power: By USB
Note: Transmit at channel 2480MHz	



Site no. : 3m Chamber Data no. : 661
 Dis. / Ant. : 3m DRH-118 Ant. pol. : VERTICAL
 Limit : 54DB
 Env. / Ins. : 23*C/54%
 Engineer :
 EUT :
 Power :
 M/N :
 Test Mode :

Freq. (MHz)	Ant. Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission			
				Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
<hr/>							
1 2479.98	28.93	4.70	83.70	81.95	54.00	-27.95	Average
2 2483.50	28.93	4.70	55.37	53.62	54.00	0.38	Average

4.6. Power Spectral Density Measurement

TEST CONFIGURATION



TEST PROCEDURE

The EUT was tested according to KDB 558074 D01 v03r02 for compliance to FCC 47CFR 15.247 requirements.

Set RBW= 3 kHz, VBW \geq 10KHz, SPAN to 1.5 times greater than the EBW,.


LIMIT

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

TEST RESULTS

Modulation Mode	Channel	Channel Frequency (MHz)	PSD (dBm/3KHz)	Maximum limit (dBm/3KHz)	PASS / FAIL
GFSK	1	2402	-18.39	8	PASS
	19	2440	-16.85	8	PASS
	39	2480	-17.29	8	PASS

Low channel



Middle channel



High channel



4.7. Spurious RF Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE


The EUT was tested according to KDB 558074 D01 v03r02 for compliance to FCC 47CFR 15.247 requirements.




The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2009 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBM= 300KHz to measure the peak field strength , and measure frequeny range from 30MHz to 26.5GHz.

LIMIT



In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

TEST RESULTS







High channel



Conducted Band Edge:



4.8. Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (c), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Refer to statement below for compliance.


The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

Antenna Connected Construction

The antenna used in this product is a internal Antenna, The directional gains of antenna used for transmitting is 0dBi.






5. Test Setup Photos of the EUT






6. External and Internal Photos of the EUT







.....End of Report.....

