



December 19, 2024

TUV SUD America CB
10 Centennial Drive FL2
Peabody, MA 01960

Attention: Director of Certification

RE: Analysis of RF Exposure for Mobile and Portable Device per KDB 447498 D01 General RF Exposure Guidance v06.

FCC ID: B7JDJCRVSIII

1. Limits

Limits for General Population/Uncontrolled Exposure (Title 47 Subpart J §2.1091 and KDB 447498 D01 referring to limits under §1.1310)

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Electric Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time (minutes)
0.3 - 1.34	614	1.63	*(100)	30
1.34 - 30	824/f	2.19/f	*(180/f ²)	30
30 - 300	27.5	0.073	0.2	30
300 - 1500	-	-	f/1500	30
1500 - 100,000	-	-	1.0	30

f = frequency in MHz

*Plane-wave equivalent power density

2. MPE Calculation Summary using a 20cm separation distance:

24125MHz at 20 cm Separation Distance			
Mode	Output Power (dBμV/m)	Power Density at 20 cm (mW/cm ²)	FCC Limit (mW/cm ²)
24125 MHz	125.2	0.19762933	1



3. Mobile MPE Calculation using a 20cm separation distance:

Using Power Density formula:

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to isotropic

R = distance to the center of radiation of the antenna

24125 MHz at 20 cm Separation Distance:

Measured Field Strength --Radiated:	125.2	dBuV/m
Maximum peak output power --Radiated:	993.3933644	(mW)
Antenna gain(typical):	0.00	(dBi)
Maximum antenna gain:	1.00	(numeric)
Prediction distance:	20.00	(cm)
Prediction frequency:	24125	(MHz)
MPE limit for uncontrolled exposure at prediction frequency:	1	(mW/cm ²)
Power density at prediction frequency:	0.19762933	(mW/cm ²)
Margin of Compliance:	-7.04	(dB)

Sincerely,

A handwritten signature in blue ink, appearing to read 'Miguel Angel Rabago Garcia', written over a horizontal line.

Name: Miguel Angel Rabago Garcia

Authorized Signatory

Title: Wireless Test Engineer